

SNM-VFI: Symmetric Nonlinear Motion-Guided Generative Video Frame Interpolation

Jisoo Jeong¹, Hong Cai¹, Jamie Menjay Lin², Hanno Ackermann¹,
Hyeonjun Sim^{3†}, Yinhao Zhu¹, Yunxiao Shi¹, and Fatih Porikli¹

Qualcomm AI Research^{1†}, Qualcomm Technologies, Inc.², and Google³
{jisojeon, hongcai, jmlin, hackerma}@qti.qualcomm.com
flhy5836@gmail.com, {yinhaoz, yunxshi, fporikli}@qti.qualcomm.com

Abstract. We propose **Symmetric Nonlinear Motion-guided Generative Video Frame Interpolation (SNM-VFI)**, a training-free framework for motion-controllable generative video frame interpolation with pre-trained optical flow and video diffusion models. Unlike conventional diffusion-based VFI methods that synthesize intermediate frames from random noise, SNM-VFI guides the generative process with correspondence-aware frames produced by a symmetric nonlinear motion model. Specifically, we first utilize a pre-trained optical flow model to construct multi-frame nonlinear flow-based intermediate frames and confidence maps. These flow-guided frames are then encoded as latent priors to initialize and iteratively guide a pre-trained Video Diffusion model, enabling the diffusion model to preserve dense motion correspondence while improving perceptual realism. To further enhance output quality, we employ confidence maps to fuse structurally reliable flow-based predictions with diffusion-generated details in uncertain regions such as occlusions and object boundaries. Extensive evaluations on challenging benchmarks, including DAVIS, Sintel, and KITTI, demonstrate that SNM-VFI achieves strong perceptual quality, competitive reconstruction accuracy, and robust temporal coherence across diverse motion scenarios.

Keywords: Video Frame Interpolation · Optical Flow · Video Diffusion

1 Introduction

Flow-based video frame interpolation (VFI) methods [7, 13, 15, 16, 33] explicitly model pixel-level correspondences by estimating optical flow [9, 11, 26] between frames. While effective in capturing motion trajectories, these approaches are fundamentally limited by their reliance on a linear motion assumption, *i.e.* constant velocity between frames. This simplification restricts their ability to handle complex, accelerated, or nonlinear motion patterns that frequently occur in real-world scenes [17, 30]. Moreover, flow-based methods often struggle with occlusions, imprecise object boundaries, and non-rigid deformations (as shown in the 2nd and 3rd columns of Fig 1).

[†] Qualcomm AI Research is an initiative of Qualcomm Technologies, Inc.

[‡] This work was done while at Qualcomm Technologies, Inc.




Fig. 1: Video Frame Interpolation results ($\hat{I}_{1/4}, \hat{I}_{2/4}, \hat{I}_{3/4}$) on the KITTI dataset. VFIFormer [18] shows interpolation results produced using a linear flow-based method, while LDMVFI [3] and GenIn [27] present results from diffusion-based VFI approaches. Quadratic [30] represents a multi-frame VFI method, and the final column displays the results generated by our approach.

In contrast, recent advances in generative modeling have introduced diffusion models into the domain of Video Frame Interpolation, demonstrating impressive capabilities in producing visually compelling and perceptually realistic video content [3, 5, 12, 27, 32]. However, these models typically operate on a per-frame or short-sequence basis, making them prone to temporal inconsistencies and incapable of capturing dense motion correspondences essential for smooth and coherent video synthesis (as shown in the 4th and 5th columns of Fig 1). These limitations highlight the necessity for a video frame interpolation framework that effectively integrates the perceptual richness of diffusion models with the precise motion guidance and correspondence modeling offered by flow-based approaches.

In this paper, we propose **Symmetric Nonlinear Motion Guided Generative Video Frame Interpolation (SNM-VFI)**, a novel framework that unifies the complementary strengths of both paradigms to achieve superior interpolation quality with robust temporal coherence. Importantly, SNM-VFI operates efficiently by leveraging pre-trained optical flow models [9, 26, 29] and off-the-shelf video diffusion models [1, 5, 27], eliminating the need for task-specific training of the generative component.

To make a pre-trained video diffusion model usable for low-level temporal visual processing, we first construct reliable motion-conditioned generative priors via symmetric nonlinear flow interpolation. As illustrated in Fig. 2 (left), linear motion models often fail to capture the complexity of real-world dynamics. Previous attempts [17, 30] incorporated additional frames (e.g., I_{-1} or I_2) to improve motion estimation, but frequently produce misaligned flow vectors ($V_{0 \rightarrow t}$ and $V_{1 \rightarrow t}$), resulting in blur artifacts (Fig. 2 middle and Fig. 1 the rear-right of the car in the yellow box of Quadratic). Moreover, these methods do not account for occlusions, further degrading interpolation quality. Our symmetric approach resolves this by jointly utilizing both past ($-V_{0 \rightarrow -1}$) and next ($-V_{1 \rightarrow 2}$) optical flows to compute two optical flows ($V_{0 \rightarrow t}$ and $V_{1 \rightarrow t}$). This design ensures robust alignment of warped flows at any intermediate point (Fig. 2 right) and effectively handles occlusions, leading to significantly improved interpolation fidelity.

In addition to the more powerful motion modeling, our framework tackles the issue of temporal inconsistency that commonly affects diffusion-based video gen-




Fig. 2: Linear motion (left), Quadratic Motion (middle), and Symmetric Nonlinear Motion (right). Linear motion assumes constant velocity, causing the optical flows ($V_{0 \rightarrow t}$ and $V_{1 \rightarrow t}$) to meet at a single point, but failing to capture complex real-world dynamics. Quadratic motion incorporates velocity and acceleration at I_0 and I_1 by leveraging additional optical flows ($V_{0 \rightarrow -1}$, $V_{1 \rightarrow 2}$), yet forward and backward flows do not always align at an intermediate point in this framework. In contrast, our symmetric nonlinear motion approach also uses ($V_{0 \rightarrow -1}$, $V_{1 \rightarrow 2}$), but applies them symmetrically at both I_0 and I_1 while explicitly accounting for occlusion. This enables more accurate nonlinear modeling and ensures alignment of flows at any intermediate point.

eration. Conventional diffusion-based VFI methods typically begin from random noise, which often leads to outputs lacking long-range temporal coherence. To mitigate this, we introduce flow-guided intermediate frames as both the initialization and dynamic guidance throughout the diffusion process. This integration of correspondence-aware motion priors ensures that the generated frames maintain temporal alignment while taking advantage of the high perceptual quality offered by generative models. Finally, we combine the best of both worlds and devise a fusion strategy to combine the outputs from our symmetric nonlinear motion-based VFI and our flow-guided diffusion-based VFI. More specifically, we replace the low-confidence areas in our flow-based interpolated frame, such as occluded regions and object boundaries where correspondences may not be available, with high-quality diffusion-generated pixels. As we shall see, this fusion strategy leads to measurable gains in perceptual quality.

In summary, our main contributions are as follows:

- We propose SNM-VFI, a training-free generative VFI framework that adapts pre-trained video diffusion models for low-level temporal visual processing using explicit motion priors.
- We introduce flow-guided latent initialization and iterative diffusion guidance, which inject correspondence-aware motion cues throughout denoising.
- We design a symmetric nonlinear motion prior that produces reliable flow-based intermediate frames and confidence maps, enabling confidence-aware fusion of accurate flow predictions and realistic diffusion-generated details in uncertain regions.
- We validate SNM-VFI through extensive experiments on DAVIS, Sintel, and KITTI, demonstrating strong perceptual quality, competitive reconstruction accuracy, and robust temporal coherence across diverse motion scenarios.

2 Related Work

2.1 Flow-Based Video Frame Interpolation (VFI)

Most flow-based video frame interpolation techniques estimate optical flow between input frames (I_0 and I_1) and warp the frames to synthesize intermediate frames. These methods can be categorized by their warping strategy: backward warping (w_b), which maps pixels from the target frame back to the source frames, and forward warping (w_f), which projects source pixels into the target frame.

Backward-warping-based VFI: Backward warping methods [10, 15, 16, 18, 24, 33] typically involves predicting two optical flows ($V_{t \rightarrow 0}$ and $V_{t \rightarrow 1}$) from the target intermediate frame (I_t) to the input frames (I_0 and I_1) using a specifically trained VFI network. These flows are then used to perform a backward warping operation on I_0 and I_1 to obtain warped images ($w_b(I_0, V_{t \rightarrow 0})$, $w_b(I_1, V_{t \rightarrow 1})$). Finally, a weighting mask is employed in a network to blend these warped images ($\hat{I}_t = M \cdot w_b(I_0, V_{t \rightarrow 0}) + (1 - M) \cdot w_b(I_1, V_{t \rightarrow 1})$). A limitation of this approach is that the optical flows ($V_{t \rightarrow 0}$ and $V_{t \rightarrow 1}$) are estimated without direct access to the intermediate frame (I_t), which can result in inaccurate flow predictions, especially in cases involving large motion. This often leads to degraded interpolation quality for fast-moving or non-rigid objects.

Forward-warping-based VFI: Forward warping methods [7, 13, 22] estimate bidirectional optical flows ($V_{0 \rightarrow 1}$ and $V_{1 \rightarrow 0}$) between two input frames (I_0 and I_1), and approximate $V_{0 \rightarrow t}$ and $V_{1 \rightarrow t}$ via linear scaling: $t \cdot V_{0 \rightarrow 1}$ and $(1 - t) \cdot V_{1 \rightarrow 0}$. Pixels are then projected into the intermediate frame using forward warping ($w_f(I_0, V_{0 \rightarrow t})$, $w_f(I_1, V_{1 \rightarrow t})$). While effective for large motion due to accurate flow estimation, forward warping faces two key challenges: 1) the conflict problem, where multiple source pixels map to the same target location, and 2) the hole problem, where certain target pixels receive no source mapping. The conflict issue is typically addressed by incorporating auxiliary cues such as learning weight map, depth, or occlusion, while holes are filled using warped outputs from the alternate source frame. These strategies enhance robustness, particularly in scenarios involving complex or large-scale motion.

Multi-frame VFI: To mitigate the limitations of the linear motion assumption inherent in two-frame-based interpolation, several methods have explored the use of multiple frames to generate more accurate intermediate results. One such approach [25] structurally extends the model to accept multiple input frames (*e.g.*, T frames) and produces a larger set of output frames (*e.g.*, $S \times T$), thereby capturing richer temporal dynamics and improving interpolation quality. Alternatively, quadratic motion estimation techniques [17, 30] aim to enhance optical flow accuracy by incorporating motion information from both past and future frames. These methods estimate not only velocity but also acceleration, allowing for more precise modeling of nonlinear motion. However, discrepancies in velocity and acceleration between frames I_0 and I_1 can cause the interpolated flow vectors $V_{0 \rightarrow t}$ and $V_{1 \rightarrow t}$ to diverge, leading to misaligned target positions and blur artifacts. Furthermore, inaccurate flow estimation in occluded regions degrades interpolation quality, necessitating more robust motion modeling strategy.

OCAI (our baseline): OCAI [13] employs both forward and backward warping strategies to achieve high-quality intermediate frame generation using only a pre-trained optical flow model. Specifically, OCAI decomposes the optical flow ($V_{0 \rightarrow 1}$) and estimates the optical flow ($V_{t \rightarrow 1}$) from I_t to I_1 through forward warping.

$$\begin{aligned} V_{0 \rightarrow 1}(x) &= V_{0 \rightarrow t}(x) + V_{t \rightarrow 1}(x + V_{0 \rightarrow t}(x)), \\ V_{t \rightarrow 1}(x) &= \omega_f(V_{0 \rightarrow 1}(x) - V_{0 \rightarrow t}(x), V_{0 \rightarrow t}(x)). \end{aligned} \quad (1)$$

OCAI addresses the conflict problem by introducing an occlusion-aware weighting mask and hole problem by leveraging optical flow consistency, which fills missing area using information from the complementary flow field.

Furthermore, OCAI computes a confidence map based on forward-backward flow consistency [14], enabling more reliable fusion and refinement of interpolated frames. Finally, the intermediate frame (I_t) is synthesized through backward warping, guided by a confidence map [13].

$$I_t = \frac{C_{t,0}}{C_{t,0} + C_{t,1}} w_b(I_0, V_{t \rightarrow 0}) + \frac{C_{t,1}}{C_{t,0} + C_{t,1}} w_b(I_1, V_{t \rightarrow 1}), \quad (2)$$

2.2 Diffusion-Based Video Frame Interpolation

Recently, diffusion-based approaches have gained considerable momentum in the video frame interpolation domain. Some methods [3, 12] condition the generative process on two input frames and synthesize intermediate frames by iteratively refining random Gaussian noise. In contrast, more advanced techniques, such as TRF [5] and GenIn [27], leverage off-the-shelf foundation models like Stable Video Diffusion [12] to generate entire video sequences from a pair of input frames. These methods independently process each input frame to generate corresponding latent representations and then merge the two latent trajectories at each diffusion step.

$$\begin{aligned} z^{k-1,s} &= \Phi(z^k, c_s, k), \quad z^{k-1,e} = \Phi(z^k, c_e, k), \\ z_n^{k-1} &= \alpha_n \cdot z_n^{k-1,s} + (1 - \alpha_n) \cdot z_{N-n-1}^{k-1,e}. \end{aligned} \quad (3)$$

where z denotes the latent representation of video frames, Φ represents the denoising network, k corresponds to each denoising timestep, and c_s and c_e refer to the conditioning inputs derived from the start and end frames, respectively. GenIn further enhances temporal coherence by introducing a rotated temporal self-attention mechanism that aligns motion across latent features more effectively. Despite their ability to produce visually compelling and perceptually realistic frames, diffusion-based methods exhibit notable limitations. They often introduce unintended variations in brightness and contrast, and due to the lack of explicit pixel-level correspondence modeling, object motion may become inconsistent across frames. This can lead to temporal discontinuities and fragmented motion trajectories, undermining the overall coherence of the generated video.




Fig. 3: Overview of SNM-VFI as a motion-guided generative visual processing framework. SNM-VFI first constructs correspondence-aware intermediate frames and confidence maps using symmetric nonlinear motion priors (Sec. 3.1). These flow-guided frames are encoded as latent priors to initialize and iteratively guide a pre-trained video diffusion model, producing temporally coherent generative interpolations (Sec. 3.2). Finally, confidence-aware fusion combines reliable flow-based structures with diffusion-generated details for enhanced interpolation quality (Sec. 3.3).

3 Proposed Approach

Our proposed approach, SNM-VFI, significantly improves the quality and robustness of video frame interpolation by integrating the complementary strengths of optical flow and generative diffusion models. In Section 3.1, we employ a multi-frame flow prediction strategy that explicitly models complex, nonlinear motion. This enables the generation of high-fidelity intermediate frames through advanced flow-based interpolation. In Section 3.2, flow-guided intermediate frames serve as conditional inputs to the diffusion model, promoting temporal coherence and perceptual realism. Section 3.3 describes the use of confidence maps to fuse flow- and diffusion-based outputs, selectively integrating reliable regions from each to ensure structural precision and visual consistency.

3.1 Symmetric Nonlinear Motion Based Flow Interpolation

Following the flow decomposition principle utilized in OCAI (Eq. 1), we first decompose the optical flow $V_{0 \rightarrow 1}$ into two directional components: $V_{0 \rightarrow t}$ and $V_{t \rightarrow 1}$. To capture nonlinear motion, we approximate $V_{0 \rightarrow t}$ not only using the base flow $V_{0 \rightarrow 1}$, but also by incorporating motion cues from symmetric neighborhood flows, specifically $V_{0 \rightarrow -1}$ and $V_{1 \rightarrow 2}$. This enriched motion context enables our model to better identify and represent complex, nonlinear motion patterns:

$$V_{0 \rightarrow t}(x) = t \cdot V_{0 \rightarrow 1}(x) + \alpha \cdot t \cdot (1 - t) \cdot \frac{-V_{0 \rightarrow -1} + w_b(-V_{1 \rightarrow 2}, V_{0 \rightarrow 1})}{2}, \quad (4)$$

where α is a nonlinear hyperparameter that controls the magnitude of the non-linearity and w_b is backward warping. The parameter α is set to 0.5. To address

occluded regions, we compute a comprehensive occlusion map [20] and replace the flow within these areas using a simplified and more stable linear motion approximation, thereby enhancing reliability in regions with uncertain motion:

$$\begin{aligned} M_{0 \rightarrow t} &= M_{0 \rightarrow 1} \cdot M_{0 \rightarrow -1} \cdot w_b(M_{1 \rightarrow 2}, V_{0 \rightarrow 1}), \\ V_{0 \rightarrow t}(p) &= V_{0 \rightarrow t}^{OCAI}(p) \quad \text{if } M_{0 \rightarrow t}(p) = 1, \end{aligned} \quad (5)$$

where M denotes the matching map, defined as $M = 1 - O$, O represents the occlusion map. Given our $V_{0 \rightarrow t}$ and Eq. 1, we derive the optical flow $V_{t \rightarrow 1}^{I_0}(x)$. Here, the superscript I_0 indicates that this flow originates from the input frame I_0 . Note that we apply the same occlusion-aware weighting mask during forward warping to address the conflict problem.

Unlike OCAI, our method does not rely on optical flow consistency for hole filling, as we do not assume linear motion. Instead, we perform forward warping on the inverse flows $-V_{0 \rightarrow t}(x)$ and $-V_{1 \rightarrow t}(x)$ using the respective flows $V_{0 \rightarrow t}(x)$ and $V_{1 \rightarrow t}(x)$. This yields additional flows $V_{t \rightarrow 0}^{I_0}(x)$ and $V_{t \rightarrow 1}^{I_1}(x)$, which are then used to fill the hole regions as follows:

$$\begin{aligned} V_{t \rightarrow 1}^{I_1} &= w_f(-V_{1 \rightarrow t}, V_{1 \rightarrow t}), \\ V_{t \rightarrow 1} &= (1 - H) \cdot V_{t \rightarrow 1}^{I_0} + H \cdot V_{t \rightarrow 1}^{I_1}, \end{aligned} \quad (6)$$

where H is hole mask used in OCAI [13] and w_f is forward warping. After we obtain final optical flows ($V_{t \rightarrow 1}$ and $V_{t \rightarrow 0}$), we compute the confidence maps and generate inter-frame I_t using Eq. 2.

3.2 Flow-Based Guidance for Temporally Consistent Video Diffusion

Given the two real frames (I_0 and I_1), a set of intermediate frames ($\hat{I}_{t_1}, \hat{I}_{t_2}, \dots, \hat{I}_{t_k}$) generated based on 3.1, we extract latent representations from the flow-based intermediate frames using a VAE encoder: $z_n^K \leftarrow VAE_e(\hat{I}_n)$. We use this latent representation as the initial input for the diffusion process, replacing random Gaussian noise, and proceed with the subsequent denoising steps. At each denoising step, we incorporate the flow-guided latent representation at the feature level as follows:

$$z^{k-1} \leftarrow w^{k-1} \cdot z^K + (1 - w^{k-1}) \cdot z_{diff}^{k-1}, \quad (7)$$

where z^K denotes the latent representation extracted from the flow-based intermediate frames, while z_{diff}^{k-1} represents the output of the diffusion step. The weighting function w^k is defined as k/K , where K denotes the total number of diffusion steps and k decreases from K to 0 during sampling. Thus, the flow-guided latent z^K has a stronger influence in early denoising stages, while the diffusion output z_{diff}^{k-1} gradually dominates in later steps to refine perceptual details. Through feature-level fusion, we inject flow information into the intermediate stages of the diffusion process. After completing the denoising steps, the final latent output is decoded using a VAE decoder (VAE_d) as follows:

$$I^{\text{Diff}} \leftarrow VAE_d(z^0) \quad (8)$$

3.3 Confidence-Aware Fusion of Flow and Diffusion Outputs

We fuse the two intermediate frames, one from the flow-based output and the other from the diffusion-based output, using a confidence map computed from Section 3.1, as follows:

$$I_t = C_t \cdot I_t^{\text{Flow}} + (1 - C_t) \cdot I_t^{\text{Diff}}. \quad (9)$$

4 Experiments

4.1 Experimental Setup

Datasets: We evaluate SNM-VFI against state-of-the-art video frame interpolation (VFI) methods using three widely adopted benchmarks: DAVIS [23], Sintel [2], and KITTI [6, 21]. Experiments are conducted under two interpolation scenarios: 1) $\times 2$ Interpolation: The task is to reconstruct the middle frame I_1 using the model. Most existing algorithms rely only on the two frames (I_0, I_2) , where some methods [17, 30], including ours, utilize four frames (I_{-2}, I_0, I_2, I_4) to generate the middle frame. 2) $\times 4$ Interpolation: The task is to generate the intermediate frames I_1, I_2, I_3 between given frames I_0 and I_4 using the model. Similar to the $\times 2$ Interpolation setting, most existing algorithms utilize only the two input frames (I_0, I_4) , whereas others, including ours, use four frames (I_{-4}, I_0, I_4, I_8) to synthesize the intermediate frames. More details can be found in the supplementary material.

Models: To ensure a fair comparison with existing VFI approaches, we adopt the official implementations and publicly released model weights, primarily those pre-trained on the Vimeo90k [31] dataset. For forward-warping based methods such as RIPR [7] and OCAI [13], we use the RAFT [26] optical flow model with weights trained on the FlyingChairs [4] and FlyingThings3D [19] datasets. In SNM-VFI, we employ the same RAFT model used in baselines like RIPR and OCAI. In addition, we integrate the GenIn [27] model, using its publicly released fine-tuned weights¹. Note that all components in our pipeline are used as-is, without any additional training or fine-tuning. Additional details are provided in the supplementary material.

Evaluation Metrics: We evaluate interpolation quality using three standard metrics: Peak Signal-to-Noise Ratio (PSNR), Structural Similarity Index Measure (SSIM) [28], and Learned Perceptual Image Patch Similarity (LPIPS with VGG) [34]. To assess perceptual realism, we also report the Fréchet Inception Distance (FID) [8] on the synthesized frames.

4.2 $\times 2$ Interpolation on DAVIS, Sintel, and KITTI

Table 1 presents the results of our experiments under the $\times 2$ interpolation setting across three benchmark datasets: DAVIS, Sintel, and KITTI. On the DAVIS

¹ The GenIn model generates a total of 25 intermediate frames $(\hat{I}_0, \hat{I}_1, \dots, \hat{I}_{24})$. For evaluation, the $\hat{I}_{12}$ frame is compared with the true middle frame, the $\hat{I}_6$ frame with the $I_{1/4}$ frame, and the $\hat{I}_{18}$ frame with the $I_{3/4}$ frame.

Table 1: Video Frame Interpolation (VFI) results for the $\times 2$ interpolation setting on the DAVIS, Sintel, and KITTI datasets. We report standard image quality metrics: PSNR ($\uparrow$), SSIM ($\uparrow$), LPIPS ($\downarrow$), and FID score ($\downarrow$), where arrows indicate whether higher or lower values are better. **Red/Blue:** **Best** and **Second Best** results.

Methods	DAVIS-2				Sintel-2				KITTI-2			
	PSNR/SSIM/LPIPS/FID	PSNR/SSIM/LPIPS/FID	PSNR/SSIM/LPIPS/FID	PSNR/SSIM/LPIPS/FID	PSNR/SSIM/LPIPS/FID	PSNR/SSIM/LPIPS/FID	PSNR/SSIM/LPIPS/FID	PSNR/SSIM/LPIPS/FID	PSNR/SSIM/LPIPS/FID	PSNR/SSIM/LPIPS/FID	PSNR/SSIM/LPIPS/FID	PSNR/SSIM/LPIPS/FID
IFRNet [15] (CVPR 2022)	27.3168/0.8749/0.1347/ 46.2731	27.3168/0.8749/0.1347/ 46.2731	27.3168/0.8749/0.1347/ 46.2731	27.3168/0.8749/0.1347/ 46.2731	29.0813/0.8898/0.1336/ 110.0396	29.0813/0.8898/0.1336/ 110.0396	29.0813/0.8898/0.1336/ 110.0396	29.0813/0.8898/0.1336/ 110.0396	21.5024/0.7620/0.2168/ 44.4112	21.5024/0.7620/0.2168/ 44.4112	21.5024/0.7620/0.2168/ 44.4112	21.5024/0.7620/0.2168/ 44.4112
VFIFormer [18] (CVPR 2022)	27.5316/0.8825/0.1415/ 47.9819	27.5316/0.8825/0.1415/ 47.9819	27.5316/0.8825/0.1415/ 47.9819	27.5316/0.8825/0.1415/ 47.9819	29.6084/0.8990/0.1185/ 110.1337	29.6084/0.8990/0.1185/ 110.1337	29.6084/0.8990/0.1185/ 110.1337	29.6084/0.8990/0.1185/ 110.1337	22.4012/0.7884/0.2268/ 40.4422	22.4012/0.7884/0.2268/ 40.4422	22.4012/0.7884/0.2268/ 40.4422	22.4012/0.7884/0.2268/ 40.4422
AMT [16] (CVPR 2023)	27.5251/0.8783/0.1331/ 46.5251	27.5251/0.8783/0.1331/ 46.5251	27.5251/0.8783/0.1331/ 46.5251	27.5251/0.8783/0.1331/ 46.5251	29.3449/0.8931/0.1260/ 102.5036	29.3449/0.8931/0.1260/ 102.5036	29.3449/0.8931/0.1260/ 102.5036	29.3449/0.8931/0.1260/ 102.5036	21.8201/0.7715/0.2220/ 42.7778	21.8201/0.7715/0.2220/ 42.7778	21.8201/0.7715/0.2220/ 42.7778	21.8201/0.7715/0.2220/ 42.7778
EMA-VFI [33] (CVPR 2023)	27.6178/0.8781/0.1456/ 47.3722	27.6178/0.8781/0.1456/ 47.3722	27.6178/0.8781/0.1456/ 47.3722	27.6178/0.8781/0.1456/ 47.3722	29.7058/0.8960/0.1373/ 111.4100	29.7058/0.8960/0.1373/ 111.4100	29.7058/0.8960/0.1373/ 111.4100	29.7058/0.8960/0.1373/ 111.4100	21.8389/0.7681/0.2536/ 49.7861	21.8389/0.7681/0.2536/ 49.7861	21.8389/0.7681/0.2536/ 49.7861	21.8389/0.7681/0.2536/ 49.7861
BiM-VFI [24] (CVPR 2025)	27.1588/0.8765/0.1471/ 35.9279	27.1588/0.8765/0.1471/ 35.9279	27.1588/0.8765/0.1471/ 35.9279	27.1588/0.8765/0.1471/ 35.9279	28.9174/0.8867/0.1355/ 70.8399	28.9174/0.8867/0.1355/ 70.8399	28.9174/0.8867/0.1355/ 70.8399	28.9174/0.8867/0.1355/ 70.8399	21.8127/0.7646/0.2343/ 27.5182	21.8127/0.7646/0.2343/ 27.5182	21.8127/0.7646/0.2343/ 27.5182	21.8127/0.7646/0.2343/ 27.5182
RIPR [7] (ECCV 2022)	25.8446/0.8638/0.1364/ 47.3994	25.8446/0.8638/0.1364/ 47.3994	25.8446/0.8638/0.1364/ 47.3994	25.8446/0.8638/0.1364/ 47.3994	27.7324/0.8813/0.1275/ 88.0443	27.7324/0.8813/0.1275/ 88.0443	27.7324/0.8813/0.1275/ 88.0443	27.7324/0.8813/0.1275/ 88.0443	21.1753/0.7381/0.1945/ 35.1997	21.1753/0.7381/0.1945/ 35.1997	21.1753/0.7381/0.1945/ 35.1997	21.1753/0.7381/0.1945/ 35.1997
OCAI [13] (CVPR 2024)	26.8707/0.8749/ 0.1327 / 43.7556	26.8707/0.8749/ 0.1327 / 43.7556	26.8707/0.8749/ 0.1327 / 43.7556	26.8707/0.8749/ 0.1327 / 43.7556	28.7139/0.8912/0.1237/ 74.6818	28.7139/0.8912/0.1237/ 74.6818	28.7139/0.8912/0.1237/ 74.6818	28.7139/0.8912/0.1237/ 74.6818	22.0865/0.7604/ 0.1886 / 27.0655	22.0865/0.7604/ 0.1886 / 27.0655	22.0865/0.7604/ 0.1886 / 27.0655	22.0865/0.7604/ 0.1886 / 27.0655
LDMVFI [3] (AAAI 2024)	25.9154/0.8461/0.1453/ 51.0077	25.9154/0.8461/0.1453/ 51.0077	25.9154/0.8461/0.1453/ 51.0077	25.9154/0.8461/0.1453/ 51.0077	26.9267/0.8524/0.1529/ 104.6009	26.9267/0.8524/0.1529/ 104.6009	26.9267/0.8524/0.1529/ 104.6009	26.9267/0.8524/0.1529/ 104.6009	19.5199/0.6764/0.2475/ 47.0781	19.5199/0.6764/0.2475/ 47.0781	19.5199/0.6764/0.2475/ 47.0781	19.5199/0.6764/0.2475/ 47.0781
TRF [5] (ECCV 2024)	15.0228/0.5397/0.4740/ 113.9287	15.0228/0.5397/0.4740/ 113.9287	15.0228/0.5397/0.4740/ 113.9287	15.0228/0.5397/0.4740/ 113.9287	16.1904/0.5782/0.4557/ 195.9670	16.1904/0.5782/0.4557/ 195.9670	16.1904/0.5782/0.4557/ 195.9670	16.1904/0.5782/0.4557/ 195.9670	13.0914/0.4464/0.4684/ 58.0689	13.0914/0.4464/0.4684/ 58.0689	13.0914/0.4464/0.4684/ 58.0689	13.0914/0.4464/0.4684/ 58.0689
GenIn [27] (ICLR 2025)	19.6487/0.6936/0.2708/ 68.7283	19.6487/0.6936/0.2708/ 68.7283	19.6487/0.6936/0.2708/ 68.7283	19.6487/0.6936/0.2708/ 68.7283	19.4844/0.6565/0.3330/ 134.3639	19.4844/0.6565/0.3330/ 134.3639	19.4844/0.6565/0.3330/ 134.3639	19.4844/0.6565/0.3330/ 134.3639	17.0116/0.5842/0.3255/ 38.7543	17.0116/0.5842/0.3255/ 38.7543	17.0116/0.5842/0.3255/ 38.7543	17.0116/0.5842/0.3255/ 38.7543
SNM-VFI	27.4797/ 0.8928 / 0.1243 / 43.0419	27.4797/ 0.8928 / 0.1243 / 43.0419	27.4797/ 0.8928 / 0.1243 / 43.0419	27.4797/ 0.8928 / 0.1243 / 43.0419	29.3269/ 0.9109 / 0.1134 / 70.7634	29.3269/ 0.9109 / 0.1134 / 70.7634	29.3269/ 0.9109 / 0.1134 / 70.7634	29.3269/ 0.9109 / 0.1134 / 70.7634	22.8125 / 0.7868 / 0.1811 / 26.4216	22.8125 / 0.7868 / 0.1811 / 26.4216	22.8125 / 0.7868 / 0.1811 / 26.4216	22.8125 / 0.7868 / 0.1811 / 26.4216

and Sintel datasets, Flow-based methods, particularly those employing backward warping (IFRNet, VFIFormer, AMT, EMA-VFI, BiM-VFI), achieve high scores in PSNR and SSIM, indicating strong pixel-level fidelity. BiM-VFI is the only method that achieves strong FID scores but performs significantly worse in PSNR, SSIM, and LPIPS compared to other backward warping methods. Forward warping methods (RIPR, OCAI) generally perform better in LPIPS and FID than backward warping approaches, excluding BiM-VFI. SNM-VFI achieves the best SSIM and LPIPS scores and remains highly competitive in PSNR and FID, with only a marginal gap compared to the top-performing model. Notably, our approach demonstrates a substantial improvement in LPIPS, outperforming all other methods by a significant margin.

On the KITTI dataset, backward warping methods continue to excel in PSNR and SSIM, while forward warping techniques perform well in LPIPS and FID. SNM-VFI achieves the best results in all metrics except SSIM, where it ranks second with a score very close to the top-performing approach. These results collectively demonstrate the robustness and effectiveness of our framework across diverse motion scenarios and evaluation criteria.

4.3 $\times 4$ Interpolation on DAVIS, Sintel, and KITTI

Middle-Frame ($I_{1/2}$) Evaluation: Table 2 reports results under the $\times 4$ interpolation setting using the same datasets. When evaluating the middle frame, we observe trends similar to those in the $\times 2$ setting. Backward warping-based methods generally achieve high PSNR and SSIM scores (excluding BiM-VFI), while forward warping-based methods perform well in LPIPS and FID. Interestingly, GenIn records the best FID score on the KITTI dataset. This highlights the trade-offs between perceptual realism and pixel-level accuracy in diffusion-based models. Our proposed method consistently shows either the best or near-best performance across all metrics. It demonstrates strong generalization across datasets and interpolation settings, achieving competitive PSNR and SSIM scores while outperforming other methods in perceptual quality metrics such as LPIPS and FID.

Table 2: Video Frame Interpolation (VFI) results on the DAVIS, Sintel, and KITTI datasets. The top section presents evaluations of the middle frame under the $\times 4$ interpolation setting, while the bottom section shows results for all intermediate frames in the $\times 4$ setting. We report standard image quality metrics: PSNR ($\uparrow$), SSIM ($\uparrow$), LPIPS ($\downarrow$), and FID score ($\downarrow$), where arrows indicate whether higher or lower values are better. **Red/Blue: Best and Second Best** results.

Methods	DAVIS-4				Sintel-4				KITTI-4			
	PSNR	SSIM	LPIPS	FID	PSNR	SSIM	LPIPS	FID	PSNR	SSIM	LPIPS	FID
Middle Frame ($I_{0.5}$)												
IFRNet [15] (CVPR 2022)	22.9465/0.7795/0.2318	81.4500	25.3899/0.8298/0.2045	164.6008	17.9034/0.6528/0.3088	66.1144						
VFIFormer [18] (CVPR 2022)	23.4146/0.7932 /0.2238	80.9076	25.8165/0.8427 /0.1979	153.9648	18.5943/0.6820 /0.3195	64.7331						
AMT [16] (CVPR 2023)	23.2578/0.7860/0.2198	78.8323	25.5592/0.8292/0.2015	161.1479	18.0569/0.6628/0.3143	64.1559						
EMA-VFI [33] (CVPR 2023)	23.2670/0.7843/0.2515	84.2363	25.7122 /0.8345/0.2121	159.2066	18.2554/0.6623/0.3423	70.8467						
BIM-VFI [24] (CVPR 2025)	23.1200/0.7867/0.2232	58.6681	25.3769/0.8261/0.2048	111.7590	18.1651/0.6588/0.3185	45.8235						
RIPR [7] (ECCV 2022)	22.2779/0.7759/0.2040	72.3845	24.2306/0.8106/0.1930	111.9524	17.7725/0.6315/ 0.2761	51.0808						
OCAI [13] (CVPR 2024)	23.0076/0.7855/ 0.2017	69.9548	25.3340/0.8292/ 0.1872	113.2435	18.3811/0.6489/0.2740	46.0131						
LDMVFI [3] (AAAI 2024)	21.9603/0.7446/0.2348	84.0895	23.6099/0.7892/0.2231	148.7152	16.8230/0.5818/0.3205	61.2554						
TRF [5] (ECCV 2024)	14.9700/0.5386/0.4801	116.1452	15.8220/0.5725/0.4771	215.3137	12.8847/0.4382/0.4675	61.3676						
GenIn [27] (ICLR 2025)	18.2682/0.6511/0.3159	79.9909	17.7754/0.6180/0.3729	149.5369	16.5727/0.5671/0.3341	41.9435						
SNM-VFI	23.2814/0.7977/0.1961	69.3161	25.6858/ 0.8405/0.1811	117.9414	19.1511/0.6867/0.2632	41.9844						
All Frames ($I_{1/4}, I_{2/4}, I_{3/4}$)												
IFRNet [15] (CVPR 2022)	23.8182/0.8019/0.2138	57.9793	25.9228/0.8456/0.1941	133.2429	18.4975/0.6737/0.2952	44.8743						
VFIFormer [18] (CVPR 2022)	24.2433/0.8139 /0.2058	59.8759	26.2521/0.8546 /0.1871	124.3194	19.1139/0.6997 /0.3073	45.1584						
AMT [16] (CVPR 2023)	24.1223/0.8079/0.2006	53.2007	26.0644/0.8451/0.1911	123.4832	18.6756/0.6823/0.2988	42.1071						
EMA-VFI [33] (CVPR 2023)	24.1316 /0.8069/0.2346	61.4262	26.2659/0.8497/0.2047	132.0049	18.6655/0.6798/0.3207	43.0282						
BIM-VFI [24] (CVPR 2025)	23.9099/0.8069/0.2051	40.1814	25.8389/0.8372/0.1907	86.5464	18.7143/0.6757/0.3037	28.7029						
RIPR [7] (ECCV 2022)	22.9510/0.7959/0.1907	51.6677	24.7052/0.8217/0.1816	93.0850	18.2286/0.6475/0.2638	33.1112						
OCAI [13] (CVPR 2024)	23.7432/0.8063/ 0.1864	51.2046	25.8927/0.8402/ 0.1747	93.8831	18.8717/0.6650/ 0.2620	29.3621						
LDMVFI [3] (AAAI 2024)	22.7786/0.7702/0.2126	54.2721	24.2163/0.8057/0.2051	108.8361	17.3220/0.6017/0.2981	31.6903						
TRF [5] (ECCV 2024)	15.3228/0.5500/0.4694	85.5805	16.0730/0.5845/0.4614	173.3449	13.3383/0.4556/0.4536	37.9767						
GenIn [27] (ICLR 2025)	18.7968/0.6696/0.2967	54.9852	18.5285/0.6414/0.3443	121.9460	17.1569/0.5855/0.3186	25.6861						
SNM-VFI	24.0859/ 0.8188/0.1814	48.5302	26.2414/0.8510/0.1688	92.4279	19.5978/0.7006/0.2519	27.6261						

All-Frame ($I_{1/4}, I_{2/4}, I_{3/4}$) Evaluations: In the $\times 4$ interpolation setting, we evaluate all generated intermediate frames ($I_{1/4}, I_{2/4}, I_{3/4}$) to assess the temporal generalization capabilities of each method. Traditional backward warping-based approaches are typically trained for fixed temporal positions (e.g., the midpoint) and struggle with arbitrary time steps. In our experiment, we adopted a hierarchical interpolation strategy: first, we generated the middle frame ($I_{2/4}$) using the input frames (I_0, I_1); then we synthesized ($I_{1/4}$) using ($I_0, I_{2/4}$), and ($I_{3/4}$) using ($I_{2/4}, I_1$). Across all experiments, we observed that the performance of all frames was consistently better than that of the middle frame ($I_{2/4}$). We hypothesize that this improvement stems from the relatively lower degree of non-linearity in the motion between adjacent frames ($I_0 \rightarrow I_{1/4}, I_1 \rightarrow I_{3/4}$) compared to the central interpolation ($I_0 \rightarrow I_{2/4}, I_1 \rightarrow I_{2/4}$). The more linear nature of these shorter temporal intervals likely contributes to the enhanced interpolation quality observed in the all-frame experiment.

4.4 Qualitative Results

Fig. 4 presents the $\times 2$ interpolation results from state-of-the-art VFI methods and our proposed approach. Backward warping-based methods such as VFIFormer [18] and EMA-VFI [33] struggle with large motion, producing blurred results despite high PSNR and SSIM scores in Table 1, especially in regions with complex motion. Forward warping-based methods like OCAI demonstrate better robustness to large motion but tend to introduce noise around object boundaries. Diffusion-based approaches can generate perceptually realistic frames, but varia-




Fig. 4: Video frame interpolation results ($\times 2$ interpolation) on DAVIS, Sintel, and KITTI. The fourth to sixth rows show results from flow-based methods: VFIFormer and EMA-VFI (backward warping) and OCAI (forward warping). The seventh and eighth rows present results from diffusion-based methods: LDMVFI and GenIn. The final row displays the output of our proposed SNM-VFI method.




Fig. 5: Video frame interpolation results ($\times 4$ interpolation) on KITTI. The second and third columns show results from flow-based methods: VFIFormer (backward warping) and OCAI (forward warping). The fourth column presents result from diffusion-based method: GenIn. The final column displays the output of our SNM-VFI method.

tions in brightness and contrast frequently lead to outputs that appear plausible yet deviate from the ground truth frame, resulting in reduced reconstruction accuracy. Moreover, diffusion-based methods often lack robustness to large motion. For example, in GenIn [27], the second Sintel example shows almost no change from I_0 while the KITTI example hallucinates new contents (in blue and green boxes), resulting in noticeable blur and temporal inconsistency.

In contrast, SNM-VFI effectively combines the strengths of optical flow and diffusion. It demonstrates strong robustness to large motion, generating coherent object trajectories while preserving smooth and accurate object boundaries. These results highlight the superior temporal consistency and perceptual quality achieved by our approach across diverse motion scenarios. Further qualitative results are available in the supplementary material.

Fig. 5 shows the $\times 4$ interpolation outputs produced by state of the art VFI methods and our proposed model. Similar to the $\times 2$ interpolation setting, backward-warping methods such as VFIFormer struggle with large-motion objects, producing noticeably blurred frames. Forward-warping methods like OCAI handle large motion more effectively but still introduce noise along object boundaries. Diffusion-based method (GenIn) generates visually realistic frames, yet it fails to maintain correspondence between objects across frames. Objects may remain static until $I_{2/4}$ and then reappear at a different location, leading to temporal inconsistency.

In contrast, our method accurately captures object motion while producing clean and stable frames. Although our qualitative results are significantly better, there are a few cases where VFIFormer reports a higher PSNR. This highlights that PSNR does not always correlate with perceived visual quality.

5 Discussion

Nonlinear Motion: The top section of Table 3 compares our symmetric nonlinear motion approach with two alternatives: quadratic [30] and enhanced quadratic

Table 3: Ablation study on SNM-VFI. We use common image evaluation metrics, including PSNR ($\uparrow$), SSIM ($\uparrow$), LPIPS ($\downarrow$), and FID ($\downarrow$). **Red: Best result.**

Methods	DAVIS (4 $\times$)				Sintel (4 $\times$)				KITTI (4 $\times$)			
	PSNR	SSIM	LPIPS	FID	PSNR	SSIM	LPIPS	FID	PSNR	SSIM	LPIPS	FID
Symmetric Nonlinear motion based flow interpolation												
Baseline (Linear) [13]	23.7432	0.8063	0.1864	51.2046	25.8927	0.8402	0.1747	93.8831	18.8717	0.6650	0.2620	29.3621
Quadratic [30]	23.8200	0.8134	0.1956	56.6269	26.1876	0.8509	0.1752	97.2842	19.0454	0.6789	0.2606	30.0474
Enhanced Quadratic [17]	23.6344	0.8082	0.2030	57.9580	26.1238	0.8469	0.1792	97.7645	18.9036	0.6732	0.2657	31.0025
Ours w/o Eq 5	24.0158	0.8093	0.1865	55.6194	26.1069	0.8463	0.1702	95.5088	19.0517	0.6757	0.2577	29.4991
Ours (Symmetric Nonlinear)	24.0369	0.8157	0.1831	52.2948	26.1153	0.8477	0.1733	96.2919	19.1260	0.6798	0.2575	29.8282
α hyperparameter in Eq. 4												
Nonlinear motion ($\alpha=1/4$)	23.9485	0.8130	0.1834	53.7636	26.0455	0.8446	0.1727	98.2369	19.0456	0.6742	0.2581	29.2620
Nonlinear motion ($\alpha=2/4$)	24.0369	0.8157	0.1831	52.2948	26.1153	0.8477	0.1733	96.2919	19.1260	0.6798	0.2575	29.8282
Nonlinear motion ($\alpha=3/4$)	23.9424	0.8118	0.1870	55.4992	26.0261	0.8450	0.1763	100.0384	18.9847	0.6736	0.2614	30.4168
Nonlinear motion ($\alpha=1.0$)	23.7348	0.8054	0.1920	56.8010	25.7951	0.8394	0.1807	104.8856	18.8022	0.6643	0.2668	30.9530
Diffusion-based VFI ablation studies												
Baseline [27]	18.7968	0.6696	0.2967	54.9852	18.5285	0.6414	0.3443	121.9460	17.1569	0.5855	0.3186	25.6861
Baseline + flow init	19.2524	0.6908	0.3152	62.7582	20.3186	0.7061	0.3112	129.3442	17.1438	0.6057	0.3297	28.1318
Baseline + weight latent	21.8624	0.7696	0.2344	51.3644	23.2930	0.7926	0.2215	110.9622	19.2261	0.6750	0.2803	25.8986
Baseline + conf weight latent	21.8168	0.7693	0.2360	54.1466	23.1672	0.7908	0.2257	115.5835	19.2286	0.6736	0.2815	25.2510
Fusion of Symmetric Nonlinear VFI and Diffusion VFI												
Confidence Masking ($\delta=0.5$)	24.0245	0.8178	0.1837	49.5342	26.1647	0.8496	0.1711	93.5126	19.5233	0.6987	0.2541	28.1704
Confidence Masking ($\delta=1.0$)	23.9757	0.8166	0.1902	49.7149	25.9308	0.8468	0.1818	98.8999	19.3254	0.6913	0.2606	28.6371
Confidence Weighting (Eq. 9)	24.0859	0.8188	0.1814	48.5302	26.2414	0.8510	0.1688	92.4279	19.5978	0.7006	0.2519	27.6261

motion [17]. In this evaluation, we replace our formulation of $V_{0 \rightarrow t}$ with each variant. The quadratic motion variant utilizes current and past flows $V_{0 \rightarrow 1}$ and $V_{0 \rightarrow -1}$, while the enhanced quadratic motion additionally incorporates $V_{0 \rightarrow 2}$.

Quadratic motion demonstrates improved performance over linear motion, yet generally underperforms our symmetric nonlinear method. An exception was observed on the Sintel dataset, where quadratic motion slightly outperforms in PSNR and SSIM. In contrast, enhanced quadratic motion consistently yields lower performance than both the baseline and our method. This decline can be attributed to the use of $V_{0 \rightarrow 2}$, which becomes less reliable in scenarios involving large temporal gaps, such as the $\times 4$ interpolation setting, where predicting long-range motion is inherently more challenging.

Moreover, both quadratic and enhanced quadratic methods fail to account for occlusions, which can introduce significant errors in flow estimation and degrade interpolation quality. However, our method explicitly predicts occlusions and restricts nonlinear motion estimation to regions consistently visible across all four input frames. This occlusion-aware design helps mitigate flow errors (Ours w/o Eq. 5 in Table 3) and contributes to the superior performance of our approach across diverse motion scenarios.

On the other hand, the linear model achieves the highest FID score. Although FID is categorized as a perceptual quality metric, it fundamentally measures dataset-level realism rather than per-frame accuracy. We hypothesize that the linear model, despite lower reconstruction accuracy, may generate smoother and more simplified intermediate frames, which can result in a better FID score. However, our method explicitly addresses artifacts that arise from non-linear motion (occluded regions) by applying a diffusion-based refinement to low-confidence areas. As a result, our final model achieves improved FID performance while maintaining strong reconstruction metrics.

Hyperparameter α : As shown in the second section of Table 3, we evaluate models using α values of $\frac{1}{4}$, $\frac{2}{4}$, $\frac{3}{4}$, 1.0 and observe that the setting of $\alpha=\frac{2}{4}$

generally yield the best performance, while the other values yield slightly worse but comparable performance. Based on this observation, we adopt $\alpha=0.5$ as our default and apply this setting across all experiments.

Flow Guidance: The third section of Table 3 presents an ablation study on how flow-based cues are integrated into the diffusion model. As a first approach, we encode the flow-guided intermediate frames using a VAE encoder and use the resulting latent to replace the initial noise. This strategy leads to slight improvements in PSNR and SSIM compared to the baseline. However, since early diffusion steps introduce substantial changes, the influence of the flow-based priors may diminish as the denoising progresses.

To address this, we explore a second strategy in which the flow-guided latent features are fused with the diffusion latents via a weighted sum after each diffusion step. In this setup, the diffusion process starts from the flow-guided latent, and stronger flow-guidance is applied in the early denoising stages, while the influence of the diffusion updates is gradually increased in later steps. This dynamic fusion preserves motion cues throughout the denoising process, resulting in substantial improvements across PSNR, SSIM, and LPIPS metrics compared to the baseline.

Additionally, we experiment with confidence-based weighting, where the flow-guided latents are modulated using confidence maps derived from the flow estimation module. While this approach still outperforms the baseline, it is less effective than the full latent fusion strategy. These results suggest that directly blending the entire latent space with adaptive weighting yields more robust guidance than relying solely on confidence-based modulation.

Fusion: The final section of Table 3 presents an ablation study on combining our symmetric nonlinear motion module with the flow-guided diffusion model. We estimate confidence using forward-backward consistency, enabling selective use of flow-based outputs in well-aligned regions, while occlusions and boundaries are handled by the diffusion model. The first fusion strategy applies confidence-based masking: flow-based outputs are used where confidence exceeds or equals a threshold (δ), and diffusion outputs elsewhere. Experiments with thresholds of 0.5 and 1.0 show that 0.5 yields better results. We also evaluate confidence-based weighting (Eq. 9), which outperforms masking by smoothly blending both sources. This selective fusion effectively integrates the structural precision of flow-based interpolation with the perceptual quality of diffusion, resulting in consistently high-quality outputs across diverse motion scenarios.

6 Conclusion

We proposed a generative video frame interpolation framework that unifies flow-based precision with diffusion-based realism. By modeling nonlinear motion and guiding a diffusion model with flow-derived frames and confidence maps, our method achieves temporally coherent and visually consistent results. Experiments on DAVIS, Sintel, and KITTI confirm its superior performance across both accuracy and perceptual quality.

References

1. Blattmann, A., Dockhorn, T., Kulal, S., Mendelevitch, D., Kilian, M., Lorenz, D., Levi, Y., English, Z., Voleti, V., Letts, A., et al.: Stable video diffusion: Scaling latent video diffusion models to large datasets. arXiv preprint arXiv:2311.15127 (2023)
2. Butler, D.J., Wulff, J., Stanley, G.B., Black, M.J.: A naturalistic open source movie for optical flow evaluation. In: Proceedings of the European Conference on Computer Vision. pp. 611–625. Springer (2012)
3. Danier, D., Zhang, F., Bull, D.: Ldmvfi: Video frame interpolation with latent diffusion models. In: Proceedings of the AAAI Conference on Artificial Intelligence. vol. 38, pp. 1472–1480 (2024)
4. Dosovitskiy, A., Fischer, P., Ilg, E., Hausser, P., Hazirbas, C., Golkov, V., Van Der Smagt, P., Cremers, D., Brox, T.: FlowNet: Learning optical flow with convolutional networks. In: Proceedings of the IEEE/CVF International Conference on Computer Vision. pp. 2758–2766 (2015)
5. Feng, H., Ding, Z., Xia, Z., Niklaus, S., Abrevaya, V., Black, M.J., Zhang, X.: Explorative inbetweening of time and space. In: European Conference on Computer Vision. pp. 378–395. Springer (2024)
6. Geiger, A., Lenz, P., Stiller, C., Urtasun, R.: Vision meets robotics: The kitti dataset. The International Journal of Robotics Research **32**(11), 1231–1237 (2013)
7. Han, Y., Luo, K., Luo, A., Liu, J., Fan, H., Luo, G., Liu, S.: Realflow: Em-based realistic optical flow dataset generation from videos. arXiv preprint arXiv:2207.11075 (2022)
8. Heusel, M., Ramsauer, H., Unterthiner, T., Nessler, B., Hochreiter, S.: Gans trained by a two time-scale update rule converge to a local nash equilibrium. Advances in neural information processing systems **30** (2017)
9. Huang, Z., Shi, X., Zhang, C., Wang, Q., Cheung, K.C., Qin, H., Dai, J., Li, H.: Flowformer: A transformer architecture for optical flow. In: Proceedings of the European Conference on Computer Vision (2022)
10. Huang, Z., Zhang, T., Heng, W., Shi, B., Zhou, S.: Real-time intermediate flow estimation for video frame interpolation. In: European Conference on Computer Vision. pp. 624–642. Springer (2022)
11. Hui, T.W., Tang, X., Loy, C.C.: A lightweight optical flow cnn-revisiting data fidelity and regularization. arXiv preprint arXiv:1903.07414 (2019)
12. Jain, S., Watson, D., Tabellion, E., Poole, B., Kontkanen, J., et al.: Video interpolation with diffusion models. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 7341–7351 (2024)
13. Jeong, J., Cai, H., Garrepalli, R., Lin, J.M., Hayat, M., Porikli, F.: Ocasi: Improving optical flow estimation by occlusion and consistency aware interpolation. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 19352–19362 (2024)
14. Jeong, J., Cai, H., Garrepalli, R., Porikli, F.: Distractflow: Improving optical flow estimation via realistic distractions and pseudo-labeling. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 13691–13700 (2023)
15. Kong, L., Jiang, B., Luo, D., Chu, W., Huang, X., Tai, Y., Wang, C., Yang, J.: Ifrnet: Intermediate feature refine network for efficient frame interpolation. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 1969–1978 (2022)

16. Li, Z., Zhu, Z.L., Han, L.H., Hou, Q., Guo, C.L., Cheng, M.M.: Amt: All-pairs multi-field transforms for efficient frame interpolation. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 9801–9810 (2023)
17. Liu, Y., Xie, L., Siyao, L., Sun, W., Qiao, Y., Dong, C.: Enhanced quadratic video interpolation. In: European conference on computer vision. pp. 41–56. Springer (2020)
18. Lu, L., Wu, R., Lin, H., Lu, J., Jia, J.: Video frame interpolation with transformer. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 3532–3542 (2022)
19. Mayer, N., Ilg, E., Hausser, P., Fischer, P., Cremers, D., Dosovitskiy, A., Brox, T.: A large dataset to train convolutional networks for disparity, optical flow, and scene flow estimation. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 4040–4048 (2016)
20. Meister, S., Hur, J., Roth, S.: Unflow: Unsupervised learning of optical flow with a bidirectional census loss. In: Proceedings of the AAAI conference on artificial intelligence. vol. 32 (2018)
21. Menze, M., Geiger, A.: Object scene flow for autonomous vehicles. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 3061–3070 (2015)
22. Niklaus, S., Liu, F.: Softmax splatting for video frame interpolation. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 5437–5446 (2020)
23. Pont-Tuset, J., Perazzi, F., Caelles, S., Arbeláez, P., Sorkine-Hornung, A., Van Gool, L.: The 2017 davis challenge on video object segmentation. arXiv preprint arXiv:1704.00675 (2017)
24. Seo, W., Oh, J., Kim, M.: Bim-vfi: Bidirectional motion field-guided frame interpolation for video with non-uniform motions. In: Proceedings of the Computer Vision and Pattern Recognition Conference. pp. 7244–7253 (2025)
25. Shang, W., Ren, D., Yang, Y., Zhang, H., Ma, K., Zuo, W.: Joint video multi-frame interpolation and deblurring under unknown exposure time. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 13935–13944 (2023)
26. Teed, Z., Deng, J.: Raft: Recurrent all-pairs field transforms for optical flow. In: Proceedings of the European Conference on Computer Vision. pp. 402–419. Springer (2020)
27. Wang, X., Zhou, B., Curless, B., Kemelmacher-Shlizerman, I., Holynski, A., Seitz, S.M.: Generative inbetweening: Adapting image-to-video models for keyframe interpolation. arXiv preprint arXiv:2408.15239 (2024)
28. Wang, Z., Bovik, A.C., Sheikh, H.R., Simoncelli, E.P.: Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing* **13**(4), 600–612 (2004)
29. Xu, H., Zhang, J., Cai, J., Rezatofighi, H., Tao, D.: Gmflow: Learning optical flow via global matching. In: Proceedings of the IEEE/CVF conference on computer vision and pattern recognition. pp. 8121–8130 (2022)
30. Xu, X., Siyao, L., Sun, W., Yin, Q., Yang, M.H.: Quadratic video interpolation. *Advances in Neural Information Processing Systems* **32** (2019)
31. Xue, T., Chen, B., Wu, J., Wei, D., Freeman, W.T.: Video enhancement with task-oriented flow. *International Journal of Computer Vision* **127**, 1106–1125 (2019)
32. Zhang, G., Zhu, Y., Cui, Y., Zhao, X., Ma, K., Wang, L.: Motion-aware generative frame interpolation. arXiv preprint arXiv:2501.03699 (2025)

33. Zhang, G., Zhu, Y., Wang, H., Chen, Y., Wu, G., Wang, L.: Extracting motion and appearance via inter-frame attention for efficient video frame interpolation. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. pp. 5682–5692 (2023)
34. Zhang, R., Isola, P., Efros, A.A., Shechtman, E., Wang, O.: The unreasonable effectiveness of deep features as a perceptual metric. In: Proceedings of the IEEE conference on computer vision and pattern recognition. pp. 586–595 (2018)

7 Implementation Details

7.1 Model implementation details

We compared our proposed method against several state-of-the-art approaches. For fair evaluation, all competing methods were implemented using their official releases and publicly available pretrained weights². Specifically, IFRNet-B [15] was employed with its baseline model configuration, while the AMT-L [16] was evaluated. For BiM-VFI [24], the *pyr_level* parameter was set to 7 during experimentation.

Using our symmetric nonlinear motion-based flow interpolation method, we generated a total of 23 intermediate frames at temporal positions $t=1/24, 2/24, 3/24, \dots, 23/24$. These synthesized intermediate frames were subsequently employed in the video diffusion process.

Unlike GenIn, which initializes from random Gaussian noise, our approach benefits from a strong initialization, enabling us to reduce the total number of diffusion steps from 50 (about 680 sec using A100 GPU) to 20. Furthermore, whereas GenIn performs noise reinjection five times up to 25 diffusion steps, our method applies noise reinjection once at each steps throughout the entire diffusion process.

7.2 Dataset details

We conducted our experiments using three benchmark datasets: DAVIS [23], Sintel [2], and KITTI [6, 21]. Unlike approaches such as DIVIM [12], which resize sequences to certain resolution, we preserved the original resolution of each dataset for both inter-frame generation and evaluation.

For DAVIS, we employed the 480p resolution sequences. In this datasets, the 12th frame of each video was designated as the target frame for the $\times 2$ setting, while the 11th, 12th, and 13th frames were used as the target frames for the $\times 4$ setting. Under the $\times 2$ setting, the 11th and 13th frames were used as inputs, while multi-frame configuration, four frames (the 9th, 11th, 13th and 15th) were employed. For the $\times 4$ setting, the 10th and 14th frames were used, and in the multi-frame configuration, four frames (the 6th, 10th, 14th, and 18th) were selected.

For Sintel, we adopted the clean version of the datasets, which excludes noise such as motion blur and fog. For KITTI dataset, we utilized the multi-view sequences. In both Sintel and KITTI, the 10th frame was designated as

² IFR-Net [15]: <https://github.com/ltkong218/IFRNet>
 VFIFormer [18]: <https://github.com/dvlab-research/VFIFormer>
 AMT [16]: <https://github.com/MCG-NKU/AMT>
 EMA-VFI [33]: <https://github.com/MCG-NJU/EMA-VFI>
 Bim-VFI [24]: <https://github.com/KAIST-VICLab/BiM-VFI>
 RIPR [7]: <https://github.com/megvii-research/RealFlow>
 LDMVFI [3]: <https://github.com/danier97/LDMVFI>
 TRF [5]: <https://time-reversal.github.io/>
 GenIn [27]: https://github.com/jeanne-wang/svd_keyframe_interpolation

the target frame for the $\times 2$ setting, while the 9^{th} , 10^{th} , and 11^{th} frames were used as the target frames for the $\times 4$ setting. In the $\times 2$ setting, the 9^{th} and 11^{th} frames were used, while in the multi-frame configuration, four frames (the 7^{th} , 9^{th} , 11^{th} , and 13^{th}) were employed. In the $\times 4$ setting, the 8^{th} and 12^{th} frames were used, and in the multi-frame configuration, four frames (the 4^{th} , 8^{th} , 12^{th} , and 16^{th}) were selected.

8 Additional Qualitative Video Frame Interpolation results

We provide additional qualitative results on the DAVIS, Sintel, and KITTI datasets (p5-9). Fig. 6 illustrates the results for the KITTI dataset under the $\times 2$ setting. As shown in the figure, particularly within the yellow circle on the right, most existing methods fail to handle large motion effectively, whereas OCAI and our proposed method successfully capture the motion. Moreover, in the right image, our method produces results with noticeably less noise. In the middle image, OCAI introduces significant noise, while our approach generates a much cleaner reconstruction.

Fig. 7 presents the results for the Sintel dataset under the $\times 2$ setting. Similar to KITTI, the right image demonstrates that other methods fail to accurately reproduce the ground-truth object. In contrast, our method generates a clean and faithful image.

Fig. 8 shows the results for the DAVIS dataset under the $\times 2$ setting. Compared to other approaches, our method produces images with reduced blur and closer resemblance to the original frames. Interestingly, in the middle frame where occlusion makes image generation particularly challenging, GenIn produces a remarkably clean facial image. Furthermore, while GenIn performs well in generating the left and right frames, it introduces substantial variations in brightness and contrast. These artifacts, although visually appealing in some cases, can negatively affect quantitative metrics such as PSNR and SSIM.

In Fig. 9 and 10, we present additional qualitative results under the $\times 4$ setting. Similar to the $\times 2$ setting, most existing algorithms struggle to accurately reconstruct regions with large motion, often producing blurred results. In contrast, our method generates relatively precise and visually consistent images under such challenging conditions. Furthermore, we present results from quadratic motion-based VFI, where the trajectories $V_{0 \rightarrow t}$ and $V_{1 \rightarrow t}$ fail to converge at a same point. As a consequence, when the two images are combined, noticeable blur artifacts are introduced, which are particularly evident in the DAVIS dataset results.




Fig. 6: Video frame interpolation results on KITTI ($\times 2$). The second to fifth rows show results from flow-based methods: VFIFormer and EVA-VFI (backward warping) and OCAI (forward warping). The sixth and seventh rows present results from diffusion-based methods: LDMVFI and GenIn. The final row displays the output of our proposed SNM-VFI method.



Fig. 7: Video frame interpolation results on Sintel ($\times 2$). The second to fifth rows show results from flow-based methods: VFIFormer and EVA-VFI (backward warping) and OCAI (forward warping). The sixth and seventh rows present results from diffusion-based methods: LDMVFI and GenIn. The final row displays the output of our proposed SNM-VFI method.




Fig. 8: Video frame interpolation results on DAVIS ($\times 2$). The second to fifth rows show results from flow-based methods: VFIFormer and EVA-VFI (backward warping) and OCAI (forward warping). The sixth and seventh rows present results from diffusion-based methods: LDMVFI and GenIn. The final row displays the output of our proposed SNM-VFI method.




Fig. 9: Video frame interpolation results on KITTI ($\times 4$). The second to fourth rows show results from flow-based methods: EVA-VFI and Bim-VFI (backward warping) and OCAI (forward warping). The fifth and sixth rows present results from diffusion-based methods: LDMVFI and GenIn. The seventh row shows the quadratic motion VFI results. The final row displays the output of our proposed SNM-VFI method.




Fig. 10: Video frame interpolation results on DAVIS ($\times 4$). The second to fourth rows show results from flow-based methods: EVA-VFI and Bim-VFI (backward warping) and OCAI (forward warping). The fifth and sixth rows present results from diffusion-based methods: LDMVFI and GenIn. The seventh row show the quadratic motion VFI results. The final row displays the output of our proposed SNM-VFI method.