

StateFlow: Building, Evolving, and Accessing 3D World States for Previsualization

Yuyang Yin^{1,*} Zixiang Li^{1,*} Longxuan Deng^{1,*} Hongkai Li¹ Shifang Zhao¹
Junnan Liu¹ Weirong Huang¹ Mengyu Wang¹ Tianxiao Fu² Yikai Wang³
Peng-Shuai Wang⁴ Xiaojie Jin¹ Yao Zhao¹ Yunchao Wei^{1,5,†}

¹Beijing Jiaotong University ²Mootion AI ³Beijing Normal University

⁴Peking University ⁵Beijing Academy of Artificial Intelligence

<https://yuyangyin.github.io/StateFlow/>




Figure 1. StateFlow turns a creative prompt into a complete, editable 3D world. Creators can construct scenes from reference images, expand environments, change visual styles, control object motion, stage dynamic events, and direct cinematic cameras through high-level intent. The same persistent world can be reused for cinematic video creation, controllable shot planning, and game-like interactive prototyping.

Abstract

*Previsualization is an intermediate layer between ideas and production in film, games, architecture, and urban design. It lets creators iteratively refine scenes, actions, cameras, and spatial-temporal dynamics. Yet existing generative methods rely on simple prompts to jointly control all of these factors through one-shot image or video synthesis, offering weak controllability and limited support for iterative editing. Fundamentally, a world comprises multiple elements with geometry, appearance, and other attributes, together with cameras. Different frames are produced through local modifications or recombinations of this shared state, which is otherwise largely reused. Therefore, we argue that the missing component is an explicit and persistent working state. To address this, we present **StateFlow**, a state-centric framework for generative previsualization. **Rather than generating videos in one shot, StateFlow uses an editable 3D world to organize scene structure, evolution, and cameras, while off-the-shelf video models enhance visual quality when higher fidelity is desired.** This world is maintained as a persistent structured 3D state of scene elements and camera configurations, serving as the core working representation for previsualization. Built on this insight, StateFlow has three stages to construct, evolve, and access the world state. State construction lifts generated 2D content into a coherent 3D world through prior-guided, conflict-aware dual-view initialization, while State evolution translates user intent into structured state transitions while preserving world memory, avoiding full-scene regeneration for each edit. State access uses render-feedback reflection to refine camera plans into visually feasible trajectories, avoiding reliance on VLM semantics alone. Experiments show that StateFlow produces high-quality 3D worlds for video creation and game-like prototyping.*

1. Introduction

Previsualization is a fundamental step in filmmaking, game development, and architectural or urban design, where creators plan scenes, block actions, test cameras, and explore spatiotemporal dynamics before final production [1, 5, 12]. Unlike final-content generation, previsualization prioritizes communicating creative intent and enabling rapid iteration over producing polished visual outputs. Creators repeatedly refine scene layout, object placement, motion, and viewpoints to explore different design choices and narrative possibilities [24].

In practice, building previsualization content remains time-consuming and expertise-intensive. Meanwhile, ex-

isting generative approaches are poorly suited to this iterative process. Although recent image and video generation methods have substantially improved visual quality [3, 4, 32, 43, 52], they are largely designed for one-shot synthesis: a simple prompt must jointly specify scene content, layout, motion, and cameras, while the generated observations expose no persistent state for local editing and validation. Consequently, they often exhibit spatiotemporal inconsistency, identity drift, and unstable local details when content is modified, extended, or viewed from different cameras.

Fundamentally, a previsualization world consists of multiple scene elements with geometry, spatial poses, semantic and appearance attributes, and dynamic states, together with camera configurations. Different shots largely reuse this information, modifying or recombining only a subset of the shared state. This suggests that previsualization should be modeled through an explicit and persistent working state rather than a sequence of isolated visual outputs.

An explicit 3D state is essential for previsualization: a shared coordinate system preserves object identity and spatial relations, supports local edits to placement and motion, and provides geometric constraints for camera planning across viewpoints and time. Existing methods can already assemble retrieved or generated assets into coherent multi-object 3D scenes [6, 8, 35, 44, 51]. However, they commonly treat scene construction as the endpoint, producing a largely static world without jointly modeling its subsequent evolution or repeated, camera-controlled access. For previsualization, an initial scene is only a starting point: the same world must remain editable as it changes and as it is viewed from different cameras.

Building on this formulation, we propose **StateFlow**, a state-centric framework for generative previsualization. Rather than generating videos in one shot, StateFlow uses an editable 3D world to organize scene structure, evolution, and cameras. Each world is represented by an editable **structured 3D state** of scene elements, geometry, spatial poses, and semantic states; StateFlow constructs and updates this state from user intent, while controllable camera trajectories provide access for scene inspection and downstream previsualization. When greater visual fidelity is desired, off-the-shelf video models [33] enhance geometry-grounded observations into expressive videos without altering the underlying world.

As shown in Fig. 1, our framework addresses three core questions in previsualization: how to initialize the structured 3D world state through **State Construction**, how to evolve the world state according to the real physical world and user intent through **State Evolution**, and how to use it for downstream tasks through **State Access**.

In **State Construction**, StateFlow translates a user’s natural-language intent into an initial 3D scene by first

*Equal contribution. †Corresponding author.

generating complementary visual references with an image model. Since a single view cannot reliably capture both object detail and global layout, we introduce *Prior-Guided Conflict-Aware Dual-View Initialization*, which combines front-view semantic grounding with BEV spatial grounding. The framework detects and resolves cross-view conflicts in object counts and spatial hypotheses, producing plausible 3D placements.

In **State Evolution**, StateFlow introduces *Intent-Guided Structured State Transition*, which translates user intent into compact updates over the structured state table, rather than continuously simulating dynamics or regenerating videos. It supports scene expansion, local style changes, object pose and motion edits, and discrete asset substitutions for events such as destruction. This keeps world evolution editable, memory-aware, and reusable for later access.

In **State Access**, StateFlow introduces *World-State Camera Planning with Render-Feedback Reflection*, a two-system design that couples VLM-based camera proposal with render-feedback verification. The VLM proposes trajectories from director intent and shot style, while geometry-faithful rendering exposes visibility, occlusion, framing, and motion issues to guide local repairs. This yields visually grounded trajectories without training a camera policy.

Overall, our formulation shifts previsualization from generating isolated visual outputs to constructing editable, evolvable, and interactive 3D worlds. Operating on the same persistent 3D world, our framework naturally supports two representative downstream previsualization applications: **video creation**, including storyboard, shot planning, and video production, and **3D game prototyping** for interactive content design. Extensive experiments across diverse tasks and application settings show that the 3D worlds constructed by our framework serve as effective representations for downstream applications, demonstrating strong flexibility, controllability, and extensibility.

In summary, our main contributions are as follows:

1. We introduce a new formulation of generative previsualization as persistent 3D world-state modeling, shifting the goal from one-shot visual synthesis to building editable, evolvable, and reusable 3D worlds.
2. We propose StateFlow, a unified state-centric framework that constructs, evolves, and accesses 3D world states through prior-guided initialization, intent-guided state transition, and render-feedback camera planning.
3. Experiments show that our method produces high-quality and fine-grained results, while naturally supporting two representative previsualization applications: video creation for storyboard, shot planning, and video production, and 3D game prototyping for interactive content design.

2. Related Work

2.1. Previsualization

Previsualization has been widely explored across film, games, and design as an intermediate process for validating scene layout, camera motion, staging, and collaboration before full production. Early studies emphasized game engines and real-time 3D tools for shot planning and preliminary scene prototyping in film and game pipelines [26, 27]. Later work extended previsualization to immersive and collaborative settings, including virtual reality, tangible interfaces, and video-based rapid ideation [1, 7, 19]. Beyond filmmaking, related studies in HCI and architectural design have framed previs as a broader method for design futuring, immersive review, and stakeholder communication [18, 58].

2.2. 3D Scene Generation

Recent 3D, 4D, and video-based generation methods create detailed objects, dynamic content, and navigable scenes from images, text, or video [21–23, 31, 37–41, 48, 49, 53, 56, 57, 60, 61]. However, they primarily generate individual assets, short dynamic sequences, or video/world reconstructions, without maintaining the persistent spatial relations, semantics, motion, and camera access required for an editable multi-object world. StateFlow instead treats video as an observation of such an explicit world state.

Existing 3D scene generation methods mainly follow three directions. Procedural approaches create large environments with hand-designed rules or asset placement pipelines [29, 30], but their diversity and realism are constrained by predefined rules and assets. LLM and VLM based methods infer object layouts and instantiate retrieved assets from curated libraries [8, 11, 36, 50, 51, 62]; while controllable, they are often limited by the coverage and style of the asset database. Recent 3D generative methods synthesize scene elements or full scenes more flexibly [6, 17, 23, 35, 41, 44, 54, 55], but accurate placement, global consistency, and high-detail scene quality remain challenging, especially under limited 3D scene data and domain coverage. In contrast, our method organizes generated content into an explicit editable 3D world state, aiming to support open-ended previsualization across diverse styles without relying on fixed scene datasets or asset domains.

2.3. Agentic Video Generation

Recent video-generation backbones, including Stable Video Diffusion (SVD) [2], CogVideoX [52], HunyuanVideo [20], Seedance [33], and Wan [43], provide increasingly capable primitives for short-clip synthesis from text or images. Building on these models, MovieAgent [46], AniMaker [34], and AniME [59] use hierarchical planning, candidate-clip selection, and director-centered coordination to generate longer, story-driven videos; VideoClaw [14],

Toonflow [13], and ViMax [15] further expose editable production stages and coordinate assets, shots, and consistency across multiple scenes. Unlike systems centered on scripts, storyboards, or dependencies, StateFlow maintains a unified 3D state of objects, relations, motion, and cameras, using rendered video as feedback for state and camera refinement.

3. Method

We present **StateFlow**, a state-centric framework for previzualization. The key idea is to treat previzualization not as one-shot output generation, but as maintaining a persistent world state that can be constructed, evolved, and accessed under different controls. In the following, we first formulate this process as persistent 3D world-state modeling, then describe how StateFlow instantiates it with an object-centric structured 3D state.

3.1. Previzualization Formulation

Both manual previs and generative previs pursue the same process: creators first establish a scene, then modify how it evolves, and finally inspect it through cameras or interactions. The difference is that manual workflows naturally maintain an explicit working state, while current generative methods often treat this state into isolated images or videos. From this perspective, previzualization can be summarized as a state-based process. Given input conditions $\mathcal{C}$, a system first builds an initial world state, then updates this state over time, and finally produces observations under controllable access:

$$\mathcal{W}^0 = \mathcal{F}_{\text{build}}(\mathcal{C}), \quad \mathcal{W}^{t+1} = \mathcal{F}_{\text{evolve}}(\mathcal{W}^t), \quad y^t = \mathcal{F}_{\text{access}}(\mathcal{W}^t). \quad (1)$$

where $\mathcal{W}^t$ denotes the world state at time t , and y^t is the resulting observation. This formulation separates three roles that are often entangled in generative visual models: the world state $\mathcal{W}^t$, its evolution $\mathcal{F}_{\text{evolve}}$, and the rendered or interactive observation y^t . In previzualization, this separation is crucial because creators repeatedly modify the same world and inspect it from different viewpoints, rather than consuming a single generated output.

3.2. Overall Pipeline

StateFlow instantiates $\mathcal{W}^t$ as an object-centric **structured 3D state**. We use an object-level state because previzualization needs to reason about what entities exist, where they are, how they look, and how they can change. At time t , the world is represented as:

$$\mathcal{W}^t = \{o_i^t\}_{i=1}^{N_t}, \quad o_i^t = (g_i^t, p_i^t, s_i^t). \quad (2)$$

Here, o_i^t denotes the i -th object entity in the world state at time t , represented by its geometry, spatial placement, and

semantic attributes. This is a minimal complete state for our setting: g_i^t provides the geometry for rendering and physical reasoning, p_i^t defines the object’s 3D position and pose for spatial layout, and s_i^t stores semantic and editable attributes such as category, appearance, and state descriptors. Removing any of these would respectively lose visual realization, spatial consistency, or controllable semantic evolution.

Built on this representation, StateFlow contains three stages: *State construction* initializes $\mathcal{W}^0$ from input conditions, *state evolution* updates the world over time, and *state access* renders or interacts with $\mathcal{W}^t$ under camera and user controls. The overall pipeline is shown in Fig. 2 This unified state representation enables automatic generation, local modification, temporal evolution and repeated observation within the same 3D world.

3.3. State Construction

Given input conditions $\mathcal{C}$, the scene construction stage initializes the first world state $\mathcal{W}^0$ by estimating both object geometry and global spatial layout. Existing generation pipelines often rely on a single view for scene construction, which either preserves appearance without reliable layout or provides layout without sufficient object appearance and vertical structure. To combine these complementary cues, we first generate a front-view image for object assets and a BEV image for spatial layout. Since the two views are generated independently, they inevitably introduce cross-view conflicts. We therefore use semantic-physical knowledge priors, instantiated with a VLM, to reconcile these conflicts and obtain a unified procedure, **Prior-Guided Conflict-Aware Dual-View Initialization**.

From the generated front view and BEV, we detect object instances and 2D layout boxes, respectively. Because the two views are independently generated, they can disagree in object count, spatial placement, and appearance details. We resolve these conflicts by factorizing the cues. We therefore assign asymmetric roles to the two views. The front view is treated as the appearance and asset source, providing object identity, local visual details, and geometry references. The BEV is treated as the spatial source, providing ground-plane placement, scene topology, and coarse spatial support.

When the detected object counts are inconsistent between two views, we handle three cases. For matched objects, we instantiate the front-view asset and place it according to the corresponding BEV layout box. For BEV-only objects, we query the VLM with the prompt, neighboring objects, and current layout context. Objects that are inconsistent with the prompt or physically unsupported by the scene are removed or down-weighted as hallucinations, while plausible contextual elements are retained. For front-only objects, we keep them as semantic anchors and use the VLM to infer tentative layout hypotheses from the prompt, object category, and nearby matched objects. These hy-




Figure 2. StateFlow turns creative intent into a persistent 3D world that can be constructed, evolved, and accessed for downstream creation. State Construction resolves cross-view conflicts between appearance, layout, and physical plausibility to build coherent object-centric worlds. State Evolution applies intent-guided world updates for scene expansion, style changes, object motion, and event transitions while preserving continuity. State Access refines camera plans with rendered feedback to ensure visibility, framing, and motion feasibility. The same world state serves both cinematic video creation and game prototyping.

potheses are later refined together with other boxes in the joint optimization.

To lift BEV layouts into 3D placements, the VLM predicts a grounding prior $\gamma_i \in \{\text{grounded}, \text{floating}\}$ for each retained object. Given a BEV box $\hat{r}_i^{\text{BEV}}$ and an asset or category size prior $\bar{s}_i$, we initialize a 3D box by a grounding-aware lifting operator:

$$b_i^{(0)} = \text{Lift}_{\gamma_i}(\hat{r}_i^{\text{BEV}}, \bar{s}_i). \quad (3)$$

For grounded objects, the vertical center is placed according to the object height; for floating objects, the height is inferred from the VLM or category prior. This converts semantic grounding cues into physically plausible 3D placement without training a 3D detector.

Finally, we refine the retained boxes with a lightweight inference-time objective:

$$\mathcal{B}^* = \arg \min_{\mathcal{B}} \mathcal{L}_{\text{front}} + \lambda_b \mathcal{L}_{\text{bev}} + \lambda_v \mathcal{L}_{\text{vlm}} + \lambda_p \mathcal{L}_{\text{phys}}. \quad (4)$$

Here, $\mathcal{L}_{\text{front}}$ preserves object identity and appearance cues from the front view, $\mathcal{L}_{\text{bev}}$ preserves global layout cues from the BEV, $\mathcal{L}_{\text{vlm}}$ enforces semantic existence and grounding priors, and $\mathcal{L}_{\text{phys}}$ penalizes obvious physical violations such as collisions or invalid scene boundaries. The optimization updates only box parameters rather than model

weights. This keeps the construction lightweight, training-free, and model-agnostic, while avoiding domain-specific 3D box detectors that typically require costly 3D annotations and can suffer from out-of-distribution failures when applied to open-ended generated scenes.

After box refinement, each optimized 3D box is used as the spatial pose term p_i^0 . In parallel, the corresponding object is cropped from the front-view image and processed independently by an image-to-3D model to obtain its geometry g_i^0 . Together with semantic attributes s_i^0 inferred from the input and knowledge priors, these terms form the initial world state:

$$\mathcal{W}^0 = \{o_i^0\}_{i=1}^{N_0}, \quad o_i^0 = (g_i^0, p_i^0, s_i^0). \quad (5)$$

The resulting $\mathcal{W}^0$ is an editable, spatially structured, and physically plausible initialization for subsequent state evolution and world interaction.

3.4. State Evolution

Given the initialized world state $\mathcal{W}^t$, the state evolution stage updates it into $\mathcal{W}^{t+1}$ according to user intent. Instead of asking a video renderer to implicitly hallucinate every dynamic process, we introduce **Intent-Guided Structured State Transition**, where a VLM queries the structured state table and predicts a compact transition plan specifying the




Figure 3. Qualitative comparison on Scene Generation

objects or scene attributes to update, the transition type, and the target state.

At the scene level, the transition plan supports global evolution such as scene expansion and scene style change. For scene expansion, the system reuses the state construction procedure to instantiate new regions or objects, and then merges them into the existing world state while preserving the original spatial support and object identities. Scene style change is handled by rewriting over scene or object descriptors, allowing localized and consistent control of style and material attributes without regenerating the entire world.

At the object level, the plan performs category-aware updates over the object state $o_i^t = (g_i^t, p_i^t, s_i^t)$. Character evolution is mainly represented by pose or trajectory updates that preserve identity while expressing behavioral states. Rigid object motion update the position and pose term p_i^t to represent movement. For events that are difficult to simulate continuously, such as explosion, destruction, or large non-rigid deformation, we use event-level asset substitution: the geometry term g_i^t is replaced by a generated or retrieved target-state asset while preserving the object’s identity, semantic role, and coarse placement. Appearance or status changes are handled by updating the semantic state term s_i^t .

Formally, the VLM produces a transition plan Δ_t from the current state and intent, and the next state is obtained by

applying it to the structured state table:

$$\begin{aligned} \Delta_t &= \text{Plan}_{\text{VLM}}(\mathcal{W}^t, u^t), \\ \mathcal{W}^{t+1} &= \text{Apply}(\mathcal{W}^t, \Delta_t) = \{o_i^{t+1}\}_{i=1}^{N_{t+1}}. \end{aligned} \quad (6)$$

Each updated object remains represented as $o_i^{t+1} = (g_i^{t+1}, p_i^{t+1}, s_i^{t+1})$. Depending on the transition type, the update affect the geometry term g_i^t , the position and pose term p_i^t , and the semantic state term s_i^t either jointly or selectively. Because evolution selectively updates over persistent object records, the resulting $\mathcal{W}^{t+1}$ remains a structured and editable 3D world state, which can be further evolved over time or accessed by downstream camera trajectories.

3.5. State Access

Given the dynamic world state $\mathcal{W}^t$, the state access stage determines how the constructed world is used for downstream tasks. While a world state can be accessed through editing commands, physical simulation, or user control, camera trajectories provide a general interface for previsualization: they convert the same persistent world into film-like keyframes, explorable videos, and game-like viewpoints without modifying the world itself. However, previous text-only camera generation[25] mainly relies on linguistic intent and lacks geometric feedback from the actual scene. To address this, we combine the semantic reasoning of a VLM with geometric evidence from rendered observations, leading to **World-State Camera Planning with**

Table 1. **Quantitative comparison with video generation methods on VBench.** Higher values indicate better performance for all metrics.

Method	Subject Cons $\uparrow$	Background Cons $\uparrow$	Aesthetic $\uparrow$	Imaging $\uparrow$	Motion Smooth $\uparrow$	Flicker $\uparrow$	Average $\uparrow$
Animaker	0.7509	0.8343	0.6795	0.6684	0.9582	0.9641	0.8092
MovieAgent	0.7533	0.8557	0.5348	0.7260	0.9895	0.9858	0.8075
Wan2.2	0.8836	0.9422	0.5220	0.6911	0.9852	0.9731	0.8283
Seedance2.0	0.8110	0.9329	0.6311	0.7184	0.9828	0.9565	0.8387
Ours	0.9135	0.9506	0.5257	0.7185	0.9923	0.9902	0.8484

Render-Feedback Reflection.

We first read camera-relevant information from $\mathcal{W}^t$, including object identities, object poses, bounding boxes, collection hierarchy, important objects, and coarse scene extent. Canonical rendered views provide additional visual context. The user instruction is summarized into segment-level director intents d_i , which specify the desired target, shot style, and motion at a high level.

For each segment, the VLM acts as a semantic proposer rather than the final controller. It generates an initial trajectory from the world state, rendered scene observations V , and director intent:

$$\pi_i^0 = \text{Propose}_{\text{VLM}}(\mathcal{W}^t, V, d_i). \quad (7)$$

We then execute the proposal in the 3D world through low-cost rendering and evaluate the rendered result:

$$R_i^k = \text{Render}(\mathcal{W}^t, \pi_i^k), \quad e_i^k = \text{Eval}(R_i^k, \pi_i^k, d_i, \mathcal{W}^t). \quad (8)$$

Here, e_i^k summarizes discrepancies such as intent mismatch, target invisibility, poor framing, collision risk, and motion artifacts.

Reflection converts these discrepancies into local repair candidates over camera parameters. For example, visibility or framing issues can be repaired by adjusting camera distance, look-at targets, or field of view; occlusion and collision issues can be repaired by changing viewpoint height, azimuth, or moving along collision-free directions. Let Δ_m denote the m -th local repair operation applied to the current trajectory. These repairs generate a compact candidate set around π_i^k rather than performing global search, from which we select the best trajectory:

$$\mathcal{P}_i^k = \{\pi_i^k + \Delta_m\}_{m=1}^M, \quad \pi_i^{k+1} = \arg \min_{\pi \in \mathcal{P}_i^k} J(\pi; d_i, \mathcal{W}^t, R_i^k). \quad (9)$$

The score J favors better trajectories satisfy intent alignment, target visibility, framing quality, collision avoidance, and motion smoothness. This local proposal-and-verification loop is efficient because it searches only over issue-driven repairs, and iterates until no significant issue is detected or maximum rounds is reached. Since only camera parameters are updated, the planner remains training-free

and does not require camera trajectory annotations. The final trajectory π_i^* provides state access for keyframe generation, free-view exploration, and third-person views while remaining grounded in the same persistent 3D world state.

4. Experiments

4.1. Implementation Details.

Our system takes a single text prompt from the user as input and automatically completes the full workflow from 3D world construction to downstream application export. We use Gemini 3.1 [9] as the vision-language model for scene understanding, intent parsing, layout reasoning, state transition planning, and camera feedback reflection. For image generation, we use Nano Banana 2 [10] to synthesize the front-view and bird’s-eye-view references used in state construction. Object-centric image crops are lifted into 3D assets using the latest Hunyuan3D model [42]. For video-based downstream outputs, we use Seedance2 [33] as the video generation backbone.

Table 2. **Quantitative comparison with scene generation.** We report CLIP-I, CLIP-T, HPS V2 and Q-Align. Higher values indicate better performance.

Method	CLIP-I $\uparrow$	CLIP-T $\uparrow$	HPS V2 $\uparrow$	Q-Align Quality/Aesthetics $\uparrow$
PartCrafter	0.542	20.761	0.110	1.675/1.587
SAM3D	0.580	15.481	0.055	2.262/2.137
SynCity	0.689	22.880	0.175	3.535/ 2.966
Ours	0.788	30.214	0.151	3.621/2.859

4.2. Comparison on Scene Generation

We compare StateFlow with representative 3D generation baselines covering different paradigms. SynCity [6] generates text-conditioned 3D worlds in a training-free, tile-by-tile manner, SAM3D [41] represents feed-forward image-to-3D generation, and PartCrafter [23] represents part-aware 3D object generation. Since our wild inference examples do not have ground-truth 3D scenes, we render each generated result into a video from a 45° bird’s-eye-view camera and compute CLIP-I and CLIP-T [28], Human Preference Score (HPS) [47] and Q-Align score [45] to measure visual and text alignment. As shown in Table 2, the results show that our method achieves overall




Figure 4. Qualitative comparison on previsualization applications. Case 1 and Case 3 showcase **video creation**, while Case 2 shows **3D game prototyping**. Video-generation baselines consistently suffer from spatial-temporal inconsistency, identity drifting, and restricted camera motion, whereas StateFlow operates on a persistent and interactive 3D world, yielding precise, highly controllable, and geometry-appearance-consistent results.

Table 3. User study and MLLM-based evaluation on 3D scene generation (top) and video generation (bottom). Each cell is reported as *user study* / *MLLM evaluation*. User study: $N=30$ participants, 12 prompts per setting. **Bold** represents the best performance.

<i>Scene-level study (45° BEV fly-around videos)</i>							
Method	Prompt Align. ↑	Layout Plaus. ↑	Completeness ↑	Geo. Quality ↑	Coherence ↑	Previs Useful. ↑	Overall Score ↑
SynCity	3.5/2.8	2.8/2.8	3.1/2.6	3.9/2.8	2.9/4.4	2.7/2.6	3.2/3.0
SAM3D	3.9/2.4	3.1/2.6	3.7/2.2	3.9/2.2	3.2/4.6	3.1/1.2	3.5/2.5
PartCrafter	2.4/2.0	1.9/2.0	1.9/2.0	2.2/2.0	2.0/3.2	1.8/1.0	2.0/2.0
w/o BEV Layout (Ours)	3.6/3.0	3.0/2.6	3.4/2.0	3.7/2.4	3.0/3.6	3.1/1.2	3.3/2.5
w/o Conflict Res. (Ours)	3.7/3.0	3.2/2.6	3.2/2.0	3.8/2.6	3.1/3.6	3.2/1.6	3.4/2.6
StateFlow (Ours)	4.4/3.6	4.6/3.3	4.2/3.7	4.2/3.6	4.6/4.7	4.7/3.1	4.5/3.7
<i>Video-level study (final rendered videos)</i>							
Method	Prompt/Story Align. ↑	Spatial Cons. ↑	Identity Cons. ↑	Motion Plaus. ↑	Camera Quality ↑	Previs Useful. ↑	Overall Score ↑
Seedance2	4.1/3.4	3.3/1.5	3.2/1.3	3.9/2.6	3.5/1.4	3.7/2.3	3.6/2.1
Wan2.2	3.5/3.6	2.8/2.4	2.7/2.2	3.4/2.7	3.0/1.6	3.1/1.5	3.1/2.3
AniMaker	2.8/1.6	2.3/1.2	2.2/1.5	2.8/2.4	2.5/2.3	2.4/1.4	2.5/1.7
MovieAgent	1.9/1.3	1.6/1.1	1.5/1.2	1.9/2.2	1.6/1.4	1.5/1.3	1.7/1.4
VLM-only Camera (Ours)	4.3/3.5	4.6/3.4	4.6/3.7	4.1/3.2	3.4/2.6	3.8/3.5	4.1/3.3
StateFlow (Ours)	4.4/3.8	4.7/4.3	4.7/3.9	4.2/3.6	4.6/4.4	4.6/4.2	4.5/4.0

superior performance, with particularly clear advantages in CLIP-I and CLIP-T. We note that HPS and Q-Align tend to exhibit strong preferences toward colorfulness and visual style, which may lead to relatively high scores for SynCity.

We also provide qualitative comparisons in Fig. 3 to inspect whether the generated outputs provide coherent spatial layout and editable scene structure required by previsualization. The visual results show that StateFlow produces more coherent and fine-grained 3D worlds than the compared baselines. In particular, our method better preserves global spatial organization while maintaining object-level details, resulting in scenes that are more suitable for downstream previsualization. In contrast, the baseline methods often suffer from incomplete scene construction, weak object relationships, or limited editable structure.

4.3. Comparison on Video Creation

We compare StateFlow with video generation methods, such as Animaker [34], MovieAgent [46], Wan2.2 [43] and Seedance2.0 [33]. These methods span large-scale text-to-video generation, narrative-driven animation synthesis, and agentic multi-shot video generation, providing a broad comparison against recent video paradigms.

Table 1 reports the quantitative comparison with representative video generation methods using VBench [16]. Our method achieves the best average score among all compared methods, indicating its overall advantage in video generation quality. In particular, our method obtains the high-

est scores in subject consistency, background consistency, motion smoothness, and flicker, suggesting that the generated videos better preserve the main object, maintain stable scene content, and exhibit smoother temporal dynamics. Although some baselines achieve slightly higher scores on aesthetic or imaging quality, these metrics are more sensitive to low-level visual preferences such as colorfulness and contrast. In contrast, our method shows stronger performance on structure and temporality related dimensions, which are more critical for controllable scene generation and previsualization.

Beyond these quantitative results, Fig. 4 presents a visual comparison with these video generation methods. StateFlow produces outputs with more stable scene structure and clearer spatial grounding, especially when the camera moves or the scene is observed from changing viewpoints. The generated videos preserve the major objects and environmental layout more reliably, while avoiding severe temporal drift or background inconsistency.

4.4. MLLM-based Evaluation and User Study

We further conduct both MLLM-based evaluation and user study to assess perceptual quality and practical usefulness, as summarized in Table 3. The evaluation covers two settings: a *scene-level* study, where each method’s output is rendered as a 45° bird’s-eye-view fly-around video, and a *video-level* study, where the final rendered videos are evaluated. For each prompt, results from all methods are shown




Figure 5. Visualization of Ablation Study

side by side in anonymized and randomized order. Participants rate each method on a 5-point Likert scale, where 1 indicates very poor quality and 5 indicates excellent quality. We also clarify that a score of 5 does not require perfection, allowing multiple methods to receive high scores when appropriate. We recruit $N=30$ participants with 12 prompts for each setting, insert attention-check items, and report per-dimension mean scores. In addition, we use gemini-3.1 as an MLLM evaluation to provide complementary automatic assessment.

At the scene level, StateFlow achieves the best performance across all evaluated dimensions, including prompt alignment, layout plausibility, completeness, geometric quality, coherence, previsualization usefulness, and overall quality. These results indicate that the proposed world-state construction produces more complete, spatially plausible, and coherent 3D scenes than existing baselines.

At the video level, StateFlow again achieves the highest overall score in both the user study and MLLM-based evaluation. Compared with video generation baselines, our method shows clear advantages in spatial consistency, identity consistency, camera quality, and previsualization usefulness. This suggests that explicitly constructing and accessing a persistent 3D world better preserves object identity and scene layout across time and viewpoints, while sup-

porting more controllable camera trajectories. Although some video baselines achieve competitive prompt/story alignment, they often exhibit weaker spatial consistency and less reliable camera behavior. In contrast, StateFlow produces more coherent and production-oriented results, making it more suitable for previsualization workflows.

4.5. Ablation Study

We further use the same MLLM-based evaluation and user study protocol to validate the key design choices of StateFlow, since these components mainly affect structural coherence, editability, and camera controllability, which are difficult to capture with metrics. The results are reported alongside the baselines in Tab. 3.

State Construction. We evaluate two construction ablations in the scene-level study. *w/o BEV Layout* removes the top-down spatial grounding and relies mainly on appearance-centric cues, which tends to produce weaker global layout, incorrect object scale, and less coherent object relations. *w/o Conflict Res.* directly combines front-view and BEV cues without resolving object-count and spatial mismatches, leading to missing, duplicated, or implausibly placed objects. These variants verify the importance of BEV grounding and conflict-aware reconciliation

for building a coherent 3D world.

State Evolution. We additionally ablate the structured state transition by replacing selective state updates with direct regeneration for edited content. This weakens identity preservation and spatial consistency across edits, since the system no longer updates persistent object records. This validates the need for evolving the world through explicit state changes rather than treating each edit as an independent generation task.

State Access. For camera planning, we compare against *VLM-only Camera*, which generates trajectories from semantic intent without render-feedback reflection. This often causes visibility, occlusion, framing, or collision issues because semantic reasoning alone cannot fully predict the visual outcome in the concrete 3D scene. The comparison verifies the effectiveness of using rendered feedback to refine camera trajectories.

5. Conclusion

This paper introduces **StateFlow**, a state-centric framework for previsualization. Rather than generating videos in one shot, it uses an editable 3D world to organize scene structure, evolution, and cameras, while off-the-shelf video models can enhance visual quality without altering the underlying world. We formulate previsualization around this persistent structured 3D state, composed of object geometry, spatial pose, and semantic attributes. Based on this representation, StateFlow initializes 3D worlds through prior-guided dual-view construction, evolves them via intent-guided state transitions, and accesses them through render-feedback camera planning for downstream applications such as keyframe generation, explorable observation, video creation, and third-person interaction.

Extensive experiments demonstrate that StateFlow provides an effective and versatile foundation for controllable previsualization, producing visually faithful results while maintaining coherent spatial layout, stable scene structure, and editable object-level organization. Beyond improving generation quality, our framework highlights the value of explicit 3D world states as an intermediate representation between generative models and production-oriented creative workflows. We believe StateFlow opens a promising direction toward more interactive, structured, and world-aware generative systems for future content creation.

Limitation and Future Work Although our method accelerates previsualization from the weeks or months typically required in industrial workflows to several minutes, it is still limited by the inference speed of third-party models and therefore cannot yet support fully

real-time interaction. In the future, with more efficient deployment and faster inference of the associated models, our method can be further accelerated.

References

- [1] Dui Ardal, Simon Alexandersson, Mirko Lempert, and André Tiago Abelho Pereira. A collaborative previsualization tool for filmmaking in virtual reality. In *Proceedings of the 16th ACM SIGGRAPH European Conference on Visual Media Production*, pages 1–10, 2019. 2, 3
- [2] Andreas Blattmann, Tim Dockhorn, Sumith Kulal, Daniel Mendelevitch, Maciej Kilian, Dominik Lorenz, Yam Levi, Zion English, Vikram Voleti, Adam Letts, et al. Stable video diffusion: Scaling latent video diffusion models to large datasets. *arXiv preprint arXiv:2311.15127*, 2023. 3
- [3] Tim Brooks, Bill Peebles, Connor Holmes, Will DePue, Yufei Guo, Leo Jing, David Schnurr, Joe Taylor, Troy Luhman, Eric Luhman, et al. Video generation models as world simulators. *OpenAI Blog*, 1(8):1, 2024. 2
- [4] Jake Bruce, Michael D Dennis, Ashley Edwards, Jack Parker-Holder, Yuge Shi, Edward Hughes, Matthew Lai, Aditi Mavalankar, Richie Steigerwald, Chris Apps, et al. Genie: Generative interactive environments. In *Forty-first International Conference on Machine Learning*, 2024. 2
- [5] Marc Christie, Patrick Olivier, and Jean-Marie Normand. Camera control in computer graphics. In *Computer graphics forum*, pages 2197–2218. Wiley Online Library, 2008. 2
- [6] Paul Engstler, Aleksandar Shtedritski, Iro Laina, Christian Rupprecht, and Andrea Vedaldi. Syncity: Training-free generation of 3d worlds. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 27585–27595, 2025. 2, 3, 7
- [7] Guangzheng Fei and Dake Liu. Tape: Tangible augmented previz environment for filmmaking. In *Proceedings of the Eleventh International Symposium of Chinese CHI*, pages 251–262, 2023. 3
- [8] Weixi Feng, Wanrong Zhu, Tsu-jui Fu, Varun Jampani, Arjun Akula, Xuehai He, Sugato Basu, Xin Eric Wang, and William Yang Wang. Layoutgpt: Compositional visual planning and generation with large language models. *Advances in Neural Information Processing Systems*, 36:18225–18250, 2023. 2, 3
- [9] Google. Gemini 3.1 Pro Preview. <https://ai.google.dev/gemini-api/docs/models/gemini-3.1-pro-preview>, 2026. Accessed: 2026-05-12. 7
- [10] Google. Nano Banana 2: Google’s latest AI image generation model. <https://blog.google/innovation-and-ai/technology/ai/nano-banana-2/>, 2026. Accessed: 2026-05-12. 7
- [11] Zeqi Gu, Yin Cui, Zhaoshuo Li, Fangyin Wei, Yunhao Ge, Jinwei Gu, Ming-Yu Liu, Abe Davis, and Yifan Ding. Artiscene: Language-driven artistic 3d scene generation through image intermediary. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 2891–2901, 2025. 3

- [12] Brett A Halperin and Stephanie M Lukin. From camera-eye to ai: Exploring the interplay of cinematography and computational visual storytelling. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems*, pages 1–18, 2025. 2
- [13] HBAI-Ltd. Toonflow-app: Open-source ai tool for animated short drama creation. <https://github.com/HBAI-Ltd/Toonflow-app>, 2026. GitHub repository, accessed 2026-08-08. 4
- [14] HITsz-TMG. Videoclaw: Ai creative video production agent. <https://github.com/HITsz-TMG/VideoClaw>, 2026. GitHub repository, accessed 2026-08-08. 3
- [15] Lingxuan Huang, Sizhe He, Hengji Zhou, Liqiang Nie, Lianghao Xia, and Chao Huang. Vimax: Agentic video generation. *arXiv preprint arXiv:2606.07649*, 2026. 4
- [16] Ziqi Huang, Yinan He, Jiashuo Yu, Fan Zhang, Chenyang Si, Yuming Jiang, Yuanhan Zhang, Tianxing Wu, Qingyang Jin, Nattapol Chanpaisit, et al. Vbench: Comprehensive benchmark suite for video generative models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 21807–21818, 2024. 9
- [17] Zehuan Huang, Yuan-Chen Guo, Xingqiao An, Yunhan Yang, Yangguang Li, Zi-Xin Zou, Ding Liang, Xihui Liu, Yan-Pei Cao, and Lu Sheng. Midi: Multi-instance diffusion for single image to 3d scene generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 23646–23657, 2025. 3
- [18] Alexander Ivanov, Tim Au Yeung, Kathryn Blair, Kurtis Danyluk, Georgina Freeman, Marcus Friedel, Carmen Hull, Michael Yuk-Shing Hung, Sydney Pratte, and Wesley Willett. One week in the future: Previs design futuring for hci research. In *Proceedings of the 2022 CHI Conference on Human Factors in Computing Systems*, pages 1–15, 2022. 3
- [19] Hye-Young Jo, Ryo Suzuki, and Yoonji Kim. Collagevis: Rapid previsualization tool for indie filmmaking using video collages. In *Proceedings of the 2024 CHI Conference on Human Factors in Computing Systems*, pages 1–16, 2024. 3
- [20] Weijie Kong, Qi Tian, Zijian Zhang, Rox Min, Zuozhuo Dai, Jin Zhou, Jiangfeng Xiong, Xin Li, Bo Wu, Jianwei Zhang, et al. Hunyuanvideo: A systematic framework for large video generative models. *arXiv preprint arXiv:2412.03603*, 2024. 3
- [21] Longfei Li, Zhiwen Fan, Wenyan Cong, Xinhang Liu, Yuyang Yin, Matt Foutter, Panwang Pan, Chenyu You, Yue Wang, Zhangyang Wang, et al. Martian world model: Controllable video synthesis with physically accurate 3d reconstructions. *Advances in Neural Information Processing Systems*, 38, 2026. 3
- [22] Hanwen Liang, Yuyang Yin, Dejia Xu, Hanxue Liang, Zhangyang Wang, Konstantinos N Plataniotis, Yao Zhao, and Yunchao Wei. Diffusion4d: Fast spatial-temporal consistent 4d generation via video diffusion models. *arXiv preprint arXiv:2405.16645*, 2024.
- [23] Yuchen Lin, Chenguo Lin, Panwang Pan, Honglei Yan, Yiqiang Feng, Yadong Mu, and Katerina Fragkiadaki. Partcrafter: Structured 3d mesh generation via compositional latent diffusion transformers. *arXiv preprint arXiv:2506.05573*, 2025. 3, 7
- [24] Christophe Lino, Marc Christie, Roberto Ranon, and William Bares. The director’s lens: an intelligent assistant for virtual cinematography. In *Proceedings of the 19th ACM international conference on Multimedia*, pages 323–332, 2011. 2
- [25] Xinhang Liu, Yu-Wing Tai, and Chi-Keung Tang. Chatcam: Empowering camera control through conversational ai. *Advances in Neural Information Processing Systems*, 37: 54483–54506, 2024. 6
- [26] Michael Nitsche. Experiments in the use of game technology for pre-visualization. In *Proceedings of the 2008 Conference on Future Play: Research, Play, Share*, pages 160–165, 2008. 3
- [27] Lesley Northam, Joe Istead, and Craig S Kaplan. A collaborative real time previsualization tool for video games and film. In *ACM SIGGRAPH 2012 Posters*, pages 1–1. 2012. 3
- [28] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PmLR, 2021. 7
- [29] Alexander Raistrick, Lahav Lipson, Zeyu Ma, Lingjie Mei, Mingzhe Wang, Yiming Zuo, Karhan Kayan, Hongyu Wen, Beining Han, Yihan Wang, Alejandro Newell, Hei Law, Ankit Goyal, Kaiyu Yang, and Jia Deng. Infinite photorealistic worlds using procedural generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12630–12641, 2023. 3
- [30] Alexander Raistrick, Lingjie Mei, Karhan Kayan, David Yan, Yiming Zuo, Beining Han, Hongyu Wen, Meenal Parakh, Stamatis Alexandropoulos, Lahav Lipson, Zeyu Ma, and Jia Deng. Infinigen indoors: Photorealistic indoor scenes using procedural generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 21783–21794, 2024. 3
- [31] Jiawei Ren, Liang Pan, Jiaxiang Tang, Chi Zhang, Ang Cao, Gang Zeng, and Ziwei Liu. Dreamgaussian4d: Generative 4d gaussian splatting. *arXiv preprint arXiv:2312.17142*, 2023. 3
- [32] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10684–10695, 2022. 2
- [33] Team Seedance, De Chen, Liyang Chen, Xin Chen, Ying Chen, Zhuo Chen, Zhuowei Chen, Feng Cheng, Tianheng Cheng, Yufeng Cheng, et al. Seedance 2.0: Advancing video generation for world complexity. *arXiv preprint arXiv:2604.14148*, 2026. 2, 3, 7, 9
- [34] Haoyuan Shi, Yunxin Li, Xinyu Chen, Longyue Wang, Baotian Hu, and Min Zhang. Animaker: Multi-agent animated storytelling with mcts-driven clip generation. In *Proceedings of the SIGGRAPH Asia 2025 Conference Papers*, pages 1–11, 2025. 3, 9

- [35] Yukai Shi, Weiyu Li, Zihao Wang, Hongyang Li, Xingyu Chen, Ping Tan, and Lei Zhang. Scenemaker: Open-set 3d scene generation with decoupled de-occlusion and pose estimation model. *arXiv preprint arXiv:2512.10957*, 2025. 2, 3
- [36] Fan-Yun Sun, Weiyu Liu, Siyi Gu, Dylan Lim, Goutam Bhat, Federico Tombari, Manling Li, Nick Haber, and Jiajun Wu. Layoutvlm: Differentiable optimization of 3d layout via vision-language models. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 29469–29478, 2025. 3
- [37] Wenqiang Sun, Shuo Chen, Fangfu Liu, Zilong Chen, Yueqi Duan, Jun Zhang, and Yikai Wang. Dimensionx: Create any 3d and 4d scenes from a single image with controllable video diffusion. *arXiv preprint arXiv:2411.04928*, 2024. 3
- [38] Wenqiang Sun, Haiyu Zhang, Haoyuan Wang, Junta Wu, Zehan Wang, Zhenwei Wang, Yunhong Wang, Jun Zhang, Tengfei Wang, and Chunchao Guo. Worldplay: Towards long-term geometric consistency for real-time interactive world modeling. *arXiv preprint arXiv:2512.14614*, 2025.
- [39] Jiaxiang Tang, Jiawei Ren, Hang Zhou, Ziwei Liu, and Gang Zeng. Dreamgaussian: Generative gaussian splatting for efficient 3d content creation. In *International Conference on Learning Representations*, pages 33879–33896, 2024.
- [40] HY Team, Chenjie Cao, Xuhui Zuo, Zhenwei Wang, Yisu Zhang, Junta Wu, Zhenyang Liu, Yuning Gong, Yang Liu, Bo Yuan, et al. Hy-world 2.0: A multi-modal world model for reconstructing, generating, and simulating 3d worlds. *arXiv e-prints*, pages arXiv–2604, 2026.
- [41] SAM 3D Team, Xingyu Chen, Fu-Jen Chu, Pierre Gleize, Kevin J Liang, Alexander Sax, Hao Tang, Weiyao Wang, Michelle Guo, Thibaut Hardin, Xiang Li, Aohan Lin, Jiawei Liu, Ziqi Ma, Anushka Sagar, Bowen Song, Xiaodong Wang, Jianing Yang, Bowen Zhang, Piotr Dollár, Georgia Gkioxari, Matt Feiszli, and Jitendra Malik. Sam 3d: 3dfy anything in images. 2025. 3, 7
- [42] Tencent Hunyuan3D Team. Hunyuan3d 2.5: Towards high-fidelity 3d assets generation with ultimate details, 2025. 7
- [43] Team Wan, Ang Wang, Baole Ai, Bin Wen, Chaojie Mao, Chen-Wei Xie, Di Chen, Feiwei Yu, Haiming Zhao, Jianxiao Yang, et al. Wan: Open and advanced large-scale video generative models. *arXiv preprint arXiv:2503.20314*, 2025. 2, 3, 9
- [44] Dilin Wang, Hyunyoung Jung, Tom Monnier, Kihyuk Sohn, Chuhan Zou, Xiaoyu Xiang, Yu-Ying Yeh, Di Liu, Zixuan Huang, Thu Nguyen-Phuoc, et al. Worldgen: From text to traversable and interactive 3d worlds. *arXiv preprint arXiv:2511.16825*, 2025. 2, 3
- [45] Haoning Wu, Zicheng Zhang, Weixia Zhang, Chaofeng Chen, Liang Liao, Chunyi Li, Yixuan Gao, Annan Wang, Erli Zhang, Wenxiu Sun, et al. Q-align: Teaching lms for visual scoring via discrete text-defined levels. *arXiv preprint arXiv:2312.17090*, 2023. 7
- [46] Weijia Wu, Zeyu Zhu, and Mike Zheng Shou. Automated movie generation via multi-agent cot planning. *arXiv preprint arXiv:2503.07314*, 2025. 3, 9
- [47] Xiaoshi Wu, Keqiang Sun, Feng Zhu, Rui Zhao, and Hongsheng Li. Human preference score: Better aligning text-to-image models with human preference. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 2096–2105, 2023. 7
- [48] Jianfeng Xiang, Zelong Lv, Sicheng Xu, Yu Deng, Ruicheng Wang, Bowen Zhang, Dong Chen, Xin Tong, and Jiaolong Yang. Structured 3d latents for scalable and versatile 3d generation. In *2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 21469–21480. IEEE, 2025. 3
- [49] Ke Xing, Hanwen Liang, Dejia Xu, Yuyang Yin, Konstantinos N Platanotis, Yao Zhao, and Yunchao Wei. Tip4gen: Text to immersive panorama 4d scene generation. In *Proceedings of the 33rd ACM International Conference on Multimedia*, pages 9267–9276, 2025. 3
- [50] Yixuan Yang, Junru Lu, Zixiang Zhao, Zhen Luo, James JQ Yu, Victor Sanchez, and Feng Zheng. Llplace: The 3d indoor scene layout generation and editing via large language model. *arXiv preprint arXiv:2406.03866*, 2024. 3
- [51] Yue Yang, Fan-Yun Sun, Luca Weihs, Eli VanderBilt, Alvaro Herrasti, Winson Han, Jiajun Wu, Nick Haber, Ranjay Krishna, Lingjie Liu, et al. Holodeck: Language guided generation of 3d embodied ai environments. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 16227–16237, 2024. 2, 3
- [52] Zhuoyi Yang, Jiayan Teng, Wendi Zheng, Ming Ding, Shiyu Huang, Jiazheng Xu, Yuanming Yang, Wenyi Hong, Xiaohan Zhang, Guanyu Feng, et al. Cogvideox: Text-to-video diffusion models with an expert transformer. *arXiv preprint arXiv:2408.06072*, 2024. 2, 3
- [53] Zhongqi Yang, Wenhong Ge, Yuqi Li, Jiaqi Chen, Haoyuan Li, Mengyin An, Fei Kang, Hua Xue, Baixin Xu, Yuyang Yin, et al. Matrix-3d: Omnidirectional explorable 3d world generation. *arXiv preprint arXiv:2508.08086*, 2025. 3
- [54] Zhifei Yang, Keyang Lu, Chao Zhang, Jiaxing Qi, Hanqi Jiang, Ruifei Ma, Shenglin Yin, Yifan Xu, Mingzhe Xing, Zhen Xiao, et al. Mmgdreamer: Mixed-modality graph for geometry-controllable 3d indoor scene generation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 9391–9399, 2025. 3
- [55] Zhifei Yang, Guangyao Zhai, Keyang Lu, YuYang Yin, Chao Zhang, Zhen Xiao, Jieyi Long, Nassir Navab, and Yikai Wang. Flowscene: Style-consistent indoor scene generation with multimodal graph rectified flow. *arXiv preprint arXiv:2603.19598*, 2026. 3
- [56] Yuyang Yin, Dejia Xu, Zhangyang Wang, Yao Zhao, and Yunchao Wei. 4dgen: Grounded 4d content generation with spatial-temporal consistency. *arXiv preprint arXiv:2312.17225*, 2023. 3
- [57] Yuyang Yin, HaoXiang Guo, Fangfu Liu, Mengyu Wang, Hanwen Liang, Eric Li, Yikai Wang, Xiaojie Jin, Yao Zhao, and Yunchao Wei. Panoworld-x: Generating explorable panoramic worlds via sphere-aware video diffusion. *arXiv preprint arXiv:2509.24997*, 2025. 3
- [58] Rongrong Yu, Ning Gu, Gun Lee, and Ayaz Khan. A systematic review of architectural design collaboration in immersive virtual environments. *Designs*, 6(5):93, 2022. 3
- [59] Lisai Zhang, Baohan Xu, Siqian Yang, Mingyu Yin, Jing Liu, Chao Xu, Siqi Wang, Yidi Wu, Yuxin Hong, Zihao

- Zhang, et al. Anime: Adaptive multi-agent planning for long animation generation. In *Proceedings of the SIGGRAPH Asia 2025 Posters*, pages 1–3. 2025. [3](#)
- [60] Yisu Zhang, Chenjie Cao, Tengfei Wang, Xuhui Zuo, Junta Wu, Jianke Zhu, and Chunchao Guo. Worldstereo: Bridging camera-guided video generation and scene reconstruction via 3d geometric memories. *arXiv preprint arXiv:2603.02049*, 2026. [3](#)
- [61] Zibo Zhao, Zeqiang Lai, Qingxiang Lin, Yunfei Zhao, Haolin Liu, Shuhui Yang, Yifei Feng, Mingxin Yang, Sheng Zhang, Xianghui Yang, et al. Hunyuan3d 2.0: Scaling diffusion models for high resolution textured 3d assets generation. *arXiv preprint arXiv:2501.12202*, 2025. [3](#)
- [62] Xiaoming Zhu, Xu Huang, Qinghongbing Xie, Zhi Deng, Junsheng Yu, Yirui Guan, Zhongyuan Liu, Lin Zhu, Qijun Zhao, Ligang Liu, et al. Imaginarium: Vision-guided high-quality 3d scene layout generation. *ACM Transactions on Graphics (TOG)*, 44(6):1–24, 2025. [3](#)