

StreamSoccer: Event-Driven Memory for Streaming Soccer Commentary

Chenxi Shao^{1,2} Bozhong Wang^{2,3} Jiaxin Huang² Zhao Liu² Sunwei Zhu²
Tianxin Hang² Gaoqi He¹ Yang Li^{1,*} Changbo Wang^{1,*}

¹East China Normal University, Shanghai, China

²Migu Video Technology Co., Ltd., Shanghai, China

³South China University of Technology, Guangzhou, Guangdong, China




Figure 1: Completed-event context under a causal stream. The three paired examples compare StreamingVLM and StreamSoccer within one 20-minute match segment selected to contain all three commentary tasks.

Abstract

Streaming video understanding requires models to causally update state as video arrives and organize growing history into semantic units that can evolve, persist, and be recalled under bounded computation and memory. This challenge is especially pronounced in live soccer commentary, where a system must describe completed events, summarize recent play, recall earlier events, or remain silent using only information available before each utterance. We present StreamSoccer, an event-driven system that uses event memory as its intermediate representation. A fixed-budget active memory integrates the stream; completed event states are retained locally and consolidated into retrievable historical records. A unified generator uses current, recent, and historical context to produce three commentary modes, while a rule-assisted scheduler selects a mode or silence. Unlike general streaming video-language models that organize history around frames, visual tokens, or caches, and soccer-commentary methods that rely on predefined clips or output timestamps, StreamSoccer explicitly models event lifecycles. We construct a three-track streaming soccer commentary dataset and layered evaluation protocol. At common reference anchors, StreamSoccer obtains CIDER scores of 38.62, 23.96, and 17.39 on current-event, recent-

window, and historical-memory commentary, ranking first on the current-event and historical-memory tracks and second on recent-window. Controlled ablations show that local completed events improve all tracks; the full system performs best on all three, with the largest additional gain on recent-window commentary. Across 174 raw-video runs on 58 matches, per-minute RTF p95 remains approximately 0.10–0.22 without sustained growth with match history. These results indicate that event memory supports streaming soccer commentary across temporal scopes while controlling long-history computation.

1 Introduction

Streaming video understanding requires models to update their state continuously as video arrives and the future remains unobserved, while retaining information useful for downstream tasks under bounded computation and memory. This challenge is particularly acute in live soccer commentary: a system must continuously understand an evolving match process and generate commentary at appropriate moments across different temporal scopes. Existing soccer-commentary methods typically rely on predefined video clips, given output timestamps, or offline full-video input, whereas general streaming video-language models manage growing history by compressing

* Corresponding authors.

frames, visual tokens, or key–value caches. These approaches offer strong video understanding and language generation, but usually do not treat an evolving semantic process as a state unit that must be maintained continuously, closed upon completion, and reused later.

This gap concerns not only the efficiency of history compression, but also the unit around which a streaming system should organize its state. A semantic process in soccer often spans multiple consecutive video clips: its relevant visual information accumulates as play unfolds and can continue to influence subsequent commentary after the process completes. Meanwhile, soccer commentary does not rely on a single temporal scale. Current-event commentary describes a just-completed event, recent-window commentary aggregates several recent events, and historical-memory commentary recalls information formed earlier in the match. A suitable intermediate representation should therefore absorb new observations as an event develops, compress a variable-duration process into a fixed-budget state, form stable and reusable memory upon completion, and support both recent retention and historical retrieval. Event memory naturally matches these requirements: a state is activated and updated with an event, closed when the event completes, and subsequently retained, consolidated, and retrieved when needed. We therefore hypothesize that event memory is an effective intermediate representation for streaming soccer commentary.

Based on this hypothesis, we introduce StreamSoccer, an event-driven streaming soccer commentary system. StreamSoccer maintains a fixed-budget active event memory as the match progresses and closes the current state as a completed event memory when an operational event ends. Recent completed events remain compact latent context, while completed memories can also be consolidated into retrievable textual records for later historical retrieval. A rule-assisted scheduler selects current-event commentary, recent-window commentary, historical-memory commentary, or silence; once a commentary mode is selected, a unified generator assembles the event context required by that mode and produces the corresponding commentary. Through this *activate–update–close–consolidate–retrieve* event lifecycle, StreamSoccer transforms a growing video history into fixed-budget states with explicit semantic roles.

To train and evaluate these capabilities, we construct three-track streaming commentary data from SoccerNet action annotations and MatchTime commentary [3, 16]. Every sample has an explicit observation cutoff and source-event provenance; data construction checks for future information and uses match-disjoint splits. Evaluation separately examines commentary quality at controlled output anchors, the use of event memory and historical context, and runtime efficiency from raw-video input.

Our contributions are threefold:

(1) We formulate soccer commentary as a streaming generation task in which each output may use only information observable before its emission time. The task comprises three complementary tracks—current-event, recent-window, and historical-memory commentary—and is supported by a data

pipeline with explicit observation cutoffs, source provenance, and match-disjoint splits.

(2) We introduce StreamSoccer, an event-driven streaming soccer commentary system that uses event memory as its intermediate representation. It continuously updates fixed-budget active-event state, retains and consolidates completed event memories, and supports unified commentary generation with recent context and historical retrieval, thereby organizing a growing video history into reusable event-level states.

(3) We evaluate StreamSoccer under distinct settings that separately measure three-track commentary quality at common reference anchors, the role of event memory, and long-history processing efficiency from raw-video input. StreamSoccer ranks first on current-event and historical-memory commentary and second on recent-window commentary; the complete event-memory system performs best across all three tracks in memory-scope ablations, while runtime efficiency shows no sustained degradation as match history grows.

2 Related Work

Soccer Commentary and Captioning. The SoccerNet series established foundational tasks and datasets for soccer video understanding [4]. SoccerNet-Caption formulates commentary as timestamped dense video captioning, MatchTime improves video–text alignment, and GOAL provides a knowledge-enhanced commentary benchmark [12, 13]. TimeSoccer, *Towards Universal Soccer Video Understanding*, and SoccerMaster further extend full-half modeling and soccer representation learning [15, 24, 26]. MatchAware conditions generation on preceding events, while GameSight combines entity-aware visual reasoning with external statistics and an evolving game state [8, 19]. These methods provide strong domain data and models but are generally evaluated on pre-defined clips, reference timestamps, or offline long videos. StreamSoccer instead maintains event state, consolidates completed events, and reuses them while operating along the match timeline.

Streaming Video-Language Models. Flash-VStream, VideoStreaming, and StreamFormer support continuous video processing through hierarchical compression, a fixed visual-token budget, and forward-only temporal modeling, respectively [14, 23, 27]. TimeChat-Online filters redundant visual tokens, while StreamingVLM maintains a compact key–value cache aligned with chunked streaming inference [22, 25]. VideoLLM-online converts offline temporal annotations into streaming dialogue supervision, while StreamBridge augments offline Video-LLMs with compressed memory and proactive activation [2, 21]. These systems demonstrate efficient continuous processing, but usually organize state as task-agnostic frames, tokens, or compressed history rather than around the evolution and lifecycle of soccer events.

Memory and Retrieval for Long Video Understanding. MART uses recurrent memory for coherent multi-sentence




Figure 2: Overview of StreamSoccer. Incoming clips are encoded as event tokens E_t and update the active event state. When an event closes, its completed memory M_j^c supports current-event commentary, enters the Recent Event Buffer, and is converted into Historical Event Records. The rule-assisted schedule selects a commentary mode or silence. For generation, selected latent states are projected into Z_t , while retrieved records $\mathcal{R}_t$ are provided as text.

video description, while MovieChat and MA-LMM compress or write long visual histories into internal memory [5, 9, 18]. VideoRAG retrieves external video content, and SoccerComment applies preconstructed multimodal memory and retrieval-augmented prompting to soccer commentary [7, 10]. Their historical context is typically a generic internal state or a prebuilt corpus. In contrast, StreamSoccer derives retrievable event records from completed memories in the current stream and reuses them as historical context once they become available.

3 Task Formulation: Streaming Soccer Commentary

Streaming soccer commentary is a generation task constrained by temporal visibility. We represent a match as a temporally ordered sequence of video clips $\mathcal{C} = \{C_1, \dots, C_T\}$, where the clip C_t arriving at step t covers the interval $[s_t, e_t]$. At decision step t , the system has an observation cutoff τ_t and may access only clips C_u satisfying $e_u \leq \tau_t$, together with auxiliary information formed by that cutoff.

Based on the match history visible by the cutoff, the system emits one commentary sentence y_t , or $\emptyset$ to remain silent. Future video, events that have not yet occurred, the final match state, and any information formed after τ_t cannot be used for the current output; using them in an input, conditioning signal, or target constitutes future leakage. This visibility constraint applies to training samples, controlled evaluation, and continuous timeline execution.

We define three complementary tracks according to the temporal scope of the commentary:

- **Current-event commentary** describes a just-completed match event, focusing on its local actions, development, and outcome.

- **Recent-window commentary** summarizes multiple recent match processes visible before the cutoff, capturing short-horizon trends, sequences of attacks and defenses, or recurring patterns.
- **Historical-memory commentary** connects the current or recent match process with earlier match information that was formed and available before the cutoff, producing commentary over a longer temporal scope.

The three tracks share the same temporal-visibility constraint but differ in the scope of history they require. This definition does not prescribe a particular event partition, memory representation, historical retrieval mechanism, or speaking scheduler.

4 Method: StreamSoccer

4.1 System Overview

As shown in Figure 2, the Vision Encoder and Clip Event Adapter map each incoming clip to fixed-budget event tokens E_t . Online Event Update compares the arriving tokens with the previous active memory, updates the ongoing state through gated integration, and uses the State Selector to continue that state or initialize a new one. When a reset closes the previous state, the completed event memory M_j^c becomes available for current-event commentary and is retained in the Recent Event Buffer. Together, these operations implement the **Streaming Event Memory Encoder** described next.

The record branch converts completed event memories into textual Historical Event Records for later retrieval. At each decision point, the rule-assisted schedule selects current-event, recent-window, historical-memory commentary, or silence. For a non-silent mode, the **Multi-Context Commentary Generator** projects the required current and recent latent states

through P_θ into the soft prefix Z_t ; historical-memory commentary additionally supplies the retrieved records $\mathcal{R}_t$ as text to the language model. This separates compact latent context from textual historical context while retaining one generation interface across the three commentary modes.

4.2 Streaming Event Memory Encoder

For each incoming clip C_t , a frozen Qwen3-VL visual encoder produces visual tokens. The Clip Event Adapter compresses them with learnable queries into a fixed number of clip-level event tokens:

$$V_t = \mathcal{F}_{\text{vis}}(C_t), \quad E_t = \mathcal{A}(V_t) \in \mathbb{R}^{K_m \times d_m}. \quad (1)$$

Here, $E_t[0]$ summarizes the current clip, while the remaining tokens retain distributed event information. Before incorporating the clip, the Operational Transition Head compares $E_t[0]$ with the previous active state M_{t-1} and predicts the operational-transition indicator b_t .

When the clip continues the ongoing process, the memory absorbs incremental information through slot-wise gating:

$$\widetilde{M}_t = (1 - G_t) \odot M_{t-1} + G_t \odot \mathcal{U}(M_{t-1}, E_t). \quad (2)$$

Here, $\mathcal{U}$ denotes the candidate update after reading the current clip, and G_t controls the retention of existing information and the writing of new information in each memory slot. The state always contains K_m tokens, regardless of the number of clips spanned by the process.

In addition to predicted transitions, a maximum event duration D_{max} provides a deterministic safeguard. Let ρ_t denote this duration safeguard. The final reset signal and state transition are

$$\begin{aligned} \rho_t &= [\text{dur}(M_{t-1}) \geq D_{\text{max}}], & r_t &= b_t \vee \rho_t, \\ M_t &= (1 - r_t)\widetilde{M}_t + r_t \mathcal{I}(E_t), & M_j^c &\leftarrow M_{t-1} \quad \text{if } r_t = 1. \end{aligned} \quad (3)$$

When $r_t = 1$, M_{t-1} is closed as the immutable completed-event memory M_j^c , and the initializer $\mathcal{I}$ uses the current clip E_t to establish the new M_t . The learned b_t represents an operational transition, whereas ρ_t serves only as a deterministic duration safeguard. Training uses teacher-forced resets and excludes duration-safeguard positions from positive transition supervision. At inference, resets are controlled jointly by the predicted b_t and deterministic ρ_t . The remaining active state is closed as the final completed-event memory at the end of the stream.

4.3 Memory-to-Record Consolidation

A completed-event memory M_j^c encodes the visual development of an event in a compact latent form. Memory-to-Record Consolidation maps it through the memory-to-language projector $P_\theta(\cdot)$ to a fixed-length soft prefix. Conditioned on this prefix and the minimal causally available match context x_j^{ctx} at event closure, the language model generates an event-record

caption c_j , followed by deterministic record assembly:

$$\begin{aligned} p(c_j \mid P_\theta(M_j^c), x_j^{\text{ctx}}), \\ R_j = \text{Assemble}(\text{metadata}_j, c_j). \end{aligned} \quad (4)$$

The fixed-length prefix keeps the language-model interface independent of the number of clips within an event. The caption c_j summarizes the event’s actions, progression, and outcome, while structured metadata and source-event provenance are populated deterministically. At event closure, M_j^c immediately enters the local event-memory buffer $\mathcal{B}_t$; in parallel, the record branch asynchronously completes caption generation, deterministic assembly, and storage, after which the ready R_j enters $\mathcal{L}_t$ for historical retrieval.

4.4 Multi-Context Commentary Generator

The Multi-Context Commentary Generator shares the memory-to-language projector P_θ , language model, and decoding process across the three tracks, while each track uses a track-specific context configuration. Let $\mathcal{B}_t^{\text{sel}} \subseteq \mathcal{B}_t$ denote the selected local completed-event memories at time t , and let $[\cdot; \cdot]$ denote memory concatenation. The latent soft prefix is

$$Z_t = \begin{cases} P_\theta(M_j^c), & \text{current-event,} \\ P_\theta([M_t; \mathcal{B}_t^{\text{sel}}]), & \text{recent/historical.} \end{cases} \quad (5)$$

Current-event commentary uses the just-closed completed-event memory M_j^c . Recent-window and historical-memory commentary concatenate the active event memory M_t with selected local completed-event memories and compress them with P_θ into a fixed-length soft prefix. Historical-memory commentary additionally serializes retrieved records $\mathcal{R}_t \subseteq \mathcal{L}_t$ as prompt text, allowing the shared generator to combine current and recent latent context with retrieved historical record text.

4.5 Online Runtime and Rule-Assisted Scheduling

At decision step t , long-term retrieval filters $\mathcal{L}_t$ by temporal range and ranks eligible records with the LTM retrieval query projection, returning the top- k records $\mathcal{R}_t$. Given the just-completed event, local memories, retrieved records, and commentary cadence, a deterministic rule-assisted scheduler selects $\delta_t \in \{\text{silence, current-event, recent-window, historical-memory}\}$.

Current-event mode requires a salient just-completed event and a satisfied cooldown; recent-window mode requires sufficient completed events and passes periodic and event-proximity gates; historical-memory mode requires records that satisfy temporal, relevance, and cooldown conditions. Otherwise, the system remains silent. When multiple modes are eligible, a fixed priority selects one mode and its context configuration; non-silent decisions invoke the Multi-Context Commentary Generator. The learned query projection only ranks historical candidates, whereas the rule-assisted policy determines speaking time, commentary mode, and context

configuration. The scheduler uses fixed thresholds, priorities, cooldowns, and queue parameters, while evaluation-specific interventions are defined by the experimental protocol.

4.6 Training Objectives

StreamSoccer uses three training stages for event-memory learning, memory-to-record consolidation, and multi-context commentary generation. The visual encoder and pretrained language-model backbone remain frozen, with language-side adaptation implemented through LoRA [6].

Stage 1 trains the Streaming Event Memory Encoder with four complementary objectives:

$$\mathcal{L}_{\text{Stage1}} = \alpha_{\text{clip}}\mathcal{L}_{\text{clip}} + \alpha_{\text{tr}}\mathcal{L}_{\text{tr}} + \alpha_{\text{evt-act}}\mathcal{L}_{\text{evt-act}} + \alpha_{\text{evt-type}}\mathcal{L}_{\text{evt-type}}. \quad (6)$$

Here, $\mathcal{L}_{\text{clip}}$ uses asymmetric loss [17] for sparse multi-label action recognition on every clip, and $\mathcal{L}_{\text{tr}}$ uses focal binary cross-entropy [11] for operational-transition prediction at valid positions. Upon event completion, $\mathcal{L}_{\text{evt-act}}$ uses focal binary cross-entropy to supervise the multi-label action set, while $\mathcal{L}_{\text{evt-type}}$ uses cross-entropy for the coarse event type. Duration-safeguard positions are masked from operational-transition supervision.

Stage 2 trains the memory-to-language projector and language-model LoRA parameters to generate c_j from M_j^c . Its autoregressive objective $\mathcal{L}_{\text{Stage2}}$ is applied only to assistant caption tokens.

Stage 3 is initialized from the first two stages and optimizes the trainable modules enabled in the reported configuration over all three commentary tracks. The task-balanced $\mathcal{L}_{\text{gen}}$ supervises commentary generation, while $\mathcal{L}_{\text{retain}}$ reuses the four Stage 1 objectives to preserve event semantics. The memory-context objective $\mathcal{L}_{\text{route}}$ supervises the required memory context, $\mathcal{L}_{\text{local}}$ ranks recent candidate events, and $\mathcal{L}_{\text{retr}}$ ranks historical candidate records. The latter two ranking losses are computed only when valid positive and negative evidence is available.

The complete Stage 3 objective is

$$\mathcal{L}_{\text{Stage3}} = \lambda_{\text{gen}}\mathcal{L}_{\text{gen}} + \lambda_{\text{retain}}\mathcal{L}_{\text{retain}} + \lambda_{\text{route}}\mathcal{L}_{\text{route}} + \lambda_{\text{local}}\mathcal{L}_{\text{local}} + \lambda_{\text{retr}}\mathcal{L}_{\text{retr}}. \quad (7)$$

The three context-selection objectives provide auxiliary supervision for memory use. At runtime, the rule-assisted scheduler determines the commentary mode and local context selection, while the query projection learned through $\mathcal{L}_{\text{retr}}$ ranks event records. This separates learned context ranking from deterministic runtime decisions.

5 Experiments

We evaluate StreamSoccer through common-anchor commentary quality, raw-video efficiency as match history grows, event-memory representation and context ablations, and a qualitative case study.

5.1 Experimental Setup

Datasets and Splits. We construct three-track streaming soccer commentary data from SoccerNet action annotations and MatchTime commentary. The dataset contains 27,639 samples: 15,189 current-event, 7,127 recent-window, and 5,323 historical-memory examples. Each sample has an explicit observation cutoff. The training, validation, and test splits contain 19,641, 4,209, and 3,789 samples, respectively, and are match-disjoint.

SoccerNet provides human-annotated action timestamps but not event intervals. We use deterministic football rules based on action categories and temporal order to organize consecutive clips into rule-derived operational events. Action-triggered event starts form positive operational-transition targets, while within-event clips form negatives. To bound the duration of a state, an active event is closed after 24 s and the next clip initializes a new state. This duration safeguard limits state length and is not treated as a positive operational transition.

Event-focused MatchTime descriptions are aligned to operational events by match, half, temporal proximity, and action compatibility, with each description assigned to at most one event. The aligned text and deterministic time, action, and event-type metadata form data-side reference records for three commentary tracks: current-event targets rewrite an aligned description as post-event commentary; recent-window targets use only video and completed local events available before the observation cutoff; and historical-memory targets additionally associate earlier eligible events from the same match and half. Data-side reference records are used only to construct supervision, whereas runtime event records are generated from completed event memory. Automated checks ensure that all conditioning information is available before the observation cutoff and retain the corresponding source-event identifiers.

Evaluation Design. Common-anchor evaluation fixes the task type, observation cutoff, and reference emission time, and discloses current-event alignment and record-readiness interventions. Raw-video evaluation additionally includes video decoding, online visual encoding, and runtime prediction. Mechanism experiments distinguish retrained structural variants from inference-time interventions.

Baselines and Metrics. Strict comparisons share the test split, cutoff, output anchor, input scope, and decoding budget; results that cannot satisfy this contract are reported as compatibility comparisons. We report track-wise BLEU-4, CIDEr [20], and BERTScore-F1 [28]. We compute BERTScore-F1 for all methods using RoBERTa-large at layer 17. Memory-to-record representation experiments additionally report token-level F1, METEOR, and ROUGE-L. Raw-video efficiency is measured by the 95th-percentile real-time factor (RTF) of the per-minute workload.

Method	Frames	Stream	Soccer FT	Current-event			Recent-window			Historical-memory		
				CIDEr	B@4	BS	CIDEr	B@4	BS	CIDEr	B@4	BS
Proprietary MLLMs												
GPT-5.4	16			5.93	0.0215	0.8586	14.28	0.0585	<u>0.8784</u>	<u>7.75</u>	<u>0.0405</u>	<u>0.8723</u>
Qwen3.6-Max-Preview	16			1.00	0.0092	<u>0.8613</u>	3.23	0.0131	0.8576	3.95	0.0194	0.8655
Streaming VLMs												
StreamingVLM (ICLR2026)	2 FPS	✓		0.7351	0.0018	0.4337	0.0532	0.0015	0.4398	0.0313	0.0000	0.4464
TimeChat-Online (ACM MM2025)	2 FPS	✓		1.2771	0.0000	0.4042	0.9740	0.0000	0.4685	1.0078	0.0000	0.4494
VideoLLM-online (CVPR2024)	2 FPS	✓		0.1595	0.0000	0.2345	0.0443	0.0000	0.2008	0.0477	0.0000	0.2393
Soccer-Specific Models												
UniSoccer (CVPR2025)	30		✓	30.97	0.2719	0.6782	27.85	0.0730	0.6510	5.69	0.0317	0.5679
SoccerMaster (CVPR2026)	30		✓	<u>33.35</u>	0.2650	0.6827	23.46	0.0569	0.5984	7.37	0.0273	0.5418
StreamSoccer (Ours)	2 FPS	✓	✓	38.62	0.2929	0.9734	<u>23.96</u>	<u>0.0652</u>	0.9612	17.39	0.0451	0.9636

Table 1: Commentary quality at shared causal output anchors. We report CIDEr, BLEU-4 (B@4), and BERTScore-F1 (BS) for current-event, recent-window, and historical-memory commentary; higher is better. CIDEr uses the $100\times$ scale. Bold and underlined values denote the best and second-best result for each metric within each track.

5.2 Commentary Quality

Table 1 compares inference at common reference anchors.

The proprietary MLLMs receive 16 track-specific sparse RGB frames per anchor. StreamingVLM, TimeChat-Online, and VideoLLM-online process the timelines at 2 FPS, with metrics conditioned on valid outputs. UniSoccer and SoccerMaster are retrained on match-disjoint current-event and recent-window data and receive 30 causal frames; their historical rows are test-only sparse-history diagnostics without historical-memory training. StreamSoccer uses reference-anchored replay over 126 half streams, with oracle operational-event closures, current-event alignment, label-assisted action/type metadata, and record-readiness interventions.

StreamSoccer obtains the highest reported CIDEr on current-event and historical-memory commentary and ranks second on recent-window commentary, behind UniSoccer. B@4 shows the same ordering on current-event and recent-window commentary, while StreamSoccer also ranks first on the historical-memory track. Recent multi-event aggregation remains its main relative weakness. The historical rows of the soccer-specific baselines use untrained sparse-frame histories and therefore serve as compatibility comparisons.

5.3 Streaming Efficiency and Long-History Scaling

We further examine whether the computational cost of the complete raw-video path grows with the observed match history. Experiments measure the 95th-percentile real-time factor (RTF) of the per-minute workload over 174 runs on 58 source-clean matches. All methods receive the same 2 FPS input; an RTF below 1 indicates faster-than-real-time processing.

As shown in Figure 3, StreamSoccer maintains an RTF p95 of approximately 0.10–0.22 throughout a 90-minute match, without sustained growth as more match history is observed. StreamingVLM remains at approximately 0.31–0.47. VideoLLM-online becomes increasingly expensive as its con-




Figure 3: Raw per-minute RTF p95 over 58 source-clean matches and 174 runs (lower is better). TimeChat-Online stops at its context limit.

text grows, approaching or exceeding the real-time threshold late in the match, whereas TimeChat-Online reaches its context limit at approximately 55 minutes. These results show that StreamSoccer maintains stable, faster-than-real-time processing as the observed match history grows.

5.4 Validating Event Memory as an Intermediate Representation

To evaluate event memory as an intermediate representation for event-record caption generation, we compare recurrent event memory with operational-event pooling and fixed-time pooling under matched visual inputs and language readout. Operational-event pooling shares the same event support as recurrent memory, providing a matched comparison of recurrent state formation, while fixed-time pooling serves as a temporal-window baseline.

Table 2 shows a consistent ordering across all caption metrics. Recurrent event memory improves Tok-F1 by 0.0533 over fixed-time pooling and by 0.0351 over operational-event

Representation	Tok-F1	B@4	METEOR	ROUGE-L	CIDEr
Recurrent memory	0.2642	0.2777	0.2358	0.4335	37.40
Event pooling	0.2290	0.2556	0.2192	0.3986	22.20
Fixed-time pooling	0.2108	0.2462	0.2104	0.3916	15.72

Table 2: Matched projector-only comparison for memory-to-record consolidation.

pooling, with CIDEr gains of 21.68 and 15.21, respectively. Operational-event pooling also improves Tok-F1 by 0.0182 over fixed-time pooling, showing the benefit of organizing visual support around operational events rather than a fixed trailing window. With the event support held fixed, recurrent event memory provides a further consistent gain, indicating that recurrent integration of event evolution forms a more useful intermediate representation for downstream generation.




Figure 4: Normalized commentary-conditioned temporal relevance from a frozen offline VLM over a continuous five-minute match interval. Responses persist across adjacent windows and shift among action concepts as play evolves.

Memory-Scope Analysis. We compare task adaptation and memory scope in two blocks. Direct Qwen3-VL reads causal 30/180/180 s video windows; Qwen3-VL Video-SFT retains this interface and is adapted on the three-track training set. Three separately trained StreamSoccer variants then use current event memory only, add the local event-memory buffer, or further add historical event records. The direct-video and event-memory blocks assess task adaptation and memory scope, respectively.

Variant	Current	Recent	Historical
Direct Qwen3-VL	4.06	2.46	3.08
Qwen3-VL Video-SFT	27.73	12.98	11.24
<i>StreamSoccer variants</i>			
Current memory only	33.03	15.06	13.22
+ Local event-memory buffer	<u>38.57</u>	<u>17.96</u>	<u>17.22</u>
+ Historical records (Full)	38.62	23.96	17.39

Table 3: Track-wise CIDEr for direct-video adaptation and event-memory scope.

Video-SFT raises CIDEr from 4.06/2.46/3.08 to 27.73/12.98/11.24 across the three tracks, showing the

importance of task adaptation. Within the event-memory block, adding the local event-memory buffer improves all three tracks over current memory alone. The full configuration further raises the scores to 38.62/23.96/17.39 and performs best on every track, with the largest additional gain on recent-window commentary. Together, the three contexts support commentary over different temporal ranges.




Figure 5: Historical-memory commentary at a common causal anchor. The masked future stream is unobserved.

5.5 Qualitative Case Analysis

Figure 5 compares historical-memory commentary at a common causal anchor containing both earlier set-piece context and an ongoing attacking sequence.

StreamingVLM produces a repeated goal claim and fails to organize the current play, while TimeChat-Online generates descriptions inconsistent with the match time and score. StreamSoccer instead connects the ongoing pressure with earlier set-piece events and more closely matches the reference. By retaining current, recent, and historical event contexts beyond a finite video window, the layered memory reduces abrupt context loss as the window advances and supports more coherent commentary.

6 Conclusion

We introduced StreamSoccer, an event-driven system for causal streaming soccer commentary. It maintains fixed-budget active event memory, preserves recent completed events, and consolidates them into retrievable event records to support current-event, recent-window, and historical-memory commentary. At common output anchors, StreamSoccer achieves the highest reported CIDEr on the current-event and historical-memory tracks, while its raw-video RTF remains below the

real-time threshold throughout full matches. Memory-scope analysis further shows that recent completed events improve all three commentary tracks and that the full configuration performs best overall. Together with the representation comparison and long-history efficiency results, these findings support event memory as a compact intermediate representation for long streaming soccer video.

References

- [1] Bai, S.; Cai, Y.; Chen, R.; Chen, K.; Chen, X.; Cheng, Z.; Deng, L.; Ding, W.; Gao, C.; Ge, C.; Ge, W.; Guo, Z.; Huang, Q.; Huang, J.; Huang, F.; Hui, B.; Jiang, S.; Li, Z.; Li, M.; Li, M.; Li, K.; Lin, Z.; Lin, J.; Liu, X.; Liu, J.; Liu, C.; Liu, Y.; Liu, D.; Liu, S.; Lu, D.; Luo, R.; Lv, C.; Men, R.; Meng, L.; Ren, X.; Ren, X.; Song, S.; Sun, Y.; Tang, J.; Tu, J.; Wan, J.; Wang, P.; Wang, P.; Wang, Q.; Wang, Y.; Xie, T.; Xu, Y.; Xu, H.; Xu, J.; Yang, Z.; Yang, M.; Yang, J.; Yang, A.; Yu, B.; Zhang, F.; Zhang, H.; Zhang, X.; Zheng, B.; Zhong, H.; Zhou, J.; Zhou, F.; Zhou, J.; Zhu, Y.; and Zhu, K. 2025. Qwen3-VL Technical Report. arXiv:2511.21631.
- [2] Chen, J.; Lv, Z.; Wu, S.; Lin, K. Q.; Song, C.; Gao, D.; Liu, J.-W.; Gao, Z.; Mao, D.; and Shou, M. Z. 2024. VideoLLM-online: Online Video Large Language Model for Streaming Video. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 18407–18418.
- [3] Deliège, A.; Cioppa, A.; Giancola, S.; Seikavandi, M. J.; Dueholm, J. V.; Nasrollahi, K.; Ghanem, B.; Moeslund, T. B.; and Van Droogenbroeck, M. 2021. SoccerNet-v2: A Dataset and Benchmarks for Holistic Understanding of Broadcast Soccer Videos. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, 4503–4514.
- [4] Giancola, S.; Amine, M.; Dghaily, T.; and Ghanem, B. 2018. SoccerNet: A Scalable Dataset for Action Spotting in Soccer Videos. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, 1711–1721.
- [5] He, B.; Li, H.; Jang, Y. K.; Jia, M.; Cao, X.; Shah, A.; Shrivastava, A.; and Lim, S.-N. 2024. MA-LMM: Memory-Augmented Large Multimodal Model for Long-Term Video Understanding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 13504–13514.
- [6] Hu, E. J.; Shen, Y.; Wallis, P.; Allen-Zhu, Z.; Li, Y.; Wang, S.; Wang, L.; and Chen, W. 2022. LoRA: Low-Rank Adaptation of Large Language Models. In *International Conference on Learning Representations*.
- [7] Jeong, S.; Kim, K.; Baek, J.; and Hwang, S. J. 2025. VideoRAG: Retrieval-Augmented Generation over Video Corpus. In *Findings of the Association for Computational Linguistics: ACL 2025*, 21278–21298.
- [8] Jin, Z.; Qin, X.; Zhou, S.; Yun, K.; and Jia, J. 2026. Towards Automatic Soccer Commentary Generation with Knowledge-Enhanced Visual Reasoning. Accepted at IEEE International Conference on Multimedia and Expo, arXiv:2604.00057.
- [9] Lei, J.; Wang, L.; Shen, Y.; Yu, D.; Berg, T.; and Bansal, M. 2020. MART: Memory-Augmented Recurrent Transformer for Coherent Video Paragraph Captioning. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, 2603–2614.
- [10] Li, X.; He, Y.; Zu, S.; Li, Z.; Shi, T.; Xie, Y.; and Zhang, K. 2025. Multi-Modal Large Language Model with RAG Strategies in Soccer Commentary Generation. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, 6197–6206.
- [11] Lin, T.-Y.; Goyal, P.; Girshick, R.; He, K.; and Dollár, P. 2017. Focal Loss for Dense Object Detection. In *Proceedings of the IEEE International Conference on Computer Vision*, 2999–3007.
- [12] Mkhallati, H.; Cioppa, A.; Giancola, S.; Ghanem, B.; and Van Droogenbroeck, M. 2023. SoccerNet-Caption: Dense Video Captioning for Soccer Broadcasts Commentaries. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, 5074–5085.
- [13] Qi, J.; Yu, J.; Tu, T.; Gao, K.; Xu, Y.; Guan, X.; Wang, X.; Xu, B.; Hou, L.; Li, J.; and Tang, J. 2023. GOAL: A Challenging Knowledge-Grounded Video Captioning Benchmark for Real-Time Soccer Commentary Generation. In *Proceedings of the 32nd ACM International Conference on Information and Knowledge Management*, 5391–5395.
- [14] Qian, R.; Dong, X.; Zhang, P.; Zang, Y.; Ding, S.; Lin, D.; and Wang, J. 2024. Streaming Long Video Understanding with Large Language Models. In *Advances in Neural Information Processing Systems*, volume 37, 119336–119360.
- [15] Rao, J.; Wu, H.; Jiang, H.; Zhang, Y.; Wang, Y.; and Xie, W. 2025. Towards Universal Soccer Video Understanding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 8384–8394.
- [16] Rao, J.; Wu, H.; Liu, C.; Wang, Y.; and Xie, W. 2024. MatchTime: Towards Automatic Soccer Game Commentary Generation. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, 1671–1685.
- [17] Ridnik, T.; Ben-Baruch, E.; Zamir, N.; Noy, A.; Friedman, I.; Protter, M.; and Zelnik-Manor, L. 2021. Asymmetric Loss for Multi-Label Classification. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 82–91.
- [18] Song, E.; Chai, W.; Wang, G.; Zhang, Y.; Zhou, H.; Wu, F.; Chi, H.; Guo, X.; Ye, T.; Zhang, Y.; Lu, Y.; Hwang, J.-N.; and Wang, G. 2024. MovieChat: From Dense Token to Sparse Memory for Long Video Understanding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 18221–18232.
- [19] Sun, H.; Kertkeidkachorn, N.; and Shirai, K. 2026. Visual and Memory-Augmented Soccer Commentary Generation. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics*, 10614–10629.
- [20] Vedantam, R.; Zitnick, C. L.; and Parikh, D. 2015. CIDEr: Consensus-Based Image Description Evaluation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 4566–4575.

- [21] Wang, H.; Feng, B.; Lai, Z.; Xu, M.; Li, S.; Ge, W.; Dehghan, A.; Cao, M.; and Huang, P. 2025. StreamBridge: Turning Your Offline Video Large Language Model into a Proactive Streaming Assistant. In *Advances in Neural Information Processing Systems*, volume 38, 132332–132359.
- [22] Xu, R.; Xiao, G.; Chen, Y.; He, L.; Lu, Y.; and Han, S. 2026. StreamingVLM: Real-Time Understanding for Infinite Video Streams. *International Conference on Learning Representations*, arXiv:2510.09608.
- [23] Yan, Y.; Xu, J.; Di, S.; Liu, Y.; Shi, Y.; Chen, Q.; Li, Z.; Huang, Y.; and Xie, W. 2025. Learning Streaming Video Representation via Multitask Training. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 9900–9912.
- [24] Yang, H.; Rao, J.; Wu, H.; and Xie, W. 2026. SoccerMaster: A Vision Foundation Model for Soccer Understanding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 21549–21560.
- [25] Yao, L.; Li, Y.; Wei, Y.; Li, L.; Ren, S.; Liu, Y.; Ouyang, K.; Wang, L.; Li, S.; Li, S.; Kong, L.; Liu, Q.; Zhang, Y.; and Sun, X. 2025. TimeChat-Online: 80% Visual Tokens Are Naturally Redundant in Streaming Videos. In *Proceedings of the 33rd ACM International Conference on Multimedia*, 10807–10816.
- [26] You, L.; Huang, W.; Xie, X.; Wei, X.; Li, B.; Lin, S.; Li, Y.; and Wang, C. 2025. TimeSoccer: An End-to-End Multimodal Large Language Model for Soccer Commentary Generation. In *Proceedings of the 33rd ACM International Conference on Multimedia*, 3418–3427.
- [27] Zhang, H.; Wang, Y.; Tang, Y.; Liu, Y.; Feng, J.; and Jin, X. 2025. Flash-VStream: Efficient Real-Time Understanding for Long Video Streams. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 21059–21069.
- [28] Zhang, T.; Kishore, V.; Wu, F.; Weinberger, K. Q.; and Artzi, Y. 2020. BERTScore: Evaluating Text Generation with BERT. In *International Conference on Learning Representations*.

A Evidence and Evaluation Contract

The paper uses separate protocols for controlled commentary quality, streaming state execution, and raw-video efficiency. Keeping these protocols separate prevents a controlled output-anchor experiment from being interpreted as an evaluation of autonomous speaking decisions.

A.1 Claim–Evidence Map

Table A.1 records what each headline experiment supports and, equally importantly, what it does not test.

A.2 Evaluation Protocol Matrix

We distinguish four evaluation settings in Table A.2. *Sample-level conditional evaluation* reads a preconstructed causal sample and is used for model-development diagnostics. *Reference-anchored streaming replay* advances persistent state over each half but takes the output anchor and task from the test row. *Free-scheduler streaming replay* advances the same type of state while allowing the deterministic rule-assisted scheduler to choose a commentary mode or silence. *Raw-video scaling* includes video decoding and online visual encoding and measures system cost as the visible history grows.

The frozen reference-anchored run behind the StreamSoccer row of Table 1 uses checkpoint step 1,000. It processes 86,145 causal clips from 63 test matches (126 half streams), emits all 3,789 test anchors, and constructs 20,689 event-record traces. Inference uses cached Qwen tokens, oracle operational closures, rule memory gating, embedding-based top-3 retrieval, same-half eligibility, and a 90-s minimum historical gap. Current-event identity alignment and record-readiness intervention are evaluation controls. The result establishes controlled streaming quality, not free-scheduler system quality.

A.3 Baseline and Statistical Contract

The external rows in the main table have different native interfaces. Table A.3 makes the consequential differences explicit. We call a comparison *strict* only when the test split, causal cutoff, output anchor, input scope, and decoding budget can be aligned. A row that preserves the method’s native interface but cannot meet all of these conditions is a *compatibility comparison*; it is retained for context and does not constitute a controlled architectural ranking.

CIDEr is reported on the $100\times$ scale. BERTScore-F1 uses the shared RoBERTa-large scorer at layer 17, and all generated-output rows are rescored by the same evaluation code. Uncertainty is clustered by match because anchors from the same match are not independent. For a paired comparison we re-sample matches with replacement and retain all anchors belonging to the sampled matches. When only one training seed is available, the resulting confidence interval quantifies test-set variation, not training variance; we report the checkpoint and seed rather than implying multi-seed stability. The frozen

representation comparison in Appendix D uses 10,000 paired match-cluster bootstrap replicates.

A.4 Metrics and Interpretation Boundaries

Table A.4 groups the reported metrics by the question they answer. Text-reference similarity, retrieval, continuous execution, and raw-video efficiency are evaluated separately; a strong value in one group does not substitute for evidence in another.

Paper claim	Primary evidence	Supported interpretation	Outside the experiment’s scope
Commentary quality at shared causal anchors	Reference-anchored streaming replay and common-anchor base-lines	Conditional generation quality at fixed legal output anchors for the three commentary tracks	Free speaking-time selection, naturally available event records, or a purely visual front end
Availability-aware semantic preference at shared anchors	Frozen four-way blinded LLM audit against silver references	Reference-conditioned judge preference over the fixed 3,789-anchor population, including missing-output penalties	Human preference, claim-level factuality, historical-record attribution, free speaking-time selection, or judge-model generalization
Event memory is a useful intermediate representation	Matched recurrent-memory, operational-event-pooling, and fixed-time-pooling comparison	Downstream event-record caption decodability under a matched language readout and adaptation budget	Natural event discovery, full record factuality, or equal up-stream training cost
Accessible memory scope changes track-specific commentary quality	Separately trained memory-scope variants in the main text	Observed differences between configurations with different accessible memory scopes and training targets	Statistical significance of every incremental gain or a causal decomposition of every component targets
Long-history processing remains efficient	Raw-video per-minute RTF scaling over full matches	Growth of end-to-end processing workload as more match history is observed	Scheduler quality or the response latency of an individual commentary utterance

Table A.1: Claim–evidence map for the headline results. Each row deliberately limits the interpretation to the corresponding evaluation protocol.

Setting	Visual input and state	Output time / task	Event closure	Action/type metadata	Current-event alignment	Record readiness	Main use	
Sample-level conditional	Preconstructed or cached sample; no full-half replay required	Given by sample	Controlled or materialized	Controlled fields	Given by sample IDs	Preconstructed evidence context	Conditional generation and matched ablations	
Reference-anchored replay	Continuous Qwen tokens at 2 FPS; state persists within each half	cached and task type	Reference anchor and task type	Oracle operational closures	Label-assisted action/type fields	Just-completed event aligned to the current-event target	Historical anchors deterministically drain pending caption jobs before retrieval	Main-paper common-anchor commentary quality
Free-scheduler replay	Continuous Qwen tokens; state persists within each half	cached	Rule-assisted scheduler	Predicted transition plus duration rollover	Current audited replay is label-assisted	None from reference targets	Natural asynchronous readiness	Cadence, mode counts, delay, duplicates, and readiness audit
Raw-video scaling	Raw video decoding, online visual encoding, persistent state	Fixed evaluation workload; separate from native free scheduling	Predicted transition plus duration rollover	Predicted front-end metadata	None from reference targets	Runtime-managed records	Per-minute RTF, VRAM, coverage, and history scaling	

Table A.2: Evaluation protocol matrix. Table 1 uses the reference-anchored row. It evaluates commentary quality under controlled anchors; it does not evaluate the speaking scheduler or natural record readiness.

Method family	Input	Stream state	Soccer FT	Anchor/interface	Coverage treatment	Contract
Proprietary MLLMs	16 frames	No	No	Track-specific causal sparse frames at each anchor	One request per test anchor; invalid calls must be reported	Compatibility
General streaming VLMs	2 FPS	Yes	No	Continuous causal timeline with anchored scoring	Metrics are conditioned on valid outputs; context-limit and invalid-output coverage are disclosed separately	Compatibility
Soccer-specific models	30 frames	No	Yes	Causal sparse frames at each anchor	Retrained current/recent rows use the match-disjoint split; historical rows are test-only sparse-history diagnostics	Current/recent stricter; historical compatibility
StreamSoccer	2 FPS	Yes	Yes	Reference-anchored continuous replay	3,789/3,789 anchors emitted; interventions disclosed in Table A.2	Controlled reference replay

Table A.3: Protocol cards for the method families in the main commentary-quality table. FT denotes task-specific fine-tuning.

Metric	Definition	Interpretation boundary
Token F1	Harmonic mean of token-level precision and recall against the reference	Direct lexical-content overlap; insensitive to unsupported facts expressed with overlapping words
BLEU-4	Modified 1- to 4-gram precision with a brevity penalty	Local phrase agreement; brittle to valid paraphrases and not a factuality metric
METEOR	Unigram alignment combining precision, recall, and an ordering penalty	More recall-sensitive than BLEU, but still reference-dependent
ROUGE-L	Longest-common-subsequence overlap between prediction and reference	Sequence-level content coverage and ordering, not historical-evidence use
CIDEr	TF-IDF-weighted n -gram agreement; displayed on the $100\times$ scale	Main caption-style content score; scales and scorer versions must not be mixed
BERTScore-F1	Contextual-token similarity under the shared RoBERTa-large layer-17 scorer	Semantic reference similarity; does not establish factual correctness
Valid coverage	Non-empty valid outputs divided by requested output anchors	Must accompany quality scores so failed requests are not silently removed
Strict blind win rate	Fraction of the fixed test population for which an anonymized candidate is selected under the fixed judge configuration; NO_RESPONSE cannot win	Availability-aware preference against one silver reference under one judge, not human-verified semantic correctness
R@ k / MRR	Fraction of eligible positives in the top k , and mean reciprocal positive rank	Retrieval ranking on the declared eligible population; does not show that generation used the record
Retrieval-ready rate	Decisions at which at least one eligible, fully inserted event record is available	Runtime record availability; distinct from retrieval correctness
RTF	Processing wall time divided by represented video duration	Values below one are faster than real time; cached-replay and raw-video RTFs are not interchangeable
Latency / VRAM	Request p50/p95 wall time and peak process memory	Tail response and resource cost under the stated timing boundary and valid-run population
Clustered 95% CI	Bootstrap interval obtained by resampling matches and retaining their anchors	Test-population variation; with one training seed it is not training-seed uncertainty

Table A.4: Metric definitions and permitted interpretations. No automatic reference-similarity metric is treated as a direct factuality measure.

B Data Construction and Operational-Event Semantics

B.1 Sources, Funnel, and Match-Disjoint Splits

We use SoccerNet full-match videos and action timestamps [3, 4] to construct the causal video stream and operational events. MatchTime commentary [16] provides the text used for the three-track commentary data. SoccerNet-Caption [12] supplies the legacy memory-to-record representation benchmark used in Appendix D. The roles and frozen data funnel are shown in Table B.1.

The 422 MatchTime matches are split at match level using the sorted match ID: 70% train, 15% validation, and 15% test. Table B.2 shows the resulting counts. The canonical audit finds no match or sample-ID overlap across splits. Every sample

Data level	Count
SoccerNet matches / half streams	500 / 1,000
Non-overlapping 4-s clips	685,903
Rule-derived operational events	166,419
MatchTime matches used	422
Caption-aligned operational events	15,189
Current-event samples	15,189
Recent-window samples	7,127
Historical-memory samples	5,323
Total three-track samples	27,639

Table B.1: Frozen data funnel. Commentary alignment covers a salient subset of all operational events rather than a uniform sample of match states.

Split	Matches	Current	Recent	Historical	Total
Train	295	10,853	5,013	3,775	19,641
Validation	64	2,286	1,105	818	4,209
Test	63	2,050	1,009	730	3,789
Total	422	15,189	7,127	5,323	27,639

Table B.2: Match-disjoint three-track split.

stores a causal cutoff and provenance event IDs; automated checks reject video, local-event, or historical references that form after that cutoff.

B.2 Operational Eventization and Boundary Timeline

Each half is partitioned into non-overlapping four-second clips. For data assignment, clip C_t uses the half-open interval $[s_t, e_t)$, so an action timestamp a belongs to C_t iff $s_t \leq a < e_t$. The causal model may use C_t only after $e_t \leq \tau_t$. At 2 FPS, a full clip contains eight sampled frames.

Operational eventization groups the SoccerNet action timestamps using deterministic football rules. Set pieces and administrative actions can start a new event. Finish, stoppage, administrative, and eligible clearance actions can close the active event after the triggering clip has been included. A maximum duration $D_{\max} = 24$ s closes an overly long state, and the last active state is deterministically closed at half end. These are operational units for memory control; they are not manually segmented natural events.

Table B.3 gives the exact action groups used by the eventizer. When a clip contains several actions, a fixed priority resolves the primary action: goals and shots precede penalties and cards, followed by fouls/offside, set pieces, clearance and ball-out actions, substitutions, kick-off, and end-of-period control labels. A card that coincides with a stoppage is retained in the stoppage episode rather than forcing a redundant start.

Here, REQUESTSNEWEVENT covers set pieces and administration/discipline actions except a card coincident with an active stoppage, while HASTERMINALACTION covers finish, stoppage, administration/discipline, and clearance without an immediate set-piece, finish, or stoppage follow-up. Annotated

Group	SoccerNet actions	Operational role
Set piece	Corner, Throw-in, Direct free-kick, Indirect free-kick, Penalty, Kick-off	Closes an existing state before C_t and starts a new event at C_t
Finish	Goal, Shots on target, Shots off target	Included in the active event, then closes it as <code>terminal_finish</code>
Stoppage	Ball out of play, Foul, Offside	Included in the active event, then closes it as <code>terminal_stoppage</code>
Defensive resolution	Clearance	Closes after C_t only when the next clip contains no set piece, finish, or stoppage follow-up
Administration / discipline	Substitution, Yellow card, Red card, Yellow-to-red card, End of period	Starts a new event unless a card coincides with an active stoppage; closes after inclusion
Open play	No action from the groups above	Continues the active state; its type is upgraded when the first meaningful action arrives

Table B.3: Deterministic action groups and their operational-event effects. These rules organize memory lifecycles; they do not define natural event ground truth.

next-clip actions are used only to construct offline episode labels and are not model inputs. A start-triggered clip belongs to the new event; a terminal-action clip remains in the event that it closes.

The implementation places the transition label on the first clip of the new event. Figure B.1 shows the ownership convention as a flow. At a reset, the previous state is exported before the arriving clip initializes the next event. A terminal-action clip remains in the event it closes, and current-event supervision observes only the completed state.

The transition head predicts b_t , the operational-transition indicator. Training supplies a binary operational-transition label and masks duration-rollover positions from that loss. ρ_t is the deterministic duration safeguard, and the final reset is $r_t = b_t \vee \rho_t$ (with deterministic stream-end closure handled separately). Thus transition, rollover, and final reset are not interchangeable labels.

The frozen eventizer produces 166,419 operational events with mean duration 16.49 s and median duration 20 s. A total of 66,941 events (40.2%) close by the maximum-duration safeguard. The large rollover fraction is why our claims are consistently phrased in terms of *rule-derived operational events*, not natural semantic-boundary annotations.

B.3 Three-Track Supervision and Quality Control

MatchTime commentary descriptions are aligned to operational events using match, half, temporal proximity, and action compatibility, and each description is assigned to at most one event. The aligned description and deterministic time, action, event-type, and match-state fields form a data-side reference record. This record is used to construct supervision; at runtime, historical records are generated from completed event memory instead.

Candidate generation first restricts captions to the same

match and half. A caption is eligible when its timestamp lies inside the event interval or no more than 15 s outside it. A second action-anchored path admits a caption up to 30 s from a compatible event action, accommodating delayed goal or shot commentary while still requiring semantic action agreement. Candidates are ranked deterministically by text validity, action compatibility, importance, absence of multi-event ambiguity, availability and distance of an action anchor, membership in or distance to the event window, annotation-label availability, and finally caption ID. Semantically anchored high-confidence candidates are assigned first across a match. In the frozen dataset, a caption ID is consumed after assignment, so one caption supervises at most one canonical event. Event IDs, action sets, timestamps, match state, and split membership are fixed before any language rewriting.

Automated quality control checks causal validity, match/half consistency, event-ID existence, one-to-one current-caption assignment, duplicate sample IDs, and split isolation. Text transformations preserve deterministic team, time, action, and score fields outside unconstrained language generation. The frozen automatic audit establishes structural consistency and traceability; it does not constitute human verification of every generated or rewritten sentence.

C Reproducible Implementation

C.1 Architecture Specification

The pretrained backbone is Qwen3-VL-8B-Instruct [1]. The visual encoder and base language-model weights are frozen. Table C.1 lists the fixed dimensions of the reported configuration. The Clip Event Adapter produces $K_m = 9$ clip-level event tokens (one special token and eight slots). The active memory uses the same token budget, and the memory-to-language projector produces $K_p = 8$ soft prefix tokens.

The transition head compares the previous active state with

Algorithm B.1 Rule-derived operational eventization for one half

Require: temporally ordered clips $C_1, \dots, C_T$, assigned action timestamps, maximum duration $D_{\max}$

Ensure: ordered operational-event episodes

```
1:  $active \leftarrow \emptyset$ 
2: for each clip  $C_t$  in temporal order do
3:    $actions \leftarrow \text{ASSIGNEDACTIONS}(C_t)$ 
4:    $next\_actions \leftarrow \text{ASSIGNEDACTIONS}(C_{t+1})$  if  $t < T$ , else  $\emptyset$ 
5:   if  $active = \emptyset$  then
6:      $active \leftarrow \text{STARTEVENT}(C_t)$ 
7:   else if  $\text{REQUESTSNEWEVENT}(C_t, actions)$  then
8:      $\text{CLOSEEVENT}(active)$ 
9:      $active \leftarrow \text{STARTEVENT}(C_t)$ 
10:  end if
11:   $\text{ATTACH}(active, C_t, actions)$ 
12:   $\text{UPDATEEVENTTYPE}(active, actions)$ 
13:  if  $\text{HASTERMINALACTION}(C_t, actions, next\_actions)$  then
14:     $\text{CLOSEEVENT}(active)$ 
15:     $active \leftarrow \emptyset$ 
16:  else if  $\text{DURATION}(active) \geq D_{\max}$  then
17:     $\text{CLOSEEVENT}(active, \text{max\_duration})$ 
18:     $active \leftarrow \emptyset$ 
19:  end if
20: end for
21: if  $active \neq \emptyset$  then
22:    $\text{CLOSEEVENT}(active, \text{half\_end})$ 
23: end if
```




Figure B.1: Boundary and clip-ownership convention. The data eventizer stores the transition label on the first clip of the new event. At reset, the pre-reset state is the completed memory and the current clip initializes the next state.

the current clip and receives action and age cues. On reset, the pre-reset state is exported as M_j^c . Completed event memories enter $\mathcal{B}_t$ immediately, while record caption generation and deterministic record assembly complete asynchronously before R_j becomes eligible for $\mathcal{L}_t$. Historical records are text supplied to the language prompt; they are not additional latent memory tokens.

C.2 Three-Stage Training

Table C.2 summarizes the configured training recipes. The pre-trained backbone tensors are loaded in bfloat16, and bfloat16 is enabled only on supported trainer paths. The frozen artifacts do not establish automatic mixed-precision execution for every trainer.

Track	Construction contract
Current-event	Context: just-completed M_j^c and causal match state. Target: one post-event commentary sentence. Provenance: current event ID, cutoff, and alignment metadata.
Recent-window	Context: active context and completed local events from the preceding 180 s. Target: one recent multi-event summary. Provenance: selected local event IDs and cutoff.
Historical-memory	Context: current/local context plus eligible earlier same-match, same-half records. Target: one sentence relating current play to earlier context. Provenance: historical source IDs, candidate set, and cutoff.

Table B.4: Construction contract for the three commentary tracks. Every conditioning item must exist no later than the stored causal cutoff.




Figure B.2: Causal commentary-data construction. Action timestamps and deterministic rules define operational-event intervals; MatchTime supplies the main three-track branch and SoccerNet-Caption the Stage 2 supervision branch. Candidate pools and split assignments are fixed before model-assisted rewriting, while selected evidence IDs are validated before the final match-disjoint manifests.

Component / symbol	Reported value	Specification
Backbone	Qwen3-VL-8B-Instruct	Frozen visual encoder and frozen base LLM
Visual/LLM hidden size d_v, d_l	4096 / 4096	Pretrained token spaces
Event-memory hidden size d_m	1024	Adapter, active memory, and completed event memory
Clip Event Adapter $\mathcal{A}$	2 layers, 8 heads	Cross-attention resampler; $K_m = 9$ output tokens
Memory update $\mathcal{U}$	2 layers, 8 heads	Memory-to-clip attention, self-attention, FFN, and per-token gate G_t
Memory initializer $\mathcal{I}$	1 layer	Initializes a new active state from E_t
Memory-to-language projector P_θ	2 layers, 8 heads	$K_p = 8$ projected soft-prefix tokens
Maximum active duration $D_{\max}$	24 s	Deterministic duration-rollover safeguard
LoRA for Stages 2–3	$r = 8, \alpha = 16$, dropout 0.05	Targets <code>q_proj</code> , <code>k_proj</code> , <code>v_proj</code> , and <code>o_proj</code>

Table C.1: Architecture specification for the paper-facing configuration.

Stage	Trainable path	Per-process batch / accumulation	Learning rate and schedule	Main objective / budget
1: streaming event memory	Clip Event Adapter, event-memory encoder, transition and auxiliary event heads	1 / 16	10^{-4} ; 500-step warmup; AdamW	Teacher-forced reset; up to 50k steps; weights 0.5 clip action, 1.0 transition, 1.0 completed-event action set, 0.3 event type
2: memory-to-record	Memory projector and language LoRA; base LLM frozen	1 / 16	Projector 10^{-4} , LoRA 10^{-5} ; 500-step warmup	Assistant caption tokens only; projector alignment then LoRA warmup and joint fitting; target length 192
3: multi-context commentary	Language LoRA, memory projector, route/local/retrieval auxiliary heads; Stage-1 memory cached/frozen in the reported run	2 / 8 per process	LoRA 2×10^{-5} , projector 3×10^{-5} ; 500-step warmup	Three-track response CE with auxiliary context losses; 10k configured budget; prompt/target/generation limits 2048/128/96

Table C.2: Three-stage training configuration. The displayed batch size is per process. Stage 3 uses prompt profile `paper_clean_v2` and seed 42 for the configured sampler.

The memory-cache Stage 3 training path requires an explicit Stage 1 checkpoint matching the materialized memory tokens and stores that frozen Stage 1 state in the Stage 3 checkpoint. The local step-1,000 replay artifact does not retain the training launch command or source-checkpoint hashes, so it does not independently verify Stage 2 checkpoint initialization for this run. Stage 3 uses a memory-cache curriculum: the first 5,000 configured steps use task-legal teacher-forced context, while the next 5,000 expose runtime-selected context, increasing the predicted-context ratio from 0.10 to 0.50 every 250 steps. The main-text quality result uses checkpoint step 1,000 and is evaluated by reference-anchored replay. This checkpoint lies in the teacher-forced phase and has not undergone the second-phase runtime-context exposure. The frozen replay protocol records the config, checkpoint, reference, and clip SHA-256 hashes together with the effective inference settings.

C.3 Inference, Retrieval, and Scheduler Parameters

Table C.3 separates memory/retrieval settings from the rule-assisted speaking policy. The scheduler is deterministic and is included to reproduce executed system behavior; it is not a learned policy and is not ranked as a separate scientific contribution.

Event closures enqueue caption jobs. The completed event

Runtime parameter	Value
Clip duration / sampling	4 s / 2 FPS
Local event-memory buffer horizon / maximum selected	180 s / 4 events
Historical retrieval	embedding top-3
Historical eligibility	same half, gap ≥ 90 s
Current-event cooldown	12 s
Recent-window tick / minimum events	120 s / 3
Window cooldown after event output	20 s
Historical cooldown / minimum records	180 s / 8
Historical score threshold	0.12
Scheduler priority	history > event > recent
Commentary decoding	deterministic, max 96 tokens
Record-caption decoding	deterministic, max 64 tokens

Table C.3: Default runtime and rule-assisted scheduler settings. The replay in Table 1 fixes output anchors and therefore does not evaluate these scheduler thresholds.

memory is immediately available, whereas an event record becomes historically retrievable only after caption generation, deterministic assembly, and insertion complete. The reference-anchored protocol deterministically drains pending jobs before retrieval at a historical anchor; the free-scheduler protocol does not. On the frozen main-table replay, eight parallel workers process 86,145 clips and insert 20,689 ready records. These workers partition independent half streams; state is not shared across halves.

Caption-queue and record-readiness timeline. At closure, the pre-reset state is exported as M_j^c , inserted immediately into $\mathcal{B}_t$, and enqueued as a caption job. It is not yet part of the event-record LTM $\mathcal{L}_t$. A drain projects the completed memory, generates the event-record caption c_j , attaches deterministic identity, time, action, type, and match-state fields, and inserts the resulting auditable record R_j when its generated caption is non-empty. Only a non-empty record whose insertion has completed is retrieval-eligible, so

$$\begin{aligned} M_j^c \in \mathcal{B}_t &\implies \text{caption job} \implies c_j \text{ ready,} \\ c_j \text{ ready} &\implies R_j \in \mathcal{L}_t. \end{aligned}$$

The cached-token replay batches at most four caption jobs. With its zero timer-wait setting, normal draining occurs when a batch fills, before a pending record would age out of the local event-memory buffer, or at stream end. A historical reference anchor additionally forces pending jobs to drain, which is the record-readiness intervention disclosed in Table A.2. Free-scheduler replay never drains because of a target anchor and therefore observes natural asynchronous readiness. The frozen raw-video deployment runtime interprets zero wait as immediate draining; its timing is reported separately from cached replay.

C.4 Artifact Provenance

Table C.4 provides stable labels for the results used in Appendices A–D. These labels identify result-specific frozen sources

ID	Result	Step / seed	Population
ANCHOR-S1K	Main-paper StreamSoccer commentary-quality row	1,000 / 42	63 matches; 3,789 anchors
REP-MEM	Recurrent event memory representation row	3,000 / 42	49 matches; 1,726 events
REP-EVENT	Operational-event pooling row	3,000 / 42	49 matches; 1,726 events
REP-FIXED	Fixed-time pooling row	3,000 / 42	49 matches; 1,726 events

Table C.4: Stable artifact labels for the protocol and representation results in Appendices A–D.

without exposing server absolute paths, usernames, or machine names.

Result-specific protocol and evaluation files, rather than this PDF, store the available content hashes, commands, check-point identities, and scorer settings. The frozen local records do not contain a unified release manifest or a code revision hash, so this appendix does not claim either. The three representation rows share the same implementation, data order, targets, projector initialization, optimization budget, and deterministic decoding settings; only the representation and its fitted checkpoint differ.

D Event-Memory Mechanism Evidence

D.1 Matched Intermediate-Representation Comparison

We directly compare three visual summaries for event-record caption generation. Recurrent event memory exports M_j^c when an operational event closes. Operational-event pooling averages clip-level event tokens over the same event support, isolating the value of recurrent state formation. Fixed-time pooling averages at most six clips from the trailing 24 s, providing a simple temporal-window control. Every row supplies a 9×1024 representation to an independently fitted but architecturally identical projector and language readout initialized from the same state.

All three methods are trained for 3,000 optimizer steps with global batch 16, giving 48,000 sampled-event exposures per row. Inference is deterministic with a 64-token generation limit. Recurrent memory exceeds operational-event pooling by 0.0351 Tok-F1 and fixed-time pooling by 0.0533; the paired intervals exclude zero. Operational-event pooling also exceeds fixed-time pooling by 0.0182 Tok-F1, with 95% interval [0.0114, 0.0252]. The event-pooling-versus-fixed-time contrast supports event-aligned temporal support, whereas the recurrent-memory-versus-event-pooling contrast supports learned state formation under matched event support.

This experiment is deliberately bounded. It uses one seed and the legacy 5,676-train/1,726-test protocol. The final checkpoints are compared at a fixed step rather than selected independently. The 1,726-event population is a legacy development/evaluation population rather than a never-observed

Representation	Tok-F1	B@4	METEOR	ROUGE-L	CIDEr
Recurrent memory	0.2642	0.2777	0.2358	0.4335	37.40
Event pooling	0.2290	0.2556	0.2192	0.3986	22.20
Fixed-time pooling	0.2108	0.2462	0.2104	0.3916	15.72

Table D.1: Matched memory-to-record representation comparison on 1,726 events from 49 matches. CIDEr uses the $100\times$ scale.

Tok-F1 difference	Mean	95% paired CI
Memory — event pooling	0.0351	[0.0259, 0.0444]
Memory — fixed pooling	0.0533	[0.0448, 0.0625]
Event pooling — fixed pooling	0.0182	[0.0114, 0.0252]

Table D.2: Tok-F1 differences from 10,000 paired match-cluster bootstrap replicates.

test set. The stored decoder drops some leading special-token fragments. A deterministic text-only sensitivity repair yields Tok-F1 values of 0.3093, 0.2705, and 0.2566 for recurrent memory, event pooling, and fixed-time pooling, respectively, and preserves the three-method ordering. Table D.1 reports the unrepaired frozen decoder outputs and supports matched-budget representation decodability only; it does not establish never-observed-test generalization, record factuality, or multi-seed training stability.

E Commentary Quality, Memory Scope, and Retrieval

E.1 Expanded Commentary-Quality Results

Table E.1 adds metrics and coverage for the StreamSoccer row in the main commentary-quality table. These values come from the same step-1,000 reference-anchored replay described in Appendix A; they do not constitute a separate free-scheduler evaluation. The replay emits one valid output at every one of the 3,789 test anchors, with no empty generations.

Retrieval traces provide a separate diagnostic of historical-record availability. Among 324 frozen retrieval-loss queries with positive supervision, embedding retrieval obtains $R@1 = 0.0741$, $R@3 = R@5 = 0.1327$, and $MRR = 0.1003$. In total, 371 anchored outputs contain retrieved records, and 43.92% of scheduler decisions are retrieval-ready under this controlled replay. These figures characterize the frozen retriever and do not establish that every retrieved record improves the generated commentary.

E.2 Blinded LLM Semantic Audit

We conduct a fixed-protocol four-way blinded audit over all 3,789 test anchors from 63 matches. For each anchor, a temperature-zero GPT-5.6-terra judge receives the silver reference, task description, and four candidate slots under a sample-specific deterministic permutation. Model identities are withheld from the prompt. A missing model output remains in its randomized slot as NO_RESPONSE and cannot

Track	N	Valid	Tok-F1	B@4	METEOR	ROUGE-L	CIDEr	BS
Current-event	2,050	100%	0.3234	0.2929	0.2487	0.4606	38.62	0.9734
Recent-window	1,009	100%	0.3499	0.0652	0.1518	0.2680	23.96	0.9612
Historical-memory	730	100%	0.2292	0.0451	0.1441	0.2146	17.39	0.9636

Table E.1: Additional StreamSoccer commentary metrics under reference-anchored replay. CIDEr uses the $100\times$ scale, BS denotes BERTScore-F1, and valid coverage is the fraction of requested anchors producing a non-empty output.

win; every strict win rate therefore uses the full 3,789-anchor population rather than a valid-output-only subset. All four models respond on 1,086 anchors, and at least one external model has NO_RESPONSE on the remaining 2,703 anchors. Response rate is reported beside preference so availability is visible alongside preference.

The judge selects StreamSoccer on 3,530 of 3,789 anchors, giving a strict win rate of 93.16% with match-clustered 95% CI [92.32%, 94.01%]. This ordering holds on each commentary track. The randomized label positions A–D receive 960, 971, 911, and 947 wins, respectively (25.34%, 25.63%, 24.04%, and 24.99% of judged anchors), so the result is not concentrated in one displayed position. Under the declared NO_RESPONSE-cannot-win protocol, StreamSoccer is the preferred available response against the silver reference across the fixed test population. This single-judge audit does not convert silver references into human preference labels or establish claim-level factual correctness. It ranks final outputs and does not determine whether a retrieved historical record supports or causes a historical-memory response.

E.3 Memory-Scope Analysis

The main text compares separately trained configurations with progressively broader accessible context. Table E.3 reports the locally verified CIDEr values alongside the protocol details in this appendix. These rows are configuration comparisons: changing memory scope also changes the context and objectives available during training, so the differences are not inference-only causal ablations of one checkpoint.

Each frozen evaluation summary contains 3,789 exact-ID matches and no unmatched outputs. The current-only and local event-memory buffer rows use their respective step-10,000 retrained checkpoints; the full row uses the selected step-1,000 full-model checkpoint. Relative to the current-only configuration, the local event-memory buffer configuration is higher by 5.54, 2.89, and 4.00 CIDEr on the current, recent, and historical tracks. Relative to the local event-memory buffer configuration, the full configuration is higher by 0.05, 6.01, and 0.17 CIDEr, respectively. These are configuration-level differences and do not isolate the causal effect of retrieved historical records on a particular generation.

E.4 Historical-Record Intervention

The retrieval diagnostics above measure whether the expected source is found, but they do not isolate whether the language

model uses a relevant record. We therefore perform a controlled intervention on historical-positive anchors while holding the checkpoint, current and local context, output anchor, and decoding settings fixed. The three non-empty arms each use three records, whereas the no-record arm removes the historical block.

Table E.4 reports the completed same-checkpoint intervention on a frozen set of 209 historical-memory anchors from 56 matches (79 half streams). Current/local latent context, output anchor, decoding, and the non-historical prompt are identical across arms; only the textual historical-record block changes. Every requested output is non-empty. The runtime-ranked arm bypasses the learned NULL decision solely to impose the same three-record input budget as the other non-empty arms; it is therefore a controlled retrieval diagnostic rather than the native online policy.

Injecting matched hard-negative records instead of no historical record raises per-anchor token-F1 by 0.1298 (match-clustered 95% CI [0.1157, 0.1441]). Oracle-ID injection raises it by 0.1393 over no historical record (95% CI [0.1253, 0.1538]). The paired intervals for runtime minus matched hard negatives ($\Delta = -0.0042$; 95% CI [-0.0222, 0.0137]) and oracle minus runtime ($\Delta = +0.0137$; 95% CI [-0.0043, 0.0318]) both include zero. Among the three non-empty arms with a fixed top-3 budget, the audit detects no automatic-metric advantage of runtime-ranked records over hard negatives and no automatic-metric gap to the oracle arm. The no-record contrasts show that adding a historical-record block changes the generator’s automatic overlap, but neither comparison establishes semantic use of relevant historical evidence or superior runtime retrieval.

Method	Current	Recent	Historical	Overall [95% CI]	Response
StreamSoccer	90.73	96.63	95.21	93.16 [92.32, 94.01]	100.00
StreamingVLM	8.68	3.37	4.38	6.44 [5.65, 7.21]	93.77
TimeChat-Online	0.59	0.00	0.41	0.40 [0.21, 0.61]	41.20
VideoLLM-online	0.00	0.00	0.00	0.00 [0.00, 0.00]	64.61

Table E.2: Strict win rate and response rate (%) in the frozen blinded LLM semantic audit. Current, recent, and historical contain 2,050, 1,009, and 730 anchors. Overall intervals use 10,000 match-cluster bootstrap replicates over 63 matches; missing outputs remain in the fixed denominator and cannot win.

Configuration	Current	Recent	Historical
Current memory only	33.03	15.06	13.22
+ local event-memory buffer	38.57	17.96	17.22
Full three-scope model	38.62	23.96	17.39

Table E.3: Verified CIDEr (100×) results for the separately trained memory-scope configurations.

Historical input	Records	Tok-F1	B@4	CIDEr	BS
No historical record	0	0.1426	0.0169	2.61	0.8543
Matched hard-negative top-3	3	0.2724	0.0726	30.92	0.8922
Runtime-ranked top-3 [†]	3	0.2682	0.0697	30.15	0.8906
Oracle-ID top-3 [‡]	3	0.2819	0.0841	37.96	0.8947

Table E.4: Automatic overlap diagnostics for the four-arm historical-record intervention. All arms use the identical 209-anchor population and have 100% valid coverage. CIDEr uses the 100× scale and BS denotes BERTScore-F1. [†]The learned NULL decision is bypassed only to fix the three-record budget. [‡]The positive record is placed at rank 1; this is a controlled oracle, not native online performance.

F Continuous Execution and Long-History Efficiency

F.1 Raw-Video Efficiency

The raw-video benchmark includes video decoding, online visual encoding, persistent state updates, and the fixed evaluation workload. It is separate from the native free-scheduler policy. Table F.1 reports p95 cumulative real-time factor (RTF) and the p95 peak VRAM at the last supported horizon.

StreamSoccer’s source-clean cohort contains 58 matches and 174 complete runs. The full-match RTF has median 0.1163 and p95 0.1221; a match-cluster bootstrap gives a median-RTF interval of [0.1137, 0.1183]. Whole-run peak VRAM has median 17,992 MiB and p95 17,996 MiB.

F.2 Record Readiness and Latency Breakdown

Table F.2 decomposes the measured StreamSoccer workload into auditable wall-time components. The entries are component-wise p95 RTFs computed over the full run; because their tails need not occur on the same request, their sum is not an isolated commentary latency.

Request-level end-to-end p95 latency is 2.467, 3.826, 3.855, and 3.801 s at T15, T30, T45, and T90, respectively. Record-caption work is asynchronous: completed event memory enters

the local event-memory buffer immediately, but a historical record becomes eligible only after captioning, assembly, and insertion.

To quantify the reference-triggered readiness intervention, we audit the 730 historical-memory anchors against an otherwise identical natural-queue shadow that disables anchor-triggered draining. Table F.3 reports the paired result. Reference anchors trigger pending caption consolidation at 594 anchors and drain 1,269 caption jobs. Every force-drained job corresponds to an event ending 4–76 s before its anchor, below the frozen 90-s historical eligibility gap. Consequently, reference-induced consolidation changes neither the eligible candidate set nor retrieved record identities, and it makes no positive historical evidence newly available at any audited anchor.

F.3 Free-Scheduler Execution Audit

We additionally audit a frozen free-scheduler replay to demonstrate that the state, caption queue, retrieval, and rule-assisted speaking path execute over complete half streams. This run uses checkpoint step 7,000, cached Qwen tokens, predicted operational transitions, embedding retrieval with same-half and 90-s-gap eligibility, and label-assisted action/type fields. It is an execution audit rather than a ranking of scheduler strategies.

Only 88 of 5,949 free-scheduler outputs occur within one second of a reference anchor. Text metrics on that small matched subset would therefore confound coverage and timing with language quality and are not used as commentary quality evidence.

G Auditable Cases and Failure Analysis

G.1 Case-Selection Protocol

The gallery uses only frozen test outputs. For each of the three commentary tracks, we retain the five pre-indexed candidates in the frozen case manifest; row i aligns candidate i from the current-event, recent-window, and historical-memory tracks. This fixed five-by-three ordering is recorded with the sample IDs in the frozen selection manifest and is not changed after rendering. Each card shows causal visual evidence, the reference, three external streaming VLM outputs, and the StreamSoccer output. The displayed text is a literal, compact

Method	T15	T30	T45	T90	Peak VRAM
StreamingVLM	0.274	0.285	0.291	0.285	17,072 MiB
TimeChat-Online*	0.138	0.231	0.322	–	77,603 MiB
VideoLLM-online	0.171	0.259	0.328	0.559	50,969 MiB
StreamSoccer	0.110	0.119	0.119	0.122	17,996 MiB

Table F.1: Raw-video efficiency. T15–T90 are p95 cumulative RTFs after 15, 30, 45, and 90 minutes of observed match time. Peak VRAM is the p95 value at the last valid horizon. *TimeChat-Online has no T90 value because its supported context ends before that horizon.

Component	p95 RTF
Raw video decode	0.0053
Visual encoding	0.0273
State update	0.0040
External generation wall	0.0201
Native generation wall	0.0692

Table F.2: Diagnostic component-wise p95 RTFs for the frozen raw-video StreamSoccer workload. Prompt construction, post-processing, and residual overhead are not separately tabulated.

Audit item	Value
Half streams / clips	126 / 86,145
Commentary outputs	5,949
Comments per minute	1.0505
Current / recent / historical	2,976 / 2,820 / 153
Caption jobs	20,658
Ready / empty captions	20,654 / 4
Exact / near-duplicate rate	0.000168 / 0
Event-to-comment delay	4.0 s
Total latency p50 / p95	2.357 / 4.209 s
Scheduler steps with retrieval-ready records	82,770 / 86,145 (96.08%)

Table F.4: Continuous free-scheduler execution audit. The scheduler is rule-assisted and the run retains label-assisted action/type metadata.

Audit item	Value
Historical-memory anchors	730
Anchors with pending jobs (forced / shadow)	594 / 603
Reference-triggered drain batches	594
Unique force-drained caption jobs	1,269
Eligible candidate set changed	0 / 730
Retrieved record identities changed	0 / 730
Positive-evidence readiness changed	0 / 730

Table F.3: Paired record-readiness audit of the 730 historical-memory anchors. The forced condition reproduces reference-anchored replay; the natural-queue shadow disables only anchor-triggered caption draining.

prefix of the frozen output; the full output and exact color-span audit remain in the associated case-card artifact.

G.2 Success and Failure Gallery

Figure G.1 lays out five aligned rows of examples. Columns correspond to current-event, recent-window, and historical-memory commentary, respectively; each card retains only visual evidence frames, with no timestamps or timeline. Light blue-grey identifies the reference, amber identifies external streaming VLMs, and blue identifies StreamSoccer. Red text marks wording heuristically flagged as unsupported, repetitive, malformed, or generic; green text marks StreamSoccer wording heuristically aligned to the reference event/evidence. These colors are qualitative reading aids rather than population-level error rates.

G.3 Mechanically Audited Failures

This subsection reports deterministic mechanical failures only. The fixed-protocol four-way audit in Appendix E.2 ranks the four permuted candidate slots, including NO_RESPONSE, and does not assign claim-level semantic-error labels; no population-level semantic-error frequency is reported. In the step-10,000 reference-anchored replay, 4 of 3,789 commentary outputs contain CJK or mojibake characters, including one output containing both repetition and encoding contamination. The same audit flags 38 of 20,689 generated caption records. In the step-7,000 free-scheduler replay, 4 of 20,658 record captions are empty; the commentary exact-duplicate rate is 0.000168 and the near-duplicate rate is zero.

H Scope, Limitations, and Artifact Index

H.1 Scope and Limitations

The following boundaries apply to the evidence in the main text and this appendix.

- Operational events are deterministic, rule-derived units for state control, not unconstrained discovery of natural semantic events. The 24-s rollover safeguard closes 40.2% of constructed events.
- MatchTime alignment covers 9.13% (15,189 / 166,419) of all operational events and therefore emphasizes moments for which commentary supervision is available.
- The main commentary table is reference-anchored and uses oracle operational closure, current-event alignment, label-assisted action/type metadata, and a record-readiness intervention.
- The free-scheduler audit uses checkpoint step 7,000, cached visual tokens, and label-assisted action/type metadata. It demonstrates continuous execution, not a purely visual, target-independent commentary benchmark.
- The raw-video benchmark uses a fixed current-event/recent-window/historical-memory request workload to compare history scaling; it does not evaluate each method’s native speaking decisions.
- The deployed scheduler is deterministic and rule-assisted. Scheduler strategy learning is outside the paper’s central claim.
- Generated event-record captions are model outputs rather than verified facts. Record availability is evaluated separately from downstream commentary quality, and no record-level factual-correctness claim is made.
- The blinded semantic audit uses one temperature-zero LLM judge and silver references. It measures availability-aware, reference-conditioned preference under the frozen

Artifact ID	Paper-facing role and frozen evidence records
ANCHOR-S1K	Reference-anchored StreamSoccer quality and retrieval diagnostics. <i>Records</i> : protocol and content hashes; command; traces; predictions; evaluation summary
REP-MEM	Recurrent event-memory representation result. <i>Records</i> : checkpoint hash; predictions; scores; paired bootstrap
REP-EVENT	Operational-event pooling result. <i>Records</i> : checkpoint hash; predictions; scores; paired bootstrap
REP-FIXED	Fixed-time pooling result. <i>Records</i> : checkpoint hash; predictions; scores; paired bootstrap
SCOPE-CUR	Current-memory-only configuration. <i>Records</i> : replay command and evaluation summary
SCOPE-LOCAL	Current plus local event-memory buffer configuration. <i>Records</i> : replay command and evaluation summary
SCOPE-FULL	Full three-scope configuration. <i>Records</i> : replay command and evaluation summary

Table H.1: Reproduction map for the frozen results and audits. Each stable ID names the evidence records supporting the corresponding paper-facing result.

Artifact ID	Paper-facing role and frozen evidence records
RAW-EWL	Raw-video efficiency, coverage, and stage timing. <i>Records</i> : run manifest; per-request timings; aggregate tables
FREE-S7K	Free-scheduler continuous-execution audit. <i>Records</i> : traces; queue audit; outputs; summary
HIST-CF209	Four-arm historical-record intervention. <i>Records</i> : protocol; 209-anchor manifest; 836 outputs; evaluation summary; match-cluster bootstrap
READY-730	Paired record-readiness audit. <i>Records</i> : protocol; 730 paired rows; drain traces; audit summary
BLIND-3789	Four-way blinded LLM semantic audit. <i>Records</i> : protocol and source hashes; 3,789 permuted ballots; decoded judgments; match-cluster bootstrap
FAIL-S10K	Step-10,000 reference-anchored mechanical failure audit. <i>Records</i> : commentary and record outputs; character, repetition, and encoding audit; aggregate counts
CASE-FROZEN	Fixed qualitative gallery. <i>Records</i> : selection manifest; displayed records; exact outputs; highlight/render audit

Table H.1: Reproduction map, continued.

prompt rather than human preference or claim-level factuality.

- Experiments use one soccer data ecosystem. Cross-league, cross-language, and broadcast-style generalization have not been established.
- Retained context-token count is not instrumented in the current raw-video artifact. Zero-valued context fields in diagnostic logs must not be interpreted as proof that no context was retained.

H.2 Reproduction Map

Table H.1 extends the stable labels in Table C.4 to every frozen result and audit reported in this appendix.

The map uses stable IDs instead of absolute machine paths. Each result is backed by a frozen run-specific protocol or

manifest together with the listed row-level outputs or traces and aggregate summary. Large row-level files are not duplicated in this PDF. The historical intervention, record-readiness audit, blinded semantic audit, and case-gallery selection are complete.

LLM Usage

ChatGPT was used to aid in polishing the writing, including grammar, readability, and sentence clarity. Separately, GPT-5.6-terra was used as the single evaluator in the blinded semantic audit in [Appendix E.2](#). It ranked anonymized candidate commentaries against a silver reference under a frozen prompt; its judgments were used only for evaluation and were not used as training targets.