arXiv:2611.04490v1 [cs.CV] 3 Nov 2026

POLARIMETRIC SCATTERING-STRUCTURE CONTRASTIVE LEARNING FOR FEW-SHOT HRRP RECOGNITION

Fangyi Wang, Peng Zhao, and Haipeng Wang[*†]

Fudan University, China

ABSTRACT

Few-shot high-resolution range profile (HRRP) recognition is challenged by strong aspect-dependent variation and sparse novel-class support. We propose polarimetric scattering-structure contrastive learning (PSS-CL), which supplies an episodic HRRP encoder with a structured physical training view. Dominant local responses are represented by their soft affinities to canonical polarimetric mechanisms, normalized range locations, and energy contributions. A symmetric cross-view objective transfers this scattering structure to the learned HRRP representation, while episodic prototype learning supports novel-class inference without the physical branch. We conduct Random-aspect and Cross-aspect experiments on a six-class measured dataset. In Cross-aspect 1-, 3-, and 5-shot recognition, PSS-CL achieves 81.73%, 86.92%, and 90.98% mean class accuracy (MCA), respectively, outperforming the best competing results by 5.62%, 3.09%, and 3.56%.

***Index Terms*—** high-resolution range profile, few-shot learning, radar signal processing, contrastive learning, radar target recognition

1. INTRODUCTION

A high-resolution range profile (HRRP) is a one-dimensional complex radar signature obtained by coherently projecting the scattering responses of a target onto the radar line of sight. Its range cells resolve the distribution of dominant scattering centers along the target extent, providing a compact one-dimensional representation for recognition. Observation aspect changes the visibility, amplitude, and phase of local scattering centers, resulting in large intra-class variations. In few-shot recognition, one or a few labeled support HRRPs provide sparse coverage of the aspect-dependent distribution of each novel class. A query observed at a different aspect may consequently deviate considerably from the support prototype. Figure 1 summarizes HRRP formation and the resulting Cross-aspect prototype mismatch.

Existing HRRP recognition studies have progressively replaced handcrafted statistics with learned representations. Probabilistic and generative models describe HRRPs using class-factorized, conditional, mixture, or adversarial latent variables [1, 2, 3, 4]. Recurrent Bayesian networks and deep sequence models exploit dependencies among multi-aspect observations [5, 6]. More recent methods incorporate prior-guided contrastive learning, semantic hierarchies, target-aspect constraints, and polarization fusion to strengthen discriminative representations [7, 8, 9, 10]. These methods learn primarily from densely labeled base-class distributions, leaving novel-class support sets with sparse aspect coverage and unstable few-shot prototypes.



Fig. 1. HRRP formation and the Cross-aspect few-shot recognition challenge. Dominant scattering centers form a one-dimensional range profile, while aspect-dependent scattering causes support–query prototype mismatch.

Few-shot learning transfers reusable knowledge from base classes to tasks with small support sets. Representative approaches learn similarity functions or task-specific metrics through Siamese Networks, Matching Networks, Prototypical Networks, and Relation Networks [11, 12, 13, 14]; other methods learn adaptable initializations or episodic classifiers [15, 16], and strong representation baselines are also effective [17]. For HRRP data, prior-assisted task-wise discriminant analysis and fully polarimetric scattering-center matching demonstrate the value of domain knowledge under limited supervision [18, 19]. Existing objectives and physical descriptors provide complementary cues, yet few-shot HRRP learning lacks a fixed-dimensional training view that preserves local polarimetric mechanism relations and range organization without altering novel-class inference.

To address this problem, PSS-CL transfers a range-structured polarimetric scattering view to an episodic HRRP encoder through cross-view contrast. An auxiliary aspect-aware loss is used during training, while novel-class inference requires only the HRRP encoder and prototype classifier.

Our main contributions are summarized as follows:

- We construct a structured polarimetric scattering view by aggregating canonical soft-response affinities, range locations, and energy contributions from dominant scattering regions.
- We introduce cross-view scattering alignment that transfers this physical view to an episodically trained HRRP encoder. The physical branch supplies training supervision and is removed for novel-class prototype inference.
- On a six-class measured dataset, PSS-CL achieves the highest MCA among the compared methods under the present protocol: 81.73%, 86.92%, and 90.98% in Cross-aspect 1-, 3-, and

Corresponding author: Haipeng Wang.

This work was supported in part by the National Natural Science Foundation of China (Grant No. 62271153) and the Fundamental and Interdisciplinary Disciplines Breakthrough Plan of the Ministry of Education of China (Grant No. JYB2025XDXM110).

This work has been submitted to the IEEE for possible publication. Copyright may be transferred without notice, after which this version may no longer be accessible.



Fig. 2. Overview of PSS-CL. The structured physical branch provides training-only cross-view supervision for episodic HRRP learning.

5-shot recognition.

2. METHOD

2.1. Problem formulation and overview

Let the base-class training set be $\mathcal{D}_{\text{base}} = \{(X_i, y_i, \theta_i)\}_{i=1}^{N_b}$, where $X_i \in \mathbb{R}^{6\times L}$ is a fully polarimetric complex HRRP represented by the real and imaginary parts of the HH, HV, and VV channels. The variables y_i and θ_i denote the class label and aspect angle, respectively. We consider class-disjoint few-shot recognition: base classes are used for representation learning; evaluation uses unseen classes under an N-way K-shot protocol.

PSS-CL combines structured scattering-view construction, cross-view alignment, and episodic class learning. Cameron decomposition is applied to dominant scattering regions; mechanism similarities, range locations, and energy contributions form a compact physical view. A shared HRRP encoder produces class and scattering embeddings. Cross-view contrast aligns the scattering embedding with the physical view. Episodic prototypes optimize the class embedding, with aspect-aware contrast serving as an auxiliary regularizer. Inference uses only the encoder and class branch.

2.2. Local polarimetric scattering-view construction

For sample i, let $\mathbf{S}_i(n)$ be the 2×2 polarimetric scattering matrix at range cell n. Its energy is

$$P_i(n) = \|\mathbf{S}_i(n)\|_F^2 = |S_{i,\text{HH}}(n)|^2 + 2|S_{i,\text{HV}}(n)|^2 + |S_{i,\text{VV}}(n)|^2, \tag{1}$$

where calibrated monostatic reciprocity gives $S_{i,\text{VH}} = S_{i,\text{HV}}$. After joint energy normalization, a seven-cell moving average and 0.1-normalized prominence threshold with seven-cell non-maximum suppression retain $M_i \le M_{\max} = 16$ seven-cell windows; the global maximum handles an empty detection. Their centers and energies are

$$c_{i,m} = \arg\max_{n\in\mathcal{W}_{i,m}} P_i(n), \qquad A_{i,m} = \sum_{n\in\mathcal{W}_{i,m}} P_i(n). \tag{2}$$

k	*Scattering Response*	z_k
1	*Trihedral*	1
2	*Cylinder*	0.5
3	*Dipole*	0
4	*Narrow diplane*	-0.5
5	*Dihedral*	-1
6	*Quarter wave*	$\pm j$

Fig. 3. Six canonical polarimetric scattering-response families used in the Cameron implementation.

We instantiate the local polarimetric decomposition using the Cameron formulation, which characterizes a reciprocal response by its maximum symmetric component and measures it against canonical scattering responses [20, 21, 22]. For the scattering matrix at cell n, define $\alpha = (S_{\text{HH}} + S_{\text{VV}})/\sqrt{2}$, $\beta = (S_{\text{HH}} - S_{\text{VV}})/\sqrt{2}$, and $\gamma = (S_{\text{HV}} + S_{\text{VH}})/\sqrt{2}$, where sample and cell indices are omitted. The Cameron real rotation parameter and maximum symmetric component are

$$\begin{aligned} \varphi &= \frac{1}{2}\,\text{atan2}\big(2\Re\{\beta\gamma^*\}, |\beta|^2 - |\gamma|^2\big)\,, \\ \mu &= \beta\cos\varphi + \gamma\sin\varphi. \end{aligned} \tag{3}$$

Let $\lambda^{(1)}$ and $\lambda^{(2)}$ denote $\alpha+\mu$ and $\alpha-\mu$, ordered such that $|\lambda^{(1)}| \ge |\lambda^{(2)}|$. Restoring the indices, the Cameron coordinate is $z_{i,n} = \lambda_{i,n}^{(2)}/\lambda_{i,n}^{(1)}$, with $|z_{i,n}| \le 1$; it is set to zero when $|\lambda_{i,n}^{(1)}| < \delta$, where $\delta = 10^{-8}$. Figure 3 illustrates the six canonical response families used to construct the local scattering view. Their coordinates are $z_k \in \{1, 0.5, 0, -0.5, -1, \text{j}\}$. The pair $\pm$j constitutes one quarter-wave family under the Cameron metric.

The squared Cameron affinity, $s_{i,n,k} = \cos^2 d_C(z_{i,n}, z_k)$, is

$$s_{i,n,k} = \frac{\max\big(|1 + z_{i,n} z_k^*|^2, |z_{i,n} + z_k^*|^2\big)}{(1 + |z_{i,n}|^2)(1 + |z_k|^2)}, \quad k = 1, \ldots, 6, \quad (4)$$

where $s_{i,n,k} \in [0, 1]$. Each retained cell is represented by its complete six-dimensional similarity vector. The energy-weighted relation within window m is

$$q_{i,m,k} = \frac{\sum_{n \in \mathcal{W}_{i,m}} P_i(n) s_{i,n,k}}{\sum_{n \in \mathcal{W}_{i,m}} P_i(n) + \delta}. \quad (5)$$

The vector $\mathbf{q}_{i,m} = [q_{i,m,1}, \ldots, q_{i,m,6}]$ records the continuous relation between a local response and all canonical mechanisms.

To obtain a fixed-dimensional representation, the span from the first to last retained window boundary is mapped linearly to $[0, 1]$ and divided into R intervals. Let $b(c_{i,m}) \in \{1, \ldots, R\}$ denote the clipped interval index of center $c_{i,m}$ and define

$$\begin{aligned} w_{i,m} &= \frac{A_{i,m}}{\sum_{j=1}^{M_i} A_{i,j} + \delta}, \\ G_i(r, k) &= \sum_{\substack{m=1 \\ b(c_{i,m})=r}}^{M_i} w_{i,m} q_{i,m,k}. \end{aligned} \quad (6)$$

Collecting these entries gives $\mathbf{G}_i = [G_i(r, k)] \in \mathbb{R}^{R \times 6}$. The structured and location-free global scattering views are

$$\mathbf{g}_i = \mathrm{norm}(\mathrm{vec}(\mathbf{G}_i)) \in \mathbb{R}^{6R}, \quad \bar{\mathbf{g}}_i = \mathrm{norm}\left(\sum_{m=1}^{M_i} w_{i,m} \mathbf{q}_{i,m}\right). \quad (7)$$

Here, $\mathrm{norm}(\mathbf{x}) = \mathbf{x} / \max(\|\mathbf{x}\|_2, \delta)$. Thus, $\mathbf{g}_i$ describes how polarimetric mechanisms are distributed along range; $\bar{\mathbf{g}}_i$ removes their locations for the ablation in Table 2.

2.3. Cross-view scattering alignment and class learning

A lightweight one-dimensional encoder extracts the shared HRRP feature $\mathbf{h}_i = E_h(X_i)$. Two projection heads generate the class and scattering embeddings, where "id" denotes the target-identity (class) space. A two-layer multilayer perceptron encodes the structured scattering view:

$$\begin{aligned} \mathbf{z}_i^{\mathrm{id}} &= \mathrm{norm}\left(P_{\mathrm{id}}(\mathbf{h}_i)\right), \\ \mathbf{z}_i^{\mathrm{sc}} &= \mathrm{norm}\left(P_{\mathrm{sc}}(\mathbf{h}_i)\right), \qquad \mathbf{v}_i = \mathrm{norm}\left(E_g(\mathbf{g}_i)\right). \end{aligned} \quad (8)$$

The paired embeddings $\mathbf{z}_i^{\mathrm{sc}}$ and $\mathbf{v}_i$ describe the same HRRP sample in a training episode batch of size B. With $\ell_{ij}^{\mathrm{sc}} = (\mathbf{z}_i^{\mathrm{sc}})^\top \mathbf{v}_j / \tau_{\mathrm{sc}}$, their symmetric cross-view contrastive loss is

$$\mathcal{L}_{\mathrm{sc}} = -\frac{1}{2B} \sum_{i=1}^{B} \left[\log \frac{e^{\ell_{ii}^{\mathrm{sc}}}}{\sum_{j=1}^{B} e^{\ell_{ij}^{\mathrm{sc}}}} + \log \frac{e^{\ell_{ii}^{\mathrm{sc}}}}{\sum_{j=1}^{B} e^{\ell_{ji}^{\mathrm{sc}}}} \right]. \quad (9)$$

This objective transfers local polarimetric structure to the shared HRRP feature. Same-class instances remain negatives because $\mathbf{g}_i$ is sample-specific; class invariance is learned only by the identity head.

As an auxiliary class-space regularizer during base-class training, the class branch employs aspect-aware supervised contrastive learning [7]. For anchor i, let $\mathcal{P}(i) = \{p \neq i \mid y_p = y_i\}$. Each contrastive batch contains all support and query samples in an episode, ensuring $\mathcal{P}(i) \neq \varnothing$. The circular aspect difference and normalized positive weight are

$$\begin{aligned} \Delta\theta_{ip} &= \min\left(|\theta_i - \theta_p|, 360^\circ - |\theta_i - \theta_p|\right), \\ \widetilde{a}_{ip} &= \frac{1 + \eta \Delta\theta_{ip}/180^\circ}{\sum_{r \in \mathcal{P}(i)} (1 + \eta \Delta\theta_{ir}/180^\circ)}. \end{aligned} \quad (10)$$

The coefficient $\eta \geq 0$ controls the emphasis on wider aspect separations. The resulting loss is

$$\mathcal{L}_{\mathrm{ca}} = -\frac{1}{B} \sum_{i=1}^{B} \sum_{p \in \mathcal{P}(i)} \widetilde{a}_{ip} \log \frac{e^{(\mathbf{z}_i^{\mathrm{id}})^\top \mathbf{z}_p^{\mathrm{id}} / \tau_{\mathrm{ca}}}}{\sum_{j \neq i} e^{(\mathbf{z}_i^{\mathrm{id}})^\top \mathbf{z}_j^{\mathrm{id}} / \tau_{\mathrm{ca}}}}. \quad (11)$$

The weighting emphasizes same-class positive pairs separated by wider aspect intervals. Aspect angles determine positive-pair weights only during training; the HRRP signal X_i remains the input to E_h.

2.4. Episodic prototype learning and inference

For an N-way K-shot episode with query set $\mathcal{Q}$, the prototype, score, episodic loss, and total objective are

$$\begin{aligned} \mathbf{p}_c &= \mathrm{norm}\left(K^{-1} \sum_{k=1}^{K} \mathbf{z}_{c,k}^{\mathrm{id}}\right), \qquad d(q, c) = (\mathbf{z}_q^{\mathrm{id}})^\top \mathbf{p}_c, \\ \mathcal{L}_{\mathrm{ep}} &= -|\mathcal{Q}|^{-1} \sum_{(q, y_q) \in \mathcal{Q}} \log \frac{e^{d(q, y_q)/\tau_{\mathrm{ep}}}}{\sum_c e^{d(q, c)/\tau_{\mathrm{ep}}}}, \\ \mathcal{L} &= \mathcal{L}_{\mathrm{ep}} + \lambda_{\mathrm{sc}} \mathcal{L}_{\mathrm{sc}} + \lambda_{\mathrm{ca}} \mathcal{L}_{\mathrm{ca}}. \end{aligned} \quad (12)$$

Novel-class evaluation encodes support and query HRRPs with E_h and P_{id}, constructs support prototypes, and applies cosine scoring. The scattering-view encoder, scattering head, and aspect annotations provide training supervision and are discarded after training.

3. EXPERIMENTS

3.1. Dataset and settings

The measured dataset contains 56,356 complex HRRPs in three synchronized channels: HH, HV, and VV. The range-registered profiles come from six targets: bulk carrier, container, passenger, fishing, tanker, and reflector group. Each $L = 1024$ HRRP was acquired at 10 GHz with a 120-MHz bandwidth and 1.25-m range resolution. For each class, the measurements collectively span 0°–360° in azimuth and 0°–25° in pitch. We use two complementary 3/3 class splits: Fold A assigns the first three classes to base training and the remaining classes to novel-class evaluation; Fold B exchanges the two groups.

Each fold trains one full-azimuth base-class model for both protocols. A 3-way K-shot episode, $K \in \{1, 3, 5\}$, contains 15 queries per class, with no overlap between support and query samples. Random-aspect draws samples without replacement from the full azimuth range. Cross-aspect draws support and query samples from two 60° sectors centered 120° apart, leaving a 60° boundary gap. Each fold uses 5,000 training episodes with uniformly sampled K and 500 episodes from a disjoint base-class validation pool. All methods share 2,000 test episodes per fold, protocol, and shot. MCA first averages per-class query accuracy over episodes and then over folds.

The four-stage 1-D ResNet-12 outputs 128-dimensional embeddings after global average pooling; all three heads are two-layer

MLPs. One episode forms a batch. We set $R = 16$, $\tau_{\mathrm{sc}} = \tau_{\mathrm{ca}} = 0.07$, $\tau_{\mathrm{ep}} = 0.1$, $\eta = 1$, and $\lambda_{\mathrm{sc}} = \lambda_{\mathrm{ca}} = 0.5$. AdamW uses a 10^{-3} learning rate and 10^{-4} weight decay; all choices use only base validation.

Table 1. MCA (%) on the measured HRRP dataset.

Method	Random-aspect			Cross-aspect		
	1-shot	3-shot	5-shot	1-shot	3-shot	5-shot
General few-shot learning						
Matching Nets [12]	72.42	79.16	84.28	60.83	67.76	70.69
ProtoNet [13]	76.28	82.36	84.55	63.52	72.32	73.85
RelationNet [14]	74.76	81.55	85.39	63.19	70.93	75.46
MAML [15]	70.35	74.16	76.60	58.70	63.98	67.25
MetaOptNet [16]	75.95	83.05	86.16	66.81	74.72	76.66
DN4 [23]	77.53	82.73	87.13	67.47	75.69	77.53
FEAT [24]	76.72	81.55	83.64	68.87	74.92	80.52
DeepEMD [25]	81.90	83.89	86.56	71.20	75.51	80.10
HRRP-oriented methods						
PriorK-NN [7]	73.61	79.73	85.49	69.42	76.10	79.23
GAF-MLGNN [26]	80.88	85.71	90.81	73.93	80.65	84.71
MTBC [27]	85.71	89.27	92.65	76.11	82.39	87.42
DeepSCOM [19]	82.05	86.40	88.94	73.85	83.83	86.99
PSS-CL (Ours)	**88.23**	**93.09**	**95.21**	**81.73**	**86.92**	**90.98**

3.2. Comparison with competing methods

Table 1 compares eight general and four HRRP-oriented few-shot methods. All use the same folds, episodes, inputs, and support–query selections. General baselines share ResNet-12, while HRRP methods retain their published architectures. PSS-CL ranks first in every setting, exceeding the best competing result by 2.52%, 3.82%, and 2.56% under Random-aspect evaluation and by 5.62%, 3.09%, and 3.56% under Cross-aspect evaluation. Its 1-shot Random-to-Cross decrease is 6.50%, compared with 12.76% for ProtoNet. The smaller drop suggests that scattering-structure supervision helps preserve class information when the support and query aspects differ.

Figure 4 reports the Cross-aspect fishing–tanker–reflector fold. The mean diagonal accuracy rises from 82.14% to 88.92% and 92.24% as the shot number increases. At 5-shot, all three class accuracies exceed 90%, compared with 80.43%–83.61% at 1-shot. Fishing-to-tanker errors fall from 12.52% to 8.10% and 6.13%, while ship–reflector errors fall from 6.71%–9.68% to 2.72%–4.91%. The consistent decrease shows that additional support samples improve the prototypes for all three classes.



Fig. 4. Cross-aspect confusion matrices for the fishing–tanker–reflector fold: (a) 1-shot; (b) 3-shot; (c) 5-shot.

3.3. Ablation study

Table 2 separates the effects of cross-view alignment, aspect regularization, and the structured view $\mathbf{g}_i$. With the global view $\bar{\mathbf{g}}_i$, $\mathcal{L}_{\mathrm{sc}}$ improves the episodic baseline by 10.64%, 9.36%, and 8.69%, while $\mathcal{L}_{\mathrm{ca}}$ alone adds 7.26%, 6.10%, and 5.79%. Combining both losses reaches 78.33%, 84.49%, and 87.68%. Replacing $\bar{\mathbf{g}}_i$ with the range-structured view $\mathbf{g}_i$ further adds 3.40%, 2.43%, and 3.30%. Overall, PSS-CL improves the baseline by 17.23%, 14.53%, and 14.16%. The larger 1-shot gain highlights the value of physical structure when support is most limited, while the consistent gains show that the three components work together.

Table 2. Ablation results under Cross-aspect evaluation (MCA, %).

Configuration	$\mathcal{L}_{\mathrm{sc}}$	$\mathcal{L}_{\mathrm{ca}}$	View	1-shot	3-shot	5-shot
Episodic baseline	–	–	–	64.50	72.39	76.82
Scattering alignment	✓	–	$\bar{\mathbf{g}}_i$	75.14	81.75	85.51
Aspect regularizer	–	✓	–	71.76	78.49	82.61
Global scattering view	✓	✓	$\bar{\mathbf{g}}_i$	78.33	84.49	87.68
PSS-CL (Ours)	✓	✓	$\mathbf{g}_i$	**81.73**	**86.92**	**90.98**

3.4. Hyperparameter sensitivity

Figure 5 reports a post-selection Cross-aspect 1-shot diagnostic, with defaults fixed on the base validation set. For $\lambda_{\mathrm{sc}} = 0.5$, the MCA rises from 78.18% at $R = 4$ to 81.73% at $R = 16$, then falls to 79.29% at $R = 64$. This agrees with the need to balance range detail against sparsity. At $R = 16$, the three tested values of λ_{sc} give 80.23%–81.73%. For the aspect regularizer, $\tau_{\mathrm{ca}} = 0.07$ gives 80.60%, 81.73%, and 80.36% for $\eta = 0.5$, 1, and 2, whereas all curves fall below 79% at $\tau_{\mathrm{ca}} = 0.20$. The gradual changes around the selected values show that performance does not rely on a narrow parameter choice.



Fig. 5. Post-selection Cross-aspect 1-shot sensitivity to (a) R and λ_{sc}; (b) τ_{ca} and η.

4. CONCLUSION

In this paper, we presented PSS-CL for few-shot HRRP recognition. Cross-view contrast transfers range–mechanism organization from a structured fully polarimetric view to the HRRP encoder. Episodic prototype learning and aspect regularization support novel-class recognition, with the physical branch used only during training. On the measured six-class dataset, PSS-CL achieves the highest MCA among the compared methods under both protocols.

5. REFERENCES

[1] L. Liao, L. Du, and J. Chen, "Class factorized complex variational auto-encoder for HRR radar target recognition," *Signal Process.*, vol. 182, pp. 107932, 2021.

[2] J. Chen, L. Du, and L. Liao, "Discriminative mixture variational autoencoder for semisupervised classification," *IEEE Trans. Cybern.*, vol. 52, no. 5, pp. 3032–3046, 2022.

[3] C. Du, B. Chen, B. Xu, D. Guo, and H. Liu, "Factorized discriminative conditional variational auto-encoder for radar HRRP target recognition," *Signal Process.*, vol. 158, pp. 176–189, 2019.

[4] Y. Huang, Y. Wen, L. Shi, and X. Ding, "Recognition-aware HRRP generation with generative adversarial network," *IEEE Geosci. Remote Sens. Lett.*, vol. 19, pp. 1–5, 2022.

[5] W. Chen, B. Chen, Y. Liu, X. Peng, H. Fan, F. Yu, and H. Liu, "Bidirectional recurrent gamma belief network for HRRP target recognition," *Signal Process.*, vol. 188, pp. 108213, 2021.

[6] D. Guo, B. Chen, W. Chen, C. Wang, H. Liu, and M. Zhou, "Variational temporal deep generative model for radar HRRP target recognition," *IEEE Trans. Signal Process.*, vol. 68, pp. 5795–5809, 2020.

[7] Q. Liu, X. Zhang, and Y. Liu, "A prior-knowledge-guided neural network based on supervised contrastive learning for radar HRRP recognition," *IEEE Trans. Aerosp. Electron. Syst.*, vol. 60, no. 3, pp. 2854–2873, 2024.

[8] Y. Liu, T. Long, L. Zhang, Y. Wang, X. Zhang, and Y. Li, "SDHC: Joint semantic-data guided hierarchical classification for fine-grained HRRP target recognition," *IEEE Trans. Aerosp. Electron. Syst.*, vol. 60, no. 4, pp. 3993–4009, 2024.

[9] Q. Liu, X. Zhang, and Y. Liu, "Target-aspect-guided neural network with geometric constraints for imbalanced radar target recognition," *IEEE Trans. Aerosp. Electron. Syst.*, vol. 61, no. 5, pp. 12122–12142, 2025.

[10] Y. Zhou, S. Liu, H. W. Gao, H. Lin, G. Wei, X. Wang, and X. M. Pan, "A dual-polarization feature fusion network for radar automatic target recognition based on HRRP sequences," *IEEE Trans. Aerosp. Electron. Syst.*, vol. 61, no. 5, pp. 14642–14655, 2025.

[11] G. Koch, R. Zemel, and R. Salakhutdinov, "Siamese neural networks for one-shot image recognition," in *ICML Deep Learning Workshop*, 2015.

[12] O. Vinyals, C. Blundell, T. Lillicrap, K. Kavukcuoglu, and D. Wierstra, "Matching networks for one shot learning," in *Adv. Neural Inf. Process. Syst.*, 2016, vol. 29.

[13] J. Snell, K. Swersky, and R. Zemel, "Prototypical networks for few-shot learning," in *Adv. Neural Inf. Process. Syst.*, 2017, vol. 30.

[14] F. Sung, Y. Yang, L. Zhang, T. Xiang, P. H. S. Torr, and T. M. Hospedales, "Learning to compare: Relation network for few-shot learning," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2018, pp. 1199–1208.

[15] C. Finn, P. Abbeel, and S. Levine, "Model-agnostic meta-learning for fast adaptation of deep networks," in *Proc. 34th Int. Conf. Mach. Learn. (ICML)*, 2017, vol. 70, pp. 1126–1135.

[16] K. Lee, S. Maji, A. Ravichandran, and S. Soatto, "Meta-learning with differentiable convex optimization," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2019, pp. 10657–10665.

[17] W. Y. Chen, Y. C. Liu, Z. Kira, Y. C. F. Wang, and J. B. Huang, "A closer look at few-shot classification," in *Int. Conf. Learn. Represent. (ICLR)*, 2019.

[18] J. Li, W. Guo, F. Wei, T. Zhang, and W. Yu, "Prior information-assisted few-shot HRRP recognition based on task-wise shrinkage quadratic discriminant analysis," *IEEE Trans. Aerosp. Electron. Syst.*, vol. 60, no. 6, pp. 9354–9368, 2024.

[19] Z. Guo, Z. Liu, R. Xie, and L. Ran, "HRRP few-shot target recognition for full polarimetric radars via SCs optimal matching," *IEEE Trans. Aerosp. Electron. Syst.*, vol. 61, no. 2, pp. 4526–4541, 2025.

[20] W. L. Cameron and L. K. Leung, "Feature motivated polarization scattering matrix decomposition," in *Proc. IEEE Int. Radar Conf.*, 1990, pp. 549–557.

[21] W. L. Cameron, N. N. Youssef, and L. K. Leung, "Simulated polarimetric signatures of primitive geometrical shapes," *IEEE Trans. Geosci. Remote Sens.*, vol. 34, no. 3, pp. 793–803, 1996.

[22] W. L. Cameron and H. Rais, "Polarization symmetric scatterer metric space," *IEEE Trans. Geosci. Remote Sens.*, vol. 47, no. 4, pp. 1097–1107, 2009.

[23] W. Li, L. Wang, J. Xu, J. Huo, Y. Gao, and J. Luo, "Revisiting local descriptor based image-to-class measure for few-shot learning," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2019, pp. 7260–7268.

[24] H. J. Ye, H. Hu, D. C. Zhan, and F. Sha, "Few-shot learning via embedding adaptation with set-to-set functions," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2020, pp. 8808–8817.

[25] C. Zhang, Y. Cai, G. Lin, and C. Shen, "DeepEMD: Few-shot image classification with differentiable earth mover's distance and structured classifiers," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2020, pp. 12203–12213.

[26] L. Chen, P. Hu, Q. Liu, and Z. Liu, "GAF-MLGNN: An efficient meta-learning framework for few-shot HRRP RATR with GNN," *IEEE Trans. Signal Inf. Process. Netw.*, vol. 12, pp. 341–356, 2026.

[27] S. Li, W. Li, P. Huang, M. Zheng, B. Tian, and S. Xu, "MTBC: Masked vision transformer and brownian distance covariance classifier for cross-domain few-shot HRRP recognition," *IEEE Sensors J.*, vol. 25, no. 9, pp. 16440–16454, 2025.

DISCLOSURE

The authors have no relevant financial or nonfinancial interests to disclose.

COMPLIANCE WITH ETHICAL STANDARDS

This study did not involve human or animal subjects; therefore, ethical approval was not required.