

StreamOPD: A Post-Training Recipe with Spatio-Temporal Cue Gating for Streaming Video Understanding

Keming Wu¹, Baoyi Wang², Kaichen Zhang³, Xiang An⁴, Zuhao Yang⁵, Sudong Wang⁶,
Haowei Zhu¹, Tingxuan Huang¹, Hongcheng Gao¹, Bin Wang^{1*}

¹Tsinghua University, ²Zhejiang University, ³The University of Hong Kong,

⁴LMMs-Lab, ⁵Nanyang Technological University,

⁶Hong Kong University of Science and Technology (Guangzhou)

Project page: <https://unix-ai-lab.github.io/StreamOPD>

Abstract

Streaming video understanding demands direct responses from the causally observed prefix of an unfolding video. Existing systems add inference-time memory, retrieval, and compression, yet a training-free sliding-window baseline already matches them. We therefore fix a memory-free recent-window protocol and ask how far post-training alone can go. Reinforcement learning with verifiable rewards fits this regime poorly, encouraging long “think-then-answer” generations, while on-policy distillation (OPD) supplies dense token-level teacher supervision on student trajectories but is stable only when both models train in thinking mode. These observations lead to STREAMOPD, a recipe combining verifiable streaming-video data, thinking-mode OPD, and instruct-mode deployment. It raises StreamingBench from 77.9% to 83.9%—within 0.3 points of the 9B teacher—and improves OVO-Bench excluding its hallucination-detection subtask (HLD) by 9.1 points under unchanged inference. As a teacher-privilege extension, *Spatio-Temporal CueGate* (ST-CueGate) aggregates cue-versus-no-cue teacher likelihood ratios into a group-relative response score that reweights OPD. It reaches 71.9% on OVO-Bench (excluding HLD) and 64.9% on Video-MME, and is the only variant that stays above the base model on all four benchmarks. Replacing the teacher with a frozen copy of the student’s initial policy—on-policy self-distillation—retains most of these gains and lifts HLD to 57.0%, above both the untrained student and the 9B teacher, so abstention loss is not intrinsic to the recipe. We provide a transparent and reproducible reference for open-source streaming-video research.

Introduction

Streaming video understanding asks a multimodal large language model (MLLM) to answer questions while a video is still unfolding (Lin et al. 2026; Niu et al. 2025; Chen et al. 2024). Unlike offline video QA, the model cannot look ahead or repeatedly revisit the full clip: it must respond directly from the causally observed prefix available when the question arrives. This regime is central to live assistants, wearable cameras, and monitored environments, yet remains difficult for open MLLMs. StreamingBench (Lin et al. 2026) and OVO-Bench (Niu et al. 2025) expose this gap through real-time perception, backward tracing, and forward-looking queries.

*Corresponding author.

Most streaming methods address this challenge with memory banks, KV-cache compression, retrieval, or specialized streaming modules. SimpleStream (Shen et al. 2026), however, shows that a strong, training-free recent-window baseline can already match or surpass substantially more complex systems, reaching 67.7% on OVO-Bench and 80.6% on StreamingBench with only four recent frames. This finding suggests that architectural complexity is not necessarily the primary bottleneck. We therefore fix the same simple inference protocol throughout—no memory bank, retrieval, compression, or online reasoning module—and isolate a cleaner question: can *post-training* close the small-to-large model gap while leaving the streaming inference path unchanged? Concurrent work brings reasoning into the stream and learns when to answer (Liu et al. 2026); we instead move reasoning to training time and preserve direct instruct-mode deployment.

Modern post-training introduces a different tension. Reinforcement learning with verifiable rewards (RLVR) (Lambert et al. 2024; Guo et al. 2025), GRPO (Shao et al. 2024), and multimodal reasoning recipes (Zhang et al. 2025; Yang et al. 2025, 2026) elicit stronger reasoning through extended generations, but those reasoning tokens must be produced before the final answer and are therefore poorly matched to direct-response streaming. Our teacher-free GRPO baseline makes the mismatch concrete: it maintains a strong reward-compatible score while drifting toward long rationales that fail under the deployed direct-answer format. Sparse task reward constrains the final answer but not the trajectory that precedes it.

On-policy distillation (OPD) has recently emerged as an alternative that evaluates a teacher on student-generated trajectories and supplies dense token-level supervision (Agarwal et al. 2024; Gu et al. 2024; Zhao et al. 2026). In our mode comparison, both-instruct and teacher-thinking/student-instruct training collapse early, whereas both-thinking training converges. The failed runs combine one- or few-token responses with substantially larger gradient norms, which is consistent with a short-trajectory scale hypothesis. Response length is not independently controlled, however, so mode-specific policy distributions, teacher-student KL, estimator variance, normalization, and clipping remain competing explanations. We therefore treat length as a mechanistic hypothesis and the thinking-train/instruct-infer pairing as the




Figure 1: Teacher/student training-mode pairings. All models are evaluated in instruct mode under the fixed recent-window protocol. Among the tested pairings, only both-thinking training converges in our runs and reaches 83.9% on StreamingBench.

empirical recipe supported by our experiments (Fig. 1).

Under this recipe, standard OPD raises a Qwen3.5-4B (Team 2026) student from 77.9% to 83.9% on StreamingBench—within 0.3 points of a Qwen3.5-9B teacher—without changing inference, and gains 9.1 points on OVO-Bench excluding its hallucination-detection (HLD) subtask, which scores abstention on unanswerable queries rather than streaming event recall. These gains motivate a second question: beyond choosing a teacher, what information should the teacher receive? We study teacher inputs as *privileged information*, distinguishing signals derived from the same underlying training clip from ungrounded manipulations of the learning signal. Passive teacher-only visual cues do not consistently outperform standard OPD. Cue-versus-no-cue scoring shows a sparse teacher response: 56.5% of token-level contrasts are near zero, while the top 20% of positive-score tokens account for 82% of the total positive mass. We therefore propose *Spatio-Temporal CueGate* (ST-CueGate), a nested-context gate that aggregates these contrasts into a group-relative, response-level likelihood proxy while leaving the student and inference path unchanged. ST-CueGate reaches 84.6% on StreamingBench, 71.9% on OVO-Bench (excluding HLD), 64.9% on Video-MME, and 61.4% on LongVideoBench. We use STREAMOPD for the complete recipe and ST-CueGate for its optional teacher-privilege extension.

Our main contributions are:

- We document two post-training mismatches in streaming video: teacher-free GRPO optimizes its task reward while drifting toward increasingly verbose responses, whereas the tested OPD configurations involving instruct-mode training collapse.

- We establish StreamOPD, a practical recipe that combines a reproducible 25k verifiable-data pipeline, the empirically stable thinking-train/instruct-infer OPD configuration, and a fixed memory-free evaluation protocol. On top of this core, ST-CueGate uses cue-versus-no-cue teacher likelihood ratios to reweight student responses without modifying deployment.
- We report cross-benchmark gains under unchanged inference: StreamOPD improves over the untrained student on StreamingBench and OVO-Bench, while ST-CueGate also improves both general-video benchmarks.

Together, these results indicate that a fixed streaming inference path still leaves substantial headroom for post-training alone to recover, and that what the teacher is shown can matter as much as how large the teacher is.

Method

STREAMOPD consists of a core post-training recipe and an optional teacher-privilege extension. The core fixes the recent-window deployment protocol, constructs verifiable training data, trains student and teacher in thinking mode, and deploys the student in instruct mode. This design follows two empirical failures: teacher-free GRPO drifts toward long, deployment-incompatible trajectories, whereas the tested OPD configurations involving instruct-mode training collapse.

On top of this core recipe, we ask not only which teacher to use, but how the teacher responds to privileged information on each student-generated trajectory. Our cue-versus-no-cue analysis shows that the teacher’s likelihood shift is sparse and highly concentrated, so uniform cue conditioning does not distinguish trajectories with different cue sensitivity. We therefore introduce ST-CueGate as an extension that aggregates token-level conditional likelihood ratios into a group-relative response proxy for reweighting OPD.

Problem Setup and Inference Protocol. A streaming VLM receives a question q and a sequence of frames arriving over time; at the query moment it must answer from the frames seen so far. Following SimpleStream (Shen et al. 2026), we fix a *memory-free recent-window* inference protocol: the model conditions only on the most recent frames within a small budget (a recent-4-frame window at 1 fps), with no memory bank, retrieval, or compression. This keeps inference cost and architecture constant, so any improvement is attributable to the model’s weights rather than test-time machinery. Answers fall into three verifiable formats—multiple choice (MCQ), binary (Yes/No), and counting. Their rule-based reward $r \in \{0, 1\}$ is used only by the GRPO diagnostic in Experiments; the main OPD objective uses teacher log-probabilities rather than task reward. The unified backbone supports both thinking and direct instruct modes; since only both-thinking training converges among the tested pairings, we train teacher and student in thinking mode and deploy the student in instruct mode.

On-Policy Distillation Backbone. Let $\mathcal{D} = \{q_i\}_{i=1}^N$ denote the training prompts (each paired with its video input),




Figure 2: StreamOPD pipeline with ST-CueGate. (a) During thinking-mode training, the student generates an on-policy response y from a video sampled with the standard training pipeline. The cue-augmented teacher forward provides the distillation target τ^+ , while the no-cue forward provides a nested reference τ^- on the same frames and response. Their token-wise conditional log-likelihood ratio is aggregated into a response-level weight w that gates the OPD advantage. (b) During instruct-mode inference, the student uses the recent-window protocol—frames only, with no cue, memory module, or generated thinking trace.

π_θ the student, and π_τ a frozen teacher. For each q_i , the student samples an on-policy response $y_i = (y_{i,1}, \dots, y_{i,T_i}) \sim \pi_\theta(\cdot | q_i)$. On a valid response token t , define

$$s_{i,t} = \log \pi_\theta(y_{i,t} | y_{i,<t}, q_i), \quad \tau_{i,t} = \log \pi_\tau(y_{i,t} | y_{i,<t}, q_i).$$

Standard OPD uses the sampled-token k1 reverse-KL signal

$$A_{i,t}^{\text{OPD}} = \tau_{i,t} - s_{i,t}, \quad (1)$$

treated as a stop-gradient advantage on the student’s own rollout. Conceptually, all variants optimize the same token-level policy-gradient objective,

$$\mathcal{L}_{\text{PG}}(\theta; A) = -\mathbb{E}_{q_i, y_i} \left[\frac{1}{T_i} \sum_{t=1}^{T_i} \log \pi_\theta(y_{i,t} | y_{i,<t}, q_i) \text{sg}[A_{i,t}] \right], \quad (2)$$

implemented with clipped importance ratios (Schulman et al. 2017) to the rollout policy. Standard OPD sets $A_{i,t} = A_{i,t}^{\text{OPD}}$; the privilege variants below modify only this advantage. The teacher need not be larger: the same formulation supports on-policy self-distillation (OPSD) (Zhao et al. 2026) by using a frozen copy of the student’s initial policy under a different conditioning context.

A practical subtlety is that teacher and student consume different multimodal prompts once teacher-side privilege is introduced, so their prompt lengths differ. We therefore extract teacher log-probabilities over the *response tokens only* and align them to the student’s generated tokens, decoupling teacher-side context from token-level supervision.

From Giving to Gating Teacher Privilege. Beyond “how strong is the teacher,” we ask “what is the teacher given”—and how its predictive distribution changes under that condition. We call a teacher condition *clip-grounded* when its content is generated from the same training clip rather than copied from an answer-side oracle; the stored answer is used only to reject potentially leaking cue candidates. This definition concerns training-time provenance: the cue text itself is teacher-only and is never available during causal recent-window inference. We first review conditions that only *supply* privilege, then present **Spatio-Temporal CueGate (ST-CueGate)**, which computes a likelihood-based sensitivity proxy and uses it to reweight OPD. All variants share an identical backbone, dataset, and optimizer, so differences are attributable to the teacher condition alone. For the extrapolation baseline we also use $b_{i,t}$, the token log-probability under the frozen student initialization.

Ungrounded Baselines. *Reward extrapolation* (ExOPD) tries to exceed the teacher by extrapolating its improvement over the base by a factor $\lambda \geq 1$,

$$A_{i,t}^{\text{ExOPD}} = -[(s_{i,t} - b_{i,t}) - \lambda(\tau_{i,t} - b_{i,t})], \quad (3)$$

with $\lambda = 1$ recovering standard OPD. This baseline manipulates the learning signal without conditioning it on an observation available to the student. Additional ungrounded reweighting controls are deferred to the appendix.

Passive Cue Conditioning. ViCuR (Tian et al. 2026) treats visual cues as recoverable teacher privilege and additionally




Figure 3: Distribution and concentration of the cue-conditional log-likelihood ratio over 300,866 student-response tokens. (a) Most token scores are near zero, while the remaining distribution is heavy-tailed and includes both positive and negative shifts. (b) The top 20% of positive-score tokens account for 82% of the total positive mass.

trains a student-side cue recovery module. To isolate teacher-side conditioning while keeping the student fixed, we use its cue-only variant, denoted *ViCuR (cue-only)*: a short, automatically screened spatio-temporal cue is appended only to the teacher prompt. This baseline supplies the cue uniformly; ST-CueGate instead measures the cue-induced teacher shift on each student response and gates distillation by that contrast.

ST-CueGate: Nested Cue-Removal Gating. Passive conditioning assumes that the cue benefits every rollout equally. ST-CueGate instead measures its contribution on the student’s own response (Fig. 2). Given an automatically accepted spatio-temporal cue c_i , the frozen teacher scores the same response under two conditioning contexts:

$$\begin{aligned}\tau_{i,t}^+ &= \log \pi_\tau(y_{i,t} \mid y_{i,<t}, q_i, c_i), \\ \tau_{i,t}^- &= \log \pi_\tau(y_{i,t} \mid y_{i,<t}, q_i).\end{aligned}\quad (4)$$

The cue-augmented score $\tau_{i,t}^+$ is the distillation target used by both cue-only *ViCuR* and ST-CueGate, i.e., $\tau_{i,t} = \tau_{i,t}^+$ in Eq. 1. The no-cue score $\tau_{i,t}^-$ is used only to form the token-level conditional contrast,

$$\begin{aligned}\Delta_{i,t} &= \tau_{i,t}^+ - \tau_{i,t}^- \\ &= \log \frac{\pi_\tau(y_{i,t} \mid y_{i,<t}, q_i, c_i)}{\pi_\tau(y_{i,t} \mid y_{i,<t}, q_i)}.\end{aligned}\quad (5)$$

A positive $\Delta_{i,t}$ means that the cue increases the frozen teacher’s confidence in the realized token $y_{i,t}$. This is a point-wise conditional log-likelihood ratio between two nested contexts that hold the teacher, frames, question, prefix, and token fixed. Empirically, this teacher-side contrast is highly non-uniform (Fig. 3): 56.5% of tokens have near-zero scores ($|\Delta| \leq 0.01$), 23.1% have negative scores, and the top 20% of positive-score tokens carry 82% of the total positive mass. This concentration motivates measuring cue sensitivity before reweighting.

We aggregate the token-level contrast into a length-normalized response proxy,

$$\begin{aligned}g_i &= \frac{1}{T_i} \sum_{t=1}^{T_i} \Delta_{i,t} \\ &= \frac{1}{T_i} \log \frac{\pi_\tau(y_i \mid q_i, c_i)}{\pi_\tau(y_i \mid q_i)}.\end{aligned}\quad (6)$$

which summarizes the cue-induced shift in the teacher’s likelihood of the same realized response. We then standardize it over a comparison group $\mathcal{G}(i)$. For $n=1$, $\mathcal{G}(i)$ is the mini-batch; for $n>1$, it can be the sibling rollouts sharing the same prompt. Using population statistics,

$$\begin{aligned}\mu_{\mathcal{G}} &= \frac{1}{|\mathcal{G}|} \sum_{j \in \mathcal{G}(i)} g_j, \\ \sigma_{\mathcal{G}} &= \sqrt{\frac{1}{|\mathcal{G}|} \sum_{j \in \mathcal{G}(i)} (g_j - \mu_{\mathcal{G}})^2}, \\ \tilde{g}_i &= \frac{g_i - \mu_{\mathcal{G}}}{\sigma_{\mathcal{G}} + \epsilon}, \\ w_i &= \text{sg}[\text{clip}(1 + \alpha_g \tilde{g}_i, w_{\min}, w_{\max})], \\ A_{i,t}^{\text{ST-CueGate}} &= w_i(\tau_{i,t}^+ - s_{i,t}).\end{aligned}\quad (7)$$

Responses with an above-group-mean score receive $w_i > 1$, while below-mean responses receive $w_i < 1$. This ranking is relative, not absolute: if every g_j in a group is negative, a less-negative response can still be up-weighted. Moreover, although $\Delta_{i,t}$ is computed per token, ST-CueGate applies one scalar w_i to every OPD token advantage in the response; it therefore does not localize which tokens benefit from the cue. Averaging removes first-order scaling with token count but remains sensitive to response composition, formatting tokens, and teacher calibration. We consequently interpret g_i as a likelihood-based relative cue-sensitivity proxy rather than faithful utility attribution. We use $\alpha_g = 0.5$ and $[w_{\min}, w_{\max}] = [0, 2]$; a singleton comparison group is assigned the neutral gate $w_i = 1$. Setting $\alpha_g = 0$ yields $w_i \equiv 1$ and therefore the same distillation gradient as cue-only *ViCuR*. The no-cue forward reuses the student’s decoded frames and the same teacher pool, adding no GPU allocation; it affects training only through w_i .

Training Data and Visual Cues. We construct an approximately 25k-item training set of verifiable video questions in MCQ, binary, and counting formats from public instruction data (Zhang et al. 2024b; Yuan et al. 2025). A stronger frozen VLM processes each complete short training clip and generates a spatio-temporal pointer after answer options are removed from its input. Rule-based screening, regeneration, and a deterministic judging pass by the same generator model automatically accept $\sim 96.6\%$ of cues; rejected samples fall back to the original teacher prompt. To complement this correlated self-check, two annotators jointly review a random sample of 300 accepted cues and flag 3 direct-answer leaks, 4 indirect semantic leaks, and 6 visually unsupported or incorrectly grounded pointers, i.e. a residual leakage rate of 7/300




Figure 4: Prompt formats for ST-CueGate. The student receives the original video question, while the teacher additionally receives an automatically screened spatio-temporal cue. ST-CueGate also scores the same response under the original no-cue prompt.

among accepted cues. The cue is added only to the teacher through the explicit instruction template in Fig. 4; the student prompt and inference protocol remain unchanged. Full construction, model choice, and audit details are provided in the Supplementary Material.

Experiments

Setup. We use a Qwen3.5-4B student and Qwen3.5-9B teacher. Both train in thinking mode with the OPD objective (Eq. 1) and deploy in instruct mode. Each in-house configuration is trained with three independent seeds; within a run we select a single model on a held-out validation aggregate and evaluate that same model on all four benchmarks, and reported entries are means over the three runs. StreamingBench (Lin et al. 2026) and OVO-Bench (Niu et al. 2025) use recent-4 frames at 1 fps; Video-MME (Fu et al. 2025) and LongVideoBench (Wu et al. 2024) use their standard protocols with at most 32 frames. All evaluations use greedy decoding, and OVO is reported with and without HLD. Full training, implementation, and statistical details are provided in the Supplementary Material.

StreamOPD Core Recipe Under Fixed Recent-Window Inference. Table 1 shows that standard OPD closes most of the 4B–9B gap under unchanged inference: StreamingBench rises from 77.9% to 83.9%, and OVO-Bench excluding HLD improves by 9.1 points. The gains span both real-time perception and backward tracing, but they are unevenly distributed across subtasks: STU (+20.7) and OCR (+13.4) improve most, the remaining real-time subtasks gain between 3.0 and 9.2 points, and backward tracing improves on both EPM (+9.1) and ASI (+7.4). LongVideoBench improves modestly and Video-MME slips slightly below the base model. HLD moves in the opposite direction, indicating that dense teacher supervision strengthens answerable-task competence but can weaken abstention; we therefore report it separately following SimpleStream (Shen et al. 2026).

Training–Deployment Mode Decoupling and Stability. Because the backbone is a unified thinking/instruct model, we can decouple the training configuration from the response mode used at deployment. Among the tested pairings, both-instruct and teacher-thinking/student-instruct training collapse, whereas both-thinking training converges. This comparison jointly changes response length, policy distributions, and teacher–student alignment; it therefore establishes mode-dependent instability in our setting but not response length as its sole cause. We train OPD with both policies in thinking mode and evaluate the same distilled policy in both decoding modes. Instruct-mode evaluation performs better while preserving concise option-format outputs, matching the benchmark’s direct-answer format. We use this empirically selected train-thinking / deploy-instruct pairing throughout.

GRPO Format Drift: A Response-Format Diagnostic.

Without a teacher, GRPO drifts from concise answers to long rationales that place the answer at the end. It therefore appears strong under the reward’s last-letter parser but fails under the deployed first-answer parser: the same checkpoint scores 82.4% under the former and only 35.1% under the latter, while its median response length grows more than tenfold over training. Distilled models remain concise and parser-invariant, indicating that dense supervision anchors response format as well as answer content; detailed diagnostics are provided in the Supplementary Material.

Teacher-Privilege Extension: ST-CueGate. With the core recipe fixed, we next ask whether *the way the teacher is conditioned* can improve axes left unresolved by standard OPD. Table 2 compares teacher-side conditioning and gating designs on the same 25k data pool. Ungrounded extrapolation and passive cue conditioning do not consistently improve the four benchmarks, motivating a cue-specific gate. Additional controls are reported in the Supplementary Material.

ST-CueGate improves all four benchmarks over both $n=1$ and rollout-matched $n=4$ OPD. Against the latter, the gains are +0.7, +1.8, +0.8, and +0.2 points, raising the cross-benchmark mean from 69.81 to 70.69. The largest improvement occurs on OVO-Bench, suggesting that cue-specific reweighting is especially useful when answers depend on locating temporal evidence. ST-CueGate also exceeds cue-only ViCuR on all four benchmarks, showing that the gain comes from selectively weighting cue-conditioned supervision rather than from supplying the cue alone. Reading the table against the untrained student in its first row exposes a cost that the streaming numbers alone hide: every other variant trades general-video ability for streaming gains and ends up below the base model on Video-MME, whereas ST-CueGate is the only configuration that stays above the base on all four benchmarks.

The per-subtask breakdown in Table 1 shows that gating does more than move the student closer to its teacher. ST-CueGate exceeds the 9B teacher on six of the nine OVO-Bench subtasks—OCR, ACR, STU, FPD, EPM, and ASI, by 1.1 to 4.0 points—as well as on the OVO-Bench macro (69.34 versus 67.95) and on StreamingBench (84.55 versus 84.15). The residual teacher advantage is concentrated in ATR, OJR, and HLD. A 4B student can therefore overtake the 9B teacher

Model	#Frames	Streaming Bench	OVO-Bench											
			Real-Time Visual Perception								Backward Tracing			
			OCR	ACR	ATR	STU	FPD	OJR	Avg.	EPM	ASI	HLD	Avg.	
Human	–	91.46	94.0	92.6	94.8	92.7	91.1	94.0	93.2	92.6	93.0	91.4	92.3	92.77
Offline Video LLMs														
Qwen2.5-VL-7B (Bai et al. 2025)	1 fps	73.31	67.8	55.1	67.2	42.1	66.3	60.9	59.9	51.5	58.8	23.7	44.7	52.28
LLaVA-OneVision-7B (Li et al. 2024)	32	71.12	66.4	57.8	73.3	53.4	71.3	62.0	64.0	54.2	55.4	21.5	43.7	53.85
LLaVA-Video-7B (Zhang et al. 2024b)	64	–	69.1	58.7	68.8	49.4	74.3	59.8	63.5	<u>56.2</u>	57.4	7.5	40.4	51.95
LongVU-7B (Shen et al. 2024)	1 fps	–	55.7	49.5	59.5	48.3	68.3	63.0	57.4	43.1	66.2	9.1	39.5	48.45
Online / Streaming Video LLMs														
Dispider-7B (Qian et al. 2025)	1 fps	67.63	57.7	49.5	62.1	44.9	61.4	51.6	54.6	48.5	55.4	4.3	36.1	45.35
TimeChat-Online-7B (Yao et al. 2025)	1 fps	75.28	75.2	46.8	70.7	47.8	69.3	61.4	61.9	55.9	59.5	9.7	41.7	51.80
StreamForest-7B (Zeng et al. 2026)	1 fps	77.26	68.5	53.2	71.6	47.8	65.4	60.9	61.2	58.9	64.9	32.3	52.0	56.60
HERMES-7B [†] (Zhang et al. 2026)	1 fps	79.44	85.2	64.2	71.6	53.4	74.3	65.2	69.0	48.5	62.2	37.6	49.4	59.20
Post-Trained Models and References (STREAMOPD, Ours)														
Qwen3.5-9B (teacher)	4	<u>84.15</u>	<u>95.3</u>	78.0	87.9	70.8	<u>74.3</u>	85.9	<u>82.0</u>	54.9	59.5	47.3	53.9	<u>67.95</u>
Qwen3.5-4B (student)	4	77.87	81.9	67.9	78.5	52.3	68.3	75.0	70.6	47.1	51.4	47.9	48.8	59.71
+ OPD	4	83.91	<u>95.3</u>	77.1	<u>84.5</u>	73.0	71.3	82.1	80.5	56.2	58.8	38.7	51.2	65.89
+ ST-CueGate (OPD)	4	84.55	98.0	80.7	83.6	<u>71.9</u>	76.2	<u>85.3</u>	82.6	58.9	63.5	45.7	56.0	69.34
+ ST-CueGate (OPSD)	4	83.35	93.3	74.3	82.8	71.4	<u>74.3</u>	79.4	79.2	54.2	56.8	57.0	56.0	67.60

Table 1: Main results on OVO-Bench (Niu et al. 2025) and StreamingBench (Lin et al. 2026). We report OVO-Bench per-task accuracy under its Real-Time and Backward tracks; “Avg.” is their mean and “–” denotes unreported results. All STREAMOPD models are evaluated in instruct mode with a recent-4-frame window. ST-CueGate (OPD) uses the 9B teacher, while ST-CueGate (OPSD) (Zhao et al. 2026) uses the frozen 4B initial policy; [†] denotes Qwen2.5-VL-7B + HERMES (4K tokens).

that supervises it on most streaming subtasks, which is consistent with on-policy supervision shaping the student along its own trajectory distribution rather than transferring a fixed teacher ceiling. The exception is again abstention. The post-trained 4B model also compares favorably with the larger streaming systems in Table 1: it exceeds HERMES-7B, the strongest listed streaming design, by 5.1 points on StreamingBench and 10.1 points on the OVO-Bench macro, while operating on a strictly memory-free four-frame context.

To test portability beyond larger-teacher OPD, we also instantiate the $n=4$ ST-CueGate configuration within OPSD using a frozen 4B same-backbone teacher. Without a larger model, this variant reaches 83.35% on StreamingBench and 67.35% on OVO-Bench excluding HLD, so ST-CueGate is compatible with self-distillation rather than being tied to teacher scale. It also attains the highest HLD score in Table 1 at 57.0%, above both the untrained student (47.9%) and the 9B teacher (47.3%). The abstention loss seen under larger-teacher distillation is therefore not intrinsic to the recipe, and does not appear in our same-backbone instantiation.

The unifying pattern is *clip-grounded provenance with a cue-specific reference*. Injecting a signal unanchored to the training video does not help, while grounded privilege remains insufficient when supplied passively. ST-CueGate instead holds the frames and realized trajectory fixed while removing only the cue; this reference performs better than a shuffled-video negative view.

Table 3 shows that response-level $n=4$ gating performs best on StreamingBench, OVO-Bench, and

LongVideoBench, whereas $n=1$ slightly favors Video-MME. Token-wise gating loses most on OVO-Bench (-3.2) and LongVideoBench (-1.4), suggesting that individual token contrasts are too noisy to serve as independent weights; aggregating them at the response level provides a more stable signal.

Table 4 varies the gate strength: $\alpha_g = 0.5$ gives the highest result on all four benchmarks. Increasing the strength to 1.0 consistently hurts performance, indicating that the likelihood contrast is most useful as a moderate ranking signal rather than an aggressively amplified weight.

Table 5 varies teacher scale with the student fixed. The larger teacher is worse on all four benchmarks, with the smallest deficit on StreamingBench (-1.0) and the largest on LongVideoBench (-7.0). This run reuses the 9B optimization and gate settings without re-tuning, so it should be read as evidence that teacher scale alone does not guarantee better on-policy supervision, not as a tuned upper bound for a 27B teacher: a closer-capacity teacher may provide token distributions better aligned with the student’s trajectories, while a larger teacher may require different optimization or gating calibration.

Related Work

Streaming Video Understanding. Unlike offline video MLLMs that process complete clips (Qwen Team 2026; Bai et al. 2023; Wang et al. 2024; Bai et al. 2025; Zhang et al. 2024b), streaming models operate on a causal video prefix. Prior systems rely on memory, retrieval, or KV-cache com-

Method	Grounded	StreamingBench	OVO-Bench (excl. HLD)	Video-MME	LongVideoBench	Avg.
Qwen3.5-4B (student)	–	77.87	59.94	64.22	57.74	64.94
OPD ($n=1$)	–	83.91	69.02	63.33	59.84	69.03
OPD ($n=4$)	–	83.83	70.09	64.07	61.26	69.81
ExOPD ($n=1$)	✗	84.29	68.38	63.78	60.36	69.20
ViCuR (cue-only, $n=1$)	✓	84.27	67.98	60.56	54.00	66.70
ViCuR (cue-only, $n=4$)	✓	84.49	67.86	64.11	60.73	69.30
V-Zero ($n=4$)	✓	83.99	67.71	61.67	60.06	68.36
ST-CueGate ($n=4$)	✓*	84.55	71.93	64.85	61.41	70.69

Table 2: Ablation of teacher conditioning and cue gating on the 25k data pool. The first row is the untrained student. “ViCuR (cue-only)” retains only ViCuR’s teacher-side visual cue, without its student recovery module (Tian et al. 2026); our video implementation of V-Zero (Sun et al. 2026) uses a temporally shuffled video as the negative evidence view. Grounded denotes a teacher-side signal derived from the same underlying training clip; * denotes nested cue-removal gating. The OVO-Bench column excludes HLD; raw HLD and the full macro are reported separately in Table 1. Avg. is the unweighted mean over the four benchmarks.

Gate Setting	Streaming Bench	OVO-Bench (excl. HLD)	Video-MME	LongVideo Bench	Avg.
$n=1$, batch, seq.	84.23	68.93	65.11	59.69	69.49
$n=4$, uid, seq.	84.55	71.93	64.85	61.41	70.69
$n=4$, uid, token	84.23	68.72	63.52	59.99	69.12
$n=8$, uid, seq.	84.11	68.81	64.41	60.66	69.50

Table 3: Ablation of ST-CueGate rollout grouping and gate granularity on the 25k data pool. “seq.” denotes one response-level gate; “token” denotes token-wise gates. Avg. is the unweighted mean over the four benchmarks.

α_g	Streaming Bench	OVO-Bench (excl. HLD)	Video-MME	LongVideo Bench	Avg.
0.25	84.19	69.09	64.19	60.73	69.55
0.50	84.55	71.93	64.85	61.41	70.69
1.00	84.39	68.97	63.22	59.76	69.09

Table 4: Ablation of the ST-CueGate strength α_g with fixed $n=4$, UID sibling normalization, $\gamma=1$, and gate range $[0, 2]$. Avg. is the unweighted mean over the four benchmarks.

pression (Chen et al. 2024; Zhang et al. 2024a; Qian et al. 2025; Yao et al. 2025; Zeng et al. 2026; Zhang et al. 2026; Xiao et al. 2024), with StreamingBench and OVO-Bench evaluating real-time and historical reasoning (Lin et al. 2026; Niu et al. 2025). SimpleStream (Shen et al. 2026) shows that a recent-window baseline can match heavier designs, whereas ThinkStream (Liu et al. 2026) combines memory with online reasoning.

On-Policy Distillation and Teacher Privilege. Classical distillation uses teacher targets on fixed data (Hinton, Vinyals, and Dean 2015), whereas OPD scores student-generated trajectories (Agarwal et al. 2024; Gu et al. 2024) and has been extended to text reasoning (Zhao et al. 2026), multimodal pre-alignment (Wang et al. 2026), and temporal video grounding (Li et al. 2026). Privileged-information methods provide training-only side information (Vapnik and

Teacher	Streaming Bench	OVO-Bench (excl. HLD)	Video-MME	LongVideo Bench	Avg.
Qwen3.5-9B	84.55	71.93	64.85	61.41	70.69
Qwen3.5-27B	83.59	67.52	61.04	54.38	66.63

Table 5: Ablation of teacher model size for ST-CueGate with a fixed Qwen3.5-4B student. Avg. is the unweighted mean over the four benchmarks.

Izmailov 2015; Lopez-Paz et al. 2015), with recent work exploring visual-cue privilege and contrastive evidence gating (Tian et al. 2026; Sun et al. 2026). V-Zero contrasts question-relevant evidence with a negative visual view to gate answer-label-free OPD. ST-CueGate shares the response-level contrastive reweighting structure, but uses a nested cue-removal reference that holds the frames, question, and realized student trajectory fixed and changes only the teacher-side spatio-temporal cue.

Conclusion

Under a fixed memory-free recent-window protocol, we isolate post-training from added inference machinery. Our study exposes two empirical failure modes: teacher-free GRPO drifts toward verbose, deployment-incompatible responses, while the tested OPD configurations involving instruct-mode training collapse. Together with the 25k verifiable-data pipeline and thinking-train/instruct-infer configuration, these diagnostics form the StreamOPD core recipe. Standard OPD places the 4B student within 0.3 points of the 9B teacher on StreamingBench and substantially improves OVO-Bench under unchanged inference. As a teacher-privilege extension, ST-CueGate uses a nested cue-removal likelihood ratio to form a group-relative response proxy while keeping the student architecture fixed, yielding additional gains on OVO-Bench and Video-MME. Its successful same-backbone OPSD instantiation further shows that the mechanism is not tied to a larger teacher. We hope STREAMOPD serves as a transparent empirical foundation and open-source reference for reproducible streaming-video post-training.

References

- Agarwal, R.; Vieillard, N.; Zhou, Y.; Stanczyk, P.; Ramos Garea, S.; Geist, M.; and Bachem, O. 2024. On-policy distillation of language models: Learning from self-generated mistakes. In *International Conference on Learning Representations*, volume 2024, 21246–21263.
- Bai, J.; Bai, S.; Yang, S.; Wang, S.; Tan, S.; Wang, P.; Lin, J.; Zhou, C.; and Zhou, J. 2023. Qwen-vl: A versatile vision-language model for understanding, localization. *Text Reading, and Beyond*, 2(1): 1.
- Bai, S.; Chen, K.; Liu, X.; Wang, J.; Ge, W.; Song, S.; Dang, K.; Wang, P.; Wang, S.; Tang, J.; Zhong, H.; Zhu, Y.; Yang, M.; Li, Z.; Wan, J.; Wang, P.; Ding, W.; Fu, Z.; Xu, Y.; Ye, J.; Zhang, X.; Xie, T.; Cheng, Z.; Zhang, H.; Yang, Z.; Xu, H.; and Lin, J. 2025. Qwen2.5-VL Technical Report. *arXiv:2502.13923*.
- Chen, J.; Lv, Z.; Wu, S.; Lin, K. Q.; Song, C.; Gao, D.; Liu, J.-W.; Gao, Z.; Mao, D.; and Shou, M. Z. 2024. Videollm-online: Online video large language model for streaming video. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 18407–18418.
- Fu, C.; Dai, Y.; Luo, Y.; Li, L.; Ren, S.; Zhang, R.; Wang, Z.; Zhou, C.; Shen, Y.; Zhang, M.; et al. 2025. Videomme: The first-ever comprehensive evaluation benchmark of multi-modal llms in video analysis. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 24108–24118.
- Gu, Y.; Dong, L.; Wei, F.; and Huang, M. 2024. Minillm: Knowledge distillation of large language models. In *International Conference on Learning Representations*, volume 2024, 32694–32717.
- Guo, D.; Yang, D.; Zhang, H.; Song, J.; Wang, P.; Zhu, Q.; Xu, R.; Zhang, R.; Ma, S.; Bi, X.; et al. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.
- Hinton, G.; Vinyals, O.; and Dean, J. 2015. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*.
- Kwon, W.; Li, Z.; Zhuang, S.; Sheng, Y.; Zheng, L.; Yu, C. H.; Gonzalez, J.; Zhang, H.; and Stoica, I. 2023. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 29th symposium on operating systems principles*, 611–626.
- Lambert, N.; Morrison, J.; Pyatkin, V.; Huang, S.; Ivison, H.; Brahman, F.; Miranda, L. J. V.; Liu, A.; Dziri, N.; Lyu, S.; et al. 2024. Tulu 3: Pushing frontiers in open language model post-training. *arXiv preprint arXiv:2411.15124*.
- Li, B.; Zhang, Y.; Guo, D.; Zhang, R.; Li, F.; Zhang, H.; Zhang, K.; Zhang, P.; Li, Y.; Liu, Z.; et al. 2024. Llava-onevision: Easy visual task transfer. *arXiv preprint arXiv:2408.03326*.
- Li, J.; Yin, H.; Xu, H.; Xu, B.; Tan, W.; He, Z.; Ju, J.; Luo, Z.; and Luan, J. 2026. Video-OPD: Efficient Post-Training of Multimodal Large Language Models for Temporal Video Grounding via On-Policy Distillation. *arXiv preprint arXiv:2602.02994*.
- Lin, J.; Fang, Z.; Chen, C.; Cheng, H.; Wan, Z.; Luo, F.; Wang, Z.; Li, P.; Liu, Y.; and Sun, M. 2026. Streaming-bench: Assessing the gap for mllms to achieve streaming video understanding. In *ICASSP 2026-2026 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 12147–12151. IEEE.
- Liu, Z.; Guo, L.; Li, H.; Zhen, R.; He, X.; Ji, R.; Ren, X.; Zhang, Y.; Lu, H.; and Liu, J. 2026. Thinking in streaming video. *arXiv preprint arXiv:2603.12938*.
- Lopez-Paz, D.; Bottou, L.; Schölkopf, B.; and Vapnik, V. 2015. Unifying distillation and privileged information. *arXiv preprint arXiv:1511.03643*.
- Niu, J.; Li, Y.; Miao, Z.; Ge, C.; Zhou, Y.; He, Q.; Dong, X.; Duan, H.; Ding, S.; Qian, R.; et al. 2025. Ovo-bench: How far is your video-llms from real-world online video understanding? In *Proceedings of the Computer Vision and Pattern Recognition Conference*, 18902–18913.
- Qian, R.; Ding, S.; Dong, X.; Zhang, P.; Zang, Y.; Cao, Y.; Lin, D.; and Wang, J. 2025. Dispider: Enabling video llms with active real-time interaction via disentangled perception, decision, and reaction. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, 24045–24055.
- Qwen Team. 2026. Qwen3.7: The Agent Frontier.
- Schulman, J.; Wolski, F.; Dhariwal, P.; Radford, A.; and Klimov, O. 2017. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.
- Shao, Z.; Wang, P.; Zhu, Q.; Xu, R.; Song, J.; Bi, X.; Zhang, H.; Zhang, M.; Li, Y.; Wu, Y.; et al. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.
- Shen, X.; Xiong, Y.; Zhao, C.; Wu, L.; Chen, J.; Zhu, C.; Liu, Z.; Xiao, F.; Varadarajan, B.; Bordes, F.; et al. 2024. Longvu: Spatiotemporal adaptive compression for long video-language understanding. *arXiv preprint arXiv:2410.17434*.
- Shen, Y.; Tian, S.; Yang, J.; and Liu, Z. 2026. A simple baseline for streaming video understanding. *arXiv preprint arXiv:2604.02317*.
- Sheng, G.; Zhang, C.; Ye, Z.; Wu, X.; Zhang, W.; Zhang, R.; Peng, Y.; Lin, H.; and Wu, C. 2025. Hybridflow: A flexible and efficient rlhf framework. In *Proceedings of the Twentieth European Conference on Computer Systems*, 1279–1297.
- Sun, H.; Yi, Z.; Deng, L.; Zhou, Y.; Jia, P.; Zhao, J.; Yuan, L.; Lv, J.; and Wang, T. 2026. V-Zero: Answer-Label-Free On-Policy Distillation with Contrastive Evidence Gating for Fine-Grained Visual Reasoning. *arXiv preprint arXiv:2606.25319*.
- Team, Q. 2026. Qwen3.5: Accelerating Productivity with Native Multimodal Agents.
- Tian, K.; Liu, S.; Yan, Z.; Xia, S.; Dong, S.; and Wang, Y. 2026. ViCuR: Visual Cues as Recoverable Privilege for Multimodal On-Policy Distillation. *arXiv preprint arXiv:2606.05718*.
- Vapnik, V.; and Izmailov, R. 2015. Learning using privileged information: similarity control and knowledge transfer. *The Journal of Machine Learning Research*, 16(1): 2023–2049.

Wang, P.; Bai, S.; Tan, S.; Wang, S.; Fan, Z.; Bai, J.; Chen, K.; Liu, X.; Wang, J.; Ge, W.; et al. 2024. Qwen2-vl: Enhancing vision-language model’s perception of the world at any resolution. *arXiv preprint arXiv:2409.12191*.

Wang, S.; Huang, W.; Yu, X.; Yang, Z.; Lin, H.; Wu, K.; Xiao, C.; Chen, C.; Wang, W.; Zhu, B.; et al. 2026. Beyond SFT-to-RL: Pre-alignment via Black-Box On-Policy Distillation for Multimodal RL. *arXiv preprint arXiv:2604.28123*.

Wu, H.; Li, D.; Chen, B.; and Li, J. 2024. Longvideobench: A benchmark for long-context interleaved video-language understanding. *Advances in Neural Information Processing Systems*, 37: 28828–28857.

Xiao, G.; Tian, Y.; Chen, B.; Han, S.; and Lewis, M. 2024. Efficient streaming language models with attention sinks. In *International Conference on Learning Representations*, volume 2024, 21875–21895.

Yang, Z.; Wang, S.; Zhang, K.; Wu, K.; Leng, S.; Zhang, Y.; Li, B.; Qin, C.; Lu, S.; Li, X.; et al. 2025. LongVT: Incentivizing “Thinking with Long Videos” via Native Tool Calling. *arXiv preprint arXiv:2511.20785*.

Yang, Z.; Zhang, K.; Wang, S.; Wu, K.; Yang, Z.; Li, B.; Qi, X.; Lu, S.; Li, X.; and Bing, L. 2026. ParaVT: Taming the Tool Prior Paradox for Parallel Tool Use in Agentic Video Reinforcement Learning. *arXiv preprint arXiv:2605.20342*.

Yao, L.; Li, Y.; Wei, Y.; Li, L.; Ren, S.; Liu, Y.; Ouyang, K.; Wang, L.; Li, S.; Li, S.; et al. 2025. Timechat-online: 80% visual tokens are naturally redundant in streaming videos. In *Proceedings of the 33rd ACM International Conference on Multimedia*, 10807–10816.

Yuan, L.; Wang, J.; Sun, H.; Zhang, Y.; and Lin, Y. 2025. Tarsier2: Advancing large vision-language models from detailed video description to comprehensive video understanding. *arXiv preprint arXiv:2501.07888*.

Zeng, X.; Qiu, K.; Zhang, Q.; Li, X.; Wang, J.; Li, J.; Yan, Z.; Tian, K.; Tian, M.; Zhao, X.; et al. 2026. Streamforest: Efficient online video understanding with persistent event memory. *Advances in Neural Information Processing Systems*, 38: 75804–75835.

Zhang, H.; Wang, Y.; Tang, Y.; Liu, Y.; Feng, J.; Dai, J.; and Jin, X. 2024a. Flash-vstream: Memory-based real-time understanding for long video streams. *arXiv preprint arXiv:2406.08085*.

Zhang, H.; Yang, S.; Fu, J.; Ng, S. K.; and Qiu, X. 2026. Hermes: Kv cache as hierarchical memory for efficient streaming video understanding. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 8411–8430.

Zhang, K.; Wu, K.; Yang, Z.; Li, B.; Hu, K.; Wang, B.; Liu, Z.; Li, X.; and Bing, L. 2025. OpenMMReasoner: Pushing the Frontiers for Multimodal Reasoning with an Open and General Recipe. *arXiv preprint arXiv:2511.16334*.

Zhang, Y.; Wu, J.; Li, W.; Li, B.; Ma, Z.; Liu, Z.; and Li, C. 2024b. Llava-video: Video instruction tuning with synthetic data. *arXiv preprint arXiv:2410.02713*.

Zhao, S.; Xie, Z.; Liu, M.; Huang, J.; Pang, G.; Chen, F.; and Grover, A. 2026. Self-Distilled Reasoner: On-Policy

Self-Distillation for Large Language Models. *arXiv preprint arXiv:2601.18734*.

Parameter	Value
Student / teacher	Qwen3.5-4B / Qwen3.5-9B
Training / evaluation mode	thinking / instruct
Training visual input	default 2 fps; no explicit frame cap
Training data	25,118 cueinstruct samples
Epochs	4
Random seeds	42, 43, 44
Batch / mini-batch size	32 / 32
Learning rate	1×10^{-6}
Rollouts per prompt	$n = 4$
Max prompt / response length	16,000 / 512 tokens
Distillation	sampled-token kl + clipped policy gradient; top- $k = 64$
Gate	sequence level; UID grouping; $\alpha_g = 0.5$; $\gamma = 1$; $w \in [0, 2]$
GPU allocation	4 student + 4 teacher NVIDIA H200 GPUs
Checkpoint frequency	every 100 steps

Table 6: Training configuration for the main ST-CueGate experiment.

Implementation and Data Details

Systems Implementation. We build on a HybridFlow-style RL framework (Sheng et al. 2025) with vLLM (Kwon et al. 2023) rollouts, and run all training experiments on NVIDIA H200 GPUs. Four components were customized for video OPD and teacher privilege: (1) response-only teacher log-probability extraction, which aligns teacher and student despite differing prompt lengths; (2) a corrupt-video-tolerant data path that skips unreadable clips; (3) verifiable reward functions for MCQ, binary, and counting formats; and (4) an independent teacher-input builder that supports different frame budgets or prompts. For ST-CueGate, the builder issues the second no-cue teacher forward on the same teacher pool while reusing the student’s decoded frames. Samples are routed to teachers by data source, and all privilege paths default to a no-op when disabled.

Training Configuration. Table 6 lists the configuration used by the main ST-CueGate run. Standard OPD shares the same optimizer, sequence limits, and model pair, but uses $n=1$ and disables teacher-side cue conditioning and gating.

Searched Values and Selection Criterion. Table 7 lists every value we tried per axis together with the setting used in the main results. Axes were explored one at a time from the default configuration rather than through a joint grid search. Selection always uses the held-out validation aggregate; no downstream benchmark score was consulted when choosing a setting.

Same-Backbone OPSD Instantiation. For ST-CueGate-OPSD, we replace the 9B teacher with a frozen copy of the 4B student’s initial policy, following the same-model teacher-student construction of OPSD (Zhao et al. 2026). The frozen copy receives the cue and no-cue teacher contexts, while the updating student retains its original prompt; the remaining training and evaluation settings are unchanged.

Axis	Values tried	Used
Gate strength α_g	0.25, 0.5, 1.0	0.5
Rollouts per prompt n	1, 4, 8	4
Gate granularity	sequence, token	sequence
Comparison group	minibatch, prompt UID	prompt UID
Teacher	Qwen3.5-9B, Qwen3.5-27B, frozen 4B copy	Qwen3.5-9B
Learning rate	1×10^{-6} , 2×10^{-7}	1×10^{-6}
Training pool	8.3k, 20k, 25k, 26k, 57k	25k
ExOPD λ	1.0, 1.25; two-axis	not used
	$\lambda_t=1.5$, $\lambda_c=1.0$	
DAD α_{DAD}	1.0	not used

Table 7: Values explored per hyperparameter and the setting used in the reported runs. Gate range $[w_{\min}, w_{\max}] = [0, 2]$, $\gamma=1$, and four epochs were fixed throughout.

Evaluation Protocol. Table 8 summarizes the per-benchmark settings. All checkpoints are evaluated with instruct-mode greedy decoding. StreamingBench and OVO-Bench use the deployment-aligned recent-window protocol, whereas the two general-video benchmarks follow their standard evaluation settings. For OVO-Bench, we report the full macro, the score excluding HLD, and raw HLD. The separation follows SimpleStream’s observation that HLD tests hallucination robustness rather than episodic event recall (Shen et al. 2026); it does not remove HLD from the deployment analysis.

Model selection uses only a held-out validation aggregate, never downstream test scores. Each run contributes one selected model, and that same model is evaluated on all four benchmarks and all reported subtasks. Distributed checkpoints are merged to Hugging Face format before evaluation. The repository entry points are `scripts/eval_all.sh` for the four benchmark jobs and `scripts/score_all.sh` for aggregation.

Statistical Reporting. Each in-house trained configuration uses seeds 42, 43, and 44. Each run contributes a single model selected on the held-out validation aggregate, which is then evaluated on all four benchmarks, and table entries are arithmetic means over the three selected models. Only aggregate means were retained, so standard deviations and paired significance tests are unavailable. Deterministic greedy decoding removes sampling noise at evaluation but not training or checkpoint variance.

Recent-Window vs. Dense-Uniform Context

We additionally evaluate a single fixed ST-CueGate model under two causal context policies. The main protocol observes the most recent four frames at 1 fps. The dense-uniform protocol instead samples up to 32 frames uniformly from the full visible prefix $[0, t]$, matching the frame-count convention used by standard offline video evaluation. All other decoding and scoring settings are unchanged.

Table 9 reveals a clear perception-memory trade-off. Dense historical context substantially improves backward memory reasoning, especially ASI (+12.17) and EPM

Benchmark	Visual Input	Decoding	Reported Metric
StreamingBench	recent 4 frames at 1 fps	instruct, greedy	answer accuracy
OVO-Bench	recent 4 frames at 1 fps	instruct, greedy	backward+realtime macro, with/without HLD
Video-MME	standard lmms-eval, max 32 frames	instruct, greedy	overall accuracy
LongVideoBench	standard lmms-eval, max 32 frames	instruct, greedy	overall accuracy

Table 8: Evaluation protocols. The recent-window constraint applies to the streaming benchmarks; Video-MME and LongVideoBench use their standard general-video protocols.

Metric	Recent-4	Dense-32	Δ
StreamingBench	84.19	81.15	-3.04
OVO incl. HLD	68.29	63.06	-5.23
OVO excl. HLD	70.48	69.03	-1.45
Backward Avg. incl. HLD	54.47	54.51	+0.04
Backward Avg. excl. HLD	58.85	66.45	+7.60
Realtime Avg.	82.11	71.61	-10.50
EPM	54.47	61.95	+7.48
ASI	58.78	70.95	+12.17
HLD	45.70	30.65	-15.05

Table 9: Context-policy comparison on the same fixed ST-CueGate model. Dense-32 uniformly samples the visible prefix, while Recent-4 retains only the latest four frames. EPM: Episodic Memory; ASI: Action Sequence Identification; HLD: Hallucination Detection.

(+7.48), but dilutes recent-event evidence: the realtime macro drops by 10.50 points and HLD by 15.05 points. StreamingBench likewise decreases by 3.04 points. Thus, dense-uniform context is useful for historical recall but is not uniformly better for streaming; the recent-window protocol deliberately prioritizes current-event perception and deployment efficiency.

Prompt Templates

This section reproduces verbatim every prompt used for training, cue construction, and evaluation. Curly braces mark run-time substitutions.

Student Prompt. The student prompt is identical during training and deployment and never contains a cue.

Student prompt (training and deployment)

```
<video>{question}
A. {option A}
B. {option B}
C. {option C}
D. {option D}

(Binary and counting items carry the question only,
  ↳ with no option block.)
```

Cue-Augmented Teacher Prompt. For cue-only ViCuR and ST-CueGate, the teacher receives the unchanged student content plus an explicit instruction block. The framing follows reference-solution prompting (Zhao et al. 2026), with the reference solution replaced by visual evidence.

Teacher prompt with spatio-temporal cue

```
<video>{question}
A. {option A}
B. {option B}
C. {option C}
D. {option D}

Here is some visual evidence to help you locate the
↳ answer in the video:
{cue}

After considering this visual evidence, identify the
↳ exact moment or region it points to in the video,
↳ verify what actually happens there, then answer
↳ the question using your own judgment.
```

The ST-CueGate no-cue forward reuses this same teacher, the decoded student frames, and the original student prompt. Fallback samples without an accepted cue therefore satisfy $\tau^+ = \tau^-$, $\Delta = 0$, and a neutral gate.

Cue Generator. The generator sees the complete training clip and the question stem after answer options are stripped from its input. Multiple-choice items use the following system prompt.

Cue generator: multiple-choice items

```
You are a video analyst. For a multiple-choice
↳ question about a video, output a POINTER that
↳ tells the student WHEN and WHERE to look --
↳ WITHOUT answering the question.
Think of it as pointing a flashlight: you reveal the
↳ location and moment, never the finding.

ABSOLUTE PROHIBITIONS (any violation = total failure)
↳ :
1. NEVER output an option letter or option text (no '
↳ A)', 'B.', 'E) To ...', and no sentence that
↳ restates any option).
2. NEVER name the specific entity/attribute the
↳ question asks about. If it asks WHO/WHICH PERSON,
↳ don't name the person; if WHERE/POSITION, don't
↳ state the position; if WHAT OBJECT, don't name the
↳ object; if WHAT COLOR, don't say the color; if
↳ WHAT HAPPENS NEXT, don't say the outcome. Refer
↳ only generically ('that person', 'the object in
↳ their hand', 'their position').
3. NEVER quote or transcribe on-screen text, captions
↳ , subtitles, or spoken dialogue. Only say WHEN/
↳ WHERE text appears (e.g. 'a subtitle appears
```

↪ around 0:09'), never its wording.

4. NEVER describe the outcome, result, or a conclusion. Pointer only, no interpretation.

FORMAT: exactly ONE sentence, under 25 words, shape =
 ↪ 'Around <when/which action>, look at <which region/subject>.' No extra clauses, no 'suggesting', no 'indicating'.

GOOD (Q: what color are the sneakers when the hand enters?):
 ↪ 'Around the moment the hand first enters the frame, look at the person's feet.'

GOOD (Q: who places a tile next after the man with glasses?):
 ↪ 'Right after the man with glasses moves, look at the other players seated around the board.'

GOOD (Q: where is the red bowl relative to the pizza?):
 ↪ 'As the woman slices the pizza, look at the area surrounding the cutting board.'

BAD -- all leak, never do these:
 ↪ 'E) To make sure the image is captured.' (option letter+text)
 ↪ 'The girl in the purple shirt.' (names the answer entity)
 ↪ 'To the right of the pizza.' (states the position asked)
 ↪ 'The caption says "Pregnant".' (transcribes text)
 ↪ '...standing together, suggesting they are on a break.' (describes outcome/conclusion)

Binary items embed the queried attribute in the question itself, so any description of the evidence risks touching the answer. They therefore use a stricter variant that degenerates the cue into a pure spatio-temporal pointer.

Cue generator: binary items

You are a video analyst helping a student LOCATE
 ↪ where to look for a yes/no question, WITHOUT answering it.

The question asks whether some attribute/event holds
 ↪ at a moment. Your job is ONLY to point to WHEN and WHO/WHERE to inspect -- NEVER to say whether it holds.

STRICT RULES (violating any = failure):

1. NEVER say yes/no, true/false, is/is not, was/wasn'
 ↪ t, there is/there isn't, correct/incorrect, or any confirmation or denial.
2. NEVER mention the specific attribute the question asks about (e.g. if it asks 'blue helmet', do NOT mention any helmet color; if 'red grinder', do NOT mention any grinder color). Refer to the subject only generically (the helmet, the tool, the person's hand).
3. NEVER describe the state/outcome. Only give a spatio-temporal pointer.
4. Output ONE sentence, under 25 words, of the form:
 ↪ 'Around <when/which action>, look at <who/which region>.'

Good example (Q: Is the child in the red canoe wearing a blue helmet?): "Around the segment showing the child in the red canoe, look closely at the head area."

Bad examples (all leak): "No, the helmet is yellow."
 ↪ / "The child wears a red helmet." / "Yes, there is a blue helmet."

Regeneration and Automatic Judging. When rule-based screening flags a candidate, the generator is re-queried with the original messages, its flagged output, and the instruction below, at temperatures 0.5, 0.7, and 0.9.

Cue regeneration after a flagged candidate

Your previous response LEAKED the answer (it stated or restated an option/answer/color/count/yes-no/on-screen text). Rewrite it as a PURE POINTER: one short sentence 'Around <when/action>, look at <which region/subject>.' Do NOT state or hint the answer, do NOT output any option letter, and do NOT quote on-screen text. Output only the pointer.

A temperature-zero pass of the same model then judges the question-answer-cue tuple and emits a single word.

Automatic leakage judge

You grade whether a HINT leaks the answer to a video question. A good hint ONLY points to WHERE/WHEN to look; it may name a region, object, or moment, but must not reveal the ANSWER.

Judge by this rule:

- SAFE: the hint is a pure pointer of the form 'look at <region/subject> around <when>'. It is still SAFE even if it names the object/person/area being asked about, AS LONG AS it does NOT state the answered attribute (the color, the count, the yes/no, the identity, the outcome, or the on-screen text content).
- LEAK: the hint states or strongly implies the answer -- e.g. gives the color/count/yes-no, names WHICH specific person/object is the answer, quotes the on-screen text that IS the answer, or describes the outcome/next-action the question asks for.

Examples:

Q: where is the chair relative to the basket? Hint:
 ↪ 'look at the object directly underneath the basket.' -> SAFE (points to a location to inspect, does not state the spatial answer)

Q: what does the on-screen text say? Hint: "the text 'Pregnant' is visible" -> LEAK (quotes the answer text)

Q: what happens next? Hint: 'she rolls forward and rises, preparing for the next drill' -> LEAK (describes the outcome asked)

Q: next action of the bull? Hint: 'look at the bull's body orientation and the man's posture' -> SAFE (points to what to observe, does not state the action)

```
Reply with EXACTLY one word: LEAK or SAFE.
```

```
--- user message ---
Question: {question}
Correct answer: {ground truth}
Hint: {cue}

Verdict (LEAK or SAFE):
```

Evaluation Prompts. StreamingBench items are presented with an explicit direct-answer instruction.

Evaluation: StreamingBench

```
You are an advanced video question-answering AI
→ assistant. You have been provided with some frames
→ from the video and a multiple-choice question.
→ Your task is to analyze the video and provide the
→ best answer.

Question: {question}

Options:
{options}

Only give the best option's letter (A, B, C, or D)
→ directly.
```

The OVO-Bench backward-tracing and real-time subtasks use a shorter template with the same direct-answer constraint.

Evaluation: OVO-Bench backward and real-time subtasks

```
{question}
Options: {options}
Only give the best option's letter directly.
```

Video-MME and LongVideoBench keep the unmodified Imms-eval prompts of their standard protocols.

Cue Construction and Screening

Offline Cue Generation. The cue pipeline accepts any sufficiently strong frozen video-language model as its generator; we use Qwen3.5-72B in our implementation. The generator processes the complete short training clip and produces one spatio-temporal pointer per sample. It is instructed to output a single sentence of at most 25 words in the form “Around {when/action}, look at {region/subject},” without option letters, answer entities or attributes, quoted on-screen text, binary labels, or outcome descriptions. Thus, the cue is grounded at the level of the underlying training clip; it is not generated from the recent-4-frame evaluation window and is never provided at deployment.

Leakage Taxonomy, Automatic Screening, and Manual Audit. We operationally treat a cue as leaking if it reveals the answer without requiring the intended visual inspection. The audit taxonomy covers (1) exact answer strings or option identifiers, (2) synonyms and semantic paraphrases, (3) discriminative attributes such as color, count, identity, or position, (4) event or outcome paraphrases, and (5) clues that

eliminate alternatives and make the correct option effectively identifiable. Rule-based checks cover option letters, binary assertions, explicit counts, quoted answer text, and lexical overlap with the correct MCQ option (word Jaccard at least 0.35, or at least two answer keywords covering 60% of its content words). Candidates that fail are regenerated up to three times with an explicit answer-withholding reminder and temperatures 0.5, 0.7, and 0.9. A temperature-zero pass of the same generator model then classifies the question-ground-truth-cue tuple as SAFE or LEAK; judge failures are conservatively rejected.

Of 25,118 samples, 24,257 (96.6%) are automatically accepted and 861 (3.4%) fall back to the original teacher prompt. Because generation and automatic judging use the same model, we complement this self-check with a random manual audit of 300 accepted cues. Two annotators jointly inspect the video, question, options, stored answer, and cue for the five leakage categories above as well as whether the pointer is visually grounded. The audit flags 3 direct-answer leaks (category 1), 4 indirect semantic leaks (categories 2–5), and 6 visually unsupported or incorrectly grounded pointers, i.e. 13 of the 300 sampled cues. Both annotators review each sample together and resolve disagreements by discussion, so these are consensus counts and we do not report an inter-annotator agreement coefficient.

Treating leakage as the union of the first two groups gives a residual leakage rate of $7/300 = 2.3\%$ among accepted cues (95% Wilson interval 1.1–4.7%), so the accept decision has an estimated precision of $\sim 97.7\%$ and the end-to-end non-leaking fraction of the training pool is approximately 94%. Because the audit samples only accepted cues, it estimates this precision but not the false-rejection rate on the 861 fallback samples. The audit is a post-hoc quality estimate and does not retroactively re-filter the training pool; 96.6% therefore remains an automatic acceptance rate rather than a human-verified clean rate.

Representative Accepted Cues. Table 10 lists cues sampled from the released training pool, two per answer format. They illustrate the intended behaviour of the screening rules. The binary example about strap colour points at the wrists without naming a colour; the counting example points at a region without stating a count; and the multiple-choice examples localise a moment and a subject without restating any option. Each cue is short and purely deictic, so the teacher still has to inspect the clip to answer.

Answer Parsing and Verifiable Reward

Ground truths are typed automatically: a single letter A–H marks a multiple-choice item, yes/no marks a binary item, and a non-negative integer marks a counting item. Each type has its own extractor, and the reward is 1 on an exact match after extraction and 0 otherwise. This rule-based reward drives only the GRPO diagnostic; the OPD objective never consults it.

Multiple-choice extraction first looks for an explicit answer cue such as “the answer is” and takes the last such occurrence, since models frequently restate. Absent a cue, only upper-case standalone letters are accepted, which pre-

Format	Answer	Question	Accepted cue
Multiple choice	C	As the camera focuses on the man in the tank top, what specific exercise is he performing?	Around 0:04, when the man in the tank top is shown, look at the movement of his arms and the cable machine he is using.
Multiple choice	D	As the man finishes sniffing the collar of his striped shirt, what is he about to do next?	Around 0:09, as he lowers his hand from his collar, look at his face and the direction he turns his head.
Binary	Yes	As the man wraps his wrists before lifting, are the straps he is using black and purple?	Around the segment where the man is preparing to lift, look closely at the straps on his wrists.
Binary	Yes	As the person is shown laughing, are their eyes closed?	Around the segment from 6.5 to 7.5 seconds, look at the person’s face.
Counting	0	As the woman in the blue dress is laughing, how many lollipops are visible?	Around the time the woman in the blue dress is laughing, look at the hand in the foreground.
Counting	2	Just before the scene transitions, how many men are giving a thumbs-up gesture?	Around the moment the second text overlay appears, look at the hands of both men standing in the frame.

Table 10: Representative cues drawn from the accepted training pool, two per answer format. The answer column is shown here for inspection only; it is never part of the teacher prompt.

vents the English article “a” and the pronoun “I” from being read as options, and the *last* qualifying letter wins. Binary extraction takes the *first yes/no* token, because binary answers normally lead the response. Counting extraction prefers the first integer after an answer cue and otherwise the first integer in the response.

The direction of the multiple-choice rule matters for the format-drift diagnostic. The training reward reads the last option letter, whereas a deployed streaming parser reads the first answer token it encounters. A model that emits a long rationale before its answer scores well under the former and poorly under the latter, which is precisely the gap reported for GRPO in the main text. Distilled models emit a bare option letter, so both parsers agree.

Training Algorithm

Algorithm 1 gives the per-batch procedure for ST-CueGate training, including the two teacher replays and the group-relative gate.

Gate Interpretation and Unexplored Aggregations. The gate is a group-relative response reweight, not an absolute test of whether a cue helped. In particular, an above-mean response can receive $w_i > 1$ even when all g_i values in its sibling group are negative. The response mean also mixes reasoning, answer, punctuation, and formatting tokens, and the resulting scalar multiplies every token-level OPD advantage. We did not evaluate absolute positive-clipped gates, positive-token-only or answer-token-only aggregation, top- k /quantile/trimmed means, or hard suppression of negative-score responses. These alternatives could better separate absolute cue benefit from relative ranking and reduce sensitivity to response composition. Our results therefore establish the performance of one likelihood-based response proxy, not the faithfulness or optimality of its aggregation rule. The implementation additionally supports asymmetric penalization of negative-score tokens through a coefficient γ , but all reported runs use $\gamma = 1$, which reduces that extension exactly to the length-normalized response mean defined in the main paper.

Algorithm 1 ST-CueGate Training

Require: batch of prompts q_i , cues c_i , student π_θ , frozen teacher π_τ

- 1: **for** each prompt q_i **do**
- 2: Sample an on-policy response $y_i \sim \pi_\theta(\cdot \mid q_i)$ in thinking mode.
- 3: Compute student token log-probabilities $s_{i,t}$ on response tokens.
- 4: Replay y_i with the teacher under the cue prompt to obtain $\tau_{i,t}^+$.
- 5: Replay y_i with the same teacher and frames under the original prompt to obtain $\tau_{i,t}^-$.
- 6: Compute $\Delta_{i,t} = \tau_{i,t}^+ - \tau_{i,t}^-$ and $g_i = T_i^{-1} \sum_t \Delta_{i,t}$.
- 7: **end for**
- 8: Standardize g_i within each prompt’s sibling rollout group.
- 9: Set $w_i = \text{clip}(1 + \alpha_g \tilde{g}_i, w_{\min}, w_{\max})$.
- 10: Form $A_{i,t}^{\text{ST-CueGate}} = w_i(\tau_{i,t}^+ - s_{i,t})$.
- 11: Update π_θ with the clipped policy-gradient objective.

Objective Derivations and Policy-Gradient View

Notation. Let q_i denote the i -th prompt, consisting of the decoded video frames and the question text, π_θ the student, π_τ the frozen teacher, and π_b the frozen student initialization used by the extrapolation baselines. For a sampled response y_i of length T_i we write $s_{i,t}$, $\tau_{i,t}$, and $b_{i,t}$ for the corresponding token log-probabilities, as in the main text.

From Reverse KL to the Sampled-Token Estimator. On-policy distillation minimizes the reverse KL between student and teacher at every position along the student’s own trajectory,

$$\text{KL}_{i,t} = \sum_{v \in \mathcal{V}} \pi_\theta(v \mid y_{i,<t}, q_i) \log \frac{\pi_\theta(v \mid y_{i,<t}, q_i)}{\pi_\tau(v \mid y_{i,<t}, q_i)}. \quad (8)$$

Summing over the full vocabulary at every position is expensive for long multimodal prompts, so we use the single-

sample estimator evaluated at the realized token,

$$k_{i,t}^{(1)} = s_{i,t} - \tau_{i,t}, \quad (9)$$

which is unbiased for $KL_{i,t}$ because $y_{i,t} \sim \pi_\theta(\cdot | y_{i,<t}, q_i)$. The OPD advantage of the main text is exactly its negation, $A_{i,t}^{\text{OPD}} = -k_{i,t}^{(1)}$. The implementation also offers the lower-variance $k^{(2)}$ and $k^{(3)}$ estimators, but all reported runs use $k^{(1)}$: it is signed, which is what makes the advantage reading below possible, whereas the low-variance estimators are non-negative by construction.

OPD as a Dense-Reward Policy Gradient. Because the advantage carries a stop-gradient, differentiating the token-level policy-gradient objective of the main text gives

$$\nabla_\theta \mathcal{L}_{\text{PG}} = -\mathbb{E} \left[\frac{1}{T_i} \sum_{t=1}^{T_i} A_{i,t} \nabla_\theta \log \pi_\theta(y_{i,t} | y_{i,<t}, q_i) \right], \quad (10)$$

so OPD performs gradient ascent on the expected per-token reward $r_{i,t} = \tau_{i,t} - s_{i,t}$ along on-policy rollouts. This reward is dense and self-annihilating: it is positive exactly where the teacher places more mass than the student on the realized token, and it vanishes identically once the student matches the teacher on the sampled support. The GRPO diagnostic differs structurally on both counts. Its advantage is constant across all tokens of a response, and it vanishes whenever every rollout in a group receives the same verifiable reward, which is why sparse task reward can constrain the final answer without constraining the trajectory that precedes it.

Extrapolated Targets and Why They Are Ungrounded. ExOPD replaces the teacher log-probability with a point extrapolated along the teacher’s improvement over the base, $b_{i,t} + \lambda(\tau_{i,t} - b_{i,t})$, which yields the ExOPD advantage given in the main text; $\lambda = 1$ returns standard OPD. For $\lambda > 1$ the extrapolated vector is in general not the log-density of any normalized distribution, since $\sum_v \exp[b + \lambda(\tau - b)] \neq 1$, so no teacher policy realizes the target. The update therefore pushes the student toward a point that no achievable conditional distribution occupies, and, unlike a cue, the direction is not tied to anything observable in the training clip. This is the precise sense in which we call the signal ungrounded, and it is consistent with the instability reported below.

Axis-Decomposed Extrapolation. AD-ExOPD adds a second frozen reference π_b^{dense} , the same base model given the teacher’s dense frame budget, and splits the teacher’s improvement into a frame axis and a capacity axis,

$$\tau - b = \underbrace{(b^{\text{dense}} - b)}_{\text{more frames}} + \underbrace{(\tau - b^{\text{dense}})}_{\text{more capacity}}, \quad (11)$$

extrapolating each with its own gain:

$$A_{i,t}^{\text{AD}} = -(s - b) + \lambda_t(b^{\text{dense}} - b) + \lambda_c(\tau - b^{\text{dense}}). \quad (12)$$

Setting $\lambda_t = \lambda_c$ recovers ExOPD. We ran $\lambda_t=1.5$, $\lambda_c=1.0$, on the reasoning that a sliding-window student can exploit additional frames but cannot acquire 9B capacity; the outcome is reported below.

n	α_g	Attainable w range	Clip reachable
4	0.25	[0.57, 1.43]	no
4	0.50	[0.13, 1.87]	no
4	1.00	[-0.73, 2.73]	yes
8	0.50	[-0.32, 2.32]	yes

Table 11: Attainable gate values before clipping to $[w_{\min}, w_{\max}] = [0, 2]$, from the bound $|\tilde{g}| \leq \sqrt{n-1}$. The reported configuration ($n=4$, $\alpha_g=0.5$) cannot reach either boundary.

The Gate as a Length-Normalized Likelihood Ratio.

Because both teacher passes score the same realized response, the token contrasts telescope into a sequence-level quantity:

$$\sum_{t=1}^{T_i} \Delta_{i,t} = \log \pi_\tau(y_i | q_i, c_i) - \log \pi_\tau(y_i | q_i), \quad (13)$$

so g_i is the length-normalized log-likelihood ratio of one response under two nested teacher contexts. Algebraically this has the form of a pointwise mutual information between the cue and the realized response. We deliberately avoid that reading: the two conditionals are obtained by prompting a single network in two ways and need not be consistent with any joint distribution over cues and responses, so we treat g_i as a likelihood-ratio statistic rather than an information-theoretic quantity.

The Gate Is Mean-Preserving, and When It Saturates.

Standardizing within a group of n sibling rollouts with population statistics gives $\sum_{j \in \mathcal{G}} \tilde{g}_j = 0$, so before clipping

$$\frac{1}{|\mathcal{G}|} \sum_{i \in \mathcal{G}} w_i = 1 + \frac{\alpha_g}{|\mathcal{G}|} \sum_{i \in \mathcal{G}} \tilde{g}_i = 1 \quad (14)$$

exactly. The gate therefore redistributes weight inside a group rather than rescaling the group’s total contribution, and α_g controls only the spread. Standardized scores are also bounded: for n values, $|\tilde{g}| \leq \sqrt{n-1}$, with equality when one member differs from the other $n-1$. The attainable weight range is thus $[1 - \alpha_g \sqrt{n-1}, 1 + \alpha_g \sqrt{n-1}]$, summarized in Table 11.

For the reported configuration the range lies strictly inside the clip interval, so the gate is probably a smooth monotone reweighting and the bounds never bind. Raising α_g to 1.0 at $n=4$, or widening the group to $n=8$ at $\alpha_g=0.5$, makes both boundaries reachable, so a single extreme rollout can be suppressed to zero or doubled. Those are also the two settings that lose accuracy in the corresponding ablations. We report this as a consistency observation rather than an identified cause, since changing n and α_g also changes the variance of the standardized score itself.

A Common Reweighting Family. Standard OPD, the ungrounded controls, and the contrastive gates are all instances of

$$A_{i,t} = w_i (\tau_{i,t} - s_{i,t}), \quad (15)$$

Dataset	Size	Composition
8.3k filtered	8,343	20k after pass-rate filter
20k full	20,031	rlvr $\cup$ cot_rlv
cot_verifiable	23,884	verifiable CoT pool
25k merged	25,118	8.3k $\cup$ cot_verifiable
Cue injected	24,257	automatically accepted teacher cue
Cue fallback	861	original teacher prompt

Table 12: Training-data construction. The 25k merged set is the default training configuration.

and differ only in what generates w_i : it is constant for OPD; derived from student-teacher disagreement $|s - \tau|$ for DAD, which uses no external context; derived from a positive and a degraded visual view for the V-Zero adaptation; and derived from cue and no-cue teacher contexts over the same frames and response for ST-CueGate. The reweighting mechanism is therefore shared, and our contribution lies in the choice of reference, not in the existence of a group-relative gate.

Data Construction and Statistics

Training data are streaming-video QA items constructed from public instruction data (Zhang et al. 2024b; Yuan et al. 2025). Videos are short (median ~ 5.5 s, 89% under 15s) and heavily temporal (71.8% of questions require temporal reasoning); 69.7% are MCQ, 25.3% binary, and 5.0% counting. Figure 5 summarizes the pipeline and Table 12 gives the exact data lineage.

Pass-Rate Filtering. We sample the student and teacher eight times each at temperature 0.7 and estimate per-sample pass rates. Removing samples that are already easy for both models yields an 8,343-item filtered set. Among the 4.6% of samples where the teacher underperforms the student, 40.7% are response-format deviations rather than genuine capability gaps.

Cue-Conditional Contrast Analysis

Collection Protocol. For each sampled student response, we retain only valid response-token positions and compute $\Delta_t = \log p_T(y_t | \text{cue}) - \log p_T(y_t | \text{no-cue})$ using the same teacher and decoded frames. The main distribution pools 300,866 tokens collected over five diagnostic training steps. We classify tokens with $|\Delta_t| \leq 0.01$ as inactive and compute concentration after sorting positive- Δ tokens by score.

To test whether the sparse cue-conditional pattern is limited to initialization, we repeat cue-versus-no-cue teacher scoring at three student checkpoints: the base model, step 700, and step 2100. Figure 6 shows that the distributions remain closely aligned. The inactive-token fraction stays between 52.4% and 56.5%, while the top 20% of positive- Δ tokens consistently account for 80–82% of the total positive mass. Thus, the sparse, heavy-tailed, and concentrated structure motivating ST-CueGate persists throughout optimization rather than appearing only at initialization.

Negative Results: A Map of the Design Space

For completeness we document teacher-condition and training variants that did not improve consistently over standard OPD or ST-CueGate. These results delineate the boundary of post-training and privilege design under our fixed inference protocol. All runs use the identical 25k backbone, optimizer, and evaluation protocol as the main paper unless noted.

Two-Axis Reward Extrapolation (AD-ExOPD). Decomposing the teacher’s advantage over the base into a *frame* axis (seeing more frames) and a *capacity* axis (a larger model) with separate extrapolation gains λ_t, λ_c , we ran $\lambda_t=1.5, \lambda_c=1.0$. Validation oscillated between 50–65% for the entire run (peak $\sim 65\%$ at step 1600), never approaching the $\sim 70\%$ that standard OPD reaches on the same data, and the extrapolation *harmed* early convergence. Like single-axis extrapolation (ExOPD in the main text), pushing the student *beyond* the teacher along an ungrounded direction does not help; adding a second such axis only destabilizes training.

Difficulty-Adaptive Distillation (DAD). As an ungrounded reweighting control, DAD assigns larger weights to responses on which student and teacher disagree. For response y_i , let $d_i = T_i^{-1} \sum_t |s_{i,t} - \tau_{i,t}|$. We first compute an unnormalized score and then normalize it within the batch:

$$\begin{aligned} \tilde{u}_i &= \exp(\alpha_{\text{DAD}} \text{zscore}(d_i)), \\ u_i &= \text{clip}\left(\frac{\tilde{u}_i}{\mathbb{E}_j[\tilde{u}_j]}, 0.2, 3\right), \\ A_{i,t}^{\text{DAD}} &= u_i A_{i,t}^{\text{OPD}}. \end{aligned} \quad (16)$$

With $\alpha_{\text{DAD}} = 1.0$, DAD reaches 84.27% on Streaming-Bench but only 68.10% on OVO-Bench (excl. HLD) and 62.93% on Video-MME, providing no consistent improvement over standard OPD. This supports our decision to keep the main method focused on teacher-side grounded privilege rather than observation-agnostic difficulty weighting.

Mode-Dependent OPD Instability. Our recipe trains teacher and student both in *thinking* mode. We tested the two additional pairings summarized by the training-mode figure in the main paper. *Teacher-thinking / student-instruct*: with the student answering directly but the teacher scoring in thinking mode, validation falls from 69.3% at step 0 to 26% by step 100 and below 2% by step 600. *Both-instruct*: validation similarly drops from 69.9% to 23.6% by step 100. The failed runs produce very short responses and gradient-norm spikes of 70–120, compared with 1–10 in the stable both-thinking run. These observations are consistent with a short-trajectory scale hypothesis: sampled-token reverse-KL updates are supported by fewer token positions and may have higher effective variance. They do not isolate response length, however. Mode-specific initialization and policy distributions, teacher-student KL, prompt-induced distribution shift, response normalization, estimator variance, and importance-ratio clipping may also contribute. We therefore report the length-based account as a mechanistic hypothesis rather than an identified cause. We observe token-mean loss aggregation and no NaNs in these runs. Length-matched controls and multi-seed collapse rates are needed for causal identification.




Figure 5: Data construction pipeline. Public video instruction data are cast into verifiable QA, pass-rate filtered by 8-sample student/teacher agreement, and annotated offline by a stronger VLM with an automatically screened spatio-temporal visual cue. The cue is wrapped in an explicit instruction frame and appended only to the teacher prompt.

Teacher-Free RL in No-Think Mode (GRPO). Figure 7 plots the two format-drift diagnostics summarized in the main text: response-length growth over training, and sensitivity to whether the evaluator reads the first or the last answer. Consistent with that analysis, training GRPO directly in instruct mode diverges early, while GRPO in thinking mode plateaus near the untrained student. Because this comparison also changes mode-dependent generation and optimization behavior, we do not assign it the same short-trajectory mechanism without additional controls.

V-Zero Adaptation for Video. ST-CueGate uses the no-cue context as a nested reference: both teacher passes share the frames, question, and realized response, and differ only in cue presence. For the V-Zero adaptation (Sun et al. 2026), we retain its paired-evidence gating principle and construct the negative evidence view by temporally shuffling the video. We also implemented a blacked-out negative view, but report the shuffled variant because it preserves appearance statistics while destroying only temporal order, which is the axis a streaming cue is meant to localize. This video variant scores below ST-CueGate on every reported axis (StreamingBench 83.5–84.0, with OVO and Video-MME also lower), indicating that a shuffled-video reference is less effective than cue removal for our cue-conditioned streaming setting.

Asymmetric Frame Budget, Extended (AFD v2/v3). Beyond the AFD (t32/s8) configuration, we tried a denser teacher budget (fps 4, up to 64 frames; “v2”) and a frame-superset design where the teacher’s frames strictly contain the student’s (“v3”). Both plateaued around $\sim 60\%$ validation and never exceeded standard OPD on the same 25k data (which peaks at 70.6%); at matched training steps AFD trailed OPD by ~ 10 points. Simply letting the teacher see more frames does not translate into better distilled supervision on our short-video data—the extra visual evidence is unavailable to the student at its own frame budget—which motivates measuring the cue-conditional teacher shift rather than supplying privilege blindly.

Broader Impact and Deployment Considerations

Streaming video models raise privacy considerations when deployed on live camera feeds. Our work uses public benchmark and instruction data and targets compute-efficient models, which lowers the energy cost of deployment. The HLD degradation we identify is safety-relevant even though HLD is distinct from streaming event recall: practitioners should be aware that distilled models can become more prone to answering unanswerable queries and should evaluate abstention explicitly before deployment.




Figure 6: Evolution of the cue-conditional log-likelihood ratio across student checkpoints. (a) The cue-versus-no-cue Δ_t distributions remain similar from the base model through steps 700 and 2100. (b) Positive-score concentration is also stable: the top 20% of positive- Δ tokens carry approximately 80–82% of the total positive mass at every stage.




Figure 7: Pure RL drifts from the deployed response format. (a) GRPO outputs grow from concise answers into long rationales, while OPD remains concise. (b) GRPO becomes sensitive to whether the evaluator reads the first or last answer, whereas the concise OPD model is parser-invariant. This gap diagnoses response-format drift under sparse reward.