

When Guidance Goes Off-Scale: Recalibrating Diffusion Transformers under Analog Compute-in-Memory Nonidealities

Wenshuai Yao^{*1}, Wenyong Zhou^{*2}

¹School of Integrated Circuits, Peking University, Beijing, China

²Department of Electrical and Computer Engineering, The University of Hong Kong, Hong Kong SAR, China

Abstract

Diffusion Transformers (DiTs) incur high memory traffic and energy costs because sampling repeatedly evaluates large denoisers dominated by linear operations. Analog compute-in-memory (CIM) can alleviate these costs by executing linear operations within weight-storing memory arrays. However, CIM nonidealities perturb effective weights, with errors accumulating along the state-dependent denoising trajectory; their interaction with classifier-free guidance (CFG) remains under-explored. In this paper, we characterize the impact of analog CIM nonidealities on DiT sampling. Although conditional and unconditional predictions can each remain close to their clean counterparts, their difference—the CFG residual—is disproportionately attenuated and rotated. Identifying this residual as a controllable failure channel, we propose a retraining-free, sampler-side recalibration that adjusts only the CFG scale for a given CIM condition. Trajectory-level analysis shows that moderate recalibration strengthens the target-oriented component preserved in the distorted residual, enabling earlier commitment to a prompt-consistent semantic region. In contrast, excessive guidance amplifies the full noisy residual and degrades quality, resulting in a finite, noise-dependent optimum. Extensive experiments on PixArt- Σ , PixArt- α , and DiT-XL/2 show that the optimal guidance scale increases with CIM noise. Using 30,000 samples per condition, guidance recalibration consistently restores generation quality across simulated CIM mappings, closing at least 87% of the CIM-induced FID gap at $\sigma_{\text{CIM}} = 0.20$. It reduces FID from 59.22 to 20.49 on PixArt- Σ , 72.37 to 21.12 on PixArt- α , and 20.89 to 6.62 on DiT-XL/2.

Introduction

Diffusion models have become a leading paradigm for high-fidelity image generation (Ho, Jain, and Abbeel 2020), and Diffusion Transformers (DiTs) demonstrate that transformer backbones can scale this paradigm effectively for both class-conditional and text-to-image synthesis (Peebles and Xie 2023; Chen et al. 2024b,a). Achieving this quality, however, incurs substantial hardware cost. DiT sampling requires repeated evaluations of a large denoiser over many timesteps and repeated movement of large weight matrices between memory and compute units for attention projections and feed-forward layers. Analog compute-in-memory (CIM) is therefore an attractive deployment substrate: by performing




Figure 1: Qualitative comparison across four prompts. Each triplet shows clean generation, CIM with clean-selected guidance, and CIM with recalibrated guidance.

linear operations within memory arrays, it can reduce costly data movement and improve energy efficiency (Shafiee et al. 2016; Sebastian et al. 2020).

Analog CIM computation is subject to numerical non-idealities. Programming variation, conductance drift, read variation, and mixed-signal peripheral effects perturb the effective weights and computations realized by the deployed network (Sebastian et al. 2020; Joshi et al. 2020). Such perturbations are particularly consequential for diffusion sampling. Unlike a feed-forward prediction task, a denoiser is evaluated repeatedly in a closed loop (Song et al. 2021). An error at one timestep therefore changes the latent state supplied to all subsequent timesteps, causing hardware-induced deviations to accumulate along a state-dependent denoising trajectory. While recent work has explored CIM acceleration for diffusion workloads (Jing et al. 2024), the generation-quality degradation of modern pretrained DiTs under analog CIM nonidealities remains insufficiently understood. In particular, it is unclear how these nonidealities affect classifier-free guidance (CFG) (Ho and Salimans 2022), the primary conditional control mechanism used in diffusion sampling.

CFG combines unconditional and conditional denoiser predictions as

$$\epsilon_w(x_t, t) = \epsilon_u(x_t, t) + w(\epsilon_c(x_t, t) - \epsilon_u(x_t, t)), \quad (1)$$

where w is the guidance scale and $g_t = \epsilon_c(x_t, t) - \epsilon_u(x_t, t)$ is the CFG residual. Reusing a guidance scale selected under clean digital inference after deployment implicitly assumes that the CFG residual remains sufficiently stable for the clean guidance calibration to transfer to CIM inference.

^{*}These authors contributed equally.

Our analysis shows that this assumption can fail under CIM nonidealities. Although the conditional and unconditional predictions can each remain relatively close to their clean counterparts, their smaller difference—the CFG residual—is disproportionately distorted in relative magnitude and direction. This subtraction-sensitive distortion makes the clean-selected guidance scale miscalibrated under analog CIM nonidealities.

This observation identifies the CFG residual as a failure channel and the guidance scale as an available sampler-side control variable. We therefore propose *guidance recalibration*, a retraining-free, sampler-side procedure that selects only the CFG scale for a target CIM operating condition. The pretrained denoiser, CIM mapping, scheduler, and sampling budget all remain unchanged. Figure 1 illustrates the resulting recovery: compared with clean generation, CIM inference using the clean-selected scale exhibits substantial degradation, whereas recalibrating the existing CFG scale restores image structure and prompt-consistent details.

We view CFG as one-dimensional control of a state-dependent sampling trajectory. Under analog CIM nonidealities, the noisy CFG residual retains a useful component aligned with clean conditional control, but it also contains differential residual errors; meanwhile, common drift in the denoiser branches cannot be removed by changing the guidance scale alone. Moderate recalibration amplifies the retained useful component sufficiently to steer the trajectory toward the target semantic basin. Once the trajectory reaches its neighborhood, the learned denoising field provides local attraction toward that basin, and subsequent steps continue to refine the same semantic content. In contrast, excessive guidance amplifies both useful control and residual distortion, eventually driving the trajectory toward over-conditioned or low-quality regions. Thus, recalibration need not reproduce the clean trajectory at every timestep; rather, it restores a favorable trajectory-level operating point under the target CIM condition. Our contributions are threefold:

- We identify a subtraction-sensitive failure channel in CIM-deployed DiTs: the CFG residual is disproportionately distorted despite relatively stable conditional and unconditional predictions.
- We propose a retraining-free, sampler-side guidance recalibration that adjusts only the CFG scale for a target CIM condition, without modifying the model or sampler.
- We provide a trajectory-level account of the finite, noise-dependent guidance optimum and support it through residual, timestep, intervention, layer, seed, and perturbation analyses across three DiT models.

Related Work

Diffusion Transformers. Diffusion models generate samples through iterative denoising (Ho, Jain, and Abbeel 2020), and Diffusion Transformers (DiTs) use scalable transformer backbones as denoisers (Peebles and Xie 2023). Representative DiT models span both class-conditional generation and large-scale text-to-image synthesis, including DiT-XL/2, PixArt- α , and PixArt- Σ (Peebles and Xie 2023; Chen et al.

2024b,a). Their repeated attention and feed-forward projections make sampling computationally and memory intensive, motivating efficient hardware deployment. We study how analog CIM nonidealities affect this iterative DiT sampling process.

Analog CIM for Generative Models. Compute-in-memory (CIM) reduces data movement by executing matrix operations within memory arrays (Shafiee et al. 2016; Sebastian et al. 2020). Prior work has explored CIM and heterogeneous acceleration for diffusion workloads, including diffusion-specific dataflows, mixed-precision designs, and analog implementations of score-based generation (Jing et al. 2024; Zhu et al. 2025; Guo et al. 2026; Yang et al. 2026). For LLM deployment, NORA rescales linear operations to redistribute analog error among inputs, outputs, and weights (Hou et al. 2025). However, analog CIM nonidealities, such as programming variation, drift, and read noise, perturb the effective deployed weights and computations (Joshi et al. 2020; Sebastian et al. 2020). Existing studies primarily characterize hardware efficiency or aggregate generation degradation. In contrast, we identify how persistent CIM-induced perturbations distort the CFG residual control channel in modern pretrained DiTs and show that this diffusion-specific distortion can be mitigated through sampler-side guidance recalibration.

Classifier-Free Guidance. Classifier-free guidance (CFG) combines conditional and unconditional predictions to improve condition adherence during diffusion sampling (Ho and Salimans 2022). Several methods refine CFG under clean digital inference by controlling prediction magnitude, residual geometry, or the timesteps at which guidance is applied, including CFG Rescale, APG, Limited-Interval Guidance, C²FG, and CFG++ (Lin et al. 2024; Sadat, Hilliges, and Weber 2025; Kynkäänniemi et al. 2024; Gao et al. 2026; Chung et al. 2025). Recent analysis also interprets CFG through predictor-corrector dynamics (Bradley and Nakkiran 2025). These methods improve the trade-off between quality and alignment or reduce artifacts and off-manifold behavior under standard digital inference. Our work instead considers a deployment-induced miscalibration problem: analog CIM nonidealities distort the CFG residual itself, making the clean-selected guidance scale suboptimal. Rather than introducing a new guidance rule, we recalibrate the existing scalar guidance scale for the target CIM operating condition.

Guidance Recalibration under Analog CIM

We first formulate hybrid analog CIM deployment and CFG sampling. We then identify the CFG residual as a subtraction-sensitive failure channel under CIM nonidealities, recalibrate its scalar control gain, and provide a trajectory-level interpretation of the resulting finite guidance optimum based on semantic basin dynamics.

CIM Deployment and CFG

We consider a hybrid analog CIM deployment of DiTs, illustrated in Figure 2. Static linear weights in attention projections and feed-forward layers are mapped to CIM arrays,




Figure 2: Hybrid analog CIM deployment. (a) CIM-based matrix multiplication. (b) DiT mapping: linear layers are executed on CIM arrays, while other operations remain digital.

whereas normalization, nonlinear activations, softmax, data-dependent attention products, and scheduler updates remain digital. This setting preserves the original DiT architecture while accelerating the matrix operations that dominate its repeated denoiser evaluations.

Motivated by hardware studies that model conductance variability through Gaussian weight perturbations (Joshi et al. 2020; Wan et al. 2022), we perturb each mapped linear weight matrix W_ℓ as

$$\widetilde{W}_\ell = W_\ell \odot (1 + \sigma_{\text{CIM}} \Xi_\ell), \quad [\Xi_\ell]_{ij} \stackrel{\text{i.i.d.}}{\sim} \mathcal{N}(0, 1), \quad (2)$$

where σ_{CIM} controls the perturbation severity. A sampled realization is fixed throughout a denoising trajectory, reflecting persistent weight-related deviations in a deployed CIM array. Equation (2) is an algorithm-level proxy for analog CIM nonidealities rather than a complete circuit-level model.

Classifier-free guidance (CFG) combines unconditional and conditional denoiser predictions as

$$\epsilon_{w,t} = u_t + w g_t, \quad g_t = c_t - u_t, \quad (3)$$

where $u_t = \epsilon_\theta(x_t, t, \emptyset)$ and $c_t = \epsilon_\theta(x_t, t, y)$ denote the unconditional and conditional predictions, respectively. The scalar w controls the strength of the conditional residual g_t . Let w_0 denote the scale selected under clean digital inference. A straightforward deployment baseline reuses w_0 after mapping the model to CIM; this baseline can become miscalibrated under CIM nonidealities.

CFG Residual Distortion

Let $\tilde{\theta}(\xi)$ denote the effective weights under a CIM realization ξ . At a given latent state x_t , the induced prediction perturbation is

$$\delta_t(x_t, y; \xi) = \epsilon_{\tilde{\theta}(\xi)}(x_t, t, y) - \epsilon_\theta(x_t, t, y). \quad (4)$$

Although Equation (2) is Gaussian at the weight level, the resulting output perturbation generally depends on the state, timestep, condition, and CIM realization.

For the two CFG branches, we write

$$\tilde{u}_t = u_t + \delta_{u,t}, \quad \tilde{c}_t = c_t + \delta_{c,t}. \quad (5)$$

Their noisy residual is therefore

$$\tilde{g}_t = \tilde{c}_t - \tilde{u}_t = g_t + \delta_{g,t}, \quad \delta_{g,t} = \delta_{c,t} - \delta_{u,t}. \quad (6)$$



Figure 3: PixArt- Σ generations at 1024×1024 resolution under increasing CIM nonidealities at the clean-selected scale $w_0 = 2.0$.




Figure 4: CFG and residual diagnostics under CIM nonidealities. (a) Branch perturbations. (b) Residual rotation. (c) Clean-aligned decomposition. (d–e) Timestep statistics at $\sigma_{\text{CIM}} = 0.20$; shading indicates 95% confidence intervals.

This subtraction exposes differential branch errors. Even when $\delta_{u,t}$ and $\delta_{c,t}$ are small relative to the branch predictions, their difference can be substantial relative to the smaller residual g_t .

Figure 3 visualizes generation at the clean-selected guidance scale as the CIM perturbation level increases.

We characterize this distortion by decomposing the noisy residual into a component aligned with the clean residual and an orthogonal component:

$$\tilde{g}_t = \alpha_t g_t + \eta_t, \quad \alpha_t = \frac{\langle \tilde{g}_t, g_t \rangle}{\|g_t\|_2^2}, \quad \langle \eta_t, g_t \rangle = 0. \quad (7)$$

Here, $\alpha_t g_t$ is the retained clean-aligned component, while η_t denotes the residual component orthogonal to g_t . Both terms vary over timesteps, latent states, prompts, and CIM realizations.

Figure 4 shows that the conditional and unconditional




Figure 5: Conceptual sampling trajectories under (a) clean inference, (b) CIM inference with the clean-selected scale w_0 , and (c) CIM inference with the recalibrated scale w^* . Shaded contours indicate semantic basins; arrows denote base and guidance updates. Each trajectory segment is the vector sum of the two component arrows.

branches remain substantially closer to their clean counterparts than does their difference. In particular, the noisy residual exhibits reduced directional agreement, attenuated aligned magnitude, and large relative error. Thus, beyond introducing generic denoiser drift, CIM nonidealities disproportionately distort the control channel directly scaled by CFG.

Substituting Equation (7) into CFG gives

$$\tilde{\epsilon}_{w,t} = u_t + \delta_{u,t} + w(\alpha_t g_t + \eta_t). \quad (8)$$

Equation (8) identifies a controllable trade-off: changing w cannot directly remove the common branch drift $\delta_{u,t}$, but it simultaneously scales the retained useful component $\alpha_t g_t$ and the orthogonal residual component η_t .

Guidance Recalibration

Motivated by this diagnosis, we recalibrate only the existing CFG scale for a target CIM operating condition. The pretrained denoiser, CIM mapping, scheduler, and sampling budget remain fixed. Given an independent calibration set $\mathcal{D}_{\text{cal}}$ and a candidate set of guidance scales $\mathcal{W}$, we select

$$w^*(\mathcal{C}) = \arg \min_{w \in \mathcal{W}} \mathcal{L}(w; \mathcal{D}_{\text{cal}}, \mathcal{C}), \quad (9)$$

where $\mathcal{C}$ denotes the target CIM operating condition, including the mapped layers, nonideality model, and perturbation level. In our main experiments, $\mathcal{L}$ is FID and $\mathcal{C}$ is indexed by σ_{CIM} ; we write the corresponding selected scale as w_σ^* .

The selected scale w^* is fixed for all subsequent samples under the same operating condition. This procedure requires no retraining, weight update, activation correction, per-prompt adaptation, or additional denoiser evaluation during sampling. The sweep is performed once per target operating condition; after selection, deployment retains the original sampling procedure and uses w^* as a fixed scalar setting. Rather than attempting to invert CIM errors or reproduce the clean trajectory at individual timesteps, guidance recalibration selects a favorable operating point for the noisy closed-loop sampler.

Trajectory Interpretation

Guidance recalibration acts on a closed-loop sampling process. For a generic reverse sampler,

$$\tilde{x}_{t-1}^{(w)} = S_t \left(\tilde{x}_t^{(w)}, \tilde{\epsilon}_{w,t} \right), \quad (10)$$

changing w affects not only the current update but also the latent states supplied to all subsequent denoiser evaluations. Recalibration is therefore a trajectory-level control problem rather than pointwise matching of clean denoiser predictions.

Defining $\Delta x_t^{(w)} = \tilde{x}_{t-1}^{(w)} - \tilde{x}_t^{(w)}$ and locally linearizing the sampler around the noisy unconditional prediction at the current state gives

$$\Delta x_t^{(w)} \approx v_{u,t} + w r_t, \quad r_t = B_t \tilde{g}_t, \quad (11)$$

where $v_{u,t}$ is the base update, B_t is the local prediction-to-state mapping induced by the sampler, and r_t is the sampler-propagated residual control. When r_t retains a component that promotes target-consistent structure over semantically informative steps, increasing w can strengthen this retained control and help the trajectory reach a region in which the target semantics become locally persistent.

Figure 5 provides a conceptual interpretation. Under CIM nonidealities, the clean-selected scale w_0 can yield insufficient target-oriented control because the residual is attenuated and rotated. A moderately larger scale w^* amplifies the useful component that remains, allowing the trajectory to reach a target-consistent region earlier. Once target-consistent structure becomes locally dominant, the learned denoising dynamics tend to preserve and refine that structure over subsequent steps, yielding attractor-like local behavior. Related attractor-like behavior has been used to characterize persistent diffusion trajectories in memorization settings (Jain et al. 2025); here, *semantic basin* denotes the local persistence of target-consistent structure. This account predicts that recalibration should advance persistent semantic entry, which we examine through the timestep analysis in Figure 8.

The benefit is bounded: excessive guidance amplifies the entire distorted residual, including components misaligned with target progress, while leaving the common drift $\delta_{u,t}$ uncontrolled. These errors accumulate along the closed-loop

Model and benchmark	σ_{CIM}	CFG w	FID↓	KID $\times 10^3$ ↓	Alignment↑	Precision↑	Density↑	Coverage↑
PixArt- Σ (512 ² , COCO)	0 (clean)	1.5	20.51	7.75	30.34	0.550	0.654	0.595
	0.05	1.5 (= w_0)	20.31	7.68	30.31	0.551	0.647	0.582
	0.10	1.5→2.0	21.12→ 19.98	8.27→ 7.05	30.09→ 30.69	0.513→ 0.552	0.575→ 0.654	0.556→ 0.580
	0.15	1.5→2.5	28.62→ 20.18	12.85→ 6.87	29.37→ 30.79	0.432→ 0.543	0.423→ 0.628	0.477→ 0.572
	0.20	1.5→4.5	59.22→ 20.49	30.41→ 6.49	27.32→ 31.17	0.248→ 0.527	0.203→ 0.602	0.292→ 0.560
PixArt- α (512 ² , COCO)	0 (clean)	1.5	21.63	8.21	29.98	0.545	0.624	0.567
	0.05	1.5→2.0	21.84→ 21.01	8.50→ 7.32	29.89→ 30.48	0.533→ 0.571	0.616→ 0.717	0.561→ 0.587
	0.10	1.5→2.5	24.16→ 20.75	10.34→ 7.10	29.52→ 30.65	0.495→ 0.576	0.537→ 0.716	0.514→ 0.589
	0.15	1.5→3.0	35.44→ 20.71	17.68→ 7.10	28.53→ 30.60	0.385→ 0.558	0.368→ 0.655	0.418→ 0.566
	0.20	1.5→5.0	72.37→ 21.12	40.60→ 7.39	25.95→ 30.68	0.212→ 0.517	0.148→ 0.609	0.208→ 0.536
DiT-XL/2 (256 ² , ImageNet)	0 (clean)	1.3	4.49	0.85	82.77	0.822	1.060	0.872
	0.05	1.3 (= w_0)	4.51	0.82	81.60	0.807	1.039	0.857
	0.10	1.3→1.4	5.13→ 4.66	1.03→ 0.83	79.10→ 82.40	0.776→ 0.805	0.946→ 0.995	0.828→ 0.845
	0.15	1.3→1.7	8.65→ 5.20	3.24→ 1.24	72.63→ 85.76	0.670→ 0.797	0.790→ 0.991	0.768→ 0.855
	0.20	1.3→2.0	20.89→ 6.62	11.68→ 1.39	59.28→ 84.91	0.537→ 0.756	0.563→ 0.880	0.645→ 0.819

Table 1: Large-scale population-level evaluation across three diffusion transformers and multiple simulated CIM mappings, with 30,000 samples per setting. Noisy entries report $w_0 \rightarrow w_\sigma^*$; a single value is shown when the selected scales coincide. Underlining marks the recalibrated endpoint, and bold marks improvement over the clean-guidance baseline.

trajectory, causing over-conditioning and degraded samples. Thus, the optimal guidance scale is finite and depends on the CIM condition. This analysis predicts that the preferred scale shifts with CIM severity, recalibration accelerates semantic commitment, and both residual distortion and base-path drift contribute to degradation.

Experiments

Experimental Setup

Models and benchmarks. We evaluate PixArt- Σ -XL/2 and PixArt- α -XL/2 at 512² for text-to-image generation and DiT-XL/2 at 256² for class-conditional generation. PixArt- Σ and Stable Diffusion 3.5 Medium (SD3.5 Medium) (Esser et al. 2024; Stability AI 2024) at 1024² are used only for qualitative examples in Figures 3 and 7. For standard evaluation, our 30,000-sample text-to-image setting uses MSCOCO 2014 validation captions and references (Lin et al. 2014), while the 30,000-sample canonical class-conditional DiT setting uses ImageNet validation statistics (Deng et al. 2009). Quantitative PixArt experiments use the default DPM-Solver scheduler (Lu et al. 2022) with 20 denoising steps, while DiT-XL/2 uses 50 steps. We first identify w_0 under clean inference and w_σ^* in an independent 3,000-sample guidance sweep, then hold both scales fixed for all subsequent 30,000-sample evaluations.

CIM protocol. Unless specified otherwise, Equation (2) is applied to the query, key, value, and output projections of self- and cross-attention and to both feed-forward linear layers. Each deterministic weight-noise draw represents an independently programmed virtual CIM device and remains fixed for all samples and denoising steps within its inference batch. Different batches are assigned to different virtual devices, yielding a population-level evaluation across CIM mappings. A single guidance scale is shared across the en-




Figure 6: Guidance response on a 3,000-prompt PixArt- Σ sweep. (a) FID and (b) CLIPScore versus w . (c) FID at w_0 and w_σ^* .

tire device population without per-device adaptation. Clean-selected and recalibrated settings use identical prompts, sample seeds, CIM realizations, samplers, and mapped layer sets.

Metrics. We report FID (Heusel et al. 2017) and KID (Bińkowski et al. 2018) for distributional quality. Conditional alignment is CLIPScore (Radford et al. 2021; Hessel et al. 2021) for text-to-image models and ImageNet ViT-B/16 (Dosovitskiy et al. 2021) top-1 accuracy for DiT-XL/2. Precision measures sample fidelity, while density and coverage characterize local realism and support coverage (Kynkäänniemi et al. 2019; Naeem et al. 2020). DINO-clean is the paired DINOv2 cosine similarity (Oquab et al. 2024) between a CIM output and the clean output generated with w_0 from the same condition and sample seed. Accordingly, FID and related distributional metrics characterize the pooled output distribution of the simulated device population.

Experimental Results

Noise-Dependent Guidance Response Figure 6 characterizes the response to w on 3,000 COCO 2017 validation prompts. The FID curves exhibit a finite minimum rather



Figure 7: Qualitative comparisons under CIM noise. Left: PixArt- Σ text-to-image generation at $\sigma_{\text{CIM}} = 0.15$, using $w_0 = 1.5$ and $w_\sigma^* = 2.5$. Right: SD3.5 Medium text rendering at $\sigma_{\text{CIM}} = 0.10$, using $w_0 = 1.5$ and $w_\sigma^* = 3.0$.

than monotonic improvement. The FID-optimal scale moves from 1.5 at $\sigma_{\text{CIM}} \in \{0, 0.05\}$ to 2.0, 2.5, and 4.5 at noise levels 0.10, 0.15, and 0.20, respectively. At $\sigma_{\text{CIM}} = 0.20$, recalibration lowers FID from 75.94 to 37.42, whereas further increases in w degrade FID. CLIPScore increases and then saturates as w grows, indicating that semantic alignment alone is insufficient for selecting the operating point: excessive guidance can preserve prompt alignment while degrading distributional fidelity. The selected scales are then fixed for the independent 30,000-sample evaluation below.

Calibration Efficiency and Transfer To assess whether guidance recalibration requires a large calibration set, we select the guidance scale using 256 calibration prompts and evaluate it on 2,000 disjoint prompts. At $\sigma_{\text{CIM}} = 0.15$, recalibration reduces FID from 51.09 to 43.92, and at $\sigma_{\text{CIM}} = 0.20$, from 79.94 to 44.03, compared with a clean reference of 43.58. The selected scale is shared across all held-out prompts, without per-prompt search or adaptation. Thus, a small calibration subset is sufficient to identify a transferable operating point, making recalibration a lightweight deployment-time procedure.

Large-Scale Generation Quality Using scales selected on independent 3,000-sample sweeps, Table 1 evaluates the pooled population-level distribution with 30,000 samples per setting. At $\sigma_{\text{CIM}} = 0.20$, recalibration reduces FID from 59.22 to 20.49 on PixArt- Σ , from 72.37 to 21.12 on PixArt- α , and from 20.89 to 6.62 on DiT-XL/2. KID changes in the same direction, while conditional alignment, precision, density, and coverage improve for all three models. For each model at $\sigma_{\text{CIM}} = 0.20$, a single recalibrated scale shared across the simulated device population closes at least 87% of the CIM-induced FID gap relative to clean inference without modifying the noisy weights or sampling budget.

Comparison with Sampler-Side Guidance Controls Although not designed for CIM, these methods provide relevant sampler-side comparisons. We tune CFG Rescale (Lin et al. 2024), APG (Sadat, Hilliges, and Weber 2025), C^2FG (Gao et al. 2026), and Limited-Interval Guidance (Kynkäänniemi et al. 2024) under identical CIM settings and report the shared 3,000-prompt comparison. The clean-best row is shared with Figure 6, while fixed recalibration uses its preselected scale rather than the sweep optimum.

Method	$\sigma_{\text{CIM}} = 0.15$	$\sigma_{\text{CIM}} = 0.20$
Clean-best CFG	44.93	75.94
CFG Rescale	40.40	40.72
APG	39.21	41.08
C^2FG	38.11	39.52
Limited-Interval Guidance	37.28	38.76
Fixed recalibration (ours)	36.60	37.61

Table 2: FID in the shared 3,000-prompt PixArt- Σ comparison of sampler-side guidance controls.

Table 2 shows that all sampler-side controls improve over clean-best CFG, indicating that the guidance residual remains an effective correction channel under CIM noise. However, their correction forms were developed for generic guidance artifacts under standard inference rather than the noise-dependent residual distortion induced by CIM. Even after configuration search under each CIM condition, they remain less effective than directly recalibrating the residual strength for the target operating point. This ordering is consistent with guidance-scale mismatch being a substantial and directly correctable component of CIM-induced degradation.

Qualitative Comparisons Figure 7 provides paired qualitative comparisons. Recalibration improves object structure and prompt-specific details for general text-to-image prompts, while also producing more legible and coherent rendered text. These examples indicate that the recovery extends beyond aggregate distributional metrics to challenging semantic and structural details.

Timestep Semantic Entry We probe whether quality recovery is accompanied by earlier semantic commitment during sampling. At each reverse step, we decode the scheduler-consistent predicted-clean sample $\hat{x}_{0|t}$. For each of 1,000 prompts, its CLIP image embedding retrieves the matching text from 1,000 candidates. We define the semantic entry index as the earliest reverse step, counted from the start of sampling, at which the aggregate top-1 retrieval rate reaches a threshold θ and remains above it thereafter. Based on visual inspection of intermediate generations, we set $\theta = 0.30$, at which prompt-consistent content becomes persistently recognizable.




Figure 8: Timestep semantic-entry analysis. (a) Ten evenly spaced checkpoints from 20-step predicted-clean trajectories for two prompts; rows show clean inference, CIM with w_0 , and CIM with w_σ^* . (b–d) Prompt retrieval top-1 accuracy across all steps. (e) Persistent semantic-entry indices at $\theta = 0.30$.

(a) Endpoint counterfactuals								(b) Continuous endpoint interpolation: FID↓					
Metric	Clean	CIM w_0	CIM w_σ^*	Restore u	Restore g	Remove η	Restore α	Intervention	0.00	0.25	0.50	0.75	1.00
FID↓	36.19	75.41	36.64	42.83	68.34	127.75	44.49	Restore aligned gain	75.4	64.1	55.6	49.1	44.5
CLIP↑	30.45	27.27	31.27	28.52	28.87	23.23	30.35	Remove orthogonal term	75.4	86.6	99.6	114.0	127.9
DINO-clean↑	1.000	0.463	0.673	0.621	0.631	0.261	0.699	Remove base error	75.4	58.5	48.3	44.0	42.9

Table 3: Residual-surgery analysis at $\sigma_{\text{CIM}} = 0.20$ over 3,000 prompts. (a) Endpoint counterfactuals. (b) FID along intervention paths from untreated CIM (0) to the full intervention (1).

Figure 8(a) visualizes ten evenly spaced checkpoints for two prompts under clean inference, CIM with w_0 , and CIM with w_σ^* . Panels (b–e) show that recalibration advances persistent entry from step 11 to 10 at $\sigma_{\text{CIM}} = 0.10$, from 12 to 10 at 0.15, and from 15 to 11 at 0.20. The increasing gain with noise is consistent with the proposed trajectory-level interpretation: strengthening the retained target-oriented residual moves the sampler into a target-consistent semantic region earlier, after which the state-dependent denoising dynamics preserve and refine those semantics.

Counterfactual Residual Surgery To probe the decomposition $\tilde{g} = \alpha g + \eta$ through interventions, Table 3 applies counterfactual modifications to paired clean and noisy predictions at $\sigma_{\text{CIM}} = 0.20$. The endpoint interventions restore the clean base prediction u , the clean residual g , or the clean-aligned gain α , and separately remove the orthogonal component η . Continuous paths vary each intervention from untreated CIM at strength 0 to the full intervention at strength 1, reducing dependence on any single endpoint.

Restoring u lowers FID from 75.41 to 42.83, while restoring α yields 44.49 and improves monotonically as the intervention strength increases. Likewise, progressively removing base-path error improves FID, indicating that both com-

mon drift and weakened target-oriented residual control contribute to degradation. Removing η alone worsens FID, indicating that its effect is coupled to base drift and trajectory feedback rather than independently removable. Recalibration reaches 36.64, close to the clean FID of 36.19, by scaling the intact noisy residual instead of attempting componentwise cancellation.

Conclusion

In this paper, we systematically studied the impact of analog CIM nonidealities on DiT sampling and identified the CFG residual as a critical and controllable failure channel. We proposed a retraining-free, sampler-side guidance recalibration method that adjusts only the CFG scale for a target CIM operating condition. Extensive experiments show that the preferred guidance scale increases with CIM noise and that our method consistently restores generation quality. At $\sigma_{\text{CIM}} = 0.20$, guidance recalibration closes at least 87% of the CIM-induced FID gap, reducing FID from 59.22 to 20.49 on PixArt- Σ , from 72.37 to 21.12 on PixArt- α , and from 20.89 to 6.62 on DiT-XL/2. We further provide a trajectory-level interpretation of how guidance recalibration restores generation quality under CIM noise.

References

- Birnkowski, M.; Sutherland, D. J.; Arbel, M.; and Gretton, A. 2018. Demystifying MMD GANs. In *International Conference on Learning Representations*.
- Bradley, A.; and Nakkiran, P. 2025. Classifier-Free Guidance Is a Predictor-Corrector. *Transactions on Machine Learning Research*.
- Chen, J.; Ge, C.; Xie, E.; Wu, Y.; Yao, L.; Ren, X.; Wang, Z.; Luo, P.; Lu, H.; and Li, Z. 2024a. PixArt- Σ : Weak-to-Strong Training of Diffusion Transformer for 4K Text-to-Image Generation. In *European Conference on Computer Vision*, 74–91.
- Chen, J.; Yu, J.; Ge, C.; Yao, L.; Xie, E.; Wu, Y.; Wang, Z.; Kwok, J.; Luo, P.; Lu, H.; and Li, Z. 2024b. PixArt- α : Fast Training of Diffusion Transformer for Photorealistic Text-to-Image Synthesis. In *International Conference on Learning Representations*.
- Chung, H.; Kim, J.; Park, G. Y.; Nam, H.; and Ye, J. C. 2025. CFG++: Manifold-Constrained Classifier Free Guidance for Diffusion Models. In *International Conference on Learning Representations*.
- Deng, J.; Dong, W.; Socher, R.; Li, L.-J.; Li, K.; and Fei-Fei, L. 2009. ImageNet: A Large-Scale Hierarchical Image Database. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 248–255.
- Dosovitskiy, A.; Beyer, L.; Kolesnikov, A.; Weissenborn, D.; Zhai, X.; Unterthiner, T.; Dehghani, M.; Minderer, M.; Heigold, G.; Gelly, S.; Uszkoreit, J.; and Houshy, N. 2021. An Image Is Worth 16x16 Words: Transformers for Image Recognition at Scale. In *International Conference on Learning Representations*.
- Esser, P.; Kulal, S.; Blattmann, A.; Entezari, R.; Müller, J.; Saini, H.; Levi, Y.; Lorenz, D.; Sauer, A.; Boesel, F.; Podell, D.; Dockhorn, T.; English, Z.; and Rombach, R. 2024. Scaling Rectified Flow Transformers for High-Resolution Image Synthesis. In *International Conference on Machine Learning*, 12606–12633.
- Gao, J.; Zheng, T.; Zou, J.; Yang, F.; Liu, S.; Fan, L.; Zhang, Z.; Zhang, H.; Chen, J.; Jiang, P.-T.; Li, B.; and Wang, J. 2026. C²FG: Control Classifier-Free Guidance via Score Discrepancy Analysis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 34398–34407.
- Guo, R.; Wang, L.; Chen, X.; Jiang, K.; Yue, Z.; Han, H.; Wang, Y.; Tu, F.; Wei, S.; Hu, Y.; and Yin, S. 2026. Denim: Heterogeneous Compute-in-Memory Accelerator Exploiting Denoising-Similarity for Diffusion Models. *IEEE Journal of Solid-State Circuits*, 1–15.
- Hessel, J.; Holtzman, A.; Forbes, M.; Le Bras, R.; and Choi, Y. 2021. CLIPScore: A Reference-Free Evaluation Metric for Image Captioning. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, 7514–7528.
- Heusel, M.; Ramsauer, H.; Unterthiner, T.; Nessler, B.; and Hochreiter, S. 2017. GANs Trained by a Two Time-Scale Update Rule Converge to a Local Nash Equilibrium. In *Advances in Neural Information Processing Systems*.
- Ho, J.; Jain, A.; and Abbeel, P. 2020. Denoising Diffusion Probabilistic Models. In *Advances in Neural Information Processing Systems*, volume 33, 6840–6851.
- Ho, J.; and Salimans, T. 2022. Classifier-Free Diffusion Guidance. *arXiv preprint arXiv:2207.12598*.
- Hou, Y.; Tsai, H.; El Maghraoui, K.; Gokmen, T.; Burr, G. W.; and Liu, L. 2025. NORA: Noise-Optimized Rescaling of LLMs on Analog Compute-in-Memory Accelerators. In *2025 Design, Automation & Test in Europe Conference*.
- Jain, A.; Kobayashi, Y.; Shibuya, T.; Takida, Y.; Memon, N.; Togelius, J.; and Mitsufuji, Y. 2025. Classifier-Free Guidance Inside the Attraction Basin May Cause Memorization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 12871–12879.
- Jing, Y.; Wu, M.; Zhou, J.; Sun, Y.; Ma, Y.; Huang, R.; Jia, T.; and Ye, L. 2024. AIG-CIM: A Scalable Chiplet Module with Tri-Gear Heterogeneous Compute-in-Memory for Diffusion Acceleration. In *Proceedings of the 61st ACM/IEEE Design Automation Conference*, 1–6.
- Joshi, V.; Le Gallo, M.; Haefeli, S.; Boybat, I.; Nandakumar, S. R.; Piveteau, C.; Dazzi, M.; Rajendran, B.; Sebastian, A.; and Eleftheriou, E. 2020. Accurate Deep Neural Network Inference Using Computational Phase-Change Memory. *Nature Communications*, 11: 2473.
- Kynkäänniemi, T.; Aittala, M.; Karras, T.; Laine, S.; Aila, T.; and Lehtinen, J. 2024. Applying Guidance in a Limited Interval Improves Sample and Distribution Quality in Diffusion Models. In *Advances in Neural Information Processing Systems*.
- Kynkäänniemi, T.; Karras, T.; Laine, S.; Lehtinen, J.; and Aila, T. 2019. Improved Precision and Recall Metric for Assessing Generative Models. In *Advances in Neural Information Processing Systems*.
- Lin, S.; Liu, B.; Li, J.; and Yang, X. 2024. Common Diffusion Noise Schedules and Sample Steps Are Flawed. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, 5404–5411.
- Lin, T.-Y.; Maire, M.; Belongie, S.; Hays, J.; Perona, P.; Ramanan, D.; Dollár, P.; and Zitnick, C. L. 2014. Microsoft COCO: Common Objects in Context. In *European Conference on Computer Vision*, 740–755.
- Lu, C.; Zhou, Y.; Bao, F.; Chen, J.; Li, C.; and Zhu, J. 2022. DPM-Solver: A Fast ODE Solver for Diffusion Probabilistic Model Sampling in Around 10 Steps. In *Advances in Neural Information Processing Systems*, volume 35, 5775–5787.
- Naeem, M. F.; Oh, S. J.; Uh, Y.; Choi, Y.; and Yoo, J. 2020. Reliable Fidelity and Diversity Metrics for Generative Models. In *International Conference on Machine Learning*, 7176–7185.
- Oquab, M.; Darcet, T.; Moutakanni, T.; Vo, H. V.; Szafraniec, M.; Khalidov, V.; Fernandez, P.; Haziza, D.; Massa, F.; El-Nouby, A.; Assran, M.; Ballas, N.; Galuba, W.; Howes, R.; Huang, P.-Y.; Li, S.-W.; Misra, I.; Rabbat, M.; Sharma, V.; Synnaeve, G.; Xu, H.; Jégou, H.; Mairal, J.; Labatut, P.; Joulin, A.; and Bojanowski, P. 2024. DINOv2: Learning Robust Visual Features without Supervision. *Transactions on Machine Learning Research*.

Peebles, W.; and Xie, S. 2023. Scalable Diffusion Models with Transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 4195–4205.

Radford, A.; Kim, J. W.; Hallacy, C.; Ramesh, A.; Goh, G.; Agarwal, S.; Sastry, G.; Askell, A.; Mishkin, P.; Clark, J.; Krueger, G.; and Sutskever, I. 2021. Learning Transferable Visual Models From Natural Language Supervision. In *International Conference on Machine Learning*, 8748–8763.

Sadat, S.; Hilliges, O.; and Weber, R. M. 2025. Eliminating Oversaturation and Artifacts of High Guidance Scales in Diffusion Models. In *International Conference on Learning Representations*.

Sebastian, A.; Le Gallo, M.; Khaddam-Aljameh, R.; and Eleftheriou, E. 2020. Memory Devices and Applications for In-Memory Computing. *Nature Nanotechnology*, 15: 529–544.

Shafiee, A.; Nag, A.; Muralimanohar, N.; Balasubramonian, R.; Strachan, J. P.; Hu, M.; Williams, R. S.; and Srikumar, V. 2016. ISAAC: A Convolutional Neural Network Accelerator with In-Situ Analog Arithmetic in Crossbars. In *Proceedings of the 43rd International Symposium on Computer Architecture*, 14–26.

Song, Y.; Sohl-Dickstein, J.; Kingma, D. P.; Kumar, A.; Ermon, S.; and Poole, B. 2021. Score-Based Generative Modeling through Stochastic Differential Equations. In *International Conference on Learning Representations*.

Stability AI. 2024. Introducing Stable Diffusion 3.5. <https://stability.ai/news/introducing-stable-diffusion-3-5>. Accessed: 2026-07-29.

Wan, W.; Kubendran, R.; Schaefer, C.; Eryilmaz, S. B.; Zhang, W.; Wu, D.; Deiss, S.; Raina, P.; Qian, H.; Gao, B.; Joshi, S.; Wu, H.; Wong, H.-S. P.; and Cauwenberghs, G. 2022. A Compute-in-Memory Chip Based on Resistive Random-Access Memory. *Nature*, 608: 504–512.

Yang, J.; Chen, H.; Chen, J.; et al. 2026. Resistive Memory-Based Neural Differential Equation Solver for Score-Based Diffusion Model. *Nature Communications*, 17: 6354.

Zhu, Z.; Li, H.; Ren, W.; Wu, M.; Ye, L.; Huang, R.; and Jia, T. 2025. Leveraging Compute-in-Memory for Efficient Generative Model Inference in TPUs. In *2025 Design, Automation & Test in Europe Conference*, 1–7.