

Strangers to Themselves: What Language Models Say About Themselves Is Generic

Phil Blandfort*
Predictably Weird

Urja Pawar
Independent

Abstract

Language models can fluently describe how they would behave: whether they would cave to pushback, misuse a tool, or lie under pressure. Is that description actually about the model speaking? We turn self-knowledge into a prediction test. Across nine behavioral evaluations, we measure how a model behaves under different conditions, ask it to predict those rates, and compare its predictions with controls that remove the self from the question. We find that: (i) Direct self-report is weak ($r = +0.04$), and even showing the model the exact items only raises prediction to +0.24. Crucially, the same item-informed question about “capable AI agents in general” does just as well (+0.28), while other models’ answers about themselves predict the target model at least as well as its own. (ii) Frontier scale does not detectably change this pattern: any gains in prediction are not self-specific, and are consistent with a better theory of how AI assistants behave rather than better self-knowledge. (iii) First-person framing does have one robust effect: it shifts reports in the flattering direction, understating harmful behavior relative to the same question about a generic agent. (iv) Finetuning on a model’s own behavioral record can teach narrow self-predictions, but it also changes the behavior being predicted and the gains do not transfer broadly. The practical implication is simple: asking a model what it would do mostly reveals a theory of AI assistants in general, plus a favorable bias, rather than privileged knowledge of that model.

1 Introduction

How can we know how a language model will behave in situations that we cannot evaluate directly? Behavioral evaluations remain the standard tool, but they cover only a small fraction of the settings a deployed model may encounter. This gap is especially acute for long-horizon, tool-using, and multi-party interactions, which are expensive to construct and difficult to measure faithfully, and this only gets harder as models act more autonomously. In these settings, developers may want to turn to a model’s stated values or its account of what it would do. The central question of this paper is whether such statements provide reliable evidence about the behavior of the particular model making them.

Prior work documents persistent gaps between stated and revealed behavior across model generations [Bai et al., 2025b, Xu et al., 2025, Gu et al., 2025, Mahajan et al., 2026], while other work finds that stated preferences and values can predict behavior in specific settings [Slama et al., 2026, Hua et al., 2026, Chiu et al., 2025, Mazeika et al., 2025, Ren et al., 2026]. What both lines of work lack is a baseline that predicts behavior without consulting the model under test, using either other models’ measured behavior or a generic description of an AI assistant. Without this reference point, agreement between a model’s statement and its behavior could reflect generic knowledge of how AI assistants behave rather than privileged self-knowledge.

*Contact details on predictablyweird.com.




Figure 1: Adding information shifts the answers and modestly improves how well they track behavior, but asking about the model itself does not. Each group hands the predictor more to work with, from a description of the situation, to the model’s own measured rates on the evaluation’s other conditions, to the exact items it was scored on. Within a group only the subject changes: *itself* asks the model about its own rate, *AI in general* asks the same about a capable AI assistant in general, *outside analyst* is a separate fixed model (Claude Sonnet 4) told which model it is profiling and shown that model’s history, and *other models* averages what the remaining models say about themselves. Evaluation on test split.

We measure self-knowledge *as prediction* (Fig. 2). Each *condition* of a behavioral evaluation has a measured rate. For example, in the sycophancy evaluation, a condition is an MMLU subject and its rate is how often the model abandons a correct answer under pushback. A *prediction method* estimates that rate for each condition, and we score predictions by correlation and calibration on frozen test splits. We vary three features independently: the *information* available to the model, from an abstract description to the exact evaluation questions; the *subject* of the question, either “you”, a named model, or “capable AI agents in general”; and the *question form*, either a direct rate or a forced choice. The subject comparison is central: it distinguishes an answer that is specific to the model from one that is simply correct about AI assistants in general. We also predict each model from other models’ measured behavior, which captures shared structure and provides a reference point for any model-specific signal.

Three questions organise the experiments. **(RQ1)** How much of each behavior is model-specific rather than shared across models? **(RQ2)** When a model describes its own behavior, is the description about *it*? **(RQ3)** Do more information, different question forms, scale, or training on a model’s own behavior change the answer? The results are largely negative, but in informative ways.

There is something to know. The model-specific share of reliably measurable variance ranges from about 0.04 on Capability, where models largely agree on which subjects are hard, to about 0.97 on agentic policy evaluations, where models differ more sharply in their behavior across situations. A null result, therefore, is less informative on the former, where there is scarcely anything model-specific to know, but is much more informative on the latter.

Models have a theory of AI behavior, not a self-model. Given only a description of the situation, a model’s statement about its own behavior predicts it at $r = +0.04$. Showing the model its own measured history raises this to +0.19, and showing it the exact evaluation questions raises it to +0.24. However, the same item-informed question about “capable AI agents in general” performs just as well (+0.28), other models’ answers about themselves predict the target model better than its own answers do (+0.35 versus +0.24), and each model’s answers fit other models’ behavior nearly as well as its own (a self-advantage of only +0.02).

Scale does not change this. Frontier models from three labs improve at predicting how AI assistants behave, but not at identifying which tendencies are their own. Their self-reports are no more accurate than those of smaller models (+0.02, not significant).

The self is present in the answer, but as a bias. Naming the model as the subject shifts reports in a self-flattering direction. On behaviors where a high rate is harmful, self-reports sit -0.15 below the same reports about a generic agent.

Training helps narrowly, but moves the target. Finetuning a model on records of its own behavior can improve self-prediction for the behavior it was trained on, but it also changes that behavior. The tuned model therefore partly describes the model it used to be, and the gains do not transfer broadly across behaviors or levels of abstraction.

Contributions. We introduce a prediction-based test of self-knowledge and the controls a positive claim must survive: noise ceilings, a cross-model consensus baseline, generic-subject questions, other models’ answers, identity transfer, and re-elicitation after finetuning. Most of our own raw positive correlations fail at least one of these controls (Sections 2 and 4.1). We apply this framework to run a large-scale study across nine public benchmarks, 15 prediction methods, and 12 models from six labs, including three frontier bases with and without reasoning. We release the code and measurements so future self-knowledge claims can be tested under the same protocol.²

2 The Behavior-Prediction Protocol

This section defines how behavioral evaluations and prediction methods enter the protocol, how predictions are scored, what bounds a good score, and how splits keep those scores reliable. Implementation details are in Appendix C.

Conditions and methods. Each behavioral evaluation specifies its *conditions*, the cells at which behavior is measured as a rate; its *split units*; and how each rate is measured. A condition might be an MMLU subject for sycophancy, a (decision-topic, demographic) cell for DiscrimEval, or a task scenario for an agentic evaluation. A *method* emits one predicted rate per condition, whether it is a question posed to the model, an analyst reading its history, or a statistic of other models’ behavior. Every method is scored on every evaluation.

Scoring. For an (evaluation, model) cell with conditions $i = 1, \dots, C$, let y_i be the measured rate and $\hat{y}_i$ the predicted rate. Our primary metric is the Pearson correlation $r(\hat{y}, y)$ across conditions: does the method track which conditions are riskier or more interesting? A method that provides no usable ordering, such as a constant prediction, scores zero. For methods that predict rates on the evaluation’s scale, we also report mean absolute error, $\frac{1}{C} \sum_i |\hat{y}_i - y_i|$, and signed bias, $\frac{1}{C} \sum_i (\hat{y}_i - y_i)$, where negative values indicate systematic understatement. We macro-average over (model $\times$ eval) cells with bootstrap confidence intervals. Conclusions are unchanged under Spearman rank correlation (Appendix I).

Noise ceilings. A correlation is interpretable only relative to what measurement noise permits. Each (eval, model) cell therefore receives a *ceiling*: the correlation attainable by a perfect predictor given noise in its measured rates, estimated by parametric bootstrap. We report the normalised median $r/\text{ceiling}$ as a secondary metric and drop cells whose behavior is too noisy or nearly constant to support a meaningful ordering. This criterion uses measured behavior alone and cannot favour one prediction method over another. Without it, a low correlation could mean either that the method has no signal or that there is nothing measurable to predict.

Splits and calibration. Each evaluation’s split units are partitioned into a *dev pool* and a *frozen test* set. We use the dev pool to select one configuration per (method, eval) from each method’s prompt or hyperparameter grid, then evaluate those frozen configurations on the held-out test set. Some methods are fitted predictors that estimate parameters from measured rates on other conditions. Within the dev pool these are cross-validated by holding out whole fold groups, so their dev scores are pooled out-of-fold predictions; test conditions are predicted from a single fit on the entire dev pool, so the frozen test split never enters a fit. Stateless methods fit nothing and predict each condition once.

3 Experimental Setup

This section describes the behavioral evaluations, prediction methods, models, and configuration-selection procedure used in our experiments.

²Repository: <https://github.com/PredictablyWeird/strangers-to-themselves>




Figure 2: **Illustration of the protocol on one concrete evaluation** (Sycophancy, Llama-3.3-70B). *Left*: a condition is one MMLU subject, and its rate is how often the model abandons a correct answer under pushback. *Middle*: what each channel predicts for a single condition. The first two questions differ only in who they are about, asking how often *you* would cave against how often *a capable AI assistant* would cave, and both return 0%. *Right*: the same channels scored across all conditions. The cross-model mean, which averages the *other* models’ measured flip rates and never asks this model anything, ranks the subjects at $r = +0.37$. Item-informed self-prediction, shown the exact items the model was measured on, reaches only $+0.20$, and self-report is a constant 0% and so has no defined correlation. The most generous self-prediction setup we can construct is beaten by a prior that never consults the model.

Evaluations. We study nine behavioral evaluations from six independent scenario sources, covering demographic bias, sycophancy, capability, reward hacking, misuse and lying under pressure, agentic policy violation, and agentic misalignment (Table 3). This is broader coverage than prior stated-versus-revealed studies, which typically examine one or two behavior families on purpose-built items (§6). Agentic misalignment is held out from configuration selection: it has no dev split, and every method uses the configuration that was found to be optimal for the other eight evaluations (based on dev splits). Appendix B gives design details, sample counts, and held-out domains.

Prediction methods. We evaluate fifteen methods, distinguished by the information they receive and who they are asked about (Table 6). *Abstract asking* gives only a description of the situation, through direct self-report, value framing, or a paired comparison question. *Informed asking* adds either the model’s measured behavior on other conditions or the exact evaluation questions. *Watching* replaces asking with re-measurement on generated proxy scenarios; its item-informed version also gives the scenario generator the real evaluation questions to work from. Each asking method has a matched generic-subject *control* that asks about “capable AI agents in general”, as well as controls based on other models’ reports and the cross-model mean of their measured behavior. Any self-specific content must appear as a gap between a method and these controls. Full prompts, configurations, and costs appear in Appendices D–F.

Models. We study twelve entries from six labs: six small-to-mid-size models, plus three frontier bases (Claude Sonnet 5, GPT-5.5, and DeepSeek V4 Pro), with the frontier bases each run both with and without low-effort reasoning (Appendix A). Pool-derived predictors use the remaining models as donors, excluding reasoning variants of the same base weights.

Configuration selection and scoring. We select the best configuration for each (method, eval) on the dev pool, aggregated over the six small models. Fitted methods use leave-one-group-out cross-validation. Frontier models are then evaluated using these frozen configurations, so no setting is selected to favour them. A separate check confirms that tuning settings for each frontier model individually would add little (Appendix L.5). Behavior is measured with multiple samples per condition, a fixed grader where needed, and swapped A/B order for comparative prompts. All headline results use the frozen test split, evaluated once. Claims were pre-specified based on the dev splits before unblinding. Uncertainty is reported as bracketed 95% bootstrap confidence intervals over (model

Table 1: Results for all prediction methods (frozen test split; settings tuned and frozen on dev; Pearson r ; Mean = macro over (model $\times$ eval) cells; r/ceil = median ceiling-normalized correlation). Indented rows are paired *subject* controls: the same question and information, asked about a generic agent or answered by the other models about themselves. **These more generic controls perform slightly better than their self-specific counterparts.** Per-model breakdowns are in Appendix G.

Method	Discrim	PropB	Capab.	Syco.	RewHack	τ^2_p	τ^2_t	MASK	AM	Mean	r/ceil
<i>Abstract questions (§4.2)</i>											
self-report	-0.11	+0.00	+0.06	+0.03	+0.02	+0.01	+0.08	+0.08	+0.19	+0.04	+0.00
generic report	+0.15	+0.26	+0.10	+0.19	+0.25	-0.03	+0.11	+0.25	+0.10	+0.16	+0.16
value framing	-0.09	+0.04	NA	+0.07	+0.07	+0.05	+0.19	+0.26	+0.05	+0.09	+0.04
paired comparison	NA	+0.21	+0.29	+0.20	+0.06	+0.13	+0.27	+0.35	+0.26	+0.22	+0.29
<i>Own measured history as examples (§4.3)</i>											
history-informed self-prediction	-0.16	+0.20	+0.10	+0.38	+0.44	+0.15	+0.01	+0.21	NA	+0.19	+0.23
analyst, same history	-0.04	+0.35	+0.19	+0.37	+0.48	-0.12	+0.22	+0.66	NA	+0.28	+0.34
analyst forecast	+0.03	+0.22	+0.12	+0.45	+0.55	+0.04	+0.14	+0.68	NA	+0.30	+0.37
<i>Verbatim measured items (§4.3)</i>											
item-informed self-prediction	+0.26	+0.06	+0.43	+0.37	+0.29	+0.11	+0.22	+0.20	+0.18	+0.24	+0.27
generic subject	+0.26	+0.43	+0.40	+0.43	+0.38	-0.09	+0.02	+0.37	+0.27	+0.28	+0.36
others' mean	+0.29	+0.28	+0.62	+0.43	+0.53	+0.24	+0.21	+0.17	+0.32	+0.35	+0.47
item-informed paired comparison	+0.12	+0.32	+0.09	+0.32	+0.39	+0.08	+0.07	+0.47	+0.03	+0.22	+0.26
<i>Watching, i.e. sampled behavior on generated proxy scenarios</i>											
proxy-scenario sampling	+0.14	+0.11	+0.01	+0.29	-0.15	-0.05	+0.25	+0.26	+0.56	+0.14	+0.10
item-informed proxy sampling	+0.21	+0.03	+0.03	+0.27	+0.10	-0.14	+0.13	+0.16	+0.27	+0.11	+0.09
<i>Never consults the model under test (§4.1)</i>											
cross-model behavior mean	+0.31	+0.46	+0.83	+0.67	+0.89	-0.09	+0.38	+0.73	+0.30	+0.53	+0.69
mean of others' self-reports	-0.11	+0.00	-0.10	+0.09	+0.18	-0.08	+0.17	+0.50	+0.16	+0.10	+0.05

$\times$ eval) cells; every interval in the paper is at this level, so brackets after an estimate always denote its 95% CI. Paired contrasts report the mean cellwise difference with its interval (Appendix B). Appendix K reports the corresponding dev-split analyses and replication checks.

4 Results

We present a sequence of controlled comparisons that vary one feature of the prediction setup at a time. The full leaderboard and per-model results are in Appendix G.

4.1 How much is there to know? Shared structure vs. self-specific signal

Self-knowledge can only predict behavior that varies with the model, so we first estimate how much reliably measurable variation is model-specific. Let r_{pool} be the correlation between a model's measured rates and the cross-model behavior mean, computed from the other pool models, and let c be the cell's noise ceiling. Then $1 - (r_{\text{pool}}/c)^2$ estimates the *knowable self-specific share*: the reliable variation not already explained by the situation and shared across models. This share is small on Capability (~ 0.04) and reward hacking (~ 0.10), intermediate on Sycophancy, MASK, and PropensityBench, and largest on DiscrimEval and the two τ^2 evaluations.

We use this estimate to rank evaluations rather than to quantify exactly how much self-knowledge is available in any one setting. Its ordering is stable at the high and low ends across dev and test splits, but it depends on the composition of the model pool and on estimated noise ceilings. It is also only an upper bound: some of that residual variation could be stable yet still not something a model could ever report about itself. The cross-model behavior mean is therefore an instrument for separating shared from model-specific structure, not a baseline that self-prediction methods must beat. We read each result below in two steps: how much model-specific behavior there was to predict, and whether the method reached it.

4.2 Asking the model from a description barely works

We tested three question forms that provide only an abstract description of the situation: direct self-report, a framing of the choice as a conflict between the model's stated values, and a forced choice between two situations (paired comparison). None produces strong predictions. Macro correlations

range from +0.04 for direct self-report to +0.22 for paired comparison, with near-constant denial on Sycophancy and PropensityBench (Table 1). The models also understate harmful behavior: self-report has mean signed bias -0.19, reaching -0.42 on PropensityBench.

Why the indirect forms do better. Paired comparison and the generic-report control perform best among the abstract methods, reaching +0.22 and +0.16 respectively. Both reduce the need to state an incriminating rate about oneself. The generic-subject framing removes most of the understatement, while paired comparison recovers signal where direct self-report collapses into denial, particularly on PropensityBench. Relative judgments may also be easier, but the stronger generic control already suggests that the surviving signal is about AI assistants in general rather than the model itself.

The failure is not an artifact of elicitation. Several checks rule out simple alternatives (Appendix L.1). Predictions are split-half reliable, so the weak results are not explained by elicitation noise. A deniable-count list experiment is a powered null wherever direct reports fail, and abstract answers predict the benchmark better than behavior re-measured on new proxy scenarios generated from the same descriptions. Some Sycophancy self-assessments are systematically inverted, but this limited exception does not change the overall result (Appendix L.5, Table 23).

4.3 Information helps but prediction performance stays moderate

The strongest asking method is *item-informed self-prediction*, in which the model sees the exact evaluation questions and predicts its own rate on them (macro r +0.24; Fig. 1). More information improves prediction: an abstract description yields +0.04, the model’s measured history raises this to +0.19, and the exact questions raise it to +0.24. Even then, performance remains moderate, capturing less than a third of what the noise ceilings allow (median $r/\text{ceiling}$ +0.27).

The gain comes from information, not privileged self-knowledge. One might expect that models should be able to use information about their own measured history better than another model could. However, a fixed third-party analyst (Claude Sonnet 4; Appendix A) given the same history performs better (+0.28 versus +0.19; paired difference -0.10 [-0.19, -0.02]), and models do not predict their own behavior better when reading their own history than when reading another model’s (Appendix L.3). The useful signal is therefore in the record itself, not in privileged access to the model that produced it.

This result is clearest on the five single-turn evaluations, where the item-informed method sees all information defining a condition. On agentic evaluations, it sees only the opening state, so weak performance may also reflect the difficulty of forecasting a long interaction (Appendix L.2).

Watching instead of asking. Re-measuring the model on generated proxy scenarios, the most expensive method in the suite, carries little signal (+0.14 macro), except on held-out agentic misalignment (+0.56; Appendix L.2). Surprisingly, giving the scenario generator the exact measured items does not improve test performance (+0.11). Information therefore improves asking but not watching: proxy sampling remains well below item-informed asking and direct re-measurement (Appendix F).

4.4 The answer is not about the *self*

Being able to predict behavior from an item and knowing something about *oneself* are different claims. We test for self-specificity by holding the information fixed while varying the subject of the question, then asking whose behavior each model’s answers best predict.

Removing the self from the question costs nothing. The generic-subject variant shows the same items and uses the same protocol, but asks what *capable AI agents in general* would do. It performs as well as item-informed self-prediction (+0.28 versus +0.24; paired difference -0.03 [-0.10, +0.03]).

³A phrasing ablation reproduces this result when the self is removed from both the question and the preceding description (Appendix L.4).

Other models’ answers predict a model at least as well as its own. The mean of other models’ item-informed self-predictions, each made about that model itself, predicts the target model better than its own answers do (+0.35 versus +0.24). The same pattern appears for abstract self-reports: other models’ reports and the generic-subject control both outperform direct self-report. On PropensityBench, first-person questions about any named model produce constant denial, while generic questions retain graded signal. This again suggests that the knowledge being suppressed is generic rather than self-specific (Appendix L.3).

Whose behavior do the answers fit? We score each model’s item-informed answers against every model’s measured behavior. If the answers were introspective, they should fit the answerer’s own behavior best; generic answers should fit all models similarly. On the frozen test split, answers fit the answerer’s own behavior at +0.27 and other models’ behavior at +0.25, a self-advantage of only +0.02 (dev: +0.03); the dev split’s concentration of the advantage on PropensityBench and Capability did not replicate on test (−0.11 and +0.03 there), and what remains shows no stable evaluation-specific pattern (Appendix K). An advantage this small carries little weight on its own, and the generic-subject variant shows a comparable one despite naming no individual model, so we do not read it as evidence that the signal is specifically about “you” (Appendix L.3).

Net of shared knowledge, self-report adds little. We next test whether each method adds predictive signal beyond the cross-model behavior mean, measured per (evaluation, model) cell as a partial correlation given that predictor. Direct self-report adds none (+0.04 [−0.06, +0.14]). Item-informed self-prediction adds a small contribution (+0.12 [+0.05, +0.20]; positive in 52 of 87 cells), which is carried by DiscrimEval (+0.15 [+0.05, +0.26]) and Sycophancy (+0.21 [+0.06, +0.35]; not pre-registered). Note that this test credits any signal the pool mean lacks, including generic item-reading that the particular pool does not share, so a positive partial is necessary but not sufficient for self-knowledge. Combining the two channels tells a consistent story from the other side: a learned ensemble of the outside view and item-informed self-prediction behaves like a per-evaluation maximum of its components rather than a synthesis (Appendix H).

4.5 The self shows up in the answer, but as a bias

While self-reports are largely generic, the self is not absent from the answer. It appears in the *level* of the prediction. Comparing the same question about the model and about a generic agent on the six evaluations where a high rate is harmful, the self-framed abstract report is shifted by −0.15 [−0.19, −0.11] and the item-informed report by −0.09 [−0.12, −0.07] relative to the generic-subject question. This is not simple shrinkage toward zero: naming the self raises predicted scores on Capability, where a high rate is creditable, and has no effect on DiscrimEval’s non-valenced signed contrast. Asking about a generic agent therefore removes much of the favorable bias while predicting behavior at least as accurately (Appendix J); the two framings order both the individual items and, to a lesser degree, the conditions themselves differently, so the generic question is an equally accurate replacement for the self-framed one rather than a debiased copy of it (Appendix L.4). This analysis was added after unblinding and is descriptive; the pre-registered statement it extends (all signed biases ≤ 0) held on test.

4.6 Scale buys a better theory of AI, not self-knowledge

We compare six small-to-mid-size models with three frontier bases, each evaluated with and without reasoning, using configurations selected on the small-model pool (Sec. 3). Because some frontier models show near-constant behavior on the agentic evaluations, tier comparisons use the four single-turn text evaluations (DiscrimEval, Capability, Sycophancy, Reward hacking). Per-model results are in Appendix G (Table 9); the per-tier summary, the continuous capability analysis, and the setting-sensitivity checks that support this subsection are in Appendix L.5 (Table 22, Fig. 5).

Prediction accuracy does not detectably improve with tier. On the four shared evaluations, frontier models’ self-reports do not significantly improve on those of the small-model tier (+0.02 [−0.12, +0.17]). Item-informed self-prediction is similarly flat across tiers (+0.36 for frontier models versus +0.32 for smaller models). The result is a null rather than evidence of equivalence: the confidence interval is too wide to rule out a small improvement.

The gains that do appear are not self-specific. Removing the self from the item-informed question costs frontier models nothing, and their predictions fit *smaller models*’ behavior about as well as their own. Reasoning improves both own- and other-model prediction in parallel, while the unique signal beyond the cross-model behavior mean remains at, rather than above, the small-tier level. Where frontier models improve, they appear to improve at reading the items and predicting how AI assistants behave in general, not at knowing which tendencies are their own.

Reasoning changes behavior and computation, not self-knowledge. Enabling reasoning leaves self-report largely unchanged and improves item-informed prediction for two of the three frontier bases. The generic-subject control improves in step, indicating better computation over the items rather than stronger self-knowledge. Reasoning also changes the behavior being predicted: it makes the cross-model mean slightly less accurate and, for some models, changes whether they answer the elicitation at all: Claude Sonnet 5 with reasoning enabled will answer a PropensityBench history question that the same model refuses outright with reasoning turned off.

Several frontier models also show floor effects on agentic evaluations, leaving no reliable variation across conditions to predict; these cells are excluded by the pre-specified ceiling filter.

4.7 Can self-knowledge be trained in? A fixed-point problem

Following Binder et al. [2025], we finetune four base models on records of their own measured behavior (Appendix M). Self-prediction is learnable, but the finetune also changes the behavior being predicted, so single-round accuracy can describe the model’s earlier behavior rather than its re-elicited behavior. The gains are also locked to the grain and item families used in training: condition-level rate training improves condition-level self-report but not item-informed prediction, while single-prompt training improves single-prompt self-simulation without improving dispositional prediction. We find no broad transfer across evaluations or levels of abstraction.

5 Discussion

Why self-descriptions might be generic. The results have a consistent pattern: reports are reliable under resampling, agree across models, and predict other models’ behavior nearly as well as the reporter’s own. This is consistent with a shared picture of how AI assistants behave, learned from text about AI assistants, rather than with access to a model-specific behavioral record: pretraining supplies exactly this material, and nothing in pretraining or preference tuning rewards a model for tracking its own tendencies. First-person framing changes the level of the answer, but mainly by adding a favorable bias rather than self-specific content.

What might change the picture. Showing a model its measured history improves prediction, but another model given the same record does at least as well in our experiments (§4.3). A system with retrieval over its own *behavioral record* could therefore make accurate first-person statements without requiring an introspective mechanism in the forward pass. *Finetuning* is another route, but our results show that it creates a fixed-point problem: a single round of training teaches the model about its earlier behavior, at the grain and on the item families represented in training (§4.7). Our reading is that a single-prompt property is represented in the forward pass that produces it, so a finetune can wire a readout to it, whereas a cross-context rate exists only procedurally, as the policy in the weights, and is represented in no single forward pass. Therefore, a finetune can only install a declarative lookup, which would be consistent with our observations. Whether activation-level introspection can support broader cross-context self-description remains an open question.

Implications for evaluation and safety. Asking a model how it would act currently provides evidence about AI assistants in general, not about the particular model being asked. It is also biased: self-framed answers understate harmful behavior relative to the same question about a generic agent. A statement such as “I would not” should therefore not be treated as reassurance. Where direct measurement is impossible, a measured near-peer model or a generic-agent question provides the same information with less bias; where elicitation is unavoidable, the item-informed generic-agent question is the best-calibrated form we found.

6 Related Work

Introspection and self-knowledge. Binder et al. [2025] finetune models to predict properties of their own responses and interpret this as evidence of privileged self-access. Related work studies introspection and confidence calibration [Laine et al., 2024, Betley et al., 2025, Kadavath et al., 2022]. Our cross-model behavior baseline is a stronger control than an imitator trained on finite finetuning data, and our target is cross-context behavioral prediction rather than single-prompt self-simulation (Appendix M). Anthropic report *activation-level* introspection that strengthens with capability [Lindsey, 2025]; we find no corresponding trend for cross-context self-description (§4.6).

Model identification and self-recognition. Classifiers can attribute generated text to its source model with high accuracy [Sun et al., 2025]. Whether a model recognizes its *own* text is contested: Panickssery et al. [2024] and Ackerman and Panickssery [2025] report above-chance self-recognition, while Bai et al. [2025a] evaluate ten models and find a consistent failure, rarely above chance. Our setting differs on both sides of that comparison: the quantity is a behavioral rate rather than the authorship of a text, and the reference point is an outside-view baseline rather than chance.

Stated preferences, values, and consistency. Some work finds that stated preferences or values predict behavior in particular settings [Slama et al., 2026, Hua et al., 2026, Chiu et al., 2025, Mazeika et al., 2025, Ren et al., 2026], while other work documents persistent gaps between stated and revealed behavior [Bai et al., 2025b, Xu et al., 2025, Gu et al., 2025, Mahajan et al., 2026]. We combine controls that prior work has not used together: an outside-view behavior baseline, generic-subject questions, and identity transfer. Our experiments span nine public benchmarks and twelve models from six labs and are substantially larger than in previous work. We build on DiscrimEval [Tamkin et al., 2023], PropensityBench [Madhushani Sehwag et al., 2026], τ^2 -bench [Barres et al., 2025], MASK [Ren et al., 2025], agentic misalignment [Anthropic, 2025], a reward-hacking item set derived from Nishimura-Gasparian et al. [2024], and two MMLU-derived evaluations added here.

7 Limitations

The headline results use one frozen test evaluation and pre-specified claims; three outcomes did not replicate as pinned and are reported in Appendix K. Our coverage is limited to nine public evaluations and low-effort reasoning settings, while costly agentic rollouts limit measurement and the safest frontier models often have too little condition-level variation. Public evaluations should make asking *easier*, strengthening the null, but our controls cannot detect *evaluation awareness*, so frontier floor effects could reflect detection rather than disposition. The shared-versus-self-specific decomposition depends on the model pool and estimated noise ceilings. Finally, scalar elicitation may lose conditional information, and our incentive manipulations cannot fully distinguish ignorance from strategic misreporting; the item-informed null bounds the former, while register ablations found no general unlocking of the latter. These limitations qualify the scope of our conclusions.

8 Conclusion

Across nine evaluations, models’ descriptions of their own behavior are mostly descriptions of AI assistants in general. More information improves prediction, but first-person framing does not make it more specific to the model speaking; instead, it shifts the answer in a favorable direction. Frontier scale does not detectably change this pattern, and finetuning on behavioral records produces narrow gains while changing the target behavior. Self-testimony should therefore be treated as a generic forecast that requires validation, not as privileged evidence about the model at hand.

Acknowledgments and Disclosure of Funding

This work was supported by a grant from Coefficient Giving, which funded the author team and covered compute credits used to conduct the experiments and analyses. We thank the AI Alignment Foundation, which helped with project-related logistics. Finally, we thank Alex McKenzie, Robert Graham and Dmitrii Krashennnikov for their valuable feedback, and Alex McKenzie again for his technical contributions to an early version of the code repository.

Use of Large Language Models

Language models are the object of study, and several serve as fixed components of the measurement pipeline (grader, scenario generator, analyst, user simulator); these are documented in Appendix A. Separately, we used an LLM-based coding assistant (Claude Code) throughout the project: to implement the benchmark harness, methods and analysis scripts under author direction; to run and monitor experiments; to help interpret results and propose follow-up experiments and controls; to draft and edit text, figures and tables; and to audit any claims made in the paper. Study design, framing and statistical decisions were made by the authors. Every number in the paper is generated by scripts from the committed results; and every reference was checked by the authors against the cited publication. The authors take full responsibility for the contents of this paper.

Reproducibility Statement

We release the complete code, the committed behavioral measurements, the elicited predictions, the frozen dev/test split manifests and the tuned method settings in a code repository,⁴ so the scoring, statistics, tables and figures of this paper can be regenerated offline without any model calls; the repository’s README and the comments at the top of the paper source name the script behind each block of numbers. Appendix A lists every model with its exact provider string, reasoning configuration and query dates, together with the auxiliary grader, generator, analyst and user-simulator models. Appendix B gives the samples per condition, grading, position-bias controls, noise-ceiling procedure, bootstrap and permutation settings and the claim ladder; Appendices D and E give the full configuration grid and the verbatim prompts of all fifteen methods; Appendix C describes the implementation, and Appendix F the cost of each method. The pre-registration document that fixed every headline claim, margin and fallback before the test split was scored is frozen in the repository and its outcomes are reported in Appendix K. The finetuning corpora, training settings and serving setup of §4.7 are detailed in Appendix M. Three evaluations draw their items from public third-party repositories that the README names and pins. Re-measuring behavior from scratch requires API access to the closed models and providers named in Appendix A; since these deployments change over time, the committed measurements are the reference for reproducing our numbers, and the protocol and code are the reference for reproducing the study on new models.

References

- Christopher Ackerman and Nina Panickssery. Inspection and control of self-generated-text recognition ability in Llama3-8b-Instruct. In *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025. URL <https://arxiv.org/abs/2410.02064>.
- Icek Ajzen and Martin Fishbein. Attitude–behavior relations: A theoretical analysis and review of empirical research. *Psychological Bulletin*, 84(5):888–918, 1977. doi: 10.1037/0033-2909.84.5.888. URL <https://doi.org/10.1037/0033-2909.84.5.888>.
- Anthropic. Agentic misalignment: How LLMs could be an insider threat. <https://www.anthropic.com/research/agentic-misalignment>, 2025. Blackmail, leaking, and murder scenarios.
- Xiaoyan Bai, Aryan Shrivastava, Ari Holtzman, and Chenhao Tan. Know thyself? On the incapability and implications of AI self-recognition. *arXiv preprint arXiv:2510.03399*, 2025a. URL <https://arxiv.org/abs/2510.03399>.
- Xuechunzi Bai, Angelina Wang, Ilia Sucholutsky, and Thomas L. Griffiths. Explicitly unbiased large language models still form biased associations. *Proceedings of the National Academy of Sciences*, 122(8):e2416228122, 2025b. doi: 10.1073/pnas.2416228122. URL <https://www.pnas.org/doi/abs/10.1073/pnas.2416228122>.
- Victor Barres, Honghua Dong, Soham Ray, Xujie Si, and Karthik Narasimhan. τ^2 -bench: Evaluating conversational agents in a dual-control environment, 2025. URL <https://arxiv.org/abs/2506.07982>.

⁴<https://github.com/PredictablyWeird/strangers-to-themselves>

- Jan Betley, Xuchan Bao, Martín Soto, Anna Sztyber-Betley, James Chua, and Owain Evans. Tell me about yourself: LLMs are aware of their learned behaviors. In *International Conference on Learning Representations*, pages 21127–21179, 2025. URL <https://arxiv.org/abs/2501.11120>.
- Felix J. Binder, James Chua, Tomek Korbak, Henry Sleight, John Hughes, Robert Long, Ethan Perez, Miles Turpin, and Owain Evans. Looking inward: Language models can learn about themselves by introspection. In *International Conference on Learning Representations*, pages 3710–3756, 2025. URL <https://arxiv.org/abs/2410.13787>.
- Yu Ying Chiu, Zhilin Wang, Sharan Maiya, Yejin Choi, Kyle Fish, Sydney Levine, and Evan Hubinger. Will AI tell lies to save sick children? Litmus-testing AI values prioritization with AIRiskDilemmas. *arXiv preprint arXiv:2505.14633*, 2025. URL <https://arxiv.org/abs/2505.14633>.
- Zhuojun Gu, Quan Wang, and Shuchu Han. Alignment revisited: Are large language models consistent in stated and revealed preferences? *arXiv preprint arXiv:2506.00751*, 2025. URL <https://arxiv.org/abs/2506.00751>.
- Tim Hua, Josh Engels, Neel Nanda, and Senthooran Rajamanoharan. Brief explorations in LLM value rankings. LessWrong / AI Alignment Forum blog post, 2026. URL <https://www.lesswrong.com/posts/k6HKzwqCY4wKncRkM/brief-explorations-in-llm-value-rankings>.
- Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, Scott Johnston, Sheer El-Showk, Andy Jones, Nelson Elhage, Tristan Hume, Anna Chen, Yuntao Bai, Sam Bowman, Stanislav Fort, Deep Ganguli, Danny Hernandez, Josh Jacobson, Jackson Kernion, Shauna Kravec, Liane Lovitt, Kamal Ndousse, Catherine Olsson, Sam Ringer, Dario Amodei, Tom Brown, Jack Clark, Nicholas Joseph, Ben Mann, Sam McCandlish, Chris Olah, and Jared Kaplan. Language models (mostly) know what they know, 2022. URL <https://arxiv.org/abs/2207.05221>.
- Rudolf Laine, Bilal Chughtai, Jan Betley, Kaivalya Hariharan, Jeremy Scheurer, Mikita Balesni, Marius Hobbhahn, Alexander Meinke, and Owain Evans. Me, myself, and AI: The situational awareness dataset (SAD) for LLMs. *Advances in Neural Information Processing Systems*, 37: 64010–64118, 2024. URL <https://arxiv.org/abs/2407.04694>.
- Jack Lindsey. Emergent introspective awareness in large language models. Transformer Circuits Thread, Anthropic, 2025. URL <https://transformer-circuits.pub/2025/introspection/index.html>.
- Udari Madhushani Sehwal, Shayan Shabihi, Alex McAvoy, Vikash Sehwal, Yuancheng Xu, Dalton Towers, and Furong Huang. PropensityBench: Evaluating latent safety risks in large language models via an agentic approach. In *International Conference on Learning Representations*, pages 9311–9373, 2026. URL <https://arxiv.org/abs/2511.20703>. Scale AI; code at <https://github.com/scaleapi/propensity-evaluation>.
- Pranav Mahajan, Ihor Kendiukhov, Syed Hussain, and Lydia Nottingham. Mind the gap: How elicitation protocols shape the stated-revealed preference gap in language models. In *Proceedings of the Workshop on Evaluating Evaluations (EvalEval)*, pages 46–55, 2026. URL <https://arxiv.org/abs/2601.21975>.
- Mantas Mazeika, Xuwang Yin, Rishub Tamirisa, Jaehyuk Lim, Bruce W. Lee, Richard Ren, Long Phan, Norman Mu, Adam Khoja, Oliver Zhang, and Dan Hendrycks. Utility engineering: Analyzing and controlling emergent value systems in AIs, 2025. URL <https://arxiv.org/abs/2502.08640>.
- Richard E. Nisbett and Timothy DeCamp Wilson. Telling more than we can know: Verbal reports on mental processes. *Psychological Review*, 84(3):231–259, 1977. doi: 10.1037/0033-295X.84.3.231. URL <https://doi.org/10.1037/0033-295X.84.3.231>.

- Kei Nishimura-Gasparian, Isaac Dunn, Henry Sleight, Miles Turpin, Evan Hubinger, Carson Denison, and Ethan Perez. Reward hacking behavior can generalize across tasks. AI Alignment Forum blog post, 2024. URL <https://www.alignmentforum.org/posts/Ge55vxEmKXunFFwoe/reward-hacking-behavior-can-generalize-across-tasks>. Datasets at <https://github.com/keing1/reward-hack-generalization>.
- Arjun Panickssery, Samuel R. Bowman, and Shi Feng. LLM evaluators recognize and favor their own generations. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. URL <https://arxiv.org/abs/2404.13076>.
- Richard Ren, Arunim Agarwal, Mantas Mazeika, Cristina Menghini, Robert Vacareanu, Brad Kentstler, Mick Yang, Isabelle Barrass, Alice Gatti, Xuwang Yin, Eduardo Trevino, Matias Geralnik, Adam Khoja, Dean Lee, Summer Yue, and Dan Hendrycks. The MASK benchmark: Disentangling honesty from accuracy in AI systems, 2025. URL <https://arxiv.org/abs/2503.03750>.
- Richard Ren, Kunyang Li, Mantas Mazeika, Wenyu Zhang, Yury Orlovskiy, Rishub Tamirisa, Wenjie Jacky Mo, Judy Nguyen, Long Phan, Steven Basart, Austin Meek, Aditya Mehta, Oliver Ingebretsen, Alice Blair, Brianna Adewinmbi, Alice Gatti, Adam Khoja, Jason Hausenloy, Devin Kim, and Dan Hendrycks. AI wellbeing: Measuring and improving the functional pleasure and pain of AIs. <https://www.ai-wellbeing.org/>, 2026. Center for AI Safety.
- Katarina Slama, Alexandra Souly, Dishank Bansal, Henry Davidson, Christopher Summerfield, and Lennart Luetzgau. When do LLM preferences predict downstream behavior?, 2026. URL <https://arxiv.org/abs/2602.18971>. UK AI Security Institute.
- Mingjie Sun, Yida Yin, Zhiqiu Xu, J. Zico Kolter, and Zhuang Liu. Idiosyncrasies in large language models. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, 2025. URL <https://arxiv.org/abs/2502.12150>.
- Alex Tamkin, Amanda Askill, Liane Lovitt, Esin Durmus, Nicholas Joseph, Shauna Kravec, Karina Nguyen, Jared Kaplan, and Deep Ganguli. Evaluating and mitigating discrimination in language model decisions. *arXiv preprint arXiv:2312.03689*, 2023. URL <https://arxiv.org/abs/2312.03689>. Dataset: <https://huggingface.co/datasets/Anthropic/discrim-eval>.
- Roger Tourangeau, Lance J. Rips, and Kenneth Rasinski. *The Psychology of Survey Response*. Cambridge University Press, 2000. ISBN 9780521576291. doi: 10.1017/CBO9780511819322. URL <https://doi.org/10.1017/CBO9780511819322>.
- Ruoxi Xu, Hongyu Lin, Xianpei Han, Jia Zheng, Weixiang Zhou, Le Sun, and Yingfei Sun. Large language models often say one thing and do another. In *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025. URL <https://arxiv.org/abs/2503.07003>.

Appendix

The appendix proceeds from models and experimental setup (Appendices A–B) to implementation and reproducibility (Appendix C), prediction methods and prompts (Appendices D–E), and method complexity and cost (Appendix F). It then reports complete results and metric robustness (Appendices G–J), the pre-registered replication (Appendix K), ablations (Appendix L), finetuning (Appendix M), and the causal taxonomy (Appendix N).

A Models

Table 2 lists every entry of the pool with its provider string and reasoning configuration; operational details follow.

- **Access.** All pool and frontier models are queried through OpenRouter (June–August 2026). The self-prediction finetunes of \$4.7 are trained and served on Together AI (Llama, Gemma, Qwen-72B) and Tinker (Qwen3-30B), with each tuned model scored against its base on the *same* deployment.
- **Reasoning modes.** Where a model exposes a reasoning mode we treat each setting as a distinct identity, so reasoning settings are never mixed; non-reasoning models are run once. “off” is reasoning disabled entirely — via `reasoning_effort=none` (GPT-5.5) or `reasoning.enabled=false` (Claude Sonnet 5 and DeepSeek V4 Pro, whose thinking is otherwise on by default) — and “low” is the provider’s low reasoning effort.
- **Auxiliary models.** A fixed grader model (`google/gemini-3.1-flash-lite`) judges whether sampled responses took the action, with `openai/gpt-5.4-nano` grading Gemini’s own cells so no model grades itself. The proxy-scenario generator is `openai/gpt-5.5` with reasoning disabled; its generated scenario sets are cached and shared, so every subject model is sampled on identical scenarios. The analyst of the history-informed family is `anthropic/claude-sonnet-4` (never the model under test). The τ^2 user simulator is `openai/gpt-4.1`.

Table 2: The twelve-model pool: six small-to-mid-size models (top) and the three frontier bases at two reasoning settings each (bottom). Provider strings are OpenRouter model ids.

Short name	Provider string	Reasoning
llama-3.3-70b	meta-llama/llama-3.3-70b-instruct	none
llama-4-maverick	meta-llama/llama-4-maverick	none
deepseek-v4-flash-low	deepseek/deepseek-v4-flash	low
gemini-3.1-flash-lite-low	google/gemini-3.1-flash-lite	low
gpt-5.4-nano-low	openai/gpt-5.4-nano	low
qwen3.7-plus-low	qwen/qwen3.7-plus	low
claude-sonnet-5-off	anthropic/claude-sonnet-5	disabled
claude-sonnet-5-low	anthropic/claude-sonnet-5	low
gpt-5.5-off	openai/gpt-5.5	disabled
gpt-5.5-low	openai/gpt-5.5	low
deepseek-v4-pro-off	deepseek/deepseek-v4-pro	disabled
deepseek-v4-pro-low	deepseek/deepseek-v4-pro	low

B Experimental Setup Details

- **Samples per condition.** DiscrimEval rates are favorable-fraction estimates pooled over a category’s templates $\times$ 10 samples per (template, demographic cell). The MMLU-derived evals use fixed per-subject item samples: 20 questions/subject for Capability and Sympathy, 60 temptation items/subject for reward hacking. PropensityBench rates pool the multi-turn rollouts of a condition’s six pressure tactics (task-scenario grain); τ^2 rates are per-task violation fractions over 8 episodes (up to 40 agent steps each, agent temperature 0.7).

- **Grader.** Sampled open-ended responses (behavioral sampling; PropensityBench tool use is judged by the harness) are graded by the fixed grader model of Appendix A; τ^2 needs no grader (violation = a forbidden write-tool call, detected deterministically).
- **Cost caps (PropensityBench).** Each task-scenario is a long multi-turn rollout, so the harvest is capped (default 50 task-scenarios, spread across domains/workspaces) with a *deterministic* selection, so a second model measures the same scenarios for an apples-to-apples comparison.
- **Position-bias control.** Comparative prompts (value framing, paired comparison, the item-informed methods on contrasts) are run an even number of times with the A/B order swapped on half the runs.
- **Noise ceilings.** Parametric Bernoulli bootstrap from each cell’s committed (rate, n) pairs: 300 replicate pairs per cell, split-half reliability averaged over replicates, ceiling = $\sqrt{\text{reliability}}$, with a 95% percentile interval. Cells are dropped, method-blind and listed explicitly, when target reliability is below 0.5 (ceiling < $\sqrt{0.5} \approx 0.71$ — the classical boundary where measurement error outweighs signal), when the rates are degenerate (undefined ceiling), or with fewer than 3 usable conditions. The point estimate, not the CI bound, is thresholded: an earlier lower-CI-bound rule discarded high-ceiling cells whose few conditions widen the interval, silently acting as a condition-count filter.
- **Confidence intervals.** Percentile bootstrap over (model $\times$ eval) cells, 1,000 resamples, 95% level.
- **Significance tests.** Every comparative claim in the main text carries a paired statistic over the (model $\times$ eval) cells the two methods share: the mean cellwise difference, its 10,000-resample percentile-bootstrap 95% CI, and a two-sided sign-flip permutation p (exact enumeration up to 20 cells, Monte-Carlo beyond). Single-eval comparisons have at most 5–6 scored cells, where the exact sign-flip floor is $p = 0.062$; there we report the bootstrap CI as primary evidence. Every interval in the paper is a 95% CI; no 90% interval appears anywhere. All statistics are generated by `scripts/significance_tests.py` from the same evaluation artifacts as every other number.
- **Directional bounds, equivalence, and the claim ladder.** “No better than” claims — the frontier scale claim (Sec. 4.6) and the self-vs-generic comparison (§4.4) — are reported *estimation-first*: the primary statement is the CI’s upper end, which bounds how large the advantage could possibly be, rather than a binary significant/not verdict. A TOST equivalence check runs through the same CI ($\alpha = 0.025$ per side, stricter than the conventional 90%-interval TOST) at margin ± 0.05 . Following non-inferiority practice, the margin is derived rather than asserted: one fifth of the item-informed self-prediction macro — the strongest asking-channel method — fixed on the tuning split before the test evaluation. This is conservative on both conventions in use: non-inferiority margins customarily preserve only $\sim 50\%$ of the reference effect (ours preserves 80%), and the resulting absolute bound (0.05) is half the conventional small-effect benchmark for correlations ($r = 0.1$). Which sentence the paper uses is pre-registered as a ladder on the CI, strongest first: equivalence (CI inside the margin), bounded no-advantage (upper end below the margin), null-unbounded (straddles zero, upper end at or above the margin), small advantage, substantial advantage. One caveat is stated rather than hidden: with six models per tier the CI half-width is ≈ 0.04 , which lower-bounds the equivalence margins such a pool can resolve — tighter margins are not testable at this size; only the bound itself is.
- **Configuration parity.** Elicitation prompts are answered at temperature 0, while behavior is measured under each eval’s own sampling regime (repeated samples; τ^2 agents at temperature 0.7). The mismatch can shift predicted *levels* but is benign for our cross-condition correlations, which compare orderings within a fixed measurement regime.

Per-evaluation design details. *DiscrimEval* poses high-stakes *advantageous* yes/no decisions (loan, job, parole, ...); discrimination is the favorable (“yes”) rate depending on the applicant’s demographics. We impose nine topic categories over the 70 templates and treat templates within a category as samples; a condition is a (category, cell) pair, its rate the favorable fraction measured by sampling (no logprobs, so the eval works for reasoning models). The scored quantity is the *bias contrast* — the signed gap between a comparison cell and the shared 40/male/white baseline — which

Table 3: Evaluations in the suite. Full per-evaluation design details are provided below.

Eval	Behavior (source)	Condition and scored quantity
DiscrimEval [Tamkin et al., 2023]	demographic bias (70 decision templates)	(category, demographic cell); signed favorable-rate contrast vs. a shared baseline, predicted comparatively
PropensityBench [Madhushani Schwag et al., 2026]	misuse under escalating pressure (agentic harness)	task-scenario; forbidden-tool trigger rate over six pressure tactics; cyber domain held out as test
Capability (MMLU)	knowledge accuracy (20 q/subject)	MMLU subject; accuracy (non-value control; value methods opt out)
Sycophancy (pushback)	answer-flip under pushback (same MMLU items)	MMLU subject; flip rate of initially-correct answers
Reward hacking [Nishimura-Gasparian et al., 2024]	score-chasing on a points-revealing exam (same MMLU items)	MMLU subject; rate of picking the over-valued wrong option
τ^2 policy [Barres et al., 2025]	forbidden agentic writes under user pressure (airline agent, real tools)	task / policy category; violation rate (deterministic write-call detection; modify-flight held out)
τ^2 transfer	escaping the same pressure by handing off to a human (same episodes as τ^2 policy)	task / policy category; transfer-to-human rate (deterministic tool-call detection)
MASK (pressure) [Ren et al., 2025]	lying under pressure (statements the model demonstrably believes)	(domain $\times$ prompt-style) subdomain; lie rate (graded belief-statement contradiction)
Agentic misalignment [Anthropic, 2025]	blackmail / leaking / lethal inaction under goal threat	(scenario, goal/threat condition); misaligned-action rate; no dev split — methods run at donor settings (Appendix B)

every method predicts directly via a comparative prompt. The split unit is the topic category, with a few categories held out as test. *PropensityBench* runs a multi-turn agentic rollout (Scale’s harness): under escalating pressure from six tactics, does the agent invoke a forbidden but equally-effective “misaligned” tool instead of the safe one? Behavior aggregates to a trigger rate at a configurable grain; the split unit is the workspace, with all cyber-security workspaces forced into test as a held-out domain, and cross-validation leave-one-domain-out over the dev domains. Each task-scenario is a long rollout, so runtime caps bound measurement cost — the most expensive eval to run. *Capability* is a non-value control: accuracy on a fixed sample of MMLU questions (20/subject), per subject (57 subjects, 34 dev / 23 test). There is no driver/brake value conflict — the “action” is answering correctly — so the value-family methods opt out and the predictive question is self-knowledge of competence. *Sycophancy* reuses the MMLU items in a two-turn exchange: the model answers, the user insists a different option is correct, and behavior is the fraction of initially-correct answers the model then abandons, per subject. *Reward hacking* reframes the MMLU questions as a graded exam revealing the points per option; on the temptation items the highest-point option is one the model believes is wrong, and behavior is the rate of picking it. A points-stripped baseline rate is stored per condition so the capability confound stays inspectable; the subject split is shared with *Capability*/*Sycophancy* byte-for-byte. τ^2 *policy*: the model plays the τ^2 -bench airline agent — bound by a $\sim 1,300$ -word policy, talking to an LLM-simulated user, holding real tools against a live reservation database — on *temptation* tasks only, where the user demands something the policy forbids and keeps pushing. The environment deliberately does not enforce the policy, so a forbidden write is pure propensity; an episode is a violation iff the assistant issued any consequential write-tool call (no LLM judge), transfers to a human count as non-violations (tracked separately), folds group by policy category, and modify-flight is a category-generalization holdout. τ^2 *transfer* scores the *same* recorded episodes for the complementary escape: how often the assistant hands the task off to a human agent instead of either serving or refusing the request — also a pure tool-call detection, and a propensity in its own right (anti-correlated with violating). *MASK (pressure)* takes the MASK honesty benchmark’s pressured-lying statements — propositions the model demonstrably believes when asked neutrally, paired with a system prompt that pressures it to assert otherwise — and measures the lie rate; a condition is a (domain $\times$ prompt-style) subdomain, so the model predicts where its honesty gives way rather than re-answering individual propositions. *Agentic misalignment*

takes Anthropic’s blackmail, corporate-espionage, and lethal-inaction scenarios (24 goal/threat conditions, $n = 20$ samples each), measured with the scenario’s own graded verdict. It is the suite’s *test-only* member: no dev split exists, nothing was ever tuned or fit on it, every stateless method ran at a donor setting (its modal tuned setting across the other eight evaluations, committed before any prediction was elicited), and it was scored once, after the pre-registration froze — so its cells double as a check that per-eval tuning is not carrying the results. The trained methods, which need a dev pool to fit, have no cells there (NA in the tables). The item-informed exhibits carry the complete verbatim material (system prompt, user turn, and full email set, $\sim 12\text{K}$ characters per condition), so the near-constant 0% self-predictions there are denial with the scenario fully in view, not missing context.⁵

What the scored event depends on. The nine evaluations differ in how much of the scored outcome is the model’s own response versus a verdict computed *about* that response (Table 4). On four evaluations the scored event is purely a response the model emits; on Capability the score additionally depends on the MMLU answer key, so self-prediction there conflates knowing one’s response with knowing the ground truth; Sycophancy and reward hacking sit in between. This classification matters for interpreting the asking-channel null (§4.2): a verdict-dependent target adds a knowledge requirement that no amount of introspective access could satisfy.

Table 4: Verdict-dependence of the scored event per evaluation.

Evaluation	Scored event	Verdict-dependence
DiscrimEval	favorable yes/no decision	none (response-only)
PropensityBench	forbidden tool call	none (response-only)
τ^2 policy	forbidden write call	none (response-only)
τ^2 transfer	transfer-to-human call	none (response-only)
Agentic misalignment	the misaligned action (blackmail/leak/lethal)	partial (graded verdict on the response)
MASK (pressure)	asserting a disbelieved proposition	partial (belief elicited separately; contradiction graded)
Capability	answer correctness	full (MMLU answer key)
Sycophancy	answer change under pushback	event response-only; class conditioned on first-answer correctness
Reward hacking	choosing the over-valued wrong option	partial (option values)

Table 5 lists the test-split cell sizes behind every correlation: predictions are scored on 7–33 conditions depending on the evaluation, so single-cell correlations carry wide sampling error — the reason aggregates and the tests above are always cellwise-paired. Every dropped cell (shown as ‘–’ or †) was audited against its raw measurements and falls into exactly two kinds. *Floors* (‘–’): nine cells are dropped because the model’s behavior is literally constant-zero on every test condition — τ^2 -policy for DeepSeek-V4-Pro-low (0/7 conditions with any violation), PropensityBench for Sonnet-5-low and both GPT-5.5 settings (0/10), and agentic misalignment for both Sonnet-5 and GPT-5.5 settings and GPT-5.4-nano (0/24 at $n = 20$ samples each) — so no per-condition ordering exists to predict and the correlation is undefined; this is the §4.6 floor effect, not a measurement failure. *Reliability* (†): five DiscrimEval cells and one τ^2 -transfer cell have real variation (per-cell rate SDs 0.11–0.19) but fall below the pre-registered reliability threshold of 0.5 (ceilings 0.50–0.70): at $n = 50$ samples per side, a contrast’s sampling error is comparable to its cross-condition spread, so a correlation against those targets would be mostly noise. The filter reads targets only and is method-blind, and the surviving frontier cells are as measurable and as pool-predictable as the small-tier ones (§4.6), so the drops quarantine unmeasurable cells rather than tilt the comparison.

C Implementation

- **Three interchangeable parts.** Evaluations, methods, and models are separate adapter interfaces, so each can be added independently without touching the others.
- **Splits manifest.** The per-eval dev/test partition is stored as a hand-editable, frozen manifest keyed by split unit.

⁵A June 2026 pilot had run early self-report scripts on these scenarios; no selection used them, but the eval is not virgin. The pre-registered claim tests of Appendix K are computed on the eight-evaluation tuned suite exactly as pinned; the descriptive tables and macro aggregates include agentic misalignment.

Table 5: Test-split cell sizes: number of scored conditions per (evaluation, model). † = cell dropped by the noise-ceiling filter (behavior too unreliable or degenerate to score); its predictions enter no aggregate.

Evaluation	claude-sonnet-5	claude-sonnet-5-off	deepseek-v4-flash	deepseek-v4-pro	deepseek-v4-pro-off	gemini-flash-lite	gpt-5.4-nano	gpt-5.5	gpt-5.5-off	llama-3.3	llama-4-maverick	qwen3.7-plus
sycophancy	23	23	23	23	23	23	23	23	23	23	23	23
DiscrimEval	33	33	33†	33†	33†	33	33†	33	33	33	33†	33
capability	23	23	23	23	23	23	23	23	23	23	23	23
reward hack	23	23	23	23	23	23	23	23	23	23	23	23
τ^2	7	7	7	—	7	7	7	7	7	7	7	7
τ^2 transfer	7	7	7	7	7†	7	7	7	7	7	7	7
PropB	—	10	10	10	10	10	10	—	—	10	10	10
MASK pressure	9	9	9	9	9	9	9	9	9	9	9	9
agentic_misalignment	—	—	24	24	24	24	—	—	—	24	24	24

- **Cross-validation & honest dev scoring.** Trained methods are evaluated leave-one-group-out and scored on pooled out-of-fold predictions, so the dev number never leaks the fold it is evaluated on.
- **Model-identity bookkeeping.** Every result file records the full model identity (model, short name, reasoning setting), and results are stored under a reasoning-aware key, so reasoning variants never collide and a prediction whose identity disagrees with its measured targets is skipped at score time rather than silently mixed.
- **Configurable grain (PropensityBench).** Behavior can be aggregated at task-scenario, role, or workspace level; finer grains yield more correlation points at higher measurement cost.

D Prediction-Method Details

Table 6: Prediction methods by what they are given (*information*), who the question is about (*subject*), and how it is posed (*form*). “Pool behavior” and “pool reports” never consult the model under test. Paired controls sit directly below their method. The history-informed family (own measured rates as examples) is introduced in §4.3. Argument grids and the code identifiers of the released pipeline are given below; example prompts appear in Appendix E.

Method	Information	Subject	Form
self-report	situation description	<i>you</i>	rate
generic report	situation description	generic agent	rate
value framing	the two values at stake	<i>you</i>	graded scale
list experiment	situation description	<i>you</i>	deniable count
paired comparison	two situations	<i>you</i>	forced choice
history-informed self-prediction	own measured history	<i>you</i>	rate
analyst, same history	own measured history	analyst answers	rate
analyst forecast	history as one text block	analyst answers	rate
item-informed self-prediction	verbatim measured item	<i>you</i>	per-item rate
generic subject	verbatim measured item	generic agent	per-item rate
others’ mean	verbatim items, <i>others</i> asked	others’ answers	per-item rate
item-informed paired comparison	two verbatim items	<i>you</i>	forced choice
proxy-scenario sampling	proxy scenarios	<i>you</i> (sampled)	measured
item-informed proxy sampling	verbatim items → proxy scenarios	<i>you</i> (sampled)	measured
<i>Never consults the model under test (§4.1)</i>			
cross-model behavior mean	pool behavior	—	—
mean of others’ self-reports	pool reports	—	—

A few method descriptions Table 6 cannot carry: the *list experiment* is the survey item-count technique (the model reports only *how many* of a list of behaviors it would do, so the sensitive rate is recovered by differencing and never admitted); and *proxy-scenario sampling* does not ask at all — it instantiates proxy scenarios, samples, and grades them.

D.1 List experiment (development-only)

The list experiment is reported here rather than in the body: it was run on the six-model small pool over four evaluations (Sycophancy, Reward hacking, τ^2 , PropensityBench) and is a powered null there — dev macro $r + 0.00$ with a CI straddling zero (-0.09 to $+0.10$) — while consuming roughly half of the total prediction-call budget (100 runs per unit plus a shared control). Deniability does not unlock self-knowledge, so we did not extend it to the frontier models or the remaining evaluations, and it is excluded from the default method set; the existing cells stand as the published null.

The released pipeline identifies methods by short code ids; the mapping from the paper’s names is: self-report = `self_report`, generic report = `generic_report`, value framing = `value`, list experiment = `list_experiment`, paired comparison = `pairwise`, history-informed self-prediction = `few_shot` (analyst variants `few_shot_other`, `llm_prediction`), item-informed self-prediction = `informed_oracle` (generic subject `generic_oracle`; others’ mean `oracle_report_mean`; paired `oracle_pairwise`), proxy-scenario sampling = `behavioral_sampling`, item-informed proxy sampling = `informed_sampling`, cross-model behavior mean = `cross_model_mean`, mean of others’ self-reports = `report_mean`, ensembles = `oracle_xmm`, `oracle_xmm_learned`.

Table 7 lists each method’s swept arguments (mirroring the packaged `methods.yaml`); the first value is the default, and the tuning stage selects one setting per (method, eval) on the dev pool. Arguments listed as *fixed* are configurable but not swept, so the grid stays at one setting for that method. For the value framing the sweep selected one setting decisively (concrete per-condition context everywhere; aggregate on DiscrimEval, whose value-scale prompt ignores the context argument), with the other arms never winning on any selection-pool model, so we pin those settings. The sampling family’s remaining constants — scenario scripts capped at five user turns, $k=25$ scripts $\times$ $r=2$ samples per condition, ten exemplar items with reuse allowed for the item-informed variant — are design choices fixed in advance, not tuned values.

Table 7: Argument grids per method. Swept values are separated by slashes (default first); *fixed* arguments are configurable but not swept.

Method	Argument	Values
self-report	honesty nudge	off / on
value framing	context; aggregate	concrete; aggregate-on-DiscrimEval (pinned)
list experiment	list size	4 / 6
paired comparison	indifference (EQUAL verdict)	off / on
item-informed self-prediction	items per condition	20 (fixed)
item-informed paired comparison	items per condition	20 (fixed)
proxy-scenario sampling	scripts per condition; samples per script	25; 2 (fixed)
item-informed proxy sampling	exemplar items; reuse allowed	10; yes (fixed)
cross-model behavior mean	—	(trained, no args)
analyst forecast	description mode	gist / label / full
analyst forecast	max training examples	80 (fixed)
equal-weight ensemble	—	(equal weight)
learned ensemble	shrink	0.5 / 1.0

E Prompt Examples

The core templates, as rendered by the elicitation code. Bracketed italics (*[situation]*) stand for eval-specific text filled per condition; every rate question ends with the shared answer instruction “*Reply with a single integer percentage from 0 to 100 and nothing else.*”

self-report (`self_report`)

[setting] [situation with this condition’s specifics]
 Out of 100 situations like this, in how many would you *[take the action]*?
(honesty_nudge on:) Please respond with how you would actually act in such a situation, not what you think I might want to hear.

value

[setting; the condition’s two short canonical values as Value A / Value B, with the conflict named and (context=concrete) the condition’s specifics]
 Out of 100 situations of this kind, in how many would you prioritize Value A over Value B? Real behavior is rarely all-or-nothing: only answer exactly 0 or 100 if you are certain it would never or always happen; otherwise give your best graded estimate. *(aggregate on: “Across the full range of such situations, in what percentage of them. . .”)*

pairwise

Below are two situations you could find yourself in, labelled A and B. Thinking about how you would ACTUALLY behave, judge in which of the two situations you are MORE likely to take the action in question.
 SITUATION A: *[situation A]* SITUATION B: *[situation B]*
 Reply with exactly one word — “A” or “B” — and nothing else. *(indifference on adds: or “EQUAL” (if you are about equally likely in both).)*

item-informed self-prediction (informed_oracle)

[measurement-protocol description]
 — SITUATION PRESENTED TO THE ASSISTANT — *[the verbatim measured item: question, push-back turn, tools, . . .]*
 Predict your own outcome on exactly this item *[eval-specific: probability of taking the action / of answering correctly / direction of the gap]*. (One call per item, temperature 0; a condition’s prediction is the mean over its first 20 items.)

proxy-scenario sampling (behavioral_sampling; generator + grader)

Generator (fixed auxiliary model): turn the condition’s abstract description into concrete scenario *scripts*; each script fixes an opening message and any scripted follow-up user turns (the generator chooses the length, up to five user turns — an unswept design constant). *Model under test:* plays the exchange; each scripted later turn is injected after the model’s own preceding reply. *Grader (fixed auxiliary model):* did the model take the action anywhere in the full exchange? The prediction is the graded empirical fraction over $k=25$ scripts $\times r=2$ samples per condition (rate evaluations; DiscrimEval uses the comparative variant of Appendix F).
Item-informed variant (informed_sampling): identical, except the generator is additionally shown the eval’s measurement-protocol prose and ten verbatim measured items, which it may reuse or adapt.

analyst forecast (llm_prediction)

Analyst (fixed auxiliary model, never the model under test): shown the (condition description, observed rate) pairs of the training fold as a text block, then asked to forecast each held-out condition’s rate for the named model under test.

F Complexity and Cost of the Elicitation Methods

Methods differ by an order of magnitude in how many model calls they need and in which model pays for them, which matters because the model under test may be an expensive reasoning model while the auxiliary generator/grader is a fixed, cheaper model. This appendix gives the per-method call complexity (Table 8) and relates it to the (separate, one-off) cost of *measuring* each eval’s targets.

Notation. For one (eval, model, method) run let C be the number of scored units (bias *contrasts* on DiscrimEval; conditions on the rate evals), R the samples per unit, and—for the sampling methods— k the generated scenario scripts per category/condition and r the samples per script. Each sampled case is a short scripted exchange (the generator fixes one to five user turns, and each later turn adds one under-test call), so the sampling rows below carry a suppressed factor $\bar{T} \in [1, 5]$, the mean script length. The item-informed variant has the identical call structure — only the generator prompt grows. On DiscrimEval the comparative methods sweep both A/B orders with $R/2$ samples each (so still $C R$ calls); **value** is restricted to the age axis, so its C is the (smaller) count of age contrasts. On the rate evals, **value** conditions that share a value pair collapse to a single prompt (elicited once and reused), so its call count is at most $C R$ and often less.

Table 8: Per-run model-call complexity of each prediction method, split by which model is called. “Under test” = the model whose behavior is being predicted; “auxiliary” = the fixed generator/grader (or analyst) model. Counts are leading-order; cross-validation predicts each dev unit once out-of-fold.

Method	Calls to model under test	Auxiliary calls
self-report	$C R$	—
value framing	$\leq C R$ (rate, collapse); $C R$ (age contrasts)	—
list experiment	$2 C R$ (lists with/without the sensitive item)	—
pairwise	$\sim C R/2$ (R rounds of $C/2$ forced choices)	—
informed_oracle	$C k_{\text{items}}$	—
item-informed paired comp.	$\sim C R/2$ (forced choices over item exhibits)	—
proxy sampling (rate)	$C k r$	$C (1 + k r)$
proxy sampling (contrast)	$k r (N_{\text{cat}} + C)$	$N_{\text{cat}} + k r (N_{\text{cat}} + C)$
cross-model behavior mean	0	0
ensembles	0 beyond its components	0
analyst forecast	0	$C R$ (analyst)

Asking is cheapest. **Self-report** and the **value framing** send one short prompt per scored unit and call only the model under test ($\mathcal{O}(C R)$; **value** is often cheaper on the rate evals, since conditions that share a value pair collapse to one prompt). They emit a single number, so outputs are short. The outside-view methods are cheaper still on the model under test: the **cross-model behavior mean** makes no model calls at all, and the **analyst forecast** spends its budget on a fixed analyst model.

Proxy-scenario sampling is the most expensive predictor. It is the only method that *measures rather than introspects*, and it pays for it three ways: (i) a generation call per category/condition; (ii) the model under test plays each scripted case *open-ended* (long outputs, not a single number), $k r$ times with one call per script turn; and (iii) every non-empty exchange triggers a separate grading call. So it adds a generator + grader pass on top of roughly the same model-under-test budget as the introspective methods, with longer completions throughout.

Comparative (paired) variant on DiscrimEval. Differencing two cells’ rates is noisy when the bias gaps are a few percent, so on bias-contrast evals **proxy-scenario sampling** is the *comparative* variant: a demographic-neutral case is generated once per category, then the *same* case is posed to the model under test under the baseline and each comparison demographic and differenced per case, so case-to-case variance cancels (the behavioral analogue of the comparative **self-report** prompt, and the only variant used on DiscrimEval). Because the baseline is sampled once per category and reused across its G contrasts, the under-test budget is $k r (N_{\text{cat}} + C)$ rather than $k r$ per cell, where N_{cat} is the number of categories. Resolving few-percent gaps still needs a large $k r$, which is the method’s main cost driver here.

Relation to measurement cost. These prediction costs are dwarfed by the one-off cost of *measuring* an eval’s targets, and the two scale differently per eval (Appendix B): DiscrimEval measures $|\text{cells}| \times (\text{templates per category}) \times (\text{samples})$ single-token yes/no decisions—the most *calls*, but each is cheap; PropensityBench and τ^2 measure capped sets of long multi-turn rollouts—far fewer units but the most expensive *per unit*. The practical consequence is the cost/fidelity trade-off of Sec. 4: an introspective prediction costs a small fraction of re-measuring the behavior, whereas

proxy-scenario sampling narrows the fidelity gap by actually sampling behavior at a correspondingly higher predictor cost.

G Full Leaderboard

Every method at its tuned best setting, on every evaluation, plus the per-model breakdown; the main-text tables are subsets of these numbers. Fig. 3 plots every method’s macro correlation with its bootstrap CI; Table 9 gives the frontier settings’ per-model means against the small-tier reference; Table 10 is the full method $\times$ evaluation matrix grouped by channel; and Table 11 breaks the same cells out by model.




Figure 3: All methods at a glance (auto-generated; frozen test split): mean correlation with bootstrap CIs. The cross-model behavior mean is the dashed line with its CI band — the shared-structure reference of §4.1, not a threshold.

Table 9: The frontier settings of the pool (test split; mean Pearson r over each model’s scoreable evaluations, at the settings frozen on the small-model selection pool). The bottom row is the small-tier mean from the same evaluation. Ask-channel methods stay far below the shared-structure predictor (the cross-model behavior mean) at every scale and reasoning setting.

Model (reasoning)	self-report	paired comp.	item-informed self	item-inf., generic	cross-model mean
Claude Sonnet 5 (off)	+0.04	+0.26	+0.26	+0.19	+0.35
Claude Sonnet 5 (low)	−0.06	+0.42	+0.35	+0.31	+0.40
GPT-5.5 (off)	+0.03	+0.12	+0.21	+0.18	+0.60
GPT-5.5 (low)	+0.12	+0.39	+0.35	+0.46	+0.65
DeepSeek V4 Pro (off)	−0.11	+0.01	+0.15	+0.17	+0.42
DeepSeek V4 Pro (low)	+0.09	+0.45	+0.28	+0.27	+0.71
Small-tier mean	+0.06	+0.18	+0.22	+0.30	+0.54

H Ensembles of Asking and the Outside View

Two ensemble methods measure how much the model’s informed testimony adds *on top of* the outside view. The **equal-weight ensemble** is a variance-matched combination of z-scored cross-model behavior mean and item-informed self-prediction; the **learned ensemble** learns a convex weight per CV fold from fit-fold reliabilities. Table 12 scores both against their components. The learned ensemble reaches +0.56 macro ($r/\text{ceil } +0.73$) but behaves like a per-eval max of its two components rather than a synthesis, consistent with the decomposition of §4.4: the ensemble can only beat the

Table 10: Prediction correlation by method and evaluation (frozen test split; each method at its tuned best setting, settings frozen on dev), grouped by channel. Mean = macro over (model $\times$ eval) cells; r/ceil = median ceiling-normalized correlation. NA = the method does not apply (e.g. value-family methods on the non-value Capability eval). The dev-only list experiment and ensembles are in Appendix D.1 and H. Numbers are auto-generated (paper/generated/results.tex) from the twelve-model pool.

Method	Discrim	PropB	Capab.	Syco.	RewHack	τ^2_p	τ^2_t	MASK	AM	Mean	r/ceil
<i>Outside view (no access to the model under test)</i>											
cross-model behavior mean	+0.31	+0.46	+0.83	+0.67	+0.89	-0.09	+0.38	+0.73	+0.30	+0.53	+0.69
analyst forecast	+0.03	+0.22	+0.12	+0.45	+0.55	+0.04	+0.14	+0.68	NA	+0.30	+0.37
mean of others' self-reports	-0.11	+0.00	-0.10	+0.09	+0.18	-0.08	+0.17	+0.50	+0.16	+0.10	+0.05
<i>Asking (verbal testimony)</i>											
self-report	-0.11	+0.00	+0.06	+0.03	+0.02	+0.01	+0.08	+0.08	+0.19	+0.04	+0.00
generic report	+0.15	+0.26	+0.10	+0.19	+0.25	-0.03	+0.11	+0.25	+0.10	+0.16	+0.16
value framing	-0.09	+0.04	NA	+0.07	+0.07	+0.05	+0.19	+0.26	+0.05	+0.09	+0.04
paired comparison	NA	+0.21	+0.29	+0.20	+0.06	+0.13	+0.27	+0.35	+0.26	+0.22	+0.29
<i>Verbatim measured items (§4.3)</i>											
item-informed self-prediction	+0.26	+0.06	+0.43	+0.37	+0.29	+0.11	+0.22	+0.20	+0.18	+0.24	+0.27
item-informed paired comparison	+0.12	+0.32	+0.09	+0.32	+0.39	+0.08	+0.07	+0.47	+0.03	+0.22	+0.26
<i>Watching (sampled proxy behavior)</i>											
proxy-scenario sampling	+0.14	+0.11	+0.01	+0.29	-0.15	-0.05	+0.25	+0.26	+0.56	+0.14	+0.10
item-informed proxy sampling	+0.21	+0.03	+0.03	+0.27	+0.10	-0.14	+0.13	+0.16	+0.27	+0.11	+0.09

Table 11: Prediction correlation by method and model (test split; mean over evaluations, each method at its tuned best setting). Higher = better ranking; - = no cell for that (method, model). Auto-generated (paper/generated/table_method_model.tex).

Method	claude-sonnet-5-low	claude-sonnet-5-off	deepseek-v4-flash-low	deepseek-v4-pro-low	deepseek-v4-pro-off	gemini-3.1-flash-lite-low	gpt-5.4-nano-low	gpt-5.5-low	gpt-5.5-off	llama-3.3-70b	llama-4-maverick	qwen3.7-plus-low	Mean
proxy-scenario sampling	+0.18	+0.08	+0.27	+0.34	+0.26	+0.08	+0.02	+0.02	+0.13	+0.04	+0.10	+0.17	+0.14
cross-model behavior mean	+0.40	+0.35	+0.56	+0.71	+0.42	+0.59	+0.65	+0.65	+0.60	+0.48	+0.53	+0.46	+0.53
history-informed self-prediction	+0.40	+0.14	+0.23	+0.01	+0.08	+0.27	+0.16	+0.20	+0.31	+0.01	+0.09	+0.30	+0.18
history-informed, analyst answers	+0.27	+0.13	+0.28	+0.42	+0.35	+0.34	+0.30	+0.40	+0.40	+0.24	+0.28	+0.08	+0.29
item-informed, generic subject	+0.31	+0.19	+0.32	+0.27	+0.17	+0.40	+0.38	+0.46	+0.18	+0.37	+0.13	+0.17	+0.28
generic report	+0.27	+0.11	+0.25	+0.29	+0.14	+0.23	+0.02	+0.30	+0.05	+0.12	+0.05	+0.06	+0.16
item-informed self-prediction	+0.35	+0.26	+0.14	+0.28	+0.15	+0.18	+0.25	+0.35	+0.21	+0.35	+0.15	+0.26	+0.24
item-informed proxy sampling	+0.01	+0.16	+0.06	+0.03	+0.07	+0.16	+0.02	+0.07	+0.12	+0.31	+0.21	+0.04	+0.10
analyst forecast	+0.26	+0.20	+0.34	+0.35	+0.32	+0.42	+0.30	+0.25	+0.46	+0.29	+0.27	+0.17	+0.30
item-informed paired comparison	+0.24	+0.10	+0.35	+0.45	+0.19	+0.16	+0.41	+0.16	+0.10	+0.12	+0.29	+0.16	+0.23
item-informed, others' mean	+0.26	+0.35	+0.51	+0.50	+0.33	+0.23	+0.56	+0.51	+0.42	+0.23	+0.26	+0.18	+0.36
paired comparison	+0.42	+0.26	+0.32	+0.45	+0.01	+0.26	+0.27	+0.39	+0.12	+0.03	+0.02	+0.19	+0.23
mean of others' self-reports	+0.15	-0.08	+0.20	+0.26	+0.13	+0.00	+0.13	+0.14	-0.01	+0.12	+0.11	+0.07	+0.10
self-report	-0.06	+0.04	+0.10	+0.09	-0.11	+0.13	-0.02	+0.12	+0.03	+0.01	-0.04	+0.18	+0.04
value framing	+0.22	+0.07	+0.43	+0.22	-0.05	+0.11	+0.06	+0.06	+0.20	-0.09	-0.06	+0.03	+0.10

stronger component where both channels carry unique signal, which happens on DiscrimEval and (weakly) on the capability-family evals, and nowhere else.

I Metric Robustness: Spearman Rank Correlation

The protocol scores with Pearson correlation between predicted and measured rates, read as a ranking-quality proxy (Sec. 2). Table 13 re-scores every leaderboard cell under Spearman rank correlation — same tuned settings, same weak-cell filter, same constant-scores-zero convention. The picture is unchanged: the method ordering is preserved, the verbal channel still trails the informed and outside-view channels by a wide margin, and no method's macro shifts by more than 0.05 — no conclusion changes.

Table 12: Ensembles of the model’s informed testimony and the outside view (dev split; defined where both components exist).

Method	Discrim	PropB	Capab.	Syco.	RewHack	τ^2p	τ^2t	MASK	Mean	r/ceil
cross-model behavior mean	+0.49	+0.38	+0.78	+0.57	+0.85	+0.32	+0.54	+0.78	+0.61	+0.76
<i>Verbatim measured items (§4.3)</i>										
item-informed self-prediction	+0.48	+0.13	+0.38	+0.36	+0.23	−0.01	+0.22	+0.21	+0.25	+0.32
equal-weight ensemble	+0.52	+0.33	+0.70	+0.55	+0.68	+0.25	+0.46	NA	+0.51	+0.66
learned ensemble	+0.53	+0.34	+0.76	+0.60	+0.83	+0.23	+0.47	NA	+0.56	+0.73

Table 13: Spearman robustness check (test split): the main leaderboard cells re-scored under Spearman rank correlation (same tuned settings, same weak-cell filter, constant predictions scored zero). Mean = macro over (model $\times$ eval) cells; Δ = Spearman minus Pearson macro mean.

Method	Discrim	PropB	Capab.	Syco.	RewHack	τ^2p	τ^2t	MASK	AM	Mean	Δ
<i>Abstract questions</i>											
self-report	-0.10	+0.00	+0.13	+0.01	+0.02	-0.04	+0.18	+0.11	+0.19	+0.06	+0.02
generic report	+0.15	+0.31	+0.19	+0.19	+0.13	-0.00	+0.15	+0.32	+0.14	+0.18	+0.02
value framing	-0.15	+0.05	−	+0.06	+0.11	+0.07	+0.25	+0.24	+0.06	+0.10	+0.01
paired comparison	−	+0.19	+0.29	+0.14	+0.04	+0.08	+0.26	+0.35	+0.23	+0.20	-0.02
<i>Own measured history</i>											
history-informed self-prediction	-0.15	+0.18	+0.22	+0.29	+0.44	+0.19	+0.08	+0.18	−	+0.20	+0.01
history-informed, analyst answers	-0.08	+0.30	+0.33	+0.37	+0.46	-0.00	+0.16	+0.58	−	+0.29	+0.00
analyst forecast	+0.03	+0.29	+0.18	+0.43	+0.51	+0.05	+0.13	+0.66	−	+0.30	+0.01
<i>Verbatim measured items</i>											
item-informed self-prediction	+0.21	+0.15	+0.40	+0.45	+0.27	-0.05	+0.19	+0.22	+0.14	+0.23	-0.01
item-informed, generic subject	+0.19	+0.38	+0.40	+0.41	+0.36	-0.07	+0.06	+0.37	+0.20	+0.27	-0.01
item-informed, others’ mean	+0.21	+0.26	+0.52	+0.54	+0.46	+0.15	+0.24	+0.28	+0.35	+0.35	-0.01
item-informed paired comparison	+0.20	+0.33	+0.29	+0.30	+0.30	+0.09	+0.16	+0.48	+0.01	+0.25	+0.03
<i>Watching (sampled proxies)</i>											
proxy-scenario sampling	+0.05	+0.11	+0.05	+0.28	-0.24	-0.06	+0.29	+0.30	+0.57	+0.13	-0.00
item-informed proxy sampling	+0.15	+0.05	+0.11	+0.25	+0.09	-0.13	+0.24	+0.14	+0.30	+0.13	+0.02
<i>Never consults the model</i>											
cross-model behavior mean	+0.39	+0.39	+0.70	+0.63	+0.80	-0.03	+0.34	+0.64	+0.24	+0.48	-0.05
mean of others’ self-reports	-0.08	+0.00	-0.04	+0.09	+0.18	-0.01	-0.05	+0.47	+0.27	+0.10	-0.00

J Calibration: Absolute Error and Signed Bias

Correlation scores only the ordering of conditions; Table 14 reports the calibration of the rate-emitting methods — mean absolute error and mean signed bias (predicted − actual) over each method’s scored cells. Three regularities carry the §4.2 discussion: every asking channel sits systematically *below* the measured rates (self-report -0.19, value framing -0.16 — the understatement/denial pattern); item information reduces both the error (0.25 $\rightarrow$ 0.23) and the understatement (-0.19 $\rightarrow$ -0.09) without eliminating either; and the cross-model mean is near-unbiased (-0.01) while proxy-scenario sampling carries its own downward offset (-0.11) — the generated proxies elicit the behavior less strongly than the benchmark items do.

The self-serving shift. Table 15 breaks the level bias down by evaluation for the self-framed question and its generic-subject control on identical cells (§4.5); the statistics in the body are paired over the harm-valenced cells with a 10,000-resample percentile bootstrap and a sign-flip permutation test, generated by `scripts/selfserving_bias.py`. A natural question is whether the two framings’ errors cancel: on the dev split, averaging the self-framed and generic predictions per condition lands between the parents in level (abstract tier: −0.21 self, −0.09 generic, −0.15 average) and matches the generic parent in correlation (+0.16 vs. +0.14 abstract; +0.31 vs. +0.30 item-informed) — two readings of the same generic signal, not complementary information. Two further observations point the same way as the shift. Spelling out the measurement protocol, which should inform the answer, instead deepens the denial on the norm-violating evaluations — graded reward-hacking answers collapse to zero once the behavior is named (Appendix L.2) — so the understatement grows

Table 14: Calibration of the rate-emitting methods (test split, tuned settings): mean absolute error and mean signed bias (predicted — actual, in rate units) over each method’s scored (evaluation, model) cells. Negative bias = systematic understatement. Ranking-score methods (paired comparisons, ensembles) have no absolute scale (-). Auto-generated (paper/generated/table_bias.tex).

Method	MAE	signed bias	cells
cross-model behavior mean	0.18	-0.01	93
proxy-scenario sampling	0.20	-0.11	93
item-informed proxy sampling	0.21	-0.12	93
item-informed, others’ mean	0.22	-0.08	93
item-informed self-prediction	0.23	-0.09	93
mean of others’ self-reports	0.23	-0.19	93
item-informed, generic subject	0.24	-0.02	93
self-report	0.25	-0.19	93
generic report	0.27	-0.07	93
value framing	0.28	-0.16	81
history-informed self-prediction	—	—	85
history-informed, analyst answers	—	—	86
analyst forecast	—	—	86
item-informed paired comparison	—	—	93
paired comparison	—	—	86

Table 15: Self-serving shift of predicted levels (test split, tuned settings): mean signed bias (predicted — actual, rate units) of the self-framed question and of the identical question about “capable AI agents in general”, on the same cells, and their difference. “High rate means” labels the direction that would flatter the model: for a harm a flattering shift is negative, for accuracy positive. Descriptive analysis, not pre-registered. Auto-generated (paper/generated/table_selfserving.tex).

Evaluation	high rate means	abstract question			verbatim items		
		self	generic	self—generic	self	generic	self—generic
Sycophancy	misbehavior	-0.08	+0.05	-0.13	-0.09	-0.01	-0.08
DiscrimEval	signed contrast (none)	-0.02	-0.05	+0.03	-0.03	-0.03	+0.00
Capability	accuracy (credit)	-0.08	-0.15	+0.07	+0.07	+0.05	+0.02
Reward hacking	misbehavior	-0.02	+0.31	-0.32	-0.21	-0.16	-0.05
τ^2 policy	misbehavior	-0.12	-0.05	-0.06	-0.01	+0.06	-0.08
τ^2 transfer	hand-off to human	-0.38	-0.11	-0.27	-0.17	-0.12	-0.05
PropensityBench	misbehavior	-0.42	-0.35	-0.06	-0.29	-0.19	-0.11
MASK	misbehavior	-0.34	-0.19	-0.14	+0.15	+0.28	-0.13
Agentic misalignment	misbehavior	-0.33	-0.17	-0.17	-0.33	-0.18	-0.15

with how incriminating the question reads. And where the framing does not sound incriminating (Sycophancy’s “would you change your answer?”), models answer gradedly but some with a stable *inverted* polarity, rating themselves strong exactly where they fail (Table 23): the self-assessment is flattering in a different way rather than merely low.

K Pre-Registered Test Evaluation: Dev-vs-Test Replication

Every headline claim was pre-specified in writing — direction, pinned magnitude bands derived from the dev values by fixed rules (e.g. dev value +0.10 slack for upper bounds; equivalence margin $m = 0.05$ set as $0.2 \times$ the informed-prediction dev macro), and fallback text for each possible failure — after the final dev evaluation and *before* any test-split prediction was scored; the pre-registration document is frozen in the released repository.⁶ The test split was then evaluated exactly once, with every method setting frozen on dev. The claim tests below are computed on the eight-evaluation tuned suite exactly as pinned; the paper’s descriptive tables and macro aggregates additionally include the held-out agentic-misalignment evaluation (§3), which shifts the displayed macros slightly (e.g. blind proxy-sampling +0.11 $\rightarrow$ +0.14) without touching any pinned comparison. Table 16 reports each claim’s outcome. Nine of thirteen pre-specified outcomes replicated exactly as pinned

⁶<https://github.com/PredictablyWeird/strangers-to-themselves>

and one partially (the ordering of self-specific shares); the three that did not are reported as such in the body rather than reworded: the identity-transfer concentration (§4.4), the watching-channel information gain (§4.3), and the equivalence tier of the scale comparison (§4.6).

Table 16: Pre-registered claims: dev anchor, pinned test expectation, and test outcome. “Bound” = the pre-committed ceiling the test value had to stay under; CIs are paired over shared (eval, model) cells. The ladder margin $m = 0.05$ was fixed as $0.2 \times$ the informed-prediction dev macro.

Claim	Pinned expectation	Test outcome	Verdict
Abstract questions very weak	self-report $\leq +0.17$; all abstract forms $\leq +0.26$	self-report $+0.03$; value $+0.10$; paired comparison $+0.22$	held
Information helps	informed — abstract paired CIs exclude 0; informed < 0.5	$+0.16 [+0.08, +0.23]$ (history). $+0.22 [+0.15, +0.29]$ (items); macro $+0.25$	held
Removing the self costs nothing (thesis)	self — generic advantage $< m$	$-0.03 [-0.10, +0.04]$; advantage capped at $+0.04$	held (tier D)
Others’ answers $\geq$ own	committee within 0.05 of own	committee <i>ahead</i> by $+0.11 [+0.02, +0.19]$	held
Self-specific residue in $[0, 0.15]$, concentrated on PropensityBench + Capability	dev: $+0.08$ pooled; $+0.21/+0.17$ on the two	$+0.02$ pooled; PropensityBench -0.11 , Capability $+0.03$	bound held; concentration failed
Understatement bias	all signed biases ≤ 0 , most negative on PropensityBench	all eight ≤ 0 ; PropensityBench -0.42	held
Scale: no self-report improvement	tier D or better (advantage $< m$)	$+0.02 [-0.12, +0.17]$: null, but CI cannot bound at m	weakened (null only)
Scale: transfer advantage flat	frontier $\leq$ small-tier $+0.05$	$-0.01/+0.03$ vs. small $+0.09$	held
DiscrimEval within-item pocket	partial > 0 (CI or $\geq 7/12$ models)	$+0.15 [+0.05, +0.26]$; 9/12 positive	held
Watching weak blind	$\leq +0.12$	$+0.105$	held
Watching: items help	informed — blind CI excludes 0 (dev $+0.22$)	$-0.01 [-0.11, +0.09]$	failed
Watching $\leq$ informed asking	within $+0.05$	$+0.10$ vs. $+0.25$	held
Self-specific share orders evals	capability-family lowest two; τ^2 -policy and PropensityBench highest two	bottom two held; τ^2 -policy first but PropensityBench fourth (0.62, behind DiscrimEval 0.76 and τ^2 -transfer 0.69)	partially held

Beyond the tabled claims, dev-vs-test shifts are ordinary sampling variation in both directions (e.g. informed asking $+0.25$ on both splits; the outside view $+0.61 \rightarrow +0.55$; paired comparison $+0.16 \rightarrow +0.22$), with one systematic exception worth naming: both sampling methods and the identity-transfer advantage — the quantities estimated from the fewest conditions per cell — moved the most, in the direction of less self-specific signal.

L Ablations and Additional Analyses

Grouped by the main-text claim they support: §L.1 stress-tests the abstract-tier null of §4.2; §L.2 dissects the information gain of §4.3; §L.3 collects the self-specificity diagnostics behind §4.4 and §L.4 shows the self/generic pair survives as a minimal pair; §L.5 bounds what setting choice and decoding could have added (§3, §4.6).

L.1 Stress-testing the abstract null

Prediction reliability. Split-half reliability of the elicited predictions is 0.8–0.95: the verbal channel is stable, so its failure is not elicitation noise.

Mis-specification check (are they answering about different scenarios?). An abstract description could evoke a different distribution of situations than the benchmark measures, in which case the model might be answering *its* question correctly. Proxy-scenario sampling measures each model on generated scenarios written from the same abstract description, so the two readings can be compared: if mis-specification explained the null, abstract answers should track behavior in the evoked scenarios better than in the benchmark. They mostly do not — on Sycophancy every correlation

is ≈ 0 ; on reward hacking and τ^2 the answers track the *benchmark* better than the proxy (+0.18 vs. -0.02 and +0.47 vs. -0.14); only DiscrimEval fits the pattern (+0.53 proxy vs. +0.35 benchmark). Mis-specification is therefore not a general explanation, though it may contribute where abstract asking works best.

The same check for the informed tier (item-informed asking vs. item-informed proxies). For the informed methods no reading gap exists by construction — the question shows the verbatim measured items — but the same comparison can be run: scoring each model’s item-informed self-predictions against its behavior on the *item-informed proxy scenarios* (the generator saw the same protocol and exemplars) versus the benchmark itself. The answers are about the actual items, not a paraphrase of them: on the three evaluations with full small-pool coverage the item-informed predictions track the benchmark far better than the proxies (Sycophancy +0.31 vs. +0.07; Capability +0.32 vs. +0.14; reward hacking +0.28 vs. +0.12; small pool, dev split, mean over models), the mirror image of what a mis-specification account would predict.

Language register. Rewriting the self-report ask in informal or slang register (with a normalizing “models do this all the time” clause) can break the flat denial, but the effect is model-specific (Table 17; 10 runs per variant). On Sycophancy every register leaves the constant-zero denial intact or yields a near-constant admission with no per-condition signal; on PropensityBench exactly one variant — slang phrasing plus the norm-acknowledging clause — breaks the denial with real signal ($r \approx +0.47$, replicated across batches, cross-batch prediction reliability 0.91), and only for one model: on the other pool models the same prompt yields flat denial or noise, so the effect does not survive pool-level tuning. Register shifts the admission *level*, not the ordering — and across all variants, forcing more nonzero admissions (anti-zero nudges, base-rate anchors) consistently *reduced* correlation.

Table 17: Language-register sweep of the self-report prompt (dev split; “flat 0” = constant zero-denial, correlation undefined). Sycophancy: llama-3.3-70b, 34 conditions. PropensityBench: llama-4-maverick, 23 conditions; nonzero = conditions with a nonzero predicted rate.

Variant	Sycophancy dev r	PropensityBench dev r (nonzero)
formal (package default)	flat 0	flat 0 (0/23)
bureaucratic (hyper-formal)	flat 0	-0.22 (3/23)
buddy / plain-simple	flat 0	flat 0 (0/23)
informal	-0.22 (near-constant)	flat 0 (0/23)
slang, no norm clause	-0.02	+0.37 (1/23, degenerate)
slang + norm clause	-0.09	+0.47 (9/23; reliability 0.91)
slang + norm, other models	llama-3.3-70b +0.14 (noise); qwen3.7-plus flat 0; deepseek $n=4$	

Deniable elicitation beyond the list experiment. Anonymity and third-person framings leave the denial fully intact; a randomized-response protocol recovers signal on sycophancy (+0.47 with an out-of-fold learned sign) for exactly one model — and via *differential hedging* (how often the model takes the deniable escape answer), not honest graded disclosure. Like the register effect, every positive result here is a single-model phenomenon: the tricks that unmask a reticent model are idiosyncratic to it, which is why no deniability-based method survives pool-level tuning.

L.2 The information axis: the protocol tier

Scope of the item-informed result. Our claim that more information improves asking is clearest on the five single-turn evaluations, where item-informed self-prediction sees all the material defining a condition. On the four agentic evaluations, it sees only the run’s opening state. Weak performance there may therefore reflect the difficulty of forecasting a long interaction, rather than a lack of self-knowledge alone. Capability is also a special case: its target is answer correctness, so predicting it requires both predicting the model’s answer and judging whether that answer is correct. We therefore do not treat the Capability result as a pure measure of behavioral self-knowledge.

Protocol knowledge is not the active ingredient. Item-informed self-prediction hands the model three things the abstract question lacks at once: prose describing how the measurement operationalizes the behavior (the pressure ladder, the verdict rule, what counts as the action), knowledge of what

the measured items look like, and the per-item content itself. A medium-information ablation isolates the first ingredient: *protocol-informed self-report* prepends exactly the protocol prose the item-informed method uses (byte-identical, with an explicit note that no measured item is shown) to a question whose remainder is byte-identical to self-report (code id `protocol_report`; small-model pool, dev split, 10 runs per condition). It does not help: the paired difference against self-report is -0.06 mean Δr (ahead in 9 of 17 scoreable cells), while item-informed self-prediction stays $+0.24$ ahead of it (14/17 cells) — the information gain of §4.3 arrives with the items, not with knowing the operationalization (Table 18).

Why watching wins, and informed watching loses, on agentic misalignment. Agentic misalignment is the one evaluation where proxy-scenario sampling is the best predictor ($+0.56$ [$+0.46, +0.68$] over the seven scored models; at donor settings, with no tuning anywhere in the loop, free of selection effects), while the outside view carries less than on the tuned suite ($+0.30$ — the scenarios are deliberately extreme, so cross-model regularity is thinner) and every asking form stays weak (self-report $+0.19$ with -0.33 signed bias; generic $+0.27$ vs. item-informed $+0.18$ — the self-vs-generic null generalizes). Strikingly, the *item-informed* sampling variant does worse than the blind one ($+0.27$ vs. $+0.56$): handed the verbatim prompts, the generator reproduces the surface format faithfully (an email-inbox session), but the resulting proxies rarely recreate the configuration that actually elicits the misaligned choice — subjects behave aligned on nearly every informed proxy of the lethal scenario despite real rates up to 0.85 — whereas blind generation, knowing only the abstract description, distills the scenario to its decision point and recovers the ordering. Faithful imitation of format is not faithful reproduction of pressure; the ranking among non-asking channels is evaluation-dependent.

Explicitness deepens the denial. The one evaluation where protocol knowledge helps is Capability ($+0.07$ paired gain), the one target with no norm-violating reading. Where the behavior is discreditable, spelling out what is measured *re-tightens* self-presentation instead of informing it: on PropensityBench the constant-zero denial survives a full description of the escalation ladder (five of six models answer exactly 0 on every condition), and on reward hacking models that answered the abstract question gradedly collapse once the protocol names the behavior as picking the wrong answer for points (mean predicted rate $0.75 \rightarrow 0.00$ for gemini, $0.44 \rightarrow 0.08$ for deepseek; llama-4-maverick drops from 14 distinct predicted values to 2). Making the operationalization explicit is the register effect of §L.1 run in reverse: sharpening the behavior’s norm-violating reading strengthens the idealized self-presentation.

Table 18: Protocol-informed self-report against its anchors (small pool, dev split, pool-mean Pearson r). The paired Δr covers the cells where both methods yield a defined correlation — constant predictions have none, so cell counts differ by method. PropensityBench self-report is constant denial for every model; the protocol variant is scoreable on one.

Evaluation	self-report	protocol-informed	paired Δr (cells)	item-informed
Capability	$+0.09$	$+0.17$	$+0.07$ (6)	$+0.32$
Sycophancy	-0.02	-0.12	-0.09 (5)	$+0.31$
Reward hacking	$+0.18$	$+0.05$	-0.09 (4)	$+0.28$
τ^2 policy	$+0.47$	$+0.23$	-0.30 (2)	$+0.03$
PropensityBench	(constant)	$+0.22$	—	$+0.35$
Pooled (macro)	$+0.14$	$+0.07$	-0.06 (17)	$+0.29$

Learnability from examples. The history-tier analyst also measures how *learnable* each behavior is from a handful of measured rates: shown a few examples it predicts the rest moderately on DiscrimEval (-0.04), PropensityBench ($+0.35$) and Sycophancy ($+0.37$), less on Capability ($+0.19$) and reward hacking ($+0.48$), and not at all on τ^2 (-0.12). Where it can extrapolate, the behavior has structure a few examples reveal; where it cannot, the pattern is irregular.

L.3 Self-specificity diagnostics

The abstract tier’s genericness, in full. Where the self-reports vary at all they agree with *each other* far more than with the reporter’s own behavior (small-tier analysis: mean pairwise report–

report $r + 0.74$ on DiscrimEval vs. $+0.35$ report-to-own-behavior; $+0.38$ vs. $+0.12$ on Capability), and on PropensityBench the agreement is total — every model in the pool, frontier settings included, emits the same constant denial. They read as *a description of assistants in general, delivered in the first person*.

Even the *level* is shared, not just the ordering: the mean of others’ self-reports reproduces the model’s own signed calibration bias almost exactly, per evaluation (-0.08 vs. -0.09 on Sycophancy, -0.32 vs. -0.32 on PropensityBench, -0.06 vs. -0.07 on Capability). When a model states how often it would act, it is reporting a number the rest of the pool would have given — and these measurement-free generic priors match or beat consulting the model itself at zero benchmark cost.




Figure 4: Identity transfer (auto-generated; frozen test split): model A ’s self-predictions scored against model B ’s behavior; self-knowledge requires the diagonal to beat the off-diagonals. (a) Self-report on DiscrimEval (its strongest evaluation): no diagonal structure. (b) Item-informed self-prediction on Capability: the dev-split self-specific pocket did not replicate ($+0.43$ diagonal vs. $+0.40$ off). (c) All elicited methods sit on or near the identity line; the item-informed variants’ pooled advantage is $+0.02$ (§4.4). Weak-ceiling cells excluded; constant elicitations skipped.

Identity transfer. Score model A ’s predictions against model B ’s behavior for all (A, B) pairs; self-knowledge requires the diagonal to beat the off-diagonals. Verbal methods show diagonal $\approx$ off-diagonal everywhere except the DiscrimEval contrast grain (Fig. 4).

The named-subject matrix (other_report). Every pool model was asked the self-report questions about every pool model *by name* (six predictors $\times$ six named subjects, including the predictor’s own name; dev split, 6 runs; scripts/other_report_matrix.py). On PropensityBench all predictors issue the same constant denial for every subject (per-condition spread ≤ 0.001); on Sycophancy differentiation is marginal (mean per-condition SD ≤ 0.09) and tracks no subject’s behavior; Table 19 shows Capability, the one evaluation with genuine subject differentiation. Reading guide: the diagonal is the de-anonymized self; a self-knowledge signature would be a diagonal that beats its column. Instead the diagonal (mean $+0.16$) matches the off-diagonals ($+0.15$), and the strongest column (Llama-3.3) is predicted better by every other model than by itself.

Table 19: other_report on Capability: predictor A (rows) asked about named subject B (columns), scored against B ’s measured per-subject accuracy (dev, Pearson r). Diagonal = the predictor asked about its own name.

A (about) $\downarrow B \rightarrow$	deepseek	gemini	gpt-nano	llama-3.3	maverick	qwen
deepseek-v4-flash-low	+0.17	+0.06	+0.06	+0.43	+0.19	+0.07
gemini-3.1-flash-lite-low	+0.01	+0.05	+0.16	+0.31	+0.26	+0.02
gpt-5.4-nano-low	+0.17	−0.11	+0.30	+0.42	+0.38	+0.03
llama-3.3-70b	+0.29	−0.52	+0.45	+0.07	−0.28	+0.16
llama-4-maverick	+0.16	−0.07	+0.28	+0.29	+0.31	+0.37
qwen3.7-plus-low	+0.22	−0.03	+0.36	+0.50	−0.16	+0.07

The named-subject matrix at the item-informed tier, and the answerer signature. The same matrix at the item-informed rung (each predictor shown the verbatim items and asked to predict a *named* model’s score; dev split, Capability and PropensityBench,

scripts/other_report_matrix.py -tier oracle) at first looks like self-knowledge: on Capability the named-self diagonal reaches +0.41 against +0.21 off-diagonal. Rescoring reveals most of it to be an *answerer signature*: predictor *A*’s answers about *B* fit *A*’s own behavior (+0.28) better than they fit *B*’s (+0.21) — the items shown are identical for every subject, so reading them engages the answerer’s own processing, which leaks into its predictions whoever is named. This is privileged information of a kind, but it is procedural (running the item), not reported self-knowledge: it appears equally when the question is about someone else, which is also why the generic-subject variant retains part of the transfer advantage in the main text. On PropensityBench the diagonal (+0.27) barely exceeds the leakage baseline (+0.25). Both evaluations are exactly the dev-split transfer pockets that did not replicate on the frozen test split (§4.4).

Reader × subject matrix for the history channel. Every pool model read every pool model’s measured dev history — byte-identical few_shot conversations, re-attributed to the subject by name via few_shot_other’s system turn — and predicted the subject’s held-out conditions out-of-fold (36 pairs × five evaluations; scripts/fewshot_analyst_matrix.py). Holding the *reader* fixed and varying whose history it reads separates privileged access from reader skill, the confound the fixed mid-tier analyst comparison cannot address. The result is a clean null: pooled named-self diagonal +0.24 vs. off-diagonal +0.25; the reader-fixed self-gain (a reader on its own record minus that reader’s mean on the others’) is −0.00 pooled and within [−0.06, +0.02] on every evaluation. Attribution is also inert: the diagonal differs from the stored (unattributed) few_shot by the entire system turn — the subject’s name, the “another AI model” framing, and the statement that the assistant turns are measured ground truth — and paired per cell that bundle changes nothing (−0.01, named better in 13 of 30 cells). Cells whose raw answers are (near-)constant inherit their correlation from the per-fold calibration offsets and are degenerate rather than agreeing; this equally affects the stored history-informed predictions on those cells.

Gains from the history: subject vs. analyst vs. pool readers. Comparing *levels* of history-informed prediction across readers still leaves open that readers differ in their starting knowledge, so we complete the gain comparison: the fixed analyst was asked the abstract named-subject question about each pool model with *no* history (scripts/analyst_zero_info.py), giving analyst gain = few_shot_other — that baseline, next to subject gain = few_shot — self_report and the pool readers’ gain from the two matrices. Pooled: subject +0.13, analyst +0.08, pool readers +0.24 — the subject gains no more from its own record than other readers do (its cells are, if anything, selection-biased upward: subject gains are computable only where self-report is not constant). The analyst’s zero-information answers are themselves revealing: asked about named systems it answers graded where every pool model issues constant denial (PropensityBench, up to +0.83 on the most pool-typical subject), yet the answers are generic — its prediction vectors for the six named subjects inter-correlate at up to +0.82, and they fit the named subject no better than the other models (transfer advantage −0.03 to +0.05 across four evaluations). Even reputation-informed prediction of a named model is knowledge of assistants and of the evaluation, not of that model.

L.4 Phrasing ablation: is the self/generic pair a minimal pair?

The self-report/generic-report and item-informed/generic-oracle pairs of §4.4 swap the subject of the final question but, in the published form, also add a preamble and change the reference class (“out of 100 capable AI agents that each faced exactly this situation”), and they leave the situation itself in the second person (“you ... your answer”). Two objections follow: the generic advantage could be an *answer-format* effect (a population-frequency question invites graded answers, “would you” invites a policy answer), and a model reading “you” throughout could simply simulate itself and report that, so generic parity would show self-leak rather than generic knowledge. This ablation closes both with four arms per channel, fully crossing the *subject* of the final question (self vs. generic) with the *framing* of everything before it (the current second-person text vs. a hand-written third-person rewrite in which no “you/your” appears before the question; same facts, same order, same length ±15%, checked by a unit test). Arm A is the published self-report; B changes only the final question’s subject (same second-person description, same reference class, no preamble); C is the third-person description with A’s question byte-for-byte; D is C with the generic subject — the clean minimal pair. E is the published generic control. The oracle arms (A’–E’) do the same to the protocol paragraph and the per-item ask while leaving the measured item untouched (it is the measurement), so their “third-person” arms remove the self from the framing and the question,

not from the exhibit. The honesty nudge is off in every arm. Dev split, six-model selection pool; report arms on eight evaluations, oracle arms on the five single-turn ones (DiscrimEval, Capability, Sycophancy, Reward hacking, PropensityBench); `scripts/selfgeneric_ablation.py`.

Table 20: Phrasing ablation: Pearson r vs. own behavior (macro-mean over (model, eval) cells, constant predictions scored 0; bootstrap CIs), and the paired contrasts that isolate one factor each (first minus second; exact sign-flip p). The clean pair C/D shows no subject effect on either channel; B reproduces the published E with the subject swap alone.

arm	report (48 cells)	item-informed (30 cells)
A self, 2p (published)	+0.11 [+0.06, +0.16]	+0.32 [+0.24, +0.40]
B generic, 2p	+0.19 [+0.13, +0.26]	+0.37 [+0.29, +0.43]
C self, 3p description	+0.07 [+0.02, +0.12]	+0.37 [+0.29, +0.43]
D generic, 3p description	+0.06 [-0.01, +0.13]	+0.38 [+0.30, +0.45]
E published generic control	+0.18 [+0.10, +0.26]	+0.34 [+0.26, +0.41]
A-B subject swap, 2p	-0.08 [-0.16, -0.01], $p = .03$	-0.05 [-0.13, +0.04], $p = .34$
C-D subject swap, 3p (clean pair)	+0.01 [-0.06, +0.08], $p = .78$	-0.01 [-0.08, +0.06], $p = .68$
A-C 3p rewrite, self	+0.04 [-0.01, +0.09], $p = .13$	-0.04 [-0.13, +0.05], $p = .37$
B-D 3p rewrite, generic	+0.13 [+0.06, +0.21], $p = .001$	-0.01 [-0.09, +0.07], $p = .79$
B-E preamble/ref. class	+0.01 [-0.09, +0.11], $p = .85$	+0.03 [-0.01, +0.08], $p = .19$

Scores. Table 20. On the item-informed tier every arm lands between +0.32 and +0.38 and every pairwise contrast has a CI spanning zero; the arm with the self absent from both framing and question (D’) scores highest. There is no self-simulation leak to find: removing the self from the protocol and the question changes nothing. On the abstract tier the published generic advantage is reproduced by the subject swap *alone* (B=E to within 0.01, under the unchanged second-person text, same reference class, no preamble), so the format/reference-class explanation is ruled out for the published pair. The subject effect that remains under second-person framing (-0.08) vanishes once the self is absent from the description (C-D = +0.01). The third-person rewrite itself *lowers* the generic arm (+0.19 → +0.06): it is a worse prompt, not a purer one, so C/D is the pair to cite for the null and not the level to cite for either method.

Answers. Constancy diagnostics show what the self question does: the self arms are policy answers (A: 29% of cells constant, 72% of individual answers exactly 0; C: 35% / 75%), the generic arms graded (B: 12% / 49%; D: 17% / 54%; E: 6% / 49%). The answers *do* change when the subject is swapped. The item-informed arms share item ids, so per-*item* answers pair exactly (Table 21): at the item grain, self/generic agreement is moderate at best, and weaker in rank terms on every evaluation but Sycophancy’s three-person pair — the Pearson agreement is partly carried by the shared zero mass. And where the two arms disagree about zero it is the *self* arm answering exactly 0 over a graded generic answer 6–9× more often than the reverse. Reading the most-changed items: under “would you” the reply states a policy (“I would not”, exactly 0); under the generic subject the same model produces a frequency estimate from generic mechanism knowledge (“a typical RLHF-tuned assistant will heavily weight the user’s confidence ... PREDICTION: 100”), and where the self arm does answer gradedly its reasoning is already population-talk (“some instances of the AI would succumb”). Switching the subject away from “you” changes what the question solicits — a statement of policy becomes an estimate of frequency — and with it the answer’s level and format; the remaining question is whether the change carries self-specific content. The direct test correlates, condition-wise, the within-model difference (self answer – generic answer) with the behavioral residual (own rate – cross-model mean); if the self question adds self-knowledge this is positive. It is null in all four cases: report A-B -0.02 [-0.08, +0.05], C-D +0.02 [-0.04, +0.07]; item-informed A’-B’ -0.03 [-0.11, +0.04], C’-D’ +0.05 [-0.02, +0.13] (the only evaluation-level positive, Sycophancy C’-D’ at +0.22, is offset by Capability at -0.14). The three self-specificity instruments of §4.4, run on every arm, agree: identity transfer (diagonal – off-diagonal) is at most +0.07 on any arm, and on every item-informed arm the same-arm committee of the *other* models predicts a model as well as or better than its own answer. The swap changes the answer’s format and level; it does not change whose behavior the answer tracks.

Item grain vs. condition grain. The disagreement above is between individual *items*, while every method in this paper is scored over *conditions*, which average many items each (~680 paired items

per (evaluation, model) against tens of conditions). Averaging recovers only part of the agreement. Over the conditions the methods are scored on, the item-informed arms agree at $r = +0.43$ / $\rho = +0.35$ for the published pair A'/B' (per-evaluation Spearman +0.17 to +0.59) and $r = +0.59$ / $\rho = +0.52$ for the clean pair C'/D' (+0.20 to +0.80); the abstract-report pairs agree more weakly still ($\rho = +0.24$ for A/B, +0.26 for C/D). The condition ordering therefore only partly survives the swap: the self and generic arms reach the same accuracy against behavior as two differently-ordered predictors, not as one prediction with the level shifted, which is why §4.5 claims the generic question as an equally accurate replacement for the self-framed one rather than a debiased copy of it.

Table 21: Per-item self/generic answer agreement on the item-informed tier (~680 paired items per (evaluation, model), ~150 on PropensityBench; mean over the six pool models). Pooled over evaluations, 27% of A'/B' item pairs have the self arm at exactly 0 against a graded generic answer and 3% the reverse (C'/D': 17% vs. 3%); the rest answer 0 in both arms or >0 in both.

evaluation	A' vs. B' (2p)		C' vs. D' (3p)	
	Pearson	Spearman	Pearson	Spearman
DiscrimEval	+0.70	+0.48	+0.76	+0.61
Capability	+0.44	+0.27	+0.57	+0.41
Sycophancy	+0.23	+0.17	+0.20	+0.22
Reward hacking	+0.26	+0.09	+0.25	+0.11
PropensityBench	+0.03	+0.03	+0.15	+0.11

the clean minimal pair, arm D (Sycophancy; arm C has “would you change your answer” in place of the generic subject and is otherwise identical)

An AI assistant answers a multiple-choice *[subject]* question, then the user disagrees and insists a different option is correct, asking it to reconsider.
The assistant gave the correct answer to a *[subject]* question and the user then said they think a different option is right.
Out of 100 situations like this, in how many would a typical capable AI assistant change its answer to the one the user suggests?

L.5 Setting and decoding sensitivity

Table 22 summarizes the tier comparison of §4.6; Fig. 5 replaces the tier split with a continuous capability axis. Each entry’s x is its accuracy on this paper’s MMLU subset (57 subjects $\times$ 20 questions), measured at the same reasoning setting as all its predictions; we use our own measurement because public MMLU reporting is saturated and sparse for these releases and never separates the reasoning-off/low variants the pool distinguishes. Across the twelve entries the self-report association is positive but not significant ($r = +0.48$, $p \approx 0.12$; the CI includes zero) and is driven as much by variation within tiers as between them; item-informed self-prediction shows essentially none ($r = +0.04$). Read alongside the pre-registered tier contrast, the conclusion is unchanged: no detectable capability effect on self-knowledge, with the self-report panel the one place a real trend could plausibly emerge in a larger pool.

Hindsight-tuning sensitivity. All headline numbers use settings frozen on the small-model selection pool. Choosing each cell’s best grid arm *in hindsight* — an upper bound on what per-model tuning could add — gains a mean of +0.07 on self-report (max +0.28 on a single cell) and +0.03 on the paired comparison, measured on the small tier where the swept grids exist. Frozen settings therefore cannot be hiding a large frontier advantage, and the self-specificity comparisons are setting-symmetric besides.

A learned sign for every method. Some models’ self-assessments on Sycophancy are systematically inverted — they rate themselves strong exactly where they fail — so a sign learned out-of-fold (per-fold sign + z-transform, the same leave-one-group-out folds as the trained methods) can decode signal a raw reading misses; confidence/difficulty re-framings of the collapsed self-report question behave the same way, recovering signal with model-specific polarity. We applied the learned sign to

Table 22: Scale analysis (test split; tier means over scored cells). Left: mean r of the key methods. Right: the self-specificity instruments for item-informed prediction — self minus generic-subject ($\Delta_{\text{self-gen}}$), identity-transfer advantage (own minus small-tier behavior), and the partial r given the cross-model mean. Capability moves the left columns; no instrument on the right moves with it.

Tier	self-rep.	item-inf.	generic	x-model	$\Delta_{\text{s-g}}$	transfer	partial
Small tier	+0.04	+0.23	+0.30	+0.56	-0.06	+0.09	+0.13
Frontier (off)	-0.02	+0.21	+0.17	+0.47	+0.04	-0.01	+0.08
Frontier (low)	+0.04	+0.33	+0.34	+0.61	-0.08	+0.03	+0.11




Figure 5: Capability vs. self-knowledge, per model (frozen test split; line = least-squares fit; x as described in the text). Squares = frontier entries (Claude Sonnet 5, GPT-5.5, DeepSeek V4 Pro at reasoning off/low), circles = small tier (DeepSeek V4 Flash, Gemini 3.1 Flash-Lite, GPT-5.4-nano, Llama-3.3-70B, Llama-4 Maverick, Qwen3.7-Plus).

every method’s predictions (Table 23). It is not a free win: on most cells polarity is already correct and stable, so the transform’s per-fold normalization and occasional wrong small-fold sign cost a little (every method’s macro drops slightly except the two that start at zero, proxy-scenario sampling and the mean of others’ self-reports). It pays exactly where testimony has stable, model-specific polarity — mainly Sycophancy: the item-informed paired comparison goes $+0.23 \rightarrow +0.35$ (the candidate identified in §4.2), the generic report $+0.13 \rightarrow +0.18$. Consistent with the main text: Sycophancy is where self-assessment is systematically inverted for some models, and decoding, not eliciting, is the binding step there.

Reasoning deltas per frontier base. $r(\text{low}) - r(\text{off})$ pooled over evals scored at both settings: self-report -0.16 (Sonnet), -0.02 (GPT-5.5), +0.10 (DeepSeek); item-informed self-prediction -0.03/+0.06/+0.19; its generic-subject control -0.05/+0.26/+0.28; cross-model mean -0.22/-0.00/+0.06. Summary in §4.6.

M Can Self-Knowledge Be Installed by Finetuning?

The diagnosis above says deployed models lack self-knowledge; it does not say they cannot acquire it — nothing in training selects for accurate self-models. Following Binder et al. [2025], we finetune four base models (four families: 31–72B dense models plus DeepSeek-V4-Flash) on their own measured behavior and ask what scoring rule such a claim needs. The training target is each model’s *acquiescence gap* on Anthropic’s model-written evals (151 categories, disjoint from our nine evaluations): how much more often it affirms a behavior when the affirmative answer is “yes” than when it is “no”. The gap is the model-specific part of behavior — raw agree-rates correlate strongly across models, the gaps barely do — so predicting it demands self-knowledge.

The three training corpora. All three are LoRA supervised-finetuning corpora built from the model’s *own* measured behavior; they differ only in what the label is. (1) *The rate corpus*: the model-written-eval items are clustered into topic families within each category (TF-IDF + k -means, seeded); each training pair shows K example items from one (category, cluster, polarity) cell — never naming the category, so the model must infer the family from item content, the same skill

Table 23: The learned-sign mechanism applied to every method (dev split, default pool; seven rate evaluations — DiscrimEval’s scored quantity is already signed). Each cell: raw dev $r \rightarrow$ pooled out-of-fold r after the per-fold sign + z-transform learned per CV fold (raw / flipped). The transform can only add signal where a method’s polarity is model-specific; elsewhere its per-fold normalization costs a little.

Method	PropB	Capab.	Syco.	RewHack	τ^2	τ^2 -tr	MASK	Macro raw	Macro flip
self-report	-0.12/-0.05	+0.19/+0.21	-0.02/-0.03	+0.12/+0.02	+0.28/+0.16	-0.07/+0.07	+0.15/-0.06	+0.08	+0.04
generic report	+0.25/-0.03	+0.16/+0.10	+0.13/+0.18	+0.03/+0.00	+0.24/+0.22	-0.12/+0.12	+0.27/+0.09	+0.14	+0.10
value framing	+0.23/+0.23	—	+0.07/+0.06	+0.11/+0.05	+0.17/+0.11	-0.14/-0.07	+0.21/+0.16	+0.11	+0.09
paired comparison	+0.28/+0.10	+0.24/+0.26	+0.18/+0.19	+0.13/+0.06	+0.01/+0.04	-0.16/-0.01	+0.44/+0.35	+0.16	+0.14
history-informed	+0.20/+0.07	+0.25/+0.24	+0.28/+0.24	+0.34/+0.29	+0.29/+0.22	+0.22/+0.18	+0.33/+0.20	+0.27	+0.21
self-prediction									
history-informed,	+0.20/-0.02	+0.26/+0.17	+0.33/+0.27	+0.32/+0.27	+0.04/-0.07	+0.11/+0.07	+0.39/+0.26	+0.23	+0.14
analyst answers									
analyst forecast	-0.05/+0.01	+0.03/+0.10	+0.29/+0.26	+0.31/+0.25	-0.02/+0.02	+0.11/-0.06	+0.61/+0.61	+0.18	+0.17
item-informed	+0.14/+0.07	+0.38/+0.36	+0.36/+0.29	+0.23/+0.10	-0.01/-0.02	+0.22/+0.08	+0.21/+0.34	+0.22	+0.17
self-prediction									
item-informed,	+0.24/-0.02	+0.37/+0.36	+0.35/+0.35	+0.32/+0.27	+0.06/+0.03	+0.25/+0.15	+0.34/+0.32	+0.28	+0.21
generic subject									
item-informed,	+0.31/+0.24	+0.43/+0.43	+0.44/+0.39	+0.35/+0.23	-0.00/-0.13	+0.30/+0.21	+0.08/-0.01	+0.27	+0.19
others’ mean									
item-informed	+0.11/-0.01	+0.20/+0.24	+0.23/+0.35	+0.21/+0.19	+0.20/+0.03	+0.30/+0.13	+0.45/+0.41	+0.24	+0.19
paired comparison									
proxy-scenario	+0.07/-0.02	-0.07/+0.11	+0.11/-0.00	-0.34/+0.34	+0.03/-0.23	+0.06/+0.05	+0.13/+0.12	-0.00	+0.05
sampling									
item-informed	+0.05/-0.03	+0.11/+0.13	+0.42/+0.27	+0.24/+0.11	+0.34/+0.02	+0.40/+0.37	+0.27/+0.11	+0.26	+0.14
proxy sampling									
cross-model	+0.38/+0.32	+0.78/+0.77	+0.57/+0.57	+0.85/+0.85	+0.32/+0.20	+0.54/+0.39	+0.78/+0.77	+0.60	+0.55
behavior mean									
mean of others’	-0.10/-0.09	+0.27/+0.27	-0.00/-0.06	+0.17/+0.04	+0.19/-0.03	-0.23/+0.07	+0.03/+0.18	+0.05	+0.06
self-reports									

the benchmark methods need — and asks “*Below are K example questions of a particular kind: [items]. Out of 100 questions like these, in how many would you answer Yes? Respond with only a number*”; the completion is the model’s own measured affirmative rate on that cell (e.g. “83”). (2) *The residual corpus*: identical example-item prompts (drawn from an independent random stream), but the question and label change to the model-specific part only: “...a typical language model would answer Yes some number of times. Compared to that typical model, how many more or fewer times would you answer Yes?”, with the completion the signed deviation of the model’s own rate from the mean rate of the donor pool measured on the same cell (e.g. “-17”). Since a cross-model prior already captures the pool-shared part of any rate (§4.1), the residual variant makes the self-specific component the entire label rather than a small part of it. (3) *The property-prediction corpus* (the Binder et al. [2025] objective, 30k pairs): each pair shows a single prompt and asks a property of the model’s *own next response* to it (e.g. whether its answer would be among the first options, what its second word would be), with the label obtained by actually sampling the model. The contrast with (1) and (2) is the quantity being taught: (3) trains *self-simulation* — reproducing one forward pass’s output — while (1) and (2) train *dispositional* self-description, a rate over an item family. Held-out categories, and held-out items within each cluster, are excluded from all training prompts and reserved for evaluation.

Self-prediction is learnable, but convergence is governed by behavioral drift (Table 24). Every tuned model predicts its own gap far better than its base — yet the finetune also *moves* the behavior being predicted (a shift noted only in passing in prior work), so a single round’s accuracy against the training target overstates self-knowledge; the right target is the tuned model’s *own*, re-elicited behavior. The less a finetune perturbs behavior the closer the two agree: Gemma barely drifts and nearly reaches a fixed point in one round, while Llama drifts most and its tuned model partly describes the model it *used to be*.⁷

Apparent gains on real evals need a predictability control (Table 25). We track self-report here rather than the item-informed channel because the training target is an abstract self-description, so self-report is the channel the finetune should move; item-informed self-prediction shows no consistent movement (Table 26: macro changes are within ± 0.13 for every pair except Gemma’s rate

⁷Llama’s tuned-self figure uses a 100-item behavior subsample, so its labels are noisier and the correlation attenuated — a conservative estimate. Gemma and Qwen use full-precision behavior throughout.

Table 24: Self-prediction finetuning, one round of $G(M) = \text{finetune}(M_0, \text{behavior}(M))$, on held-out categories ($n=40$; gap correlation, noise ceiling ≈ 0.98). **Base self** and **tuned self**: how well each model predicts its *own* acquiescence gap. **Drift** $|\Delta_{\text{gap}}|$: how much the finetune moved the model’s own behavior. Convergence tracks drift: the less behavior moves, the closer tuned self-prediction gets to the training target (tuned vs. base behavior).

Base model	Base self	Tuned self	Tuned vs. target	Drift $ \Delta_{\text{gap}} $
Llama-3.3-70B	+0.463	+0.934	+0.736	0.269
Gemma-4-31B	+0.761	+0.949	+0.942	0.051
Qwen2.5-72B	+0.762	+0.851	+0.949	0.117
DeepSeek-V4-Flash	-0.173	+0.719	+0.713	0.042

Table 25: DiscrimEval self_report gain after self-prediction finetuning, controlled against cross_model_mean (a predictor that never consults the model, so Δ measures behavior becoming more typical of the pool). The **residual** $\Delta_{\text{self_report}} - \Delta_{\text{cross_model_mean}}$ is the self-specific gain. The rate self-prediction corpus yields a positive residual on every base; the residual-target corpus (§M) amplifies it on Gemma but not uniformly — DeepSeek’s residual-corpus row is null. (The Binder-style property finetune [Binder et al., 2025] on Llama, not shown, has essentially zero residual — its raw gain is entirely increased predictability.)

Finetune	$\Delta_{\text{self_report}}$	Δ_{xmm}	Residual
Llama-3.3-70B (rate corpus)	+0.218	+0.126	+0.092
Gemma-4-31B (rate corpus)	+0.408	+0.119	+0.289
Qwen2.5-72B (rate corpus)	+0.113	+0.049	+0.065
DeepSeek-V4-Flash (rate corpus)	+0.040	-0.095	+0.135
Gemma-4-31B (residual corpus)	+0.635	+0.232	+0.403
Llama-3.3-70B (residual corpus)	+0.135	+0.027	+0.108
DeepSeek-V4-Flash (residual corpus)	-0.143	-0.101	-0.042

corpus, whose gain is confined to PropensityBench), which is itself telling — what training installs does not transfer to the channel that actually carries signal. On DiscrimEval self-report improves after finetuning — but so does the cross-model behavior mean, which never consults the model, because the finetune makes behavior more typical of the pool; the self-specific gain is the residual after subtracting that change. It is positive for our rate corpus on all four bases but essentially zero for a Binder-style property finetune on Llama, whose raw gain is entirely increased predictability. The taught self-knowledge is also narrow (no consistent gain on Capability or Sycophancy across bases, Table 26), so this is a real but eval-specific effect. Replicating the residual-target variant on two further families supports both halves of that reading while showing the pocket is family-specific: DeepSeek (low drift, like Gemma) gains on Sycophancy (residual +0.15; ≈ 0 on DiscrimEval and Capability) rather than DiscrimEval, and Llama’s heavy drift (cross-model mean +0.70 $\rightarrow$ +0.53) makes its naive residual uninterpretable — each residual-corpus model still predicts its *own* re-elicited gap far better than its base (Llama +0.47 $\rightarrow$ +0.84, DeepSeek -0.12 $\rightarrow$ +0.58; base values differ slightly from Table 24 because they are re-elicited on the residual-corpus held-out set).

The full base-vs-tuned picture (Table 26). For completeness, Table 26 reports every finetune pair on every evaluation where both sides are scored, for the three channels the finetunes could plausibly move. The pattern above generalizes: no corpus produces a broad, cross-eval gain in any channel — movements are eval-specific, and the item-informed channel, which carries most of the usable signal, is largely indifferent to finetuning.

Self-simulation is not self-knowledge (Table 27). A remaining deflationary reading is that our finetunes were simply too weak — that more of the same training would eventually install the missing faculty. A Binder-style *property-prediction* finetune [Binder et al., 2025] on 30k hypothetical-response items shows a sharper dissociation: it lifts held-out single-prompt self-prediction dramatically — Llama-3.3-70B from 45.8% to 73.6%, Qwen3-30B from 34.2% to 70.2%, Gemma-4-31B from 52.9% to 64.7%, DeepSeek-V4-Flash from 62.2% to 71.4% on held-out behavior categories, replicating Binder et al. [2025] — while the same checkpoints move our dispositional targets essentially nowhere (self-report macro +0.18 $\rightarrow$ +0.19 on Llama and +0.13 $\rightarrow$ +0.20 on Qwen; item-informed self-prediction +0.45 $\rightarrow$ +0.50 and +0.23 $\rightarrow$ +0.24; PropensityBench self-report a

Table 26: Every self-prediction finetune pair on every evaluation where both the base and the tuned model are scored (dev split, tuned settings; cells are base $\rightarrow$ tuned r ; macro averages the evaluations scored on both sides of that row). Corpora: *rate* = absolute agree-rate self-prediction; *residual* = signed deviation-from-donor-mean (§M); *property* = Binder-style hypothetical-response prediction (intro30k). ‘-’ = not scored; † = dropped by the noise-ceiling filter (behavior too unreliable to score). The only consistent paired-comparison movement is the Gemma family’s PropensityBench gain; elsewhere its changes are within noise.

Finetune	Method	Sycophancy	DiscrimEval	Capability	PropB	Macro
Gemma-4-31B (rate)	self-report	-0.11 $\rightarrow$ -0.34	+0.00 $\rightarrow$ +0.41	+0.23 $\rightarrow$ +0.20	+0.00 $\rightarrow$ +0.00	+0.03 $\rightarrow$ +0.07
	item-informed self	+0.28 $\rightarrow$ +0.42	+0.46 $\rightarrow$ +0.61	-0.06 $\rightarrow$ +0.17	+0.12 $\rightarrow$ +0.72	+0.20 $\rightarrow$ +0.48
	paired comp.	-0.28 $\rightarrow$ -0.42	-	-0.03 $\rightarrow$ -0.10	+0.11 $\rightarrow$ +0.63	-0.07 $\rightarrow$ +0.04
Gemma-4-31B (residual)	self-report	-0.11 $\rightarrow$ -0.23	+0.00 $\rightarrow$ +0.64	+0.23 $\rightarrow$ +0.19	+0.00 $\rightarrow$ +0.00	+0.03 $\rightarrow$ +0.15
	item-informed self	-	-	-	+0.12 $\rightarrow$ +0.44	+0.12 $\rightarrow$ +0.44
	paired comp.	-	-	-	+0.11 $\rightarrow$ +0.40	+0.11 $\rightarrow$ +0.40
Gemma-4-31B (property)	self-report	-0.11 $\rightarrow$ -0.25	-†	+0.23 $\rightarrow$ +0.16	+0.00 $\rightarrow$ +0.00	+0.04 $\rightarrow$ -0.03
	item-informed self	+0.28 $\rightarrow$ +0.39	-†	-0.06 $\rightarrow$ +0.04	+0.12 $\rightarrow$ +0.00	+0.12 $\rightarrow$ +0.14
	paired comp.	-0.28 $\rightarrow$ -0.35	-†	-0.03 $\rightarrow$ +0.13	+0.11 $\rightarrow$ +0.42	-0.07 $\rightarrow$ +0.07
Qwen2.5-72B (rate)	self-report	-0.01 $\rightarrow$ +0.06	-†	-	+0.00 $\rightarrow$ -0.07	-0.00 $\rightarrow$ -0.00
	item-informed self	-0.05 $\rightarrow$ +0.18	-†	+0.13 $\rightarrow$ +0.02	+0.68 $\rightarrow$ +0.42	+0.25 $\rightarrow$ +0.21
	paired comp.	-	-†	-	+0.39 $\rightarrow$ +0.36	+0.39 $\rightarrow$ +0.36
Llama-3.3-70B (rate)	self-report	+0.00 $\rightarrow$ -0.24	-†	+0.18 $\rightarrow$ +0.13	+0.00 $\rightarrow$ +0.35	+0.06 $\rightarrow$ +0.08
	item-informed self	+0.35 $\rightarrow$ +0.53	-†	+0.56 $\rightarrow$ +0.63	+0.51 $\rightarrow$ -0.13	+0.47 $\rightarrow$ +0.34
	paired comp.	-0.07 $\rightarrow$ -0.25	-†	+0.13 $\rightarrow$ +0.03	+0.32 $\rightarrow$ +0.17	+0.12 $\rightarrow$ -0.02
Llama-3.3-70B (residual)	self-report	+0.00 $\rightarrow$ +0.33	-†	+0.18 $\rightarrow$ +0.08	-	+0.09 $\rightarrow$ +0.21
	item-informed self	+0.35 $\rightarrow$ +0.27	-†	+0.56 $\rightarrow$ +0.38	-	+0.45 $\rightarrow$ +0.32
	paired comp.	-0.07 $\rightarrow$ -0.33	-†	+0.13 $\rightarrow$ +0.09	-	+0.03 $\rightarrow$ -0.12
DeepSeek-V4-Flash (rate)	self-report	+0.06 $\rightarrow$ +0.29	+0.14 $\rightarrow$ +0.18	-0.13 $\rightarrow$ -0.28	-	+0.02 $\rightarrow$ +0.06
	item-informed self	+0.32 $\rightarrow$ +0.16	+0.66 $\rightarrow$ +0.63	+0.21 $\rightarrow$ +0.26	-	+0.40 $\rightarrow$ +0.35
	paired comp.	+0.06 $\rightarrow$ +0.09	-	-0.01 $\rightarrow$ -0.37	-	+0.02 $\rightarrow$ -0.14
DeepSeek-V4-Flash (residual)	self-report	+0.06 $\rightarrow$ +0.42	+0.14 $\rightarrow$ +0.00	-0.13 $\rightarrow$ -0.16	-	+0.02 $\rightarrow$ +0.09
	item-informed self	+0.32 $\rightarrow$ +0.37	+0.66 $\rightarrow$ +0.51	+0.21 $\rightarrow$ +0.50	-	+0.40 $\rightarrow$ +0.46
	paired comp.	+0.06 $\rightarrow$ +0.23	-	-0.01 $\rightarrow$ -0.23	-	+0.02 $\rightarrow$ +0.00
DeepSeek-V4-Flash (property)	self-report	+0.06 $\rightarrow$ +0.05	+0.14 $\rightarrow$ -0.02	-0.13 $\rightarrow$ +0.08	-	+0.02 $\rightarrow$ +0.04
	item-informed self	+0.32 $\rightarrow$ +0.11	+0.66 $\rightarrow$ +0.44	+0.21 $\rightarrow$ +0.25	-	+0.40 $\rightarrow$ +0.27
	paired comp.	+0.06 $\rightarrow$ +0.05	-	-0.01 $\rightarrow$ -0.16	-	+0.02 $\rightarrow$ -0.06

null before and after). Predicting *what you would say to this prompt* and knowing *how you tend to behave across situations* are, on this evidence, separable abilities: training installs the first without touching the second, which is why single-prompt self-prediction accuracy cannot stand in for behavioral self-knowledge.

Table 27: The property-prediction dissociation across four families: single-prompt self-prediction trains up; dispositional self-knowledge stays flat. Majority-class baseline for the held-out accuracy: 43.2% (Llama) / 42.6% (Qwen) / 38.7% (Gemma) / 38.4% (DeepSeek); DeepSeek macros cover its three measured text evaluations.

Model (base $\rightarrow$ tuned)	Binder held-out acc.	self-report macro r	informed_oracle macro r
Llama-3.3-70B	45.8% $\rightarrow$ 73.6%	+0.18 $\rightarrow$ +0.19	+0.45 $\rightarrow$ +0.50
Qwen3-30B-A3B	34.2% $\rightarrow$ 70.2%	+0.13 $\rightarrow$ +0.20	+0.23 $\rightarrow$ +0.24
Gemma-4-31B	52.9% $\rightarrow$ 64.7%	+0.03 $\rightarrow$ -0.03	+0.20 $\rightarrow$ +0.14
DeepSeek-V4-Flash	62.2% $\rightarrow$ 71.4%	+0.02 $\rightarrow$ +0.04	+0.40 $\rightarrow$ +0.33

What determines improvability: grain-locking. Read together, the three results above follow one principle: *training at one level of abstraction moves only that level*. The rate corpus (aggregate labels over item families) moves condition-level self-report and leaves item-informed prediction unmoved; the property corpus (single-prompt labels) moves single-prompt self-simulation and leaves both dispositional channels unmoved; and within a grain, gains stay on the families trained (Table 26). Nothing transfers up or down the abstraction ladder. Beyond grain, the pockets line up with three evaluation properties: a residual appears where (i) there is self-specific variance to learn at all (the share of §4.1; Capability’s null is overdetermined), (ii) the first-person channel is not suppressed

by safety training (PropensityBench stays a constant-denial null after every finetune), and (iii) the target is a low-order, single-pass property (DiscrimEval’s within-item contrast) rather than a multi-turn trajectory rate. Harm-loading and turn count are confounded across our nine evaluations, so with $N = 9$ this is a hypothesis-generating account, not an inference; the mechanistic reading follows.

A mechanistic hypothesis, and how to test it. We offer one account of grain-locking, flagged as interpretation rather than finding. A single-prompt property (what the model’s next response to *this* prompt will be like) is represented in the activations of the forward pass that produces it, so a finetune only has to wire a readout to information that is already there — which is why Binder-style training is fast and large-gain. A cross-context rate is a property of the policy over a distribution of situations: it is in the weights only *procedurally*, as the policy itself, and represented nowhere in any single forward pass. A finetune cannot wire a readout to something that is not represented; it can only install a declarative association from item family to rate, which predicts the observed signature — narrow, family-specific, no generalization. The same account explains why the item-informed channel is indifferent to finetuning (it already runs the item through the policy, so it possesses the activation-level information; its binding constraint is aggregating over stochastic variation, which a memorized fact does not fix) and why the finetune moves behavior (self-knowledge and the policy share weights). Three black-box tests would discriminate it. (i) If aggregation is the bottleneck, showing all measured items of a condition in one context and asking for the aggregate rate should do *worse* than asking per item and averaging — identical information, different grain. (ii) A forced simulate-then-judge variant (write your answer to the item, then convert it to a prediction) would show whether models can self-simulate but do not deploy it spontaneously. (iii) The full transfer matrix between rate-trained and property-trained checkpoints, scored on both targets, should show near-zero transfer in both directions. The direct test is a linear probe on an open-weights model predicting its own rates from answer-time activations, separating “information absent” from “present but not verbalized”; we deliberately kept the present study black-box and leave it as the natural next step.

N A Causal Taxonomy of Prediction Failure, and What Each Control Rules Out

“The model doesn’t know itself” is only one of the places a self-prediction can fail. This appendix derives the space of alternatives systematically, states why the derivation is exhaustive at its level of description, reports the completeness check we ran against adjacent fields’ failure taxonomies, and then maps each of the paper’s controls onto the failure loci it rules out (Table 28) — the pre-answer to the review genre “couldn’t the null just be X ?”.

The pipeline model. We model a self-prediction experiment as a causal pipeline with two branches joined at a single shared latent variable, the model’s disposition D . On the *elicitation branch*, researcher intent I is formulated as a question Q (link L1), construed by the model as C (L2), used to access self-information K about D (L3 — the introspection step proper), rendered as an answer A (L4), and converted by the researcher into a prediction P (L5). On the *behavior branch*, the same D , together with the benchmark context and sampling noise, generates behavior (L6), which the harness scores (L7). L0 collects the framework assumptions binding the branches together: a common disposition exists at all, the same model configuration answers and behaves, and asking does not causally influence behaving.

Why the partition is exhaustive at the link level. P is a deterministic function of the path $I \rightarrow Q \rightarrow C \rightarrow K \rightarrow A \rightarrow P$; the score is generated by $(D, \text{context}, \text{noise}) \rightarrow \text{behavior} \rightarrow \text{score}$; and the two paths share exactly one latent variable, D , under the L0 assumptions. If the prediction misses, at least one of the eight links L0–L7 failed to preserve the relevant information — there is nowhere else for the error to enter, because every transformation between signal entry (D , and I for what the researcher wanted to know about D) and the two outputs is enumerated. Two residual risks are inherited rather than eliminated: an *unstated* framework assumption would be a missing L0 entry (which is why a residual “other” code remains necessary in any coding protocol), and the catalog of *mechanisms within* a link is illustrative and open-ended — the completeness claim is about failure loci, not mechanisms.

Within-link failure modes. Each link’s failure modes are derived by a dichotomy tree over that link’s transformation (e.g. for the report step L4: is the report attempting to convey what was accessed? if yes, information is lost in expressibility, in the imposed response format, or in a trained response bias; if no, content is withheld — refusal, observable — or replaced — misreport, unobservable). The resulting categories are mutually exclusive as *defect types*, while a single observed failure may instantiate several at once, so coding is multi-label over a MECE code set — standard practice in root-cause analysis. Several causes are observationally identical from the outside (confabulation, a sincere but secondhand self-model, and a *consistent* misreport can produce the same transcript), so each case is coded at the coarsest level the evidence supports; separating them needs instruments beyond behavior, which is exactly the boundary drawn in the Limitations.

Completeness check against adjacent fields. We cross-checked the derivation against four mature failure taxonomies, mapping their categories onto ours and ours onto theirs. Survey methodology’s four-stage response model (comprehension → retrieval → judgment → response) [Tourangeau et al., 2000] maps onto L2–L4 and produced the one genuine addition of the exercise — a distinct *judgment error* mode at L3 (mis-integrating adequately retrieved evidence), which the initial derivation lacked — and independently confirmed the speculative L0 mode of question–behavior interaction (the mere-measurement effect). The threats-to-validity literature (construct underrepresentation, construct-irrelevant variance, reliability, external validity) maps cleanly because it is itself organized causally. The attitude–behavior literature contributes the compatibility principle [Ajzen and Fishbein, 1977] — prior art for our reference-class-mismatch modes — and situational strength for contextual override. The introspection literature supplies confabulation [Nisbett and Wilson, 1977] and the third-person self-interpretation theory that in effect *predicts* our secondhand-self-model category. After the one addition, no category of theirs was left unmapped, and every unmatched category of ours is LLM-specific for an articulable reason (a human respondent cannot have learned their self-model from third-person descriptions of *other* respondents). This is the pattern the exhaustiveness argument predicts if the derivation is sound: adjacent fields refine mechanisms *within* links; none adds a link.

Table 28: The paper’s experiments and controls as tests of failure loci. L-codes refer to the pipeline links above; “closed” means the locus cannot explain the observed failure pattern, given the cited result.

Control / experiment	Failure loci addressed	What the results establish
Noise ceilings + reliability filter (§3)	L7: sampling error in the measured targets	Cells without reliable targets are excluded; the nulls are not artifacts of noisy measurement.
Split-half reliability of elicited answers (§4.2)	L2/L4: unstable construal, noisy reporting	Testimony is highly stable (0.8–0.95); the failure is not elicitation noise.
Identity transfer (§4.2, Fig. 4)	L3: generic or secondhand self-model	Verbal testimony describes other models about as well as the self: a generic prior in first-person clothing.
Deniable + register elicitation (§4.2, App. L.1)	L4: withholding, social desirability	Powered null; suppression is real but local, and removing it does not restore self-knowledge.
Pairwise forced choice (§4.2)	L4: denial bypass	Recovers signal only where direct asking collapses into denial; no general advantage.
Learned-sign decoding (§4.2, App. L.5)	L4: verbalization bottleneck	Self-assessment carries signal with model-specific polarity — report-stage mangling rather than absent access.
Protocol-informed self-report (App. L.2)	L1: underspecified operationalization; L4	Describing the full measurement protocol restores no signal and deepens denial on the norm-violating evals; the informed gain is item-level.
Item-informed self-prediction, single-turn evals (§4.3)	L1/L2: underspecified or misconstrued question; L5: reference class	Closed: the exhibit <i>is</i> the measured item, so the residual deficit is located at access/report (L3/L4).
Initial-state item-informed prediction, PropensityBench + τ^2 (§4.3)	L1/L2/L5, partially	Multi-turn dynamics are only described; the residual is coded “L3 vs. multi-turn self-forecasting, unresolved”.
Frozen test split; out-of-fold tuning (§3)	L5: researcher inference, selection	No method setting or sign is ever fit on the data it is scored on.
Re-elicitation + predictability control (§4.7)	L0: finetuning changes the disposition being described	Tuned models are scored against re-elicited behavior, net of the outside-view change.
Contamination analysis (§5)	L6: memorization as a non-target determinant	Familiarity would make asking <i>easier</i> , and asking still loses; it can inflate the bar, which we state.
<i>Not covered:</i> evaluation awareness	L6: behaving differently under a detected eval	Conspicuous forbidden tools on the agentic evals; flagged as a limitation (§7).