

RbFT-Net: Rectify-Before-Fuse Temporal Radar Anchors for 4D Radar–Camera Depth Completion

Wentao Zhao¹, Shouxuan Wu², Yongtao Cen¹, Tianchen Deng¹, Yuyang Zhang³, Jingchuan Wang¹

¹School of Automation and Intelligent Sensing, Institute of Medical Robotics, Shanghai Jiao Tong University, Shanghai 200240, China

²School of Electronic and Information Engineering, Beijing Jiaotong University, Beijing, China

³State Key Laboratory of Advanced Rail Autonomous Operation and School of Electronic and Information Engineering, Beijing Jiaotong University, Beijing 100044, China

Abstract

Dense metric depth prediction from cameras and millimeter-wave radar offers a cost-effective sensing solution for autonomous systems. However, radar measurements are inherently sparse and susceptible to clutter, multipath reflections, and projection errors. While aggregating multiple radar frames provides denser metric cues, it also introduces temporal misalignment and dynamic-object interference. Directly propagating such unreliable measurements can therefore corrupt large regions of the predicted depth map. To address this issue, we propose RbFT-Net, an end-to-end *rectify-before-fuse* framework for multi-frame 4D radar–camera depth completion. Rather than assuming accumulated radar returns to be accurate, RbFT-Net treats them as noisy temporal anchor candidates. An image-conditioned rectification module jointly corrects their image-plane locations and metric depths while estimating pointwise reliability. The rectified anchors are then selectively propagated before high-level multi-modal fusion, suppressing the influence of unreliable measurements. Experiments on ZJU-4DRadarCam and a newly collected 4D radar–camera–LiDAR dataset show that RbFT-Net consistently outperforms the evaluated independent radar–camera methods and remains competitive with plug-in pipelines using auxiliary monocular depth models. Cross-platform evaluation and component analyses further support the effectiveness of the proposed rectification and reliability-aware propagation strategy.

Introduction

Dense metric depth estimation is fundamental to autonomous driving, robotic navigation, and 3D scene understanding. Cameras provide rich appearance cues but cannot directly resolve metric scale and may degrade under adverse visual conditions, whereas LiDAR provides accurate geometry at a relatively high cost. Millimeter-wave radar offers direct metric ranging and robustness to illumination changes, making it an attractive complementary sensor for dense depth prediction (Lin, Dai, and Van Gool 2020; Lo and Vandewalle 2021; Long et al. 2021; Singh et al. 2023). In particular, 4D radar resolves elevation in addition to range, azimuth, and Doppler, allowing height-aware radar returns to be projected into the camera view as sparse metric cues (Li et al. 2024b; Sun et al. 2024; Wang et al. 2025).

Existing radar–camera depth completion methods commonly propagate projected radar measurements to dense image regions under visual guidance (Long et al. 2021; Singh et al. 2023; Li et al. 2024b; Sun et al. 2024, 2025b). However, radar returns are extremely sparse and may be inconsistent with visual structures because of limited angular resolution, multipath effects, clutter, calibration uncertainty, and radar-to-image misprojection. Once propagated, inaccurate radar measurements can contaminate much larger image regions, particularly around object boundaries, thin structures, and distant objects. Recent plug-in methods alleviate the limited structural information of radar by incorporating dense predictions from separately trained monocular depth models (Li et al. 2024b; Qin et al. 2025; Wang et al. 2025). Although these predictions provide strong structural priors, they introduce an additional model dependency and increase the size and complexity of the complete inference pipeline. This motivates an independent solution that directly predicts dense metric depth from radar and RGB inputs.

A complementary source of information is the temporal measurements naturally available in radar streams. Consecutive radar frames provide complementary metric observations and can alleviate the sparsity of single-frame input. A conventional temporal fusion strategy is to use ego-motion to warp historical measurements into the current view (Zhou et al. 2025). Although such geometric alignment reduces rigid inter-frame displacement, it does not guarantee accurate radar-to-image anchors: the warped returns may still be affected by calibration uncertainty, radar depth noise, multipath reflections, and independently moving objects. Direct accumulation further retains temporal misalignment while also aggregating clutter and other unreliable returns. Multi-frame radar can therefore become denser without becoming more reliable, potentially amplifying errors during subsequent propagation. This raises the central question of this work: *how can noisy temporal radar measurements be rectified and selectively exploited before their errors propagate into dense depth predictions?*

To address this question, we propose **RbFT-Net**, an end-to-end *rectify-before-fuse* framework for multi-frame 4D radar–camera depth completion. Rather than assuming accumulated radar returns to be accurate depth measurements, RbFT-Net treats them as noisy temporal anchor candidates. An image-conditioned rectification module jointly corrects

their image-plane locations and metric depths while estimating pointwise reliability. The resulting anchors are then selectively propagated according to their reliability and target-anchor compatibility before high-level multi-modal fusion and dense refinement. This design suppresses unreliable temporal measurements before their errors spread over the image. Operating directly on accumulated radar returns, RbFT-Net predicts dense metric depth from radar and RGB without relying on an auxiliary monocular depth model. Combined with an efficient dense prediction backbone, it forms a compact independent pipeline.

We conduct extensive experiments on ZJU-4DRadarCam (Li et al. 2024b) and a newly collected dataset acquired using a different 4D radar-camera platform. RbFT-Net achieves the strongest overall performance among independent methods and remains competitive with plug-in pipelines across both datasets. Zero-shot and limited-data adaptation experiments further evaluate its cross-sensor transferability, while comprehensive ablations and efficiency analyses validate the proposed components and demonstrate a favorable accuracy-efficiency trade-off.

Our main contributions are summarized as follows:

- We propose RbFT-Net, an end-to-end rectify-before-fuse framework that rectifies noisy temporal radar anchors before reliability-aware propagation and high-level multi-modal fusion.
- We introduce an image-conditioned temporal anchor rectification module that jointly corrects the image-plane locations and metric depths of noisy radar returns while estimating their pointwise reliability.
- We develop a reliability-aware propagation strategy that combines anchor reliability with target-anchor compatibility to selectively transfer trustworthy metric evidence to dense image regions.
- We collect a new 4D radar-camera-LiDAR dataset using a different sensing platform and conduct in-domain, zero-shot, and limited-data cross-sensor evaluations. The dataset and evaluation protocol will be made publicly available.

Related Work

Following TacoDepth (Wang et al. 2025), we categorize radar-camera depth completion methods as independent or plug-in. Independent methods directly predict metric depth from radar and RGB, whereas plug-in methods additionally rely on an auxiliary monocular depth model. We also review temporal fusion for depth estimation.

Independent Radar-Camera Depth Completion. Depth completion commonly propagates sparse measurements using learned spatial affinities or image-conditioned weights. Representative methods such as CSPN++ (Cheng et al. 2020) and BP-Net (Tang et al. 2024) are effective for relatively accurate LiDAR samples, but can be sensitive to the substantially sparser and noisier measurements provided by radar.

Independent radar-camera methods directly fuse radar and RGB inputs. Early studies explored sensor complementarity, pixel-depth association, and ordinal depth prediction (Lin,

Dai, and Van Gool 2020; Long et al. 2021; Lo and Vandewalle 2021; Singh et al. 2023). Subsequent methods improve radar utilization through confidence modeling (Sun et al. 2024), sparse supervision (Li et al. 2024a), geometric upsampling (Sun et al. 2025b), lightweight distillation (Sun et al. 2025a,c), transformer-based fusion (Huang et al. 2024), and structure-aware modeling (Zhang et al. 2025). Just-Depth (Yun, Kim, and Lee 2026) focuses on efficient estimation under sparse supervision, while TacoDepth (Wang et al. 2025) provides an independent one-stage configuration. Despite recent efforts to recalibrate projected radar returns (Qin et al. 2025), existing methods generally do not jointly rectify their image locations and metric depths while estimating reliability before dense propagation.

Plug-in Radar-Camera Depth Completion. Plug-in methods combine radar measurements with predictions from a separately trained monocular depth model. RadarCam-Depth (Li et al. 2024b) incorporates 4D radar into an auxiliary monocular depth representation, while radar-guided polynomial fitting (Rim et al. 2025) and RaCalNet (Qin et al. 2025) recover the metric scale and shift of affine-invariant depth predictions. TacoDepth (Wang et al. 2025) also supports a plug-in configuration. Although these methods benefit from dense monocular structure, their complete inference pipelines require an additional depth network, motivating more compact independent alternatives.

Temporal Fusion for Depth Estimation. Multi-frame monocular methods exploit neighboring images through geometric matching, cost volumes, or motion-aware modeling (Watson et al. 2021; Guizilini et al. 2022; Zhou et al. 2025), typically relying on relative poses or geometric warping. Radar-camera methods commonly accumulate consecutive radar sweeps to increase input density (Lin, Dai, and Van Gool 2020; Long et al. 2021; Gasperini et al. 2021; Lo and Vandewalle 2021). However, direct accumulation can introduce temporal misalignment, dynamic returns, clutter, and multipath interference, making denser radar input not necessarily more reliable. In contrast, RbFT-Net treats accumulated returns as noisy temporal anchors and jointly rectifies their locations and depths while estimating their reliability before dense propagation.

Method

Overview

Given the current RGB image I_t and a short temporal window of 4D radar frames $\{\mathcal{R}_{t-k}\}_{k=0}^{T-1}$, our goal is to predict a dense metric depth map D_t in the current camera view. As illustrated in Fig. 1, RbFT-Net follows a *rectify-before-fuse* paradigm: it first rectifies temporal radar anchors using image context and then performs reliability-aware propagation and high-level multi-modal fusion.

Radar returns from all T frames are directly projected into the current image using the calibrated radar-camera extrinsics and camera intrinsics, without ego-motion compensation:

$$\mathcal{A}_t = \{a_i = (\mathbf{p}_i, z_i, \mathbf{r}_i)\}_{i=1}^N, \quad (1)$$




Figure 1: Overview of RbFT-Net. Directly accumulated multi-frame 4D radar returns are treated as noisy temporal anchor candidates. Image-conditioned rectification corrects their image-plane locations and metric depths while estimating pointwise reliability. The resulting anchors are selectively propagated according to their reliability and target–anchor compatibility to produce dense metric depth.

where $\mathbf{p}_i = (u_i, v_i)$ is the projected location in the current image, z_i is the corresponding metric depth, and $\mathbf{r}_i$ contains the radar attributes. The candidates are processed as an unordered set without explicit temporal-index encoding. Although direct accumulation increases observation density, it also introduces temporal misalignment under sensor or object motion and retains cluttered returns. Therefore, $\mathcal{A}_t$ is treated as a set of noisy anchor candidates rather than reliable depth measurements.

The image-conditioned anchor rectification module samples local visual context around each candidate and predicts its spatial offset, depth residual, and pointwise reliability. The resulting rectified anchor is represented as

$$\hat{a}_i = (\hat{\mathbf{p}}_i, \hat{z}_i, c_i, \mathbf{f}_i^a), \quad (2)$$

where $\hat{\mathbf{p}}_i = (\hat{u}_i, \hat{v}_i)$ and $\hat{z}_i$ are the rectified image location and metric depth, $c_i \in [0, 1]$ is the estimated reliability, and $\mathbf{f}_i^a$ is the anchor feature used for propagation.

The reliability-aware propagation module evaluates nearby anchors according to their reliability and target–anchor compatibility, aggregates informative metric evidence, and performs image-guided refinement to produce the final depth map. The overall framework is summarized as

$$\hat{\mathcal{A}}_t = \mathcal{F}_{\text{rect}}(\mathcal{A}_t, I_t), \quad D_t = \mathcal{F}_{\text{prop}}(I_t, \mathcal{R}_t, \hat{\mathcal{A}}_t), \quad (3)$$

where $\mathcal{F}_{\text{rect}}$ denotes image-conditioned anchor rectification, while $\mathcal{F}_{\text{prop}}$ includes reliability-aware propagation, high-level multi-modal fusion, and dense refinement.

Image-Conditioned Radar Anchor Rectification

Accumulated radar returns provide metric measurements but may contain inaccurate projections and depths due to limited angular resolution, multipath, clutter, and temporal inconsistency. We therefore rectify each temporal anchor candidate using local image evidence before propagation.

As shown in Fig. 2, the module comprises a radar query sampler (RQS), radar-centered attention (RCA), multi-scale anchor fusion (MAF), and three prediction heads. RQS samples local image features, while RCA first models radar-neighborhood consistency through self-attention and weighted pooling and then retrieves compatible visual evidence through cross-attention. MAF integrates the resulting

multi-scale representations before three prediction heads estimate the spatial offset, depth residual, and reliability.

For each candidate $a_i \in \mathcal{A}_t$, its depth and radar attributes are encoded as

$$\mathbf{f}_i^r = \mathcal{E}_{\text{rad}}([z_i, \mathbf{r}_i]). \quad (4)$$

Meanwhile, the image encoder extracts a multi-scale feature pyramid:

$$\{\mathbf{F}^s\}_{s=1}^S = \mathcal{E}_{\text{img}}(I_t), \quad (5)$$

where $\mathbf{p}_i^s$ denotes $\mathbf{p}_i$ mapped to the coordinate system of $\mathbf{F}^s$.

Radar Query Sampler. Directly sampling at $\mathbf{p}_i^s$ may provide unreliable visual evidence when the radar projection is inaccurate. At each scale, RQS therefore predicts M radar-conditioned sampling offsets:

$$\{\delta_{i,m}^s\}_{m=1}^M = \mathcal{H}_{\text{off}}^s(\mathbf{f}_i^r), \quad (6)$$

and extracts the corresponding image features through bilinear sampling:

$$\mathbf{x}_{i,m}^s = \text{Bil}(\mathbf{F}^s, \mathbf{p}_i^s + \delta_{i,m}^s), \quad m = 1, \dots, M. \quad (7)$$

This local sampling allows visual evidence to be collected around the initial projection without requiring explicit correspondence search.

Radar-Centered Attention. RCA first models the local consistency among radar candidates and then retrieves visually compatible evidence through cross-modal attention. For each candidate a_i , we collect a local radar neighborhood $\mathcal{N}_i^r$ and form its radar tokens as

$$\mathbf{G}_i^r = \{\mathbf{g}_{i,j}^r \mid a_j \in \mathcal{N}_i^r\}, \quad \mathbf{g}_{i,j}^r = [\mathbf{f}_j^r, \phi(\mathbf{p}_j - \mathbf{p}_i)], \quad (8)$$

where $\phi(\cdot)$ encodes the relative position with respect to the center candidate.

Self-attention is first applied within the radar neighborhood:

$$\mathbf{Z}_i^r = \text{Attn}(\mathbf{G}_i^r \mathbf{W}_q^r, \mathbf{G}_i^r \mathbf{W}_k^r, \mathbf{G}_i^r \mathbf{W}_v^r). \quad (9)$$

The resulting neighbor features are summarized by weighted pooling:

$$\bar{\mathbf{f}}_i^r = \sum_{a_j \in \mathcal{N}_i^r} \beta_{i,j} \mathbf{z}_{i,j}^r, \quad \beta_i = \text{softmax}(\mathcal{H}_{\text{wp}}(\mathbf{Z}_i^r)). \quad (10)$$




Figure 2: Image-conditioned radar anchor rectification. RQS and RCA aggregate local visual evidence around each radar candidate across multiple scales, while MAF predicts spatial and depth corrections with pointwise reliability to produce rectified temporal anchors.

This radar self-attention and weighted pooling characterize the local measurement consistency while suppressing unreliable neighboring returns.

At each image scale, the pooled radar representation serves as the query, while the image features sampled by RQS provide the keys and values:

$$\mathbf{q}_i^s = \mathbf{W}_q^s \bar{\mathbf{f}}_i^r, \quad \mathbf{k}_{i,m}^s = \mathbf{W}_k^s \mathbf{x}_{i,m}^s, \quad \mathbf{v}_{i,m}^s = \mathbf{W}_v^s \mathbf{x}_{i,m}^s. \quad (11)$$

The cross-attention output is computed as

$$\alpha_{i,m}^s = \text{softmax}_m \left(\frac{(\mathbf{q}_i^s)^\top \mathbf{k}_{i,m}^s}{\sqrt{d}} \right), \quad \bar{\mathbf{f}}_i^s = \sum_{m=1}^M \alpha_{i,m}^s \mathbf{v}_{i,m}^s. \quad (12)$$

Finally, the radar and visual representations are fused to produce the scale-specific anchor feature:

$$\tilde{\mathbf{f}}_i^s = \mathcal{F}_{\text{rca}}^s \left([\bar{\mathbf{f}}_i^r, \bar{\mathbf{f}}_i^s] \right). \quad (13)$$

Multi-Scale Anchor Fusion. Fine-scale features preserve local boundaries, whereas coarse-scale features provide broader contextual information. MAF integrates the representations from all scales while retaining the original radar feature:

$$\mathbf{h}_i = \mathcal{F}_{\text{maf}} \left(\tilde{\mathbf{f}}_i^1, \dots, \tilde{\mathbf{f}}_i^S, \mathbf{f}_i^r \right). \quad (14)$$

Three lightweight heads predict the image-plane offset, depth residual, and pointwise reliability:

$$\Delta \mathbf{p}_i = \mathcal{H}_{\text{spa}}(\mathbf{h}_i), \quad \Delta z_i = \mathcal{H}_{\text{dep}}(\mathbf{h}_i), \quad c_i = \sigma(\mathcal{H}_{\text{conf}}(\mathbf{h}_i)). \quad (15)$$

The rectified location and depth are obtained through residual updates:

$$\hat{\mathbf{p}}_i = \mathbf{p}_i + \Delta \mathbf{p}_i, \quad \hat{z}_i = z_i + \Delta z_i. \quad (16)$$

Finally, we retain $\mathbf{f}_i^a = \mathbf{h}_i$ and define the rectified temporal anchor set as

$$\hat{\mathcal{A}}_t = \{\hat{a}_i = (\hat{\mathbf{p}}_i, \hat{z}_i, c_i, \mathbf{f}_i^a)\}_{i=1}^N. \quad (17)$$

Rather than serving as a binary mask, c_i continuously modulates each anchor's contribution during subsequent dense propagation.




Figure 3: Reliability-aware anchor propagation. For each target location, spatially neighboring anchors are scored, and the top four are aggregated using reliability-modulated weights.

Reliability-Aware Anchor Propagation

Although rectification improves the quality of temporal radar anchors, they remain sparse and unevenly distributed. Moreover, directly propagating all nearby anchors may spread residual misalignment, clutter, and dynamic returns into dense image regions. We therefore introduce reliability-aware anchor propagation, which selects informative anchors for each target location and adaptively aggregates their metric evidence before dense refinement.

Reliability-Guided Anchor Selection. Given the rectified temporal anchors $\hat{\mathcal{A}}_t$, we first retrieve the K nearest anchors for each target location $\mathbf{p}$ on the propagation feature map:

$$\mathcal{N}_K(\mathbf{p}) = \text{KNN}(\mathbf{p}, \hat{\mathcal{A}}_t). \quad (18)$$

For each candidate $\hat{a}_i \in \mathcal{N}_K(\mathbf{p})$, we construct a target-anchor representation from the target image context, anchor feature, rectified depth, and relative projected position:

$$\mathbf{m}_{p,i} = [\mathbf{F}(\mathbf{p}), \mathbf{f}_i^a, \hat{z}_i, \phi_p(\mathbf{p} - \hat{\mathbf{p}}_i)], \quad (19)$$

where $\mathbf{F}(\mathbf{p})$ denotes the image feature at the target location, and $\phi_p(\cdot)$ encodes the relative position between the target and rectified anchor.

Table 1: Quantitative comparison on ZJU-4DRadarCam. All plug-in methods use the same DPT-Hybrid (Ranftl, Bochkovski, and Koltun 2021). N/A denotes results not reported in the original paper. Bold and underlined values indicate the category-wise best and second-best results, respectively, while **best** and **second-best** indicate the corresponding overall rankings.

Type	Method	0–50m						0–70m						0–80m					
		MAE↓	RMSE↓	iMAE↓	iRMSE↓	Rel↓	δ_1 ↑	MAE↓	RMSE↓	iMAE↓	iRMSE↓	Rel↓	δ_1 ↑	MAE↓	RMSE↓	iMAE↓	iRMSE↓	Rel↓	δ_1 ↑
Plug-in	RadarCam (*24)	<u>1067.5</u>	<u>2817.4</u>	<u>10.5</u>	<u>22.9</u>	0.087	0.920	<u>1157.0</u>	<u>3117.7</u>	<u>10.4</u>	<u>22.9</u>	<u>0.087</u>	<u>0.921</u>	<u>1183.5</u>	<u>3229.0</u>	<u>10.4</u>	<u>22.8</u>	0.090	0.920
	TacoDepth (*25)	930.2	2477.3	9.3	20.8	N/A	N/A	983.1	2779.6	9.3	20.9	0.076	0.932	1032.5	2850.3	9.4	20.9	N/A	N/A
Indep- endent	DORN (*21)	2210.2	4129.7	19.8	31.9	0.157	0.783	2402.2	4625.2	19.8	31.9	0.160	0.777	2447.6	4760.0	19.9	31.9	0.161	0.776
	Singh (*23)	1785.4	3704.6	18.1	35.3	0.146	0.831	1932.7	4137.1	18.0	35.2	0.147	0.828	1979.5	4309.3	17.9	35.1	0.147	0.828
	BP-Net (*24)	1404.8	2923.1	10.6	<u>21.2</u>	0.104	<u>0.895</u>	1531.0	3259.6	10.5	<u>21.0</u>	0.105	<u>0.892</u>	1568.2	3383.4	<u>10.4</u>	<u>21.0</u>	0.105	<u>0.892</u>
	XD-RC (*25)	1155.0	2863.0	11.7	24.6	<u>0.094</u>	0.891	1248.0	3223.0	11.7	24.5	<u>0.095</u>	0.890	1275.0	3341.0	11.7	24.5	<u>0.095</u>	0.889
	TacoDepth (*25)	1120.1	2686.7	12.8	25.0	N/A	N/A	1181.8	<u>2906.3</u>	12.7	24.9	N/A	N/A	1201.1	2990.7	12.7	24.9	N/A	N/A
	JustDepth (*26)	1224.7	3157.5	12.8	25.2	0.096	0.888	1307.8	3479.0	12.7	25.2	0.096	0.888	1334.6	3618.1	12.7	25.2	0.096	0.888
	SomeDepth (*26)	<u>1029.2</u>	<u>2631.6</u>	<u>10.4</u>	22.8	N/A	N/A	<u>1111.6</u>	2946.9	<u>10.4</u>	22.8	N/A	N/A	<u>1137.2</u>	3053.0	<u>10.4</u>	22.8	N/A	N/A
	RbFT-Net	917.4	2473.4	6.8	16.9	0.067	0.944	1001.0	2740.8	6.8	16.8	0.068	0.943	1023.7	2827.6	6.7	16.8	0.068	0.942

A lightweight MLP predicts a compatibility score:

$$s_i(\mathbf{p}) = \mathcal{M}_{\text{sel}}(\mathbf{m}_{p,i}). \quad (20)$$

Rather than propagating all neighboring anchors, we retain the K_s candidates with the highest compatibility scores:

$$\mathcal{T}_{K_s}(\mathbf{p}) = \underset{\hat{a}_i \in \mathcal{N}_K(\mathbf{p})}{\text{TopK}}(s_i(\mathbf{p}), K_s). \quad (21)$$

We set $K_s = 4$ in all experiments.

The selected anchors are adaptively weighted according to both their target compatibility and predicted reliability:

$$w_i(\mathbf{p}) = \frac{c_i \exp(s_i(\mathbf{p}))}{\sum_{\hat{a}_j \in \mathcal{T}_{K_s}(\mathbf{p})} c_j \exp(s_j(\mathbf{p}))}. \quad (22)$$

The propagated anchor representation is then obtained as

$$\bar{\mathbf{f}}^a(\mathbf{p}) = \sum_{\hat{a}_i \in \mathcal{T}_{K_s}(\mathbf{p})} w_i(\mathbf{p}) \mathcal{E}_a([\mathbf{f}_i^a, \hat{z}_i]), \quad (23)$$

where $\mathcal{E}_a$ embeds the anchor feature together with its rectified metric depth.

This two-stage strategy first restricts candidates by spatial proximity and then selects visually compatible anchors through learned relevance. The explicit reliability modulation suppresses residual erroneous returns during propagation.

Multi-Modal Fusion and Refinement. After rectification and reliability-aware propagation, the temporal anchors form the propagated feature map $\bar{\mathbf{F}}^a$. We then adopt the lightweight MFN-CSPN++ architecture of BP-Net (Tang et al. 2024) for high-level multi-modal fusion and dense refinement:

$$D_t = \mathcal{R}_{\text{ref}}(\mathbf{F}, \mathbf{F}_{\text{rad}}^t, \bar{\mathbf{F}}^a), \quad (24)$$

where $\mathbf{F}_{\text{rad}}^t$ preserves the directly observed current-frame measurements, while $\bar{\mathbf{F}}^a$ provides reliability-aware metric evidence from the rectified temporal anchors.

Unlike BP-Net, which directly aggregates the four nearest sparse measurements, RbFT-Net performs reliability-aware aggregation over rectified temporal anchors before lightweight MFN-CSPN refinement.

Training Objectives

The network is trained end-to-end using LiDAR-projected depth supervision. The overall objective is

$$\mathcal{L} = \lambda_d \mathcal{L}_{\text{depth}} + \lambda_a \mathcal{L}_{\text{anchor}} + \lambda_c \mathcal{L}_{\text{conf}} + \lambda_p \mathcal{L}_{\text{prop}}. \quad (25)$$

Here, $\mathcal{L}_{\text{depth}}$ supervises the final depth prediction, while $\mathcal{L}_{\text{anchor}}$ constrains the rectified anchor depths. $\mathcal{L}_{\text{conf}}$ provides error-aware supervision for anchor reliability, and $\mathcal{L}_{\text{prop}}$ encourages the propagation module to favor depth-consistent anchors. Detailed loss definitions and supervision construction are provided in the supplementary material.

Experiments

Experimental Setup

Datasets. We evaluate RbFT-Net on ZJU-4DRadarCam (Li et al. 2024b) and a newly collected dataset from a different 4D radar-camera platform. Both provide synchronized radar, camera, and LiDAR data, with projected radar as input and LiDAR depth as ground truth.

Compared Methods. We compare with representative plug-in methods (Li et al. 2024b; Wang et al. 2025) and independent methods (Lo and Vandewalle 2021; Singh et al. 2023; Sun et al. 2025c; Wang et al. 2025; Yun, Kim, and Lee 2026; Hou and Ohtsuki 2026). The evaluated plug-in methods use DPT-Hybrid (Ranftl, Bochkovski, and Koltun 2021) for auxiliary monocular depth. We also adapt BP-Net (Tang et al. 2024) to radar inputs as a propagation baseline without anchor rectification or reliability modeling.

Evaluation Metrics. We report MAE and RMSE in millimeters, iMAE and iRMSE in 1/km, and the unitless AbsRel and δ_1 over valid ground-truth pixels. Lower values are better except for δ_1 .

Implementation Details. RbFT-Net is trained at 288×864 on ZJU-4DRadarCam and 288×832 on our dataset, using five accumulated radar frames by default. For each target location, it retrieves $K = 8$ rectified anchors and aggregates the top $K_s = 4$ based on learned compatibility scores. Additional settings and dataset statistics are provided in the supplementary material.




Figure 4: Qualitative comparison on ZJU-4DRadarCam.

Table 2: Evaluation on our newly collected dataset within the 0–70 m range under different target-domain data regimes. Zero-shot models are trained only on ZJU-4DRadarCam; adaptation models are fine-tuned for three epochs using 10% of the target-domain training set.

Setting	Method	MAE ↓	RMSE ↓	iMAE ↓	iRMSE ↓	Rel ↓	δ_1 ↑
Standard 100%	DORN	2243.2	4928.2	6.4	16.6	0.106	0.884
	Singh	1824.6	4685.2	5.9	15.7	0.092	0.918
	RadarCam	1644.9	<u>4120.7</u>	5.7	<u>14.4</u>	0.078	<u>0.938</u>
	JustDepth	<u>1559.7</u>	4229.3	<u>4.5</u>	15.4	0.072	0.938
	RbFT-Net	1430.4	3622.1	4.1	12.4	0.069	0.941
Zero-shot 0%	RadarCam	9373.0	13073.8	32.4	44.8	0.412	0.284
	JustDepth	<u>9286.3</u>	13431.7	<u>27.9</u>	<u>38.2</u>	<u>0.360</u>	<u>0.331</u>
	RbFT-Net	7185.9	10692.7	21.5	31.1	0.319	0.421
Adaptation 10%	RadarCam	<u>3416.7</u>	<u>5792.0</u>	<u>8.0</u>	<u>16.1</u>	<u>0.137</u>	<u>0.835</u>
	JustDepth	4082.6	6821.5	11.2	27.1	0.186	0.752
	RbFT-Net	2312.3	4696.8	6.4	15.0	0.105	0.895

Comparison with State-of-the-Art Methods

ZJU-4DRadarCam. Table 1 reports the quantitative results on ZJU-4DRadarCam. RbFT-Net consistently achieves the best performance among independent methods across all metrics and evaluation ranges. Compared with the strongest independent baseline for each metric, it reduces MAE by approximately 10%, iMAE by about 35%, and iRMSE by over 25%. Without relying on the auxiliary DPT-Hybrid monocular depth model, RbFT-Net remains competitive with, and in most reported settings surpasses, the plug-in TacoDepth configuration. The qualitative comparisons in Fig. 4 show cleaner depth predictions with sharper object boundaries and fewer artifacts in distant regions.

Evaluation on the Newly Collected Dataset. Table 2 compares the methods under standard training, zero-shot transfer, and limited-data adaptation. With the full target-domain training set, RbFT-Net achieves the strongest overall performance. For cross-platform evaluation, ZJU-4DRadarCam serves as the source domain and the newly collected dataset as the target domain. Under zero-shot transfer, RbFT-Net consistently outperforms the compared methods despite differences in sensing platforms and scene distributions, reducing MAE by 22.6% relative to JustDepth and RMSE by 18.2%

Table 3: 0–70 m accuracy–efficiency comparison on ZJU-4DRadarCam. FPS is measured on an NVIDIA RTX PRO 5000. RbFT-Net uses five radar frames; all other methods use one. Plug-in parameter counts include auxiliary depth models.

Type	Method	Params (M) ↓	FPS ↑	MAE ↓	RMSE ↓	δ_1 ↑
Plug-in	RadarCam (Li et al. 2024b)	156.26	12.04	1157.0	3117.7	0.921
	TacoDepth (Wang et al. 2025)	137.25	N/A	983.1	<u>2779.6</u>	<u>0.932</u>
Independent	DORN (Lo and Vandewalle 2021)	107.88	24.74	2402.2	4625.2	0.777
	BP-Net (Tang et al. 2024)	89.87	12.04	1531.0	3259.6	0.892
	JustDepth (Yun, Kim, and Lee 2026)	16.07	110.06	1307.8	3479.0	0.888
	RbFT-Net (Ours)	<u>44.20</u>	<u>44.88</u>	<u>1001.0</u>	2740.8	0.943

relative to RadarCam. When fine-tuned for three epochs using the same 10% target-domain subset, RbFT-Net again achieves the best results across all metrics, demonstrating effective adaptation under limited target-domain supervision.

Accuracy and Efficiency. Table 3 compares representative methods under their default input configurations. RbFT-Net uses only about **1/3** of the parameters of complete plug-in pipelines, whose parameter counts include the auxiliary 123M-parameter DPT-Hybrid, while achieving the best overall accuracy. Despite processing five radar frames, it runs in real time at 44.88 FPS. Table 5 further shows that directly extending competing methods to multiple frames yields only limited accuracy gains, demonstrating the favorable accuracy–efficiency trade-off of RbFT-Net.

Ablation Studies

We conduct ablation studies on ZJU-4DRadarCam under the 0–70 m evaluation range to analyze the contributions of the proposed components and the effect of temporal radar input.

Component Analysis. Table 4 evaluates the proposed rectification and propagation designs. With reliability estimation retained, spatial and depth rectification individually reduce RMSE by 258.2 and 180.2 mm, respectively, and their combination provides further improvement. Given fully rectified anchors, learned propagation outperforms direct 4-NN aggregation, while confidence guidance further reduces RMSE from 2980.1 to 2740.8 mm. These results demonstrate the complementary effects of anchor rectification and reliability-aware propagation.

Table 4: Component ablation on ZJU-4DRadarCam. All variants use five radar frames. *4-NN* directly aggregates the four nearest anchors, whereas *Learned* denotes feature-based propagation.

Rectification			Anchor	Metrics [0–70 m]			
Spatial	Depth	Conf.	Propagation	MAE ↓	RMSE ↓	Rel ↓	δ_1 ↑
		✓	Learned	1287.1	3064.6	0.087	0.920
✓		✓	Learned	1055.5	2806.4	0.071	0.938
	✓	✓	Learned	1135.7	2884.4	0.077	0.929
✓	✓		4-NN	1355.7	3062.6	0.096	0.904
✓	✓		Learned	1207.3	2980.1	0.081	0.923
✓	✓	✓	Learned	1001.0	2740.8	0.068	0.943

Table 5: Effect of the number of radar frames within the 0–70 m range in RMSE (mm). Radar points denote the average number of valid projected returns per sample.

Method	Number of Radar Frames				
	1	2	3	5	7
Avg. radar points	493.5	987.2	1480.9	2468.0	3455.3
RadarCam (Li et al. 2024b)	3117.7	3104.1	3092.4	3071.9	3085.1
BP-Net (Tang et al. 2024)	3259.6	3172.4	3135.8	3121.3	3156.8
RbFT-Net (Ours)	2987.3	2841.5	2794.0	2740.8	2760.2

Effect of Temporal Input. Table 5 compares methods retrained for each temporal window under the same direct-accumulation setting. Despite the near-linear increase in projected points, RadarCam and BP-Net gain only modestly from additional frames, whereas RbFT-Net reduces RMSE by 246.5 mm from one to five frames, demonstrating the benefit of rectifying temporal returns before propagation. The slight degradation at seven frames suggests increased misalignment and noise, while processing more radar points also incurs additional computational cost. We therefore use five frames by default as a practical trade-off among observation density, temporal noise, and efficiency.

Analysis and Visualization

Reliability Analysis. Fig. 5 examines the relationship among predicted reliability, anchor depth error, and propagation usage. Both the point-wise correlation and binned statistics show that anchor depth error generally decreases with increasing reliability. High-reliability anchors also tend to contribute more frequently to the learned target–anchor associations. This relationship is not absolute, since anchor selection additionally depends on target–anchor compatibility and the relative quality of nearby candidates. Overall, these results indicate that the predicted reliability provides an effective cue for identifying accurate and informative rectified anchors during dense depth propagation.

Structure-Consistent Propagation. Fig. 6 visualizes target–anchor associations from two complementary perspectives. Fig. 6(a) shows the anchors aggregated for selected target locations, while Fig. 6(b) shows the target regions influenced by selected anchors. Without reliability-guided




Figure 5: Reliability analysis of rectified radar anchors. Higher reliability corresponds to lower depth error and greater propagation usage.




Figure 6: Visualization of learned target–anchor associations. (a) Anchors contributing to selected target regions. (b) Target regions influenced by selected anchors. Reliability-guided selection reduces propagation across unrelated structures and object boundaries.

selection, the four nearest anchors are directly aggregated based on spatial proximity, often propagating information across unrelated structures and object boundaries. In contrast, RbFT-Net selects reliable anchors compatible with each target location, favoring depth evidence from the same local surface and reducing propagation across object boundaries. This structure-consistent behavior emerges without explicit semantic supervision.

Conclusion

This paper presented RbFT-Net, a compact independent framework for multi-frame 4D radar–camera depth completion. Its rectify-before-fuse design corrects noisy temporal anchors before reliability-aware propagation and multi-modal fusion. By modeling anchor locations, depths, and reliability, RbFT-Net exploits denser temporal cues while suppressing unreliable propagation. Experiments on a public benchmark and a newly collected dataset, including cross-platform transfer and limited-data adaptation, demonstrate its robustness across radar–camera platforms.

References

- Cheng, X.; Wang, P.; Guan, C.; and Yang, R. 2020. Cspn++: Learning context and resource aware convolutional spatial propagation networks for depth completion. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, 10615–10622.
- Gasparini, S.; Koch, P.; Dallabetta, V.; Navab, N.; Busam, B.; and Tombari, F. 2021. R4dyn: Exploring radar for self-supervised monocular depth estimation of dynamic scenes. In *2021 International Conference on 3D Vision (3DV)*, 751–760. IEEE.
- Guizilini, V.; Ambrus, R.; Chen, D.; Zakharov, S.; and Gaidon, A. 2022. Multi-Frame Self-Supervised Depth with Transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 160–170.
- Hou, Z.; and Ohtsuki, T. 2026. Selection, Not Fusion: Radar-Modulated State Space Models for Radar-Camera Depth Estimation. *arXiv preprint arXiv:2605.11840*.
- Huang, X.; Ma, Y.; Yu, Z.; and Zhao, H. 2024. RCDformer: Transformer-based dense depth estimation by sparse radar and camera. *Neurocomputing*, 589: 127668.
- Li, H.; Jing, M.; Jin, W.; Dong, S.; Liang, J.; Fan, H.; and Ji, R. 2024a. Sparse beats dense: Rethinking supervision in radar-camera depth completion. In *European Conference on Computer Vision*, 127–143. Springer.
- Li, H.; Ma, Y.; Gu, Y.; Hu, K.; Liu, Y.; and Zuo, X. 2024b. Radarcam-depth: Radar-camera fusion for depth estimation with learned metric scale. In *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 10665–10672. IEEE.
- Lin, J.-T.; Dai, D.; and Van Gool, L. 2020. Depth estimation from monocular images and sparse radar data. In *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 10233–10240. IEEE.
- Lo, C.-C.; and Vandewalle, P. 2021. Depth estimation from monocular images and sparse radar using deep ordinal regression network. In *2021 IEEE International Conference on Image Processing (ICIP)*, 3343–3347. IEEE.
- Long, Y.; Morris, D.; Liu, X.; Castro, M.; Chakravarty, P.; and Narayanan, P. 2021. Radar-camera pixel depth association for depth completion. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 12507–12516.
- Qin, X.; Zhao, W.; Cao, C.; Niu, Y.; Deng, T.; Jiang, H.; Guo, R.; and Wang, J. 2025. RaCalNet: Radar Calibration Network for Sparse-Supervised Metric Depth Estimation. *arXiv preprint arXiv:2506.15560*.
- Ranftl, R.; Bochkovskiy, A.; and Koltun, V. 2021. Vision transformers for dense prediction. In *Proceedings of the IEEE/CVF international conference on computer vision*, 12179–12188.
- Rim, P.; Park, H.; Ezhov, V.; Moon, J.; and Wong, A. 2025. Radar-guided polynomial fitting for metric depth estimation. *arXiv preprint arXiv:2503.17182*.
- Singh, A. D.; Ba, Y.; Sarker, A.; Zhang, H.; Kadambi, A.; Soatto, S.; Srivastava, M.; and Wong, A. 2023. Depth estimation from camera image and mmwave radar point cloud. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 9275–9285.
- Sun, H.; Feng, H.; Ott, J.; Servadei, L.; and Wille, R. 2024. Cafnet: A confidence-driven framework for radar camera depth estimation. In *2024 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2734–2740. IEEE.
- Sun, H.; Vysotskaya, N.; Sukianto, T.; Feng, H.; Ott, J.; Peng, X.; Servadei, L.; and Wille, R. 2025a. Lircdepth: Lightweight radar-camera depth estimation via knowledge distillation and uncertainty guidance. In *ICASSP 2025-2025 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 1–5. IEEE.
- Sun, H.; Wang, Z.; Feng, H.; Ott, J.; Servadei, L.; and Wille, R. 2025b. Get-up: Geometric-aware depth estimation with radar points upsampling. In *2025 IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, 1850–1860. IEEE.
- Sun, H.; Wang, Z.; Peng, X.; Ott, J.; Stettinger, G.; Servadei, L.; and Wille, R. 2025c. XD-RCDepth: Lightweight Radar-Camera Depth Estimation with Explainability-Aligned and Distribution-Aware Distillation. *arXiv preprint arXiv:2510.13565*.
- Tang, J.; Tian, F.-P.; An, B.; Li, J.; and Tan, P. 2024. Bilateral propagation network for depth completion. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 9763–9772.
- Wang, Y.; Li, J.; Hong, C.; Li, R.; Sun, L.; Song, X.; Wang, Z.; Cao, Z.; and Lin, G. 2025. Tacodepth: Towards efficient radar-camera depth estimation with one-stage fusion. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 10523–10533.
- Watson, J.; Mac Aodha, O.; Prisacariu, V.; Brostow, G.; and Firman, M. 2021. The temporal opportunist: Self-supervised multi-frame monocular depth. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 1164–1174.
- Yun, W.; Kim, D.; and Lee, S. 2026. JustDepth: Real-Time Radar-Camera Depth Estimation With Single-Scan LiDAR Supervision. *IEEE Robotics and Automation Letters*.
- Zhang, F.; Yu, Z.; Li, C.; Zhang, R.; Bai, X.; Zhou, Z.; Cao, S.-Y.; Wang, F.; and Shen, H.-L. 2025. Structure-Aware Radar-Camera Depth Estimation. In *2025 IEEE International Conference on Robotics and Automation (ICRA)*, 13028–13035. IEEE.
- Zhou, K.; Bian, J.-W.; Zheng, J.-Q.; Zhong, J.; Xie, Q.; Trigoni, N.; and Markham, A. 2025. Manydepth2: Motion-aware self-supervised monocular depth estimation in dynamic scenes. *IEEE Robotics and Automation Letters*.