

RT-DETR-WORLD: TRANSFERRING RICH LLM SEMANTICS TO REAL-TIME OPEN-VOCABULARY DETECTION

Yupeng Zhang¹ Ziyi Zhao² Juntao Cheng^{3,4} Sheng Wang¹ Ningnan Guo¹ Ruize Han² Liang Wan¹

¹Tianjin University. ²Shenzhen University of Advanced Technology. ³Shanghai Jiaotong University.

⁴Shanghai AI Laboratory.

{zhangyupeng, kevinwang630, guo_nn, lwan}@tju.edu.cn, suat25060113@stu.suat-sz.edu.cn
hanruize@suat-sz.edu.cn, juntao-cheng@sjtu.edu.cn

ABSTRACT

Open-vocabulary detection (OVD) recognizes categories unseen during training through textual category queries, yet achieving strong generalization with real-time efficiency remains challenging. Beyond vocabulary scaling, zero-shot generalization may benefit from reusable visual-semantic cues learned from seen data, including attributes, actions, states, and contextual relations. Existing real-time OVD methods primarily emphasize vocabulary coverage and efficient region/query-text matching; under strict efficiency constraints, compact detectors may struggle to absorb rich instance semantics and scene context. We propose **RT-DETR-World**, a compact DETR-style detector that transfers the rich semantics conveyed by descriptions during training while retaining lightweight query-text matching at inference. We construct **GroundingCapv2** with three levels of supervision: category names for standard OVD, object descriptions conveying instance-level semantics, and image descriptions conveying object relations and scene context. These descriptions serve only as training-time semantic supervision. To help the compact detector absorb these semantics, we propose **Dual-Path Description Alignment (DDA)**, combining a deployment-consistent MiniLM pathway with a training-only LLM teacher. MiniLM provides query-category supervision and object-description alignment, while offline teacher features supervise matched queries and global visual representations at the object and image levels, respectively. All teacher features are precomputed, and the teacher-side modules are removed after training. We further propose **Relation-Aware Negative Relaxation (RNR)**, which uses teacher-derived semantic similarities to relax related negatives while preserving exact positives. Experiments demonstrate competitive zero-shot accuracy and a favorable accuracy-efficiency trade-off. *The code will be released.*

1 INTRODUCTION

Open-vocabulary detection (OVD) (Zareian et al., 2021) uses natural-language queries to recognize categories unseen during training. Real-world applications such as robotics, autonomous driving, and edge vision demand strong zero-shot generalization and efficient inference. Recent real-time OVD methods, including Grounding DINO 1.5 Edge (Ren et al., 2024), YOLO-World (Cheng et al., 2024), YOLOE (Wang et al., 2025), and OV-DEIM (Wang et al., 2026), have substantially improved the speed-accuracy trade-off, highlighting the potential of compact open-vocabulary detectors.

Beyond scaling the training vocabulary, zero-shot generalization may also benefit from reusable visual-semantic factors learned from seen data. As illustrated in Fig. 1, the rich semantics conveyed by descriptions reveal such fine-grained cues, helping match visual instances to unseen category concepts. For example, cues associated with *chair* and *wheel*, *two-seat configuration* and *sofa*, or *wooden material* and *spoon* may facilitate the recognition of *wheelchair*, *two-seater sofa*, and *wooden spoon*, respectively. This intuition echoes the compositionality principle of compositional zero-shot learning (CZSL) (Jiang et al., 2024; Zhang et al., 2024), where reusable semantic factors learned from seen compositions support the recognition of unseen combinations.




Figure 1: **Descriptions convey rich, reusable visual-semantic factors.** Fine-grained cues learned from seen data may help match visual instances to unseen category concepts at test time.

Large-scale grounded vision-language detectors further demonstrate the value of the rich semantics conveyed by descriptions, as attributes, actions, and relations provide useful cues for distinguishing and localizing object instances. GLIP (Li et al., 2022b) and Grounding DINO (Liu et al., 2024b) unify object detection and phrase grounding, while LLMDET (Fu et al., 2025b) further enriches detector representations through region- and image-level language generation. However, their heavy vision-language architectures and multi-layer cross-modal interactions hinder real-time deployment. In contrast, real-time OVD methods favor lightweight region/query-text matching. While efficient, these methods remain focused on vocabulary coverage and matching efficiency, underutilizing the rich semantics conveyed by descriptions. Moreover, under strict efficiency constraints, the limited representation capacity of compact detectors makes it difficult to fully absorb instance semantics and scene context. **Therefore, how to transfer such rich semantics into compact detectors without compromising inference efficiency remains underexplored.**

To address this challenge, we propose **RT-DETR-World**, which transfers the rich semantics conveyed by descriptions during training while retaining only lightweight vision-language matching at inference. Specifically, to obtain strong general-purpose visual representations, we adopt a frozen DINOv3 (Siméoni et al., 2025) as the visual encoder, followed by a lightweight multi-scale projector and a DETR decoder that produces object queries. A compact MiniLM (Wang et al., 2021) encodes category names and category-oriented textual prompts, whose embeddings are directly matched with object queries for open-vocabulary classification, avoiding the additional inference overhead of costly multi-layer cross-modal interaction. We further construct **GroundingCapv2** upon GroundingCap-1M (Fu et al., 2025b) with three levels of supervision: (i) *category names* for standard OVD; (ii) *object descriptions* conveying instance attributes, actions, poses, and states; and (iii) *image descriptions* conveying object relations, scene context, and global semantics. These descriptions serve only as training-time semantic supervision, while the deployed detector retains the standard category-oriented OVD interface.

To help the compact detector absorb these multi-level semantics, we propose **Dual-Path Description Alignment (DDA)**, which combines a deployment-consistent MiniLM pathway with a training-only LLM teacher. The MiniLM pathway uses category names for standard query-category supervision and aligns object descriptions with Hungarian-matched queries to inject fine-grained instance semantics. Since lightweight alignment alone may be insufficient for a capacity-limited detector, the caption-contrastively tuned LLM text encoder from LLM2CLIP (Huang et al., 2026) provides stronger offline semantic targets: object- and image-description features supervise matched queries and global visual representations, respectively. These features are precomputed, so the LLM is absent during training and inference, and all auxiliary alignment modules are removed after training. Moreover, different descriptions may share attributes, actions, states, or context, yet standard contrastive learning treats all unmatched pairs as equally strong negatives. We therefore propose **Relation-Aware Negative Relaxation (RNR)**, which uses teacher-derived semantic similarities to reduce the repulsion of related negatives while preserving exact positives. RNR is applied to the MiniLM object-description alignment and the teacher-based object- and image-level alignments.

Our contributions are threefold: (1) We propose **RT-DETR-World**, a compact OVD framework that leverages rich semantic supervision from descriptions while retaining lightweight inference, and construct **GroundingCapv2** with explicit category-, object-, and image-level supervision. (2) We introduce **DDA**, which combines a deployment-consistent MiniLM pathway with a training-only LLM teacher to help the compact detector better absorb these rich semantics without additional




Figure 2: **Confidence-routed GroundingAgent-Opt.** Qwen3-VL-8B agents curate GroundingCap-1M category and object annotations, routing uncertain cases to Qwen3-VL-32B. Together with inherited image descriptions, curated annotations form GroundingCapv2’s tri-level supervision.

inference cost. (3) We propose **RNR**, which uses teacher-derived semantic similarities to relax related negatives while preserving exact positives. *See Appendix A for related work.*

2 GROUNDINGCAPV2

2.1 TRI-LEVEL DATA FORMULATION

GroundingCap-1M (Fu et al., 2025b) aggregates localized phrases and detailed image descriptions from heterogeneous sources. Detection datasets mainly provide category labels, while grounding and image-text sources provide phrases or tags that may mix category identity, instance details, and context. We reorganize GroundingCap-1M into GroundingCapv2 with three explicit levels: category names define the standard OVD interface, while object and image descriptions convey instance- and scene-level semantics during training. Formally, the b -th sample is represented as $S_b = (I_b, B_b, \mathcal{T}_b^{\text{cat}}, \mathcal{T}_b^{\text{obj}}, t_b^{\text{img}})$, where I_b and B_b denote the image and its annotated regions. The category annotations $\mathcal{T}_b^{\text{cat}} = \{(i, c_{bi}) \mid i \in \mathcal{J}_b^{\text{cat}}\}$ associate region i with a concise category name c_{bi} , while the object annotations $\mathcal{T}_b^{\text{obj}} = \{(i, d_{bi}) \mid i \in \mathcal{J}_b^{\text{obj}}\}$ associate it with a description d_{bi} conveying attributes, parts, quantities, actions, poses, and states. The image description t_b^{img} captures object relations, scene context, and global semantics. Here, $\mathcal{J}_b^{\text{cat}}$ and $\mathcal{J}_b^{\text{obj}}$ index regions with valid category and object-description annotations, respectively. Since they may differ, each region receives only the reliable supervision available from its source.

Table 1 summarizes the five sources and their region-level coverage. Cat. and Obj. denote valid category and object-description annotations, with Obj. coverage for detection-origin sources including category-name fallback. For COCO (Lin et al., 2014) and V3Det (Wang et al., 2023a), source categories are preserved and instance-specific descriptions are generated, while unreliable descriptions fall back to category names. For GQA (Hudson & Manning, 2019), Flickr30K Entities (Plummer et al., 2015), and LLaVA-Cap (Liu et al., 2023), original grounded phrases provide object-level supervision, and category names are added only when supported by concrete visual concepts. Inherited image descriptions provide image-level supervision. Overall, GroundingCapv2 contains 1,115,690 samples and 8,050,813 regions, with category and object-description coverage of 95.8% and 98.5%, respectively; 1,115,656 samples also contain image descriptions.

Table 1: Statistics of GroundingCapv2 after standardization.

Source	Samples	Regions	Coverage (%)	
			Cat.	Obj.
COCO	205,815	1,234,235	100.0	100.0
V3Det	166,106	683,814	100.0	100.0
GQA	358,181	3,972,578	93.2	97.1
Flickr30K Ent.	79,035	531,791	93.9	99.7
LLaVA-Cap	306,553	1,628,395	97.6	99.9
GroundingCapv2	1,115,690	8,050,813	95.8	98.5

2.2 CONFIDENCE-ROUTED DATA CURATION

Generating descriptions at scale and normalizing categories may introduce incorrect visual details, category assignments, or region identities. To mitigate these errors, **GroundingAgent-Opt** employs role-specialized Qwen3-VL-8B agents for proposal and verification, while routing ambiguous cases to Qwen3-VL-32B for multimodal adjudication, as illustrated in Fig. 2. This confidence-routed workflow prioritizes annotation precision while limiting large-model use. (i) **Detection-**




Figure 3: **Overview of RT-DETR-World.** A frozen DINOv3 visual encoder, lightweight multi-scale projector, DETR decoder, and compact MiniLM form the deployable detector. DDA combines a deployment-consistent MiniLM pathway with training-only object- and image-level LLM supervision. RNR uses LLM-derived description similarities to relax semantically related negatives across the three description-alignment objectives. All teacher-side components are removed at inference.

origin annotations. For COCO and V3Det, a Qwen3-VL-8B proposer generates a concise instance description from the image, annotated region, and immutable source category. An independent Qwen3-VL-8B verifier checks region identity, category consistency, and unsupported visual details. Confident and consistent descriptions are accepted, ambiguous cases are routed to Qwen3-VL-32B, and unresolved descriptions fall back to the source category. **(ii) Region–phrase annotations.** For GQA, Flickr30K Entities, and LLaVA-Cap, the original region phrases are retained. A text-only Qwen3-VL-8B proposer extracts and normalizes a candidate category, and an independent verifier determines whether the phrase supports a concrete visual concept. Consistent, high-confidence candidates are accepted, while ambiguous or conflicting cases are adjudicated by Qwen3-VL-32B using the image, region, and phrase. If no reliable category is identified, the category field remains empty and the original phrase continues to provide object-description supervision.

Quality control. COCO and V3Det source categories remain fixed. GroundingAgent-Opt accepts generated descriptions for 85.5% and 87.6% of their regions, respectively, with the remainder using category-name fallback. All original phrases from GQA, Flickr30K Entities, and LLaVA-Cap are retained. We rebuild the category- and object-description-to-region mappings, verify region indices, token spans, and reconstructed text, and retain confidence and routing metadata solely for auditing.

3 RT-DETR-WORLD

3.1 OVERALL ARCHITECTURE

As shown in Fig. 3, RT-DETR-World comprises a compact deployable detector and training-only alignment branches supervised by precomputed features from an offline LLM teacher. Given an image, a frozen DINOv3 (Siméoni et al., 2025) extracts visual features, which are adapted into multi-scale detection features by a lightweight projector. MiniLM (Wang et al., 2021) encodes category names and category-oriented textual prompts. Vision–text similarities guide Language-Guided Query Selection and open-vocabulary classification, while the DETR decoder refines the selected queries and regresses bounding boxes. During training, **Dual-Path Description Alignment (DDA)** complements standard query–category supervision with the rich semantics conveyed by object and image descriptions. Its deployment-consistent MiniLM pathway aligns object descriptions with Hungarian-matched queries, while the teacher pathway aligns matched queries and global visual representations with precomputed LLM2CLIP embeddings of object and image descriptions, respectively. **Relation-Aware Negative Relaxation (RNR)** uses teacher-derived semantic similarities to reduce the repulsion of related negatives across the three alignment objectives while preserving

exact positives. The LLM itself is absent during detector training and inference, and all auxiliary alignment modules are removed after training. The deployed detector retains only the lightweight, category-oriented MiniLM interface.

3.2 DUAL-PATH DESCRIPTION ALIGNMENT (DDA)

The rich semantics conveyed by object and image descriptions provide dense supervision, yet a compact real-time detector may struggle to absorb them through a single lightweight query–text pathway. We therefore propose **Dual-Path Description Alignment (DDA)**, which combines a deployment-consistent MiniLM pathway with a training-only teacher pathway based on precomputed LLM features. The teacher pathway provides expressive semantic targets, while the MiniLM pathway transfers fine-grained instance semantics into the representations retained at inference. All auxiliary alignment modules are removed after training, adding no inference overhead.

Offline LLM semantic targets. Following the notation in Sec. 2, let b index a sample and i an annotated region in $\mathcal{B}_b$. DDA encodes the semantics conveyed by descriptions using the caption-contrastively tuned LLM text encoder from LLM2CLIP (Huang et al., 2026). For each $i \in \mathcal{J}_b^{\text{obj}}$, the object description is encoded as $\mathbf{e}_{bi}^{\text{obj}} = E_L(d_{bi})$, while each available image description yields $\mathbf{e}_b^{\text{img}} = E_L(t_b^{\text{img}})$. Here, E_L denotes the frozen LLM text encoder, and $\mathbf{e}_{bi}^{\text{obj}}, \mathbf{e}_b^{\text{img}} \in \mathbb{R}^{d_L}$ are the corresponding embeddings in the d_L -dimensional teacher space. They serve as semantic alignment targets and relation references for RNR. All teacher embeddings are precomputed; thus, the LLM is never loaded during detector training or inference.

Deployment-consistent MiniLM pathway. Let $\mathbf{q}_{b, \pi_b(i)} \in \mathbb{R}^{d_q}$ denote the final-layer object query assigned by Hungarian matching to region i in sample b , where π_b is the assignment function and d_q is the query dimension. For each $i \in \mathcal{J}_b^{\text{cat}}$, MiniLM encodes the category name c_{bi} for the standard query–category classification objective. For each $i \in \mathcal{J}_b^{\text{obj}}$, we pool the valid non-special-token features of d_{bi} and project the text and query representations into a shared alignment space:

$$\mathbf{m}_{bi} = P_m^t(\text{Pool}(E_m(d_{bi}))), \quad \mathbf{v}_{bi}^m = P_m^v(\mathbf{q}_{b, \pi_b(i)}), \quad (1)$$

where $E_m(d_{bi}) \in \mathbb{R}^{n_{bi} \times d_m}$ denotes the MiniLM token-feature sequence, with sequence length n_{bi} and hidden dimension d_m . Pool averages the valid non-special-token features. The learnable projections $P_m^t : \mathbb{R}^{d_m} \rightarrow \mathbb{R}^{d_a}$ and $P_m^v : \mathbb{R}^{d_q} \rightarrow \mathbb{R}^{d_a}$ map the text and query features into a shared d_a -dimensional space. This alignment enriches the MiniLM and object-query representations retained at inference with fine-grained instance semantics. Object descriptions and both projection heads are used only during training.

Training-only teacher alignment. The teacher pathway aligns object- and image-level visual representations with the precomputed semantic targets. For each $i \in \mathcal{J}_b^{\text{obj}}$, the Hungarian-matched query is projected into the teacher space. At the image level, valid spatial features from each projected feature level are pooled, concatenated, and mapped into the same space:

$$\mathbf{v}_{bi}^{\text{tch}} = P_o(\mathbf{q}_{b, \pi_b(i)}), \quad \mathbf{g}_b = P_g \left(\parallel_{\ell=1}^L \text{MAP}(\mathbf{F}_b^\ell) \right), \quad (2)$$

where $P_o : \mathbb{R}^{d_q} \rightarrow \mathbb{R}^{d_L}$ maps the matched query into the teacher space, yielding $\mathbf{v}_{bi}^{\text{tch}}$. $\mathbf{F}_b^\ell \in \mathbb{R}^{H_\ell \times W_\ell \times d_\ell}$ denotes the projected visual feature at level ℓ , and L is the number of feature levels. MAP performs mask-aware average pooling over valid spatial positions, while $\parallel$ denotes concatenation across feature levels. Finally, $P_g : \mathbb{R}^{\sum_{\ell=1}^L d_\ell} \rightarrow \mathbb{R}^{d_L}$ maps the concatenated feature into the teacher space, yielding the global visual representation $\mathbf{g}_b$. We align $\mathbf{v}_{bi}^{\text{tch}}$ with $\mathbf{e}_{bi}^{\text{obj}}$ and $\mathbf{g}_b$ with $\mathbf{e}_b^{\text{img}}$ to transfer instance semantics and global scene semantics, respectively. Both teacher-alignment projection heads are discarded after training.

3.3 RELATION-AWARE NEGATIVE RELAXATION (RNR)

The semantics conveyed by descriptions are not mutually exclusive: unmatched samples may share attributes, actions, states, or context, yet standard contrastive learning weights all unmatched cross-modal pairs equally, potentially over-separating related representations. We therefore propose

Relation-Aware Negative Relaxation (RNR), which uses precomputed LLM2CLIP embeddings to estimate semantic relations and selectively reduces the repulsion of related negatives while preserving exact positives. Owing to its stronger modeling of complex descriptions, the semantic similarities derived from the caption-contrastively tuned LLM teacher embeddings provide more reliable estimates of paraphrases, implicit relations, and partial semantic overlap than surface-form similarity or similarities derived from the evolving MiniLM representations. Freezing and precomputing its embeddings further ensures consistent relation estimates without online LLM inference.

For each DDA alignment objective, we collect N triplets $\{(\mathbf{v}_n, \mathbf{t}_n, \mathbf{e}_n)\}_{n=1}^N$, where $\mathbf{v}_n$ and $\mathbf{t}_n$ are paired visual and text representations, and $\mathbf{e}_n$ is the corresponding frozen teacher embedding. The bidirectional logits are

$$z_{nm}^{v2t} = \frac{\text{sim}(\mathbf{v}_n, \mathbf{t}_m)}{\tau}, \quad z_{nm}^{t2v} = \frac{\text{sim}(\mathbf{t}_n, \mathbf{v}_m)}{\tau}, \quad (3)$$

where $\text{sim}(\cdot, \cdot)$ denotes cosine similarity, $\tau > 0$ is the temperature, and $n, m \in \{1, \dots, N\}$ index the paired representations.

The teacher-derived semantic relation and its corresponding pair weight are defined as

$$r_{nm} = [\text{sim}(\mathbf{e}_n, \mathbf{e}_m)]_+, \quad w_{nm} = \begin{cases} 1, & m \in \mathcal{P}_n, \\ 1 - \alpha r_{nm}, & m \notin \mathcal{P}_n, \end{cases} \quad (4)$$

where $[x]_+ = \max(x, 0)$ and $r_{nm} \in [0, 1]$. $\mathcal{P}_n$ denotes the exact positive correspondences of anchor n , typically the singleton $\{n\}$, and $\alpha \in [0, 1]$ controls the maximum relaxation. Exact positives retain unit weight, while related negatives receive weights in $[1 - \alpha, 1]$.

For either direction $s \in \{v2t, t2v\}$, the per-anchor loss is $\ell_n^s = -\log \left[\sum_{m \in \mathcal{P}_n} \exp(z_{nm}^s) / \sum_{m=1}^N w_{nm} \exp(z_{nm}^s) \right]$. The complete bidirectional objective is $\mathcal{C}_{\text{RNR}}(\mathbf{V}, \mathbf{T}; \mathbf{E}) = \frac{1}{2N} \sum_{n=1}^N (\ell_n^{v2t} + \ell_n^{t2v})$, where $\mathbf{V}$, $\mathbf{T}$, and $\mathbf{E}$ stack the visual, text, and teacher representations, respectively.

RNR leaves exact-positive terms unchanged and discounts only the denominator contributions of semantically related negatives. Thus, an unmatched pair is relaxed but never treated as a positive. The same teacher-derived relation weights are used in both directions, and $\alpha = 0$ recovers standard bidirectional contrastive learning.

We apply RNR to the three DDA alignment objectives:

$$\mathcal{L}_{\text{M}}^{\text{obj}} = \mathcal{C}_{\text{RNR}}(\mathbf{V}^{\text{m}}, \mathbf{M}; \mathbf{E}^{\text{obj}}), \quad \mathcal{L}_{\text{L}}^{\text{obj}} = \mathcal{C}_{\text{RNR}}(\mathbf{V}^{\text{tch}}, \mathbf{E}^{\text{obj}}; \mathbf{E}^{\text{obj}}), \quad \mathcal{L}_{\text{L}}^{\text{img}} = \mathcal{C}_{\text{RNR}}(\mathbf{G}, \mathbf{E}^{\text{img}}; \mathbf{E}^{\text{img}}), \quad (5)$$

where $\mathbf{V}^{\text{m}}$, $\mathbf{M}$, $\mathbf{V}^{\text{tch}}$, and $\mathbf{E}^{\text{obj}}$ stack the valid object-level representations over all (b, i) with $i \in \mathcal{J}_b^{\text{obj}}$, while $\mathbf{G}$ and $\mathbf{E}^{\text{img}}$ stack image-level representations for samples with valid image descriptions. In the MiniLM objective, $\mathbf{E}^{\text{obj}}$ determines only the relation weights; in the teacher objectives, the LLM embeddings serve as both alignment targets and relation references.

3.4 TRAINING OBJECTIVE AND IMPLEMENTATION DETAILS

Training objective. The base detection objective $\mathcal{L}_{\text{det}}$ includes Hungarian-matched query-category classification and box regression losses. Combining it with three DDA objectives gives

$$\mathcal{L} = \mathcal{L}_{\text{det}} + \lambda_{\text{M}} \mathcal{L}_{\text{M}}^{\text{obj}} + \lambda_{\text{o}} \mathcal{L}_{\text{L}}^{\text{obj}} + \lambda_{\text{g}} \mathcal{L}_{\text{L}}^{\text{img}}, \quad (6)$$

where λ_{M} , λ_{o} , and λ_{g} weight the MiniLM object, LLM object, and LLM image objectives, respectively. RNR introduces no additional loss term and only reweights negative contributions within these description-alignment objectives. At inference, offline teacher targets and training-only alignment modules are discarded, while the deployable MiniLM query-text pathway remains unchanged.

Implementation details. RT-DETR-World-S, -S+, and -B use frozen DINOv3 ViT-S/16, ViT-S+/16, and ViT-B/16 backbones (Siméoni et al., 2025), respectively. Each variant employs a two-layer multi-scale projector with 256-dimensional features and a three-layer DETR decoder. We use 13 groups of 300 object queries during training and retain one 300-query group at inference. MiniLMv2-L6-H768 (Wang et al., 2021) has a maximum input length of 256 tokens, while the

Table 2: Zero-shot detection on LVIS minival, reported as standard AP / Fixed AP.

Method	Backbone	Text Encoder	Training Data	FPS	AP/AP ^{Fixed}	AP _r /AP _r ^{Fixed}	AP _c /AP _c ^{Fixed}	AP _f /AP _f ^{Fixed}	Parameters (M)		
									Visual/Det.	Text	Total
GLIP-T	Swin-T	BERT-base	OG	–	– / 24.9	– / 17.7	– / 19.5	– / 31.0	≈122	≈110	232
GLIP-T	Swin-T	BERT-base	OG, Cap4M	–	– / 26.0	– / 20.8	– / 21.4	– / 31.0	≈122	≈110	232
GLIPv2-T	Swin-T	BERT-base	OG, Cap4M	–	– / 29.0	– / –	– / –	– / –	≈122	≈110	232
Grounding DINO-T	Swin-T	BERT-base	OG	–	– / 25.6	– / 14.4	– / 19.6	– / 32.2	≈62	≈110	172
Grounding DINO-T	Swin-T	BERT-base	OG, Cap4M	–	– / 27.4	– / 18.1	– / 23.3	– / 32.7	≈62	≈110	172
MM-Grounding-DINO-T	Swin-T	BERT-base	O365, GoldG, GRIT, V3Det	–	– / 41.4	– / 34.2	– / 37.4	– / 46.2	64.1	108.9	173.0
LLMDet-T	Swin-T	BERT-base	GroundingCap-1M	–	– / 44.7	– / 37.3	– / 39.5	– / 50.7	64.1	108.9	173.0
Grounding DINO 1.5 Edge	EfficientViT-L1	–	G-20M	–	– / 33.5	– / 28.0	– / 34.3	– / 33.9	–	–	–
YOLO-Worldv2.1-S	YOLOv8-S	CLIP-B/32	OG	18*	– / 25.5	– / 19.1	– / 22.6	– / 29.3	13	63.4 [†]	76.4
YOLO-Worldv2.1-M	YOLOv8-M	CLIP-B/32	OG	17*	– / 32.7	– / 24.4	– / 30.2	– / 36.4	29	63.4 [†]	92.4
YOLO-Worldv2.1-L	YOLOv8-L	CLIP-B/32	OG	16*	– / 35.5	– / 24.4	– / 34.0	– / 38.8	48	63.4 [†]	111.4
YOLOE8-S	YOLOv8-S	MobileCLIP-B(LT)	OG	18*	25.7 / 27.9	19.0 / 22.3	25.9 / 27.8	26.7 / 29.0	12	63.4 [†]	75.4
YOLOE8-M	YOLOv8-M	MobileCLIP-B(LT)	OG	17*	29.9 / 32.6	23.6 / 26.9	29.2 / 31.9	31.7 / 34.4	27	63.4 [†]	90.4
YOLOE8-L	YOLOv8-L	MobileCLIP-B(LT)	OG	17*	33.3 / 35.9	30.8 / 33.2	32.2 / 34.8	34.6 / 37.3	45	63.4 [†]	108.4
YOLOE11-S	YOLOv11-S	MobileCLIP-B(LT)	OG	18*	25.2 / 27.5	19.3 / 21.4	24.4 / 26.8	26.7 / 29.3	10	63.4 [†]	73.4
YOLOE11-M	YOLOv11-M	MobileCLIP-B(LT)	OG	18*	30.5 / 33.0	22.4 / 26.9	30.4 / 32.5	32.1 / 34.5	21	63.4 [†]	84.4
YOLOE11-L	YOLOv11-L	MobileCLIP-B(LT)	OG	17*	32.4 / 35.2	25.6 / 29.1	31.9 / 35.0	34.1 / 36.5	26	63.4 [†]	89.4
OV-DEIM-S	ViT-T	MobileCLIP-B(LT)	OG	161	27.7 / 29.6	23.6 / 25.2	28.1 / 30.2	28.0 / 30.0	11	63.4 [†]	74.4
OV-DEIM-M	ViT-T+	MobileCLIP-B(LT)	OG	109	30.6 / 32.6	25.3 / 26.9	30.2 / 31.5	31.9 / 34.1	20	63.4 [†]	83.4
OV-DEIM-L	ViT-S	MobileCLIP-B(LT)	OG	91	33.7 / 35.9	34.3 / 36.8	33.4 / 35.5	34.0 / 36.0	36	63.4 [†]	99.4
RT-DETR-World-S (Ours)	DINOv3-S/16	MiniLMv2-L6-H768	GroundingCapv2	63	31.4 / 35.2	28.2 / 32.0	30.4 / 33.8	32.9 / 36.9	36.5	66.6	103.1
RT-DETR-World-S+ (Ours)	DINOv3-S+/16	MiniLMv2-L6-H768	GroundingCapv2	58	32.6 / 36.6	26.6 / 31.1	31.9 / 35.8	34.3 / 38.2	43.6	66.6	110.2
RT-DETR-World-B (Ours)	DINOv3-B/16	MiniLMv2-L6-H768	GroundingCapv2	32	36.6 / 40.0	33.7 / 37.1	36.4 / 39.6	37.4 / 40.9	120.6	66.6	187.2

Notes: “–” denotes an unreported result. OG denotes Objects365 and GoldG, O365 denotes Objects365, and G-20M denotes Grounding-20M. Visual/Det. denotes deployable detector parameters excluding the text encoder, while Total includes both. For GLIP, GLIPv2, and the original Grounding DINO, the Visual/Det.–text decomposition is estimated from reported model sizes and encoder specifications. The text encoder and complete parameter breakdown of Grounding DINO 1.5 Edge are not publicly reported. [†] The text encoder is used to construct or cache vocabulary embeddings and is excluded from the detector parameters reported by the original method; we report it separately and include it in Total. Training-only language modules, including the LLM branch of LLMDet and our LLM2CLIP teacher, are excluded. FPS follows the OV-DEIM protocol with category embeddings cached before timing. * FPS includes NMS post-processing overhead.

LLM2CLIP teacher provides precomputed 1,152-dimensional object- and image-description embeddings. We set $(\lambda_M, \lambda_o, \lambda_g) = (0.25, 0.1, 0.1)$ in Eq. (6), $\tau = 0.07$ in Eq. (3), and $\alpha = 0.25$ in Eq. (4). The three description-alignment losses are linearly warmed up over the first 2,000 iterations.

All variants are trained for 150k iterations on four NVIDIA RTX 4090 GPUs with 12 images per GPU, yielding a batch size of 48. During training, the shorter image side is randomly resized within [480, 800] pixels, with the longer side capped at 1,333 pixels. At evaluation, the shorter side is resized to 800 pixels with the same cap. We use AdamW with a learning rate of 3×10^{-4} and weight decay of 10^{-4} ; MiniLMv2 uses a learning-rate multiplier of 0.1. The learning rate is warmed up for 1k iterations and multiplied by 0.1 at 120k and 140k iterations.

4 EXPERIMENTAL RESULTS

4.1 SETUP

Evaluation protocol and metrics. All RT-DETR-World variants are trained on GroundingCapv2 described in Sec. 2 and evaluated without target-specific fine-tuning. For LVIS v1.0 minival (Gupta et al., 2019), we use the official names of all 1,203 categories as category queries without training on LVIS annotations. We report standard AP and Fixed AP (Dave et al., 2021), together with their rare-, common-, and frequent-category counterparts. These groups contain 337, 461, and 405 categories, respectively. Standard AP uses the default limit of 300 detections per image, whereas Fixed AP replaces this image-level limit with a fixed per-category detection budget. Following prior OVD implementations, we retain the top 1,000 predictions over all query–category pairs for Fixed AP evaluation. Unless otherwise specified, the remaining benchmarks report standard AP. For efficiency evaluation, we follow OV-DEIM (Wang et al., 2026). FPS is measured on a T4 GPU using TensorRT, with category embeddings cached and NMS included where applicable.

Comparison methods. We compare RT-DETR-World with two groups of open-vocabulary detectors. The first comprises general-purpose OVD and grounding models, including GLIP (Li et al., 2022b), GLIPv2 (Zhang et al., 2022), Grounding DINO (Liu et al., 2024b), MM-Grounding-DINO (Zhao et al., 2024b), and LLMDet (Fu et al., 2025b). The second comprises real-time OVD models, including Grounding DINO 1.5 Edge (Ren et al., 2024), YOLO-World (Cheng et al., 2024), YOLOE (Wang et al., 2025), and OV-DEIM (Wang et al., 2026). Unless otherwise stated, baseline results are taken from the corresponding papers or official repositories.

4.2 TRANSFER AND ROBUSTNESS EVALUATION

We evaluate zero-shot transfer on LVIS minival (Gupta et al., 2019) and ODinW13/35 (Li et al., 2022a), and distribution-shift robustness on COCO-O (Mao et al., 2023), using COCO (Lin et al., 2014) as the in-distribution reference. Together, these benchmarks assess large-vocabulary detection, cross-domain transfer, and robustness to natural distribution shifts. To prevent evaluation leakage, we exclude from GroundingCapv2 any images overlapping the target evaluation splits. Since GroundingCapv2 contains COCO training images and COCO-O shares the COCO category space, COCO-O is treated as a distribution-shift benchmark rather than unseen-category evaluation. At inference, the LLM teacher and all training-only alignment modules are removed, leaving only the deployable RT-DETR-World detector.

Large-vocabulary detection on LVIS. LVIS contains 1,203 categories with a long-tailed distribution over rare, common, and frequent classes. As shown in Table 2, RT-DETR-World-S, -S+, and -B achieve standard/Fixed AP scores of 31.4/35.2, 32.6/36.6, and 36.6/40.0, respectively. Among the compared real-time detectors, RT-DETR-World-S+ reaches 36.6 Fixed AP and 58 FPS, exceeding the previous best Fixed AP of 35.9 by 0.7 points. RT-DETR-World-B further improves Fixed AP to 40.0 and achieves 32 FPS outperforming the strongest prior real-time result by 4.1 points. It also obtains 37.1, 39.6, and 40.9 Fixed AP on rare, common, and frequent categories, respectively. OV-DEIM-L remains a strong compact operating point, achieving 35.9 Fixed AP at 91 FPS; RT-DETR-World-S+ and -B trade additional latency for higher accuracy. Compared with general-purpose cross-modal models, RT-DETR-World-B remains 1.4 and 4.7 Fixed AP below MM-Grounding-DINO-T and LLMDet-T, respectively, delineating the remaining accuracy gap under our streamlined inference architecture.

Cross-domain transfer on ODinW. ODinW comprises 35 detection datasets spanning diverse domains and vocabularies. Following prior work, we report mean AP over the commonly used 13-dataset subset (ODinW13) and the complete ODinW35 benchmark. As shown in Table 3, RT-DETR-World performs consistently well across all three model scales. RT-DETR-World-S achieves 40.1 and 18.7 AP, outperforming YOLO-Worldv2.1-L by 4.5 and 2.1 points and the strongest YOLOE variant by 8.2 and 3.9 points on ODinW13 and ODinW35, respectively. Despite using the smallest backbone in our family, it approaches OV-DEIM-L, which obtains 41.6 and 19.2 AP. Scaling to RT-DETR-World-B raises performance to 43.8 AP on ODinW13 and 20.2 AP on ODinW35, surpassing OV-DEIM-L by 2.2 and 1.0 points, respectively. These results demonstrate that RT-DETR-World transfers effectively across datasets with substantially different domains, visual appearances, and category vocabularies.

Table 3: Zero-shot cross-domain transfer on ODinW.

Method	Backbone	ODinW13	ODinW35
YOLO-Worldv2.1-S	YOLOv8-S	15.3	7.8
YOLO-Worldv2.1-M	YOLOv8-M	21.4	10.5
YOLO-Worldv2.1-L	YOLOv8-L	35.6	16.6
YOLOEv8-S	YOLOv8-S	28.0	12.7
YOLOEv8-M	YOLOv8-M	30.9	14.3
YOLOEv8-L	YOLOv8-L	31.9	14.8
YOLOEv11-S	YOLOv11-S	28.2	12.7
YOLOEv11-M	YOLOv11-M	30.5	14.2
YOLOEv11-L	YOLOv11-L	31.4	14.4
OV-DEIM-S	ViT-T	32.9	14.8
OV-DEIM-M	ViT-T+	36.6	16.2
OV-DEIM-L	ViT-S	41.6	19.2
RT-DETR-World-S	DINOv3-S/16	40.1	18.7
RT-DETR-World-S+	DINOv3-S+/16	41.5	18.8
RT-DETR-World-B	DINOv3-B/16	43.8	20.2

Distribution-shift robustness on COCO-O. COCO-O retains the 80 COCO categories but evaluates them across six naturally shifted domains: sketch, weather, cartoon, painting, tattoo, and handmade. Because GroundingCapv2 includes COCO training images, we use COCO-O to evaluate distribution-shift robustness rather than unseen-category recognition. Following prior work, effective robustness is computed as $ER = AP_{COCO-O} - 0.45 AP_{COCO}$.

As shown in Table 4, RT-DETR-World exhibits strong robustness across model scales. RT-DETR-World-S obtains 34.9 AP on COCO-O, exceeding YOLO-Worldv2.1-L by 7.6 points despite having a 3.0-point lower in-distribution

Table 4: COCO-O distribution-shift robustness. ‡ indicates the use of COCO training images.

Method	Backbone	COCO AP	COCO-O AP	ER
YOLO-Worldv2.1-S	YOLOv8-S	38.2	11.9	-5.3
YOLO-Worldv2.1-M	YOLOv8-M	43.8	16.7	-3.0
YOLO-Worldv2.1-L	YOLOv8-L	46.0	27.3	+6.6
YOLOEv8-S	YOLOv8-S	35.6	15.4	-0.6
YOLOEv8-M	YOLOv8-M	42.2	17.7	-1.3
YOLOEv8-L	YOLOv8-L	45.4	19.8	-0.6
YOLOEv11-S	YOLOv11-S	37.0	16.0	-0.7
YOLOEv11-M	YOLOv11-M	43.1	17.8	-1.6
YOLOEv11-L	YOLOv11-L	45.1	18.8	-1.5
OV-DEIM-S	ViT-T	40.8	24.4	+6.0
OV-DEIM-M	ViT-T+	43.3	29.6	+10.2
OV-DEIM-L	ViT-S	45.9	43.3	+22.7
RT-DETR-World-S [‡]	DINOv3-S/16	43.0	34.9	+15.6
RT-DETR-World-S+ [‡]	DINOv3-S+/16	45.0	39.4	+19.2
RT-DETR-World-B [‡]	DINOv3-B/16	47.2	46.2	+24.9

Table 5: Ablation of training supervision on LVIS minival.

ID	Training Data	LLM Teacher		Deployable MiniLM Path			LVIS Minival			
		Image	Object	Category	Object Desc.	Source C/P	AP	AP _r	AP _c	AP _f
B0	GroundingCap-1M	–	–	–	–	✓	27.9	18.3	24.8	32.4
B1	GroundingCap-1M	✓	✓	–	–	✓	32.9	23.6	30.2	36.9
C0	GroundingCapv2	✓	✓	✓	–	–	33.1	25.7	32.2	35.1
C1	GroundingCapv2	–	–	✓	✓	–	32.2	22.9	30.3	35.6
C2	GroundingCapv2	✓	–	✓	✓	–	33.1	27.8	32.6	34.4
C3	GroundingCapv2	–	✓	✓	✓	–	33.6	29.1	32.5	35.3
C4	GroundingCapv2	✓	✓	✓	✓	–	35.2	32.0	33.8	36.9

Notes: GroundingCap-1M denotes LLMDet’s annotations, while GroundingCapv2 denotes our tri-level annotations. Image and Object denote LLM-teacher alignment with image and object descriptions, respectively. Category and Object Desc. denote MiniLM supervision from category names and object descriptions. Source C/P denotes source-specific category or region-phrase supervision. The LLM teacher and auxiliary alignment modules are removed at inference.

COCO AP. It also surpasses the strongest YOLOE-L result by 15.1 points. RT-DETR-World-S+ further improves COCO-O AP to 39.4 and effective robustness to +19.2. RT-DETR-World-B achieves the strongest overall results, with 47.2 AP on COCO, 46.2 AP on COCO-O, and +24.9 effective robustness. Compared with OV-DEIM-L, it improves COCO-O AP by 2.9 points and effective robustness by 2.2 points. These results show that RT-DETR-World retains strong detection performance under substantial appearance shifts rather than relying solely on in-distribution accuracy.

4.3 ABLATION STUDIES

Unless otherwise specified, all ablations use RT-DETR-World-S with a frozen DINOv3-S/16 backbone and identical training settings; AP denotes Fixed AP throughout.

Supervision ablation. Table 5 analyzes the contributions of the two DDA pathways under different annotation formulations. On GroundingCap-1M annotations, adding object- and image-level LLM-teacher supervision improves AP from 27.9 (B0) to 32.9 (B1), a gain of 5.0 points without changing the deployable detector. Under GroundingCapv2, adding MiniLM object-description alignment to the category-only configuration improves AP from 33.1 (C0) to 35.2 (C4), with a large AP_r gain from 25.7 to 32.0. Starting from the MiniLM-only configuration C1, image- and object-level teacher alignment individually improve AP from 32.2 to 33.1 (C2) and 33.6 (C3), respectively. Combining both levels raises AP to 35.2 (C4). The complementary gains from image- and object-level targets demonstrate the benefit of transferring both global context and instance semantics, while the strong rare-category improvement supports the use of multi-level semantic supervision.

Comparison of auxiliary alignment strategies. Table 6 compares RNR with alternative strategies for auxiliary semantic supervision. The LLMDet-style caption-generation objective (Fu et al., 2025b) performs poorly under the same compact detector setting, whereas hard contrastive alignment provides a stronger baseline at 33.6 AP. SoftCLIP-style soft alignment (Gao et al., 2024) and SRCL-style similarity regulation (Jiang et al., 2023) yield modest improvements, reaching 33.8 and 33.9 AP, respectively. Unlike SoftCLIP, which replaces exact correspondence targets with soft targets derived from intra-modal similarity, and SRCL, which relies on progressively refined cross-modal similarity, RNR preserves exact-positive targets and only discounts related negatives using frozen LLM-teacher relations. This design separates semantic relatedness from instance correspondence, avoiding ambiguous positive targets while providing stable relation estimates. Consequently, RNR achieves 35.2 AP, outperforming hard contrastive alignment and SRCL-style regulation by 1.6 and 1.3 points, respectively. The improvement is most pronounced for rare categories, where RNR raises AP_r by 4.4 points over hard alignment. *See Appendices B and C for hyperparameter sensitivity and qualitative results, respectively.*

Table 6: Auxiliary alignment strategies on LVIS minival.

Auxiliary Supervision	AP	AP _r	AP _c	AP _f
LLMDet-style Caption Generation	28.5	18.3	26.4	32.2
Hard Contrastive Alignment	33.6	27.6	31.7	36.4
SoftCLIP-style Soft Alignment	33.8	25.1	32.6	36.5
SRCL-style Similarity Reweighting	33.9	26.2	32.2	36.8
RNR (Ours)	35.2	32.0	33.8	36.9

Note: SoftCLIP and SRCL are adapted to the same auxiliary-alignment setting.

5 CONCLUSION

We present **RT-DETR-World**, a compact open-vocabulary detector that learns the rich semantics conveyed by descriptions during training while retaining lightweight query–text matching at infer-

ence. **GroundingCapv2** provides category-, object-, and image-level supervision. **DDA** transfers fine-grained instance semantics and scene context through a deployable MiniLM pathway and offline LLM-teacher targets, while **RNR** relaxes semantically related negatives. All teacher-side components are removed after training, adding no inference overhead. Extensive experiments demonstrate competitive large-vocabulary detection, strong cross-domain transfer, and distribution-shift robustness with real-time inference. These results indicate that rich training-time language supervision can enhance compact open-vocabulary detectors without increasing inference cost.

AI USE STATEMENT

In this work, we used generative AI tools for dataset construction and translation. Specifically, Qwen3-VL was used in our GroundingAgent-Opt pipeline to generate and curate annotations for GroundingCapv2, including instance descriptions and category annotations. The models, agent roles, routing strategy, and data-curation procedure are described in detail in the paper. Generative AI tools were also used to assist with English translation of author-written content.

We did not use generative AI tools to develop the proposed methodology, formulate theoretical or mathematical claims, write proofs, design experiments, implement the method, or interpret experimental results. The remaining required disclosure tasks are not applicable to this work.

Additionally, generative AI tools were used for language polishing and readability improvement of author-written text. All AI-assisted writing was reviewed and revised by the authors, and AI-generated annotations were processed and verified through the curation and quality-control procedures described in the paper. We take responsibility for the final content of this work, including text, claims, and artifacts produced with the aid of generative AI.

ETHICS STATEMENT

This work does not involve the collection of new human-subject data or personally identifiable information. All experiments are conducted on publicly available object detection, grounding, and image-text datasets or their processed derivatives. GroundingCapv2 is constructed by reorganizing and augmenting existing data with model-generated annotations, followed by the curation and quality-control procedures described in the paper. We do not intend the proposed method or dataset construction pipeline for applications that violate privacy, safety, or applicable data-use policies.

REPRODUCIBILITY STATEMENT

We provide detailed descriptions of the model architecture, training settings, evaluation protocols, data construction procedure, and ablation configurations in the paper. The construction and standardization of GroundingCapv2 are also described in the main text. To facilitate reproducibility, we will make the code and processed dataset annotations publicly available.

REFERENCES

- Alex Andonian, Shixing Chen, and Raffay Hamid. Robust cross-modal representation learning with progressive self-distillation. In *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 16409–16420. IEEE, 2022.
- Ankan Bansal, Karan Sikka, Gaurav Sharma, Rama Chellappa, and Ajay Divakaran. Zero-shot object detection. In *European conference on computer vision*, pp. 397–414. Springer, 2018.
- Tianheng Cheng, Lin Song, Yixiao Ge, Wenyu Liu, Xinggang Wang, and Ying Shan. Yolo-world: Real-time open-vocabulary object detection. In *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 16901–16911. IEEE, 2024.
- Achal Dave, Piotr Dollár, Deva Ramanan, Alexander Kirillov, and Ross Girshick. Evaluating large-vocabulary object detectors: The devil is in the details. *arXiv preprint arXiv:2102.01066*, 2021.
- Shenghao Fu, Junkai Yan, Qize Yang, Xihan Wei, Xiaohua Xie, and Wei-Shi Zheng. A hierarchical semantic distillation framework for open-vocabulary object detection. *IEEE Transactions on Multimedia*, 2025a.

- Shenghao Fu, Qize Yang, Qijie Mo, Junkai Yan, Xihan Wei, Jingke Meng, Xiaohua Xie, and Wei-Shi Zheng. Llm-det: Learning strong open-vocabulary object detectors under the supervision of large language models. In *2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 14987–14997. IEEE, 2025b.
- Yuting Gao, Jinfeng Liu, Zihan Xu, Tong Wu, Enwei Zhang, Ke Li, Jie Yang, Wei Liu, and Xing Sun. Softclip: Softer cross-modal alignment makes clip stronger. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pp. 1860–1868, 2024.
- Shashank Goel, Hritik Bansal, Sumit Bhatia, Ryan Rossi, Vishwa Vinay, and Aditya Grover. Cyclip: Cyclic contrastive language-image pretraining. *Advances in Neural Information Processing Systems*, 35:6704–6719, 2022.
- Xiuye Gu, Tsung-Yi Lin, Weicheng Kuo, and Yin Cui. Open-vocabulary object detection via vision and language knowledge distillation. *arXiv preprint arXiv:2104.13921*, 2021.
- Agrim Gupta, Piotr Dollar, and Ross Girshick. Lvis: A dataset for large vocabulary instance segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 5356–5364, 2019.
- Weiquan Huang, Aoqi Wu, Yifan Yang, Xufang Luo, Yuqing Yang, Usman Naseem, Chunyu Wang, Qi Dai, Xiyang Dai, Dongdong Chen, et al. Llm2clip: Powerful language model unlocks richer cross-modality representation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pp. 5131–5139, 2026.
- Drew A Hudson and Christopher D Manning. Gqa: A new dataset for real-world visual reasoning and compositional question answering. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 6693–6702. IEEE, 2019.
- Chaoya Jiang, Wei Ye, Haiyang Xu, Songfang Huang, Fei Huang, and Shikun Zhang. Vision language pre-training by contrastive learning with cross-modal similarity regulation. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 14660–14679, 2023.
- Chenyi Jiang, Shidong Wang, Yang Long, Zechao Li, Haofeng Zhang, and Ling Shao. Imaginary-connected embedding in complex space for unseen attribute-object discrimination. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 47(3):1395–1413, 2024.
- Jooyeon Kim, Eulrang Cho, Sehyung Kim, and Hyunwoo J Kim. Retrieval-augmented open-vocabulary object detection. In *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 17427–17436. IEEE, 2024.
- Weicheng Kuo, Yin Cui, Xiuye Gu, AJ Piergiovanni, and Anelia Angelova. F-vlm: Open-vocabulary object detection upon frozen vision and language models. *arXiv preprint arXiv:2209.15639*, 2022.
- Chunyu Li, Haotian Liu, Liunian Li, Pengchuan Zhang, Jyoti Aneja, Jianwei Yang, Ping Jin, Houdong Hu, Zicheng Liu, Yong Jae Lee, et al. Elevator: A benchmark and toolkit for evaluating language-augmented visual models. *Advances in Neural Information Processing Systems*, 35: 9287–9301, 2022a.
- Liangqi Li, Jiaxu Miao, Dahu Shi, Wenming Tan, Ye Ren, Yi Yang, and Shiliang Pu. Distilling detr with visual-linguistic knowledge for open-vocabulary object detection. In *2023 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 6478–6487. IEEE, 2023.
- Liunian Harold Li, Pengchuan Zhang, Haotian Zhang, Jianwei Yang, Chunyu Li, Yiwu Zhong, Lijuan Wang, Lu Yuan, Lei Zhang, Jenq-Neng Hwang, et al. Grounded language-image pre-training. In *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 10955–10965. IEEE, 2022b.
- Yanshu Li, Bohan Hu, Zhengdao Li, Linshan Li, Weiming Liu, Ruizhi Qian, Guangxin Wu, Hao Zhang, Jifeng Shen, Piotr Koniusz, et al. Deco-detr: Decoupled cognition detr for efficient open-vocabulary object detection. In *International Conference on Learning Representations*, volume 2026, pp. 124043–124063, 2026.

- Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, pp. 740–755. Springer, 2014.
- Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *Advances in neural information processing systems*, 36:34892–34916, 2023.
- Lihao Liu, Juexiao Feng, Hui Chen, Ao Wang, Lin Song, Jungong Han, and Guiguang Ding. Yolo-unio: Efficient universal open-world object detection. *arXiv preprint arXiv:2412.20645*, 2024a.
- Shilong Liu, Zhaoyang Zeng, Tianhe Ren, Feng Li, Hao Zhang, Jie Yang, Qing Jiang, Chunyuan Li, Jianwei Yang, Hang Su, et al. Grounding dino: Marrying dino with grounded pre-training for open-set object detection. In *European conference on computer vision*, pp. 38–55. Springer, 2024b.
- Xiaofeng Mao, Yuefeng Chen, Yao Zhu, Da Chen, Hang Su, Rong Zhang, and Hui Xue. Coco-o: A benchmark for object detectors under natural distribution shifts. In *2023 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 6316–6327. IEEE, 2023.
- Bryan A Plummer, Liwei Wang, Chris M Cervantes, Juan C Caicedo, Julia Hockenmaier, and Svetlana Lazebnik. Flickr30k entities: Collecting region-to-phrase correspondences for richer image-to-sentence models. In *Proceedings of the IEEE international conference on computer vision*, pp. 2641–2649, 2015.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pp. 8748–8763, 2021.
- Tianhe Ren, Qing Jiang, Shilong Liu, Zhaoyang Zeng, Wenlong Liu, Han Gao, Hongjie Huang, Zhengyu Ma, Xiaohe Jiang, Yihao Chen, et al. Grounding dino 1.5: Advance the “edge” of open-set object detection. *arXiv preprint arXiv:2405.10300*, 2024.
- Oriane Siméoni, Huy V Vo, Maximilian Seitzer, Federico Baldassarre, Maxime Oquab, Cijo Jose, Vasil Khalidov, Marc Szafraniec, Seungeun Yi, Michaël Ramamonjisoa, et al. Dinov3. *arXiv preprint arXiv:2508.10104*, 2025.
- Ao Wang, Lihao Liu, Hui Chen, Zijia Lin, Jungong Han, and Guiguang Ding. Yoloe: Real-time seeing anythi. In *2025 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 24591–24602. IEEE, 2025.
- Jiaqi Wang, Pan Zhang, Tao Chu, Yuhang Cao, Yujie Zhou, Tong Wu, Bin Wang, Conghui He, and Dahua Lin. V3det: Vast vocabulary visual detection dataset. In *2023 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 19787–19797. IEEE, 2023a.
- Leilei Wang, Longfei Liu, Xi Shen, Xuanlong Yu, Ying Tiffany He, Fei Richard Yu, and Yingyi Chen. Ov-deim: Real-time detr-style open-vocabulary object detection with gridsynthetic augmentation. *arXiv preprint arXiv:2603.07022*, 2026.
- Luting Wang, Yi Liu, Penghui Du, Zihan Ding, Yue Liao, Qiaosong Qi, Biaolong Chen, and Si Liu. Object-aware distillation pyramid for open-vocabulary object detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 11186–11196, 2023b.
- Wenhui Wang, Hangbo Bao, Shaohan Huang, Li Dong, and Furu Wei. Minilmv2: Multi-head self-attention relation distillation for compressing pretrained transformers. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pp. 2140–2151, 2021.
- Size Wu, Wenwei Zhang, Sheng Jin, Wentao Liu, and Chen Change Loy. Aligning bag of regions for open-vocabulary object detection. In *2023 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 15254–15264. IEEE, 2023.
- Alireza Zareian, Kevin Dela Rosa, Derek Hao Hu, and Shih-Fu Chang. Open-vocabulary object detection using captions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14393–14402, 2021.

- Haotian Zhang, Pengchuan Zhang, Xiaowei Hu, Yen-Chun Chen, Liunian Li, Xiyang Dai, Lijuan Wang, Lu Yuan, Jenq-Neng Hwang, and Jianfeng Gao. Glipv2: Unifying localization and vision-language understanding. *Advances in neural information processing systems*, 35:36067–36080, 2022.
- Tian Zhang, Kongming Liang, Ruoyi Du, Wei Chen, and Zhanyu Ma. Disentangling before composing: Learning invariant disentangled features for compositional zero-shot learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 47(2):1132–1147, 2024.
- Yupeng Zhang, Ruize Han, Zhiwei Chen, Wei Feng, and Liang Wan. Noovd: Novel category discovery and embedding for open-vocabulary object detection. *arXiv preprint arXiv:2603.21069*, 2026.
- Shiyu Zhao, Samuel Schuster, Long Zhao, Zhixing Zhang, Yumin Suh, Manmohan Chandraker, Dimitris N Metaxas, et al. Taming self-training for open-vocabulary object detection. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 13938–13947, 2024a.
- Xiangyu Zhao, Yicheng Chen, Shilin Xu, Xiangtai Li, Xinjiang Wang, Yining Li, and Haian Huang. An open and comprehensive pipeline for unified object grounding and detection. *arXiv preprint arXiv:2401.02361*, 2024b.
- Xingyi Zhou, Rohit Girdhar, Armand Joulin, Philipp Krähenbühl, and Ishan Misra. Detecting twenty-thousand classes using image-level supervision. In *European Conference on Computer Vision*, pp. 350–368, 2022.

APPENDIX

A RELATED WORK

Zero-shot detection (ZSD) and open-vocabulary detection (OVD). Early ZSD (Bansal et al., 2018) transfers semantic knowledge from seen to predefined unseen categories through visual-semantic embeddings, while OVR-CNN (Zareian et al., 2021) extends this paradigm to OVD via image-caption pretraining. With large-scale VLMs such as CLIP (Radford et al., 2021), later methods mainly explore knowledge transfer and weak supervision. ViLD (Gu et al., 2021), OADP (Wang et al., 2023b), and DK-DETR (Li et al., 2023) distill region-level or relational knowledge; F-VLM (Kuo et al., 2022) and NoOVD (Zhang et al., 2026) adapt pretrained VLM representations to detection; while Detic (Zhou et al., 2022) and SAS-Det (Zhao et al., 2024a) expand the training vocabulary through image-level supervision or pseudo-labels. Grounded pretraining provides another effective paradigm. GLIP (Li et al., 2022b), Grounding DINO (Liu et al., 2024b), and MM-Grounding-DINO (Zhao et al., 2024b) unify detection and phrase grounding, while LLMdet (Fu et al., 2025b) further introduces image- and region-level caption supervision. Efficient OVD is explored by Grounding DINO 1.5-Edge (Ren et al., 2024) for edge deployment, YOLO-World (Cheng et al., 2024) and YOLOE (Wang et al., 2025) via efficient or re-parameterizable vision-language alignment, YOLO-UniOW (Liu et al., 2024a) via adaptive text decision learning, and OV-DEIM (Wang et al., 2026) with an efficient end-to-end DETR design. In contrast, RT-DETR-World uses object- and image-level descriptions only during training, preserves semantic relations through RNR, and removes all teacher-side components at inference.

Multi-granular description supervision and relational alignment. Conventional image-text contrastive learning treats all unmatched pairs as negatives, ignoring their many-to-many semantic relations. CLIP-PSD (Andonian et al., 2022) and SoftCLIP (Gao et al., 2024) introduce soft targets via self-distillation or intra-modal similarities, CyCLIP (Goel et al., 2022) regularizes cross-modal geometry, and SRCL (Jiang et al., 2023) reweights negatives by semantic similarity. These methods mainly target general vision-language pretraining and derive relational supervision from model predictions or external visual-language signals rather than sample-specific descriptions.

In OVD, DK-DETR (Li et al., 2023) distills region semantics and relations, RALF (Kim et al., 2024) exploits retrieved negatives and LLM-generated concepts, and HD-OVD (Fu et al., 2025a) transfers CLIP knowledge across instance, category, and image levels. BARON (Wu et al., 2023) aligns related region groups, while DeCo-DETR (Li et al., 2026) organizes LLaVA-generated region descriptions into hierarchical prototypes. In contrast, we use sample-specific object and image descriptions encoded by a frozen LLM2CLIP (Huang et al., 2026) teacher to supervise matched queries and global visual representations. Their semantic similarities relax related negatives while preserving exact positives. All teacher features are precomputed, leaving inference unchanged.

B HYPERPARAMETER SENSITIVITY

We vary the LLM-teacher weight, RNR relaxation coefficient, and MiniLM description weight individually while fixing the remaining hyperparameters to their default values. All experiments use RT-DETR-World-S and report Fixed AP on LVIS minival.

Table 7: Hyperparameter sensitivity on LVIS minival. All results are reported using Fixed AP.

(a) LLM teacher weight λ_{aux}						(b) RNR coefficient α						(c) MiniLM description weight λ_{desc}					
λ_{aux}	AP	AP _r	AP _c	AP _f		α	AP	AP _r	AP _c	AP _f		λ_{desc}	AP	AP _r	AP _c	AP _f	
0	32.2	22.9	30.3	35.6		0	33.6	27.6	31.7	36.4		0	33.1	25.7	32.2	35.1	
0.05	31.6	23.8	29.3	35.0		0.1	34.3	30.6	33.4	35.4		0.1	33.9	28.0	33.1	35.6	
0.1	35.2	32.0	33.8	36.9		0.25	35.2	32.0	33.8	36.9		0.25	35.2	32.0	33.8	36.9	
0.2	34.3	32.5	33.0	35.8		0.5	33.4	29.4	32.0	35.4		0.5	34.3	30.2	34.1	35.1	
												0.75	33.3	29.2	32.3	34.8	
												1.0	33.3	29.7	33.3	34.0	

Notes: $\lambda_{\text{aux}} = \lambda_o = \lambda_g$ and $\lambda_{\text{desc}} = \lambda_M$. Unless varied, the default values are $\lambda_{\text{aux}} = 0.1$, $\alpha = 0.25$, and $\lambda_{\text{desc}} = 0.25$.

As shown in Table 7, $\lambda_{\text{aux}} = 0.1$ achieves the highest overall AP of 35.2. Increasing it to 0.2 further improves AP_r to 32.5 but reduces overall AP to 34.3.



Figure 4: **Qualitative zero-shot detections on LVIS minival.** Using the full 1,203-category vocabulary, RT-DETR-World localizes diverse objects across indoor, outdoor, and cluttered scenes, including small and fine-grained instances. Labels and numbers indicate predicted categories and confidence scores, respectively.

For RNR, increasing α from 0 to 0.25 improves AP from 33.6 to 35.2 and AP_r from 27.6 to 32.0, whereas excessive relaxation at $\alpha = 0.5$ degrades performance. Similarly, increasing the MiniLM description weight from 0 to 0.25 improves AP from 33.1 to 35.2 and AP_r from 25.7 to 32.0. Although $\lambda_{desc} = 0.5$ yields the highest AP_c of 34.1, larger weights reduce overall AP to 33.3 at both 0.75 and 1.0. We therefore use $\lambda_{aux} = 0.1$, $\alpha = 0.25$, and $\lambda_{desc} = 0.25$ by default.

C VISUALIZATION AND ANALYSIS

Qualitative results. Fig. 4 presents zero-shot detections produced by RT-DETR-World-B using all 1,203 LVIS category names as queries. The model recognizes objects across diverse environments, ranging from indoor living spaces and dining scenes to crowded streets and natural settings. It successfully localizes not only salient objects such as persons, furniture, and animals, but also small or fine-grained instances such as wall sockets, water faucets, bottle caps, wristbands, radiators, and computer peripherals. The results also show consistent localization of multiple instances in crowded scenes, as illustrated by the birds, persons, cups, and tabletop objects. These examples qualitatively support the model’s ability to associate category concepts with visual cues at different scales and levels of granularity. Some low-confidence and overlapping predictions remain in densely populated scenes, indicating that fine-grained category discrimination and confidence calibration remain challenging under a large vocabulary.