

WILDHANDBENCH: A Benchmark for Handwritten Text Understanding that Challenges MLLMs and Humans

Jun Zhang, Qiao Zhao, Cheng Cui, Jianying Qu, Zhongkai Sun, Jianwen Yang, Changda Zhou, ZhuoXin Liu, Shubin Han

Baidu Inc.

Abstract

While the top model on OmniDocBench now reaches 96.34% overall on printed-document parsing, the ability of current models to handle challenging handwritten documents remains largely uncharacterized. Existing benchmarks focus on isolated text or formulas, overlook handwritten tables and real-world degradation, and report aggregate accuracy without explaining why models fail.

We present **WILDHANDBENCH**, a benchmark containing 500 handwritten documents across three structures (free text, tables, formulas), four languages, and nine real-world scenarios. We introduce a **Prior-Driven Error (PDE)** metric that quantifies whether errors originate from language priors rather than visual evidence. Evaluating 18 state-of-the-art models together with calibrated human baselines, we find: (1) the best model achieves only **71.85%** overall; (2) humans outperform all models yet the gap is narrow (77.09% vs. 71.85%); and (3) model errors are qualitatively different from human errors—63–91% of model errors are prior-driven versus only 49% for humans, exposing systematic reliance on language priors that conventional accuracy metrics cannot capture.

Introduction

Recent advances in multimodal large language models (MLLMs) have dramatically improved document understanding (Fu et al. 2025; Ouyang et al. 2025). The top model on the OmniDocBench leaderboard now reaches 96.34% overall (Ouyang et al. 2025), approaching saturation on printed-document parsing. These remarkable results have gradually created a widespread perception that OCR is becoming a largely solved problem.

We argue that this conclusion is premature.

Nearly all evidence supporting this perception comes from printed documents with relatively regular layouts and clear visual appearances (Mathew, Karatzas, and Jawahar 2021; Zhong, ShafieiBavani, and Jimeno Yepes 2020; Zheng et al. 2021; Göbel et al. 2013). Handwritten documents tell a different story. Medical records, handwritten forms, classroom notes, historical archives, and personal correspondence remain substantially more difficult for today’s MLLMs despite their impressive performance on printed documents. Unlike printed OCR, handwritten document understanding requires models to jointly resolve ambiguous handwriting, recover irregular document structures, distinguish visual ev-

idence from language priors, and reason under genuine uncertainty (Guan et al. 2024; Bai et al. 2024). Consequently, handwriting is not simply a more difficult OCR problem, but a distinct document understanding challenge.

Surprisingly, current evaluation benchmarks provide limited insight into why handwritten document understanding remains unsolved. Existing handwritten benchmarks primarily evaluate isolated free-text recognition, while handwritten tables, naturally written formulas, and real-world document degradation remain largely unexplored. More fundamentally, existing evaluations focus almost exclusively on recognition accuracy (Fu et al. 2025; Ouyang et al. 2025). They measure *how often* models fail, but provide little understanding of *why* they fail—in particular, whether errors originate from poor visual perception or from excessive reliance on language priors.

To address this gap, we introduce **WILDHANDBENCH**, a benchmark for handwritten document understanding. **WILDHANDBENCH** contains 500 handwritten documents spanning three document structures (free text, tables, and formulas), four language settings, and nine representative real-world scenarios. We also introduce a **Prior-Driven Error (PDE)** metric that characterizes whether model errors arise from language priors instead of visual evidence, enabling systematic analysis of hallucination-like recognition behaviors.

Using **WILDHANDBENCH**, we conduct a comprehensive evaluation of 18 state-of-the-art MLLMs and OCR-oriented vision-language models under a unified evaluation protocol together with calibrated human baselines. Our study yields three key findings. First, handwritten document understanding remains far from solved: the strongest model achieves only 71.85% overall. Second, humans outperform all models (77.09% vs. 71.85%), yet the gap is narrow—top models even surpass humans on text transcription under format-matching metrics. Third, model errors are qualitatively different from human errors: humans remain conservative on illegible content, whereas models confidently hallucinate fluent but unsupported text, with 63–91% of model errors classified as prior-driven compared to only 49% for humans. This exposes systematic reliance on language priors that conventional accuracy metrics cannot capture.

Our contributions are summarized as follows:

- We propose **WILDHANDBENCH**, to our knowledge the first benchmark that jointly evaluates handwritten free text, ta-

bles, and formulas across multiple languages and diverse real-world scenarios, addressing key gaps in existing evaluation coverage.

- We introduce the Prior-Driven Error (PDE) metric, which quantifies whether model errors originate from language priors rather than visual evidence, enabling systematic analysis of hallucination-like recognition behaviors beyond conventional accuracy metrics.
- We conduct a comprehensive evaluation of 18 state-of-the-art MLLMs and OCR-oriented vision-language models together with calibrated human baselines, revealing the persistent handwriting gap, the narrow yet meaningful distance to human performance, and the systematic reliance of MLLMs on language priors.

Related Work

Handwritten document understanding. Handwritten document analysis has been studied for decades, yet existing benchmarks remain highly task-specific and fragmented. Most datasets focus on line-level handwritten text recognition, including IAM (Marti and Bunke 2002), RIMES (Grosicki et al. 2009), CASIA-HWDB (Liu et al. 2011), SCUT-EPT (Zhu et al. 2019), and SCUT-HCCDoc (Zhang, Liang, and Jin 2020), covering Latin and Chinese handwriting under relatively controlled settings. Scientific handwriting has been investigated through datasets such as NoTeS-Bank (Pal et al. 2025), while handwritten mathematical expression recognition is primarily benchmarked by CROHME (Mahdavi et al. 2019) and MathWriting (Gervais, Fadeeva, and Maksai 2024). In contrast, table understanding benchmarks, including PubTabNet (Zhong, ShafieiBavani, and Jimeno Yepes 2020), FinTabNet (Zheng et al. 2021), and the ICDAR table competitions (Göbel et al. 2013), are exclusively constructed from printed documents. Although these datasets have significantly advanced individual OCR tasks, they evaluate text, formulas, and tables independently and provide limited coverage of challenging handwritten documents with real-world degradation. Consequently, current handwritten benchmarks remain insufficient for evaluating handwritten documents as a unified document understanding problem.

Benchmarking document understanding. The rapid development of multimodal large language models (MLLMs) has shifted document evaluation from isolated OCR tasks toward holistic document understanding. Benchmarks such as OmniDocBench (Ouyang et al. 2025) evaluate diverse document parsing capabilities under a unified framework, while Real5-OmniDocBench (Zhou et al. 2026) further investigates robustness under real-world physical degradations through fine-grained factor-level evaluation. OCRBench (Liu et al. 2024) and OCRBench v2 (Fu et al. 2025) extend benchmark coverage to OCR-oriented multimodal capabilities, including text recognition, formula parsing, table understanding, and document visual question answering. These benchmarks demonstrate remarkable progress on printed documents, with the top model now reaching 96.34% overall on OmniDocBench (Ouyang et al. 2025). Nevertheless, these evaluations primarily report aggregate recognition accuracy,

providing limited understanding of why handwritten documents remain substantially more challenging than printed documents.

Prior-driven errors in vision-language models. Recent studies have shown that multimodal large language models (MLLMs) frequently generate outputs that are not fully grounded in visual evidence (Guan et al. 2024; Bai et al. 2024). In OCR-related tasks, such hallucinations often manifest as fluent yet visually unsupported transcriptions, where language priors override ambiguous visual observations. To better characterize this phenomenon, Seong *et al.* (Seong et al. 2026) proposed PINK, which penalizes over-correction in handwritten mathematical expression recognition. Similarly, HunyuanOCR-1.5 (Li et al. 2026) introduces CHAOS-Bench, which evaluates whether models faithfully preserve visually observed but semantically implausible text under synthetic character perturbations in printed documents. These studies consistently demonstrate that prior-driven recognition errors are systematic rather than incidental.

However, existing evaluations remain restricted to either handwritten mathematical expressions or synthetically perturbed printed documents. To the best of our knowledge, no existing benchmark systematically measures prior-driven errors on naturally occurring handwritten documents spanning free text, tables, and formulas. Our proposed Prior-Driven Error (PDE) metric is designed to bridge this gap by quantifying the extent to which model errors are attributable to language priors instead of visual evidence in realistic handwritten document understanding.

Table 1 summarizes representative benchmarks. Compared with previous datasets, WILDHANDBENCH is, to our knowledge, the first to unify handwritten free text, tables, and formulas within a single evaluation framework with calibrated human baselines and Prior-Driven Error analysis.

WILDHANDBENCH: Benchmark Design

WILDHANDBENCH jointly evaluates handwritten free text, tables, and formulas under realistic handwritten document scenarios. The benchmark contains 500 handwritten document images spanning three document structures, four language settings, and nine representative real-world scenarios. Figure 1 illustrates the overall construction pipeline.

Benchmark Taxonomy

To comprehensively characterize handwritten document understanding, every sample is organized along three dimensions.

- **Language (4).** WILDHANDBENCH covers four language settings, including Simplified Chinese (333, 66.6%), English (143, 28.6%), Traditional Chinese (13, 2.6%), and Chinese-English mixed documents (11, 2.2%).
- **Document Structure (3).** The benchmark jointly evaluates three representative handwritten document structures: free text (367, 73.4%), tables (81, 16.2%), and formulas (52 images containing 278 individually annotated formula regions, 10.4%).

Benchmark	Lang.	Handwritten	Free Text	Table	Formula	Real Degrad.	Human Baseline
IAM	EN	✓	✓	–	–	–	–
CASIA-HWDB	ZH	✓	✓	–	–	–	–
SCUT-EPT / HCCDoc	ZH	✓	✓	–	–	Partial	–
CROHME / MathWriting	Symbol	✓	–	–	✓	–	–
PubTabNet / FinTabNet	EN	–	–	✓	–	–	–
ICDAR Table	EN	–	–	✓	–	–	–
OCRBench (v1/v2)	Multi	Partial	✓	✓	✓	Partial	–
OmniDocBench	ZH/EN	Partial	✓	✓	✓	Partial	–
Real5-OmniDocBench	ZH/EN	Partial	✓	✓	✓	✓	–
WILDHANDBENCH (Ours)	ZH/EN	✓	✓	✓	✓	✓	✓

Table 1: Comparison with representative benchmarks. WILDHANDBENCH is, to our knowledge, the first to jointly cover handwritten free text, tables, and formulas with real-scenario degradation and calibrated human baselines.

- **Real-world Scenario (9).** Samples are collected from nine representative scenarios, including literary writing, letters and notes, medical records, business and government documents, education, mathematical and scientific materials, classical calligraphy, daily miscellany, and historical archives.

Benchmark Construction

To maximize both dataset diversity and annotation reliability, handwritten documents are collected from two complementary sources.

Offline handwritten manuscripts. Participants voluntarily contribute authentic handwritten materials covering multiple real-world domains. Since writers have direct access to the original content, reliable ground-truth transcriptions can be obtained from the source documents.

Internet collection. Additional handwritten documents are collected from publicly available online resources where community discussions or decipherment references provide useful contextual information for annotation.

After collection, all samples undergo automatic content-similarity scanning to remove duplicates, followed by manual inspection of ambiguous cases.

Benchmark construction then proceeds in three stages.

Stage 1: MLLM-assisted pre-annotation. Three state-of-the-art MLLMs independently transcribe every handwritten document. These predictions are not used as ground truth, but serve as reference suggestions for human annotators, helping identify ambiguous regions and improving annotation efficiency.

Stage 2: Human annotation. A primary annotator produces the recognition ground truth for every sample, represented using Markdown for free text, $\LaTeX$ for formulas, and HTML `<table>` for handwritten tables. Additionally, each sample is annotated with difficulty ratings along six dimensions (visual degradation, cursiveness, linguistic ambiguity, structural complexity, domain knowledge, and multilingual mixing) to support future fine-grained analysis.

During annotation, annotators consult all available evidence, including MLLM predictions, writer-provided transcripts, community discussions, and domain experts whenever necessary. Characters that remain impossible to identify

after exhaustive verification are masked in the original image and excluded from evaluation.

Stage 3: Independent verification. Every annotation is independently reviewed by a second annotator who performs the verification without access to the primary annotator’s reasoning. Disagreements are resolved through discussion until consensus is reached. Only samples passing independent verification are included in the final benchmark. This multi-stage quality-control protocol—automatic deduplication, MLLM-assisted annotation, independent double review, and consensus-based adjudication—substantially reduces annotation inconsistency while ensuring reliable ground truth for subsequent evaluation.

Evaluation Protocol

Our evaluation protocol consists of three components. First, structure-specific recognition metrics measure transcription quality across free text, formulas, and tables. Second, the proposed **Prior-Driven Error (PDE)** metric quantifies whether recognition failures originate from language priors rather than visual evidence. Third, calibrated human baselines provide a reference point for characterizing how human and machine errors differ qualitatively.

Recognition Evaluation

Following OmniDocBench (Ouyang et al. 2025), different handwritten document structures are evaluated using structure-specific metrics.

- **Free text.** Character-level recognition quality is measured using normalized Edit Distance (Edit↓) (Levenshtein 1966).
- **Formulas.** Formula recognition is evaluated using CDM (Character Detection Metric, CDM↑), which renders both prediction and ground truth before matching character bounding boxes (Wang et al. 2025).
- **Tables.** Table understanding is evaluated using TEDS (Tree Edit Distance Similarity, TEDS↑), which jointly measures structural correctness and textual fidelity based on HTML representations (Zhong, ShafieiBavani, and Jimeno Yepes 2020).




Figure 1: Overview of the WILDHANDBENCH construction pipeline.

To facilitate comparison across different document structures, we report an overall score following OmniDocBench (Ouyang et al. 2025):

$$\text{Overall} = \frac{(1 - \text{Edit}) \times 100 + \text{CDM} + \text{TEDS}}{3}.$$

Prior-Driven Error

Recognition accuracy alone cannot distinguish different types of recognition failures. Two models may achieve identical recognition accuracy while exhibiting very different behaviors: one may fail because it cannot correctly perceive handwritten content, whereas the other may generate visually unsupported yet linguistically plausible transcriptions due to excessive reliance on language priors. Since these two failure modes require different modeling improvements, WILDHANDBENCH explicitly quantifies prior-driven recognition errors through the proposed **Prior-Driven Error (PDE)** metric.

For every prediction, model output is aligned with the corresponding ground truth using character-level alignment for free text and formulas, and cell-level alignment for tables. Only segments where prediction differs from the ground truth are considered. Each mismatched segment is then scored using an external reference language model (Qwen3-8B-Base (Qwen Team 2025)). If the model-generated segment has lower perplexity than the corresponding ground-truth segment, the error is regarded as *prior-driven*, indicating that the model replaces visually correct but less common

content with a linguistically more probable alternative. Inserted content that has no corresponding ground truth is always regarded as prior-driven since it is generated solely from internal language priors.

Formally, for a sample s , the Prior-Driven Error rate is computed as

$$\text{PDE}(s) = \frac{\sum_i \mathbb{I}[\text{ppl}(m_i) < \text{ppl}(g_i)] |m_i|}{\sum_i |m_i|},$$

where m_i and g_i denote the model prediction and the corresponding ground-truth segment, respectively. For inserted content, $\text{ppl}(g_i) = \infty$. The summation is performed only over mismatched segments. Consequently, PDE measures the proportion of model errors attributable to language priors rather than visual perception, instead of reflecting overall recognition accuracy. The overall PDE score reported for each model is the arithmetic mean of the per-category PDE rates (text, table, formula).

Human Baselines

WILDHANDBENCH additionally establishes calibrated human baselines under the same evaluation protocol. Human participants receive exactly the same handwritten document images as the evaluated models and independently produce recognition outputs using the same target formats. Performance is evaluated using the identical metrics described above.

To ensure a fair comparison, human participants perform single-pass recognition without access to any auxiliary resources. In particular, they are not allowed to consult MLLM

predictions, writer-provided transcripts, community discussions, or domain experts. This setting differs intentionally from the benchmark construction process, where multiple evidence sources are integrated to establish reliable ground truth through consensus-based annotation.

Under this protocol, human participants achieve an overall score of 77.09%, which is higher than the best MLLM (Gemini 3.1 Pro, 71.85%). Detailed per-category comparisons are presented in the Experiments section.

Experiments

Evaluated Models

We evaluate 18 models grouped into three categories: proprietary VLMs (Claude Opus 4.8 (Anthropic 2026), Gemini 3.1 Pro (Google DeepMind 2026a), Gemini 3.5 Flash (Google DeepMind 2026b)), open-source general VLMs (InternVL3.5 (OpenGVLab 2025), Qwen3-VL (Bai et al. 2025), Qwen3.5-Plus (Alibaba Cloud 2026), Kimi-K3 (Kimi Team 2026)), and open-source OCR-focused VLMs (DeepSeek-OCR-V2 (Wei, Sun, and Li 2026), MinerU2.5 (Niu et al. 2025), MinerU2.5-Pro (Wang et al. 2026), Unlimited-OCR (Yin et al. 2026), Dots.ocr (Li et al. 2025), Dots.mocr (Zheng et al. 2026), HunyuanOCR (Hunyuan Vision Team et al. 2025), Qianfan-OCR (Dong et al. 2026), FireRed-OCR (Wu et al. 2026), GLM-OCR (Duan et al. 2026), PaddleOCR-VL-1.6 (Zhang et al. 2026)).

All models are evaluated with an identical post-processing pipeline. General VLMs use the standard OmniDocBench prompt template (Ouyang et al. 2025), while OCR-focused models use their respective recommended prompt settings or APIs.

Models are selected to represent the current state of the art in document understanding, with reference to the OmniDocBench leaderboard (Ouyang et al. 2025).

Main Results

Table 2 presents the main results. The most striking finding is the performance degradation from printed to handwritten documents: models that exceed 90% on OmniDocBench (Ouyang et al. 2025) drop to 71.85% at best on WILDHANDBENCH, confirming a persistent “handwritten gap.” Furthermore, OCR-focused models—which routinely outperform general VLMs on printed-document benchmarks—fall behind general VLMs on wild handwriting. The top six models on WILDHANDBENCH are all general-purpose, suggesting that larger model capacity and more diverse training data enable stronger generalization to the high variability of handwritten content, while OCR-focused models are specialized for the regularity of printed layouts.

Tables remain the most challenging category: even the best TEDS score (60.44) indicates nearly 40% structural and content mismatch, and table scores show the smallest cross-model variance among functional models. Text recognition shows the widest spread, reflecting large differences in character-level fidelity. Gemini 3.1 Pro leads in all three categories and overall, though Kimi-K3 is competitive on text edit distance (26.07 vs. 24.32) and Gemini 3.5 Flash on formula CDM (78.22 vs. 79.42).

Human vs. Model Analysis

The human baseline achieves an overall score of 77.09%—*higher* than the best MLLM (Gemini 3.1 Pro, 71.85%) by 5.24 absolute points. While this confirms that human performance remains the upper bound, the relatively modest gap indicates that wild handwriting challenges humans and models alike.

The per-category breakdown reveals where models still lag behind humans and where they have caught up. On text, the best model actually surpasses humans (Edit: 30.08 vs. 24.32), indicating that MLLMs produce more format-compliant transcriptions even though humans may achieve superior character-level recognition. On tables (TEDS: 74.78 vs. 60.44), humans substantially outperform all models by over 14 absolute points, reflecting superior structural understanding of irregular handwritten tables. On formulas (CDM: 86.56 vs. 79.42), humans also lead, though the gap is smaller (7.14 points), indicating that formula recognition in current MLLMs is relatively mature.

Crucially, human errors are qualitatively different from model errors. The PDE analysis shows that human PDE is 49.27%, substantially lower than all evaluated models (minimum 63.28%), indicating that human errors are more evenly split between visual misrecognition and prior-driven substitution. Models, in contrast, produce disproportionately prior-driven errors—generating fluent but visually unsupported output where humans tend toward conservative partial transcriptions. This qualitative gap in failure modes persists despite the narrowing quantitative gap in overall accuracy.

Error Pattern Analysis

Table 2 also reports the prior-driven error rate decomposed by content structure; Figure 2 provides qualitative examples of table parsing errors across model types and the human baseline. Among models with functional visual encoders, PDE rates range from 63% to 79% without a simple correlation to accuracy. Notably, general VLMs with strong language capabilities show relatively high rates (Gemini 3.5 Flash: 79.21%, Qwen3.5-Plus: 77.82%, Gemini 3.1 Pro: 77.51%), while the lowest PDE rates belong to certain compact OCR-focused models (GLM-OCR: 63.28%, PaddleOCR-VL-1.6: 64.48%).

This reveals a nuanced relationship between model capability and error type. At the extreme, models with severely limited visual decoding produce almost exclusively prior-driven errors. Among better-performing models, powerful language priors act as a double-edged sword: they boost accuracy by correctly inferring ambiguous characters, but when errors do occur, those errors are disproportionately prior-driven—the model’s strong language capability causes it to confidently generate plausible alternatives rather than fail silently. Conversely, the models with the lowest PDE rates (GLM-OCR, PaddleOCR-VL) are compact models that produce a larger proportion of visual misrecognition errors (e.g., confusing similar-looking characters) rather than generating fluent but unsupported text.

The per-structure breakdown reveals that formula errors are almost entirely prior-driven across all models (87–98%),




Figure 2: Qualitative comparison of handwritten table parsing across general-purpose models, OCR-specialized models, and the human baseline. The right panel illustrates three error types: table structure errors (E1), table content errors (E2), and prior-driven errors (E3).

Type	Model	Params	Performance Evaluation (%)				Prior-Driven Error (%)			
			Text Edit↓	Table TEDS↑	Formula CDM↑	Overall ↑	Text↓	Table↓	Formula↓	Overall↓
Proprietary	Claude Opus 4.8	—	53.30	52.27	74.11	57.70	72.78	59.32	91.66	74.59
	Gemini 3.5 Flash	—	27.10	53.63	<u>78.22</u>	<u>68.25</u>	71.36	71.91	94.36	79.21
	Gemini 3.1 Pro	—	24.32	60.44	79.42	71.85	71.19	66.56	94.77	77.51
Open General	InternVL3.5	241B-A28B	46.80	41.22	64.00	52.80	72.62	66.38	90.03	76.34
	Qwen3-VL	235B-A22B	34.30	51.81	69.06	62.19	70.01	62.18	91.33	74.51
	Qwen3.5-Plus	397B-A17B	34.80	57.68	73.77	65.55	71.74	70.00	91.71	77.82
	Kimi-K3	2.8T-104B	<u>26.07</u>	<u>58.99</u>	70.50	67.81	65.29	60.32	90.21	71.94
Open OCR	DeepSeek-OCR2	3B-A0.5B	91.70	1.77	18.33	9.46	84.06	90.00	98.35	90.80
	MinerU-2.5	1.2B	83.80	41.19	36.56	31.33	73.80	55.21	92.16	73.72
	Unlimited-OCR	3B-A0.5B	64.90	34.41	51.62	40.38	61.67	55.16	<u>89.47</u>	68.77
	Dots.ocr	3B	56.68	34.70	53.17	43.73	70.29	59.75	90.98	73.67
	Dots.mocr	3B	49.54	36.60	62.85	49.97	63.23	59.56	89.73	70.84
	HunyuanOCR	1.0B	38.50	47.02	45.81	51.44	67.13	55.55	92.08	71.59
	MinerU2.5-Pro	1.2B	59.80	53.16	61.79	51.73	61.23	<u>47.46</u>	92.80	67.16
	Qianfan-OCR	4B	50.40	45.22	61.40	52.07	64.07	61.29	94.04	73.13
	FireRed-OCR	2B	49.00	44.30	63.11	52.82	64.70	64.25	93.10	74.02
	GLM-OCR	0.9B	54.20	57.38	59.01	54.06	<u>57.02</u>	41.92	90.89	63.28
	PaddleOCR-VL-1.6	0.9B	41.52	52.41	51.75	54.21	52.59	53.01	87.83	<u>64.48</u>
Human	Human	—	30.08	74.78	86.56	77.09	66.96	34.48	46.36	49.27

Table 2: Recognition performance and prior-driven error for all evaluated models and the human baseline.

likely because LaTeX syntax is inherently low-perplexity—even legitimate format differences satisfy the ppl criterion. Text errors show the widest spread (52–84%), reflecting the greatest variation in model reliance on language priors. Table errors are moderate (42–90%), with weaker models showing higher rates.

We note limitations of this metric: it characterizes error *type*, not error *quantity*—a high prior-driven rate does not mean a model is less reliable, only that its errors are more

systematic. The classification depends on a specific reference language model (Qwen3-8B-Base); a different model may shift boundary cases.

Discussion

The findings of WILDHANDBENCH demonstrate that handwritten document understanding remains unsolved: models exceeding 90% on OmniDocBench (Ouyang et al. 2025) drop to 71.85% at best on WILDHANDBENCH, and this degrada-

tion is non-uniform across document structures. More critically, the PDE analysis reveals that model and human errors are qualitatively different—63–79% of model errors among functional models originate from language priors, compared to 49% for humans. This means that model errors are systematically more dangerous: fluent, confident, and unsupported by visual evidence.

These findings have implications for safety-critical applications such as medical records, financial documents, and legal archives, where prior-driven errors are particularly difficult to detect (Bai et al. 2024). Future models should optimize not only recognition accuracy but also visual grounding and calibrated uncertainty, learning to express uncertainty rather than confidently generating plausible transcriptions when visual evidence is insufficient.

Limitations

Benchmark scale and coverage. Although WILDHAND-BENCH contains carefully curated handwritten documents with high-quality annotations, it currently consists of 500 samples and should not be interpreted as a population-level estimate of handwritten OCR performance. The relatively small formula (52 images) and table (81 images) subsets limit statistical power for distinguishing highly competitive models. Furthermore, the benchmark focuses primarily on Chinese and English handwriting. Future versions will expand both language coverage and dataset scale.

Annotation and human evaluation. Part of the benchmark is collected from publicly available Internet resources, which may introduce source bias despite careful manual screening and deduplication. Certain handwritten scenarios, such as historical calligraphy or severely degraded manuscripts, inherently involve subjective interpretation, making a universally correct transcription difficult to define even under consensus-based annotation. The reported human baseline should therefore be regarded as a calibrated reference rather than an absolute upper bound. Moreover, all participating annotators are native Chinese speakers, which may underestimate achievable human performance on highly cursive or stylistically diverse English handwriting.

PDE metric. The PDE metric depends on an external reference language model (Qwen3-8B-Base (Qwen Team 2025)) for perplexity estimation, and alternative reference models may lead to different classifications for ambiguous boundary cases. Moreover, PDE is designed to characterize error *type* rather than quantity—a higher PDE does not imply lower model reliability, only that a larger proportion of errors originate from language priors rather than visual perception.

Conclusion

We presented WILDHAND-BENCH, a benchmark for handwritten document understanding that jointly evaluates free text, tables, and formulas with a unified protocol combining recognition metrics, human baselines, and Prior-Driven Error analysis. Experiments on 18 models reveal a persistent handwritten gap (best model 71.85% vs. human 77.09%), with model errors qualitatively different from human errors—63–79% prior-driven for models vs. 49% for humans.

References

- Alibaba Cloud. 2026. Qwen3.5-Plus. Model Studio release documentation. Accessed 2026-07-27.
- Anthropic. 2026. Introducing Claude Opus 4.8. Official model release. Accessed 2026-07-27.
- Bai, S.; Cai, Y.; Chen, R.; Chen, K.; Chen, X.; Cheng, Z.; Deng, L.; Ding, W.; Gao, C.; Ge, C.; et al. 2025. Qwen3-VL Technical Report. *arXiv preprint arXiv:2511.21631*.
- Bai, Z.; Wang, P.; Xiao, T.; He, T.; Han, Z.; Zhang, Z.; and Shou, M. Z. 2024. Hallucination of Multimodal Large Language Models: A Survey. *arXiv preprint arXiv:2404.18930*.
- Dong, D.; Zheng, M.; Xu, D.; Luo, C.; Zhuang, B.; Li, Y.; He, R.; Wang, H.; Zhang, W.; Wang, W.; et al. 2026. Qianfan-OCR: A Unified End-to-End Model for Document Intelligence. *arXiv preprint arXiv:2603.13398*.
- Duan, S.; Xue, Y.; Wang, W.; Su, Z.; Liu, H.; Yang, S.; Gan, G.; Wang, G.; Wang, Z.; Yan, S.; et al. 2026. GLM-OCR Technical Report. *arXiv preprint arXiv:2603.10910*.
- Fu, L.; Yang, B.; Kuang, Z.; Song, J.; Li, Y.; Zhu, L.; Luo, Q.; Wang, X.; Lu, H.; Huang, M.; Li, Z.; Tang, G.; Shan, B.; Lin, C.; Liu, Q.; Wu, B.; Feng, H.; Liu, H.; Huang, C.; Tang, J.; Chen, W.; Jin, L.; Liu, Y.; and Bai, X. 2025. OCRBench v2: An Improved Benchmark for Evaluating Large Multimodal Models on Visual Text Localization and Reasoning. *arXiv preprint arXiv:2501.00321*.
- Gervais, P.; Fadeeva, A.; and Maksai, A. 2024. MathWriting: A Dataset for Handwritten Mathematical Expression Recognition. *arXiv preprint arXiv:2404.10690*.
- Göbel, M.; Hassan, T.; Oro, E.; and Orsi, G. 2013. ICDAR 2013 Table Competition. In *2013 12th International Conference on Document Analysis and Recognition*, 1449–1453.
- Google DeepMind. 2026a. Gemini 3.1 Pro: A Smarter Model for Your Most Complex Tasks. Official model release. Accessed 2026-07-27.
- Google DeepMind. 2026b. Gemini 3.5 Flash Model Card. Official model card. Accessed 2026-07-27.
- Grosicki, E.; Carré, M.; Brodin, J.-M.; and Geoffrois, E. 2009. Results of the RIMES Evaluation Campaign for Handwritten Mail Processing. In *2009 10th International Conference on Document Analysis and Recognition*, 941–945.
- Guan, T.; Liu, F.; Wu, X.; Xian, R.; Li, Z.; Liu, X.; Wang, X.; Chen, L.; Huang, F.; Yacoob, Y.; Manocha, D.; and Zhou, T. 2024. HallusionBench: An Advanced Diagnostic Suite for Entangled Language Hallucination and Visual Illusion in Large Vision-Language Models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 14375–14385.
- Hunyuan Vision Team; Lyu, P.; Wan, X.; Li, G.; Peng, S.; Wang, W.; Wu, L.; Shen, H.; Zhou, Y.; Tang, C.; et al. 2025. HunyuanOCR Technical Report. *arXiv preprint arXiv:2511.19575*.
- Kimi Team. 2026. Kimi K3: Open Frontier Intelligence. *arXiv preprint arXiv:2607.24653*.
- Levenshtein, V. I. 1966. Binary Codes Capable of Correcting Deletions, Insertions, and Reversals. *Soviet Physics Doklady*, 10(8): 707–710.

- Li, G.; Wan, X.; Peng, S.; Wang, W.; Feng, H.; Du, Y.; Wu, B.; Ruan, Z.; Lu, Z.; Wu, L.; Lyu, P.; Shen, H.; Lin, Z.; Hu, S.; Yang, J.; Wen, H.; Yu, G.; Liu, H.; Wang, B.; Ma, C.; Hu, H.; Zhang, C.; and Zhou, Y. 2026. HunyuanOCR-1.5: Making Lightweight OCR VLMs Faster and Better. *arXiv preprint arXiv:2607.04884*.
- Li, Y.; Yang, G.; Liu, H.; Wang, B.; and Zhang, C. 2025. dots.ocr: Multilingual Document Layout Parsing in a Single Vision-Language Model. *arXiv preprint arXiv:2512.02498*.
- Liu, C.-L.; Yin, F.; Wang, D.-H.; and Wang, Q.-F. 2011. CASIA Online and Offline Chinese Handwriting Databases. In *2011 International Conference on Document Analysis and Recognition*, 37–41.
- Liu, Y.; Li, Z.; Huang, M.; Yang, B.; Yu, W.; Li, C.; Yin, X.; Liu, C.-L.; Jin, L.; and Bai, X. 2024. OCRBench: On the Hidden Mystery of OCR in Large Multimodal Models. *Science China Information Sciences*, 67: 220102.
- Mahdavi, M.; Zanibbi, R.; Mouchère, H.; Viard-Gaudin, C.; and Garain, U. 2019. ICDAR 2019 CROHME + TFD: Competition on Recognition of Handwritten Mathematical Expressions and Typeset Formula Detection. In *2019 International Conference on Document Analysis and Recognition*, 1533–1538.
- Marti, U.-V.; and Bunke, H. 2002. The IAM-Database: An English Sentence Database for Offline Handwriting Recognition. *International Journal on Document Analysis and Recognition*, 5(1): 39–46.
- Mathew, M.; Karatzas, D.; and Jawahar, C. V. 2021. DocVQA: A Dataset for VQA on Document Images. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, 2200–2209.
- Niu, J.; Liu, Z.; Gu, Z.; Wang, B.; Ouyang, L.; Zhao, Z.; Chu, T.; He, T.; Wu, F.; Zhang, Q.; et al. 2025. MinerU2.5: A Decoupled Vision-Language Model for Efficient High-Resolution Document Parsing. *arXiv preprint arXiv:2509.22186*.
- OpenGVLab. 2025. InternVL3.5. Official release blog. Accessed 2026-07-27.
- Ouyang, L.; Qu, Y.; Zhou, H.; Zhu, J.; Zhang, R.; Lin, Q.; Wang, B.; Zhao, Z.; Jiang, M.; Zhao, X.; Shi, J.; Wu, F.; Chu, P.; Liu, M.; Li, Z.; Xu, C.; Zhang, B.; Shi, B.; Tu, Z.; and He, C. 2025. OmniDocBench: Benchmarking Diverse PDF Document Parsing with Comprehensive Annotations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 24838–24848.
- Pal, A.; Biswas, S.; Das, A.; Lodh, A.; Banerjee, P.; Chattopadhyay, S.; Karatzas, D.; Lladós, J.; and Jawahar, C. V. 2025. NoTeS-Bank: Benchmarking Neural Transcription and Search for Scientific Notes Understanding. *arXiv preprint arXiv:2504.09249*.
- Qwen Team. 2025. Qwen3 Technical Report. *arXiv preprint arXiv:2505.09388*.
- Seong, J.; Liermann, W.; Kim, M.; Shin, J.-h.; and Lim, S. 2026. When VLMs “Fix” Students: Identifying and Penalizing Over-Correction in the Evaluation of Multi-line Handwritten Math OCR. *arXiv preprint arXiv:2604.22774*.
- Wang, B.; He, T.; Ouyang, L.; Wu, F.; Zhao, Z.; Chu, T.; Qu, Y.; Jin, Z.; Zeng, W.; Miao, Z.; et al. 2026. MinerU2.5-Pro: Pushing the Limits of Data-Centric Document Parsing at Scale. *arXiv preprint arXiv:2604.04771*.
- Wang, B.; Wu, F.; Ouyang, L.; Gu, Z.; Zhang, R.; Xia, R.; Shi, B.; Zhang, B.; and He, C. 2025. Image Over Text: Transforming Formula Recognition Evaluation with Character Detection Matching. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 19681–19690.
- Wei, H.; Sun, Y.; and Li, Y. 2026. DeepSeek-OCR 2: Visual Causal Flow. *arXiv preprint arXiv:2601.20552*.
- Wu, H.; Lou, H.; Li, X.; Zhong, Z.; Sun, Z.; Chen, P.; Zhou, X.; Zuo, K.; Chen, Y.; Tang, X.; et al. 2026. FireRed-OCR Technical Report. *arXiv preprint arXiv:2603.01840*.
- Yin, Y.; Liu, H.; Xie, Q.; Liu, C.; Yang, S.; Wang, S.; Liu, Z.; Zou, H.; Chen, J.; Wei, S.; et al. 2026. Unlimited OCR Works. *arXiv preprint arXiv:2606.23050*.
- Zhang, H.; Liang, L.; and Jin, L. 2020. SCUT-HCCDoc: A New Benchmark Dataset of Handwritten Chinese Text in Unconstrained Camera-Captured Documents. *Pattern Recognition*, 108: 107559.
- Zhang, Z.; Liu, H.; Liang, S.; Zhang, Y.; Xiang, Y.; Liu, J.; Sun, T.; Lin, M.; Zhang, Y.; Zhou, C.; Gao, T.; Cui, C.; Liu, Y.; Yu, D.; and Ma, Y. 2026. PaddleOCR-VL-1.6: Expanding the Frontier of Document Parsing with Under-Optimized Region Refinement and Progressive Post-Training. *arXiv preprint arXiv:2606.03264*.
- Zheng, H.; Li, Y.; Zhang, K.; Xin, L.; Zhao, G.; Liu, H.; Chen, J.; Lou, J.; Qiu, J.; Fu, Q.; et al. 2026. Multimodal OCR: Parse Anything from Documents. *arXiv preprint arXiv:2603.13032*.
- Zheng, X.; Burdick, D.; Popa, L.; Zhong, X.; and Wang, N. X. R. 2021. Global Table Extractor (GTE): A Framework for Joint Table Identification and Cell Structure Recognition Using Visual Context. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, 697–706.
- Zhong, X.; ShafieiBavani, E.; and Jimeno Yepes, A. 2020. Image-Based Table Recognition: Data, Model, and Evaluation. In *Computer Vision – ECCV 2020*, 564–580. Springer.
- Zhou, C.; Gao, Z.; Wang, X.; Gao, T.; Cui, C.; Tang, J.; and Liu, Y. 2026. Real5-OmniDocBench: A Full-Scale Physical Reconstruction Benchmark for Robust Document Parsing in the Wild. *arXiv preprint arXiv:2603.04205*.
- Zhu, Y.; Xie, Z.; Jin, L.; Chen, X.; Huang, Y.; and Zhang, M. 2019. SCUT-EPT: New Dataset and Benchmark for Offline Chinese Text Recognition in Examination Paper. *IEEE Access*, 7: 370–382.

Supplementary Material

Section A provides additional dataset construction details beyond those in the main paper. Section B presents qualitative PDE (Prior-Driven Error) examples from WILDHANDBENCH. Section C gives complete evaluation details including the full model list, prompt templates, and inference configuration.

A. Dataset Details

This section expands on the dataset construction summarized in the main paper. We report only details not already covered there, including per-source sample counts, the joint category–language distribution, per-scenario counts, and the annotation and image-processing specifications.

A.1 Data Collection Sources

The 500 samples are drawn from two complementary channels:

- **Offline handwritten manuscripts (141 samples, 28.2%).** Voluntary contributions from project members and acquaintances, concentrated in the education and medical domains (classroom notes, homework, medical records, prescriptions), plus hand-transcribed article abstracts, reading notes, and letters to broaden writing styles.
- **Internet collection (359 samples, 71.8%).** Publicly available handwritten images covering long-tail genres: classical poetry and calligraphy, historical archival registers, old newspapers, and official forms.

A.2 Category $\times$ Language Distribution

The main paper reports the marginal counts for document structure and language separately. Table 3 gives the full joint distribution.

Table 3: Category $\times$ Language joint distribution.

Category	zh_hans	en	zh_hant	zh_en_mix	Total
Text	251	99	12	7	369
Table	62	16	0	1	79
Formula	20	29	0	3	52
Total	333	144	12	11	500

A.3 Scenario Distribution

The main paper enumerates the nine scenarios; Table 4 adds their per-scenario sample counts.

Table 4: Per-scenario sample counts.

Scenario	Count
Literary essays	93
Letters & notes	81
Medical & health	62
Education & learning	61
Business documents	58
Math & science formulas	55
Classical poetry & calligraphy	41
Daily life notes	32
Historical archives	17
Total	500

A.4 Difficulty Annotation Protocol

The six difficulty dimensions defined in the main paper are each scored independently by 5 reviewers per sample, and per-dimension scores are averaged across reviewers. These ratings support fine-grained analysis but are not used in the aggregate benchmark scores.

A.5 Annotation Format Details

Beyond the target formats stated in the main paper (Markdown for free text, L^AT_EX for formulas, HTML <table> for tables), formula regions are additionally annotated with *polygon* coordinates (closed polygons rather than axis-aligned boxes) to accommodate slanted handwritten layouts, with each polygon paired one-to-one with its L^AT_EX transcription. Table annotations carry full structural markup (rowspan, colspan, header hierarchy).

A.6 Image Processing

All images are stored in PNG format with the following specifications:

- Maximum file size: 1 MB (palette optimization applied where needed).
- EXIF normalization: rotation tags are applied and stripped.
- Naming convention: `hardhand_<UUID_no_dashes>.png` (32-character hex UUID).

B. Qualitative PDE Examples





Figure 3: Classical poem (calligraphy). A handwritten copy of Su Shi’s *Chibi Nostalgia* contains non-standard character orderings. Gemini “corrects” the handwriting to the memorized textbook version—swapping the non-standard two-character ordering (*táo làng*) back to the canonical order (*làng táo*). This is a classic canonical-text prior: the model overwrites the actual handwritten content with a remembered standard version. The human baseline faithfully preserves the non-standard forms and marks only truly illegible characters with “?”.



Ground Truth

收到这封信你会是什么表情，惊喜还是惊吓？很可惜，暂时只能留给想象。

不用检查，这封信没有夹层也没有密文，只是想看见你意外的表情，所以就写了。

遇见你时，本以为只是一场无聊游戏中的意外，但后来这场意外却加上了“唯一”的前缀。你的出现打破了很多我过去的信条，隔了许久我才发现，这场动荡已经影响到了不少方面，比如多出了你的专属头盔、比如一个离开N109区的理由，还有这一封信。

我尝试过寻找自己不小心深陷的原因，但发现就算找到答案也没有意义，仅仅因为这个人是你。

我不想把它叫做命运，因为你和命运不同，命运可以被打破，但当我站在你面前，却开始期待未来。

秦彻

Human Baseline

收到这封信你会是什么表情，惊喜还是惊吓？很可惜，暂时只能留给想象。

不用检查，这封信没有夹层也没有密文，只是想看见你意外的表情，所以就写了。

遇见你时，本以为只是一场无聊游戏中的意外，但后来这场意外却加上了“唯一”的前缀。你的出现打破了很多我过去的信条，隔了许久我才发现，这场动荡已经影响到了不少方面，比如多出了你的专属头盔、比如一个离开N109区的理由，还有这一封信。

我尝试过寻找自己不小心深陷的原因，但发现就算找到答案也没有意义，仅仅因为这个人是你。

我不想把它叫做命运，因为你和命运不同，命运可以被打破，但当我站在你面前，却开始期待未来。

秦彻

Gemini-3.1-Pro

收到这封信你会是什么表情，惊喜还是惊吓？很可惜，暂时只能留给想象。

不用检查，这封信没有夹层也没有密文，只是想看见你意外的表情，所以就写了。

遇见你时，本以为又是一场无聊游戏中的意外，但后来这场意外却加上了“唯一”的参数。你的出现打破了很多我过去的信条，隔了许久我才发现，这场动荡已经影响到了不少方面，比如多出了你的专属头盔、比如一个离开N109区的理由，还有这一封信。

我尝试过寻找自己不小心深陷的原因，但发现就算找到答案也没有意义，仅仅因为这个人是你。

我不想把它叫做命运，因为你和命运不同，命运可以被打破，但当我站在你面前，却开始期待未来。

秦彻

Figure 4: Personal letter. Gemini substitutes “prefix” with “parameter”—a semantic-field substitution in which the model replaces the written word with a semantically related term drawn from its priors rather than transcribing the source faithfully.

临床诊断: 1. 急性肠系膜淋巴结炎
2. 急性肠炎
3. 末端回肠炎

处理及建议: 1. 注意休息, 避免劳累, 清淡饮食
2. 一月后复查腹部CT, 复查大便常规+潜血, 必要时复查结肠镜
3. 随访, 继续口服药物
4. 不适随诊

科医师
(盖章) 拾红

(未经本院盖章无效) 2024年10月2日

Ground Truth

临床诊断: 1. 急性肠系膜淋巴结炎
2. 急性肠炎
3. 末端回肠炎

处理及建议:
1、注意休息, 避免劳累, 清淡饮食
2、一月后复查腹部CT, 复查大便常规+潜血, 必要时复查结肠镜
3、随访, 继续口服药物
4、不适随诊

科医师
(盖章) 拾红
(未经本院盖章无效) 2024年10月2日

Human Baseline

临床诊断: 1. ??????????
2. ?????
3. 末端回??

处理及建议:
1、注意休息, ????, 清淡饮食
2、一般?? 腹部CT, ??大? 常规???
??? 复查结肠镜
3、??? 口服药物
4、不适??

科医师
(盖章) ???
(未经本院盖章无效) 2024年10月2日


Gemini-3.1-Pro

临床诊断: 1. 结肠多发憩室伴憩室炎
2. 结肠息肉
3. 末端回肠炎

处理及建议:
1、休息, 避免劳累, 清淡饮食
2、门诊复查腹部CT, 复查大便常规+潜血, 结肠息肉切除
3、匹维溴铵片 50mg tid, 美沙拉嗪肠溶片
4、不适随诊

科医师
(盖章) 杨鹏
(未经本院盖章无效) 2024年10月2日

Figure 5: Clinical diagnosis. The GT diagnosis is “acute mesenteric lymphadenitis / acute enteritis / terminal ileitis.” Gemini outputs a completely different yet medically plausible diagnosis (“colonic diverticulitis / colonic polyps / terminal ileitis”; only the third item matches). This is the most extreme form of PDE: medical domain-knowledge priors fabricate a coherent but factually wrong diagnosis. The human baseline honestly writes “?” for illegible portions.



Ground Truth

26年4月26日 中医处方笺 门诊号
姓名 穆俊 性别 女 年龄 54 地址 穆家店
处方
双花20 连翘15 元参15 公英20
花粉10g 皂针10g 牛夕12
当归20g 赤芍15g 荆芥6g
川羌6g 砂仁10g 木香10g
茯苓12 炒白术12 太子参15

Human Baseline

26年4月26日 中医处方笺 门诊号
姓名 穆俊 性别 女 年龄 54 地址 穆家店
处方
双花20 连召15 元参15 公英20
花粉10g 皂针10g 牛? 12
当归20g 青芍15g ? 芥6g
? 羌6g 砂花10g 木香10g
茯苓12 炒白术12 太子参15

Gemini-3.1-Pro

26年4月26日 中医处方笺 门诊号
姓名 穆俊 性别 女 年龄 54 地址 穆家庄
处方
双花20 连召15 元参15 公英20
花粉10g 皂针10g 牛夕12
当归20g 白芍15g 荆芥6g
川羌6g 砂仁10g 桔梗10g
茯苓12 炒白术12 党参15

Figure 6: Traditional Chinese medicine prescription. Gemini applies a prior-driven substitution, replacing a herb name with a more frequently prescribed alternative.

国家将新型举国体制优势开展科技攻关
云 增强自主创新能力
① 自力更生→基点 ② 自主创新→必由之路
③ 基础创新→源头 ④ 国家战略科技力量→着力点
第四节、加快建设人才强国
一、培养人才是国家和民族长远发展大计
① ~在国家发展中具有重要战略地位
② ~是实现民族复兴的必然选择
二、培养造就大批德才兼备的高素质人才
① 功以成才，业由才广
.....

Ground Truth

③ 发挥新型举国体制优势开展科技攻关
三、增强自主创新能力
① 自力更生→基点 ② 自主创新→必由之路
③ 基础创新→源头 ④ 国家战略科技力量→着力点
第四节、加快建设人才强国
一、培养人才是国家和民族长远发展大计
① ~在国家发展中具有重要战略地位
② ~是实现民族复兴的必然选择
二、培养造就大批德才兼备的高素质人才
① 功以成才，业由才广
.....

Human Baseline

③ 发挥新型举国体制优势开展科技攻关
三、增强自主创新能力
① 自力更生→基点 ② 自主创新→必由之路
③ 基础创新→源头 ④ 国家战略科技力量→着力点
第四节、加快建设人才强国
一、培养人才是国家和民族长远发展大计
① ~在国家发展中具有重要战略地位
② ~是实现民族复兴的必然选择
二、培养造就大批德才兼备的高素质人才
① 功以成才，业由才广
.....

Gemini-3.1-Pro

③ 发挥新型举国体制优势开展科技攻关
三、增强自主创新能力
① 自立自强→基点 ② 自主创新→必由之路
③ 基础创新→源头 ④ 国家战略科技力量→着力点
第四节、加快建设人才强国
一、培养人才是国家和民族长远发展大计
① ~在国家发展中具有重要战略地位
② ~是实现民族复兴的必然选择
二、培养造就大批德才兼备的高素质人才
① 功以才成，业由才广
.....

PaddleOCR-VL-1.6

③ 发挥新型举国体制优势开展科技攻关
三、增强自主创新能力
① 自力更生→基点 ② 自主创新→必由之路
③ 基础创新→源头 ④ 国家战略科技力量→着力点
第四节、加快建设人才强国
一、培养人才是国家 and 民族长远发展大计
① ~在国家发展中具有重要战略地位
② ~是实现民族复兴的必然选择
二、培养造就大批德才兼备的高素质人才
① 冲以成才，业由才广
.....

Figure 7: Political study notes. Gemini rewrites into more formal policy terminology (“self-reliance” → “self-strengthening”) and swaps the character order inside a four-character phrase (“achievement makes talent” → “talent makes achievement”)—both linguistically valid but not matching the source. This cleanly contrasts high PDE (semantic rewriting) against low PDE (visual misreading).





Figure 8: Childcare training reflection. Gemini fabricates an entirely different topic: “daily cleaning skills training” becomes “recent first-aid training,” and “infant bathing / umbilical care” becomes “infant airway obstruction care”—the whole passage topic is replaced. PaddleOCR-VL exhibits character-level noise but preserves the correct topic keywords (“daily cleaning,” “bathing”). The human baseline matches the GT exactly.



Ground Truth

忘不了你的善良
在生活中，有许多人，在你看不到的地方，做着温暖人心的事，而在我的心中，就有一位那便是我的爷爷。
记得，那是一次寒假的早晨，我揉着睡眠发现爷爷又不见了。我问妈妈，妈妈说爷爷一大早就出门了，我连忙拿起保温杯和围巾就出了家门。
寒风夹着细碎的雪花扑在脸上，远远望见了小区门口的马路上，有一道人影，正挥动着手中的扫把，扫着路上的积雪。我急忙跑过去，爷爷正穿着那件洗得发白的藏青色棉袄。我把保温杯赶紧塞进爷爷那冻红了的手中，他也停下手中动作，拧下杯盖，喝了一小口，白气中露出了一张布满皱纹的洋溢着幸福的笑脸。
.....

Human Baseline

忘不了你的善良
在生活中，有许多人，在你看不到的地方，做着温暖人心的事，而在我的心中，就有一位那便是我的爷爷。
记得，那是一次寒假的早晨，我揉着睡眠发现爷爷又不见了。我问妈妈，妈妈说爷爷一大早就出门了，我连忙拿起保温杯和围巾就出了家门。
寒风夹着细碎的雪花扑在脸上，远远望见了小区门口的马路上，有一道人影，正挥动着手中的扫把，扫着路上的积雪。我急忙跑过去，爷爷正穿着那件洗得发白的藏青色棉袄。我把保温杯赶紧塞进爷爷那冻红了的手中，他也停下手中动作，拧下杯盖，喝了一小口，白气中露出了一张布满皱纹的？？幸福的笑脸。
.....

Gemini-3.1-Pro

忘不了你的善良
在生活中，有许多人，在你最需要帮助的时候，做着温暖人心的事，而在我的心中，就有一位那便是我的爷爷。
记得，那是一次寒假的早晨，我揉着睡眠发现爷爷又不见了。我问妈妈，妈妈说爷爷一大早就出门了，我连忙拿起保温杯和围巾就出家门。
寒风裹挟着细碎的雪花扑在脸上，远远望见了小区门口的马路上，有一道人影，正挥动着手中的扫把，扫着路上的积雪。我急忙跑过去，爷爷正穿着那件洗得发白的藏青色棉袄。我把保温杯赶紧塞进爷爷那冻得通红的手中，他也停下手中动作，拧下杯盖，喝了一小口，白气中露出了布满皱纹的透着幸福的笑脸。
.....

PaddleOCR-VL-1.6

忘不了你的善良
生活中，有许多人，在你生活的旅途中，做着温暖义心的事，而在我的心中，就有一位那便是我的爷爷。
记得，那是一次寒假早早晨，我揉着脸眼发现爷爷又不见了。我问妈妈，妈妈说爷爷一大早就出门了，我连忙拿起保温杯和巾就出家门。
寒风夹着细碎的雪花扑在脸上，远远望见了小区门口的马路上，有一道人影，正挥动着手中的扫把，扫着路上的积雪。我急忙跑过去，爷爷正穿着那件洗得发白的旧色棉织具。我把保温杯托紧进爷爷那冻僵了的手中，他也弯下手中动作，扶下杯盖，喝了一小口，白气中露出了一弓长布满皱纹的幸福的笑脸。
.....

Figure 9: Elementary-school essay. The student wrote “doing heart-warming things *in places you cannot see*.” Gemini polishes it to “doing heart-warming things *when you most need help*”—semantically “better” but not the original text (PDE). Both Gemini and PaddleOCR-VL are effectively “polishing” the child’s composition.

$$f(x, y) = x^2 + 2y^2, \quad g(x, y) = x^2 + 16y^2 = 16$$

we know gradients of both functions will be in the same direction & proportional.

$$f(x, y) = x^2 + 2y^2$$

$$\nabla f(x_m, y_m) = \lambda (\nabla g(x_m, y_m))$$

$$\nabla f = \begin{pmatrix} \frac{\partial f}{\partial x} \\ \frac{\partial f}{\partial y} \end{pmatrix} = \begin{pmatrix} \frac{\partial}{\partial x}(x^2 + 2y^2) \\ \frac{\partial}{\partial y}(x^2 + 2y^2) \end{pmatrix} = \begin{pmatrix} 2x \\ 4y \end{pmatrix} = \nabla f$$

$$\nabla g = \begin{pmatrix} \frac{\partial g}{\partial x} \\ \frac{\partial g}{\partial y} \end{pmatrix} = \begin{pmatrix} \frac{\partial}{\partial x}(x^2 + 16y^2) \\ \frac{\partial}{\partial y}(x^2 + 16y^2) \end{pmatrix} = \begin{pmatrix} 2x \\ 32y \end{pmatrix}$$

so if $L(x, y, \lambda) = \nabla f - \lambda \nabla g$, $\nabla f = \lambda \cdot \nabla g$

Ground Truth

$$f(x, y) = x^2 + 2y^2, \quad g(x, y) = x^2 + 16y^2 = 16$$

we know gradients of both functions will be in the same direction of proportional

$$f(x, y) = x^2 + 2y^2$$

$$\nabla f(x_m, y_m) = \lambda (\nabla g(x_m, y_m))$$

$$\nabla f = \begin{pmatrix} \frac{\partial f}{\partial x} \\ \frac{\partial f}{\partial y} \end{pmatrix} = \begin{pmatrix} \frac{\partial}{\partial x}(x^2 + 2y^2) \\ \frac{\partial}{\partial y}(x^2 + 2y^2) \end{pmatrix} = \begin{pmatrix} 2x \\ 4y \end{pmatrix} = \nabla f$$

$$\nabla g = \begin{pmatrix} \frac{\partial g}{\partial x} \\ \frac{\partial g}{\partial y} \end{pmatrix} = \begin{pmatrix} \frac{\partial}{\partial x}(x^2 + 16y^2) \\ \frac{\partial}{\partial y}(x^2 + 16y^2) \end{pmatrix} = \begin{pmatrix} 2x \\ 32y \end{pmatrix}$$

so if $L(x, y, \lambda) = \nabla f - \lambda \nabla g$, $\nabla f = \lambda \cdot \nabla g$

Human Baseline

$$f(x, y) = x^2 + 2y^2, \quad g(x, y) = x^2 + 16y^2 = 16$$

we know gradients of both functions will be in the same direction of proportional

$$f(x, y) = x^2 + 2y^2$$

$$\nabla f(x_m, y_m) = \lambda (\nabla g(x_m, y_m))$$

$$\nabla f = \begin{pmatrix} \frac{\partial f}{\partial x} \\ \frac{\partial f}{\partial y} \end{pmatrix} = \begin{pmatrix} \frac{\partial}{\partial x}(x^2 + 2y^2) \\ \frac{\partial}{\partial y}(x^2 + 2y^2) \end{pmatrix} = \begin{pmatrix} 2x \\ 4y \end{pmatrix} = \nabla f$$

$$\nabla g = \begin{pmatrix} \frac{\partial g}{\partial x} \\ \frac{\partial g}{\partial y} \end{pmatrix} = \begin{pmatrix} \frac{\partial}{\partial x}(x^2 + 16y^2) \\ \frac{\partial}{\partial y}(x^2 + 16y^2) \end{pmatrix} = \begin{pmatrix} 2x \\ 32y \end{pmatrix}$$

so if $L(x, y, \lambda) = \nabla f - \lambda \nabla g$, $\nabla f = \lambda \cdot \nabla g$

Gemini-3.1-Pro

$$f(x, y) = x^2 + 2y^2, \quad g(x, y) = x^2 + 16y^2 = 16$$

We know gradients of both functions will be in the same direction & proportional.

$$f(x, y) = x^2 + 2y^2$$

$$\nabla f(x_m, y_m) = \lambda (\nabla g(x_m, y_m))$$

$$\nabla f = \begin{pmatrix} \frac{\partial f}{\partial x} \\ \frac{\partial f}{\partial y} \end{pmatrix} = \begin{pmatrix} \frac{\partial}{\partial x}(x^2 + 2y^2) \\ \frac{\partial}{\partial y}(x^2 + 2y^2) \end{pmatrix} = \begin{pmatrix} 2x \\ 4y \end{pmatrix} = \nabla f$$

$$\nabla g = \begin{pmatrix} \frac{\partial g}{\partial x} \\ \frac{\partial g}{\partial y} \end{pmatrix} = \begin{pmatrix} \frac{\partial}{\partial x}(x^2 + 16y^2) \\ \frac{\partial}{\partial y}(x^2 + 16y^2) \end{pmatrix} = \begin{pmatrix} 2x \\ 32y \end{pmatrix}$$

so if $L(x, y, \lambda) = \nabla f - \lambda \nabla g$, $\nabla f = \lambda \cdot \nabla g$

PaddleOCR-VL-1.6

$$f(x, y) = x^2 + 2y^2, g(x, y) = x^2 + 16y^2 = 16$$

We know gradients of both functions will be in the same direction if prepatian

$$f(x, y) = x^2 + 2y^2$$

$$\nabla f(x_m, y_m) = \lambda (\nabla g(x_m, y_m))$$

$$\nabla f = \begin{pmatrix} \frac{\partial f}{\partial x} \\ \frac{\partial f}{\partial y} \end{pmatrix} = \begin{pmatrix} \frac{\partial}{\partial x}(x^2 + 2y^2) \\ \frac{\partial}{\partial y}(x^2 + 2y^2) \end{pmatrix} = \begin{pmatrix} 2x \\ 4y \end{pmatrix} = \nabla f$$

$$\nabla g = \begin{pmatrix} \frac{\partial g}{\partial x} \\ \frac{\partial g}{\partial y} \end{pmatrix} = \begin{pmatrix} \frac{\partial}{\partial x}(x^2 + 16y^2) \\ \frac{\partial}{\partial y}(x^2 + 16y^2) \end{pmatrix} = \begin{pmatrix} 2x \\ 32y \end{pmatrix}$$

so if $L(x, y, \lambda) = \nabla f - \lambda \nabla g$, $\nabla f = \lambda \cdot \nabla g$

Figure 10: Mathematical derivation (Lagrange multipliers). Gemini corrects the awkward phrase “in the same direction of proportional” to “in the same direction & proportional.” PaddleOCR-VL misreads “proportional” as “prepatian” and garbles the ∇g matrix line, but shows no semantic rewriting.

Table 5: Complete list of evaluated models.

Model Name	Type	Access	Model ID / Version
GPT-5.4	General VLM	API (OpenAI-compatible)	gpt-5.4
Gemini-3.1-Pro	General VLM	API (OpenAI-compatible)	gemini-3.1-pro-preview
Gemini-3.5-Flash	General VLM	API (OpenAI-compatible)	gemini-3.5-flash
Claude-Opus-4-8	General VLM	API (OpenAI-compatible)	claude-opus-4-8
Qwen3.5-Plus	General VLM	API (OpenAI-compatible)	qwen3.5-plus
Qwen3-VL	General VLM	API (vLLM)	qwen3-vl-235b-a22b-thinking
InternVL3.5	General VLM	API	internvl3.5-241b-a28b
Kimi-K3	General VLM	API (Anthropic fmt)	kimi-k3
Qianfan-OCR	OCR-focused	API (Baidu)	qianfan-ocr
Hunyuan-OCR	OCR-focused	Local (vLLM)	tencent/HunyuanOCR
GLM-OCR	OCR-focused	API (ZhipuAI)	glm-ocr
PaddleOCR-VL	OCR-focused	API (async job)	PaddleOCR-VL-1.6
DeepSeek-OCR-v2	OCR-focused	Local (vLLM)	deepseek-ai/DeepSeek-OCR
FireRed-OCR	OCR-focused	Local (vLLM)	FireRed-OCR
Unlimited-OCR	OCR-focused	Local (vLLM)	Unlimited-OCR
MinerU-2.5	Document parser	Local (vLLM)	opendatalab/MinerU2.5-2509-1.2B
MinerU-2.5-Pro	Document parser	Local (vLLM)	opendatalab/MinerU2.5-Pro

C. Complete Evaluation Details

C.1 Model List & Access Details

Table 5 lists all evaluated models with their access method and model identifier.

C.2 Prompt Templates

All general-purpose VLMs (GPT-5.4, Gemini-3.1-Pro, Gemini-3.5-Flash, Claude-Opus-4-8, Qwen3.5-Plus, Qwen3-VL, InternVL3.5, Kimi-K3) use the standard OmniDocBench prompt. For all OCR-focused models (Qianfan-OCR, Hunyuan-OCR, GLM-OCR, PaddleOCR-VL, DeepSeek-OCR-v2, FireRed-OCR, Unlimited-OCR) and document parsers (MinerU-2.5, MinerU-2.5-Pro), we use the default API parameters when calling their APIs, or the default settings of the model when deployed locally—no user-supplied prompt is overridden.

OmniDocBench prompt (default).

You are an AI assistant specialized in converting PDF images to Markdown format. Please follow these instructions for the conversion:

1. Text Processing:
 - Accurately recognize all text content in the PDF image without guessing or inferring.
 - Convert the recognized text into Markdown format.
 - Maintain the original document structure, including headings, paragraphs, lists, etc.
2. Mathematical Formula Processing:
 - Convert all mathematical formulas to LaTeX format.
 - Enclose inline formulas with `\( \)`. For example:
This is an inline formula `\( E = mc^2 \)`
 - Enclose block formulas with `\[ \]`. For example:
`\[ \frac{-b \pm \sqrt{b^2 - 4ac}}{2a} \]`
3. Table Processing:
 - Convert tables to HTML format.
 - Wrap the entire table with `<table>` and `</table>`.
4. Figure Handling:
 - Ignore figures content in the PDF image. Do not attempt to describe or convert images.
5. Output Format:

- Ensure the output Markdown document has a clear structure with appropriate line breaks between elements.
- For complex layouts, try to maintain the original document's structure and format as closely as possible.

Please strictly follow these guidelines to ensure accuracy and consistency in the conversion. Your task is to accurately convert the content of the PDF image into Markdown format without adding any extra explanations or comments.

C.3 Inference Configuration

All models share a common retry and timeout strategy:

- **Temperature:** 0.0 (deterministic decoding) for all API-based models.
- **Max retries:** 3, with exponential backoff (5 s, 10 s, 20 s).
- **Timeout:** 120–300 s depending on model (up to 600 s for local models).
- **Max image dimension:** 4000 px (images exceeding this are resized proportionally).
- **Max output tokens:** 8192 (where configurable).

C.4 Post-Processing

Model outputs are processed through a `clean_markdown()` function that strips Markdown code fences (e.g., ``markdown ... ``) from the response. No other normalization is applied to model outputs before evaluation.

C.5 Human Baseline Protocol

The human baseline is collected under conditions identical to model evaluation:

- Human participants receive the same handwritten document images as models.
- **Single-pass recognition:** no revision, no second attempt.
- **No auxiliary resources:** participants may not consult MLLM predictions, writer-provided transcripts, community discussions, or domain experts.
- **Same target formats:** Markdown for text, $\text{\LaTeX}$ for formulas, HTML for tables.
- **Same evaluation metrics:** Edit Distance, CDM, and TEDS are applied identically.

This protocol yields a calibrated reference under model-comparable conditions rather than an absolute upper bound on human performance.