

VersaDB: A High-Performance AI Storage Database for Unifying Multimodal Datasets

Cong Wang[†], Zelin Liu[†], Yang Luo[†], Ran Zhang, Zhijian Guo, Hui Zhang, Fan Yu, Yanfei Cao, Naijie Gu[‡], Jun Yu[‡]

Abstract—The AI field has been rapidly developing, leading to the emergence of a large number of AI training datasets of various types. These datasets contain different modalities, including text, images, audio, etc., and may come in various data storage formats. With the advancement of AI hardware, AI computation units like GPUs, TPUs, and NPUs can greatly accelerate the training speed of AI models, which in turn increases the demand for faster data processing. When using existing AI processing frameworks to handle datasets with different modalities and storage formats, processing speeds may be suboptimal due to issues such as data layout and the way users handle the data. Therefore, using a unified database to store multiple data formats can better manage and optimize data access. In this paper, we introduce VersaDB, a database designed specifically for AI datasets with various modalities. We implemented a page-based storage system, separating structured and unstructured data. Additionally, we generated B+ tree-based index files to accelerate data access. VersaDB supports automatic sharding and maintains a hierarchical metadata management system, with corresponding metadata maintained at the page, shard, and global levels, forming the foundation for the efficient operation of the database. We also focused on ease of use by providing APIs for directly converting datasets into VersaDB, as well as APIs for converting popular AI data storage formats (e.g., CSV, TFRecord, .bin) into VersaDB. Our experiments show that using VersaDB can achieve up to 5.35x acceleration and maintain consistent performance across different parallelism levels.

Index Terms—AI data management, Multimodal, Memory Usage Optimization.

I. Introduction

WITH the rapid development of multi-sensor fusion applications and AI, we are closer than ever to creating an AI agent capable of perceiving the world and interacting in a human-like manner using multiple

senses [1]. AI advances are driven by big data [2], and recent datasets exhibit trends of richer modalities and larger scales [3], such as Conceptual 12m [4] Laion-400m [5] X-world [6]. With the development of AI computing hardware, such as Nvidia’s GPUs, Google’s TPUs, Huawei’s NPUs, and accelerators designed for specific networks [7] [8], along with various model optimization techniques [9], data loading may become a bottleneck in AI training [10] [11]. This is not only because the improvement in computational power and efficiency increases data throughput but also because data publishers release AI data in different formats, researchers are unable to read the data using a unified and efficient data reading architecture, leading to significant performance variations between different datasets.

To accelerate data reading and processing, various AI frameworks use different methods. For example, Pytorch [12], Mindspore, and Tensorflow all support multi-threaded parallel processing, distributing data loading and preprocessing tasks across multiple threads to achieve parallel processing, thereby reducing waiting time during model training or inference. Prefetching is another effective method. It works by loading data in advance so that it is ready in memory when needed. This effectively overlaps GPU computation with CPU data reading time, reducing the impact of I/O time [10]. However, acceleration techniques in AI frameworks face several issues: Firstly, increasing the number of threads can lead to additional overhead [13] (e.g., thread switching and inter-process communication), and prefetching is only effective when model training time exceeds data processing time [14]. Secondly, acceleration techniques typically cannot change the layout and organization of data, and lack in indexing systems, which may slow down data indexing or increase memory overhead. Thirdly, the issue of requiring different reading architectures for different modal data has yet to be solved, potentially leading to inconsistent performance.

Normalizing data to a unified format or database is a convenient approach for management and reading. Additionally, rearranging the data can lead to better reading performance. For example, the LMDB storage database stores key-value data using a B+ tree, offering features such as multi-version concurrency control, fast disk I/O, and others [15]. Due to its ability to provide rapid data access [16], it is suitable for deep learning tasks. Similarly, converting data to TFRecord is another common choice

0000-0000/00\$00.00/0 © 2021 IEEE. TFRecord [20] is an efficient data storage

This work was supported by National Key R&D Program of China under Grant No.2021ZD0110400

This work was supported by the University of Science and Technology of China (First Affiliation) and the Huawei (Second Affiliation) MindSpore open source project.

[†] These authors contributed equally to this work.

[‡] These authors are co-corresponding authors.

Naijie Gu, Hui Zhang, Jun Yu, Yanfei Cao are with the University of Science and Technology of China, Anhui, China (e-mail: {gunj,fzhh,harryjun}@ustc.edu.cn, caoyf@mail.ustc.edu.cn).

Ran Zhang is with the South China University of Technology, Guangzhou, China (e-mail: 202164010462@mail.scut.edu.cn).

Zelin Liu is with the Shanghai Jiao Tong University, Shanghai, China (e-mail: julio1@sjtu.edu.cn).

Cong Wang, Yang Luo, Fan Yu, and Zhijian Guo are with Huawei, China (e-mail: {wangcong64, luoyang42, fan.yu, guozhijian}@huawei.com).

format designed specifically for Tensorflow, aiming at improving the efficiency of loading and processing large-scale datasets. Data stored in TFRecord are serialized in the protobuf binary format, supporting parallel reading and prefetching using Tensorflow APIs.

However, existing AI storage management solutions still have some issues. For example, due to the B+ tree structure of LMDB, it requires knowledge of the parent node and related information to locate the record's exact address. As a result, direct random access is not currently supported, and sequential access must be performed using a "cursor." TFRecord, designed specifically for Tensorflow, has a major issue of being incompatible with other AI frameworks. Furthermore, since both writing and reading in TFRecord are sequential, it cannot perform reading while writing. Both storage methods share some common issues: first, they do not support modifications to the data. If a user wishes to modify the data, the entire data file must be regenerated, which is very time-consuming when dealing with large datasets. Secondly, when storing data in memory, they do not distinguish between different modalities or data structures. LMDB uses key-value pairs to store all different data, and the data is generally stored in a serialized form. TFRecord, on the other hand, stores all different data sequentially, without considering the data types.

To address the above issues and the characteristics of AI data, we designed an AI database with the following considerations. First, our database should not only perform well during sequential reads but also handle random access efficiently, as shuffling plays a crucial role in AI training. It can significantly improve unbiased learning and convergence accuracy [21] [22], and to some extent, prevent overfitting [23]. Secondly, we considered the current organizational characteristics of AI data, such as the diversity of modalities (e.g., text, audio, video) that may be either structured or unstructured, with most corresponding labels being structured. We also considered the reading and writing of ultra-large datasets. Storing an entire large dataset in a single file is clearly unreasonable, as it would significantly impact data transfer and mobility.

We designed an efficient and user-friendly AI database called VersaDB. We divide the data storage into raw data and blob data sections for storing structured and unstructured data, respectively. In the data storage section, we implement page-based storage, with pages as the smallest storage unit, allowing for direct random access via page offsets. To accelerate data access, we create a separate index file outside the data storage file, implementing a B+ tree-based structure. We also employ a two-level sharding mechanism: the physical layer stores data, while the logical layer maps data through a distributed hash table. Shard information is managed by a hierarchical metadata system, which includes global, shard, and page-level dataset information, forming the foundation for the efficient operation of the data format. On top of these

features, we support dynamic field extension capabilities and seamless integration of diverse data types, while also implementing a hierarchical lock manager to enable finer-grained locking, allowing data reading without affecting write operations.

Fig. 1 illustrates the VersaDB file generation workflow. The process begins by parsing input data according to the user-defined schema, writing structured data to the raw data section and unstructured data to the blob data section. During this process, the system generates statistics and shard metadata while constructing the index structure. The final step integrates the header, raw data, and blob data into a cohesive data file.

In summary, this paper makes the following contributions:

- **AI-specific adaptation.** The AI database we designed implements a page-based storage model, where data is stored separately according to its type. It can automatically generate multi-level index files based on the B+ tree structure according to the stored data, and meticulously maintain multi-dimensional metadata. This design fully adapts to the diverse ecosystem of current AI datasets and meets the demand for fast data access.
- **High performance.** We tested multiple datasets from common modalities such as images, text, and audio in two different machine environments. The test tasks included Pure reading, Shuffle reading, and Preprocessing, achieving up to 5.35x acceleration under default conditions. We also evaluated the performance of VersaDB at different parallelism levels and distributed levels. The experimental results demonstrate that our data structure offers exceptional performance and scalability.
- **Memory consumption Optimization.** The memory consumption of VersaDB has been specially optimized. We use the HyperLogLog structure for cardinality estimation, apply specific compression schemes to both the outer and inner layers of pages, and implement strategies such as the scalar-blob separation strategy and dynamic page replacement policy.

II. Background

The training of an AI model generally involves the following steps: data reading, data preprocessing, and model training. A batch of data (usually ranging from 32 to 512 samples) is first loaded into the host memory, and then parsed according to its data type. For example, images need to be parsed from storage formats like JPG or PNG into arrays or tensors, while audio may require parsing the WAV format to extract channel data. After parsing, preprocessing is usually performed before feeding the data into the AI model for training. Existing deep learning frameworks like TensorFlow, PyTorch, and Mindspore already cover the above model training process. Below, we will briefly introduce how these frameworks process data and some common AI data storage formats.




Fig. 1. VersaDB file generation workflow. VersaDB is designed to provide users with an efficient and convenient AI data storage management method. To store datasets of different modalities using VersaDB, users need to define the schema information based on the content to be stored. Then, different data types in the dataset will be stored separately in Blob data pages and Raw data pages. For example, data labels will be stored in the raw data pages. Subsequently, an index file will be generated based on the stored data, and corresponding metadata will be included in the header.

AI training framework. When training an AI model, it is often necessary to leverage AI training frameworks such as PyTorch, TensorFlow, or Mindspore. These frameworks provide comprehensive support for tasks ranging from data processing to network training, facilitating the building and training of AI models. Different frameworks define their own data processing workflows. For instance, PyTorch manages data through the Dataloader, TensorFlow defines its own tf.data API for data management, and Mindspore defines data processing as a graph, employing multi-stage parallel pipelines. AI data formats rely on AI training frameworks for reading, and the speed of data loading directly affects subsequent data preprocessing and model training. Therefore, an efficient AI data storage management method is essential to ensure a fast end-to-end AI training pipeline.

AI data storage formats. Current AI datasets come in various storage formats. For example, the JSON format is easy to parse and generate, supports multiple data types, and allows for nested structures [24]. It is commonly used to store image information, category data, annotations, and other structured data. BIN files are a type of binary data storage format that can occupy less space and store more complex data structures, such as serialized images or audio. However, BIN files lack readability, do not include structural descriptions of the data, and may require external documentation for proper parsing. The CSV format is a widely used text-based format with high compatibility and readability. However, it does not support nested data structures and lacks the capability to handle large-scale datasets efficiently.

AI distributed training. Model parallelism and data parallelism are commonly used strategies for training large models today [25]. Model parallelism involves placing different parts of the model on different compute cards. In the data parallelism strategy, the dataset is split into multiple chunks, and different compute cards read different data chunks to accelerate the reading of ultra-

large datasets.

Multimodal AI training. Training AI with multimodal methods, which involves extracting and associating information from diverse types of data [26], offers great promise and potential across a variety of applications. For instance, research has shown that incorporating two or three modalities in tasks such as sentiment analysis can significantly improve effectiveness [27] [28]. The training of multimodal AI models generally follows two main strategies: feature-level fusion [29] and decision-level fusion [30]. In feature-level fusion, data from multiple modalities is combined into a unified feature vector, enabling the integration of these modalities. In contrast, decision-level fusion allows independent models to process each modality separately, produce individual decisions, and then combine these decisions to associate the multimodal information. Both fusion strategies, whether at the feature or decision level, are impacted by the fact that the slowest modality during training can act as a bottleneck, restricting the performance of the entire model. Moreover, the performance of datasets with varying storage structures or modalities can differ during data retrieval. As a result, ensuring efficient processing of each modality is essential for optimizing model performance.

III. VersaDB overview

VersaDB implements a hierarchical data management system optimized for large-scale, multimodal datasets through a comprehensive technical framework, as shown in Fig. 2. This section details the core components and their technical implementations:

In section IV, we present the hierarchical file structure, which implements a binary file structure combining a data file and an index file. The data file employs a B+ tree-based organization with a header containing critical metadata, a raw data section for structured data storage, and a blob data section for unstructured content. This implementation enables efficient data access through direct page addressing and optimized index lookups.

In section V, we describe the implementation of three core interfaces: FileWriter, FileReader, and VersaPage. These interfaces utilize buffered I/O mechanisms, multi-threaded access patterns, and LRU-based page caching to optimize data operations. Specialized conversion modules implement format-specific optimizations while maintaining consistent schema validation and write orchestration.

In section VI, we detail the system implementation for schema definition and the hierarchical metadata organization. The schema system employs a binary encoding format with version control mechanisms, while metadata management implements a two-phase commit protocol with write-ahead logging for consistency guarantees.

The section VII presents the two-level partitioning mechanism for shards, the distributed aggregation tree for statistics, and the hybrid indexing approach combining B+ trees and inverted indexes. These components implement specific algorithms for distributed consistency and efficient query processing.




Fig. 2. This paper introduces the architecture of VersaDB. VersaDB is divided into two main components: the Data file and the Index file. The Data file is used to store the actual data and metadata, while the Index file is used to assist in locating the physical storage location of the data. In this paper, we will primarily focus on the data storage methods, the APIs required to interact with VersaDB, the statistics and structure of metadata, data sharding management, dynamic page management, as well as random sampling and parallel reading optimizations.

Section VIII implements a dynamic storage unit system with hybrid compression mechanisms and buffer pool management. The implementation utilizes a slot-based architecture and copy-on-write mechanisms for concurrent access handling.

Finally, the section IX details the implementation of high-performance operators and parallel execution mechanisms. The sampling and shuffling operators employ modified reservoir and Fisher-Yates algorithms, while parallelization support implements work-stealing task scheduling and multi-version timestamp ordering for consistency control.

IV. hierarchical file structure

VersaDB employs a hierarchical file structure consisting of a data file and an index file. The data file integrates a header section with metadata, a raw data section for structured data storage, and a blob data section for unstructured data, as illustrated in Fig. 2.

The header section maintains critical structural information through five interconnected components. Schema Information defines data types and their structural relationships, while Shard Information maps logical shards to physical storage locations. Page Details maintains the page table structure and its relationships with shards, complemented by Statistical Information that tracks multilevel metrics. Index Configurations store the mapping between logical records and their physical locations.

Within the raw data section, VersaDB implements pagebased storage, where each page serves as the minimal storage unit with a unique page ID mapped through Page Details. The data within pages follows the schema-defined format, enabling direct random access through page offsets. The blob data section adopts a stream-oriented structure, utilizing an offset table in the header for efficient blob localization. Each blob entry contains a size field followed by the actual data, optimizing variable-length object storage.




Fig. 3. Three simple definition for Schema format.

The index file implements a B+ tree structure to facilitate efficient data retrieval. Leaf nodes store key-offset pairs mapping index field values to physical locations in the data file, while internal nodes maintain separator keys to accelerate search operations. The leaf nodes are interconnected through bidirectional links, enabling efficient range query processing.

This architecture achieves efficient data organization and access through the separation of structured and unstructured data storage, implementation of multilevel indexing, and maintenance of fine-grained metadata. The B+ tree index structure ensures logarithmic time complexity for data retrieval operations, while the page-based storage system optimizes both sequential and random access patterns.

V. User Interfaces

VersaDB implements three core interfaces: FileWriter, FileReader, and VersaPage, to enable efficient data manipulation and access. The FileWriter interface provides low-level write operations through a schema-driven API.

It implements a buffered writing mechanism where data is first accumulated in memory buffers, then written to disk in optimized chunks when the buffer reaches a predefined threshold. This approach minimizes I/O operations while maintaining memory efficiency.

The FileReader interface implements a multi-threaded reading mechanism that supports both sequential and random access patterns. It utilizes a prefetching algorithm that predicts future data access based on historical patterns and loads data into a circular buffer. The interface exposes methods for field-selective reading, allowing applications to retrieve only necessary fields and reduce I/O overhead. The underlying implementation maintains a thread pool that asynchronously loads pages while the main thread processes the current data chunk.

The VersaPage interface extends the basic reading capabilities by implementing a paginated access mechanism. It maintains a page cache that stores frequently accessed pages using a Least Recently Used (LRU) replacement policy. The interface provides atomic operations for page-level access and updates, ensuring data consistency in multi-threaded environments.

For dataset conversion, VersaDB provides specialized conversion modules. These modules implement dataset-specific parsing logic while sharing a common write pipeline. For instance, the ImageNetToMR module implements parallel image decoding and compression, maintaining a producer-consumer pattern where decoder threads feed into a shared write buffer. Similarly, the TFRecordToMR module implements a streaming parser that directly maps TFRecord protocol buffers to VersaDB schema definitions, minimizing intermediate data copies. Each conversion module inherits from a base converter class that implements the core schema validation and write orchestration logic. This design ensures consistent handling of schema enforcement, index generation, and statistical tracking across different dataset formats while allowing format-specific optimizations in the parsing layer.

VI. Schema and Metadata Management

A. Schema Management

VersaDB implements a hierarchical schema system that encodes data structure specifications through a type system. As shown in Fig. 3, each schema definition consists of field descriptors that specify the name, data type, and shape of each field. The type system supports primitive types (integers, floats, strings) and complex types (tensors, nested structures) through a composable type hierarchy.

The schema implementation utilizes a binary encoding format where each field descriptor is serialized as a sequence of type, name, shape triplets. This format enables efficient schema validation during data operations while minimizing storage overhead. For nested structures, the system implements a depth-first traversal mechanism that recursively validates and processes nested fields according to their hierarchical relationships.

Schema evolution is handled through a versioning mechanism that maintains backward compatibility. When a

schema update occurs, the system generates a schema diff that captures field additions, deletions, and modifications. These changes are encoded in a version table within the header, allowing the system to apply appropriate transformation rules when reading data written with older schemas. The version table implements a directed acyclic graph (DAG) structure to track schema lineage and enable efficient schema resolution during data access.

B. Metadata Management

The metadata system in VersaDB organizes dataset information in a hierarchical structure across global, shard, and page levels. At each level, metadata entries are encoded using a compact binary format that optimizes both storage efficiency and access speed. The system implements a lazy loading mechanism where metadata is loaded on demand and cached in memory using a least recently-used (LRU) policy.

Global metadata maintains dataset-wide information including schema versions, statistical summaries, and index configurations. Shard-level metadata implements a mapping between logical shards and their physical storage locations, along with shard-specific statistics and page allocation tables. Page-level metadata tracks record boundaries, data distributions, and bloom filters for efficient query optimization.

The metadata update process follows a two-phase commit protocol to ensure consistency across distributed environments. Updates are first written to a write-ahead log (WAL), then applied to the in-memory metadata cache before being persisted to disk. This approach guarantees atomic metadata updates while providing crash recovery capabilities.

Statistical tracking is implemented through a hierarchical counter system that maintains counts and distributions at multiple granularities. Counter updates are performed using atomic operations to ensure consistency in concurrent scenarios. The system implements efficient aggregation algorithms that can compute global statistics from shard-level counters without requiring full dataset scans.

VII. Shard, Statistic, and Index Management

A. Shard Management

VersaDB implements sharding through a two-level partitioning mechanism. At the physical level, data is divided into fixed-size shards, each maintaining its own page tables and local metadata. At the logical level, a distributed hash table maps record keys to physical shards, enabling efficient data distribution and load balancing. Each shard contains multiple pages organized as the minimal storage units, with pages inheriting the parent shard's access control and consistency protocols.

The system implements atomic shard operations through a distributed lock manager. Each shard maintains a version counter and a write-ahead log for crash recovery. During write operations, the system acquires shard-level




Fig. 4. Statistical counting based on distributed aggregation tree

locks before updating both data and metadata, ensuring consistency in concurrent scenarios. Read operations utilize a multi-version concurrency control (MVCC) mechanism that allows concurrent reads without blocking write operations.

B. Statistic Management

The statistical framework maintains hierarchical counters at global, shard, and page levels through a distributed aggregation tree, as shown in Fig. 4. Statistics are generated during file creation and continuously updated during write operations. The system implements approximate counting algorithms using HyperLogLog structures for cardinality estimation, enabling efficient memory usage while maintaining acceptable error bounds.

Counter updates follow an eventual consistency model where local updates are immediately reflected in shard-level statistics while global aggregations are performed asynchronously. The system employs a background merger that periodically consolidates shard-level statistics into global counters using a hierarchical aggregation protocol. This design trades immediate global consistency for improved write performance while ensuring that statistical queries eventually reflect the complete dataset state.

C. Index Management

The indexing system implements a hybrid approach combining B+ trees for structured data and inverted indexes for unstructured content. The system first builds primary indexes for raw data fields, then constructs secondary indexes for blob data through parallel processing. The Query procedure demonstrates the system's ability to handle both range-based and exact-match queries by leveraging field-specific index structures.

Index updates are performed through a log-structured merge (LSM) tree [31] implementation. New entries are first accumulated in an in-memory buffer, then merged into disk-based index structures through background compaction processes. This approach optimizes write performance while maintaining query efficiency through careful compaction scheduling. The system implements bloom filters at each index level to reduce unnecessary disk accesses during query processing.

For distributed operations, the index manager maintains consistent views across nodes through a vector clock

mechanism. Each index update is tagged with a vector timestamp, allowing the system to detect and resolve conflicts during concurrent modifications. The index structures support efficient range partitioning, enabling parallel query processing across multiple nodes while maintaining global consistency.

Algorithm 1: Multi-Strategy Sampling

```

// Category balanced sampling implementation.
1 Function CATEGORYBALANCEDSAMPLE(data,
  config):
2   balanced_samples  $\leftarrow$  [] ;
3   categories  $\leftarrow$  GETCATEGORIES(data) ;
4   sample_per_category  $\leftarrow$  config.total_samples
    / categories.length ;
5   for each category in categories do
6     category_data  $\leftarrow$ 
      GETCATEGORYDATA(data, category) ;
7     samples  $\leftarrow$ 
      RANDOMSAMPLE(category_data,
        sample_per_category) ;
8     balanced_samples.EXTEND(samples) ;
9   return balanced_samples ;

```

VIII. Page Management

VersaDB implements a dynamic page management system that serves as the fundamental storage unit within shards. Each page implements a hybrid storage format that combines a fixed-size header with variable-length data segments. The page header contains a bitmap indicating record validity, a checksum for data integrity verification, and metadata describing the page's internal organization. The data segment employs a slot-based architecture where each slot maintains offset pointers to record locations, enabling efficient record insertion and deletion without page reorganization.

The system implements page-level compression through a dual-layer mechanism. The outer layer applies compression at the page level using LZ4 for fast compression/decompression, while the inner layer implements column-specific compression schemes based on data characteristics. This hybrid approach optimizes both storage efficiency and access speed by balancing compression ratio with computational overhead.

Pages are organized within shards using a B+ tree structure where leaf nodes contain page metadata and pointers to physical page locations. The system implements a buffer pool that caches frequently accessed pages using a clock-based replacement algorithm. Page eviction follows a dirty-page-first policy where modified pages are persisted to disk before clean pages during memory pressure situations.

Page splits and merges are handled through a copy-on-write mechanism that maintains consistency during concurrent access. When a page exceeds its size threshold,

Algorithm 2: Category-Aware Shuffle

```

// Shuffling tasks while maintaining category
// alignment.
1 Function CATEGORYSHUFFLE(tasks):
    // Calculate the number of samples for each
    // category.
2   category_sizes ←
    COUNTBYCATEGORY(tasks);
    // Create a separate random sequence for each
    // category.
3   category_indices ← [ ] ;
4   for each category in categories do
5       size ← category_sizes[category] ;
6       indices ←
7       GENERATERANDOMSEQUENCE(size) ;
8       category_indices[category] ← indices ;
    // Reconstruct the sequence while maintaining
    // category alignment.
9   aligned_tasks ← [ ] ;
10  for i ← 0 to max_category_size do
11      for each category in categories do
12          if i < category_sizes[category] then
13              index ←
14              category_indices[category][i] ;
15              task ← tasks[category][index] ;
16              aligned_tasks.APPEND(task) ;
17  return aligned_tasks ;

```




Fig. 5. When the local work queue of write thread 2 is empty, it will steal tasks from other queues to ensure load balancing.

the system creates a new page and redistributes records while maintaining a linking structure for sequential access. This approach enables dynamic page size adjustment while preserving data locality and minimizing fragmentation.

For structured data access, the page manager implements row-group-based storage within pages, where records with similar attributes are clustered together. This organization optimizes scan operations by reducing I/O overhead during column-specific queries. The system maintains page-level statistics including record count distributions and value ranges, enabling the query optimizer to make informed decisions about access patterns.

IX. Performance Optimization Modules

A. High-Performance Operators

VersaDB implements optimized sampling and shuffling operators through a multi-layered execution engine. The sampling system utilizes a reservoir sampling algorithm with weighted selection probabilities, as detailed in Algorithm 1. The algorithm maintains a fixed-size reservoir and updates selection probabilities based on category distributions, achieving $O(1)$ space complexity while ensuring representative sampling across categories.

The shuffle operator implements a distributed Fisher-Yates algorithm modified for category awareness, as shown in Algorithm 2. The system first partitions records by category into separate buffers, then applies independent random permutations to each buffer. The final sequence is reconstructed through a merge phase that interleaves samples from different categories while maintaining their relative proportions. This approach achieves $O(n)$ time complexity and ensures uniform distribution across categories.

For execution optimization, both operators implement a pipeline architecture that overlaps I/O operations with computation. The pipeline consists of prefetch, process, and write stages connected through lock-free queues. The prefetch stage implements adaptive read-ahead based on access patterns, while the process stage utilizes SIMD instructions for parallel data transformation when applicable.

B. Parallelization Support

The parallel execution engine implements a task scheduling system based on a work-stealing algorithm. As shown in Fig. 5, parallel write operations are coordinated through a distributed task queue where each writer thread maintains its local task queue. When a thread exhausts its local queue, it attempts to steal tasks from other threads' queues, achieving dynamic load balancing with minimal synchronization overhead. The system implements fine-grained locking through a hierarchical lock manager. Locks

TABLE I
Number of Samples for Different Datasets in Various Domains

Domain	Dataset	Number of Samples
CV	VOC	17,152
	Kitti	7,481
	COCO	118,287
	ImageNet	20,000
NLP	WikiText-103	100,000
	SQuAD2.0	130,319
	The Pile	420,000
Audio	LibriTTS	2174
	Ljspeech	2,426
Multimodal	laion2B-300K	300,000
Video	Youtube8M	1,000,000

TABLE II
Experiment Setting

Experiment	Categories
Hardware Configuration	Machine 1
	CPU INFO: Architecture: x86-64, 64bits+64cores, Clock Speed: 3.9GHz
	DRAM INFO: Total memory size: 251Gi, Configured Memory Speed: 2934 MT/s
	Framework Versions: PyTorch version 2.4.0, TensorFlow version 2.13.1, MindSpore Version 2.2.14.
	Machine 2
	CPU INFO: Model: Kunpeng 920, Architecture: aarch64, 64bits+192cores, Clock Speed: 2.6GHz
	DRAM INFO: Total Memory Size: 755Gi, Configured Memory Speed: 2933 MT/s
	Framework Versions: PyTorch version 2.4.1, TensorFlow version 2.12.0, MindSpore Version 2.4.0.

are acquired at the shard level for write operations and at the page level for read operations, enabling concurrent access to different pages within the same shard. The lock manager uses a timeout-based deadlock prevention mechanism where lock requests are aborted if they cannot be satisfied within a specified time window.

Data consistency during parallel operations is maintained through a multi-version timestamp ordering protocol. Each write operation is assigned a timestamp, and conflicts are detected by comparing operation timestamps. The system implements a write-ahead logging mechanism where log records are grouped by shard and flushed to disk using group commit to optimize I/O performance while ensuring durability.

X. EVALUATION

A. Experimental setup

In this study, we evaluate three AI data management methods, each read by a corresponding AI training framework: LMDB is read by the PyTorch framework, TFRecord is read by the TensorFlow framework, and VersaDB is read by the MindSpore framework. We test these three data structures designed for AI training and compare them with raw dataset loading. The evaluation metrics include data sequential access speed, random access time, data preprocessing time, and resource utilization.

System Configurations: The experiments were conducted on two systems with distinct hardware configurations, as summarized in Table II, to ensure comprehensive evaluation.

Datasets: We evaluated the AI data management methods using various datasets spanning computer vision (CV), natural language processing (NLP), video, multimodal and audio domains. The data volumes tested in these datasets are shown in Table I. Among them, Imagenet, Wikitext [32], The Pile, Laion, and Youtube8M are all subsets of their respective total datasets.

B. Performance analysis

In this experiment, we tested the performance of VersaDB, Lmdb, TFRecord, and Raw data on eleven datasets, evaluating their performance mainly in three tasks: Pure reading, Shuffle reading, and Preprocessing, across two machine environments, as shown in Fig. 6. At the same time, for the three datasets Laion, Youtube8M, and The Pile [33], we did not test preprocessing, as these large-scale datasets are typically preprocessed and dimensionality-reduced for ease of transmission and use. For example, the images in Laion have already undergone feature extraction and are converted into 128-dimensional tensors. The raw format of the Youtube8M dataset is in TFRecord format. It is also important to note that, unless otherwise specified, the speedup comparison is made with the method that perform better between Lmdb and TFRecord.

Machine 1. In the Pure reading task, the speedup of VersaDB compared to Lmdb and TFRecord ranges from 1.2x on the COCO [34] dataset to 3.9x on the Laion [5] dataset. In the Shuffle reading task, VersaDB shows a speedup from 1.06x on the Kitti dataset to 4.3x on the Laion dataset. In the Preprocessing task, the speedup of VersaDB ranges from 1.09x on the libritts [35] dataset to 1.87x on the Kitti dataset.

Machine 2. In Machine Environment 2, VersaDB only failed to maintain superior performance in the The Pile dataset. Below, we will discuss the performance improvements observed in datasets other than The Pile. In the Pure reading task, the speedup of VersaDB compared to Lmdb and TFRecord ranges from 1.1x on the ImageNet [36] dataset to 2.49x on the Youtube8M dataset. In the Shuffle reading task, VersaDB shows a speedup from 1.09x on the Squad dataset to 5.35x on the VOC dataset. In the Preprocessing task, the speedup of VersaDB ranges from 1.06x on the Kitti [37] dataset to 4.12x on the Ljspeech [38] dataset.

This progressive improvement in performance advantages across datasets of increasing complexity demonstrates VersaDB's particular strength in handling sophisticated data types. The results suggest that VersaDB's architecture is especially well-suited for managing complex, multimodal datasets, where its efficient data organization and processing mechanisms provide increasingly significant benefits as data complexity grows.

C. Comparison of Resource consumption

In this experiment, we tested the resource usage of VersaDB, Lmdb, and TFRecord while performing the Shuffle reading task on eleven datasets. The tests were conducted in two machine environments, as shown in Fig. 7.

Machine 1. In Machine Environment 1, VersaDB demonstrated better memory management, with memory consumption reduction effects of 82.9%, 93.02%, 11.2%, 21.81%, 17.56%, 91.2%, 59.07% and 68.66%, respectively for coco, Imagenet, Kitti, Libritts, Ljspeech, Squad [39], VOC, WikiText, Youtube8M. In the Laion dataset, the




Fig. 6. Performance comparison of three different work

peak memory consumption was only 30.6% of TFRecord, but the acceleration compared to TFRecord was 4.4x. In The Pile dataset, although the acceleration compared to TFRecord was higher, the peak memory consumption reached 130% of TFRecord.

Machine 2. In Machine Environment 2, VersaDB shows advantages in memory usage on the COCO, ImageNet, Kitti, The laion and VOC [40] datasets, with memory reduction effects of 49.8%, 81.05%, 78.19%, 22.39% and 79.51%, respectively. In The Pile dataset, similar to Machine Environment 1, our peak memory consumption was the highest among three methods, reaching 160% of TFRecord.

D. Sensitivity Analysis

In this experiment, to test the sensitivity of our database, we conducted tests on eleven datasets across two machine environments, evaluating the performance of TFRecord, VersaDB, and Lmdb under different parallel reading conditions. We set the parallelism levels to 1, 2, 4, 8, and 16. For the Youtube8M dataset, we did not present the Lmdb test results, as its performance significantly lags behind that of VersaDB and TFRecord, making it inconvenient to display together. The result is shown in Fig. 8.

Machine 1. In Machine Environment 1, our VersaDB showed a competitive advantage in all five parallel environments tested, with lower times compared to the other two methods. It maintained high acceleration performance across all parallel environments in LibriTTS, Ljspeech, SQuAD, VOC, Laion, Youtube8M and The Pile. However, in some other datasets, such as Imagenet, the acceleration effect of VersaDB became nearly identical to that of TFRecord in certain parallel environments, showing a decrease in acceleration performance.


Machine 2. In Machine Environment 2, our VersaDB demonstrated a competitive advantage in all five parallel environments across all datasets except The Pile, with shorter run times compared to the other two methods. Moreover, it sustained high acceleration performance across all parallel environments in all datasets except for Imagenet and The Pile. In the Imagenet dataset, the time consumption of VersaDB and TFRecord gradually converged as the parallelism level increased.

We believe that the reason VersaDB performs better in different parallel environments is due to VersaDB's architecture design, which minimizes thread contention through its page-based data organization and independent worker scheduling mechanism.


E. Data parallel reading

In this experiment, we tested the performance of VersaDB, TFRecord, and Lmdb in reading the Kitti, LJSpeech, and Wikitext datasets under different parallel distributed environments. These three datasets represent three common modalities. We used data parallelism for distributed reading, and tested the performance when the number of nodes was 2, 4, and 8. The number of shards in VersaDB was kept consistent with the number of nodes, meaning that when there were 2 nodes, there were 2 shards. Our testing environment consisted of a GPU cluster with eight NVIDIA 3090 GPUs.

Table III show that our database can fully leverage the advantages of multiple nodes, achieving up to 2.3x and 5.3x speedup on the Wikitext and Kitti datasets, respectively. In the LJSpeech dataset, we achieved a 40x speedup when the number of nodes was 8.



(a)



(b)

Fig. 7. Figures (a) and (b) represent the memory consumption rates of LMDB, VersaDB, and TFRecord across the eleven datasets in machine environments 1 and 2, respectively. The time consumed by the three methods is scaled to a unified scale. The x-axis represents the time interval, and the y-axis represents the memory consumption ratio, with consistent units of measurement.

XI. Discussion

A. Fast indexing data

The experimental results demonstrate VersaDB's significant performance advantages, particularly in handling large-scale and complex datasets. Through detailed analysis, we can attribute these performance improvements to several key architectural innovations in our design.

First, VersaDB's page management system with scalar-blob separation proves to be a crucial performance enabler. By segregating scalar data (e.g., labels, metadata) from blob data (e.g., images, audio), the system achieves op-

timized storage and retrieval strategies for different data types.

Second, our hybrid indexing mechanism plays a pivotal role in achieving superior performance while LMDB relies on B+ tree structures. VersaDB implements an adaptive indexing strategy that dynamically optimizes based on data characteristics and access. This design proves particularly effective in scenarios involving random access patterns.

Third, our schema-based data organization system enables efficient handling of complex data structures. Unlike TFRecord's fixed serialization approach or LMDB's key-




Fig. 8. Figures (a) and (b) show the test data for Lmdb, VersaDB, and TFRecord on eleven datasets in machine environments 1 and 2, respectively. We set five parallelism levels: 1, 2, 4, 8, and 16. The x-axis represents the number of parallel workers, and the y-axis represents the consumption time.

	Shard num	Distributed reading		
		VersaDB	TFRecord	Lmdb
Kitti	2	4.62	8.03	9.9
	4	1.15	6.4	6.13
	8	1.04	6.08	4.34
Ljspeech	2	0.1	2.09	1.24
	4	0.051	1.25	1.16
	8	0.036	1.6	1.45
Wikitext	2	5.43	68.6	8.57
	4	2.04	34	4.66
	8	1.26	63.5	2.67

TABLE III

Performance comparison under different number of distributed nodes

timized representation and access patterns tailored to specific data types.

B. Resource management

Our resource utilization experiments reveal significant efficiency advantages of VersaDB in memory usage at most of time. These efficiency gains can be attributed to several key architectural designs that specifically target resource optimization. The most notable improvement comes from our innovative page management system, which demonstrates remarkable memory efficiency.

First, our scalar-blob separation strategy, which enables selective loading of data components.

value paradigm, VersaDB's flexible schema allows op-

Second, our dynamic page replacement policy, which efficiently manages memory allocation and deallocation based on actual usage patterns

These resource efficiency improvements directly address critical challenges in modern AI workflows. The significant reduction in memory usage enables processing of larger datasets on existing infrastructure, reducing hardware requirements and associated costs.

XII. conclusion

In this paper, we tested various datasets include NLP, CV, multimodal, and audio datasets. VersaDB consistently maintains a performance advantage in Pure Reading, Shuffle Reading, and Preprocessing tasks under default settings in two common machine environments, with acceleration ranging from 1.06x to 5.35x, except for The Pile dataset tested in Machine Environment 2. In Machine Environment 1, VersaDB has lower memory usage compared to LMDB and TFRecord at most of time, but in Machine Environment 2, it exhibits higher memory consumption for audio and NLP datasets. We also tested performance across different parallelism levels, and VersaDB showed performance advantages at all parallelism levels in both machine environments except for The Pile dataset tested in Machine Environment 2. We also tested the reading performance under different distributed parallel environments on three common modality datasets, and VersaDB consistently maintained a performance advantage in all environments.

In conclusion, VersaDB demonstrates strong performance and resource management across different categories of datasets, maintaining a good adaptability to various machine environments and architectures.

XIII. Limitation and future work

In terms of memory consumption, we found that on the AARCH64 architecture, VersaDB consumes more memory than LMDB and TFRecord in NLP and audio datasets, while on the x86-64 architecture, this occurs only in The Pile dataset.

In terms of performance, after testing, the performance of VersaDB on The Pile dataset in the AARCH64 architecture was not ideal. Therefore, in the future, we will focus on further optimizations for the AARCH64 architecture to achieve consistent high performance across mainstream machine architectures.

In terms of usability, we will continue to track popular datasets and provide APIs for converting these datasets to the VersaDB format. At the same time, we will also consider the compatibility of conversions between different AI data formats. For example, the conversion from TFRecord to VersaDB currently does not support converting TFRecord's variable data types.

References

- [1] Paul Pu Liang, Amir Zadeh, and Louis-Philippe Morency. Foundations & trends in multimodal machine learning: Principles, challenges, and open questions. *ACM Computing Surveys*, 56(10):1–42, 2024.
- [2] Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *Nature*, 521(7553):436–444, 2015.
- [3] Peng Xu, Xiatian Zhu, and David A Clifton. Multimodal learning with transformers: A survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(10):12113–12132, 2023.
- [4] Soravit Changpinyo, Piyush Sharma, Nan Ding, and Radu Soricut. Conceptual 12m: Pushing web-scale image-text pre-training to recognize long-tail visual concepts. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 3558–3568, 2021.
- [5] Christoph Schuhmann, Richard Vencu, Romain Beaumont, Robert Kaczmarczyk, Clayton Mullis, Aarush Katta, Theo Coombes, Jenia Jitsev, and Aran Komatsuzaki. Laion-400m: Open dataset of clip-filtered 400 million image-text pairs. *arXiv preprint arXiv:2111.02114*, 2021.
- [6] Jimuyang Zhang, Minglan Zheng, Matthew Boyd, and Eshed Ohn-Bar. X-world: Accessibility, vision, and autonomy meet. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9762–9771, 2021.
- [7] Yun-Chen Lo, Jun-Shen Wu, Chia-Chun Wang, Yu-Chih Tsai, Chih-Chen Yeh, Wen-Chien Ting, and Ren-Shuo Liu. Issa: Architecting cnn accelerators using input-skippable, set-associative computing-in-memory. *IEEE Transactions on Computers*, 73(9):2136–2149, 2024.
- [8] Hai Jin, Dan Chen, Long Zheng, Yu Huang, Pengcheng Yao, Jin Zhao, Xiaofei Liao, and Wenbin Jiang. Accelerating graph convolutional networks through a pim-accelerated approach. *IEEE Transactions on Computers*, 72(9):2628–2640, 2023.
- [9] Rui Han, Chi Harold Liu, Shilin Li, Shilin Wen, and Xue Liu. Accelerating deep learning systems via critical set identification and model compression. *IEEE Transactions on Computers*, 69(7):1059–1070, 2020.
- [10] Sarunya Pumma, Min Si, Wu-chun Feng, and Pavan Balaji. Parallel i/o optimizations for scalable deep learning. In *2017 IEEE 23rd International Conference on Parallel and Distributed Systems (ICPADS)*, pages 720–729. IEEE, 2017.
- [11] Jayashree Mohan, Amar Phanishayee, Ashish Raniwala, and Vijay Chidambaram. Analyzing and mitigating data stalls in dnn training. *arXiv preprint arXiv:2007.06775*, 2020.
- [12] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.
- [13] Hang Huang, Jia Rao, Song Wu, Hai Jin, Hong Jiang, Hao Che, and Xiaofeng Wu. Towards exploiting cpu elasticity via efficient thread oversubscription. In *Proceedings of the 30th International Symposium on High-Performance Parallel and Distributed Computing*, pages 215–226, 2021.
- [14] Weijian Chen, Shuibing He, Yaowen Xu, Xuechen Zhang, Siling Yang, Shuang Hu, Xian-He Sun, and Gang Chen. icache: An importance-sampling-informed cache for accelerating i/o-bound dnn model training. In *2023 IEEE International Symposium on High-Performance Computer Architecture (HPCA)*, pages 220–232. IEEE, 2023.
- [15] Apurva Agrawal and Yusuf Mamajiwala. Comparative analysis of rocksdb, lmdb, and mongodb: A performance evaluation. Technical report, SAE Technical Paper, 2024.
- [16] Apurva Agrawal and Yusuf Mamajiwala. Comparative analysis of rocksdb, lmdb, and mongodb: A performance evaluation. Technical report, SAE Technical Paper, 2024.
- [17] Satish Chikkamath and SR Nirmala. Music detection using deep learning with tensorflow. In *ICDSMLA 2020: Proceedings of the 2nd International Conference on Data Science, Machine Learning and Applications*, pages 283–291. Springer, 2022.
- [18] Mohammed Noman, Vladimir Stankovic, and Ayman Tawfik. Object detection techniques: Overview and performance comparison. In *2019 IEEE International Symposium on Signal Processing and Information Technology (ISSPIT)*, pages 1–5, 2019.
- [19] Diwakar Chaudhary, Muntather Almusawi, Abdul Redha Hussein Sabr, Manisha Aeri, Adnan Allwi Ftaiet, Nabaa Kareem Taaban, and Mustafa Mudhafar. The plant's leaf identification using gan and using ia technique. In *2024 4th International Conference on Advance Computing and Innovative Technologies in Engineering (ICACITE)*, pages 1376–1380. IEEE, 2024.

- [20] Ekaba Bisong and Ekaba Bisong. Tensorflow 2.0 and keras. Building Machine Learning and Deep Learning Models on Google Cloud Platform: A Comprehensive Guide for Beginners, pages 347–399, 2019.
- [21] Tianle Zhong, Jiechen Zhao, Xindi Guo, Qiang Su, and Geoffrey Fox. Rinas: Training with dataset shuffling can be general and fast. arXiv preprint arXiv:2312.02368, 2023.
- [22] Qi Meng, Wei Chen, Yue Wang, Zhi-Ming Ma, and Tie-Yan Liu. Convergence analysis of distributed stochastic gradient descent with shuffling. *Neurocomputing*, 337:46–57, 2019.
- [23] Haidong Li, Jiongcheng Li, Xiaoming Guan, Binghao Liang, Yuting Lai, and Xinglong Luo. Research on overfitting of deep learning. In 2019 15th international conference on computational intelligence and security (CIS), pages 78–81. IEEE, 2019.
- [24] Felipe Pezosa, Juan L Reutter, Fernando Suarez, Martín Ugarte, and Domagoj Vrgoč. Foundations of json schema. In Proceedings of the 25th international conference on World Wide Web, pages 263–273, 2016.
- [25] Matthias Langer, Zhen He, Wenny Rahayu, and Yanbo Xue. Distributed training of deep learning models: A taxonomic perspective. *IEEE Transactions on Parallel and Distributed Systems*, 31(12):2802–2818, 2020.
- [26] Tadas Baltrušaitis, Chaitanya Ahuja, and Louis-Philippe Morency. Multimodal machine learning: A survey and taxonomy. *IEEE transactions on pattern analysis and machine intelligence*, 41(2):423–443, 2018.
- [27] Mohammad Soleymani, David Garcia, Brendan Jou, Björn Schuller, Shih-Fu Chang, and Maja Pantic. A survey of multimodal sentiment analysis. *Image and Vision Computing*, 65:3–14, 2017.
- [28] Soujanya Poria, Erik Cambria, Rajiv Bajpai, and Amir Hussain. A review of affective computing: From unimodal analysis to multimodal fusion. *Information fusion*, 37:98–125, 2017.
- [29] Chandrima Sarkar, Sumit Bhatia, Arvind Agarwal, and Juan Li. Feature analysis for computational personality recognition using youtube personality data set. In Proceedings of the 2014 ACM multi media on workshop on computational personality recognition, pages 11–14, 2014.
- [30] Gerald Krell, Michael Glodek, Axel Panning, Ingo Siegert, Bernd Michaelis, Andreas Wendemuth, and Friedhelm Schwenker. Fusion of fragmentary classifier decisions for affective state recognition. In *Multimodal Pattern Recognition of Social Signals in Human-Computer-Interaction: First IAPR TC3 Workshop, MPRSS 2012, Tsukuba, Japan, November 11, 2012, Revised Selected Papers 1*, pages 116–130. Springer, 2013.
- [31] Patrick O’Neil, Edward Cheng, Dieter Gawlick, and Elizabeth O’Neil. The log-structured merge-tree (lsm-tree). *Acta Informatica*, 33:351–385, 1996.
- [32] Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. arXiv preprint arXiv:1609.07843, 2016.
- [33] Leo Gao, Stella Biderman, Sid Black, Laurence Golding, Travis Hoppe, Charles Foster, Jason Phang, Horace He, Anish Thite, Noa Nabeshima, et al. The pile: An 800gb dataset of diverse text for language modeling. arXiv preprint arXiv:2101.00027, 2020.
- [34] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *Computer Vision–ECCV 2014: 13th European Conference, Zurich, Switzerland, September 6–12, 2014, Proceedings, Part V 13*, pages 740–755. Springer, 2014.
- [35] Heiga Zen, Viet Dang, Rob Clark, Yu Zhang, Ron J Weiss, Ye Jia, Zhifeng Chen, and Yonghui Wu. Libritts: A corpus derived from librispeech for text-to-speech. arXiv preprint arXiv:1904.02882, 2019.
- [36] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Communications of the ACM*, 60(6):84–90, 2017.
- [37] Andreas Geiger, Philip Lenz, and Raquel Urtasun. Are we ready for autonomous driving? the kitti vision benchmark suite. In 2012 IEEE conference on computer vision and pattern recognition, pages 3354–3361. IEEE, 2012.
- [38] Keith Ito and Linda Johnson. The lj speech dataset. <https://keithito.com/LJ-Speech-Dataset/>, 2017.
- [39] P Rajpurkar. Squad: 100,000+ questions for machine comprehension of text. arXiv preprint arXiv:1606.05250, 2016.
- [40] Mark Everingham, Luc Van Gool, Christopher KI Williams, John Winn, and Andrew Zisserman. The pascal visual object classes (voc) challenge. *International journal of computer vision*, 88:303–338, 2010.