

Privacy-Preserving Full-Body Meshing from mmWave Radar via Mesh Foundation Model Supervision

Shuxing Zhang*, Yongquan Ni, Zhenyu Ding, Yawen Lin
AI Value Center, Incaier (Haier), Qingdao, China

Abstract

Millimeter-wave (mmWave) radar enables privacy-preserving human perception, but the extreme sparsity of point clouds from commercial single-chip sensors (mean ≈ 6.5 points/frame; $\approx 28\%$ empty frames) has confined prior art to body-part keypoints or discrete action classification. We present a cross-modal teacher–student framework that lifts commercial radar to *full-body, per-frame, metric 3D mesh reconstruction with per-joint uncertainty*. Three innovations: (1) a **mesh-foundation-model teacher** — SAM 3D Body produces whole-body MHR ground truth (70 joints, 18,439 mesh vertices) from a single RGB frame with zero training, slashing annotation cost by orders of magnitude; (2) **StudentPoseFormer** — set encoding with masked attention pooling, a temporal Transformer, and a **CVAE multi-hypothesis head** that outputs both the pose mean and per-joint variance, honestly reporting where the radar cannot see; and (3) a **multi-stage ground-truth quality pipeline** (confidence gating, depth validation, temporal smoothing, bone-length consistency, bad-frame rejection) plus systematic *information-lever ablations*. On the public MM-Fi benchmark (same TI IWR6843 sensor, cross-subject), our full configuration reaches 7.45 cm 12-joint MPJPE, with ablations proving the causal value of point accumulation ($k = 3$, -0.34 cm), Doppler (-0.85 cm; -2 cm at the wrist on fast actions), and velocity loss (-0.27 cm). On our own synchronized radar + RGB-D corpus with block-level held-out splits, the pipeline achieves 21.47 cm end-to-end (per-joint hierarchy from 4.8 cm at the hip to 34.7 cm at the wrist — matching physical information limits), could be improved to 15 cm with $\sim 30k$ *diverse* samples, and a scaling law shows sample diversity, not volume, is the binding constraint. Deployment inference is radar-only — no camera, no image.

Index Terms — millimeter-wave radar, human pose estimation, privacy-preserving sensing, cross-modal distillation, probabilistic modeling, CVAE, mesh foundation model.

1 Introduction

Human perception indoors underpins elderly care, smart wards, and ambient assisted living. Cameras deliver rich reconstruction but capture identifiable visual information — a privacy risk that is structurally unacceptable in bedrooms or bathrooms [1, 2]. Millimeter-wave radar (30–300 GHz) outputs only sparse 3D points with radial velocity: it is inherently blind to faces and clothing, works in darkness and smoke, and is therefore the sensor of choice for privacy-sensitive sensing [3].

The field has progressed through three waves, each held back by the same root cause — **radar point clouds from commercial single-chip sensors are extremely sparse** (mean ≈ 6.5 detections/frame in our commercialization-grade device; 28% of frames empty): presence detection and *micro-Doppler action classification* [4, 5]; then *body-part* estimation (hand-gesture keypoints [6]);

*Corresponding author.

and most recently *deterministic* full-body joint regression [7, 8]. None achieves what downstream applications actually need: a **continuous, metric, full-body 3D mesh with a quantified statement of how much to trust each joint**, deployed with **zero visual input**.

Our work closes this gap with a cross-modal teacher–student formulation (Fig. 1):

- **Training** (offline, where cameras are permitted): a commercial radar (TI IWR6843) and an RGB-D camera (ORBEC Femto Bolt) synchronously capture the same scene. A frozen **mesh foundation model (SAM 3D Body)** [9] converts each RGB frame into whole-body 3D joints, mesh vertices, and parametric pose — **zero-shot**. The pseudolabels pass a five-stage quality gating, then supervise a radar-only student.
- **Deployment**: only the radar together with the trained student. No camera, no teacher, no image — privacy by physical design.

This paper makes four contributions:

1. **Mesh-foundation-model supervision at deployment-grade hardware** (Sec. 3.1): SAM 3D Body as an automatic, zero-training 3D-mesh teacher on a *commercial black-box radar* — versus Kinect/MoCap arrays or 12-camera triangulation at orders-of-magnitude higher cost.
2. **StudentPoseFormer** (Sec. 3.2): set encoding with masked attention pooling, a temporal Transformer, and a **CVAE head** whose prior-sampling yields both pose mean *and* per-joint uncertainty — a calibrated “known unknowns” signal missing from all deterministic regressors (cf. mid-joint 4.8 cm vs. wrist 34.7 cm errors).
3. **Quality-controlled pseudo-GT pipeline** (Sec. 3.3) transforming monocular mesh outputs into metric, radar-frame, quality-verified supervision through depth anchoring and trajectory-based extrinsic calibration.
4. **An information-lever ablation study** (Sec. 4): causal evidence that Doppler, temporal point accumulation, and velocity supervision each buy accuracy where physics allows, *and* a scaling-law finding that **diversity, not volume, binds** (our within-distribution exponent $b \approx 0.12$ vs. the MM-Fi anchor’s $b \approx 0.65$ — over $100\times$ slope difference).

2 Related Work

Cross-modal RF supervision. RF-Pose [1] and RF-Pose3D [2] pioneered “vision as a teacher for radio students” with wall-penetrating radars; both are offline or non-deployable on commodity hardware. We inherit the *paradigm* but with mmWave point clouds and a modern mesh teacher.

mmWave point-cloud pose and mesh estimation. MARS [7] (5.87 cm on a MoCap-labeled corpus) and mmMesh [8] (2.47 cm vertex error via SMPL) used development-kit radars with tunable point density plus Kinect/MoCap ground truth. We are the first to target **commercial fixed-parameter sparse point clouds** (a distinct, sparser, more realistic regime) while keeping mesh-level output. mm-Pose [10] and PointTS [11] further advance point-cloud-based pose estimation; yet all produce deterministic single hypotheses. mmDiff [12] (6.5 cm, ECCV’24) uses conditional diffusion to represent one-to-many ambiguity; we instead exploit a lightweight CVAE that simultaneously yields per-joint uncertainty, which we position as an *honesty* value rather than a pure accuracy trick.




Figure 1: Overall framework. **Left — training:** the commercial mmWave radar and an RGB-D camera synchronously capture the same scene; a frozen mesh foundation model (SAM 3D Body) converts each RGB frame into whole-body 3D pseudolabels, which must pass a five-stage quality gate before they supervise the radar-only student. **Right — deployment:** only the radar and the trained student run. The dashed box lists the modules that are physically absent, so privacy is guaranteed by construction rather than by policy.

Foundation-model-based pseudolabeling. Large monocular mesh models (e.g., SAM 3D Body [9]) have radically lowered 3D supervision cost; to our knowledge none has been paired with mmWave students in a calibrated cross-modal pose pipeline.

Benchmarks. MM-Fi [3] provides exactly our sensor (TI IWR6843) with 40 subjects $\times$ 27 actions $\times$ 320k frames, enabling fair, reproducible cross-subject comparisons.

Compared with recent state of the art, our method is a *system-level* contribution (cheap mesh teacher + commercial radar + honest uncertainty + causal ablations) and — measured at equal configuration — is the strongest published result on commercial-fixed-parameter radar, rather than a claim of absolute superiority over development-kit configurations.

3 Method

3.1 Cross-Modal Training with a Mesh Foundation Model Teacher

(a) Data acquisition and alignment. During training, the radar outputs per-frame point clouds and target tracks (`trackData.tid`); the RGB-D camera outputs color plus depth. All streams are hardware-timestamped on one host; radar frames are paired to camera frames by nearest-neighbor timestamp matching (median inter-sensor jitter ≈ 11 ms in our corpus) and spatially aligned through per-session extrinsics (Fig. 6).

(b) Teacher pseudolabels. Each paired RGB frame is fed to a frozen SAM 3D Body teacher that produces: 70 3D joint locations in the camera frame, `body_pose_params`[133] (MHR joint rotations), `global_rot`[3] (root orientation), and an 18,439-vertex MHR mesh. The 70-keypoint set maps deterministically to COCO-17 and subsequently to our BODY-13 supervisory skeleton (head plus 12 limb joints).




Figure 2: Point-cloud sequence representation. **Top:** the radar emits a variable number of detections per frame and some frames are empty. **Middle:** a sliding window of $T=5$ frames centered on the target frame t is zero-padded into a fixed $[T, M, 5]$ tensor whose channels are $(x, y, z, \text{doppler}, \text{snr})$. **Bottom:** the companion binary mask $[T, M]$ flags real detections (white, 1) versus padding (gray, 0); fully masked frames are mapped to a learned empty-frame embedding.

(c) **Depth anchoring.** Monocular estimation carries a depth-scale and `cam.t` bias: the mesh root is therefore anchored to sensor-measured depth (the RGB-D depth at the person’s location) so that the pseudolabels become **metric**, and a per-pixel depth-versus-estimate check gates obvious misestimates.

(d) **Extrinsic calibration.** During a dedicated walking phase, radar centroid trajectories are rigidly aligned to depth-anchored camera-space trajectories by Umeyama rigid registration with RANSAC robustness, yielding metric radar-frame ground truth including absolute translation:

$$\mathbf{p}_{\text{radar}} = \mathbf{R} \mathbf{p}_{\text{cam}} + \mathbf{t}, \quad (\mathbf{R}, \mathbf{t}) = \arg \min_{\mathbf{R}, \mathbf{t}} \sum_i \|\mathbf{R} \mathbf{p}_i^{\text{cam}} + \mathbf{t} - \mathbf{q}_i^{\text{radar}}\|^2. \quad (1)$$

3.2 StudentPoseFormer

Input representation. Each frame contains up to M detections, each described by a five-dimensional feature $[x, y, z, \text{doppler}, \text{snr}]$ (meters, m/s, dB). A sliding window of $T=5$ frames centered on the target frame forms a $[T, M, 5]$ tensor together with a $[T, M]$ binary validity mask (Fig. 2); empty frames are fully masked and mapped to a learned empty-frame embedding. Multi-frame accumulation mitigates sparse spatial coverage, and the Doppler channel contributes a radar-only information dimension (radial motion, whose sign flips with direction).

Set encoder. A shared MLP ($5 \rightarrow 64 \rightarrow 128 \rightarrow 256$, ReLU + LayerNorm) maps each point.




Figure 3: StudentPoseFormer architecture. **Stage 1:** a shared per-point MLP followed by masked attention pooling compresses each frame’s variable-size point set into one 256-d embedding (padded points are masked to $-\infty$ in the attention logits, making empty frames NaN-safe). **Stage 2:** a 4-layer, 8-head Transformer fuses the $T=5$ frame embeddings; the target-frame output is the human condition feature $\mathbf{c}$. **Stage 3:** at inference the CVAE head draws $K=20$ latent samples from the prior; the per-joint mean is the pose estimate and the per-joint variance is the uncertainty. **Stage 4:** an MHR head shares the fused latent ($\mathbf{c} \parallel \mathbf{z}$) and decodes a 18,439-vertex body mesh.

Masked attention pooling computes point weights by dot-product attention with the mean feature as query, masks padded points to $-\infty$ (NaN-safe for empty frames), and aggregates each frame into a single 256-d embedding:

$$\alpha_{t,m} = \frac{\exp(\mathbf{w}^\top \mathbf{h}_{t,m} / \sqrt{d})}{\sum_{m' \in \mathcal{V}_t} \exp(\mathbf{w}^\top \mathbf{h}_{t,m'} / \sqrt{d})}, \quad \mathbf{e}_t = \sum_{m \in \mathcal{V}_t} \alpha_{t,m} \mathbf{h}_{t,m}, \quad (2)$$

where $\mathbf{h}_{t,m}$ is the encoded point feature, $\mathbf{w}$ the (mean-derived) query, and $\mathcal{V}_t$ the set of valid indices in frame t . Masked pooling is robust to varying clutter: with few valid points the surviving points simply earn higher weights.

Temporal encoder. Frame embeddings add sinusoidal positional encodings and pass through a 4-layer, 8-head Transformer; the target-frame output is the human-condition feature $\mathbf{c}$ (Fig. 3).

CVAE multi-hypothesis head. Sparse radar yields one-to-many ambiguity: the same point cloud admits many plausible poses (Fig. 4). In training, an encoder $q_\phi(z \mid \text{GT}, \mathbf{c})$ maps the ground-truth joints and $\mathbf{c}$ to latent parameters (μ, σ) ; reparameterization samples z (dimension 32) and a decoder outputs 17×3 joints. A KL term regularizes the posterior toward a unit Gaussian, with β annealed from 0 to 1 over the first 20% of the schedule to prevent posterior collapse. At inference the posterior encoder is removed: we sample $z \sim \mathcal{N}(0, I)$ $K=20$ times, take the **per-joint mean** as the pose estimate and the **per-joint variance** as the uncertainty — small at well-observed trunk joints, large at distal wrists and ankles (Fig. 9), thus acting as an honest annotation of the perception boundary for downstream modules.

Parametric mesh head. A second MLP head shares the fused latent ($\mathbf{c} \parallel \mathbf{z}$) and regresses the MHR parameters `body_pose[133]`, `global_rot[3]` and shape `$\beta[10]$` , which decode into an 18,439-vertex mesh; joint training shares the uncertainty-aware backbone.

Losses.

$$\mathcal{L} = \mathcal{L}_{\text{pos}} + 0.1 \mathcal{L}_{\text{bone}} + 0.05 \mathcal{L}_{\text{vel}} + \beta \mathcal{L}_{\text{kl}}, \quad (3)$$

where $\mathcal{L}_{\text{pos}}$ is the validity-masked MPJPE over the K -hypothesis mean, $\mathcal{L}_{\text{bone}}$ enforces anatomical bone-length consistency against the teacher bone lengths (L1 per segment), and $\mathcal{L}_{\text{vel}}$ is an inter-frame velocity-alignment term that penalizes failure to track fast motion. Distal joints are down-weighted during training ($w = 2.0$ for distal emphasis in the reported metrics). We use Adam with learning rate 3×10^{-4} under cosine annealing to 1×10^{-5} , batch size 64 for the deterministic spine and 32–64 for the CVAE (batch ≤ 64 keeps the KL well calibrated), for 80–120 epochs.




Figure 4: The CVAE multi-hypothesis head in training and inference. **(a) Training:** a posterior encoder maps the teacher ground truth and the condition feature $\mathbf{c}$ to latent parameters (μ, σ) ; reparameterization samples z , a decoder reconstructs the joints, and a KL term (with β annealed from 0 to 1 over the first 20% of the schedule to prevent posterior collapse) regularizes the posterior toward a unit Gaussian. **(b) Inference:** the posterior encoder is discarded — the radar never sees the GT — and $K=20$ latents are drawn from the standard normal prior. The per-joint mean over the K decoded hypotheses is the pose estimate, and the per-joint variance is the uncertainty signal.

3.3 Teacher-Label Quality Control (Five-Stage Gating)

Candidate pseudolabels are propagated only when every stage passes (Fig. 5): (1) **confidence gating** — teacher 2D/3D confidence above a per-joint threshold; (2) **depth validation** — joints inside the RGB-D range envelope and not in depth holes; (3) **temporal smoothing** — One-Euro filtering across time to remove single-frame outliers; (4) **bone-length consistency** — per-frame bone lengths within tolerance of the subject’s median, since segment kinematics are bounded; (5) **bad-frame rejection** — frames with insufficient valid joints are dropped entirely. Only gated labels serve as supervision, and invalid joints are excluded from losses and metrics rather than imputed.

3.4 Deployment (Radar-Only)

A FIFO buffer accumulates the latest T frames and the ensemble {set encoder $\rightarrow$ temporal Transformer $\rightarrow$ prior sampling $\rightarrow$ mean/variance + MHR head} runs per frame (Fig. 7). Multi-person scenes are handled by splitting points per radar track ID (`trackData.tid`), with per-target state machines and a one-frame track-index displacement correction (Fig. 8). The output is a 17-joint skeleton, a mesh, and per-joint confidence at radar frame rate (> 10 FPS at $3\times$ CPU inference).




Figure 5: Five-stage quality control for teacher pseudolabels. A candidate frame is propagated to training only if every stage passes: (1) per-joint teacher 2D/3D confidence above threshold; (2) joints inside the RGB-D range envelope and away from depth holes; (3) One-Euro temporal filtering removes single-frame outliers; (4) per-frame bone lengths within tolerance of the subject’s median (segment kinematics are bounded); (5) frames with too few valid joints are dropped entirely. Rejected joints are excluded from all losses and metrics rather than being imputed.

4 Experiments

Setup (MM-Fi). We use the public MM-Fi benchmark [3], which provides exactly our sensor (TI IWR6843). The cross-subject split trains on S01–S07 and tests on S08–S10 over 27 action classes; windows are drawn from $[T, 128, 5]$ tensors with accumulation $k=3$, learning rate 3×10^{-4} , batch 256 and 100 epochs. Metrics are the 12 shared-limb MPJPE (cm), PA-MPJPE (mm) and a moving-track reliability score `track_r`. All configurations follow a single-variable-change protocol (the G-series), so every row isolates one information lever.

4.1 Cross-Subject Accuracy and Ablations

G1 — data scale $\neq$ diversity. Expanding from 10 to 27 action classes leaves MPJPE flat (8.07 vs. 8.06 cm). We report this as a *valuable negative result*: the binding constraint is the information content of the input, not action coverage.




Figure 6: Cross-modal spatiotemporal alignment. (i) **Temporal:** radar frames are paired to camera frames by nearest-neighbor matching of hardware timestamps (median inter-sensor jitter ≈ 11 ms in our corpus). (ii) **Spatial:** monocular mesh estimates carry a depth-scale and `cam.t` bias, so the mesh root is first anchored to the RGB-D measured depth, making the labels metric; per-session extrinsics $(\mathbf{R}, \mathbf{t})$ then map teacher joints from the camera frame into the radar frame via $\mathbf{p}_{\text{radar}} = \mathbf{R} \mathbf{p}_{\text{cam}} + \mathbf{t}$, where $(\mathbf{R}, \mathbf{t})$ is estimated by RANSAC-robust Umeyama registration of radar centroid trajectories against depth-anchored camera trajectories recorded during a dedicated walking phase.

G2 — causal value of accumulation. Point accumulation with $k=3$ buys -0.34 cm overall and produces the first loosening of the wrist wall (~ 1 cm: $15.5 \rightarrow 14.5$). However $k=5$ saturates the spatial extent and motion smear begins to hurt fast actions (A10: $14.65 \rightarrow 15.88$) — the optimum is interior, not monotone.

G3 — Doppler is used, and matters most in fast motion. Zeroing the Doppler channel costs $+0.85$ cm overall, ≈ 2 cm at the wrist and $+1.7$ cm on the fast action A10. The -0.59 fluctuation on A19 does not change the direction. The radar-only velocity dimension is therefore genuine information rather than a dormant column.

G4 — velocity supervision. Setting the velocity weight $v_w=1.0$ improves all measures ($7.70 \rightarrow 7.45$ cm; A10 -0.57 cm): penalizing motion under-reach on the loss side complements providing Doppler on the input side.

Per-joint hierarchy. Errors rise monotonically from proximal to distal joints (hip 1.7 cm $\rightarrow$ wrist 14.3 – 15.5 cm), matching the physical law reported for RF-Pose3D [2]: large, slow, well-illuminated surfaces are estimated best.

4.2 End-to-End Results on Our Own Synchronous Corpus

Our corpus contains six sessions of one subject performing rich actions (walking, falling, reaching up, stretching, sitting/squatting), yielding 3,488 teacher frames and 2,176 usable samples (1,576 train / 600 validation). We use **block-level held-out splits**: two contiguous 50-frame blocks per session are reserved for validation with a 4-frame leakage buffer on each side, so no temporally adjacent frame crosses the split. The same pipeline runs end-to-end without modification.




Figure 7: Deployment runs radar-only. A FIFO buffer maintains the most recent T frames, which are packed into the $[T, M, 5]$ input tensor and passed through the student’s forward computation to produce the skeleton, mesh, and per-joint confidence at radar frame rate. The dashed box isolates everything that is *not* present — no camera, no teacher, no pseudolabel generation — making the privacy boundary a physical property of the deployment rather than an access-control policy.

The per-joint ordering is identical to MM-Fi and, importantly, honest:

$$\begin{aligned} \text{hip } 4.8/5.0 < \text{knee } 16.4/17.6 < \text{shoulder } 19.3/19.8 < \text{ankle } 22.4/22.9 \\ < \text{head } 25.3 < \text{elbow } 27.4/28.0 < \text{wrist } 34.7/35.4 \quad (\text{cm}) \end{aligned}$$

The end-to-end 21.5 cm on hard multi-action data with strict splits is *not* a regression relative to the 16.6 cm we previously measured with a single-walker 80/20 random split — that earlier figure is inflated by temporal autocorrelation between adjacent frames leaking across the split. Qualitative frame triads (RGB | teacher | radar-student) confirm that large-amplitude poses (arms overhead, bends, stretches) are tracked frame by frame, with a known under-amplitude bias on unseen stretch poses, consistent with the wrist number.

4.3 Scaling Law: Diversity, Not Volume

We construct two families of training subsets: family A truncates in time (all frames from the first fraction of each session) while family B subsamples uniformly to preserve coverage. Fitting the within-distribution error to a power law gives

$$\text{err}(n) = 53.8 \cdot n^{-0.124}. \quad (4)$$

Extrapolating (Fig. 10), reaching 15 cm would require $\sim 30\text{k}$ in-distribution samples ($19\times$ the current amount), 12 cm would require 185k, and 10 cm would require 810k — “more of the same” is a dead end. Yet the MM-Fi anchor, which uses the *same* architecture and sensor but 6,860 samples spread over 40 subjects, reaches 8.3 cm cross-subject, implying a slope of $b \approx 0.65$ — over $100\times$ steeper. The binding variable is therefore per-sample diversity (subjects $\times$ poses $\times$ positions), not sample count. This is the single most actionable finding of the paper: collection budget should buy diversity.




Figure 8: Multi-person handling by track-ID demultiplexing. The radar’s own tracker tags each detection with a target ID (`trackData.tid`); points are split per ID into independent temporal windows and state machines, with a one-frame track-index displacement correction to absorb ID flicker. The same student weights are applied to each target independently, yielding one pose, mesh, and uncertainty vector per person.

5 Discussion and Limitations

Uncertainty as honesty. The CVAE variance is a proxy uncertainty that must be interpreted relative to calibration. We validate that it correlates with joint type (a five-point scale from confident hips to divergent wrists), but we do not yet claim posterior calibration curves. Batch size ≤ 64 was required to keep the mean per-joint standard deviation physically interpretable.

Supervision is monocular. Ground-truth noise at depth edges propagates to the student, so our per-joint error floor is bounded by teacher quality; the metric correction of Sec. 3.1 helps but does not reach motion-capture precision.

Scaling to subjects. Block-level splits with a single subject are insufficient to establish cross-subject generalization. Our plan is 3–4 subjects performing natural transitions in the final room, targeting a defensible 12–15 cm cross-session figure.

Orientation. The `global_rot` MSE of 0.908 remains the single-radar heading wall: radar-only facing estimates and “pseudo-forward” assumptions are unreliable whenever subjects do not walk toward the sensor.

Ethics. The entire training set uses informed-consent RGB-D data. Raw image frames are never present at inference time nor in any public artifact.

6 Conclusion

We introduced a cross-modal teacher–student system that lifts **commercial** mmWave radar to full-body mesh reconstruction with per-joint uncertainty, where traditional pipelines stop at clas-




Figure 9: Per-joint uncertainty produced by the CVAE head, shown as confidence circles on the estimated skeleton (radius $\propto$ per-joint standard deviation over K prior samples). Trunk joints that reflect strongly off large, slow surfaces (hips, shoulders, neck) are tightly concentrated; distal joints with small radar cross-section and fast motion (wrists, ankles) carry large, honest uncertainty. The system therefore annotates its own perception boundary: downstream applications can trust the trunk while treating the extremities as low-confidence.

sification or partial keypoints. The mesh foundation model teacher eliminates costly manual 3D annotation; the CVAE head expresses a trustworthy perception boundary; and deployment runs radar-only, so privacy holds by construction. On MM-Fi (cross-subject) the configuration reaches 7.45 cm 12-joint MPJPE, with ablations demonstrating the causal value of Doppler (-2 cm at the wrist), point accumulation (optimum $k=3$) and velocity supervision. On our own synchronous corpus the same pipeline yields an end-to-end 21.47 cm with an honest per-joint hierarchy, and the accompanying scaling equation carries one main message: *collect diverse poses, not more of the same*. The companion patent (application number available) covers the system-level claims; this paper validates them through reproducible experiments.

Acknowledgment

The authors thank the contributors of SAM 3D Body and MM-Fi, and the reviewers of the companion patent application.

References

- [1] Mingmin Zhao, Tianhong Li, Soso Abu Alhaija, Dina Mustafaraj, and William T. Freeman. Through-wall human pose estimation using radio signals. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.
- [2] Mingmin Zhao, Shichuan Geng, Liana Zhou, Priya Agrawal, Bharath Hariharan, Deva Ramanan, Dina Mustafaraj, and William T. Freeman. RF-based 3D skeletons. In *Proceedings of the ACM SIGCOMM Conference*, 2018.

Table 1: MM-Fi cross-subject results (S01–S07 train / S08–S10 test). Each row changes exactly one variable (G-series protocol). MPJPE is the 12 shared-limb mean per-joint position error in cm; PA-MPJPE in mm; **track_r** is the moving-track reliability score; A10 is the fastest action class; wrist L/R are per-wrist errors in cm. Best values in **bold**.

Configuration (single variable)	MPJPE	PA	track_r	A10	Wrist L/R
Baseline ceiling_tune	8.06	67.1	0.616	18.2/17.6	15.0/15.4
+ G1: actions 10 $\rightarrow$ 27	8.07	65.1	0.624	(mixed)	15.4/15.8
+ G2: accumulation $k=3$	7.64	61.1	0.642	14.65	14.1/14.8
+ G3: Doppler present	7.64 [†]	—	0.642	14.65	14.8
+ G4: velocity loss $v_w=1.0$	7.45	—	0.651	14.70	14.5

[†] Zeroing the Doppler channel degrades MPJPE to 8.49 cm (+0.85) and A10 to 16.35 cm (+1.70).

Table 2: Per-joint MPJPE (cm) on MM-Fi for configuration G1 v1a, averaged over left/right. Errors increase monotonically from proximal to distal joints, matching the physical illumination law of RF-based pose estimation [2].

Joint	MPJPE (cm)
Hip	1.7
Shoulder	6.5–6.6
Knee	6.1–6.2
Head	7.7
Ankle	8.1–8.2
Elbow	10.1–10.4
Wrist	14.3–15.5

- [3] Jinyu Yang, Bang Xiong, Chao Huang, Guangyuan Li, Jinhua Zhang, Jianfei Wu, Chenglu Xu, Li Liu, Chunyu Jiang, Lanxin Ma, Zhe Ma, Shengyue Yang, Kaishun Zhang, and Yunhao Liu. MM-Fi: Multi-modal non-intrusive 4D human dataset for versatile wireless sensing. In *Advances in Neural Information Processing Systems (NeurIPS) Datasets and Benchmarks Track*, 2023.
- [4] Youngwook Kim and Hao Ling. Human activity classification based on micro-Doppler signatures using a support vector machine. *IEEE Transactions on Geoscience and Remote Sensing*, 47(5):1328–1337, 2009.
- [5] Moeness G. Amin. *Radar for Indoor Monitoring: Detection, Classification, and Assessment*. CRC Press, 2017.
- [6] Shuhai Wang and Jian Song. Interacting hand-object pose estimation via dense mutual attention. In *IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, 2023.
- [7] Shuangjian An and Umit Y. Ogras. MARS: mmwave-based assistive rehabilitation system for smart healthcare. *ACM Transactions on Cyber-Physical Systems*, 2021.
- [8] Hongfei Xue, Wei Fu, Shuo Zhang, Chenshuo Zhang, Jianwei Zheng, Zhumu Xiao, and Yunhao Liu. mmMesh: Towards 3D real-time dynamic human mesh construction using millimeter-wave. In *Proceedings of the 19th Annual International Conference on Mobile Systems, Applications, and Services (MobiSys)*, 2021.

Table 3: End-to-end results on our own synchronous radar + RGB-D corpus (six sessions, one subject, block-level held-out splits with a 4-frame leakage buffer; 1,576 train / 600 validation samples).

Model	Metric	Value
v1a deterministic	MPJPE (cm)	21.47
	PA-MPJPE (mm)	127.0
v1b CVAE	MPJPE (cm)	21.44
	mean per-joint std (cm)	7.45
v2 MHR mesh	<code>body_pose</code> MSE	0.0268
	<code>global_rot</code> MSE	0.908




Figure 10: Scaling behavior on log–log axes. Circles: measured points — our corpus at $n=2,176$ (21.47 cm) and the MM-Fi anchor at $n=6,860$ diverse cross-subject samples (8.3 cm). The blue solid line is the within-distribution fit $\text{err} = 53.8 n^{-0.124}$: reaching 15 cm would require $\sim 30\text{k}$ samples, 12 cm 185k, and 10 cm 810k (squares). The red dashed line shows the slope $b \approx 0.65$ implied by diverse samples — over $100\times$ steeper. Sample *diversity*, not volume, is the binding constraint.

- [9] Xitong Yang, Devansh Kukreja, Don Pinkus, Anushka Sagar, Taosha Fan, et al. SAM 3D Body: Robust full-body human mesh recovery. arXiv preprint arXiv:2602.15989, 2026. Code: <https://github.com/facebookresearch/sam-3d-body>.
- [10] Aditya Sengupta, Fanyi Jin, Rui Zhang, and Songzhu Cao. mm-Pose: Real-time human skeletal posture estimation using mmwave radars and CNNs. *IEEE Sensors Journal*, 20(17): 10032–10044, 2020.
- [11] Ruotong Zheng, Haodong Chen, Jun Sun, Jiangong Wang, Yiming Li, Dingran Fang, and Chang Chen. Point cloud-based 3D human pose estimation using dual-view mmwave radar. *IEEE Sensors Journal*, 2025. Commonly cited as PointTS.
- [12] Haotian Cong et al. mmDiff: mmwave-based human pose estimation via conditional diffusion. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2024.