

SentZero: An Enhanced Sentence-Centric Vision-Language Pretraining for Multi-Task Zero-Shot Chest X-Ray Analysis

Hangyul Yoon¹, Hyungyung Lee¹, Edward Choi¹ and Eunho Yang^{1,†}

¹Kim Jaechul Graduate School of AI, Korea Advanced Institute of Science and Technology (KAIST)

[†]Corresponding Author

Vision-language (VL) pretraining using paired chest X-ray (CXR) images and radiology reports has shown strong potential for medical image understanding. However, existing methods often remain dependent on task-specific fine-tuning because radiology reports are lengthy, clinically dense, and difficult to align with simple zero-shot prompts. Recent sentence-level approaches partially address this limitation using clinical phrases extracted by large language models (LLMs), but they largely overlook the intrinsic characteristics of radiology discourse. In particular, limited positive-pair diversity constrains further gains, while clinically equivalent sentences frequently recur across patients, creating false negatives in contrastive learning. To address these issues, we propose **SentZero**, an enhanced sentence-centric VL pretraining framework for zero-shot, multi-task CXR analysis. SentZero introduces LLM-based abstract-level sentence structuring and mapping to expand positive-pair diversity, together with an additional loss term to mitigate false negatives. We further introduce sentence-conditioned residual modulation of visual embeddings, enabling visual features to adapt to the semantic characteristics of each input sentence. Across diverse downstream tasks and datasets, SentZero improves zero-shot generalization and outperforms prior multi-task zero-shot methods.

1. Introduction

Chest X-ray (CXR) remains one of the most widely used imaging modalities in clinical practice. With the rapid progress of vision-language (VL) pretraining, recent studies have leveraged CXR images paired with their corresponding captions, namely *radiology reports* written by expert radiologists (Zhang et al., 2022; Wang et al., 2022; Cheng et al., 2023; Li et al., 2024; Liu et al., 2024; Zhang et al., 2025). By learning contrastive alignments between images and textual descriptions, these approaches have improved visual representations and benefited various downstream tasks. However, many existing methods still require fine-tuning on labeled datasets for specific applications (Cheng et al., 2023; Zhang et al., 2025; Liu et al., 2024), even after the contrastive pretraining. A key reason is that radiology reports are long and complex, containing detailed findings, clinical context, and stylistic variations across reporters. As a result, image-text alignment in the medical domain is noisier and more difficult than in general-domain VL pretraining, where concise prompts such as "There is a dog" can be used directly for zero-shot recognition. Consequently, applying simple text prompts to CXR tasks in a zero-shot manner remains challenging, often requiring additional task-specific fine-tuning. This reliance partially undermines the fundamental goal of VL pretraining: enabling broad generalization without task-specific supervision.

To address this limitation, recent studies have explored zero-shot multi-task VL frameworks, in which a single model generalizes across multiple visual tasks using natural language prompts (Huang et al., 2021; Zhang et al., 2022, 2023; Wu et al., 2023). A pivotal milestone in this direction is the use of large language models (LLMs) for report rephrasing (Lai et al., 2024; Park et al., 2025). By standardizing radiological findings into unified prompt templates, LLM-based rephrasing reduces noise from lengthy reports and diverse expressions, extracting multiple sentences from a single report. With sentence-level supervision, this design improves interpretability and enables zero-shot grounding within a unified framework, establishing the current state of the art.

Despite these advances, existing approaches largely overlook a distinctive property of radiology discourse. Unlike general-domain captions, radiology reports are highly task-oriented and describe a narrow, well-defined set of findings, so identical or clinically equivalent statements, such as "*The lungs are clear,*" recur across many patients. Current LLM-phrase-based methods treat each extracted sentence as an independent caption of its own image, which leads to two problems. First, the hierarchical semantic structure of radiology reports remains

unexploited as a source of supervision. Second, clinically equivalent sentences from different studies are treated as negatives, creating *false-negative pairs* that are wrongly pushed apart during contrastive training. Because the space of distinct clinical descriptions is inherently narrow, such pairs are frequent and cannot be avoided simply by better phrase extraction.

We introduce **SentZero**, a *sentence-centric* VL pretraining framework that uses semantic redundancy as a source of structured supervision. First, *abstract-level sentence mapping* uses an LLM to map detailed phrases to concise topic-presence statements (e.g., “There is mild opacity in the bilateral lung base” → “There is opacity”). This provides supervision at two levels of granularity—detailed findings from the original text and their underlying clinical concepts—and enables matching of shared statements across studies. Second, we use these matches for false-negative mitigation through an auxiliary loss that selectively attracts the most relevant patches toward each shared statement. Rather than masking or relabeling such pairs at the instance level, which we find disrupts contrastive training, this auxiliary loss mitigates the effects of repeated clinical statements through selective patch-level alignment while leaving the global contrastive objective intact. Finally, *sentence-conditioned residual modulation* applies sentence-dependent scale and shift parameters to attention-pooled visual features, allowing each sentence to guide *how* the attended features are represented.

In summary, our contributions are as follows:

- We propose SentZero, a sentence-centric VL pretraining framework for zero-shot, multi-task CXR analysis. Unlike most existing VL pretraining methods in the CXR domain, SentZero transfers directly to a variety of downstream tasks without any task-specific fine-tuning.
- We leverage the shared semantic structure of radiology reports through abstract-level sentence mapping and a patch-level false-negative mitigation objective, complemented by sentence-conditioned residual modulation of visual features. We show that directly masking or relabeling false-negative pairs can impair performance, whereas our proposed selective patch-level attraction improves performance while preserving the original contrastive objective and pair assignments.
- SentZero outperforms prior zero-shot multi-task methods on most evaluated benchmarks. Given the persistent challenge of strong zero-shot generalization across CXR tasks, these results mark a step toward a general-purpose CXR encoder that supports diverse tasks without additional task-specific annotations.

2. Related Works

Vision-Language Pretraining in Chest X-ray. In recent years, increasing attention has been given to leveraging paired image–text data in CXRs. In this setting, the textual modality consists of radiology reports, which are structured clinical descriptions routinely written by radiologists. With the release of large-scale paired datasets such as MIMIC-CXR (Johnson et al., 2024, 2019), numerous CLIP-style (Radford et al., 2021) VL pretraining methods have been developed for the medical domain (Zhang et al., 2022; Wang et al., 2022; Cheng et al., 2023; Li et al., 2024; Liu et al., 2024; Zhang et al., 2025). These studies consistently show that visual encoders pretrained through image–report alignment adapt better to downstream medical tasks than those pretrained on general-domain datasets such as ImageNet.

Despite these achievements, most existing VL pretraining methods still require additional task-specific supervised fine-tuning. One key reason is that radiology reports differ substantially from general-domain image captions: they are written for diagnosis and rigorous assessment of patient status, making them lengthy, detailed, and clinically dense. Such complexity can introduce noise during VL pretraining and makes it difficult to directly apply simple text prompts for zero-shot CXR tasks. As a result, many prior studies have relied on labeled downstream datasets to fine-tune pretrained models, partially undermining the original goal of VL pretraining: learning broadly generalizable representations with minimal task-specific supervision.

Chest X-ray Pretraining for Zero-Shot Transfer. To reduce reliance on task-specific supervised fine-tuning after VL pretraining, several studies have explored zero-shot generalization across diverse CXR analysis tasks. Early methods, including MedKLIP (Wu et al., 2023) and KAD (Zhang et al., 2023), incorporated medical knowledge and clinical entities to improve semantic alignment. CARZero (Lai et al., 2024) introduced cross-attention-based alignment and LLM-driven phrase extraction, standardizing heterogeneous diagnostic expressions into sentence-level prompts for zero-shot classification and grounding. RadZero (Park et al., 2025) extended this paradigm through similarity-weighted patch aggregation and multi-positive contrastive learning (Lee et al., 2022), aligning each image with multiple finding sentences.




Figure 1: Overview of the SentZero training framework. SentZero performs multi-pair contrastive learning between sentence embeddings and weighted-sum patch embeddings (bold red line, lower-right panel). Structured tuples extracted from the findings generate augmented positive pairs through abstract-level mapping. The model is trained with a combination of the contrastive loss ($\mathcal{L}_{con}$) and the false-negative mitigation loss ($\mathcal{L}_{fn}$). Before contrastive learning, the patch embeddings are refined via a residual connection with a text-conditioning module (lower left). At inference, the similarity logits and patch attention scores support multiple zero-shot downstream tasks.

A key challenge in sentence-level pretraining is that clinically equivalent statements recur across patients, causing valid image–sentence associations to be treated as negatives. CoNNs (Lian et al., 2026) addresses this issue using structured clinical concepts to relabel or exclude cross-patient pairs from the contrastive objective. However, we empirically show that directly relabeling or masking such pairs can instead degrade performance (Sec. 4.4). SentZero explores a complementary approach: retaining the contrastive pair assignments while applying an auxiliary attraction loss to the highest-similarity patches of pairs identified through shared sentences. Furthermore, SentZero extends text conditioning beyond spatial attention by applying sentence-conditioned residual modulation to the aggregated visual features before contrastive comparison. These mechanisms provide local alignment supervision for shared clinical statements and sentence-dependent adaptation of visual representations.

3. Method

The overall training framework is illustrated in Fig. 1. Given lengthy and noisy radiology reports, we first use an LLM to extract phrase-level clinical expressions (Sec. 3.1). We then employ the LLM to structure the extracted information and perform abstract-level sentence mapping, thereby augmenting positive pairs while preserving the implicit medical semantics of the sentences. The resulting sentence and image embeddings (Sec. 3.2) are used for multi-pair contrastive learning, where the image embeddings are conditioned to reflect the semantics of each sentence rather than relying on the original patch embeddings (Sec. 3.3). During training, false-negative pairs are identified and calibrated using a false-negative mitigation loss, addressing an issue that has not been adequately handled in previous studies (Sec. 3.4). Once trained, the model can be directly applied to zero-shot classification and spatial grounding tasks without task-specific fine-tuning (Sec. 3.5).

3.1. Abstract-Level Sentence Mapping

Let $\mathcal{D}_{\text{batch}} = \{(I_i, R_i)\}_{i=1}^B$ denote a mini-batch of B paired images and radiology reports. For each report R_i corresponding to the i -th image I_i , we employ an LLM to extract a set of M_i phrases, defined as $T_i = \{S_i^{(1)}, S_i^{(2)}, \dots, S_i^{(M_i)}\}$, where each sentence represents a specific clinical finding. Here, $S_i^{(k)}$ denotes the k -th element in the set of sentences positively paired with image I_i . This phrase set was generated using LLM, which was prompted to follow template-based extraction rules, such as “*There [Presence] [Finding] of [Location],*” where square brackets denote template variables. Here, *[Finding]* can include not only a disease term but also detailed visual descriptors, such as “bilateral mild pleural effusion,” which provides additional characterization of the disease term “pleural effusion.”

To better leverage the clinical structure of radiology discourse, we additionally employ LLM to perform abstract-level structuring and sentence mapping. Each extracted phrase is mapped to a structured tuple (Topic, Presence), where the ‘Topic’ represents a specific pathology (e.g., ‘Cardiomegaly’) and ‘Presence’ indicates its clinical status (e.g., ‘Yes’, ‘No’, or ‘Maybe Yes’). From this representation, we generate concise, high-level sentences using the template: “*There [Presence] [Topic].*” These are then integrated as additional positive pairs within the contrastive learning framework. For example, the sentence ‘There is mild opacity in the bilateral lung base’ is simplified to ‘There is opacity’ and utilized as an augmented positive pair. Instead of the original set T_i , we use the augmented sentence pair set $T_i^{\text{aug}} = \{S_i^{(1)}, S_i^{(2)}, \dots, S_i^{(N_i)}\}$, where $N_i \geq M_i$ denotes the number of unique positive sentence pairs associated with I_i after the augmentation process. Finally, the images $\{I_i\}_{i=1}^B$ and augmented sentence sets $\{T_i^{\text{aug}}\}_{i=1}^B$ are used in the image-sentence contrastive learning.

3.2. Feature Extraction

Let (I_i, T_j^{aug}) denote an image-sentence set pair sampled from i -th and j -th sample of mini-batch $\mathcal{D}_{\text{batch}}$, respectively. If the image and sentence set originate from the same sample ($i = j$), the pair is treated as positive by default; otherwise ($i \neq j$), it is treated as negative.

The image I_i is passed through a visual encoder f_v with a Vision Transformer (ViT) (Dosovitskiy et al., 2021)-based architecture to obtain a global visual embedding $v_i^g \in \mathbb{R}^D$ (i.e., the [CLS] token of the final output) and local patch embeddings $v_i^l \in \mathbb{R}^{L \times D}$, where L and D denote the number of local patches and the feature dimension, respectively. The encoder f_v consists of a LoRA-finetuned ViT backbone f_v^{ViT} followed by additional trainable transformer layers f_v^{train} .

Let $h_i^{(n)} \in \mathbb{R}^{L \times D}$ denote the local patch token sequence produced by the n -th layer of the backbone f_v^{ViT} , and let N be its total depth. Since intermediate layers retain complementary information that is partially discarded in the final layer, we do not rely on $h_i^{(N)}$ alone. Instead, we select a set of intermediate layer indices $\mathcal{S}_{\text{layer}} = \{n_1, \dots, n_M\} \subset \{1, \dots, N\}$, transform the representation from each selected layer with a dedicated 2-layer multi-layer perceptron (MLP) followed by LayerNorm (Ba et al., 2016), and add their average to the final-layer representation:

$$\tilde{h}_i = h_i^{(N)} + \frac{1}{M} \sum_{m=1}^M \text{LN}_{\text{ViT}}^{(m)}(\text{MLP}_{\text{ViT}}^{(m)}(h_i^{(n_m)})),$$

where $\text{LN}_{\text{ViT}}^{(m)}$ and $\text{MLP}_{\text{ViT}}^{(m)}$ denote the LayerNorm and 2-layer MLP associated with the m -th selected layer.

The fused token sequence $\tilde{h}_i$ is further refined by the trainable transformer layers f_v^{train} , from whose output the global and local visual representations are read out as

$$[v_i^g; v_i^l] = \text{LN}_v(f_v^{\text{train}}(\tilde{h}_i)), \quad v_i^l = \text{Concat}(\{v_{i,p}\}_{p=1}^L),$$

where $v_i^g \in \mathbb{R}^D$ is the output [CLS] token and $v_{i,p} \in \mathbb{R}^D$ is the p -th patch embedding of image I_i . Here, LN_v denotes the LayerNorm applied to the final visual representation, and $\text{Concat}(\cdot)$ is the concatenation of the given embeddings along the token dimension.

In parallel, the sentences in T_j^{aug} are encoded by a bidirectional text encoder f_t . Given the k -th sentence $S_j^{(k)} \in T_j^{\text{aug}}$ of the j -th sample in the batch, its text representation is obtained as $t_j^{(k)} = \text{LN}_t(f_t(S_j^{(k)})) \in \mathbb{R}^D$, where LN_t denotes a LayerNorm applied to the final text representation.

3.3. Sentence-Conditioned Feature Modulation and Contrastive Loss

Given the patch embeddings and sentence embeddings, we perform image–sentence contrastive learning. Unlike most VL contrastive approaches, which represent an image with a single global embedding, we represent each image by a sentence-conditioned aggregation of its local patch embeddings, in which every patch is weighted by its similarity to the sentence.

Concretely, we first ℓ_2 -normalize the patch embeddings and the sentence embedding, $\bar{v}_{i,p} = v_{i,p} / \|v_{i,p}\|_2$ and $\bar{t}_j^{(k)} = t_j^{(k)} / \|t_j^{(k)}\|_2$, and compute the patch-level similarity $s_{i,j,p}^{(k)} = \langle \bar{v}_{i,p}, \bar{t}_j^{(k)} \rangle$. A softmax over the patches converts these similarities into spatial attention weights:

$$a_{i,j,p}^{(k)} = \frac{\exp(s_{i,j,p}^{(k)} / \tau_a)}{\sum_{m=1}^L \exp(s_{i,j,m}^{(k)} / \tau_a)}, \quad (3.1)$$

where τ_a is a temperature parameter and p is the patch index. The sentence-conditioned visual feature is the attention-weighted sum of the patch embeddings:

$$\tilde{v}_{i,j}^{(k)} = \sum_{p=1}^L a_{i,j,p}^{(k)} v_{i,p}.$$

In conventional VL contrastive learning, $\tilde{v}_{i,j}^{(k)}$ would be contrasted directly with the sentence embedding. We further refine this visual feature to incorporate sentence semantics through *sentence-conditioned feature modulation*. Specifically, we apply feature-wise linear modulation (FiLM) (Perez et al., 2018) with a residual connection, predicting the scale and shift parameters of LayerNorm as learnable functions of the conditioning feature. This enables sample-specific modulation of the aggregated visual feature, while the residual connection preserves its original visual information.

Specifically, we stack $R = 2$ modulation units, each consisting of a feature-wise standardization and a FiLM layer followed by two linear layers. In the r -th unit, a 2-layer MLP $\text{MLP}_{\text{FiLM}}^{(r)}$ predicts a feature-wise scale $\gamma_{i,j,r}^{(k)}$ and shift $\beta_{i,j,r}^{(k)}$, conditioned on the aggregated patch embedding and the sentence embedding:

$$\gamma_{i,j,r}^{(k)}, \beta_{i,j,r}^{(k)} = \text{MLP}_{\text{FiLM}}^{(r)}(\text{Concat}(\tilde{v}_{i,j}^{(k)}, t_j^{(k)})).$$

Starting from $u_{i,j}^{(k,0)} = \tilde{v}_{i,j}^{(k)}$, the r -th unit standardizes its input, modulates it with these sentence-dependent parameters, and then applies two successive linear projections:

$$u_{i,j}^{(k,r)} = W_r^{(2)} \left(W_r^{(1)} (\gamma_{i,j,r}^{(k)} \odot \text{Std}(u_{i,j}^{(k,r-1)}) + \beta_{i,j,r}^{(k)}) + b_r^{(1)} \right) + b_r^{(2)}, \quad r = 1, \dots, R,$$

where $\odot$ denotes element-wise multiplication, $\text{Std}(x) = (x - \mu(x)) / \sqrt{\sigma^2(x) + \epsilon}$ standardizes a vector $x \in \mathbb{R}^D$ using the mean $\mu(x)$ and variance $\sigma^2(x)$ of its D entries, with a small constant ϵ for numerical stability (i.e., a LayerNorm without learnable affine parameters, whose role is taken over by $\gamma_{i,j,r}^{(k)}$ and $\beta_{i,j,r}^{(k)}$), and $W_r^{(1)}, W_r^{(2)} \in \mathbb{R}^{D \times D}$ and $b_r^{(1)}, b_r^{(2)} \in \mathbb{R}^D$ are the parameters of the two linear layers in the r -th unit. The output of the last unit is added back to the original aggregated feature through a residual connection, followed by a LayerNorm:

$$\hat{v}_{i,j}^{(k)} = \text{LNTC}(\tilde{v}_{i,j}^{(k)} + u_{i,j}^{(k,R)}),$$

where LNTC is a LayerNorm applied to the modulated feature. In this way, the stacked module units inject sentence semantics as a learned correction to $\tilde{v}_{i,j}^{(k)}$ rather than replacing it, so the spatially aggregated visual content is retained.

We use $\hat{v}_{i,j}^{(k)}$ as the visual side of the image–sentence contrastive loss and ℓ_2 -normalize it to obtain $\bar{v}_{i,j}^{(k)}$. The similarity logit is then the temperature-scaled cosine similarity between the sentence-conditioned visual feature and the sentence embedding:

$$z_{i,j}^{(k)} = \langle \bar{v}_{i,j}^{(k)}, \bar{t}_j^{(k)} \rangle / \tau_l, \quad (3.2)$$

where τ_l is the logit temperature and $\bar{t}_j^{(k)}$ is the ℓ_2 -normalized text embedding.

Using these logits, we compute a contrastive loss between the images and sentences in each batch. Since a single image can have multiple positive sentences, we adopt the multi-positive noise-contrastive estimation (MP-NCE) loss (Lee et al., 2022) with softmax-based competition:

$$\mathcal{L}_I = -\frac{1}{N_T} \sum_{i=1}^B \sum_{n=1}^{N_i} \log \frac{\exp(z_{i,i}^{(n)})}{\exp(z_{i,i}^{(n)}) + \sum_{j \neq i}^B \sum_{m=1}^{N_j} \exp(z_{i,j}^{(m)})},$$

where N_j denotes the number of positive pair sentences for the j -th sample and N_T is the total number of sentences in the batch. That is, each positive sentence competes only against the negative sentences from other images in the batch, and the per-pair losses are averaged over all positive pairs.

For each finding sentence, we apply a text-to-image InfoNCE loss (Oord et al., 2018), defined as

$$\mathcal{L}_T = -\frac{1}{N_T} \sum_{i=1}^B \sum_{n=1}^{N_i} \log \frac{\exp(z_{i,i}^{(n)})}{\exp(z_{i,i}^{(n)}) + \sum_{j \neq i}^B \exp(z_{j,i}^{(n)})}.$$

Each sentence is paired with exactly one image, and the standard InfoNCE loss applies directly in this direction. The contrastive loss $\mathcal{L}_{\text{con}}$ is defined as the average of the image-to-text and text-to-image contrastive losses, denoted as $\mathcal{L}_{\text{con}} = (\mathcal{L}_I + \mathcal{L}_T)/2$.

3.4. False Negative Loss

However, treating all unpaired examples within a batch as strict negatives unfairly penalizes *false negatives*, i.e., image-sentence pairs drawn from different studies that nevertheless describe the same pathology. To mitigate this, we introduce a false-negative identification strategy. Specifically, if the k -th sentence of the j -th sample, $S_j^{(k)}$, also appears in the augmented text set T_i^{aug} of the i -th sample, we treat the pair $(I_i, S_j^{(k)})$ as a false negative. Accordingly, given a mini-batch of size B , we define the set of false-negative pairs $\mathcal{F}$ as

$$\mathcal{F} = \{ (i, j, k) \mid i \neq j \text{ and } S_j^{(k)} \in T_i^{\text{aug}}; k = 1, 2, \dots, N_j \}_{i,j=1}^B.$$

Rather than pulling the global image embedding toward every false-negative sentence, we align only the image regions most relevant to that sentence. For each false-negative pair $(i, j, k) \in \mathcal{F}$, we compute the cosine similarity $s_{i,j,p}^{(k)} = \cos(v_{i,p}, t_j^{(k)})$ between every patch and sentence, and select the top- $M\%$ patch indices $\mathcal{P}_{i,j}^{(k)}$. The false-negative loss $\mathcal{L}_{fn}$ then aims to maximize the cosine similarity between the selected patches and the sentence, averaged over all false-negative pairs:

$$\mathcal{L}_{fn} = \frac{1}{|\mathcal{F}|} \sum_{(i,j,k) \in \mathcal{F}} \frac{1}{|\mathcal{P}_{i,j}^{(k)}|} \sum_{p \in \mathcal{P}_{i,j}^{(k)}} (1 - s_{i,j,p}^{(k)}).$$

This auxiliary loss attracts only the top- $M\%$ highest-similarity patches toward each false-negative sentence identified through cross-study matching, counteracting repulsion through selective local alignment. It directly supervises the selected patches while preserving the global contrastive objective and its pair assignments. Thus, our false-negative mitigation does not remove false negatives from the contrastive loss; instead, it adds patch-level supervision that aligns each image with the clinical statements it shares with other studies.

The total training loss $\mathcal{L}_{\text{train}}$ is then defined as

$$\mathcal{L}_{\text{train}} = \lambda_{\text{con}} \mathcal{L}_{\text{con}} + \lambda_{fn} \mathcal{L}_{fn},$$

where λ_{con} and λ_{fn} are the coefficients for each loss term.

3.5. Multi-Task Zero-Shot Inference

After pretraining, SentZero supports zero-shot generalization across diverse downstream tasks by leveraging the learned alignment between visual features and text prompts (bottom of Fig. 1).

Zero-Shot Classification. To perform classification for a specific pathology, we construct a text prompt S_{test} using the clinical template (e.g., “There is [Finding]”). For a given test image I_{test} , we first compute the sentence-specific attended visual feature $\bar{v}_{test}$ and the text representation $\bar{t}_{test}$ as described in Sec. 3.3. The similarity logit is computed as $z = \langle \bar{v}_{test}, \bar{t}_{test} \rangle / \tau_l$ as in equation 3.2, and converted into a probability via a sigmoid function, denoted as $\hat{p} = \sigma(z)$. This probability $\hat{p}$ represents the model’s confidence in the presence of the finding described by the prompt.

Zero-Shot Grounding. To localize findings, we utilize the spatial attention weights derived from equation 3.1. For each local patch $p \in \{1, \dots, L\}$, the attention weight a_p is calculated as:

$$a_p = \frac{\exp(s_p / \tau_a)}{\sum_{m=1}^L \exp(s_m / \tau_a)},$$

where $s_p = \langle \bar{v}_p, \bar{t}_{test} \rangle$ is the patch-level similarity score. The resulting set of weights $\{a_p\}_{p=1}^L$ forms an attention map $A \in \mathbb{R}^{\sqrt{L} \times \sqrt{L}}$.

This map is then reshaped and bilinearly upsampled to the original image resolution, yielding the final Softmax Attention Map $\hat{A} = \text{bilinear}(A)$, where bilinear denotes bilinear interpolation. The acquired attention map $\hat{A}$ provides a relative distribution of importance across the image, where the values sum to one across the spatial domain. For grounding, the peak of this distribution (the maximum value in $\hat{A}$) is used to identify the most likely location of the finding.

4. Experiments

4.1. Experimental Settings

Datasets. We use MIMIC-CXR (Johnson et al., 2024, 2019) for vision–language pretraining, including all frontal and lateral views and following the official dataset split. MIMIC-CXR consists of image–report pairs from 377K chest X-ray images, 227K radiographic studies, and 65,379 patients. For report text, we use the *findings* section for phrase extraction and discard studies without extracted finding sentences. To ensure a fair comparison with RadZero (Park et al., 2025), we adopt its phrases extracted by LLaMA3-70B-Instruct and further apply abstract-level sentence mapping using Qwen3-Next-80B. The detailed instruction prompt is provided in the Appendix A.

For evaluation, we follow the multi-task zero-shot CXR benchmarks that have been commonly used in prior works (Huang et al., 2021; Zhang et al., 2023; Lai et al., 2024; Wu et al., 2023; Park et al., 2025). Zero-shot classification is evaluated on Open-I (Demner-Fushman et al., 2016), ChestXray14 (Wang et al., 2017), PadChest (Bustos et al., 2020), ChestXDet10 (Liu et al., 2020), and CheXpert (Irvin et al., 2019); and grounding is evaluated on ChestXDet10 and MS-CXR (Boecking et al., 2022). All classification datasets are used for multi-label disease classification, while the grounding datasets provide text–bounding box pairs for diverse disease expressions. Additional dataset details, including the number of samples, are provided in the Appendix A.

Baseline Models and Evaluation Metrics. Although many VL pretraining methods have been proposed in the CXR domain, only a few support zero-shot transfer. We therefore compare our model with existing VL pretraining methods that can be directly applied to zero-shot downstream tasks: GLoRIA (Huang et al., 2021), BioViL-T (Bannur et al., 2023), MedKLIP (Wu et al., 2023), KAD (Zhang et al., 2023), CARZero (Lai et al., 2024), RadZero (Park et al., 2025), CoNNs (Lian et al., 2026), and GLINT (Park et al., 2026). For GLINT, we use the ViT-B variant with a 512×512 input resolution, which is comparable to our model in both backbone size and input size.

We follow the evaluation protocols used in these prior studies (Huang et al., 2021; Zhang et al., 2023; Lai et al., 2024; Wu et al., 2023; Park et al., 2025). For zero-shot classification, we report the area under the receiver operating characteristic curve (AUROC) on multi-label test datasets. In zero-shot grounding, we use **pointing game accuracy** (Zhang et al., 2018; Lai et al., 2024; Park et al., 2025), which measures whether the spatial location with the highest model response falls within the corresponding ground-truth bounding box.

Implementation Details. The vision encoder consists of a pretrained RAD-DINO model (Pérez-García et al., 2025) with a LoRA adapter (rank=16, and alpha=48) followed by four trainable transformer blocks. The input

image size is 518×518 , and the resulting feature map has a spatial resolution of 37×37 , corresponding to 1369 patches. For the text encoder, we use MPNet (all-mpnet-base-v2) (Reimers and Gurevych, 2019; Song et al., 2020). For intermediate-layer feature selection in the vision encoder, we extract features from the 3rd, 6th, and 9th layers of the ViT backbone and fuse them with the final-layer hidden representations.

For loss computation, all temperature hyperparameters are set to $\tau_a = \tau_l = 0.1$. The loss coefficients are set to $\lambda_{con} = 1$ and $\lambda_{fn} = 0.01$, with a patch sampling ratio of $M = 20\%$ for false negative pairs. The model is trained for up to 20 epochs using the AdamW optimizer with an initial learning rate of 1×10^{-4} and a batch size of 256. Training is performed on four NVIDIA H200 GPUs with DeepSpeed ZeRO Stage 2 for memory efficiency, using a WarmupCosineLR scheduler. We apply early stopping with a patience of 3 epochs and select the checkpoint with the lowest validation loss as the final model; training completes in approximately 5 hours. All ablation studies are conducted under the same fixed random seed. Additional results of hyperparameter tuning are described in Appendix B.

4.2. Main Results

Table 1 presents the zero-shot performance of our method and prior baselines across a range of downstream vision tasks. Our method achieves the best results across multiple multi-label datasets and task types. While CARZero (Lai et al., 2024) attains the highest AUROC on CheXpert, this dataset is relatively small (500 cases), and CARZero does not maintain comparable performance on the larger classification datasets, which contain thousands to tens of thousands of samples (see Appendix A for detailed dataset profiles). Our proposed model also demonstrates improvements on localization tasks. On ChestXDet10 and MS-CXR, it outperforms the strongest baseline by 7.6 and 3.6 percentage points in pointing game accuracy, respectively.

Table 1: Zero-shot performance comparison results. The first header row indicates the task type and corresponding evaluation metric. The best and second-best results are shown in **bold** and underlined, respectively. CXR14 and CXD10 refer to the ChestXray14 and ChestXDet10 datasets, respectively.

Method	Venue	Classification (AUROC)					Grounding (Pointing Acc.)	
		OpenI	CXR14	PadChest	CXD10	CheXPert	CXD10	MS-CXR
GLoRIA	ICCV’21	0.589	0.610	0.565	0.645	0.750	0.367	-
BioViL-T	CVPR’23	0.702	0.729	0.655	0.708	0.789	0.351	0.719
MedKLIP	ICCV’23	0.759	0.726	0.629	0.713	0.879	0.481	0.407
KAD	Nat. Comm.’23	0.807	0.789	0.750	0.735	0.905	0.391	-
CARZero	CVPR’24	0.838	0.811	0.810	0.796	0.923	0.543	0.749
RadZero	NeurIPS’25	0.847	0.804	0.841	0.787	0.900	0.622	0.844
CoNNs	MICCAI’26	<u>0.871</u>	<u>0.819</u>	0.835	<u>0.825</u>	<u>0.920</u>	<u>0.656</u>	0.872
GLINT	NeurIPS’26	<u>0.871</u>	0.817	<u>0.853</u>	0.812	0.918	0.625	<u>0.886</u>
SentZero (Ours)	-	0.889	0.839	0.861	0.843	0.904	0.732	0.922

4.3. Ablation Studies on Model Components

Table 2 reports the ablation results for each component of SentZero. Starting from the baseline without any proposed component (first row), multi-layer feature aggregation improves performance, most notably on the grounding tasks (second row). Adding each of the remaining components individually on top of it (third to fifth rows) further improves classification performance, and combining all components yields the best or near-best results on most datasets. Although the text-conditioned residual connection alone achieves higher scores on PadChest and CheXpert, the full model outperforms it on the other five benchmarks by larger margins.

To assess the effect of text conditioning, we remove the text embeddings from the feature modulation units, replacing them with duplicated aggregated patch features to keep the parameter count and projection dimension unchanged. Incorporating text features improves performance on most datasets (See Table 4 in Appendix B).

4.4. Comparison on False Negative Handling Strategy

We compare our strategy with two simple alternatives that directly modify the pair assignments in the contrastive loss $\mathcal{L}_{con}$: (1) *false-negative masking*, which removes false-negative pairs from the denominator, and (2) *false-negative transition*, which relabels them as positive pairs. Prior work such as CoNNs (Lian et al., 2026) employs

Table 2: Ablation results for the model components. MF – Multi-Layer Feature Aggregation; ALM – Abstract-Level Mapping; TC – Text Conditioned Residual Connection; FN – False Negative Mitigation. Best results in each column are in **bold**.

Component				Classification					Grounding	
MF	ALM	TC	FN	OpenI	CXR14	PadChest	CXD10	CheXPert	CXD10	MS-CXR
				0.8747	0.8140	0.8592	0.8090	0.9080	0.6513	0.8922
✓				0.8741	0.8164	0.8559	0.8093	0.9109	0.6655	0.9222
✓	✓			0.8856	0.8323	0.8635	0.8395	0.8978	0.6811	0.9162
✓		✓		0.8828	0.8236	0.8652	0.8226	0.9162	0.7032	0.8922
✓			✓	0.8774	0.8239	0.8607	0.8230	0.9155	0.6556	0.8862
✓	✓	✓		0.8858	0.8376	0.8627	0.8431	0.9047	0.7121	0.9042
✓	✓	✓	✓	0.8891	0.8389	0.8609	0.8433	0.9037	0.7315	0.9222


Table 3: Comparison of false negative mitigation strategies. Best mitigation results in each column are in **bold**.

Method	Classification					Grounding	
	OpenI	CXR14	PadChest	CXD10	CheXPert	CXD10	MS-CXR
None	0.8858	0.8376	0.8627	0.8431	0.9047	0.7121	0.9042
False Negative Masking	0.8815	0.8334	0.8642	0.8444	0.8981	0.6923	0.8982
False Negative Transition	0.8492	0.8139	0.7904	0.7951	0.9067	0.5138	0.7066
Ours	0.8891	0.8389	0.8609	0.8433	0.9037	0.7315	0.9222

both operations, selectively applying them according to the presence status of each finding. Table 3 presents the results, where ‘None’ denotes training without any false-negative handling (the sixth row of Table 2). Both alternatives underperform our strategy on most benchmarks and, in most cases, also underperform the ‘None’ baseline. In particular, relabeling false negatives as positives causes large performance drops across multiple datasets, suggesting that directly modifying contrastive pair assignments can impair learning in this setting. These findings support our auxiliary loss, which selectively attracts the highest-similarity patches toward each false-negative sentence while preserving the original contrastive pair assignments.

4.5. Visualization of Attention Map

Fig. 2 visualizes attention maps for examples from the ChestXDet10 dataset, which provides bounding box annotations grounded to text phrases. As shown in the figure, the attention maps accurately highlight relevant pathological regions, including small focal lesions occupying only a limited area. These visualization results suggest that the attention maps produced by SentZero have strong potential for zero-shot visual grounding. Additional examples of visualized attention maps are in Appendix C.

**Figure 2:** Examples of attention heatmaps for relatively small lesions from the ChestXDet10 dataset. Each example shows the original image and its attention map for the given text prompt. Green boxes are the ground-truth bounding boxes.

5. Conclusion

In this work, we presented SentZero, a sentence-centric vision-language pretraining framework built for the semantic and structural complexity of CXR reports. SentZero advances sentence-level pretraining through

abstract-level mapping, selective patch-level attraction for shared clinical statements, and sentence-conditioned residual modulation of visual features, complementing prior work on structured supervision and contrastive pair relabeling. SentZero outperforms prior multi-task CXR models across diverse zero-shot tasks, showing that explicitly modeling semantic hierarchy and cross-report expression overlap is key to robust, generalizable image-sentence alignment. More broadly, SentZero lays a scalable foundation for semantically aware medical vision-language pretraining, connecting raw clinical text to fine-grained visual understanding.

References

- Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.
- Shruthi Bannur, Stephanie Hyland, Qianchu Liu, Fernando Perez-Garcia, Maximilian Ilse, Daniel C Castro, Benedikt Boecking, Harshita Sharma, Kenza Bouzid, Anja Thieme, et al. Learning to exploit temporal structure for biomedical vision-language processing. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 15016–15027, 2023.
- Benedikt Boecking, Naoto Usuyama, Shruthi Bannur, Daniel C Castro, Anton Schwaighofer, Stephanie Hyland, Maria Wetscherek, Tristan Naumann, Aditya Nori, Javier Alvarez-Valle, et al. Making the most of text semantics to improve biomedical vision-language processing. In *European conference on computer vision*, pages 1–21. Springer, 2022.
- Aurelia Bustos, Antonio Pertusa, Jose-Maria Salinas, and Maria De La Iglesia-Vaya. Padchest: A large chest x-ray image dataset with multi-label annotated reports. *Medical image analysis*, 66:101797, 2020.
- Zhihao Chen, Yang Zhou, Anh Tran, Junting Zhao, Liang Wan, Gideon Su Kai Ooi, Lionel Tim-Ee Cheng, Choon Hua Thng, Xinxing Xu, Yong Liu, et al. Medical phrase grounding with region-phrase context contrastive alignment. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 371–381. Springer, 2023.
- Pujin Cheng, Li Lin, Junyan Lyu, Yijin Huang, Wenhan Luo, and Xiaoying Tang. Prior: Prototype representation joint learning from medical images and reports. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 21361–21371, 2023.
- Dina Demner-Fushman, Marc D Kohli, Marc B Rosenman, Sonya E Shooshan, Laritza Rodriguez, Sameer Antani, George R Thoma, and Clement J McDonald. Preparing a collection of radiology examinations for distribution and retrieval. *Journal of the American Medical Informatics Association*, 23(2):304–310, 2016.
- Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. *ICLR*, 2021.
- Shih-Cheng Huang, Liyue Shen, Matthew P Lungren, and Serena Yeung. Gloria: A multimodal global-local representation learning framework for label-efficient medical image recognition. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 3942–3951, 2021.
- Jeremy Irvin, Pranav Rajpurkar, Michael Ko, Yifan Yu, Silvana Ciurea-Ilcus, Chris Chute, Henrik Marklund, Behzad Haghighi, Robyn Ball, Katie Shpanskaya, et al. Chexpert: A large chest radiograph dataset with uncertainty labels and expert comparison. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 590–597, 2019.
- Alistair Johnson, Tom Pollard, Roger Mark, Seth Berkowitz, and Steven Horng. MIMIC-CXR Database. *PhysioNet*, July 2024. doi: 10.13026/4jqj-jw95. URL <https://doi.org/10.13026/4jqj-jw95>. Version 2.1.0.
- Alistair EW Johnson, Tom J Pollard, Seth J Berkowitz, Nathaniel R Greenbaum, Matthew P Lungren, Chih-ying Deng, Roger G Mark, and Steven Horng. MIMIC-cxr, a de-identified publicly available database of chest radiographs with free-text reports. *Scientific data*, 6(1):317, 2019.

- Haoran Lai, Qingsong Yao, Zihang Jiang, Rongsheng Wang, Zhiyang He, Xiaodong Tao, and S Kevin Zhou. Carzero: Cross-attention alignment for radiology zero-shot classification. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11137–11146, 2024.
- Janghyeon Lee, Jongsuk Kim, Hyounguk Shon, Bumsoo Kim, Seung Hwan Kim, Honglak Lee, and Junmo Kim. Unclip: Unified framework for contrastive language-image pre-training. *Advances in Neural Information Processing Systems*, 35:1008–1019, 2022.
- Zhe Li, Laurence T Yang, Bocheng Ren, Xin Nie, Zhangyang Gao, Cheng Tan, and Stan Z Li. Mlip: Enhancing medical visual representation with divergence encoder and knowledge-guided contrastive learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11704–11714, 2024.
- Chenyu Lian, Hong-Yu Zhou, Chun-Ka Wong, and Jing Qin. Concept-guided noisy negative suppression for zero-shot classification and grounding of chest x-ray findings. *arXiv preprint arXiv:2605.19374*, 2026.
- Bo Liu, Zexin Lu, and Yan Wang. Towards medical vision-language contrastive pre-training via study-oriented semantic exploration. In *Proceedings of the 32nd ACM International Conference on Multimedia*, pages 4861–4870, 2024.
- Jingyu Liu, Jie Lian, and Yizhou Yu. Chestx-det10: chest x-ray dataset on detection of thoracic abnormalities. *arXiv preprint arXiv:2006.10550*, 2020.
- Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.
- Jonggwon Park, Soobum Kim, Byungmu Yoon, and Kyoyun Choi. Radzero: Similarity-based cross-attention for explainable vision-language alignment in radiology with zero-shot multi-task capability. *arXiv e-prints*, pages arXiv–2504, 2025.
- Jonggwon Park, Seongeun Lee, Junhyun Park, Hannah Yun, Hyunwoong Kim, Sohyun Jeong, Hyewon Kang, Byungmu Yoon, and Kyoyun Choi. Glint: Sparsely gated vision-language alignment for fine-grained radiology representations. *arXiv preprint arXiv:2606.03180*, 2026.
- Ethan Perez, Florian Strub, Harm De Vries, Vincent Dumoulin, and Aaron Courville. Film: Visual reasoning with a general conditioning layer. In *Proceedings of the AAAI conference on artificial intelligence*, 2018.
- Fernando Pérez-García, Harshita Sharma, Sam Bond-Taylor, Kenza Bouzid, Valentina Salvatelli, Maximilian Ilse, Shruthi Bannur, Daniel C Castro, Anton Schwaighofer, Matthew P Lungren, et al. Exploring scalable medical image encoders beyond text supervision. *Nature Machine Intelligence*, 7(1):119–130, 2025.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PmLR, 2021.
- Nils Reimers and Iryna Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks. In *Proceedings of the 2019 conference on empirical methods in natural language processing and the 9th international joint conference on natural language processing (EMNLP-IJCNLP)*, pages 3982–3992, 2019.
- Kaitao Song, Xu Tan, Tao Qin, Jianfeng Lu, and Tie-Yan Liu. Mpnet: Masked and permuted pre-training for language understanding. *Advances in neural information processing systems*, 33:16857–16867, 2020.
- Fuying Wang, Yuyin Zhou, Shujun Wang, Varut Vardhanabhuti, and Lequan Yu. Multi-granularity cross-modal alignment for generalized medical visual representation learning. *Advances in neural information processing systems*, 35:33536–33549, 2022.
- Xiaosong Wang, Yifan Peng, Le Lu, Zhiyong Lu, Mohammadhadi Bagheri, and Ronald M Summers. Chestx-ray8: Hospital-scale chest x-ray database and benchmarks on weakly-supervised classification and localization of common thorax diseases. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2097–2106, 2017.

- Chaoyi Wu, Xiaoman Zhang, Ya Zhang, Yanfeng Wang, and Weidi Xie. Medklip: Medical knowledge enhanced language-image pre-training for x-ray diagnosis. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 21372–21383, 2023.
- Jianming Zhang, Sarah Adel Bargal, Zhe Lin, Jonathan Brandt, Xiaohui Shen, and Stan Sclaroff. Top-down neural attention by excitation backprop. *International Journal of Computer Vision*, 126(10):1084–1102, 2018.
- Xiaoman Zhang, Chaoyi Wu, Ya Zhang, Weidi Xie, and Yanfeng Wang. Knowledge-enhanced visual-language pre-training on chest radiology images. *Nature Communications*, 14(1):4542, 2023.
- Yuhao Zhang, Hang Jiang, Yasuhide Miura, Christopher D Manning, and Curtis P Langlotz. Contrastive learning of medical visual representations from paired images and text. In *Machine learning for healthcare conference*, pages 2–25. PMLR, 2022.
- Ziyang Zhang, Yang Yu, Yucheng Chen, Xulei Yang, and Si Yong Yeo. Medunifier: Unifying vision-and-language pre-training on medical data with vision generation task using discrete visual representations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 29744–29755, 2025.

A. Additional Dataset Details

A.1. Dataset Profiles

We evaluate our model on a diverse set of public CXR benchmarks spanning classification, localization, and phrase grounding tasks. We verified that these evaluation images were excluded from both SentZero training and the pretraining data of the RAD-DINO checkpoint used in our experiments.

Classification Datasets. OpenI contains 7,470 CXR images paired with 3,851 radiology reports and multi-label annotations for 18 disease categories. ChestXray14 provides an official test set of 22,433 images annotated with 14 disease labels. PadChest comprises 160,868 CXR images from 67,000 patients and provides 192 labels with a highly long-tailed distribution. Following prior studies (Lai et al., 2024; Park et al., 2025), we use the subset of 39,053 samples annotated by board-certified radiologists. CheXpert includes a test set of images from 500 patients, labeled by five board-certified radiologists. Following (Lai et al., 2024), we evaluate classification performance on five observations: atelectasis, cardiomegaly, consolidation, edema, and pleural effusion.

Grounding Datasets. For visual grounding evaluation, we use ChestXDet10 and MS-CXR. ChestXDet10 is a subset of ChestXray14 and provides 542 official test images with bounding box annotations for 10 disease categories. Since ChestXDet10 also includes disease-level labels, we additionally evaluate classification performance on this dataset. MS-CXR contains 1,153 image–phrase–bounding box triplets derived from MIMIC-CXR. Because each bounding box is linked to a specific phrase from the corresponding radiology report, MS-CXR enables fine-grained phrase grounding evaluation. For a fair comparison, we follow (Chen et al., 2023) and evaluate on the released test set of 167 images.

A.2. Instructions for LLM-Based Abstract-Level Mapping

As described in Sec. 3.1, we instruct Qwen3-Next-80B to additionally extract a structured tuple containing topic and presence information for abstract-level sentence mapping. The instruction used for this process is shown in Fig. 3. We filter the generated outputs based on their format, and revise the few samples that do not conform to the Python dictionary format.

I want to extract a structured Python dictionary from the following phrase: {phrase}.

- (1) The dictionary must contain exactly two keys — "presence", and "topic" — and follow this format: `{{"presence": ..., "topic": ...}}`.
- (2) Do not leave any values blank or as "". Each dictionary value must contain only a single element.
- (3) The term "unremarkable" means that there seems no abnormality in the given anatomical structure - In such cases, just return the unremarkable + organ name as the "topic".
- (4) The "presence" field must be one of: "yes", "no", or "maybe yes".
- (5) The "topic" should represent the specific disease, device, or material mentioned in the phrase. Use concise key terms (e.g., use "effusion" instead of "right effusion"), omit unnecessary modifiers (e.g., bilateral, moderate, significant, confluent), but **do not omit any essential nouns** (e.g., use "clear lung" and "normal lung" instead of "clear" and "normal", respectively).
- (6) If the phrase contains multiple diseases or findings, do not omit any. In such cases, return multiple dictionaries, ensuring each dictionary still contains only one element per value.
- (7) Do not include any additional text before or after the output. Return only the Python dictionary. Please strictly follow conditions (1)-(7) and output only the Python dictionary without any extra comments.

Figure 3: Instruction prompt used to extract structured tuples for abstract-level sentence mapping.

B. Additional Experiments

Table 4 shows the ablation results of text feature conditioning in the feature modulation unit. Text conditioning improves performance on most datasets, indicating the benefit of incorporating textual context into feature modulation.

Table 4: Ablation results of text feature conditioning in feature modulation units.

	Classification					Grounding	
	OpenI	CXR14	PadChest	CXD10	CheXPert	CXD10	MS-CXR
w/o text feature	0.8804	0.8358	0.8599	0.8523	0.9000	0.7298	0.9042
w/ text feature	0.8891	0.8389	0.8609	0.8433	0.9037	0.7315	0.9222

Tables 5 and 6 report the effects of varying the false-negative loss coefficient and patch sampling ratio, respectively. In Table 6, the coefficient is fixed at $\lambda_{fn} = 0.01$. For the results reported in the main table, we use $\lambda_{fn} = 0.01$ and a patch sampling ratio of 20%.

Table 5: Effect of false negative loss coefficient.

λ_{fn}	Classification					Grounding	
	OpenI	CXR14	PadChest	CXD10	CheXPert	CXD10	MS-CXR
0.01	0.8891	0.8389	0.8609	0.8433	0.9037	0.7315	0.9222
0.03	0.8851	0.8381	0.8637	0.8490	0.9074	0.7018	0.8922
0.05	0.8882	0.8377	0.8591	0.8510	0.9047	0.7209	0.9341

Table 6: Effect of false negative patch sampling ratio, with $\lambda_{fn} = 0.01$.

M	Classification					Grounding	
	OpenI	CXR14	PadChest	CXD10	CheXPert	CXD10	MS-CXR
10%	0.8815	0.8350	0.8621	0.8457	0.9039	0.6998	0.9281
20%	0.8891	0.8389	0.8609	0.8433	0.9037	0.7315	0.9222
30%	0.8818	0.8335	0.8613	0.8489	0.8951	0.7168	0.9341

C. Additional Visualization Examples

We additionally visualize attention heatmaps to examine whether the pretrained model can perform reliable zero-shot grounding across diverse expressions and images. Fig. 4 presents additional examples from the ChestXDet10 dataset.




Figure 4: Additional attention heatmap examples from the ChestXDet10 dataset.

We also visualize attention maps for samples from the MS-CXR dataset in Fig. 5. Compared to ChestXDet10, MS-CXR contains longer and more detailed text phrases paired with corresponding bounding boxes, requiring more fine-grained visual grounding. These results show that our proposed model can perform zero-shot visual grounding not only for short text prompts, but also for longer and more detailed clinical descriptions.




Figure 5: Additional attention heatmap examples from the MS-CXR dataset.