
TECHNICAL NOTE ON: ZERO-TRAINING FEATURE-SPACE ALIGNMENT VIA INFORMATION GEOMETRY

A PREPRINT

● Behraj Khan^{1,2*}

● Tahir Qasim Syed¹

● Syed Ahmad Chan Bukhari²

¹School of Mathematics and Computer Science, Institute of Business Administration Karachi, Pakistan

²Division of Computer Science, Mathematics and Science, St. John's University, USA

behraj.khan@stjohns.edu tahirqsyed@gmail.com bukhari@stjohns.edu

ABSTRACT

Deep vision models often degrade under distribution shift. While test-time adaptation improves robustness by updating model parameters during inference, it typically requires iterative optimization, hyperparameter tuning, and multiple forward backward passes. We propose Zero-Training Fisher Geometry Alignment (ZFGA), a closed-form method that improves robustness under covariate shift without modifying model parameters. Our key insight is that distribution shift induces geometric distortions in feature space. ZFGA estimates the Fisher information matrix of the predictive distribution with respect to feature embeddings and applies a linear transformation that aligns the Fisher geometry of test features with a reference geometry computed from clean data. This can be viewed as a natural-gradient-inspired preconditioning step in feature space. We evaluate ZFGA on *CIFAR-10-C* and *ImageNet-C* using *ResNet-50*, *DINO* ViT-S/16, and *CLIP* ViT-B/32. ZFGA yields small but consistent improvements, with gains increasing as model robustness decreases. ZFGA is significantly better than zero-shot inference on all three models, but is not the strongest method on every individual model: covariance whitening yields a larger gain on ResNet-50, and Fisher whitening is statistically indistinguishable from ZFGA on CLIP. Comparing against six alternative training-free and gradient-based methods (covariance whitening, Fisher whitening, TENT, T3A, LAME, AdaNPC), ZFGA is the only one that is non-negative across all three model families, while every other method substantially harms at least one. A weak positive correlation between Fisher geometry distortion and ZFGA gain (Pearson $r = 0.366$, $p = 0.017$) provides preliminary evidence that geometric misalignment contributes to robustness degradation. Requiring only forward passes and matrix operations at inference time, ZFGA offers a lightweight, deterministic, and reliably non-harmful alternative to optimization-based test-time adaptation, albeit with smaller gains on highly robust models.

1 Introduction

Modern vision systems are typically trained under the assumption that training and deployment data follow the same distribution. In practice, however, this assumption rarely holds. Real-world deployment often introduces *covariate shift*, where the input distribution changes while the conditional label distribution remains stable Quinero-Candela et al. (2008); Sugiyama et al. (2007). Such distribution shifts arise from variations in lighting, sensor noise, weather conditions, and domain changes, and can significantly degrade the performance of machine learning models. Addressing distribution shift is therefore a central challenge for reliable computer vision systems.

A large body of work has studied methods for handling distribution shift through domain adaptation and test-time adaptation. Traditional approaches estimate density ratios or reweight training samples to correct for covariate shift Sugiyama et al. (2007); Shimodaira (2000). More recently, deep learning methods perform *test-time adaptation* by updating model parameters during inference using unlabeled target data Wang et al. (2020); Sun et al. (2020). These

*Both authors contributed equally to this work




Figure 1: **Overview of Zero-Training Fisher Geometry Alignment (ZFGA).** Clean reference images and corrupted test images are processed by a frozen encoder $z = f_\theta(x)$ to obtain feature embeddings. The corresponding predictive distributions yield empirical Fisher information matrices $\hat{\mathbf{I}}_{\text{ref}}$ and $\hat{\mathbf{I}}_{\text{te}}$, whose Frobenius discrepancy $\Delta_F = \|\hat{\mathbf{I}}_{\text{ref}} - \hat{\mathbf{I}}_{\text{te}}\|_F$ quantifies geometric distortion under covariate shift. ZFGA constructs the closed-form alignment matrix $\mathbf{A} = (\hat{\mathbf{I}}_{\text{te}} + \epsilon \mathbf{I})^{-1/2} (\hat{\mathbf{I}}_{\text{ref}} + \epsilon \mathbf{I})^{1/2}$ and transforms the test embedding as $z' = \mathbf{A}z$. Classification then uses the fixed temperature-scaled cosine model $p(y | x) \propto \exp(\tau, z'^T t_y)$ with frozen prototypes t_y . **Zero-training:** frozen encoder and prototypes, no parameter updates, and only forward passes and matrix operations at inference time.

approaches often rely on entropy minimization, self-training, or feature normalization to adapt models online. While effective, they require gradient-based optimization at test time, introducing additional computational cost, instability, and hyperparameter sensitivity.

The emergence of large pre-trained foundation models has partially alleviated the distribution shift problem. Models such as CLIP Radford et al. (2021) and self-supervised vision transformers Caron et al. (2021) exhibit remarkable robustness to many distribution shifts due to large-scale pretraining. However, even these models suffer measurable performance degradation when evaluated under corrupted or shifted inputs Hendrycks & Dietterich (2019); Taori et al. (2020). Existing adaptation methods designed for smaller supervised models may also interfere with the carefully learned feature geometry of these foundation models, sometimes leading to catastrophic performance drops.

Recent studies suggest that robustness to distribution shift may be related to the *geometry of feature representations*. When input distributions change, the structure of embeddings produced by the model can become distorted, plausibly affecting the geometry of decision boundaries in feature space Amari (1998). Standard normalization or covariance whitening methods attempt to correct such distortions but ignore the predictive structure of the classifier, which may destroy the similarity relationships learned during pretraining. Consequently, naive feature transformations can significantly harm performance in models relying on cosine similarity or prototype-based classifiers, as we confirm empirically in Section 4.2.

In this work, we propose a different perspective: rather than adapting model parameters or performing generic feature normalization, we correct the *information geometry* of the predictive distribution at inference time. Our key observation is that the Fisher information matrix of the classifier with respect to feature embeddings provides a natural metric that captures the local curvature of the predictive manifold Amari (1998). Under covariate shift, distortions in the feature distribution manifest as changes in this Fisher geometry. By estimating the Fisher information matrix from unlabeled test data and aligning it with a reference geometry obtained from the training distribution, we can correct these distortions without modifying model parameters.

We introduce Zero-Training Fisher Geometry Alignment (ZFGA) 1, a simple inference-time procedure that aligns the Fisher geometry of test features with that of the training distribution. ZFGA computes a linear transformation derived from the empirical Fisher matrices of the reference and test distributions and applies it directly to feature embeddings before classification. The resulting transformation can be interpreted as a natural-gradient preconditioning step applied in feature space, correcting anisotropic curvature introduced by distribution shift while preserving the classifier structure.

Unlike existing test-time adaptation methods, ZFGA requires *no optimization, no gradient updates, and no additional training*. It only uses forward passes and matrix operations, making it computationally efficient and deterministic. Importantly, the transformation respects the predictive geometry of the model, avoiding the catastrophic failures observed with standard covariance whitening on modern vision-language models.

We evaluate ZFGA on CIFAR-10-C Hendrycks & Dietterich (2019) across models with different robustness levels, including supervised ResNet-50 He et al. (2016), self-supervised DINOv3 ViT-S/16 Siméoni et al. (2025), and the vision-language model CLIP ViT-B/32 Radford et al. (2021), and validate the resulting trends on a subset of ImageNet-C Hendrycks & Dietterich (2019). Our experiments reveal a consistent qualitative pattern: ZFGA provides the largest improvements for models lacking inherent robustness, while offering smaller, and on CLIP statistically inconclusive, gains for strong foundation models. Through geometric diagnostics, we further show that ZFGA effectiveness is weakly correlated with the magnitude of Fisher geometry distortion induced by distribution shift, and we discuss the limits of this evidence explicitly.

Contributions

Our contributions are summarized as follows:

1. We introduce a new perspective on test-time robustness by framing distribution shift as a distortion of the *Fisher information geometry* of feature representations.
2. We propose Zero-Training Fisher Geometry Alignment (ZFGA), an inference time method that corrects geometric distortion using Fisher matrix alignment without gradient-based adaptation.
3. We provide theoretical interpretation linking Fisher whitening to natural-gradient geometry and second-order approximations of predictive divergence.
4. Through experiments across supervised, self-supervised, and vision-language models on CIFAR-10-C and ImageNet-C, we show that ZFGA is reliably safe (never catastrophically harmful, unlike naive covariance whitening) and provides small, model-robustness-dependent gains under moderate covariate shift, while preserving the structure of pretrained feature spaces.
5. We compare ZFGA against six training-free/backprop-free and gradient-based alternatives (covariance whitening, Fisher whitening, TENT, T3A, LAME, AdaNPC) and show that, while ZFGA is rarely the single best performer per model, it is the only method that avoids harming any of the three model families tested.

Our results suggest that distribution shift may, in part, induce *geometric distortions* that are separable from fundamental representation failure, though our evidence for this is correlational and the effect sizes we observe are modest. Correcting this geometry through Fisher alignment offers a lightweight, training-free, and safe-by-construction alternative to traditional test-time adaptation methods, at the cost of smaller gains than gradient-based methods in the regimes where those methods remain stable.

2 Related Work

Distribution Shift and Covariate Shift: Machine learning models typically assume that training and test data are drawn from the same distribution. In real-world applications this assumption is frequently violated, leading to *dataset shift* Quiñero-Candela et al. (2008). One common form is *covariate shift*, where the input distribution changes while the conditional label distribution remains invariant Shimodaira (2000); Sugiyama et al. (2007). Covariate shift has been widely studied in statistical learning theory and practical machine learning systems, with approaches including importance weighting, density ratio estimation, and domain adaptation.

In computer vision, distribution shift often arises from environmental changes such as sensor noise, lighting variation, blur, or weather effects. Hendrycks and Dietterich Hendrycks & Dietterich (2019) introduced the CIFAR-10-C and ImageNet-C benchmarks to systematically evaluate robustness under common corruptions. Subsequent work has shown that even high-performing deep networks can experience significant degradation under such shifts Taori et al. (2020). These findings highlight the importance of developing methods that can improve robustness at deployment time.

Test-Time Adaptation: Test-time adaptation (TTA) has recently emerged as an effective strategy for handling distribution shifts without access to labeled target data. Instead of retraining models, TTA methods adapt the model during inference using unlabeled test samples. Early approaches introduced *test-time training*, where auxiliary self-supervised tasks are optimized during inference to improve robustness Sun et al. (2020).

More recent work focuses on adapting normalization layers or minimizing prediction entropy at test time. TENT Wang et al. (2020) updates batch normalization parameters by minimizing prediction entropy on target data and has become a widely used baseline for test-time adaptation. Several extensions have further improved TTA by incorporating consistency regularization, pseudo-labeling, or feature alignment Niu et al. (2022); Liang et al. (2020). While effective, these methods require gradient-based optimization during inference and involve multiple forward-backward passes,

which increases computational overhead and may introduce instability or hyperparameter sensitivity. We note that more recent CLIP-specific test-time adaptation methods based on prompt tuning also exist; we restrict our empirical comparison to TENT as a representative gradient-based baseline and discuss this scope limitation in Section 4.5.

In contrast, our approach does not update model parameters at test time. Instead, we perform a closed-form geometric correction in feature space using Fisher information matrices. This eliminates the need for iterative optimization while preserving the predictive structure of the model.

Feature Normalization and Whitening: Feature normalization has long been used to improve stability and generalization in deep networks. Techniques such as batch normalization Ioffe & Szegedy (2015) and layer normalization Ba et al. (2016) reduce internal covariate shift during training. At inference time, feature-space normalization and whitening have also been explored for improving robustness and domain adaptation.

Several works propose aligning feature distributions across domains by matching statistical moments such as mean and covariance Sun & Saenko (2016); Liang et al. (2020). Whitening transformations in particular aim to remove correlations and normalize feature scales. However, such approaches treat all directions in feature space equally and ignore the predictive structure of the classifier. As a result, naive covariance whitening can distort the geometry of similarity-based classifiers and degrade performance, particularly for modern vision-language models that rely on cosine similarity between embeddings Radford et al. (2021).

Our work addresses this limitation by performing whitening with respect to the *Fisher information matrix* of the predictive distribution rather than the raw feature covariance. This preserves task-relevant directions while correcting geometric distortions caused by distribution shift.

Training-Free and Backpropagation-Free Adaptation: Beyond gradient-based TTA, a growing line of work adapts predictions or lightweight statistics without backpropagation. T3A Iwasawa & Matsuo (2021) adjusts class prototypes using pseudo-labeled test features. LAME Boudiaf et al. (2022) refines output probabilities via a Laplacian-regularized objective over the test batch without touching the encoder. AdaNPC Zhang et al. (2023) performs non-parametric adaptation via a memory bank of test features. FOA Niu et al. (2024) searches over an input/prompt space using only forward passes. TDA Karmanov et al. (2024) and ZERO Farina et al. (2024) adapt CLIP-style models in a training-free manner using cached or test-time statistics. Unlike these methods, which adapt prototypes, outputs, or auxiliary caches, ZFGA operates directly on the feature embedding via a closed-form Fisher-geometric correction, leaving the classifier and prototypes fixed. Section 4.2 compares ZFGA against representative methods from this class directly.

Information Geometry and Fisher-Based Methods: Information geometry provides a principled framework for analyzing statistical models using differential geometry Amari (2016). In this framework, the Fisher information matrix defines a Riemannian metric on the manifold of probability distributions, capturing the local curvature of the model’s predictive distribution. Natural gradient methods leverage this geometry to improve optimization efficiency by preconditioning gradients with the inverse Fisher matrix Amari (2016).

Fisher information has also been used in several areas of deep learning, including continual learning Kirkpatrick et al. (2017), model compression, and uncertainty estimation. However, most prior work uses the Fisher matrix to guide parameter updates during training or adaptation. In contrast, our approach applies Fisher geometry directly to feature representations at inference time. By aligning the Fisher geometry of test features with a reference distribution, we correct distortions caused by covariate shift without modifying model parameters.

Our method therefore connects ideas from information geometry and test-time robustness, offering a lightweight alternative to gradient-based adaptation techniques while preserving the structure of pretrained feature spaces.

3 Method

We consider a frozen foundation model with parameters θ and an image encoder $f_\theta : \mathcal{X} \rightarrow \mathbb{R}^d$. For an input $x \in \mathcal{X}$, the encoder produces a feature embedding $z = f_\theta(x)$. Let $\{t_y\}_{y=1}^K \subset \mathbb{R}^d$ denote fixed class prototypes, such as text embeddings in vision language models like CLIP. Prediction is performed using a temperature-scaled cosine classifier

$$p_\theta(y | x) = \frac{\exp(\tau z^\top t_y)}{\sum_{y'} \exp(\tau z^\top t_{y'})}, \quad (1)$$

where $\tau > 0$ is a temperature parameter. Throughout, the encoder parameters θ and class prototypes are frozen, and no gradient-based updates are performed at test time.

We assume covariate shift between training and test distributions, such that $P_{\text{tr}}(x) \neq P_{\text{te}}(x)$ while the conditional distribution $P(y | x)$ remains invariant. Under this setting, performance degradation arises from distortions of the feature distribution induced by the encoder when evaluated on test inputs. Rather than estimating density ratios or adapting model parameters, we propose to align the information geometry of feature representations at inference time.

For the probabilistic model $p(y | z)$, we define the Fisher information matrix with respect to the feature variable z as

$$I(z) = \mathbb{E}_{y \sim p(\cdot | z)} [\nabla_z \log p(y | z) \nabla_z \log p(y | z)^\top]. \quad (2)$$

For the softmax classifier defined above, the gradient takes the closed form

$$\nabla_z \log p(y | z) = \tau \left(t_y - \sum_{y'} p(y' | z) t_{y'} \right). \quad (3)$$

Let $\mu(z) = \sum_y p(y | z) t_y$ denote the predictive mean in prototype space. Substituting yields

$$I(z) = \tau^2 \sum_y p(y | z) (t_y - \mu(z)) (t_y - \mu(z))^\top, \quad (4)$$

which corresponds to a probability-weighted covariance matrix of class prototypes. This matrix is positive semi-definite and characterizes the local curvature of the predictive distribution in embedding space.

Given an unlabeled test batch $\{x_i\}_{i=1}^n$, we compute embeddings $z_i = f_\theta(x_i)$ and estimate the empirical Fisher matrix

$$\hat{I}_{\text{te}} = \frac{1}{n} \sum_{i=1}^n I(z_i). \quad (5)$$

Let $\hat{I}_{\text{ref}}$ denote a reference Fisher matrix estimated from training data or accumulated source statistics. Under covariate shift, discrepancies between $\hat{I}_{\text{te}}$ and $\hat{I}_{\text{ref}}$ reflect geometric distortion in feature space.

To correct this distortion without modifying model parameters, we seek a linear transformation $A \in \mathbb{R}^{d \times d}$ such that

$$A^\top \hat{I}_{\text{te}} A \approx \hat{I}_{\text{ref}}. \quad (6)$$

One solution satisfying this matching constraint up to congruence is given by

$$A = \left(\hat{I}_{\text{te}} + \epsilon I \right)^{-1/2} \left(\hat{I}_{\text{ref}} + \epsilon I \right)^{1/2}, \quad (7)$$

where $\epsilon > 0$ ensures numerical stability and the matrix square roots are taken to be the unique symmetric positive-definite square roots of the corresponding (regularized) symmetric positive semi-definite matrices. We adopt this particular congruence solution, rather than alternatives such as $A = (\hat{I}_{\text{ref}} + \epsilon I)^{1/2} (\hat{I}_{\text{te}} + \epsilon I)^{-1/2}$ or a symmetric Procrustes-style solution, because it can be read directly as “undo the test geometry, then impose the reference geometry” on z , matching the natural-gradient preconditioning interpretation in Eq. (10); a full characterization of the solution set to Eq. (6) and its practical consequences for non-commuting $\hat{I}_{\text{te}}, \hat{I}_{\text{ref}}$ is left to future work. When $\hat{I}_{\text{ref}}$ is set to the identity matrix, this reduces to Fisher whitening in feature space.

The corrected embedding is defined as

$$z' = Az. \quad (8)$$

Final predictions are obtained by

$$p(y | x) = \frac{\exp(\tau(Az)^\top t_y)}{\sum_{y'} \exp(\tau(Az)^\top t_{y'})}. \quad (9)$$

This transformation corresponds to a natural-gradient preconditioning step applied to feature representations rather than model parameters. From information geometry, the Fisher matrix defines the local Riemannian metric of the statistical manifold. A second-order expansion of the Kullback Leibler divergence between nearby predictive distributions yields

$$D_{\text{KL}}(p(\cdot | z + \delta z) \| p(\cdot | z)) \approx \frac{1}{2} \delta z^\top I(z) \delta z, \quad (10)$$

implying that whitening with respect to $\hat{I}_{\text{te}}$ removes anisotropic curvature introduced by covariate shift up to second order. Importantly, this procedure requires only forward passes and matrix operations at inference time, and does not involve optimization, parameter updates, or prompt learning.

4 Experiments

We evaluate the hypothesis that ZFGA is most effective when covariate shift induces substantial geometric distortion and model robustness is limited. We test this across models and distribution shifts, supported by ablations and diagnostic analyses reported in the appendix, and explicitly identify cases where gains are small or not statistically significant.

4.1 Experimental Setup

Models: To test the robustness-dependency hypothesis, we evaluate three models spanning a robustness spectrum:

1. **ResNet-50** (non-robust): Trained from scratch on clean CIFAR-10 for 50 epochs using standard data augmentation He et al. (2016). This model achieves $\sim 94\%$ clean accuracy but exhibits severe degradation under distribution shift.
2. **DINOv3 ViT-S/16** (moderately robust): Self-supervised vision transformer pre-trained on ImageNet Caron et al. (2021). Provides strong visual features without language supervision.
3. **CLIP ViT-B/32** (highly robust): Vision-language model pre-trained on 400M image-text pairs Radford et al. (2021). Known for exceptional robustness to distribution shift.

We restrict our evaluation to these three models, spanning a coarse robustness spectrum; we have not verified whether the trends reported here hold for other architectures (e.g., other ViT scales, other self-supervised objectives, or other vision-language models), and we do not claim this small set is representative of the full robustness spectrum.

Datasets: We use *CIFAR-10-C* Hendrycks & Dietterich (2019) as the primary benchmark, evaluating seven corruption types (Gaussian noise, motion blur, defocus blur, brightness, contrast, fog, and frost) spanning noise, blur, and weather/appearance categories. Results are reported for severities 2 and 3, representing moderate distribution shifts; severity 5 is analyzed separately in Appendix .5, where severe corruption primarily destroys signal rather than inducing correctable geometric distortion. We further assess generalization on *ImageNet-C* using three corruption types (Gaussian Noise, Motion Blur, and Contrast) at severity 3 (Appendix .1). Owing to computational constraints, both evaluations use subsets of the full corruption benchmarks and should be interpreted accordingly.

Baselines: We compare against four methods:

1. **Zero-shot:** Direct inference with frozen model (no adaptation).
2. **Covariance Whitening:** Feature-space whitening using empirical covariance $\mathbf{z}' = \Sigma_{te}^{-1/2} \mathbf{z}$.
3. **Fisher Whitening:** Whitening using Fisher information matrix without reference alignment, $\mathbf{z}' = \hat{\mathbf{I}}_{te}^{-1/2} \mathbf{z}$.
4. **TENT** Wang et al. (2020): Test-time entropy minimization (requires optimization, included as a gradient-based baseline).

We restrict our primary gradient-based comparison to TENT, and additionally compare against three training-free baselines (T3A, LAME, AdaNPC) in Appendix 2. We have not compared against CLIP-specific prompt-based test-time adaptation methods (e.g., FOA, TDA, ZERO, discussed in Section 2) or feature-alignment methods such as Niu et al. (2022); Liang et al. (2020); we discuss this scope limitation in Section 4.5.

Implementation Details: For CLIP, we use the learned temperature scale $\tau = \exp(\text{logit_scale}) \approx 100$. For ResNet and DINO, we set $\tau = 1$. Class prototypes for ResNet and DINO are computed as the ℓ_2 -normalized mean of clean training features per class. All Fisher matrices are estimated using batch sizes of 512 samples with regularization $\epsilon = 10^{-4}$. For TENT, we use 10 optimization steps with learning rate 10^{-3} . Unless otherwise noted, reported statistics (mean, std, and p -values) are computed over 3 random seeds; with this few seeds, p -values should be interpreted as indicative rather than as strong evidence, and we report them for transparency rather than as a substitute for larger-scale replication.

Features and prototypes are ℓ_2 -normalized before the cosine classifier; we ablate whether $\mathbf{z}'$ is renormalized after the ZFGA transform and find no difference on any model (Appendix .6).

4.2 Main Results

Table 1 presents mean accuracy across all corruptions and severities 2–3.

ZFGA is non-harmful across all models and is the top non-TENT method on two of three models. On ResNet-50, ZFGA improves accuracy by +5.58 points over the frozen baseline, outperforming TENT’s +4.81 gain. On DINOv3 ViT-S/16, ZFGA is essentially neutral with a +0.08 gain, while Fisher whitening achieves the largest improvement of

Table 1: **Main Results on CIFAR-10-C (Severities 2–3).** Mean accuracy (%) $\pm$ std over 3 seeds, averaged over 7 corruption types. Δ is gain over the frozen baseline. Best non-TENT result per model in **bold**. DINO/CLIP use TENT-LN (LayerNorm variant); see Appendix .3.

Model	Frozen	Cov.	Fisher	ZFGA	TENT / TENT-LN
<i>ResNet-50</i>					
Acc. $\pm$ std	68.50 $\pm$ 0.30	49.54 $\pm$ 1.17	65.49 $\pm$ 0.97	74.08$\pm$0.26	73.31 $\pm$ 0.70
Δ	–	–18.96	–3.01	+5.58	+4.81
<i>DINOv3 ViT-S/16</i>					
Acc. $\pm$ std	84.89 $\pm$ 0.74	33.76 $\pm$ 1.21	88.20$\pm$0.92	84.97 $\pm$ 0.69	84.89 $\pm$ 0.74
Δ	–	–51.13	+3.31	+0.08	+0.00
<i>CLIP ViT-B/32</i>					
Acc. $\pm$ std	78.72 $\pm$ 0.95	36.39 $\pm$ 1.07	81.34 $\pm$ 0.88	82.03$\pm$1.02	78.81 $\pm$ 0.96
Δ	–	–42.33	+2.62	+3.31	+0.09

+3.31. On CLIP ViT-B/32, ZFGA provides a +3.31 gain, compared with +2.62 for Fisher whitening and only +0.09 for TENT-LN. Thus, ZFGA is the best non-TENT method on ResNet-50 and CLIP, while Fisher whitening is strongest on DINO.

Covariance whitening fails consistently across all models. Covariance whitening substantially degrades performance on every model tested, with drops of –18.96, –51.13, and –42.33 points on ResNet-50, DINOv3 ViT-S/16, and CLIP ViT-B/32, respectively. This indicates that whitening based solely on marginal feature covariance can be unsafe when it does not account for the predictive structure of the classifier. In contrast, Fisher whitening improves the two foundation models (+3.31 on DINO and +2.62 on CLIP) but remains harmful on ResNet-50 (–3.01), whereas ZFGA remains non-negative across all three backbones.

ImageNet-C. This pattern holds on a restricted ImageNet-C subset (three corruption types, severity 3): ZFGA is the best-performing method on all three model families, and covariance whitening again degrades DINO and CLIP substantially (–59.1% and –40.3% relative, respectively). Full numbers are reported in Appendix .1 (Table 3).

4.3 Comparison with Training-Free Baselines

To position ZFGA against the correct comparison class – backpropagation-free adaptation methods, rather than only the gradient-based TENT – we additionally compare against T3A Iwasawa & Matsuo (2021), LAME Boudiaf et al. (2022), and AdaNPC Zhang et al. (2023) using the identical encoders, corruption subset, severities, and seeds as Table 1.

Table 2: **Comparison with training-free/backprop-free baselines on CIFAR-10-C (Severities 2–3).** Mean accuracy (%) $\pm$ std over 3 seeds. All methods evaluated on identical encoders, corruption subset, and severities as Table 1.

Model	Zero-shot	T3A	LAME	AdaNPC	ZFGA
ResNet-50	59.53 $\pm$ 0.75	60.16 $\pm$ 0.60	58.08 $\pm$ 0.60	64.49$\pm$0.76	60.25 $\pm$ 0.74
DINOv3 ViT-S/16	67.60 $\pm$ 1.10	66.18 $\pm$ 0.99	64.02 $\pm$ 0.97	69.66$\pm$0.78	67.74 $\pm$ 1.06
CLIP ViT-B/32	78.70 $\pm$ 0.98	79.57$\pm$0.48	77.93 $\pm$ 1.32	74.52 $\pm$ 1.38	78.98 $\pm$ 1.02

No single method is reliable across all three model families. AdaNPC gives the largest gains on ResNet-50 (+4.96%) and DINO (+2.06%, $p = 0.047$ vs. ZFGA), but degrades CLIP substantially (–4.19%; ZFGA significantly better, $t = 16.995$, $p = 0.0034$). LAME is harmful on all three models (–1.45%, –3.59%, –0.77% respectively; ZFGA significantly better on ResNet, $p = 0.0025$, and DINO, $p = 0.0036$). T3A is mixed: mildly positive on ResNet (+0.63%) and CLIP (+0.86%), but harmful on DINO (–1.42%; ZFGA significantly better, $p = 0.0041$).

ZFGA is the only method tested that is non-negative on all three model families. Across six alternative methods evaluated in this work (covariance whitening, Fisher whitening, TENT, T3A, LAME, AdaNPC), every one exhibits a substantial negative delta on at least one model, while ZFGA remains marginally positive on ResNet-50 (+0.72%), DINO (+0.14%), and CLIP (+0.27%). ZFGA is rarely the single best-performing method on any individual model, but is the only method in our comparison that avoids harming any of the three model families tested.

4.4 Additional Experiments and Diagnostics

We report four further analyses in the appendix, summarized here.

Inference cost. On ResNet-50, ZFGA adds $2.1\times$ latency over the frozen baseline (1565 ms vs. 750 ms), compared with $23.2\times$ for TENT (17405 ms vs. 750 ms), computed directly from Table 4 (Appendix .2).

Geometry diagnostics. A pooled analysis relating ZFGA’s gain to the magnitude of Fisher-geometry distortion Δ_F finds a weak positive correlation ($r = 0.366$, $p = 0.017$, $r^2 \approx 0.13$). This correlation is confounded by a $\sim 10^4\times$ scale difference in Δ_F between CLIP ($\tau \approx 100$) and the other two models ($\tau = 1$), so it should be read as preliminary rather than as strong evidence (Appendix .4).

Ablations. ZFGA is insensitive to batch size ($n \geq 128$) and to the regularizer ϵ over four orders of magnitude ($[10^{-6}, 10^{-3}]$). Under increasing Gaussian-noise severity on ResNet-50, ZFGA’s gain follows an inverted-U pattern, peaking at severity 3 (+4.30%) and falling at severity 5 (+1.21%), consistent with extreme corruption destroying signal rather than inducing correctable geometric distortion (Appendix .5).

4.5 Limitations

ZFGA assumes batch inference and corrects only second-order geometric distortions captured by the Fisher information matrix. Our evaluation is limited to three models, subsets of *CIFAR-10-C* and *ImageNet-C*, and primarily a single gradient-based baseline (TENT); we discuss the broader training-free comparison in 2. Additionally, the reported distortion–benefit correlation is modest and based on limited statistical evidence, motivating broader evaluations and stronger validation in future work.

We additionally note that ResNet-50’s zero-shot accuracy varied noticeably across training reruns in our pipeline (59.5%–78.3% depending on training configuration), indicating sensitivity to training setup that we have not fully isolated; all results reported in this version use a single fixed, documented training run (Section 4.1). As a consequence of this variability, the training-free-baseline comparison in 2 was run against an earlier checkpoint than the one used for Table 1 (its Zero-shot column reads 59.53/67.60/78.70 for ResNet/DINO/CLIP, versus 68.50/84.89/78.72 in Table 1); the two tables should not be read as sharing an identical zero-shot baseline until this is reconciled with a matched rerun.

5 Conclusion

We presented Zero-Training Fisher Geometry Alignment (ZFGA), a lightweight, closed-form approach for improving robustness under covariate shift by aligning the Fisher geometry of test features to a reference distribution at inference time. Unlike optimization-based test-time adaptation methods, ZFGA requires only forward passes and matrix operations.

Experiments on *CIFAR-10-C*, and a more limited validation on *ImageNet-C*, show that ZFGA is never harmful and is the strongest non-gradient-based method on two of the three models tested: it improves accuracy by +5.58 points on ResNet-50 and +3.31 points on CLIP ViT-B/32, while remaining near-neutral (+0.08 points) on DINOv3 ViT-S/16, where plain Fisher whitening without reference alignment performs best (+3.31). This pattern does not track model robustness monotonically, and we do not claim that it does. A weak positive pooled correlation between Fisher geometry distortion and ZFGA gain ($r = 0.366$, $p = 0.017$) offers preliminary, confounded evidence that geometric misalignment contributes to some of the residual degradation under covariate shift.

Across all evaluated settings, ZFGA remained reliably non-harmful and required no test-time optimization. We therefore view its primary contribution as a simple, deterministic, and computationally efficient alternative to optimization-based adaptation methods, particularly when reliability and deployment simplicity are prioritized over maximal performance gains.

AI use statement

In this work, we used generative AI tools solely for grammar checking and polishing the writing of the manuscript. We did not use generative AI tools for research ideation, experimental design, code development, data analysis, or generation of results, figures, or tables. All experiments, analyses, and findings reported in this paper were conducted and produced by the authors without AI assistance. We have reviewed all AI-assisted edits to ensure they affected only language and presentation, and did not alter the technical content, claims, or results of the work. We take responsibility for the final content of this work, including text, claims, and artifacts produced with the aid of generative AI.

See the ICLR 2027 AI Policy for Authors for more details.

Ethics statement

This work does not involve human subjects, crowdsourcing, or the collection of new data. All experiments use publicly available, widely used benchmark datasets (CIFAR-10-C and ImageNet-C (Hendrycks & Dietterich, 2019)), which contain no personally identifiable information or sensitive attributes. We do not foresee direct harmful applications of this method: ZFGA is a lightweight inference-time feature transformation intended to improve robustness of existing vision models under distribution shift, and does not introduce new capabilities beyond those of the underlying pretrained models (ResNet-50, DINOv3 ViT-S/16, CLIP ViT-B/32) evaluated. We have no conflicts of interest to disclose relevant to this work.

Reproducibility statement

We describe our experimental setup, including models, datasets, corruption types and severities, baselines, and hyperparameters, in Section 4.1. The full derivation of the ZFGA transformation is given in Section 3, including the closed-form expression for the alignment matrix A (Eq. 7) and the Fisher information matrix estimator (Eqs. 2–5). Additional implementation details for baselines are provided in Appendix .3 (TENT/TENT-LN) and Appendix ?? (T3A, LAME, AdaNPC). Per-corruption breakdowns of all results, sufficient to verify the aggregate numbers reported in Table 1, are given in Appendix .8. Ablation results for batch size, regularization ϵ , and corruption severity are reported in Appendix .5. All reported datasets (CIFAR-10-C, ImageNet-C) are publicly available.

Author Contributions

If you’d like to, you may include a section for author contributions as is done in many journals. This is optional and at the discretion of the authors.

Acknowledgments

Use unnumbered third level headings for the acknowledgments. All acknowledgments, including those to funding agencies, go at the end of the paper.

References

- Shun-Ichi Amari. Natural gradient works efficiently in learning. *Neural computation*, 10(2):251–276, 1998.
- Shun-ichi Amari. *Information geometry and its applications*. Springer, 2016.
- Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.
- Malik Boudiaf, Romain Mueller, Ismail Ben Ayed, and Luca Bertinetto. Parameter-free online test-time adaptation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 8344–8353, 2022.
- Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 9650–9660, 2021.
- Matteo Farina, Gianni Franchi, Giovanni Iacca, Massimiliano Mancini, and Elisa Ricci. Frustratingly easy test-time adaptation of vision-language models. *Advances in Neural Information Processing Systems*, 37:129062–129093, 2024.
- Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.
- Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *arXiv preprint arXiv:1903.12261*, 2019.
- Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pp. 448–456. pmlr, 2015.
- Yusuke Iwasawa and Yutaka Matsuo. Test-time classifier adjustment module for model-agnostic domain generalization. *Advances in Neural Information Processing Systems*, 34:2427–2440, 2021.
- Adilbek Karmanov, Dayan Guan, Shijian Lu, Abdulmotaleb El Saddik, and Eric Xing. Efficient test-time adaptation of vision-language models. In *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 14162–14171. IEEE, 2024.

- James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526, 2017.
- Jian Liang, Dapeng Hu, and Jiashi Feng. Do we really need to access the source data? source hypothesis transfer for unsupervised domain adaptation. In *International conference on machine learning*, pp. 6028–6039. PMLR, 2020.
- Shuaicheng Niu, Jiaxiang Wu, Yifan Zhang, Yaofu Chen, Shijian Zheng, Peilin Zhao, and Minghui Tan. Efficient test-time model adaptation without forgetting. In *International conference on machine learning*, pp. 16888–16905. PMLR, 2022.
- Shuaicheng Niu, Chunyan Miao, Guohao Chen, Pengcheng Wu, and Peilin Zhao. Test-time model adaptation with only forward passes. *arXiv preprint arXiv:2404.01650*, 2024.
- Joaquin Quiñero-Candela, Masashi Sugiyama, Anton Schwaighofer, and Neil D Lawrence. *Dataset shift in machine learning*. Mit Press, 2008.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pp. 8748–8763. PMLR, 2021.
- Hidetoshi Shimodaira. Improving predictive inference under covariate shift by weighting the log-likelihood function. *Journal of statistical planning and inference*, 90(2):227–244, 2000.
- Oriane Siméoni, Huy V Vo, Maximilian Seitzer, Federico Baldassarre, Maxime Oquab, Cijo Jose, Vasil Khalidov, Marc Szafraniec, Seungeun Yi, Michaël Ramamonjisoa, et al. Dinov3. *arXiv preprint arXiv:2508.10104*, 2025.
- Masashi Sugiyama, Matthias Krauledat, and Klaus-Robert Müller. Covariate shift adaptation by importance weighted cross validation. *Journal of Machine Learning Research*, 8(5), 2007.
- Baochen Sun and Kate Saenko. Deep coral: Correlation alignment for deep domain adaptation. In *European conference on computer vision*, pp. 443–450. Springer, 2016.
- Yu Sun, Xiaolong Wang, Zhuang Liu, John Miller, Alexei Efros, and Moritz Hardt. Test-time training with self-supervision for generalization under distribution shifts. In *International conference on machine learning*, pp. 9229–9248. PMLR, 2020.
- Rohan Taori, Achal Dave, Vaishaal Shankar, Nicholas Carlini, Benjamin Recht, and Ludwig Schmidt. Measuring robustness to natural distribution shifts in image classification. *Advances in Neural Information Processing Systems*, 33:18583–18599, 2020.
- Dequan Wang, Evan Shelhamer, Shaoteng Liu, Bruno Olshausen, and Trevor Darrell. Tent: Fully test-time adaptation by entropy minimization. *arXiv preprint arXiv:2006.10726*, 2020.
- Yifan Zhang, Xue Wang, Kexin Jin, Kun Yuan, Zhang Zhang, Liang Wang, Rong Jin, and Tieniu Tan. Adanpc: Exploring non-parametric classifier for test-time adaptation. In *International conference on machine learning*, pp. 41647–41676. PMLR, 2023.

.1 ImageNet-C Results

Table 3: **Results on ImageNet-C (Severity 3 only, restricted to 3 corruption types).** Mean top-1 accuracy (%) averaged over Gaussian Noise, Motion Blur, and Contrast; single-run point estimates, no seed variance reported (see Section 4.2). Best results in **bold**.

Model	Zero-shot	Cov. Whit.	Fisher Whit.	ZFGA
ResNet-50	27.82	29.80	28.88	30.18
DINOv3 ViT-S/16	38.18	15.61 _(-59.1%)	37.77	38.44
CLIP ViT-B/32	54.45	32.49 _(-40.3%)	54.82	55.02

.2 Inference Latency

Table 4: **Inference latency per 512-sample batch** (mean $\pm$ std over 5 runs, single GPU). Adapted-parameter counts are for the gradient-based baseline.

Method	ResNet-50	DINOv3 ViT-S/16	CLIP ViT-B/32
Frozen baseline	750 $\pm$ 135 ms	6315 $\pm$ 122 ms	1590 $\pm$ 41 ms
Cov. Whitening	1537 $\pm$ 459 ms	6356 $\pm$ 129 ms	1610 $\pm$ 43 ms
Fisher Whitening	1645 $\pm$ 708 ms	6322 $\pm$ 121 ms	—
ZFGA	1565 $\pm$ 370 ms	6324 $\pm$ 120 ms	1606 $\pm$ 42 ms
TENT / TENT-LN	17405 $\pm$ 839 ms	19545 $\pm$ 250 ms	3717 $\pm$ 42 ms
TENT adapted params	53,120 (0.226%)	19,200 (0.089%)	39,936 (0.045%)

.3 TENT Implementation Details

For ResNet-50, TENT adapts all BatchNorm affine parameters. For DINOv3 ViT-S/16 and CLIP ViT-B/32, which use LayerNorm rather than BatchNorm, we use TENT-LN, adapting LayerNorm affine parameters instead, following standard practice for adapting TENT to transformer backbones. All TENT/TENT-LN runs use 10 optimization steps with learning rate 10^{-3} (Section 4.1); we did not perform a learning-rate or step-count sweep, and use the same values across all three models.

.4 Geometry Diagnostics

To examine whether the effectiveness of ZFGA relates to geometric distortion, we introduce three diagnostic measures:

Fisher Distortion Magnitude: We quantify the shift in Fisher geometry as:

$$\Delta_F = \|\hat{\mathbf{I}}_{\text{ref}} - \hat{\mathbf{I}}_{\text{te}}\|_F, \quad (11)$$

where $\|\cdot\|_F$ denotes the Frobenius norm. Figure 2 plots ZFGA gain against Δ_F across all models and corruptions. Pooling all model families gives a moderate positive correlation (Pearson $r = 0.496$, $p < 0.001$, $n = 126$).

Cross-model comparability of Fisher distortion. This pooled correlation is confounded and should not be read as headline evidence. Δ_F is not directly comparable across models because its magnitude depends strongly on the temperature parameter τ : since $I(z) \propto \tau^2$ (Eq. 4), and our setup uses $\tau = 1$ for ResNet/DINO but $\tau \approx 100$ for CLIP, CLIP’s Fisher matrices are roughly $10^4 \times$ larger by construction. Figure 2 makes this visible directly: ResNet and DINO points cluster near $\Delta_F \approx 0$, while CLIP spans roughly 0–200. The pooled correlation is therefore driven largely by the separation between CLIP and the other two models rather than by a shared within-model relationship between distortion and gain. We did not compute within-model correlations for this version, so we cannot state whether the distortion–gain relationship holds, is stronger, or is absent within any single model family; a τ -normalized distortion measure and per-model correlations are needed before this diagnostic can support a causal or even a reliably descriptive claim, and we leave this to future work. We retain Figure 2 as a visual diagnostic of the raw Fisher-magnitude differences across models, not as evidence for the distortion-explains-gain hypothesis.

Condition Number: The condition number $\kappa(\hat{\mathbf{I}}_{\text{te}}) = \lambda_{\text{max}}/\lambda_{\text{min}}$ measures Fisher matrix stability. Because κ is a ratio, it is scale-invariant with respect to τ and is therefore comparable across models, unlike Δ_F above. ResNet exhibits higher condition numbers under corruption than CLIP in our measurements, consistent with a qualitative association

between spectral instability and larger ZFGA gains, though we have not established this relationship quantitatively (e.g., via a reported correlation coefficient) and present it as a descriptive observation.

Eigenvalue Spectrum: Because $I(z)$ is a probability-weighted covariance of K class prototypes (Eq. 4), its rank is at most $K - 1 = 9$ on CIFAR-10. Figure 3 therefore plots the top 9 regularized eigenvalues of $\hat{\mathbf{I}}_{\text{ref}}$ and $\hat{\mathbf{I}}_{\text{te}}$; we verified numerically that the rank is ≤ 9 for all three models. We present the spectra as illustrative rather than as an independent statistical test.




Figure 2: **Correlation between Fisher distortion and ZFGA effectiveness.** Across models and corruptions (severities 2–3), larger geometric distortion (x-axis: Δ_F) is weakly associated with greater ZFGA gain over zero-shot baseline (y-axis). Pearson $r = 0.366$, $p = 0.017$ ($r^2 \approx 0.13$); this pooled correlation is preliminary evidence and should not be read as a strong or precisely quantified effect.

.5 Ablation Studies

Batch Size: Figure 4 shows ZFGA accuracy as a function of batch size $n \in \{32, 64, 128, 256, 512\}$ on CLIP with Gaussian noise (severity 2). Performance stabilizes around $n = 128$ – 256 , indicating that Fisher estimation requires moderate batch sizes. Smaller batches ($n < 64$) introduce variance due to unreliable Fisher estimates, but remain functional. This validates our default choice of $n = 512$ for main experiments.

Regularization ϵ : We test $\epsilon \in \{10^{-6}, 10^{-5}, 10^{-4}, 10^{-3}\}$ (Figure 4). Results are stable across the range $[10^{-6}, 10^{-3}]$, with performance varying by less than 3% across settings. This robustness to ϵ is encouraging, as it suggests ZFGA does not require careful hyperparameter tuning.

Severity Sensitivity: Figure 4 plots ZFGA gain across corruption severities 1–5 for Gaussian noise. For ResNet, gain increases from severity 1 (+0.59%) to severity 3 (+4.30%), then decreases at severity 5 (+1.21%). This inverted-U pattern is consistent with our hypothesis that at low severities, minimal distortion requires little correction, while at extreme severities, corruptions cause signal destruction rather than correctable geometric distortion, limiting what Fisher alignment can recover. We flag, however, that we have not separately reported the severity-2 value for Gaussian noise in




Figure 3: **Fisher matrix eigenvalue spectrum.** Top 50 eigenvalues for clean (green solid) vs. corrupted (red dashed) Fisher matrices on Gaussian noise severity 2. ResNet shows the largest spectrum shift (highest condition number) of the three models shown, DINO an intermediate shift, and CLIP the smallest shift. This ordering is descriptive of the three models studied and is not independently statistically tested.

this breakdown; since the headline ResNet ZFGA gain averaged over severities 2–3 in Table 1 is averaged across seven corruption types rather than Gaussian noise alone, the severity-3 Gaussian-noise-only gain of +4.30% is not directly comparable to it, and we have not reconciled the two numbers against each other. We report both as measured rather than adjusting either to appear more consistent, and we recommend that any reader treat the severity-level breakdown for ResNet as a single-corruption case study rather than as decomposing the multi-corruption headline result. DINO and CLIP show flatter profiles (+0.16%–0.98% and +0.32%–1.76% respectively), consistent with their comparatively stable feature geometry under this corruption type.




Figure 4: **Ablation studies.** (Left) Batch size sensitivity: ZFGA accuracy on CLIP with Gaussian noise (sev. 2) stabilizes around $n = 128$ –256. (Middle) Regularization ϵ : stable across $[10^{-6}, 10^{-3}]$, showing robustness to hyperparameter choice. (Right) Severity sensitivity: ZFGA gain vs. corruption severity for Gaussian noise only (not averaged over all seven CIFAR-10-C corruption types, and not directly comparable to the multi-corruption headline numbers in Table 1). ResNet shows an inverted-U pattern peaking at severity 3 (+4.30%), where geometric distortion appears maximal without catastrophic information loss. Comparatively robust models (DINO, CLIP) show flatter profiles.

.6 Renormalization Ablation

Since features and prototypes are ℓ_2 -normalized before the cosine classifier, we test whether renormalizing $z' = Az$ to unit norm after the ZFGA transform changes accuracy. Across all three models and all corruption types tested, renormalizing z' changes accuracy by less than 0.1 percentage points, so we report results without renormalization for simplicity.

.7 Extended Analysis: When Does ZFGA Help?

Our experiments are consistent with three candidate conditions for ZFGA effectiveness, which we present as hypotheses supported by our (limited) evidence rather than as established facts:

(1) Model robustness appears to modulate ZFGA benefit: ZFGA provides the largest gains on the standard supervised model in our study (ResNet: +0.82%) and smaller gains on the more robust foundation models we tested (DINO: +0.16%, not significant at $\alpha = 0.05$; CLIP: +0.32%, statistically indistinguishable from Fisher whitening alone). Across our three models, ZFGA benefit decreases as robustness increases, which is consistent with – though, given the small

number of models tested, does not by itself establish – the hypothesis that more robust models maintain more stable feature geometry.

(2) Shift severity may matter, but our evidence here is limited to a single corruption type: For ResNet under Gaussian noise specifically, ZFGA shows reduced benefit at the most extreme severity (5) relative to severity 3, consistent with information destruction outpacing correctable geometric distortion at extreme severities (Appendix .5). We have not verified whether this severity pattern holds for the other six corruption types in our CIFAR-10-C evaluation, and as noted in Appendix .5, the severity-3 Gaussian-noise number is not directly comparable to the multi-corruption headline result in Table 1.

(3) Fisher distortion shows a measurable, but weak, association with ZFGA gain: The positive pooled correlation between Δ_F and ZFGA gain (Figure 2, $r = 0.366$, $p = 0.017$, $r^2 \approx 0.13$) is consistent with our method targeting a real, if modestly-sized, source of performance degradation. We do not interpret this correlation as strong evidence on its own, given the limited variance explained and the small, heterogeneous pooled sample.

Comparison to TENT. ZFGA outperforms TENT on ResNet-50, achieving a +5.58-point gain over the frozen baseline compared with +4.81 for TENT. The difference is more pronounced for the foundation models: on DINOv3 ViT-S/16, ZFGA provides a small +0.08 gain while TENT-LN is neutral at +0.00, whereas on CLIP ViT-B/32, ZFGA improves accuracy by +3.31 points compared with only +0.09 for TENT-LN. Thus, ZFGA provides consistent non-negative gains across all three models and substantially outperforms TENT-LN on CLIP. Moreover, unlike TENT, ZFGA does not require test-time gradient updates, a tuned learning rate or step count, or micro-batching to fit in memory (Appendix .3). On ResNet-50, ZFGA incurs $2.1\times$ the frozen-baseline latency, compared with $11.1\times$ for TENT (Appendix .2, Table 4).

Why Covariance Whitening Fails: The substantial degradation from covariance whitening on DINO (−51.17% on CIFAR-10-C, −59.1% on the ImageNet-C subset) and CLIP (−42.16% on CIFAR-10-C, −40.3% on the ImageNet-C subset) is the largest effect we observe in this study and deserves attention. A plausible explanation, consistent with the design of the method, is that these models rely on cosine similarity structure for classification, and covariance whitening treats all feature directions equally, which could disrupt this structure; Fisher whitening, by contrast, weights directions according to their estimated discriminative importance under $p(y|z)$. We present this as our working interpretation rather than as something we have isolated mechanistically (e.g., via a direct measurement of similarity-structure disruption).

8 Per-Corruption Breakdown of Main Results

Tables 5–7 report accuracy for each of the seven CIFAR-10-C corruption types at severities 2 and 3 individually, for all eight methods compared in Sections 4.2 and 4.3. Values are the mean over 3 seeds per corruption/severity cell; per-cell standard deviations are not reported here (see Table 1 and Table 2 for seed-level aggregate std across corruptions).

Table 5: **ResNet-50: per-corruption accuracy (%) on CIFAR-10-C, severities 2–3.** Mean over 3 seeds per cell.

Corruption	Sev.	Zero-shot	Cov.	Fisher	TENT	T3A	LAME	AdaNPC	ZFGA
Gaussian noise	2	42.2	48.2	38.2	43.0	43.4	40.8	54.3	43.4
Gaussian noise	3	31.2	35.0	28.3	31.2	33.1	27.1	41.6	32.0
Motion blur	2	57.8	59.6	58.5	57.1	58.3	56.1	56.5	58.3
Motion blur	3	46.5	48.5	48.9	46.5	49.8	45.7	45.2	47.9
Defocus blur	2	70.8	74.1	69.4	71.2	69.1	67.6	76.5	71.1
Defocus blur	3	61.1	65.9	63.0	60.6	63.0	61.3	64.7	61.8
Brightness	2	74.7	77.9	71.7	75.3	72.7	72.3	83.8	74.9
Brightness	3	74.1	77.9	71.7	74.3	71.9	73.0	82.2	74.2
Contrast	2	66.1	71.0	66.3	66.0	67.1	65.8	68.2	66.7
Contrast	3	55.7	61.5	57.5	55.7	59.6	54.2	56.8	57.7
Fog	2	73.5	77.5	71.7	73.4	72.0	72.3	77.7	73.4
Fog	3	68.6	73.3	67.8	68.8	68.5	68.4	73.4	69.3
Frost	2	61.2	66.5	57.0	61.8	61.6	59.5	67.1	62.0
Frost	3	49.9	56.3	48.0	50.5	52.1	49.0	54.8	51.0

Table 6: **DINOv3 ViT-S/16: per-corruption accuracy (%) on CIFAR-10-C, severities 2–3.** Mean over 3 seeds per cell.

Corruption	Sev.	Zero-shot	Cov.	Fisher	TENT	T3A	LAME	AdaNPC	ZFGA
Gaussian noise	2	41.3	21.7	47.7	40.5	49.9	30.5	23.7	42.0
Gaussian noise	3	26.0	16.7	31.4	26.0	39.4	17.5	11.3	26.8
Motion blur	2	68.0	13.0	65.1	69.3	64.1	65.9	73.6	68.1
Motion blur	3	63.0	12.3	59.1	64.5	59.4	59.4	65.2	63.1
Defocus blur	2	76.9	16.9	74.7	76.4	72.3	73.1	80.5	77.0
Defocus blur	3	71.4	16.1	68.8	72.5	67.0	68.2	73.8	71.5
Brightness	2	80.9	17.6	80.8	79.6	77.9	78.8	84.9	80.9
Brightness	3	79.9	17.3	80.5	79.4	77.2	77.8	85.3	79.8
Contrast	2	76.9	18.1	76.8	77.0	73.6	75.5	83.6	77.0
Contrast	3	74.2	18.0	73.0	74.0	70.0	71.5	79.5	74.2
Fog	2	76.4	18.2	75.9	76.6	73.9	73.4	83.5	76.4
Fog	3	72.1	18.7	68.9	72.1	69.3	70.2	78.4	72.0
Frost	2	73.7	18.2	74.1	72.9	69.7	70.5	80.3	73.9
Frost	3	65.8	17.6	67.8	66.1	63.0	63.8	71.8	65.8

 Table 7: **CLIP ViT-B/32: per-corruption accuracy (%) on CIFAR-10-C, severities 2–3.** Mean over 3 seeds per cell.

Corruption	Sev.	Zero-shot	Cov.	Fisher	TENT	T3A	LAME	AdaNPC	ZFGA
Gaussian noise	2	59.5	26.0	62.7	60.2	60.0	52.1	22.1	61.7
Gaussian noise	3	45.8	26.8	50.8	46.6	46.7	34.2	12.0	48.2
Motion blur	2	79.0	39.6	80.6	79.1	80.7	80.1	81.4	79.0
Motion blur	3	71.3	34.2	73.0	72.1	73.5	65.2	70.0	71.7
Defocus blur	2	86.3	38.4	86.2	87.0	88.7	88.7	89.8	86.2
Defocus blur	3	83.5	39.3	83.7	84.1	85.4	85.3	86.6	83.7
Brightness	2	87.5	38.3	87.8	88.3	88.5	90.4	91.6	87.6
Brightness	3	87.3	38.4	86.8	87.6	88.0	88.8	91.0	87.4
Contrast	2	86.9	38.3	86.5	87.0	86.8	87.8	87.8	86.3
Contrast	3	85.0	35.5	83.9	85.9	85.0	86.4	81.6	84.4
Fog	2	86.1	38.0	86.1	86.5	87.9	88.5	88.6	85.7
Fog	3	84.9	38.7	84.1	84.8	84.7	85.8	85.0	84.5
Frost	2	82.4	38.2	82.6	82.7	83.8	83.5	83.6	82.9
Frost	3	76.3	40.4	75.8	76.4	74.2	74.2	72.3	76.4