

WHAT PAIRED EVALUATIONS REVEAL UNDER VISUAL PERTURBATIONS

Yongda Wei Chen Zhang Yifei Wang Xinyu Wang
Bosen Shao Hanxi Li Liping Di

ABSTRACT

To understand the reliability of computer vision models in real-world applications, robustness evaluation must examine diverse visual perturbations, yet benchmarks cover only some real-world conditions and physical testing is costly. Paired evaluations link clean and perturbed predictions for the same image, retaining changes in correctness, confidence, and acceptance that aggregate accuracy does not describe. We investigate how this image correspondence supports two needs in robustness evaluation: **interpreting paired evaluation results** and **prioritizing samples for physical testing**. To interpret paired evaluation results, we fix both sets of prediction records and vary their correspondence within each class. We prove that classwise correct–correct counts give the same sharp bounds on lost acceptance and mean true-class probability decrease among retained-correct inputs as any feasible five-state refinement. Distinguishing persistent from changed wrong answers can further constrain accepted-error transitions, while shared correspondence can establish policy orderings left unresolved by separate cost intervals. To prioritize samples for physical testing, we retain each image’s synthetic responses and rank clean-correct images by their mean true-class probability under corruption. Across 44 classifiers, testing the highest-risk 20% finds 67% and 45% of failures under mild screen and print recaptures, versus 58% and 36% for clean confidence and 60% and 37% for an equal-size natural-transformation average. With both probability averaging and an A3Rank scoring adaptation, the tested corruption set yields higher mean failure recall than the natural-transform set; differences between scores depend on the source and budget. Together, these findings show that the value of correspondence depends on the evaluation objective: classwise counts suffice for specified reliability bounds, while image-specific synthetic responses improve the allocation of physical tests within the evaluated pool.

1 INTRODUCTION

Understanding the reliability of computer vision models in real-world applications requires examining their responses to diverse visual perturbations, from digital corruptions to physical changes in image capture (Hendrycks & Dietterich, 2019; Baek et al., 2024; 2025; Nugent et al., 2025). A fixed benchmark covers only a subset of these conditions, while collecting physical measurements across additional settings requires resources. This creates two needs: extracting useful reliability information from completed evaluations and deciding which images to prioritize in subsequent tests. Aggregate accuracy describes overall correctness but leaves important image-level changes unresolved. For example, an image may remain correctly classified after perturbation while its confidence falls below an acceptance threshold, changing an accepted prediction into a rejection without changing accuracy. Paired evaluations link clean and perturbed predictions for the same image, making such changes observable.

How does image correspondence in paired evaluations support the judgments needed in robustness evaluation? For completed tests, without their matching, knowing each side’s predictions does not necessarily reveal which accepted correct predictions became accepted errors or lost acceptance. The answer depends on how the records correspond and what information about that correspondence has been retained. For subsequent physical tests, associating synthetic responses with their source images may help identify which images are likely to fail under real perturbations. We examine this question in image classification through two subquestions: first, which reliability changes and policy

comparisons can be determined from separate prediction records and selected joint counts; second, whether image-specific synthetic responses improve failure discovery at a fixed physical testing budget. The first question concerns what the available records establish about completed tests; the second concerns their empirical usefulness for directing further tests.

The first part presents our analysis for **interpreting paired evaluation results**. We hold the clean and perturbed prediction records fixed and vary their correspondence within each true class (Section 4). Classwise counts are then added: first the number of images classified correctly in both conditions, followed by the full five-state breakdown of correctness and answer changes. Given the fixed records, correctness overlap provides all five-state endpoint constraints for lost acceptance among retained-correct inputs and their mean true-class probability decrease. Distinguishing persistent from changed wrong answers can further narrow accepted-error transitions. Comparing policies under a common feasible correspondence also establishes some orderings that separate cost intervals leave unresolved. The value of the additional counts depends on the policy cost, including whether it tracks where accepted errors originate or counts all accepted errors. These results specify which retained information constrains each target and how those constraints support policy comparison.

The second part focuses on **prioritizing samples for physical testing**. We retain each image’s synthetic responses and rank clean-correct images by their mean true-class probability under corruption (Section 5). On mild screen and print recaptures, a 20% testing budget finds, on average, 67% and 45% of failures, versus 60% and 37% for an equal-size natural-transformation average. Reassigning synthetic scores to other same-class images reduces screening performance, directly demonstrating the value of matching responses to source images. Crossing both probe sets with probability averaging and adapted A3Rank yields higher mean failure recall for the tested corruption set under both scores, with score preferences varying by source and budget. These comparisons assess image identity and synthetic-probe choice for allocating real tests.

Together, the analyses show that the value of correspondence depends on the judgment an evaluation is intended to support. Classwise correctness overlap already captures all five-state endpoint constraints for two reliability targets given fixed prediction records, whereas image-specific synthetic responses improve real-failure screening within the evaluated pool. More detailed information therefore calls for target-specific assessment: tighter bounds, additional policy orderings and improved predictive performance are distinct outcomes. Section 3 defines the records, response states and information levels; Section 4 develops the identification and policy results; Section 5 evaluates failure screening; and Section 6 examines the different outcome of aggregating responses for model-level prediction.

2 RELATED WORK

Robustness and performance prediction. Corruption benchmarks, replicated test sets and deployment datasets measure different distribution changes (Hendrycks & Dietterich, 2019; Recht et al., 2019; Koh et al., 2021). Synthetic robustness need not transfer uniformly to natural or perceptually different shifts (Hendrycks et al., 2021; Mintun et al., 2021; Kar et al., 2022). ImageNet-ES and ES-Diverse provide controlled physical capture variation (Baek et al., 2024; 2025). Effective robustness and accuracy-on-the-line motivate strong clean-performance baselines (Taori et al., 2020; Miller et al., 2021); pretraining and reference distributions affect these relations (Djolonga et al., 2021; Shi et al., 2023).

Paired transitions and confidence. Matched outcomes underpin correlated-proportion tests (McNemar, 1947), negative-flip analysis (Yan et al., 2021; Sawada & Kasahara, 2026) and error-consistency studies (Geirhos et al., 2020; Kim et al., 2025; Klein et al., 2025). Bench-C examines confidence and correctness changes under corruption (Sui et al., 2026), while VLM-RobustBench analyzes harmful and helpful answer flips (Saxena et al., 2026). Paired evaluations also assess reward-model robustness for language-model alignment by comparing preference rankings or confidence before and after input transformations (Wu et al., 2025; Zang et al., 2026). We study what joint counts determine beyond separate records, without claiming novelty for the partition. Calibration, failure detection and selective classification measure different aspects of confidence (Guo et al., 2017; Minderer et al., 2021; Hendrycks & Gimpel, 2017; Corbière et al., 2019; Geifman & El-Yaniv, 2017; 2019). Their behavior can change under shift or without an accuracy change (Ovadia et al., 2019; Galil & El-Yaniv,

2021; Liang et al., 2024), requiring explicit protocols and baselines (Jaeger et al., 2023; Cattelan & Silva, 2024; Traub et al., 2024).

Test prioritization and augmentation-based confidence. PRIMA uses input and model mutations with learning to rank to prioritize test inputs (Wang et al., 2021); A3Rank uses augmentation alignment to prioritize overconfident failures (Wei et al., 2024). Simple uncertainty scores can be competitive test-prioritization baselines (Weiss & Tonella, 2022). Averaging predicted-class probabilities over test-time transformations is an existing training-free confidence score (Bahat & Shakhnarovich, 2020). We use corruption responses of known clean images to prioritize subsequent physical recaptures. At equal inference counts, we compare corruption and natural-transformation averages and adapt the A3Rank scoring rule to both probe sets; its original rejection component and current-input error target are distinct from our future-recapture task.

Identification and scoring. Joint distributions constrained by their marginals are a classical problem (Strassen, 1965; Tchen, 1980; Kellerer, 1984). Stratified intersection bounds also quantify treatment harm (Kallus, 2022), while partially identified counterfactual utilities support policy comparison (Ben-Michael et al., 2024). We use elementary intersection counts and extremal subset sums; our structural question is which correctness and wrong-answer constraints alter these endpoints. Finite-record identification differs from sampling inference for partially identified parameters (Imbens & Manski, 2004). Proper scores and CORP quantify probability quality (Gneiting & Raftery, 2007; Dimitriadis et al., 2021); totals need no correspondence, unlike allocation to response states. Alternative ImageNet annotations delimit what correctness means (Beyer et al., 2020; Vasudevan et al., 2022).

3 RECORDS, TARGETS, AND MISSING CORRESPONDENCE

3.1 WHY COUNTS NEED NOT DETERMINE A JOINT CHANGE

Consider two images of the same true class y with clean probability vectors $(p_y, p_{\tilde{y}}) = (0.9, 0.1), (0.6, 0.4)$ and perturbed vectors $(0.6, 0.4), (0.2, 0.8)$ for alternative class $\tilde{y}$. At threshold 0.8, only the first clean prediction and the wrong perturbed prediction are accepted. Both correspondences give one retained-correct pair and one harmful flip, with identical class-wise five-state counts. Yet matching the accepted clean prediction to the correct perturbed one loses acceptance while retaining correctness; the other matching produces an accepted error. The counts therefore need not determine which accepted prediction failed. We ask what remains possible as increasingly detailed joint counts supplement the report.

Table 1: Five disjoint response states and aggregate metrics under the original single-label definition. The state symbols also denote empirical proportions.

State	Response	C_i	C'_i	Labels
h	Harmful flip	1	0	$\hat{y}_i \neq \hat{y}'_i$
r	Correction	0	1	$\hat{y}_i \neq \hat{y}'_i$
s	Persistent error	0	0	$\hat{y}_i = \hat{y}'_i$
w	Changed error	0	0	$\hat{y}_i \neq \hat{y}'_i$
k	Retained correctness	1	1	$\hat{y}_i = \hat{y}'_i$
Clean accuracy		Perturbed accuracy		
$a_0 = h + k$		$a_1 = r + k$		
Accuracy decrease		Label-change rate		
$a_0 - a_1 = h - r$		$F = h + r + w$		

Records and response states. For N paired inputs with shared original labels y_i , unprimed and primed quantities refer to clean and perturbed inputs. Each record carries a predicted label $\hat{y}_i$ or $\hat{y}'_i$ under a fixed tie rule, maximum probability S_i or S'_i , and true-class probability M_i or M'_i . Correctness is $C_i = \mathbf{1}\{\hat{y}_i = y_i\}$. To examine whether predictions remain accepted after perturbation, we accept a prediction when its maximum probability reaches a fixed threshold τ and reject it otherwise. Thus $Z_i = \mathbf{1}[S_i \geq \tau]$ indicates acceptance; primed counterparts use the same definitions and threshold.

Table 1 defines the five disjoint states $T_i \in \{h, r, s, w, k\}$ and their relationships to clean accuracy a_0 , perturbed accuracy a_1 , and the predicted-label change rate F . The same letters denote empirical proportions and, in events, j means $T = j$. Thus s, w, k contribute zero directly to the accuracy difference, although their probabilities may change. Given a_0, a_1, F , the state proportions have at most one remaining degree of freedom.

Table 2: Reliability targets. The first two are empirical conditional means, undefined for empty states and positive for decreases. The last three are empirical event proportions with all N evaluated inputs as denominator.

Target	Definition	Interpretation
dM_k	$\mathbb{E}[M - M' \mid T = k]$	Mean true-class probability decrease among inputs correct on both sides.
ds_j	$\mathbb{E}[S - S' \mid T = j], j \in \{s, w\}$	Mean decrease in maximum probability within the specified wrong-answer state.
E_τ	$\mathbb{P}(C' = 0, Z' = 1)$	Fraction of inputs with an accepted error after perturbation.
$L = L_k$	$\mathbb{P}(T = k, Z = 1, Z' = 0)$	Fraction remaining correct but changing from accepted to rejected.
H	$\mathbb{P}(C = 1, Z = 1, C' = 0, Z' = 1)$	Fraction changing from an accepted correct prediction to an accepted error.

Reliability targets. Table 2 distinguishes empirical conditional score changes (dM_k, ds_j) from acceptance-event proportions ($E_\tau, L = L_k, H$). In the opening example, (H, L, dM_k) is either $(0, 1/2, 0.3)$ or $(1/2, 0, 0)$, which means the counts need not point-identify these targets. E_τ , in contrast, needs only perturbed records.

Paired evaluation denotes a matched-input design, not pairwise comparison of two models. A statistic may use both sides without depending on their correspondence, as a difference of marginal means does. Here correspondence dependence means that a statistic can change when the same two sets of records are reassigned. Besides the targets above, we use $A = \mathbb{E}|S - S'|$ and $Q = \text{Corr}(S, S')$ as simple paired statistics.

3.2 INFORMATION AVAILABLE WITHOUT THE ACTUAL PAIRING

Definition 1 (Correspondence and information levels). Fix one model and condition, with n_y clean and n_y perturbed records in each true class y . Within each class, match every clean record to exactly one perturbed record, using each perturbed record once. Write $\pi_y(i) = j$ for this match and $\pi = (\pi_y)_y$ for all classwise matchings. Changing the matching changes only which records are linked; their labels, scores and acceptance decisions remain fixed.

The information levels $\mathcal{I}_0$, $\mathcal{I}_k$ and $\mathcal{I}_5$ retain, respectively, all prediction records on both sides, including true class labels, without paired counts; the same records plus the observed correct–correct counts k_y for each class; and the same records plus all five observed state counts h_y, r_y, s_y, w_y, k_y for each class. Whereas π is one matching, $\Pi(\mathcal{I})$ contains all within-class matchings consistent with the retained information. Because $\Pi(\mathcal{I}_5) \subseteq \Pi(\mathcal{I}_k) \subseteq \Pi(\mathcal{I}_0)$, retaining more counts can rule out possible matchings, while the observed matching remains feasible at every level.

For clean and perturbed correct counts a_y, b_y , overlap k_y is feasible exactly when $\max(0, a_y + b_y - n_y) \leq k_y \leq \min(a_y, b_y)$. Let $q(\pi)$ denote a target’s value under matching π . When defined throughout the feasible set, its *identified interval* spans the smallest and largest allowed values:

$$[\underline{q}(\mathcal{I}), \bar{q}(\mathcal{I})] = \left[\min_{\pi \in \Pi(\mathcal{I})} q(\pi), \max_{\pi \in \Pi(\mathcal{I})} q(\pi) \right]. \quad (1)$$

Endpoints attained by feasible correspondences are sharp, and the width measures ambiguity for fixed records, not sampling uncertainty. Classwise choices form a Cartesian product, allowing extrema of additive counts to be summed without assuming statistical independence between classes.

For H and L , marginal reference intervals follow from classwise intersection bounds. Class-conditional independent matching gives reference values. Appendix A provides the formulas and detailed sharpness proof, and Appendix C also examines accuracy-only reports.

3.3 MODELS, SOURCES, AND PROTOCOL

There are 44 models in ten fixed statistical groups, covering image–text, self-supervised and supervised models (Appendix G). Syn is a synthetic-corruption evaluation set that applies nine corruption types at severities 2 and 4 to 10,000 ImageNet images with 1,000 candidate classes. Syn-B applies these same 18 conditions to the 1,000 original images underlying ES (Baek et al., 2024) and Diverse (Baek et al., 2025), spanning 200 classes with five images per class. ES provides 54 screen-recapture conditions and Diverse provides 162 print-recapture conditions. This links synthetic and physical responses for the same images, enabling sample prioritization.

Images are split into development and evaluation sets within each class. Identification analyses use evaluation records, while acceptance thresholds are set using development images. Real capture conditions are grouped by mean development accuracy across models into mild (at least 40%), severe (20% to below 40%), and extreme (below 20%) tiers. Appendix F provides further details on data construction and evaluation protocols.

4 RETROSPECTIVE DIAGNOSIS: INFORMATION REQUIREMENTS AND POLICY COSTS

With both sets of prediction records fixed, we examine which correspondence information constrains reliability changes (Section 4.1), supports policy comparisons under different costs (Section 4.2), and reduces ambiguity in the observed records (Section 4.3). The empirical analysis distinguishes certified policy orderings from realized selection outcomes.

4.1 CORRECTNESS OVERLAP SUFFICES FOR TWO TARGETS

Theorem 1 (Endpoint sufficiency of correctness overlap). *For fixed single-label prediction records and feasible classwise overlaps k_y , the identified intervals for L and, when $K = \sum_y k_y > 0$, dM_k are identical under $\mathcal{I}_k$ and every feasible classwise five-state refinement $\mathcal{I}_5$.*

Proof idea. Fix a correspondence with the requested five-state counts. Independently permuting clean and perturbed correct identities among their correct positions preserves the wrong–wrong matching and every state count. These permutations select any k_y correct records on each side and any bijection between them. Subset intersections and extreme score sums give the sharp L and dM_k bounds, respectively (Equations (5) and (6), Appendix A). Overlaps suffice for the endpoints, but observed values may still vary within them (Table 3).

Why accepted-error transitions differ. For H , changing the wrong perturbed endpoint can change the persistent/changed-wrong split. Five-state refinement can therefore strictly narrow its overlap-conditioned interval. Appendix A gives the bounds and a three-record counterexample.

4.2 SHARED CORRESPONDENCE AND THE CHOICE OF POLICY COST

We compare fixed rejection policies under partially identified outcomes (Ben-Michael et al., 2024). Keep the clean threshold fixed and let policy j use perturbed threshold τ_j . Substituting $Z'_j = \mathbf{1}[S' \geq \tau_j]$ defines H_j, L_j and transition cost $J_j = \lambda H_j + (1 - \lambda)L_j$, $\lambda \in [0, 1]$. This cost separately

Table 3: Information and supported conclusions for fixed single-label records and within-class reassignment. Both sides’ records remain available; dM_k requires positive retained-correct support.

Target	Information used	Supported conclusion
E_τ	Perturbed records	Exact accepted-error mass.
L, dM_k	Classwise overlaps $\mathcal{I}_k$	Sharp bounds equal those under every feasible five-state refinement.
H	Five-state counts $\mathcal{I}_5$	Can tighten overlap-conditioned bounds.
$J_j - J_\ell$	Shared correspondence across policies	Can certify an ordering throughout the feasible set despite overlapping cost intervals.

penalizes accepted errors and lost correct acceptances originating from initially correct accepted predictions. Within each class, these events involve disjoint outcomes of the same records. We consider a cost counting all accepted errors below.

Given their sharp classwise count bounds, constraining their sum to at most the number u_y of correct accepted clean records determines the sharp single-policy upper cost bound (Lemma 1, Appendix A). No additional joint enumeration is needed once those bounds are known; computing five-state H bounds can still require enumeration, and the lower cost bound need not separate this way.

Comparisons use one common correspondence. For policies j, ℓ , the elementary inequality

$$\overline{\Delta}_{j\ell}(\mathcal{I}) = \max_{\pi \in \Pi(\mathcal{I})} [J_j(\pi) - J_\ell(\pi)] \leq \overline{J}_j(\mathcal{I}) - \underline{J}_\ell(\mathcal{I}) \quad (2)$$

can be strict because separate endpoints may require different correspondences. A negative left side establishes that j costs less throughout the feasible set, even if the separate intervals overlap. Appendix D reports these additional comparisons. Their information requirements depend on what the cost counts:

Corollary 1 (A cost based on total accepted errors). *Let $J'_j(\pi) = \lambda E_{\tau_j} + (1 - \lambda)L_j(\pi)$, where E_{τ_j} is the perturbed-side accepted-error mass. The identified intervals of J'_j and the upper difference bounds $\overline{\Delta}'_{j\ell}$ are identical under $\mathcal{I}_k$ and $\mathcal{I}_5$.*

Here E_{τ_j} is marginal, and correct-record symmetry preserves the attainable set of the entire vector $(L_j)_j$ across both levels. Thus the value of wrong-answer refinement depends on whether the cost tracks errors through H or counts all accepted errors through E_τ (proof in Appendix A).

Table 3 summarizes the information requirements and the conclusions they support for the targets considered in this section.

4.3 FINDINGS: HOW MUCH AMBIGUITY REMAINS IN THE OBSERVED RECORDS?

Acceptance uses the same τ on both sides, targeting 80% clean-development coverage and accepting cutoff ties. Policy comparisons fix this clean threshold; five perturbed-side thresholds target 60–100% clean-development coverage. Analytic bounds cover 11,088 model–condition cells; additional bound computations for five-state H and positive-overlap marginal dM_k cover a frozen, nonrandom 450-cell panel spanning all 44 models and four sources (Appendices B and C).

Overlap reduces full-grid mean L widths by 14–31% across sources. Five-state refinement further narrows H in 195/450 cells, but not L or dM_k , often leaving values undetermined (Figure 1). Appendix B gives full-grid results and matched-support checks for cross-source comparisons.

Table 4 distinguishes certified orderings from realized selection outcomes. Its first three rows count cells with an additional policy pair for which one policy has lower J under every feasible




Figure 1: Mean identified widths in the 450-cell panel measure correspondence ambiguity. W_0 , W_1 and W_2 use marginal records, added classwise overlap and added five-state counts. Colors partition W_0 into remaining width and two reductions; bold labels give W_0 . Five-state refinement narrows H , but not L or dM_k . Marginal dM_k ranges over positive overlaps; later levels fix observed overlaps.

Table 4: Policy comparisons and selection on the frozen 450-cell panel, $\lambda = 0.5$. Ordering rows count cells with additional strict comparisons; these counts can overlap. Counted orderings require both correct and incorrect predictions among threshold-switching records. Feasible-mean selection minimizes mean cost over uniformly weighted feasible correspondences.

Question	Comparison	Result
Shared correspondence: more orderings?	Shared correspondence vs. separate intervals ($\mathcal{I}_5$)	312/450 (69.3%)
Correctness overlap: more orderings?	$\mathcal{I}_0 \rightarrow \mathcal{I}_k$	241/450 (53.6%)
Five-state counts: more orderings?	$\mathcal{I}_k \rightarrow \mathcal{I}_5$	42/450 (9.3%)
Minimax regret: lower realized cost?	Minimax regret vs. feasible mean ($\mathcal{I}_5$)	4 lower / 3 higher 443 equal

correspondence. The last row compares observed costs of minimax-regret and feasible-mean selection; lower, higher and equal refer to the former relative to the latter. Under J' , five-state refinement adds no comparisons beyond overlap (Corollary 1). Appendix D gives source-level results, the weight grid and a worked print-recapture example.

5 PROSPECTIVE SCREENING: WHICH IMAGES DESERVE REAL RECAPTURE?

After examining what correspondence establishes about completed evaluations, we test whether image-specific synthetic responses help prioritize physical tests. We define scores and test image identity (Section 5.1), measure failure discovery at fixed budgets (Section 5.2), compare probe sets and scores at equal inference counts (Section 5.3), and assess scope and inference cost (Section 5.4).

5.1 SCORES, IMAGE SETS, AND BASELINES

For each model’s clean-correct images among the 500 real evaluation base images, define U_i as mean true-class probability over the 18 Syn-B conditions, ret_i as the fraction remaining correct, and $\delta_i = S_i - U_i$. Here true and original predicted labels coincide, so U uses the predicted-class averaging construction of Bahat & Shakhnarovich (2020) on corruptions excluding the original image. We rank subsequent recapture failures (h rather than k) by $-U$, $-S$, δ and $-\text{ret}$ on identical image sets.




Figure 2: Screening scores are evaluated by how well they distinguish images that fail under real recapture from those that remain correct. All scores use identical clean-correct image sets. (a) AUROC on a common color scale. Class- δ is the development-set class mean of $M - U$; $g(S, U)$ is fitted on development images. (b) Paired AUROC differences $U - S$ with 95% model-group resampling intervals; the dashed line marks zero gain. Numerical results, class-resampled intervals and cell counts are in Appendix E.




Figure 3: Different rankings are evaluated by the fraction of real failures they uncover at a given recapture budget. Results cover three budgets on mild conditions. Curves average the same model-condition cells; A^3 uses the same corruptions as U . Intervals and other tiers are in Appendix E.

Controls include development-class means and a frozen logistic predictor $g(S, U)$ fitted on development images. Intervals separately resample ten model groups or 200 true classes to assess within-pool sensitivity. Appendix E details fitting, identity ablation and matched class baselines.

Figure 2 compares six scores across sources and tiers and the AUROC gain of U over S . On mild ES/Diverse, U reaches 0.854/0.801, above clean confidence, retention and the class-mean drop baseline; $g(S, U)$ differs by at most 0.01. The drop δ ranks worse by 0.086/0.020, with exceptions at other budgets or splits. On extreme Diverse, U reaches only 0.512 with an inconclusive gain over S .

Image identity contributes to screening: assigning U to another clean-correct image of the same class reduces mild AUROC from about 0.85/0.80 to 0.55/0.58 on the common non-singleton subset. A development-class-mean U predictor reaches about 0.60 on both sources on its supported subset. These prediction controls complement the fixed-record identification analysis (protocols in Appendix E).

5.2 FAILURE COVERAGE AT A FIXED TESTING BUDGET

For a budget q , select the highest-risk fraction of clean-correct images and measure the share of all real failures found, with cutoff ties prorated. This *failure coverage* is recall, not the error rate within the selected images. At the primary $q = 0.2$, U covers 67% and 45% of mild ES and Diverse failures, against 58% and 36% for clean confidence (Figure 3). The $U - S$ differences exclude zero under both resampling schemes at all tested budgets $q \in \{0.1, 0.2, 0.3\}$ on mild conditions. On Diverse, coverage is nearly tied with δ at $q = 0.2$, and both δ and retention are better at $q = 0.1$ (Table 18 from Appendix E).

On extreme conditions, high failure prevalence leaves little room to improve coverage despite near-chance ranking. Appendix E quantifies this prevalence-imposed ceiling.

5.3 PROBE SETS AND SCORING RULES AT EQUAL INFERENCE COUNTS

Following Bahat & Shakhnarovich (2020), TTA_{18} averages true-class probabilities over 18 geometric and gamma transformations without label-based selection, matching U_{18} ’s inference count. The protocol fixed mild-condition coverage at $q = 0.2$ as primary and 0.03 as the practical-effect threshold. Figure 4 crosses the probe sets with probability averaging and an adapted A3Rank alignment score (Appendix E.2).

The corruption average exceeds the natural average by 0.076 coverage on ES and 0.083 on Diverse, with both model-group and class-resampled interval lower endpoints above 0.03; the AUROC gaps are 0.063 and 0.114. Under either scoring rule, the tested corruption set yields higher mean recall and AUROC than the natural set. Score preferences depend on source, metric and budget: on Diverse, U and the corruption-based A^3 have an inconclusive recall difference at 20%, and A^3 leads by 0.008 at 10% (Figure 3), while U has higher AUROC.




Figure 4: At equal inference counts, the tested corruptions yield higher mean failure recall and AUROC than natural transforms under both scoring rules. Comparisons use identical mild-condition image sets and 18 transformed inputs each. Mean denotes probability averaging; A^3 , adapted A3Rank. Lines connect point estimates; selected difference intervals appear in Appendices E.2 and E.3.

Mild gains persist against additional confidence baselines; checks of averaging, transform selection and model scoring retain the advantage over TTA (Appendices E.4 and E); Appendix E.3 examines individual probes and capture conditions. Because the sets differ in transformation family and response strength, these results establish a tested-set advantage rather than isolate corruption type.

5.4 SCOPE AND ADDITIONAL INFERENCE COST

Screening was initially explored on evaluation images. Swapping split roles and defining tiers on the opposite half preserve mild $U - S$ gaps within the same image, model and capture pool. Recapture budgets exclude the additional synthetic inference. Appendix E reports split and scoring checks, including δ , and gains from prefixed probe subsets (Table 28 from Appendix E); these characterize the tested configurations, not arbitrary smaller sets.

6 BOUNDARIES OF OTHER USES

Do paired summaries improve model-level prediction? Model-level summaries of synthetic responses are used to predict performance under mild real perturbations. Comparisons with unpaired baselines across held-out model groups test whether retaining image correspondence adds predictive value. The gains depend on the prediction target and baseline. This analysis separates the usefulness of correspondence for predicting model-level performance from its usefulness for prioritizing individual images. Appendix I reports the detailed comparisons and group-removal refits.

7 SCOPE AND CONCLUSION

The bounds assume fixed labeled records, unrestricted within-class reassignment and fixed record-level decisions. ReaL checks follow this convention; human recapture-label review remains pending. Resampling assesses sensitivity within the shared image, model and capture pool. Policy conclusions depend on thresholds and costs, with certified comparisons but mixed realized-selection outcomes.

Image correspondence supports **interpreting paired evaluation results** and **prioritizing samples for physical testing**. Correctness overlap gives the same sharp L and dM_k bounds as every feasible five-state refinement; distinguishing persistent from changed wrong answers can tighten H . Shared correspondence certifies policy orderings unresolved by separate cost intervals.

On mild screen and print conditions, image-specific corruption responses improve mean failure recall over clean confidence and the tested equal-size natural-transformation average at a fixed recapture budget. Identity ablations establish the contribution of image correspondence. Both probability averaging and adapted A3Rank favor the tested corruption set, with score preferences varying by source and budget. These findings guide information retention, reliability judgments and physical testing within the evaluated pool.

STATEMENT ON AI ASSISTANCE

Large language models assisted with research ideation and experimental implementation, literature retrieval and reference organization and polishing manuscript sections, and developing and checking mathematical proofs. They also supported analysis code and typesetting. No generative models were used to synthesize the experimental images. Verification included separate computational implementations and agent-assisted reviews; these checks do not constitute independent human replication. The authors take responsibility for the final text, mathematical claims, code, and reported results.

REPRODUCIBILITY STATEMENT

We provide supplementary code and documentation to support reproduction of the experiments and analyses. The supplementary materials specify the fixed image identities, development/evaluation splits, perturbation conditions, scoring protocol, and the 44 evaluated models and their statistical groupings, together with the 450-cell panel described in Section 4. Detailed inference settings, split definitions, and threshold conventions are provided in Appendix F, while the accompanying documentation provides instructions for obtaining the data and running the experiments. Model checkpoints and the datasets are obtained from their original sources; access to some weights (e.g., DINOv3) might require the official access procedure. The clean images are identical to those used in the study, and predictions on the physical recaptures reproduce the recorded results. For synthetic perturbations, the original per-image corruption seeds were not retained. Regeneration therefore follows the documented experimental protocol without guaranteeing pixel-level identity with the original perturbed images.

REFERENCES

- Eunsu Baek, Keondo Park, Jiyeon Kim, and Hyung-Sin Kim. Unexplored Faces of Robustness and Out-of-Distribution: Covariate Shifts in Environment and Sensor Domains. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024. URL <https://arxiv.org/abs/2404.15882>.
- Eunsu Baek, Sung-hwan Han, Taesik Gong, and Hyung-Sin Kim. Adaptive Camera Sensor for Vision Models. In *International Conference on Learning Representations*, 2025. URL https://proceedings.iclr.cc/paper_files/paper/2025/hash/ec14daa5c50745f83fb27f685f8dfc22-Abstract-Conference.html.
- Yuval Bahat and Gregory Shakhnarovich. Classification confidence estimation with test-time data-augmentation, 2020. URL <https://arxiv.org/abs/2006.16705>.
- Eli Ben-Michael, Kosuke Imai, and Zhichao Jiang. Policy learning with asymmetric counterfactual utilities. *Journal of the American Statistical Association*, 119(548):3045–3058, 2024. doi: 10.1080/01621459.2023.2300507.
- Yoshua Bengio and Yves Grandvalet. No Unbiased Estimator of the Variance of K-Fold Cross-Validation. *Journal of Machine Learning Research*, 5:1089–1105, 2004. URL <https://www.jmlr.org/papers/v5/grandvalet04a.html>.
- Lucas Beyer, Olivier J. Hénaff, Alexander Kolesnikov, Xiaohua Zhai, and Aäron van den Oord. Are we done with ImageNet?, 2020. URL <https://arxiv.org/abs/2006.07159>. ReaL annotations: <https://github.com/google-research/reassessed-imagenet>.
- Daniel Bolya, Po-Yao Huang, Peize Sun, Jang Hyun Cho, Andrea Madotto, Chen Wei, Tengyu Ma, Jiale Zhi, Jathushan Rajasegaran, Hanoona Rasheed, Junke Wang, Marco Monteiro, Hu Xu, Shiyu Dong, Nikhila Ravi, Daniel Li, Piotr Dollár, and Christoph Feichtenhofer. Perception Encoder: The best visual embeddings are not at the output of the network. In *Advances in Neural Information Processing Systems*, 2025. URL https://proceedings.neurips.cc/paper_files/paper/2025/file/57bc0a850255e2041341bf74c7e2b9fa-Paper-Conference.pdf.

- Luís Felipe P. Cattelan and Danilo Silva. How to Fix a Broken Confidence Estimator: Evaluating Post-hoc Methods for Selective Classification with Deep Neural Networks. In *Uncertainty in Artificial Intelligence*, volume 244, pp. 547–584. PMLR, 2024. URL <https://proceedings.mlr.press/v244/cattelan24a.html>.
- Gavin C. Cawley and Nicola L. C. Talbot. On Over-fitting in Model Selection and Subsequent Selection Bias in Performance Evaluation. *Journal of Machine Learning Research*, 11:2079–2107, 2010. URL <https://www.jmlr.org/papers/v11/cawley10a.html>.
- Soravit Changpinyo, Piyush Sharma, Nan Ding, and Radu Soricut. Conceptual 12M: Pushing Web-Scale Image-Text Pre-Training To Recognize Long-Tail Visual Concepts. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021. URL <https://arxiv.org/abs/2102.08981>.
- Mehdi Cherti, Romain Beaumont, Ross Wightman, Mitchell Wortsman, Gabriel Ilharco, Cade Gordon, Christoph Schuhmann, Ludwig Schmidt, and Jenia Jitsev. Reproducible scaling laws for contrastive language-image learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023. URL <https://arxiv.org/abs/2212.07143>.
- Yung-Sung Chuang, Yang Li, Dong Wang, Ching-Feng Yeh, Kehan Lyu, Ramya Raghavendra, James Glass, Lifei Huang, Jason Weston, Luke Zettlemoyer, Xinlei Chen, Zhuang Liu, Saining Xie, Wen-tau Yih, Shang-Wen Li, and Hu Xu. Meta CLIP 2: A Worldwide Scaling Recipe. In *Advances in Neural Information Processing Systems*, 2025. URL <https://arxiv.org/abs/2507.22062>.
- Charles Corbière, Nicolas Thome, Avner Bar-Hen, Matthieu Cord, and Patrick Pérez. Addressing Failure Prediction by Learning Model Confidence. In *Advances in Neural Information Processing Systems*, volume 32, 2019. URL <https://proceedings.neurips.cc/paper/2019/hash/757f843a169cc678064d9530d12a1881-Abstract.html>.
- Timo Dimitriadis, Tilmann Gneiting, and Alexander I. Jordan. Stable reliability diagrams for probabilistic classifiers. *Proceedings of the National Academy of Sciences*, 118(8):e2016191118, 2021. doi: 10.1073/pnas.2016191118. URL <https://doi.org/10.1073/pnas.2016191118>.
- Josip Djolonga, Jessica Yung, Michael Tschannen, Rob Romijnders, Lucas Beyer, Alexander Kolesnikov, Joan Puigcerver, Matthias Minderer, Alexander D’Amour, Dan Moldovan, Sylvain Gelly, Neil Houlsby, Xiaohua Zhai, and Mario Lucic. On Robustness and Transferability of Convolutional Neural Networks. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16458–16468, 2021. URL https://openaccess.thecvf.com/content/CVPR2021/html/Djolonga_On_Robustness_and_Transferability_of_Convolutional_Neural_Networks_CVPR_2021_paper.html.
- Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An Image Is Worth 16x16 Words: Transformers for Image Recognition at Scale. In *International Conference on Learning Representations*, 2021. URL <https://openreview.net/pdf?id=YicbFdNTTy>.
- Alex Fang, Albin Madappally Jose, Amit Jain, Ludwig Schmidt, Alexander Toshev, and Vaishaal Shankar. Data Filtering Networks. In *International Conference on Learning Representations*, 2024. URL <https://arxiv.org/abs/2309.17425>.
- Samir Yitzhak Gadre, Gabriel Ilharco, Alex Fang, Jonathan Hayase, Georgios Smyrnis, Thao Nguyen, Ryan Marten, Mitchell Wortsman, Dhruva Ghosh, Jieyu Zhang, Eyal Orgad, Rahim Entezari, Giannis Daras, Sarah Pratt, Vivek Ramanujan, Yonatan Bitton, Kalyani Marathe, Stephen Mussmann, Richard Vencu, Mehdi Cherti, Ranjay Krishna, Pang Wei Koh, Olga Saukh, Alexander Ratner, Shuran Song, Hannaneh Hajishirzi, Ali Farhadi, Romain Beaumont, Sewoong Oh, Alex Dimakis, Jenia Jitsev, Yair Carmon, Vaishaal Shankar, and Ludwig Schmidt. DataComp: In search of the next generation of multimodal datasets. In *Advances in Neural Information Processing Systems*, 2023. URL <https://arxiv.org/abs/2304.14108>.
- Ido Galil and Ran El-Yaniv. Disrupting Deep Uncertainty Estimation Without Harming Accuracy. In *Advances in Neural Information Processing Systems*, volume 34, 2021. URL https://proceedings.neurips.cc/paper_files/paper/2021/file/b1b20d09041289e6c3fbb81850c5da54-Paper.pdf.

- Yonatan Geifman and Ran El-Yaniv. Selective Classification for Deep Neural Networks. In *Advances in Neural Information Processing Systems*, 2017. URL <https://arxiv.org/abs/1705.08500>.
- Yonatan Geifman and Ran El-Yaniv. SelectiveNet: A Deep Neural Network with an Integrated Reject Option. In *International Conference on Machine Learning*, volume 97, pp. 2151–2159. PMLR, 2019. URL <https://proceedings.mlr.press/v97/geifman19a.html>.
- Robert Geirhos, Kristof Meding, and Felix A. Wichmann. Beyond Accuracy: Quantifying Trial-by-Trial Behaviour of CNNs and Humans by Measuring Error Consistency. In *Advances in Neural Information Processing Systems*, volume 33, 2020. URL <https://proceedings.neurips.cc/paper/2020/hash/9f6992966d4c363ea0162a056cb45fe5-Abstract.html>.
- Tilmann Gneiting and Adrian E. Raftery. Strictly Proper Scoring Rules, Prediction, and Estimation. *Journal of the American Statistical Association*, 102(477):359–378, 2007. doi: 10.1198/016214506000001437. URL <https://sites.stat.washington.edu/people/raftery/Research/PDF/Gneiting2007ja.pdf>.
- Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On Calibration of Modern Neural Networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70, pp. 1321–1330. PMLR, 2017. URL <https://proceedings.mlr.press/v70/guo17a.html>.
- Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep Residual Learning for Image Recognition. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 770–778, 2016. URL https://openaccess.thecvf.com/content_cvpr_2016/html/He_Deep_Residual_Learning_CVPR_2016_paper.html.
- Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked Autoencoders Are Scalable Vision Learners. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16000–16009, 2022. URL https://openaccess.thecvf.com/content/CVPR_2022/html/He_Masked_Autoencoders_Are_Scalable_Vision_Learners_CVPR_2022_paper.html.
- Dan Hendrycks and Thomas Dietterich. Benchmarking Neural Network Robustness to Common Corruptions and Perturbations. In *International Conference on Learning Representations*, 2019. URL <https://arxiv.org/abs/1903.12261>.
- Dan Hendrycks and Kevin Gimpel. A Baseline for Detecting Misclassified and Out-of-Distribution Examples in Neural Networks. In *International Conference on Learning Representations*, 2017. URL <https://openreview.net/forum?id=Hkg4TI9xl>.
- Dan Hendrycks, Steven Basart, Norman Mu, Saurav Kadavath, Frank Wang, Evan Dorundo, Rahul Desai, Tyler Zhu, Samyak Parajuli, Mike Guo, Dawn Song, Jacob Steinhardt, and Justin Gilmer. The Many Faces of Robustness: A Critical Analysis of Out-of-Distribution Generalization. In *IEEE/CVF International Conference on Computer Vision*, pp. 8340–8349, 2021. URL https://openaccess.thecvf.com/content/ICCV2021/html/Hendrycks_The_Many_Faces_of_Robustness_A_Critical_Analysis_of_Out-of-Distribution_ICCV_2021_paper.html.
- Gabriel Ilharco, Mitchell Wortsman, Ross Wightman, Cade Gordon, Nicholas Carlini, Rohan Taori, Achal Dave, Vaishaal Shankar, Hongseok Namkoong, John Miller, Hannaneh Hajishirzi, Ali Farhadi, and Ludwig Schmidt. Openclip, July 2021. URL <https://doi.org/10.5281/zenodo.5143773>.
- Guido W. Imbens and Charles F. Manski. Confidence Intervals for Partially Identified Parameters. *Econometrica*, 72(6):1845–1857, 2004. doi: 10.1111/j.1468-0262.2004.00555.x. URL <https://onlinelibrary.wiley.com/doi/abs/10.1111/j.1468-0262.2004.00555.x>.
- Paul F. Jaeger, Carsten T. Lüth, Lukas Klein, and Till J. Bungert. A Call to Reflect on Evaluation Practices for Failure Detection in Image Classification. In *International Conference on Learning Representations*, 2023. URL <https://iclr.cc/virtual/2023/poster/11579>.
- Nathan Kallus. What’s the harm? sharp bounds on the fraction negatively affected by treatment. In *Advances in Neural Information Processing Systems*, volume 35, 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/hash/666cccc6376058e251315b4de7e085b9-Abstract-Conference.html.

- Oğuzhan Fatih Kar, Teresa Yeo, Andrei Atanov, and Amir Zamir. 3D Common Corruptions and Data Augmentation. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 18963–18974, 2022. URL https://openaccess.thecvf.com/content/CVPR2022/html/Kar_3D_Common_Corruptions_and_Data_Augmentation_CVPR_2022_paper.html.
- Hans G. Kellerer. Duality Theorems for Marginal Problems. *Zeitschrift für Wahrscheinlichkeitstheorie und Verwandte Gebiete*, 67(4):399–432, 1984. doi: 10.1007/BF00532047. URL <https://link.springer.com/article/10.1007/BF00532047>.
- Elliot Myunghoon Kim, Avi Garg, Kenny Peng, and Nikhil Garg. Correlated Errors in Large Language Models. In *International Conference on Machine Learning*, volume 267, pp. 30038–30066. PMLR, 2025. URL <https://proceedings.mlr.press/v267/kim25e.html>.
- Thomas Klein, Sascha Meyen, Wieland Brendel, Felix A. Wichmann, and Kristof Meding. Quantifying Uncertainty in Error Consistency: Towards Reliable Behavioral Comparison of Classifiers. In *Advances in Neural Information Processing Systems*, volume 38, 2025. URL https://proceedings.neurips.cc/paper_files/paper/2025/hash/491e8f2f1fa8ab6d1f166f6c521420f6-Abstract-Conference.html.
- Pang Wei Koh, Shiori Sagawa, Henrik Marklund, Sang Michael Xie, Marvin Zhang, Akshay Balsubramani, Weihua Hu, Michihiro Yasunaga, Richard Lanus Phillips, Irena Gao, Tony Lee, Etienne David, Ian Stavness, Wei Guo, Berton Earnshaw, Imran Haque, Sara M. Beery, Jure Leskovec, Anshul Kundaje, Emma Pierson, Sergey Levine, Chelsea Finn, and Percy Liang. WILDS: A Benchmark of in-the-Wild Distribution Shifts. In *International Conference on Machine Learning*, volume 139, pp. 5637–5664. PMLR, 2021. URL <https://proceedings.mlr.press/v139/koh21a.html>.
- Alex Krizhevsky, Ilya Sutskever, and Geoffrey E. Hinton. ImageNet Classification with Deep Convolutional Neural Networks. In *Advances in Neural Information Processing Systems*, 2012. URL <https://proceedings.neurips.cc/paper/2012/hash/c399862d3b9d6b76c8436e924a68c45b-Abstract.html>.
- Xianhang Li, Zeyu Wang, and Cihang Xie. An Inverse Scaling Law for CLIP Training. In *Advances in Neural Information Processing Systems*, 2023a. URL <https://arxiv.org/abs/2305.07017>.
- Xianhang Li, Zeyu Wang, and Cihang Xie. CLIPA-v2: Scaling CLIP Training with 81.1% Zero-shot ImageNet Accuracy within a \$10,000 Budget; An Extra \$4,000 Unlocks 81.8% Accuracy. *arXiv preprint arXiv:2306.15658*, 2023b. URL <https://arxiv.org/abs/2306.15658>.
- Hengyue Liang, Le Peng, and Ju Sun. Selective Classification Under Distribution Shifts. *Transactions on Machine Learning Research*, 2024. URL <https://openreview.net/forum?id=dmxMGW6J7N>.
- Zhuang Liu, Hanzi Mao, Chao-Yuan Wu, Christoph Feichtenhofer, Trevor Darrell, and Saining Xie. A ConvNet for the 2020s. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 11976–11986, 2022. URL https://openaccess.thecvf.com/content/CVPR2022/html/Liu_A_ConvNet_for_the_2020s_CVPR_2022_paper.html.
- Charles F. Manski. Statistical treatment rules for heterogeneous populations. *Econometrica*, 72(4): 1221–1246, 2004. doi: 10.1111/j.1468-0262.2004.00530.x. URL <https://onlinelibrary.wiley.com/doi/10.1111/j.1468-0262.2004.00530.x>.
- Quinn McNemar. Note on the Sampling Error of the Difference Between Correlated Proportions or Percentages. *Psychometrika*, 12(2):153–157, 1947. doi: 10.1007/BF02295996. URL <https://www.cambridge.org/core/journals/psychometrika/article/abs/note-on-the-sampling-error-of-the-difference-between-correlated-proportions-or-percentages/698C2461BE63F5848763502D54E534FD>.
- John P Miller, Rohan Taori, Aditi Raghunathan, Shiori Sagawa, Pang Wei Koh, Vaishaal Shankar, Percy Liang, Yair Carmon, and Ludwig Schmidt. Accuracy on the Line: on the Strong Correlation Between Out-of-Distribution and In-Distribution Generalization. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139, pp. 7721–7735. PMLR, 2021. URL <https://proceedings.mlr.press/v139/miller21b.html>.

- Matthias Minderer, Josip Djolonga, Rob Romijnders, Frances Hubis, Xiaohua Zhai, Neil Houlsby, Dustin Tran, and Mario Lucic. Revisiting the Calibration of Modern Neural Networks. In *Advances in Neural Information Processing Systems*, volume 34, 2021. URL <https://proceedings.neurips.cc/paper/2021/hash/8420d359404024567b5aefda1231af24-Abstract.html>.
- Eric Mintun, Alexander Kirillov, and Saining Xie. On Interaction Between Augmentations and Corruptions in Natural Corruption Robustness. In *Advances in Neural Information Processing Systems*, volume 34, 2021. URL https://papers.neurips.cc/paper_files/paper/2021/hash/1d49780520898fe37f0cd6b41c5311bf-Abstract.html.
- Jack Nugent, Siyang Wu, Zeyu Ma, Beining Han, Meenal Parakh, Abhishek Joshi, Lingjie Mei, Alexander Raistrick, Xinyuan Li, and Jia Deng. Evaluating Robustness of Monocular Depth Estimation with Procedural Scene Perturbations. In *Advances in Neural Information Processing Systems*, volume 38, 2025. URL https://papers.neurips.cc/paper_files/paper/2025/hash/129033c7c08be683059559e8d6bfd460-Abstract-Conference.html.
- Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, Mahmoud Assran, Nicolas Ballas, Wojciech Galuba, Russell Howes, Po-Yao Huang, Shang-Wen Li, Ishan Misra, Michael Rabbat, Vasu Sharma, Gabriel Synnaeve, Hu Xu, Hervé Jegou, Julien Mairal, Patrick Labatut, Armand Joulin, and Piotr Bojanowski. DINOv2: Learning Robust Visual Features without Supervision. *Transactions on Machine Learning Research*, 2024. URL <https://arxiv.org/abs/2304.07193>.
- Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, D Sculley, Sebastian Nowozin, Joshua V. Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can You Trust Your Model’s Uncertainty? Evaluating Predictive Uncertainty Under Dataset Shift. In *Advances in Neural Information Processing Systems*, 2019. URL <https://arxiv.org/abs/1906.02530>.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning Transferable Visual Models From Natural Language Supervision. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139, pp. 8748–8763. PMLR, 2021. URL <https://proceedings.mlr.press/v139/radford21a.html>.
- Benjamin Recht, Rebecca Roelofs, Ludwig Schmidt, and Vaishaal Shankar. Do ImageNet Classifiers Generalize to ImageNet? In *International Conference on Machine Learning*, volume 97, pp. 5389–5400. PMLR, 2019. URL <https://proceedings.mlr.press/v97/recht19a.html>.
- Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision*, 115(3): 211–252, 2015. doi: 10.1007/s11263-015-0816-y. URL <https://arxiv.org/abs/1409.0575>.
- Hiroki Sawada and Shunichi Kasahara. Beyond Single-Axis Testing: Paired Evaluation of Compound Robustness in Vision-Language-Action Policies. *arXiv preprint arXiv:2609.15940*, 2026. URL <https://arxiv.org/abs/2609.15940>.
- Rohit Saxena, Alessandro Suglia, and Pasquale Minervini. VLM-RobustBench: A Comprehensive Benchmark for Robustness of Vision-Language Models. In *International Conference on Machine Learning*, 2026. URL <https://arxiv.org/abs/2603.06148>.
- Christoph Schuhmann, Richard Vencu, Romain Beaumont, Robert Kaczmarczyk, Clayton Mullis, Aarush Katta, Theo Coombes, Jenia Jitsev, and Aran Komatsuzaki. LAION-400M: Open Dataset of CLIP-Filtered 400 Million Image-Text Pairs. *arXiv preprint arXiv:2111.02114*, 2021. URL <https://arxiv.org/abs/2111.02114>.
- Christoph Schuhmann, Romain Beaumont, Richard Vencu, Cade Gordon, Ross Wightman, Mehdi Cherti, Theo Coombes, Aarush Katta, Clayton Mullis, Mitchell Wortsman, Patrick Schramowski, Srivatsa Kundurthy, Katherine Crowson, Ludwig Schmidt, Robert Kaczmarczyk, and Jenia Jitsev. LAION-5B: An open large-scale dataset for training next generation image-text models. In *Advances in Neural Information Processing Systems*, 2022. URL <https://arxiv.org/abs/2210.08402>.

- Zhouxing Shi, Nicholas Carlini, Ananth Balashankar, Ludwig Schmidt, Cho-Jui Hsieh, Alex Beutel, and Yao Qin. Effective Robustness against Natural Distribution Shifts for Models with Different Training Data. In *Advances in Neural Information Processing Systems*, volume 36, 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/e9000ecb86d45c442a1d38fae68dd8fb-Abstract-Conference.html.
- Oriane Siméoni, Huy V. Vo, Maximilian Seitzer, Federico Baldassarre, Maxime Oquab, Cijo Jose, Vasil Khalidov, Marc Szafraniec, Seungeun Yi, Michaël Ramamonjisoa, Francisco Massa, Daniel Haziza, Luca Wehrstedt, Jianyuan Wang, Timothée Darcet, Théo Moutakanni, Leonel Sentana, Claire Roberts, Andrea Vedaldi, Jamie Tolan, John Brandt, Camille Couprie, Julien Mairal, Hervé Jégou, Patrick Labatut, and Piotr Bojanowski. DINOv3. *Transactions on Machine Learning Research*, 2026. URL <https://openreview.net/forum?id=2NlGyqNjns>.
- V. Strassen. The Existence of Probability Measures with Given Marginals. *The Annals of Mathematical Statistics*, 36(2):423–439, 1965. doi: 10.1214/aoms/1177700153. URL <https://doi.org/10.1214/aoms/1177700153>.
- Xiangjie Sui, Songyang Li, Hanwei Zhu, Baoliang Chen, Yuming Fang, and Xin Sun. Diagnosing Corruption-Induced Reliability Failures in Vision-Language Models, 2026. URL <https://arxiv.org/abs/2511.19032v2>. Version 2, revised July 9, 2026; first posted in 2025.
- Quan Sun, Yuxin Fang, Ledell Wu, Xinlong Wang, and Yue Cao. EVA-CLIP: Improved Training Techniques for CLIP at Scale. *arXiv preprint arXiv:2303.15389*, 2023. URL <https://arxiv.org/abs/2303.15389>.
- Mingxing Tan and Quoc V. Le. EfficientNet: Rethinking Model Scaling for Convolutional Neural Networks. In *Proceedings of the International Conference on Machine Learning*, 2019. URL <https://arxiv.org/abs/1905.11946>.
- Rohan Taori, Achal Dave, Vaishaal Shankar, Nicholas Carlini, Benjamin Recht, and Ludwig Schmidt. Measuring Robustness to Natural Distribution Shifts in Image Classification. In *Advances in Neural Information Processing Systems*, 2020. URL <https://arxiv.org/abs/2007.00644>.
- Andre H. Tchen. Inequalities for Distributions with Given Marginals. *The Annals of Probability*, 8(4):814–827, 1980. doi: 10.1214/aop/1176994668. URL <https://doi.org/10.1214/aop/1176994668>.
- Bart Thomee, David A. Shamma, Gerald Friedland, Benjamin Elizalde, Karl Ni, Douglas Poland, Damian Borth, and Li-Jia Li. YFCC100M: The New Data in Multimedia Research. *Communications of the ACM*, 59(2):64–73, 2016. doi: 10.1145/2812802. URL <https://arxiv.org/abs/1503.01817>.
- Jeremias Traub, Till J. Bungert, Carsten T. Lüth, Michael Baumgartner, Klaus H. Maier-Hein, Lena Maier-Hein, and Paul F. Jaeger. Overcoming Common Flaws in the Evaluation of Selective Classification Systems. In *Advances in Neural Information Processing Systems*, volume 37, 2024. URL https://proceedings.nips.cc/paper_files/paper/2024/file/047c84ec50bd8ea29349b996fc64af4b-Paper-Conference.pdf.
- Michael Tschannen, Alexey Gritsenko, Xiao Wang, Muhammad Ferjad Naeem, Ibrahim Alabdulmohsin, Nikhil Parthasarathy, Talfan Evans, Lucas Beyer, Ye Xia, Basil Mustafa, Olivier Hénaff, Jeremiah Harmsen, Andreas Steiner, and Xiaohua Zhai. SigLIP 2: Multilingual Vision-Language Encoders with Improved Semantic Understanding, Localization, and Dense Features. *arXiv preprint arXiv:2502.14786*, 2025. URL <https://arxiv.org/abs/2502.14786>.
- Vijay Vasudevan, Benjamin Caine, Raphael Gontijo Lopes, Sara Fridovich-Keil, and Rebecca Roelofs. When does dough become a bagel? analyzing the remaining mistakes on ImageNet. In *Advances in Neural Information Processing Systems*, volume 35, pp. 6720–6734, 2022. doi: 10.52202/068431-0487. URL https://proceedings.neurips.cc/paper_files/paper/2022/hash/2cd5737c59645f7ef23b2842b705edf2-Abstract-Conference.html.
- Zan Wang, Hanmo You, Junjie Chen, Yingyi Zhang, Xuyuan Dong, and Wenbin Zhang. Prioritizing test inputs for deep neural networks via mutation analysis. In *Proceedings of the International Conference on Software Engineering*, pp. 397–409, 2021. doi: 10.1109/ICSE43902.2021.00046.

- Zhengyuan Wei, Haipeng Wang, Qilin Zhou, and W. K. Chan. A3Rank: Augmentation alignment analysis for prioritizing overconfident failing samples for deep learning models. *arXiv preprint arXiv:2407.14114*, 2024. URL <https://arxiv.org/abs/2407.14114>.
- Michael Weiss and Paolo Tonella. Simple techniques work surprisingly well for neural network test prioritization and active learning (replicability study). In *Proceedings of the International Symposium on Software Testing and Analysis*, 2022. doi: 10.1145/3533767.3534375.
- Ross Wightman. PyTorch Image Models. GitHub repository, 2019. URL <https://github.com/huggingface/pytorch-image-models>.
- Zhaofeng Wu, Michihiro Yasunaga, Andrew Cohen, Yoon Kim, Asli Celikyilmaz, and Marjan Ghazvininejad. reWordBench: Benchmarking and improving the robustness of reward models with transformed inputs. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 3383–3409. Association for Computational Linguistics, 2025. doi: 10.18653/v1/2025.emnlp-main.167. URL <https://aclanthology.org/2025.emnlp-main.167/>.
- Hu Xu, Saining Xie, Xiaoqing Ellen Tan, Po-Yao Huang, Russell Howes, Vasu Sharma, Shang-Wen Li, Gargi Ghosh, Luke Zettlemoyer, and Christoph Feichtenhofer. Demystifying CLIP Data. In *International Conference on Learning Representations*, 2024. URL <https://arxiv.org/abs/2309.16671>.
- Sijie Yan, Yuanjun Xiong, Kaustav Kundu, Shuo Yang, Siqi Deng, Meng Wang, Wei Xia, and Stefano Soatto. Positive-Congruent Training: Towards Regression-Free Model Updates. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14299–14308, 2021. URL https://openaccess.thecvf.com/content/CVPR2021/html/Yan_Positive-Congruent_Training_Towards_Regression-Free_Model_Updates_CVPR_2021_paper.html.
- Jiahui Yu, Zirui Wang, Vijay Vasudevan, Legg Yeung, Mojtaba Seyedhosseini, and Yonghui Wu. CoCa: Contrastive Captioners are Image-Text Foundation Models. *Transactions on Machine Learning Research*, 2022. URL <https://arxiv.org/abs/2205.01917>.
- Bianca Zadrozny and Charles Elkan. Transforming classifier scores into accurate multiclass probability estimates. In *Proceedings of the Eighth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 694–699, 2002. doi: 10.1145/775047.775151. URL <https://doi.org/10.1145/775047.775151>.
- Jianxiang Zang, Yongda Wei, Ruxue Bai, Shiyu Jiang, Nijia Mo, Binhong Li, Qiang Sun, and Hui Liu. Reward auditor: Inference on reward modeling suitability in real-world perturbed scenarios. In *International Conference on Machine Learning*, 2026. URL <https://arxiv.org/abs/2512.00920>.
- Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid Loss for Language Image Pre-Training. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2023. URL <https://arxiv.org/abs/2303.15343>.

The appendices support the two main questions separately. Appendices A–D give proofs, numerical checks and full policy comparisons. Appendix E gives screening protocols and controls, followed by inference details and the model inventory. The final appendices present model-level prediction comparisons and annotation-sensitivity analyses.

A PROOFS

This appendix proves the endpoint and policy-cost results of Section 4 under record-attached correctness and within-class reassignment.

A.1 FEASIBLE RECORDS AND COUNT CONSTRAINTS

Fix one true label y , n_y clean records and n_y perturbed records. Correctness means that the single predicted label equals y . Probabilities, predicted labels and acceptance decisions are attached to records; they are not recomputed after reassignment. A feasible correspondence is any bijection within the true class. No geometric, temporal or physical compatibility constraints are imposed.

Let a_y, b_y be the two correct counts. A correct–correct overlap k_y is feasible exactly when

$$\max(0, a_y + b_y - n_y) \leq k_y \leq \min(a_y, b_y). \quad (3)$$

The correctness-block sizes are then $k_y, h_y = a_y - k_y, r_y = b_y - k_y$, and $s_y + w_y = n_y - a_y - b_y + k_y$. A proposed s_y/w_y split must also be realizable given the wrong predicted labels; nonnegativity and the displayed sum alone are insufficient. We condition only on nonempty feasible sets, including the observed counts.

A.2 MARGINAL INTERSECTION BOUNDS

For $q \in \{H, L\}$, let u_y count correct accepted clean records and v_{qy} count wrong accepted perturbed records for H , or correct rejected ones for L . Classical intersection bounds give

$$[q_0, \bar{q}_0] = \frac{1}{N} \left[\sum_y \max(0, u_y + v_{qy} - n_y), \sum_y \min(u_y, v_{qy}) \right], \quad q_{\text{ind}} = \frac{1}{N} \sum_y \frac{u_y v_{qy}}{n_y}, \quad (4)$$

where $N = \sum_y n_y$ and q_{ind} uses class-conditional independent matching. The construction below proves sharpness; Appendix C considers reports retaining only per-class accuracies.

For two record subsets of sizes u_y, v_y , pairing their members together as much as possible attains intersection count $\min(u_y, v_y)$. Pairing them outside one another as much as possible attains $\max(0, u_y + v_y - n_y)$. Arbitrary bijections complete the unused positions. Choices in distinct true classes form a Cartesian product, so classwise extrema can be summed and divided by $N = \sum_y n_y$. This gives Equation (4). The product assignment with edge mass $1/n_y$ gives the independent value, which is also the expected count under a uniform permutation. These are finite-record identification statements, distinct from sampling inference for partially identified population parameters (Imbens & Manski, 2004).

A.3 A SYMMETRY OF THE CORRECT RECORDS

Start from any bijection satisfying the specified classwise five-state counts. Permute clean correct identities among the a_y correct row positions and, independently, perturbed correct identities among the b_y correct column positions. Keeping all incorrect identities fixed leaves the entire wrong–wrong matching unchanged and therefore preserves every five-state count, even if the constraint retained every individual wrong–wrong predicted-label pair.

There are k_y correct row positions and k_y correct column positions in the correct–correct block. These permutations can select any k_y correct clean records, any k_y correct perturbed records, and any bijection between the selected subsets. This establishes the sufficiency of classwise correctness overlap for the endpoints below. The statement requires both row and column permutations.

A.4 SHARP LOST-ACCEPTANCE BOUNDS

Write $v_y = v_{Ly}$. Under $\mathcal{I}_k$, the sharp lost-acceptance bounds are

$$[\underline{L}_k, \bar{L}_k] = \frac{1}{N} \left[\sum_y \max\{0, k_y - (a_y - u_y) - (b_y - v_y)\}, \sum_y \min\{u_y, v_y, k_y\} \right]. \quad (5)$$

Let u_y count correct accepted clean records and v_y correct rejected perturbed records. Among the k_y retained-correctness pairs, the number x with an accepted clean endpoint can range over

$$\max\{0, k_y - (a_y - u_y)\} \leq x \leq \min\{u_y, k_y\}.$$

The number z with a rejected perturbed endpoint ranges analogously from $\max\{0, k_y - (b_y - v_y)\}$ to $\min\{v_y, k_y\}$. For fixed x, z , their overlap in the k_y positions ranges from $\max\{0, x + z - k_y\}$ to $\min\{x, z\}$. Selecting the smallest or largest feasible x, z yields Equation (5). The preceding symmetry makes both extrema attainable under every additional feasible s_y/w_y split. Classwise count extrema are normalized by the total number of inputs N . No assertion is made that extrema of different targets are simultaneously attainable.

A.5 SHARP CONDITIONAL-CONFIDENCE BOUNDS

Order the true-class probabilities on each correct side as $x_{y(1)} \leq \dots \leq x_{y(a_y)}$ and $z_{y(1)} \leq \dots \leq z_{y(b_y)}$. For $K = \sum_y k_y > 0$, the sharp interval is

$$[\underline{d}_k, \bar{d}_k] = \frac{1}{K} \left[\sum_y \left(\sum_{i=1}^{k_y} x_{y(i)} - \sum_{i=b_y-k_y+1}^{b_y} z_{y(i)} \right), \sum_y \left(\sum_{i=a_y-k_y+1}^{a_y} x_{y(i)} - \sum_{i=1}^{k_y} z_{y(i)} \right) \right]. \quad (6)$$

For a selected correct-correct block, its signed difference sum is the sum of selected clean scores minus the sum of selected perturbed scores. Its value is independent of the internal matching. Selecting the smallest clean k_y scores and largest perturbed k_y scores minimizes this sum; reversing the choices maximizes it. The correct-record symmetry permits both choices under every feasible wrong-state refinement. This proves Equation (6).

Empty sums are zero. When $K = \sum_y k_y > 0$, class numerator extrema are summed and then divided by K ; an unweighted average of class conditional means would be incorrect. When $K = 0$, the conditional mean and its bounds are undefined. Knowing only total K instead of each k_y defines a different feasible set and is not the claim proved here. The argument uses elementary finite selection and separable costs.

Algorithm 1 summarizes the computation of Equations (5) and (6). It retains the valid L bounds when $K = 0$ and applies to fixed classwise overlaps.

Algorithm 1 Sharp bounds with fixed classwise correctness overlap

```

1: Require: Classwise counts  $n_y, a_y, b_y, u_y, v_y$ , correct-side scores  $x_y, z_y$ , and feasible overlaps  $k_y$ ;  $N > 0$ .
2:  $N \leftarrow \sum_y n_y, K \leftarrow \sum_y k_y; L^- \leftarrow 0, L^+ \leftarrow 0, D^- \leftarrow 0, D^+ \leftarrow 0$ .
3: for each class  $y$  do
4:   Sort  $x_y$  and  $z_y$  in ascending order as  $x_{y(i)}$  and  $z_{y(i)}$ .
5:    $L^- \leftarrow L^- + \max\{0, k_y - (a_y - u_y) - (b_y - v_y)\}$ .
6:    $L^+ \leftarrow L^+ + \min\{u_y, v_y, k_y\}$ .
7:   if  $k_y > 0$  then
8:      $D^- \leftarrow D^- + \sum_{i=1}^{k_y} x_{y(i)} - \sum_{i=b_y-k_y+1}^{b_y} z_{y(i)}$ .
9:      $D^+ \leftarrow D^+ + \sum_{i=a_y-k_y+1}^{a_y} x_{y(i)} - \sum_{i=1}^{k_y} z_{y(i)}$ .
10:  end if
11: end for
12:  $[\underline{L}_k, \bar{L}_k] \leftarrow [L^-/N, L^+/N]$ .
13: if  $K > 0$  then
14:    $[\underline{d}_k, \bar{d}_k] \leftarrow [D^-/K, D^+/K]$ .
15: else
16:   Mark the conditional-confidence bounds as undefined.
17: end if
18: Ensure: Lost-acceptance bounds  $[\underline{L}_k, \bar{L}_k]$  and conditional-confidence bounds, when defined.

```

A.6 A COUNTEREXAMPLE FOR ACCEPTED-ERROR TRANSITIONS

Let the true class be T , with alternative labels A, B , and accept maximum probability at least 0.6. The two sides contain the probability vectors in Table 5, in the order (T, A, B) .

Table 5: Prediction records for the accepted-error counterexample.

Record	Clean	Perturbed
1	(0.6, 0.2, 0.2)	(0.6, 0.2, 0.2)
2	(0.1, 0.8, 0.1)	(0.1, 0.8, 0.1)
3	(0.1, 0.8, 0.1)	(0.3, 0.3, 0.4)

Fix $k_y = 0$. The correct clean record may pair with either wrong perturbed record, so the H count can be zero or one. Imposing $s_y = 1, w_y = 0$ forces the single wrong–wrong edge to terminate at perturbed record 2, leaving record 3 for the correct clean record; consequently $H = 0$. Imposing $s_y = 0, w_y = 1$ forces the opposite allocation, giving count one and rate $H = 1/3$. Both are feasible bijections. Adding one correct accepted record to each side and fixing $k_y = 1$ gives the same distinction with positive K and denominator four.

Before the wrong-state refinement, let t_y count wrong accepted perturbed records and put $h_y = a_y - k_y$. The sharp H count bounds are

$$\max\{0, h_y - (a_y - u_y) - ((n_y - b_y) - t_y)\}, \quad \min\{u_y, t_y, h_y\}. \quad (7)$$

This is the same subset-intersection argument in the correct–wrong block. Attaining its endpoints may require permuting incorrect perturbed identities, which can change s_y/w_y ; the invariance proof for L therefore does not apply.

A.7 SINGLE-POLICY UPPER BOUNDS AND PROOF

Let h_{jy}, l_{jy} count the events H_j, L_j within class y , and let u_y count correct accepted clean records. In class y , the event counts h_{jy}, l_{jy} draw from the same u_y clean records and have disjoint perturbed endpoints, so $h_{jy} + l_{jy} \leq u_y$.

Lemma 1 (Single-policy upper bounds). *For every $\mathcal{I} \in \{\mathcal{I}_0, \mathcal{I}_k, \mathcal{I}_5\}$, policy j and $\lambda \in [0, 1]$,*

$$\max_{\pi \in \Pi(\mathcal{I})} J_j(\pi) = \frac{1}{N} \sum_y \max\{\lambda h + (1 - \lambda)l : h \in [h_{jy}, \bar{h}_{jy}], l \in [l_{jy}, \bar{l}_{jy}], h + l \leq u_y\}, \quad (8)$$

where the intervals are the sharp classwise count bounds for the two events at level $\mathcal{I}$.

Fix a class y , a policy j and a level $\mathcal{I}$. Let A_y be the u_y clean records that are correct and accepted, W_{jy} the perturbed records that are wrong and accepted by policy j , and R_{jy} the perturbed records that are correct and rejected by j ; W_{jy} and R_{jy} are disjoint. For any correspondence, $h_{jy}(\pi) = |\pi_y(A_y) \cap W_{jy}|$ and $l_{jy}(\pi) = |\pi_y(A_y) \cap R_{jy}|$, so $h_{jy} + l_{jy} \leq u_y$, and each count lies in its bounding interval. Hence every feasible (h_{jy}, l_{jy}) lies in the region on the right of Equation (8), which proves the inequality $\leq$ after summing over classes.

For $\geq$, in the case $\bar{h} + \bar{l} > u_y$, the points $P_1 = (\bar{h}, u_y - \bar{h})$ and $P_2 = (u_y - \bar{l}, \bar{l})$ lie in the region: a correspondence attaining $\bar{h}$ has $l \leq u_y - \bar{h}$, so $\bar{l} \leq u_y - \bar{h}$, and symmetrically $\bar{h} \leq u_y - \bar{l}$. The maximum of a linear function with nonnegative coefficients over the region is attained at $(\bar{h}, \bar{l})$ if $\bar{h} + \bar{l} \leq u_y$, and otherwise on the segment $h + l = u_y$ between P_1 and P_2 , hence at P_1 or P_2 ; in both cases it suffices to exhibit correspondences in $\Pi(\mathcal{I})$ with $h \geq \bar{h}$ and $l \geq \min(\bar{l}, u_y - \bar{h})$, and symmetrically with $l \geq \bar{l}$ and $h \geq \min(\bar{h}, u_y - \bar{l})$. Under $\mathcal{I}_0$, match $\bar{h} = \min(u_y, |W_{jy}|)$ records of A_y to W_{jy} , match $\min(|R_{jy}|, u_y - \bar{h}) = \min(\bar{l}, u_y - \bar{h})$ of the remaining records of A_y to R_{jy} , and complete the bijection arbitrarily; this is feasible because the two target sets are disjoint. Under $\mathcal{I}_k$ or $\mathcal{I}_5$, start from any $\pi^* \in \Pi(\mathcal{I})$ attaining $h_{jy}(\pi^*) = \bar{h}$; its correct–wrong block contains at least $\bar{h}$ columns in W_{jy} . Apply the correct-record symmetry of Appendix A, which preserves the level: permute clean correct identities so that $\bar{h}$ records of A_y occupy those columns and $\min(\bar{l}, u_y - \bar{h})$ further records of A_y occupy rows of the correct–correct block, and permute perturbed correct identities so that $\min(k_y, |R_{jy}|) \geq \min(\bar{l}, u_y - \bar{h})$ columns of that block lie in R_{jy} and are matched to those rows. The resulting correspondence has $h \geq \bar{h}$ and $l \geq \min(\bar{l}, u_y - \bar{h})$. The symmetric vertex is built from the same π^* : place $\bar{l} = \min(u_y, |R_{jy}|, k_y)$ records of A_y on R_{jy} -columns of the correct–correct block (reachable by the row and column permutations, since that block is free at every level) and $\min(\bar{h}, u_y - \bar{l})$ further records of A_y on the W_{jy} -columns of the correct–wrong block of π^* , of which there are at least $\bar{h}$. Starting instead from a correspondence that attains $\bar{l}$ can fail at $\mathcal{I}_5$, because the wrong perturbed records in the correct–wrong block are not free at that level. Classes are independent, so the classwise maxima add. The identity holds for every cost weight and every level; the panel computation of Appendix D confirms it numerically with a maximum residual of 1.39×10^{-15} percentage points. The corresponding lower bound and the difference of two policies are not covered: the difference $J_j - J_\ell$ depends on which records switch acceptance between τ_j and τ_ℓ , and its maximum over a shared correspondence can be smaller than the difference of separate endpoints (the shared-correspondence comparison in Section 4.2).

A.8 PROOF OF COROLLARY 1 (COMPARISONS UNDER A NATURAL COST)

E_{τ_j} is a function of the perturbed records alone and is therefore constant on $\Pi(\mathcal{I})$ at every level. For any π ,

$$L_j(\pi) - L_\ell(\pi) = \frac{1}{N} \sum_y \sum_{i \in A_y, C'_{\pi_y(i)}=1} (Z'_{\pi_y(i), \ell} - Z'_{\pi_y(i), j}),$$

which depends on π only through its correct–correct block: which clean correct records are matched to which perturbed correct records. By the correct-record symmetry, from any correspondence in $\Pi(\mathcal{I}_5)$ every choice of k_y clean correct records, k_y perturbed correct records and bijection between them is reachable inside $\Pi(\mathcal{I}_5)$, and $\Pi(\mathcal{I}_k)$ admits exactly the same set of correct–correct blocks because $\Pi(\mathcal{I}_5) \subseteq \Pi(\mathcal{I}_k)$ and a correct–correct block of size k_y is completable at level $\mathcal{I}_k$ whenever k_y is feasible. Hence the vector $(L_j(\pi))_j$ ranges over the same set under both levels, and so does every function of it, including J'_j and $J'_j - J'_\ell$. The same argument shows that the L_j endpoints coincide at the two levels, which is the L part of Theorem 1. Under the cost $J_j = \lambda H_j + (1 - \lambda)L_j$ the argument fails because H_j depends on the correct–wrong block, whose reachable set differs between the levels (the accepted-error result in Section 4).

A.9 SCOPE OF THE IDENTIFICATION EXPERIMENT

The classwise choices vary independently within the mathematical feasible set, without implying statistical independence between classes or between experimental cells. Neither the endpoints nor their width are a confidence interval, a causal effect, or a guarantee that a camera can realize the extremizing correspondence. With multiple acceptable labels, two correct predictions can differ. If correctness is attached to each record under its own accepted-label set, the symmetry argument applies unchanged, and enumeration under ReaL labels confirms identical L and dM_k endpoints at $\mathcal{I}_k$ and $\mathcal{I}_5$ (Appendix J); reassigning a record to another image and re-judging its correctness under that image’s label set is a different model and is not covered. Additional pair-dependent constraints or acceptance rules can also invalidate the symmetry.

A.10 VARIABLE-SUPPORT CONFIDENCE BOUNDS AND FINITE VERIFICATION

For the expanded panel, we additionally compute a marginal-only dM_k range over all assignments with positive total K . Unlike Equation (6), the denominator is allowed to vary. For each class and each feasible integer k_y , the preceding score-subset formulas give the minimum and maximum numerator. For a candidate ratio r , minimizing $\sum_y [D_y(k_y) - rk_y]$ over class choices detects whether a positive-support ratio below r exists; the maximization version detects a ratio above it. The all-zero choice cannot supply a strict inequality. Bisection on $[-1, 1]$ yields the endpoints. If no positive support is feasible, the ratio is undefined. These extra panel ranges complement the fixed-support theorem.

Numerical verification uses independent permutation enumeration, including empty overlap, tied probabilities, threshold equality and unequal class supports. The five-state endpoints in the expanded panel are obtained by exact enumeration of integer permutations. Verification covers both algebraic cases and actual prediction records.

B COVERAGE, MATCHED SUPPORT, AND NUMERICAL VERIFICATION

The analyses below support Section 4.3 by documenting the full analytic grid, the 450-cell panel and the matched-support comparisons.

B.1 FROZEN PANEL AND COMPLETE ANALYTIC GRID

The panel contains 440 deterministically selected expanded cells plus the 16 historical cells, with six duplicates removed. It includes 90 Syn, 90 Syn-B, 135 ES and 135 Diverse cells. Each of the 44 models appears, with all ten fixed groups represented. Conditions cover 18/18 Syn, 18/18 Syn-B, 54/54 ES and 113/162 Diverse settings. The model–condition pairs were fixed after prior exploration and before computing the new outcomes, with no outcome-based replacements.

The selected real conditions cover every lighting setting and all three levels of ISO, shutter speed and aperture, with incomplete coverage of their combinations. Diverse light-code coverage is 27/27 for each of l1, l2 and l3; 17/27 for l4; 10/27 for l6; and 5/27 for l7. The panel omits 49 Diverse combinations, yielding unequal coverage across lighting settings.

The full grid has 11,088 cells and 133,056 target–information-level rows; Tables 6 and 7 report the full-grid and panel results, respectively. Analytic event bounds and fixed-overlap confidence bounds cover the full grid. Five-state H bounds and marginal variable-support confidence bounds are evaluated on the 450-cell panel. Conditional means with zero overlap are undefined. With overlap fixed, 461 of the 10,968 positive-overlap dM_k intervals straddle zero; the 120 zero-overlap cells remain undefined.

Table 6: Full-grid mean identification widths (percentage points). $\mathcal{I}_0$ retains complete classwise marginal records; $\mathcal{I}_k$ additionally fixes classwise correct–correct counts. For L, dM_k , the five-state bounds equal $\mathcal{I}_k$ by Theorem 1. Conditional-confidence means exclude zero- K cells. Cells are weighted equally within each source.

Source	Cells	H		L		dM_k
		$\mathcal{I}_0$	$\mathcal{I}_k$	$\mathcal{I}_0$	$\mathcal{I}_k$	$\mathcal{I}_k$
Syn	792	8.44	3.44	6.73	4.63	6.01
Syn-B	792	1.96	0.66	6.33	5.42	2.11
ES	2,376	1.56	0.79	5.52	4.44	3.52
Diverse	7,128	0.86	0.69	2.86	1.99	5.76

Table 7: Expanded panel: mean H widths (pp), additional narrowing from wrong-state refinement, and number of cells with strictly narrower bounds. Panel means use the same cells at every level.

Source	Cells	$\mathcal{I}_0$	$\mathcal{I}_k$	$\mathcal{I}_5$	Extra	Narrower
Syn	90	8.45	3.47	2.40	1.07	90/90
Syn-B	90	1.92	0.69	0.54	0.15	25/90
ES	135	1.12	0.77	0.68	0.09	38/135
Diverse	135	0.97	0.78	0.68	0.10	42/135

B.2 MATCHING PROTOCOL AND EVENT SUPPORT

Table 8: Mean five-state width before and after matching to 200 common true classes and two evaluation records per class (pp). Matched values first average defined cells within each seed and then the five seeds equally. Candidate-probability spaces retain their original sizes of 1,000 classes for Syn and 200 for the other sources.

Source	H		L		dM_k	
	Original	Matched	Original	Matched	Original	Matched
Syn	2.40	0.87	4.61	2.52	5.97	2.76
Syn-B	0.54	0.41	5.47	4.74	2.13	1.76
ES	0.68	0.54	3.03	2.38	5.11	3.90
Diverse	0.68	0.52	2.66	2.04	5.84	4.27

The matched comparison (Table 8) fixes the 200 common true classes and selects two evaluation records per class using an outcome-independent SHA-256 ordering of seed, source, synset and image identifier. The five seeds are 20260910–20260914. Every selected model–condition cell then has 400 records. All original clean-development thresholds are retained. The sample membership is fixed across models within each source/condition selection; no score or outcome enters the selection hash. Candidate scoring spaces remain unchanged: 1,000 for Syn and 200 elsewhere. Matching to two images per class reverses the native Syn-versus-real dM_k width ordering in all five seeds, so the original ordering cannot be attributed to capture medium alone.

Seed summaries first average defined cell widths within each seed, then weight the five seed means equally. Their minimum and maximum are sensitivity summaries, not confidence intervals. There are seven undefined matched cell–seed confidence means: five Diverse and two ES. Original-panel dM_k is defined in 449/450 cells. Positive remaining five-state widths occur in 301/450 cells for H , 422/450 for L and 444/449 for dM_k . After matching, the corresponding counts are 1,244/2,250, 2,036/2,250 and 2,202/2,243. Identical endpoints at two information levels therefore rarely imply point identification of the actual value.

Event scale also affects width comparisons. Dividing each H width by its maximum feasible event mass, when that denominator is positive, gives mean native-panel ratios 0.2054 for Syn, 0.2649 for ES and 0.3381 for Diverse. The matched ratios are 0.0892, 0.2245 and 0.2576. Thus the ordering of

absolute widths is not an ordering of this normalized ambiguity. The supplementary tables stratify by K/N in $[0, .1)$, $[.1, .5)$, $[.5, 1]$ and by left/right event fractions in $[0, .1)$, $[.1, .3)$, $[.3, 1]$. Mean widths for empty strata and ratios with zero denominators are undefined. Counts of exposed records across conditions are not numbers of unique independent images.

B.3 INDEPENDENT VERIFICATION AND COMPUTATIONAL COST

Formula checks independently enumerate 252 normalized record pairs, 212,868 permutations and 905 feasible overlap/persistent-wrong strata, including tied probabilities, threshold equality, zero overlap and unequal class supports. Maximum formula discrepancy is 4.44×10^{-16} in probability units. A second implementation independently recomputes 192 endpoints from eight native and eight matched original-record cells spanning all sources and different overlap supports; the maximum discrepancy is 1.60×10^{-14} percentage points. Its marginal conditional-mean check uses explicit feasible-support dynamic programming rather than the primary ratio-bisection procedure. Additional checks confirm information-set nesting, inclusion of observed values, identical matched samples across models, and consistent aggregation by support stratum.

For the historical 16 cells, all 48 target comparisons between the previous constrained LP and new integer endpoints agree to 2.49×10^{-14} points. This is a finite comparison, not a universal LP-integrality claim. The enlarged panel uses integer permutations directly for five-state endpoints. Original H/L marginal bounds and actual statistics also agree over the full grid with the frozen earlier outputs.

The hierarchy analysis of 9,108,000 paired evaluations took 218.35 seconds on CPU, and the matched-support analysis took 88.07 seconds. These calculations use existing predictions; the reported times exclude model inference and image acquisition.

B.4 SIGNED DECOMPOSITION AND SURVIVOR SUPPORT

Beyond interval widths, this decomposition examines the difference between the observed retained-correct confidence decrease and its class-conditional independent counterpart.

Let K_y be the observed count of pairs correct on both sides, $K = \sum_y K_y$, and $\tilde{K}_y = a_y b_y / n_y$ its independent mass; a_y, b_y are the two sides' correct counts. Write $b_y^M = \mu_y - \mu'_y$ for the difference of the two marginal correct-record means and δ_y for the observed mean difference on surviving pairs. When $K > 0$,

$$dM_k - dM_{k,\text{ind}} = \underbrace{\sum_y \left(\frac{K_y}{K} - \frac{\tilde{K}_y}{\sum_z \tilde{K}_z} \right) b_y^M}_{W: \text{class composition}} + \underbrace{\sum_{y: K_y > 0} \frac{K_y}{K} (\delta_y - b_y^M)}_{V: \text{within-class selection}}. \quad (9)$$

Define b_y^M only when $a_y b_y > 0$ and set it to zero otherwise; those classes have zero observed and independent overlap weights. Independence uses a ratio of expected numerator and denominator, not an expectation of a random conditional ratio. The two terms are signed contributions to the observed difference.

Equation (9) follows by adding and subtracting $\sum_y (K_y/K) b_y^M$. The composition term changes class weights; the within-class term compares the surviving correct records to each side's complete correct set. Both terms may have either sign and may cancel. Their absolute magnitudes do not define explained-variance or causal-contribution fractions. Absolute-component comparisons (Table 9) use a numerical tie tolerance of 10^{-8} percentage points: a selection term is counted as larger only when $|V| > |W| + 10^{-8}$ in these units.

There are 120 zero- K cells: 118 Diverse and two ES. The independent overlap mass is zero in 102 cells; in another 18, observed overlap is zero but independent overlap is positive. Diverse has 2,235 cells with $1 \leq K \leq 5$ and 4,042 with $K \geq 20$. Its mean dM_k is 43.84 over positive- K cells, versus 21.06 over the latter subset; these changing subsets are descriptive and are not support-corrected estimates of a common population mean. In that $K \geq 20$ subset, mean absolute selection/composition terms remain 0.89/0.30 points.

Table 9: Signed confidence decomposition on positive- K cells. Means are cell-weighted, confidence differences are in percentage points, and the last column reports the percentage of cells where the absolute within-class selection term exceeds the absolute composition term.

Source	$K > 0$ cells	Pair – ind.	Mean $ W $	Mean $ V $	$ V > W $
Syn	792	+1.00	0.08	0.96	98.6%
Syn-B	792	+0.38	0.09	0.39	85.0%
ES	2,374	+0.52	0.21	0.67	86.3%
Diverse	7,010	+0.66	0.50	1.57	76.8%

C ADDITIONAL CHECKS OF CORRESPONDENCE INFORMATION

Three checks extend the correspondence analysis: verifying attainable endpoints by enumeration, measuring the precision gain from pairing, and bounding overlap when only accuracies are reported.

The analyses use the fixed evaluation records described in Section 3.3. Unless a table states resampling of the 200 true classes, intervals are percentile intervals from resampling the ten model groups (2,000 draws); both summarize sensitivity within this pool, not population uncertainty. Tiers are the development-defined tiers of Section 3.3.

C.1 THEOREM 1 AT SCALE

Direct permutation enumeration, independent of the analytic formulas, covers every class in 48 cells spanning all four sources and four models (19,200 classes; Syn evaluation classes hold five records, real classes two or three, so every class is enumerable). In every class the L and dM_k extrema at $\mathcal{I}_k$ equal those at $\mathcal{I}_5$ and match Equations (5) and (6). The five-state H interval is strictly narrower than the $\mathcal{I}_k$ interval in 318 classes (1.7%), most often on Syn, because a class with few records rarely contains both a persistent and a changed wrong answer. Appendix J repeats the enumeration under ReaL correctness on all real cells.

C.2 VARIANCE REDUCTION FROM PAIRING

Actual pairing also improves the precision of a measured change. The variance of the paired difference divided by the sum of marginal variances is about one third for correctness under digital corruptions, versus 0.55 on ES and 0.87 on Diverse. It approaches one on extreme recapture, where perturbed correctness variance collapses. Pairing improves precision while preserving the expected change.

Table 10 reports the ratios with group-resampled intervals by source and tier. The ratio varies across model groups (for example, 0.42 to 0.63 for correctness on ES) and rises with tier within each real source. The standard error of an estimated accuracy change scales with the square root of the ratio, so pairing shortens it by about 40% under digital corruptions and by less than 10% on extreme recapture.

Table 10: Paired-to-unpaired variance ratio with group-resampled 95% intervals, by source and tier, for correctness C , maximum probability S and true-class probability M . Cells are model-condition pairs, weighted equally.

Source	Tier	Cells	C	S	M
Syn	all tiers	792	0.32 [0.28, 0.35]	0.32 [0.27, 0.37]	0.20 [0.16, 0.23]
Syn	mild	792	0.32 [0.28, 0.35]	0.32 [0.27, 0.37]	0.20 [0.16, 0.23]
Syn-B	all tiers	792	0.33 [0.29, 0.37]	0.31 [0.25, 0.36]	0.20 [0.17, 0.23]
Syn-B	mild	792	0.33 [0.29, 0.37]	0.31 [0.25, 0.36]	0.20 [0.17, 0.23]
ES	all tiers	2376	0.55 [0.53, 0.58]	0.55 [0.50, 0.59]	0.44 [0.41, 0.46]
ES	mild	1936	0.47 [0.44, 0.50]	0.47 [0.41, 0.51]	0.34 [0.31, 0.36]
ES	severe	220	0.87 [0.86, 0.88]	0.89 [0.87, 0.91]	0.82 [0.80, 0.83]
ES	extreme	220	0.95 [0.94, 0.96]	0.96 [0.95, 0.97]	0.93 [0.92, 0.94]
Diverse	all tiers	7128	0.87 [0.86, 0.89]	0.89 [0.87, 0.90]	0.83 [0.82, 0.85]
Diverse	mild	2244	0.71 [0.68, 0.74]	0.72 [0.67, 0.76]	0.61 [0.57, 0.64]
Diverse	severe	1100	0.85 [0.84, 0.87]	0.88 [0.86, 0.90]	0.80 [0.78, 0.83]
Diverse	extreme	3784	0.98 [0.97, 0.98]	0.99 [0.98, 0.99]	0.98 [0.97, 0.98]

C.3 IDENTIFICATION FROM MARGINALS ONLY

Table 11 treats the coarser information level in which only per-class, or only global, accuracies are reported. With a_y, b_y the clean and perturbed correct counts, each k_y lies in $[\max(0, a_y + b_y - n_y), \min(a_y, b_y)]$; summing over classes bounds K , hence $h = A - K$ and $r = B - K$ for total correct counts A, B , while the net change $A - B$ is always identified. Per-class accuracies reduce the width obtained from global accuracies by 40 to 60%. On Syn, with five evaluation records per class, the width of K is of the same order as the observed gross flip rate, so gross flips are identified only to within a range comparable to their observed magnitude. On the real sources, the two or three records per class sharply limit feasible overlaps, fixing the overlap in most classes. This level sits below $\mathcal{I}_0$, which retains complete two-sided records.

Table 11: Identification of the total correct-correct overlap K from accuracies alone (percentage points of N). Classwise sums per-class Fréchet intervals; global uses only A, B and N . Gross flips $h + r = A + B - 2K$ inherit twice the width of K . Pinned is the share of classes whose interval is a single value.

Source	Tier	K width, classwise	K width, global	Observed $h+r$	Pinned (%)
Syn	all tiers	13.78	23.31	13.87	48.4
Syn	mild	13.78	23.31	13.87	48.4
Syn-B	all tiers	6.44	11.32	9.33	83.9
Syn-B	mild	6.44	11.32	9.33	83.9
ES	all tiers	5.16	10.39	26.04	87.1
ES	mild	5.90	11.15	16.02	85.2
ES	severe	2.85	9.14	59.83	92.9
ES	extreme	0.91	4.97	80.38	97.7
Diverse	all tiers	2.18	5.76	64.39	94.6
Diverse	mild	4.72	10.17	32.33	88.2
Diverse	severe	3.00	9.18	57.75	92.5
Diverse	extreme	0.43	2.15	85.35	98.9

D SHARED CORRESPONDENCE IN REJECTION-POLICY COMPARISONS

Evaluation protocol. This appendix gives the protocol behind Section 4.2: whether the information hierarchy of Definition 1 changes which rejection policies can be ruled out on fixed records. It uses the previously frozen 450-cell panel: 90 Syn, 90 Syn-B, 135 ES and 135 Diverse cells, spanning all 44 models. Syn contributes 5,000 evaluation records per cell, five per class; the other sources contribute 500, two or three per class. With true labels known on both sides, decisions are made

separately within each model-condition cell, with no common correspondence constraint across conditions. The resulting comparisons characterize policy costs under the feasible correspondences of these labeled records.

The clean acceptance rule remains $Z_i = \mathbf{1}[S_i \geq \tau_0]$, with τ_0 fixed at the original 80% clean-development threshold. The five perturbed-side policies use $Z'_{b,j} = \mathbf{1}[S'_b \geq \tau_j]$, where τ_j is the descending clean-development order statistic at rank $\text{round}(q_j n_{\text{dev}})$, for $q_j \in \{.6, .7, .8, .9, 1\}$. All cutoff ties are accepted, although a threshold for 100% development coverage need not accept every evaluation record. Neither the candidate thresholds nor the cost weights are tuned using evaluation outcomes. The frozen weights are $\lambda \in \{0, .1, \dots, 1\}$, with .5 used for the primary comparison.

Events under one shared correspondence. Let π_y map clean to perturbed records within class y , and $\pi = (\pi_y)_y$. Extend the definitions of H and L in Table 2 to policy j by

$$\begin{aligned} H_j(\pi) &= \frac{1}{N} \sum_y \sum_{i \in y} C_i Z_i (1 - C'_{\pi_y(i)}) Z'_{\pi_y(i),j}, \\ L_j(\pi) &= \frac{1}{N} \sum_y \sum_{i \in y} C_i Z_i C'_{\pi_y(i)} (1 - Z'_{\pi_y(i),j}), \\ J_j(\pi) &= \lambda H_j(\pi) + (1 - \lambda) L_j(\pi). \end{aligned} \quad (10)$$

All rates use $N = \sum_y n_y$. The cost measures changes to clean predictions that were correct and accepted. Evaluation coverage and the total accepted-error rate provide complementary perturbed-side summaries.

For $\mathcal{I} \in \{\mathcal{I}_0, \mathcal{I}_k, \mathcal{I}_5\}$, write $\Pi_{\mathcal{I},y}$ for all classwise bijections satisfying that information, and $\Pi_{\mathcal{I}} = \prod_y \Pi_{\mathcal{I},y}$. These are the feasible sets of Definition 1: unrestricted within-class permutations, permutations with the observed classwise correct-correct counts, and permutations with all five observed classwise state counts. Scores and acceptance decisions stay attached to records. Every policy in a comparison faces the *same* π .

The sharp upper difference bound and worst-case regret are

$$\begin{aligned} D_{j\ell}^+(\mathcal{I}) &= \sup_{\pi \in \Pi_{\mathcal{I}}} \{J_j(\pi) - J_\ell(\pi)\}, \\ \mathcal{R}_j(\mathcal{I}) &= \sup_{\pi \in \Pi_{\mathcal{I}}} \{J_j(\pi) - \min_{\ell} J_\ell(\pi)\} = \max_{\ell} D_{j\ell}^+(\mathcal{I}), \\ &= \frac{1}{N} \max_{\ell} \sum_y \max_{\pi_y \in \Pi_{\mathcal{I},y}} \{c_{jy}(\pi_y) - c_{\ell y}(\pi_y)\}, \end{aligned} \quad (11)$$

where c_{jy} is the classwise weighted event *count* in Equation (10). The comparator ℓ is a single policy for the cell: its maximization stays outside the class sum. Exact enumeration of classwise record permutations gives these extrema.

Policy j has strictly lower cost than ℓ throughout the feasible set if $D_{j\ell}^+ < 0$. Separate sharp intervals establish this only when $\bar{J}_j - \underline{J}_\ell < 0$; their two endpoints can require different correspondences. We count comparisons established by the shared difference but missed by that same-information interval test. Numerical strictness uses $D_{j\ell}^+ < -10^{-12}$. Establishing that a policy is no worse than every candidate is a separate property.

Selection rules and controls. Minimax regret is a classical criterion used, for example, in statistical treatment choice (Manski, 2004). Here uncertainty concerns correspondence within fixed labeled records, rather than sampling from a population. The minimax-regret rule minimizes $\mathcal{R}_j$. Its primary comparator minimizes $\mathbb{E}_{\pi \sim \text{Unif}(\Pi_{\mathcal{I}})}[J_j(\pi)]$ using the *same information*. This mean weights feasible record permutations uniformly, retaining their multiplicities; it does not weight distinct count tables uniformly. Under $\mathcal{I}_0$ it equals the classwise product-independent value. That unconstrained product assignment need not satisfy the $\mathcal{I}_k$ or $\mathcal{I}_5$ constraints and is retained only as a weaker control. Other controls keep the original 80% threshold or minimize the marginal proxy $\lambda \mathbb{P}(C' = 0, Z'_j = 1) + (1 - \lambda) \mathbb{P}(C' = 1, Z'_j = 0)$. For all minimizations, values within 10^{-12} of the minimum are tied; ties favor nominal coverage closest to .8, then lower coverage, then policy index. Actual paired costs play no role in this tie rule. Realized regret is $J_j(\pi^{\text{obs}}) - \min_{\ell} J_\ell(\pi^{\text{obs}})$.

Which comparisons become determined? At $\lambda = .5$, $\mathcal{I}_5$ establishes 641 directed comparisons in 312/450 cells that the separate J intervals miss. These counts require both correct and incorrect perturbed records among those whose acceptance changes between the policies, excluding switches with only one correctness outcome. The cell counts are 82/90 Syn, 60/90 Syn-B, 92/135 ES and 78/135 Diverse. A different comparison measures information increments: $\mathcal{I}_0 \rightarrow \mathcal{I}_k$ adds 586 mixed-outcome strict comparisons in 241 cells, and $\mathcal{I}_k \rightarrow \mathcal{I}_5$ adds 52 in 42 cells. These information increments use a different comparator from the 641 gains over separate intervals. The latter control also strengthens with information, so the number it misses need not increase across information levels.

After removing candidates strictly worse than another throughout the feasible set, a *post hoc diagnostic* merges thresholds with identical evaluation acceptance vectors, treating each distinct vector as one action. The number of cells with one remaining distinct action is 148, 189 and 191 under $\mathcal{I}_0, \mathcal{I}_k, \mathcal{I}_5$. This merging of identical actions was not a prespecified primary endpoint; the five nominal-policy results are also retained. Additional strict comparisons often leave several actions undominated. The L_j endpoints remain identical under $\mathcal{I}_k$ and $\mathcal{I}_5$, consistent with Theorem 1; five-state increments in the combined comparisons do not contradict target-specific sufficiency.

Figure 5 shows how the fraction of cells with additional determined policy comparisons varies across the frozen cost-weight grid. It measures which additional policy orderings can be established; realized policy-selection gains are reported separately below.

Shared-correspondence difference bound. The certificate $\bar{\Delta}_{j\ell}(\mathcal{I})$ of the shared-correspondence comparison in Section 4.2, Equation (2), is the quantity written $D_{j\ell}^+(\mathcal{I})$ above; Table 12 counts the cells in which it certifies an ordering that the separate sharp intervals leave open.

Table 12: Cells with at least one additional strict policy comparison at $\lambda = 0.5$, restricted to threshold-switching records containing both correct and incorrect predictions. Shared π compares common-correspondence differences against separate sharp policy intervals within $\mathcal{I}_5$; $+k$ and $+5$ instead add information ($\mathcal{I}_0 \rightarrow \mathcal{I}_k$ and $\mathcal{I}_k \rightarrow \mathcal{I}_5$). Counts summarize cells of the frozen panel.

Source	Cells	Shared π	$+k$	$+5$
Syn	90	82	77	28
Syn-B	90	60	75	6
ES	135	92	47	2
Diverse	135	78	42	6
Total	450	312	241	42




Figure 5: Sensitivity to the frozen cost-weight grid. Fractions give the share of cells in each source’s fixed panel with an additional certified ordering. Shared-correspondence comparisons use separate sharp cost intervals as the control; information increments compare successive information levels. The primary weight is $\lambda = .5$.

Single-policy bounds and policy-selection results. Within each class, the two event counts satisfy $h_{jy} + l_{jy} \leq u_y$, where u_y counts correct accepted clean records, and Lemma 1 states that maximizing the weighted cost over the separate sharp H_j/L_j count intervals intersected with this cap equals the joint single-policy upper bound. The panel computation confirms the identity: the maximum residual over 74,250 policy-weight-information rows is 1.39×10^{-15} percentage points. Once the sharp event bounds and the support cap are supplied, joint optimization adds nothing to the single-policy upper bound. Shared-correspondence differences can still strengthen comparisons. The +5 column of Table 12 is specific to the cost J_j , which charges accepted errors by their transition origin H_j : under the natural cost $\lambda E_{\tau_j} + (1 - \lambda)L_j$, Corollary 1 makes the $\mathcal{I}_k \rightarrow \mathcal{I}_5$ increment zero in every cell, because E_{τ_j} is marginal and the L_j differences range over the same set at both levels.

At $\lambda = .5$ under $\mathcal{I}_5$, minimax regret yields lower realized cost than the same-information feasible-permutation mean rule in four cells, higher cost in three and equal cost in 443. Table 13 reports the correspondingly small realized-regret differences. Gains over the fixed 80% threshold are larger, but that control was not optimized for J . Worst-case optimality follows from the minimax definition; the realized-cost comparison evaluates selection performance. The evidence supports additional finite-record comparisons, while realized-selection gains are small and mixed.

Table 13: Mean realized regret in percentage points at $\lambda = .5$, $\mathcal{I}_5$, averaging cells equally within source. Both rules use the same feasible permutations and measure regret relative to the lowest-cost policy under the observed correspondence. Better/Worse/Tied count cells where minimax has lower/higher/equal realized cost than the feasible-permutation mean rule.

Source	Cells	Feasible mean	Minimax	Better	Worse	Tied
Syn	90	0.004778	0.004222	1	1	88
Syn-B	90	0.005556	0.005556	0	0	90
ES	135	0.012593	0.004444	3	0	132
Diverse	135	0.003704	0.005185	0	2	133

Table 14 reports the full frozen weight grid. Mean realized-regret reduction is negative at six of the eleven weights. These small differences change sign across weights and do not establish a consistent actual-selection advantage.

Table 14: Realized policy-selection results over the full frozen weight grid at $\mathcal{I}_5$. Δ is feasible-permutation mean regret minus minimax regret, in percentage points, averaged equally over all 450 cells; negative values favor the mean rule. Better/Worse/Tied count lower/higher/equal realized costs for minimax.

λ	Δ (pp)	Better	Worse	Tied
0.0	0.000000	0	0	450
0.1	0.000044	1	0	449
0.2	-0.000542	0	3	447
0.3	-0.002400	2	5	443
0.4	-0.003111	4	7	439
0.5	0.002111	4	3	443
0.6	0.001182	7	9	434
0.7	-0.000076	3	9	438
0.8	-0.001396	2	7	441
0.9	-0.002791	5	8	437
1.0	0.000000	0	0	450

Numerical verification. Thirteen numerical checks cover small global Cartesian-product enumerations, non-simultaneously attainable extrema, ties and boundary cases. Across all 450 cells, verification confirms the 80% development thresholds, the earlier H/L results, finite values, inclusion of observed values, information nesting, comparison direction and regret aggregation; the largest discrepancy from the earlier results is 7.11×10^{-15} percentage points. A separate implementation shares the original record-reading procedure and independently computes every weight, policy and information level for eight original-record cells with zero discrepancy. These cells are the first and last in lexicographic order within each source. The analysis covers 74,250 bounds, 297,000 directed comparisons and 74,250 policy selections, with complete and unique coverage of the planned combinations. The calculations use existing predictions and take 167.29 seconds on CPU. Models and images recur across cells, and the results describe comparisons within the fixed panel.

D.1 A REPRODUCIBLE REAL-RECORD ILLUSTRATION

The example referenced in Section 4.3 uses the MAE ViT-L classifier and Diverse print condition 14 at lighting level 1 (500 evaluation images, 200 classes). Its clean threshold is the historical 80% development-coverage threshold. The selection protocol was fixed before choosing the case: among real panel cells with positive retained-correct support and a shared-correspondence certificate missed by separate intervals at $\lambda = 0.5$, choose the cell nearest the median marginal H width over the real panel; break ties by source, model and condition. Table 15 reports its intervals and observed values. The case illustrates the certified ordering and identified intervals for one observed condition.

Table 15: Sharp intervals and observed values in the real-record illustration. Units are percentage points for H, L and probability points for dM_k . Actual correspondence determines the observed column.

Target	$\mathcal{I}_0$	$\mathcal{I}_k$	$\mathcal{I}_5$	Observed
H	[0.4, 0.8]	[0.4, 0.8]	[0.4, 0.6]	0.6
L	[17.8, 26.2]	[19.0, 26.0]	[19.0, 26.0]	23.2
dM_k	[19.52, 30.02]	[20.58, 29.43]	[20.58, 29.43]	26.24

Choose the first policy pair in index order with mixed outcomes and a strict shared certificate missed by separate intervals. Its nominal clean-development coverages are 70% and 60%, with score thresholds 0.669638 and 0.719598. At $\mathcal{I}_5$, their J intervals are [14.9, 18.4] and [16.7, 20.3] points. Subtracting separate endpoints gives an upper difference of +1.7, whereas optimizing the difference under one common correspondence gives -1.5. The 70%-coverage policy therefore has lower transition cost for every feasible correspondence. This ordering already holds at $\mathcal{I}_0$; the example demonstrates the shared-correspondence comparison alongside the target-specific narrowing

of H . Independent classwise enumeration reproduces all nine target intervals and 75 policy-difference bounds from the underlying records.

E SCREENING PROTOCOLS AND ADDITIONAL RESULTS

These analyses support Sections 5.1–5.4 through score and identity controls, budgeted failure recall, equal-inference probe comparisons, and split and inference-cost checks.

The analyses use the fixed evaluation records, with additional model evaluations for the natural-transformation comparison described below. Unless a table states resampling of the 200 true classes, intervals are percentile intervals from resampling the ten model groups (2,000 draws); both summarize sensitivity within this pool, not population uncertainty. Tiers are the development-defined tiers of Section 3.3.

E.1 IMAGE-LEVEL SCORES: PROTOCOL, RESAMPLING, SCREENING AND IDENTITY ABLATION

Scores and sets. On clean-correct images, $M_i = S_i$, so (S, δ) and (S, U) contain identical information.

For each model, U_i averages the true-class probability $M'_{i,c}$ over the 18 Syn-B conditions c on the 500 real evaluation base images, ret_i is the share of these conditions on which the image remains correct, and $\delta_i = S_i - U_i$, which on clean-correct images equals the mean clean-minus-corrupted drop. All scores are oriented so that larger values indicate failure ($-S, -U, \delta, -\text{ret}$); the outcome for a real condition is failure among clean-correct evaluation images, and cells in which all such images share one outcome have no AUROC (118 Diverse and 2 ES cells, all but one extreme). Every score is evaluated on the same images of a cell. The class-level baseline assigns to each evaluation image the development-set mean of $M - U$ over all development images of its class. The frozen predictors $g(S)$, $g(S, U)$ and $g(S, U, \text{ret})$ are logistic regressions fitted per model and source on development clean-correct images, pooling observations across the real conditions of that source and standardizing features on the development data (L-BFGS optimization, inverse regularization strength $C = 1$). A fit on (S, δ) under the same standardization and penalty is not algebraically identical to the fit on (S, U) , because the columnwise standardization and the ℓ_2 penalty are not invariant to the linear reparameterization; recomputed on all cells, the two predictors differ in AUROC by at most 0.004 (mean 5.6×10^{-5}), so the choice is immaterial here. $g(S)$ reproduces the ranking of S exactly in 87 of the 88 model–source fits; for one model on Diverse the development fit has a positive slope and the ranking reverses, which is reported rather than corrected. Adding ret to $g(S, U)$ changes mean AUROC by at most 0.001. Within a model, δ and $-U$ have Spearman correlation between 0.23 and 0.91 across models (median 0.77).

Table 16: AUROC for ranking real failures among clean-correct images, on identical sets for every score. Class- δ is the development-set class mean of $M - U$; $g(S, U)$ is fitted on development images. The gap uses 95% model-group resampling intervals. Class-resampled intervals and cell counts are in Appendix E.

Source	Tier	S	U	δ	ret	Class- δ	$g(S, U)$	$U - S$ [95%]
ES	mild	0.778	0.854	0.768	0.823	0.580	0.855	+0.076 [+0.070, +0.080]
ES	severe	0.593	0.647	0.630	0.614	0.546	0.647	+0.054 [+0.044, +0.063]
ES	extreme	0.538	0.578	0.572	0.560	0.535	0.576	+0.040 [+0.027, +0.056]
Diverse	mild	0.678	0.801	0.781	0.755	0.587	0.809	+0.123 [+0.110, +0.131]
Diverse	severe	0.601	0.700	0.698	0.656	0.565	0.710	+0.099 [+0.084, +0.109]
Diverse	extreme	0.504	0.512	0.512	0.529	0.478	0.517	+0.008 [-0.006, +0.024]

Two resampling schemes. Figure 2 and Table 16 use intervals from resampling the ten model groups. Table 17 instead resamples the 200 true classes with replacement, applying one class draw to every cell of a source (200 draws); cells whose resampled positives or negatives vanish are skipped in that draw. Both schemes exclude zero for $U - S$ on mild and severe conditions and for $\delta - U$ on mild conditions; neither is a population confidence interval.

Table 17: Per-cell AUROC differences with 95% intervals from resampling the 200 true classes (point estimates are the plain cell means; cells is the mean number of cells retained per draw).

Source	Tier	Cells	$U - S$	$\delta - U$	$g(S, U) - S$
ES	mild	1935	+0.076 [+0.060,+0.093]	-0.086 [-0.107,-0.065]	+0.077 [+0.060,+0.097]
ES	severe	219	+0.054 [+0.035,+0.070]	-0.016 [-0.028,-0.005]	+0.054 [+0.034,+0.072]
ES	extreme	214	+0.040 [+0.020,+0.057]	-0.005 [-0.020,+0.011]	+0.038 [+0.017,+0.056]
Diverse	mild	2244	+0.123 [+0.107,+0.142]	-0.020 [-0.031,-0.007]	+0.131 [+0.110,+0.153]
Diverse	severe	1099	+0.099 [+0.084,+0.116]	-0.002 [-0.013,+0.009]	+0.108 [+0.091,+0.128]
Diverse	extreme	3174	+0.008 [-0.013,+0.039]	+0.001 [-0.015,+0.017]	+0.013 [-0.013,+0.052]

Screening levels. Table 18 fixes in advance the fraction q of clean-correct images to recapture and reports the share of a condition’s real failures among the images ranked highest by each score (ties broken at random in this table); random selection captures q in expectation. On mild conditions, U captures 49% (ES) and 26% (Diverse) of failures at $q = 0.1$ and 67% and 45% at $q = 0.2$, against 41%/21% and 58%/36% for clean confidence. This evaluation ranks labeled images within the existing pool.

Table 18: Screening: share of real failures among the top- q fraction of clean-correct images ranked by each score (cells weighted equally within source and tier). Random selection is one seeded draw per cell; its expectation is q .

Source	Tier	$q = 0.1$						$q = 0.2$					
		S	U	δ	ret	random		S	U	δ	ret	random	
ES	mild	0.406	0.489	0.395	0.487	0.096	0.578	0.672	0.568	0.648	0.199		
ES	severe	0.126	0.133	0.134	0.135	0.100	0.241	0.254	0.252	0.248	0.201		
ES	extreme	0.104	0.106	0.106	0.106	0.100	0.208	0.210	0.209	0.208	0.200		
Diverse	mild	0.208	0.260	0.271	0.271	0.099	0.357	0.449	0.452	0.441	0.200		
Diverse	severe	0.130	0.144	0.150	0.147	0.100	0.248	0.274	0.280	0.270	0.199		
Diverse	extreme	0.102	0.102	0.103	0.103	0.100	0.203	0.204	0.204	0.204	0.200		

Screening differences, attainable ceilings and budgets. Table 19 reports budget $q = 0.2$; Table 18 gives the coverage levels at $q = 0.1$ and $q = 0.2$ with a random-selection draw, and Table 21 the failure share p and the attainable ceiling $\min(1, k/n_{\text{fail}})$ with $k = \max(1, \text{round}(qn))$ recaptures. Paired differences use tie-prorated coverage (the expected coverage under random tie-breaking, which matters for the retention rate with its 19 possible values); class-resampled intervals (Table 20) recompute the coverage with resampled class weights and the same proration. On extreme conditions U attains 95% to 98% of the ceiling, but so does random selection in expectation (a fraction p of the ceiling: 91% on ES and 96% on Diverse, where U reaches 98%), so this table bounds the room for improvement without establishing retained ranking ability; the AUROC columns of Table 16 carry that information.

Table 19: Failure coverage at a 20% recapture budget and paired differences with 95% model-group resampling intervals (ties prorated; cells equally weighted). Random selection covers approximately 20% in expectation, subject to integer budget rounding. Other budgets and class-resampled intervals are in Appendix E.

Source	Tier	S	U	$U - S$ [95%]	$U - \delta$ [95%]	$U - \text{ret}$ [95%]
ES	mild	0.578	0.672	+0.094 [+0.078,+0.106]	+0.104 [+0.079,+0.140]	+0.024 [+0.013,+0.042]
ES	severe	0.241	0.254	+0.013 [+0.011,+0.017]	+0.002 [-0.001,+0.007]	+0.007 [+0.001,+0.016]
ES	extreme	0.208	0.210	+0.002 [+0.002,+0.003]	+0.001 [-0.000,+0.002]	+0.001 [+0.000,+0.004]
Diverse	mild	0.357	0.449	+0.092 [+0.075,+0.109]	-0.003 [-0.009,+0.007]	+0.008 [-0.006,+0.036]
Diverse	severe	0.248	0.274	+0.026 [+0.021,+0.032]	-0.006 [-0.008,-0.005]	+0.004 [-0.002,+0.016]
Diverse	extreme	0.203	0.204	+0.001 [+0.001,+0.002]	-0.000 [-0.001,-0.000]	+0.000 [-0.000,+0.001]

Table 20: Class-resampled 95% intervals for the paired coverage differences at each budget (200 draws of the 200 true classes, one draw shared by every cell of a source).

Source	Tier	Budget	$U - S$ [classes]	$U - \delta$ [classes]	$U - \text{ret}$ [classes]
ES	mild	0.1	[+0.064,+0.111]	[+0.077,+0.116]	[-0.009,+0.013]
ES	mild	0.2	[+0.075,+0.114]	[+0.076,+0.125]	[+0.008,+0.038]
ES	mild	0.3	[+0.079,+0.120]	[+0.057,+0.115]	[+0.015,+0.048]
ES	severe	0.1	[+0.004,+0.011]	[-0.004,+0.004]	[-0.005,+0.001]
ES	severe	0.2	[+0.006,+0.020]	[-0.003,+0.006]	[+0.001,+0.011]
ES	severe	0.3	[+0.008,+0.024]	[-0.001,+0.009]	[+0.008,+0.021]
ES	extreme	0.1	[+0.000,+0.002]	[-0.001,+0.001]	[-0.001,+0.000]
ES	extreme	0.2	[+0.000,+0.004]	[-0.001,+0.002]	[+0.000,+0.003]
ES	extreme	0.3	[+0.001,+0.006]	[-0.001,+0.002]	[+0.001,+0.005]
Diverse	mild	0.1	[+0.040,+0.065]	[-0.021,-0.002]	[-0.017,-0.003]
Diverse	mild	0.2	[+0.073,+0.113]	[-0.015,+0.008]	[-0.002,+0.020]
Diverse	mild	0.3	[+0.090,+0.133]	[-0.003,+0.018]	[+0.019,+0.048]
Diverse	severe	0.1	[+0.010,+0.017]	[-0.008,-0.003]	[-0.005,-0.000]
Diverse	severe	0.2	[+0.020,+0.034]	[-0.011,-0.002]	[-0.001,+0.010]
Diverse	severe	0.3	[+0.029,+0.046]	[-0.008,+0.002]	[+0.009,+0.022]
Diverse	extreme	0.1	[+0.001,+0.001]	[-0.001,+0.000]	[-0.000,+0.000]
Diverse	extreme	0.2	[+0.001,+0.002]	[-0.001,+0.000]	[-0.000,+0.001]
Diverse	extreme	0.3	[+0.001,+0.003]	[-0.001,+0.000]	[+0.000,+0.003]

Table 21: Failure share p among clean-correct images, attainable coverage ceiling $\min(1, k/n_{\text{fail}})$ for budgets q , and the coverage of U as a fraction of the ceiling. Each column averages cellwise quantities equally within source and tier; the last is the mean of cellwise ratios, not the ratio of the displayed means.

Source	Tier	p	attainable ceiling			$U / \text{ceiling}$	
			$q=0.1$	$q=0.2$	$q=0.3$	$q=0.1$	$q=0.2$
ES	mild	0.167	0.748	0.883	0.941	0.676	0.760
ES	severe	0.675	0.160	0.319	0.478	0.864	0.830
ES	extreme	0.908	0.112	0.223	0.335	0.956	0.947
Diverse	mild	0.360	0.373	0.643	0.815	0.777	0.739
Diverse	severe	0.652	0.170	0.339	0.500	0.891	0.853
Diverse	extreme	0.964	0.104	0.209	0.314	0.984	0.980

Protocol sensitivity without re-inference. All stored probabilities use one scoring protocol (a fixed multiplier of 100 and categorical softmax for OpenCLIP models). The stored records contain no logits, so a first check uses only rank information; the native scoring rules are recomputed from the re-inference described later in this appendix. As the rank check, U_{rank} replaces each condition’s true-class probability by its percentile rank among the clean-correct images before averaging, which is invariant to any strictly monotone within-condition rescaling, and U^γ averages $(M')^\gamma$ for $\gamma \in \{0.5, 2\}$. Table 22 shows that U_{rank} remains above clean confidence by 0.05 (ES) and 0.08 (Diverse) on mild conditions, up to 0.044 below U , and that the power transforms move U by at most 0.007. The direction of the result does not depend on the probability scale; its magnitude does.

Table 22: Protocol sensitivity: AUROC of U , of its rank-based version and of power-transformed versions, with the $U_{\text{rank}} - S$ gap and a 95% interval from resampling model groups.

Source	Tier	S	U	U_{rank}	$U^{0.5}$	U^2	$U_{\text{rank}} - S$ [groups]
ES	mild	0.778	0.854	0.832	0.854	0.851	+0.054 [+0.049,+0.058]
ES	severe	0.593	0.647	0.628	0.649	0.644	+0.035 [+0.027,+0.044]
ES	extreme	0.538	0.578	0.565	0.580	0.575	+0.028 [+0.016,+0.045]
Diverse	mild	0.678	0.801	0.757	0.805	0.794	+0.079 [+0.069,+0.086]
Diverse	severe	0.601	0.700	0.662	0.704	0.695	+0.061 [+0.052,+0.069]
Diverse	extreme	0.504	0.512	0.506	0.511	0.512	+0.003 [-0.008,+0.016]

Check on the other half of the image pool. The image-level comparisons were explored on the 500 evaluation base images. Table 23 repeats them on the 500 development images, which were used only for thresholds and calibrators, with the fitting roles exchanged (class-level baseline and g fitted on evaluation images) and no other change. The tier labels are those defined from development-set accuracy (Section 3.3), so on this half they were fixed using the same images that are evaluated; regrouping the same cells by tiers defined from evaluation-set accuracy (per-model correct counts over evaluation images, equal-weight mean, cuts 40% and 20%) moves 5 Diverse conditions from severe to mild (evaluation pool means 40.1% to 41.7%) and leaves the mild-tier gaps essentially unchanged: $U - S$ AUROC +0.128 and coverage +0.088 on Diverse against +0.128 and +0.093 under the development-defined tiers, with ES unchanged (Table 24). The gaps reproduce: $U - S$ in AUROC is +0.078 and +0.128 on mild ES and Diverse, and the budget-0.2 coverage difference is +0.111 and +0.093. This is the other half of the same pool with the same models and capture settings, not a new collection; on this half δ slightly exceeds U on severe and extreme conditions.

Table 23: Check on the development images with fitting roles exchanged: AUROC of each score, the $U - S$ gap, and the budget-0.2 coverage difference, with 95% intervals from resampling model groups (class-resampled intervals also exclude zero on mild and severe conditions).

Source	Tier	S	U	δ	ret $g(S,U)$	AUROC $U-S$	Cov. $U-S$
ES	mild	0.778	0.856	0.779	0.831	0.856 +0.078 [+0.072,+0.083]	+0.111 [+0.097,+0.129]
ES	severe	0.572	0.641	0.646	0.608	0.644 +0.069 [+0.059,+0.075]	+0.012 [+0.010,+0.015]
ES	extreme	0.504	0.560	0.577	0.553	0.563 +0.056 [+0.034,+0.072]	+0.003 [+0.002,+0.003]
Diverse	mild	0.673	0.801	0.790	0.754	0.815 +0.128 [+0.119,+0.135]	+0.093 [+0.075,+0.120]
Diverse	severe	0.588	0.701	0.709	0.663	0.718 +0.113 [+0.096,+0.128]	+0.026 [+0.020,+0.036]
Diverse	extreme	0.475	0.507	0.536	0.518	0.520 +0.032 [+0.019,+0.049]	+0.001 [+0.001,+0.002]

Table 24: Swapped-split confirmation regrouped by tiers defined from evaluation-set accuracy (development images evaluated; fitting on evaluation images). AUROC of S and U , and the $U - S$ gaps in AUROC and in coverage at $q = 0.2$, with 95% intervals from resampling model groups.

Source	Tier (eval-defined)	Conditions	S	U	AUROC $U-S$ [95%]	Cov. $U-S$ [95%]
ES	mild	44	0.778	0.856	+0.078 [+0.072,+0.083]	+0.111 [+0.097,+0.129]
ES	severe	5	0.572	0.641	+0.069 [+0.059,+0.075]	+0.012 [+0.010,+0.015]
ES	extreme	5	0.504	0.560	+0.056 [+0.034,+0.072]	+0.003 [+0.002,+0.003]
Diverse	mild	56	0.667	0.794	+0.128 [+0.118,+0.135]	+0.088 [+0.071,+0.114]
Diverse	severe	20	0.583	0.695	+0.112 [+0.093,+0.127]	+0.023 [+0.018,+0.032]
Diverse	extreme	86	0.475	0.507	+0.032 [+0.019,+0.049]	+0.001 [+0.001,+0.002]

Identity ablation on U and a class-level baseline matched to U . Table 25 reassigns U_i among clean-correct images of the same class with no fixed points (a derangement; ten seeded draws, AUROC averaged) or replaces it by the leave-one-out class mean, and compares with U_i on the same non-singleton subset; classes with a single clean-correct image have no control value and are excluded from this comparison (10 to 55 images per model). A uniform within-class permutation is not used because, with two or three images per class, it would leave about 40% of values in place. These controls answer what happens when an image receives another same-class image’s response; they are not class-level predictors. The leave-one-out mean decreases in the image’s own value and with two images per class it swaps the two, so the gap is an identity ablation, not the increment over class-level information. On mild conditions the derangement control falls to AUROC 0.55 on ES and 0.58 on Diverse against 0.85 and 0.80 for U_i , and U_i exceeds its control in 99.9% and 100.0% of cells; the same ablation applied to δ_i gives the same ordering. On extreme Diverse conditions the control degenerates in 14% of cells (all retained-correct images of the cell lie in one class, so the derangement only exchanges values among them and equals U_i in AUROC), which weakens the contrast there; excluding those cells moves the gap from +0.047 to +0.055. Table 26 evaluates development-fitted class-level predictors: the development-set class mean of U over clean-correct development images of the class, and over all development images, both evaluated on the images whose class has such a value. They reach AUROC 0.60 and 0.60, below clean confidence (0.78 and 0.68), and cover 0.30 and 0.27 of failures at the 20% budget against 0.67 and 0.45 for U . Table 27 stratifies by terciles of clean confidence within model: U_i retains AUROC 0.63 to 0.77 inside each stratum, where clean confidence retains much less separation (0.52 to 0.68), and images with above-median U_i have higher retention rates than those below the median within every stratum.

Table 25: Identity ablation: AUROC of clean confidence S , of U_i , of its within-class derangement control and of its leave-one-out class mean for ranking failing against retained-correct clean-correct images (failure as the positive class), all on the same non-singleton subset; gap is U_i minus the derangement control with a 95% interval from resampling the ten model groups; wins is the share of cells in which U_i exceeds its control.

Source	Tier	Cells	S	U	Derangement	LOO mean	Gap [95%]	Wins (%)
ES	mild	1936	0.775	0.853	0.553	0.548	+0.299 [+0.275,+0.319]	99.9
ES	severe	218	0.594	0.647	0.523	0.519	+0.124 [+0.119,+0.130]	99.1
ES	extreme	216	0.543	0.581	0.504	0.504	+0.077 [+0.058,+0.103]	80.5
Diverse	mild	2244	0.675	0.800	0.581	0.582	+0.219 [+0.205,+0.230]	100.0
Diverse	severe	1099	0.599	0.699	0.537	0.536	+0.162 [+0.148,+0.171]	99.2
Diverse	extreme	3485	0.498	0.508	0.461	0.453	+0.047 [+0.038,+0.059]	56.0

Table 26: Class-level baselines matched to U : AUROC of S , U and the development-set class mean of U over clean-correct development images (cc. dev) or over all development images (all dev), on the images whose class has such a value; the last two columns give the U minus clean-correct development class-mean gap in AUROC and in coverage at $q = 0.2$ with 95% intervals from resampling model groups.

Source	Tier	S	U	Class (cc. dev)	Class (all dev)	U -Class [95%]	Cov. U -Class [95%]
ES	mild	0.778	0.854	0.597	0.590	+0.257 [+0.238,+0.277]	+0.374 [+0.332,+0.422]
ES	severe	0.593	0.646	0.557	0.543	+0.089 [+0.080,+0.100]	+0.037 [+0.027,+0.052]
ES	extreme	0.540	0.578	0.545	0.541	+0.033 [+0.012,+0.050]	+0.006 [+0.005,+0.008]
Diverse	mild	0.678	0.801	0.604	0.596	+0.197 [+0.185,+0.206]	+0.177 [+0.148,+0.213]
Diverse	severe	0.601	0.701	0.567	0.554	+0.134 [+0.122,+0.143]	+0.051 [+0.041,+0.063]
Diverse	extreme	0.502	0.510	0.449	0.419	+0.061 [+0.036,+0.093]	+0.003 [+0.003,+0.004]

Table 27: Image-level separation within clean-confidence terciles (all conditions of each source, cells weighted equally; failure as the positive class). Gap is U_i minus its derangement control on the non-singleton subset with a 95% interval from resampling the ten model groups; the last column is the retention rate of images with above-median U_i minus that of images below the median within the stratum.

Source	Stratum	S	U	Derangement	Gap [95%]	Retention gap
ES	low	0.683	0.771	0.517	+0.255 [+0.235,+0.274]	+0.225
ES	mid	0.548	0.749	0.455	+0.294 [+0.255,+0.332]	+0.100
ES	high	0.530	0.755	0.460	+0.295 [+0.252,+0.325]	+0.075
Diverse	low	0.581	0.676	0.541	+0.136 [+0.110,+0.156]	+0.150
Diverse	mid	0.527	0.633	0.490	+0.144 [+0.117,+0.170]	+0.127
Diverse	high	0.517	0.646	0.507	+0.138 [+0.122,+0.158]	+0.116

Number of synthetic conditions. Table 28 recomputes U from subsets of the 18 Syn-B conditions fixed before any result was seen (seed-drawn, up to 20 distinct subsets per size; all 18 singletons for $m = 1$), plus the nine severity-2 and the nine severity-4 conditions. No subset was selected on outcomes; the table reports performance for each tested subset size. With six random conditions the mean coverage gain over clean confidence is 81% (ES) and 92% (Diverse) of the 18-condition gain, with minima of 67% and 68% over the prefixed draws; the worst three-condition subset still retains 51% and 41%; a single condition can fall below clean confidence on ES (worst gain -0.009). The severity-4 conditions alone reach coverage 0.669 and 0.461 against 0.672 and 0.449 for all 18, and the severity-2 conditions 0.658 and 0.416.

Table 28: Coverage at $q = 0.2$, coverage gain over S and AUROC of U_m computed from m of the 18 Syn-B conditions on mild conditions (cells weighted equally); for random subsets the mean over the prefixed subsets is followed by the minimum and maximum over subsets (minimum only for the gain).

Source	m	Subsets	n	Coverage [min,max]	$U_m - S$ [min]	AUROC [min,max]
ES	1	random	18	0.597 [0.569,0.619]	+0.019 [-0.009]	0.799 [0.785,0.816]
ES	2	random	20	0.625 [0.609,0.638]	+0.047 [+0.030]	0.818 [0.801,0.833]
ES	3	random	20	0.640 [0.626,0.652]	+0.062 [+0.048]	0.830 [0.818,0.844]
ES	6	random	20	0.654 [0.641,0.666]	+0.076 [+0.063]	0.840 [0.826,0.852]
ES	9	random	20	0.663 [0.655,0.669]	+0.085 [+0.077]	0.849 [0.837,0.854]
ES	9	severity 2 only	1	0.658	+0.080	0.837
ES	9	severity 4 only	1	0.669	+0.091	0.854
ES	18	all 18	1	0.672	+0.094	0.854
Diverse	1	random	18	0.399 [0.363,0.449]	+0.042 [+0.005]	0.730 [0.685,0.792]
Diverse	2	random	20	0.419 [0.380,0.465]	+0.061 [+0.023]	0.753 [0.711,0.809]
Diverse	3	random	20	0.429 [0.395,0.459]	+0.071 [+0.037]	0.766 [0.726,0.807]
Diverse	6	random	20	0.442 [0.419,0.457]	+0.084 [+0.062]	0.784 [0.759,0.804]
Diverse	9	random	20	0.444 [0.427,0.453]	+0.087 [+0.070]	0.792 [0.775,0.803]
Diverse	9	severity 2 only	1	0.416	+0.059	0.760
Diverse	9	severity 4 only	1	0.461	+0.103	0.811
Diverse	18	all 18	1	0.449	+0.092	0.801

Natural test-time augmentation, native scoring rules and consistency of the re-inference. The comparison of Section 5.3 follows a protocol specified before its model evaluations. The fixed set of 18 natural transformations is horizontal flip; shifts of $\pm 2\%$ and $\pm 5\%$ of the width or height in each axis (eight); zoom 1.1 and 1.2 (central crop, resized back); rotations of $\pm 5^\circ$ and $\pm 10^\circ$; gamma 0.8 and 0.9; flip combined with zoom 1.1; shifts and rotations use reflect padding and every transformation is applied to the original image before the model’s own preprocessing. The candidate pool of 30 adds zoom-out to 90%, gamma 0.6 and 1.25, flip combined with $\pm 10^\circ$ rotation, brightness 0.9 and 1.1, contrast 0.9 and 1.1, saturation 0.8 and 1.2, flip combined with a 2% shift. TTA_{18} averages the true-class probability over the 18 transformed versions of a clean-correct image, so the class is fixed to the clean prediction and neither the prediction nor the image set is changed by the augmentation; the versions with the untransformed image added as a nineteenth term follow Bahat & Shakhnarovich (2020). The development-selected variant TTA^{sel} adds transformations from the pool one at a time, each time taking the one that maximizes the mean coverage at $q = 0.2$ over all models and conditions of the source on the development images with that source’s real failure labels, until 18 are chosen; for the development-half report the selection is redone on evaluation images. Zoom-out was chosen first in three of the four selections (rotation by $+10^\circ$ in the fourth), and the selected sets share 11 to 14 members with the fixed set; the analogous selection of 18 of the 27 Syn-B conditions, denoted U^{sel} , changes U by +0.003 on ES (interval including zero) and +0.025 on Diverse, mostly by admitting severity-5 conditions. Table 29 reports the paired coverage differences for these variants at three budgets, Table 31 the development-half confirmation, and Table 32 the coverage of both averages as a function of the number of versions with the prefixed subsets of Table 28 applied by index to both lists.

Every score in this comparison is derived from a common evaluation of the 44 models on the 1,000 base images under 49 input variants: the clean image, 18 corruptions and 30 natural transformations.

Model loading, preprocessing, mixed precision and scoring follow the original evaluation procedure. Single-precision cosine similarities for OpenCLIP models, 1,000-class logits for supervised and linear-head models, and learned logit scales and SigLIP biases support the alternative scoring calculations. Three agreement tolerances were specified in advance: at least 99% prediction agreement, mean absolute probability difference at most 0.01, and clean accuracy difference at most 0.5 percentage points. The repeated evaluation reproduces the recorded clean and corruption class predictions and probabilities exactly for all 44 models and all 19 conditions (Table 30); the resulting U and S AUROCs agree with Table 16 to 10^{-16} . This confirms computational consistency on the same GPU model using the original procedure and the documented contemporary library versions. Scores recomputed from the single-precision outputs differ from the recorded half-precision probabilities by at most 0.009 and change the predicted class for at most 0.8% of images near ties. The common protocol applies softmax to cosine similarities multiplied by 100 for OpenCLIP models and to the 200-class logit subspace for other models. Native scoring uses the learned scale (14 to 117), sigmoid probabilities with the learned scale and bias for SigLIP, and full 1,000-class softmax probabilities for supervised and linear-head models. The text classifier, candidate-space predictions and eligible images remain fixed across scoring rules. Under native scoring, mean mild-condition AUROC decreases by about 0.02 for clean confidence, U_{18} and TTA_{18} (-0.020, -0.022 and -0.022 on ES), while their gaps remain unchanged. At the primary 20% recapture budget, the native-rule coverage gaps between U_{18} and TTA_{18} are 0.073 on ES and 0.072 on Diverse.

Table 29: Paired coverage differences for the variants of the natural-augmentation comparison at budgets $q \in \{0.1, 0.2, 0.3\}$ (95% intervals from resampling model groups): both averages with the untransformed image added; both under the native scoring rule; U_{18} against the development-selected natural set; the development-selected against the fixed natural set (the development-selected Syn-B set against the historical U is given in the text).

Source	Tier	q	$U^{+0} - \text{TTA}^{+0}$	native $U - \text{TTA}$	$U_{18} - \text{TTA}^{\text{sel}}$	$\text{TTA}^{\text{sel}} - \text{TTA}_{18}$
ES	mild	0.1	+0.057 [+0.046,+0.074]	+0.060 [+0.046,+0.082]	+0.054 [+0.043,+0.069]	+0.002 [-0.002,+0.007]
ES	mild	0.2	+0.076 [+0.062,+0.086]	+0.073 [+0.061,+0.082]	+0.072 [+0.060,+0.081]	+0.004 [+0.002,+0.007]
ES	mild	0.3	+0.078 [+0.062,+0.090]	+0.076 [+0.062,+0.088]	+0.076 [+0.061,+0.089]	+0.002 [+0.001,+0.003]
ES	severe	0.1	+0.007 [+0.006,+0.009]	+0.006 [+0.005,+0.007]	+0.007 [+0.005,+0.009]	+0.000 [-0.001,+0.001]
ES	severe	0.2	+0.012 [+0.009,+0.016]	+0.010 [+0.006,+0.013]	+0.012 [+0.009,+0.015]	+0.001 [+0.000,+0.002]
ES	severe	0.3	+0.017 [+0.012,+0.021]	+0.014 [+0.008,+0.019]	+0.017 [+0.011,+0.021]	+0.001 [-0.001,+0.002]
ES	extreme	0.1	+0.001 [+0.001,+0.002]	+0.001 [+0.001,+0.002]	+0.001 [+0.001,+0.002]	-0.000 [-0.000,+0.000]
ES	extreme	0.2	+0.002 [+0.002,+0.003]	+0.002 [+0.001,+0.003]	+0.002 [+0.001,+0.003]	+0.000 [-0.000,+0.001]
ES	extreme	0.3	+0.003 [+0.002,+0.004]	+0.003 [+0.001,+0.004]	+0.003 [+0.002,+0.004]	+0.000 [-0.000,+0.001]
Diverse	mild	0.1	+0.045 [+0.036,+0.052]	+0.040 [+0.031,+0.048]	+0.044 [+0.035,+0.051]	+0.002 [+0.001,+0.004]
Diverse	mild	0.2	+0.080 [+0.064,+0.095]	+0.072 [+0.052,+0.088]	+0.082 [+0.066,+0.096]	+0.001 [-0.001,+0.003]
Diverse	mild	0.3	+0.104 [+0.082,+0.121]	+0.090 [+0.064,+0.112]	+0.104 [+0.083,+0.121]	+0.001 [-0.000,+0.003]
Diverse	severe	0.1	+0.012 [+0.009,+0.014]	+0.010 [+0.008,+0.012]	+0.012 [+0.009,+0.014]	+0.000 [+0.000,+0.001]
Diverse	severe	0.2	+0.023 [+0.018,+0.027]	+0.021 [+0.015,+0.026]	+0.023 [+0.019,+0.028]	+0.000 [-0.001,+0.001]
Diverse	severe	0.3	+0.035 [+0.028,+0.041]	+0.030 [+0.020,+0.038]	+0.035 [+0.028,+0.041]	+0.001 [-0.000,+0.001]
Diverse	extreme	0.1	+0.001 [+0.000,+0.001]	+0.001 [+0.000,+0.001]	+0.001 [+0.000,+0.001]	-0.000 [-0.000,+0.000]
Diverse	extreme	0.2	+0.001 [+0.001,+0.002]	+0.001 [+0.001,+0.002]	+0.001 [+0.001,+0.002]	-0.000 [-0.000,+0.000]
Diverse	extreme	0.3	+0.002 [+0.001,+0.002]	+0.002 [+0.001,+0.002]	+0.002 [+0.001,+0.002]	+0.000 [-0.000,+0.000]

Table 30: Agreement between the re-inference and the historical clean and corruption records, by model implementation (minimum prediction agreement, maximum mean absolute probability difference and clean accuracy difference over models and conditions; range of learned logit scales), and the number of models meeting the prespecified agreement tolerances.

Implementation	Models	Pred. agreement (min)	Mean $ \Delta M $ (max)	Clean acc. diff (pp, max)	Scale (range)	Within tolerances
DINOv2	1	1.0000	0.0000	0.00	—	1/1
DINOv3	1	1.0000	0.0000	0.00	—	1/1
OpenCLIP	35	1.0000	0.0000	0.00	14.3–117.3	35/35
timm	6	1.0000	0.0000	0.00	—	6/6
torchvision	1	1.0000	0.0000	0.00	—	1/1

Table 31: Natural-augmentation comparison on the development half of the image pool with the selection of TTA^{sel} redone on evaluation images (coverage at $q = 0.2$; intervals from resampling model groups and classes).

Source	Tier	S	U_{18}	TTA_{18}	$U_{18} - \text{TTA}_{18}$ [groups]	[classes]	Δ AUROC [groups]	$U_{18} - \text{TTA}^{\text{sel}}$	
ES	mild	0.561	0.671	0.583	+0.088	[+0.076,+0.103]	[+0.058,+0.125]	+0.065 [+0.060,+0.069]	+0.085 [+0.073,+0.100]
ES	severe	0.228	0.241	0.229	+0.012	[+0.009,+0.015]	[+0.006,+0.018]	+0.065 [+0.055,+0.071]	+0.011 [+0.009,+0.015]
ES	extreme	0.204	0.207	0.204	+0.002	[+0.002,+0.003]	[+0.001,+0.004]	+0.057 [+0.037,+0.072]	+0.002 [+0.002,+0.003]
Diverse	mild	0.334	0.428	0.345	+0.082	[+0.066,+0.109]	[+0.069,+0.100]	+0.117 [+0.108,+0.123]	+0.080 [+0.064,+0.105]
Diverse	severe	0.239	0.265	0.242	+0.024	[+0.018,+0.033]	[+0.019,+0.030]	+0.104 [+0.087,+0.118]	+0.024 [+0.018,+0.033]
Diverse	extreme	0.202	0.203	0.202	+0.001	[+0.001,+0.002]	[+0.001,+0.002]	+0.035 [+0.021,+0.049]	+0.001 [+0.001,+0.002]

Table 32: Coverage at $q = 0.2$, gain over S and AUROC of the corruption average and of the natural-augmentation average computed from m versions, mild conditions, with the prefixed subsets of Table 28 applied by index to both lists (mean over subsets followed by the minimum and maximum; minimum only for the gain).

Source	Pool	m	Subsets	Coverage: mean [min, max]	Gain over S : mean [min]	AUROC: mean [min, max]
ES	U	1	18	0.597 [0.569,0.619]	+0.019 [-0.009]	0.799 [0.785,0.816]
ES	U	2	20	0.625 [0.609,0.638]	+0.047 [+0.030]	0.818 [0.802,0.833]
ES	U	3	20	0.640 [0.626,0.652]	+0.062 [+0.048]	0.830 [0.818,0.844]
ES	U	6	20	0.654 [0.641,0.666]	+0.076 [+0.063]	0.840 [0.826,0.852]
ES	U	9	20	0.663 [0.655,0.669]	+0.085 [+0.077]	0.849 [0.837,0.854]
ES	U	18	1	0.672	+0.094	0.854
ES	TTA	1	18	0.574 [0.553,0.585]	-0.004 [-0.025]	0.777 [0.767,0.783]
ES	TTA	2	20	0.584 [0.575,0.592]	+0.006 [-0.003]	0.783 [0.776,0.788]
ES	TTA	3	20	0.590 [0.584,0.597]	+0.012 [+0.005]	0.787 [0.783,0.789]
ES	TTA	6	20	0.594 [0.589,0.597]	+0.015 [+0.011]	0.789 [0.785,0.791]
ES	TTA	9	20	0.596 [0.592,0.598]	+0.017 [+0.014]	0.789 [0.787,0.791]
ES	TTA	18	1	0.596	+0.018	0.791
Diverse	U	1	18	0.399 [0.363,0.449]	+0.042 [+0.006]	0.730 [0.685,0.792]
Diverse	U	2	20	0.419 [0.380,0.465]	+0.061 [+0.023]	0.753 [0.711,0.809]
Diverse	U	3	20	0.429 [0.395,0.459]	+0.071 [+0.038]	0.766 [0.726,0.807]
Diverse	U	6	20	0.442 [0.419,0.457]	+0.084 [+0.062]	0.784 [0.759,0.804]
Diverse	U	9	20	0.444 [0.428,0.454]	+0.087 [+0.070]	0.792 [0.775,0.803]
Diverse	U	18	1	0.449	+0.092	0.801
Diverse	TTA	1	18	0.358 [0.351,0.363]	+0.001 [-0.006]	0.679 [0.675,0.684]
Diverse	TTA	2	20	0.361 [0.356,0.365]	+0.003 [-0.002]	0.682 [0.678,0.686]
Diverse	TTA	3	20	0.363 [0.357,0.366]	+0.006 [+0.000]	0.685 [0.680,0.688]
Diverse	TTA	6	20	0.364 [0.361,0.366]	+0.007 [+0.004]	0.686 [0.684,0.689]
Diverse	TTA	9	20	0.365 [0.363,0.368]	+0.008 [+0.006]	0.687 [0.685,0.689]
Diverse	TTA	18	1	0.366	+0.009	0.688

E.2 A RELATED AUGMENTATION-ALIGNMENT RANKING SCORE

We evaluate the scoring equations of A3Rank (Wei et al., 2024) on the fixed natural and corruption probe sets, separately. This adds one directly related ranking construction while keeping the same 18 probe evaluations and common clean prediction. Its score is evaluated for subsequent recapture failures, whereas the original work targets errors on the scored input and includes a downstream rejection component. We retain the score’s sums and three roles, but do not train its rejector or reproduce its model-specific training augmentations. The original score has no tuned weights: its alignment terms are summed with equal weight, and its only model-specific ingredient is the variant set drawn from the classifier’s training augmentations, which we replace by the fixed probe sets. PRIMA’s learned ranking with input and model mutations uses different resources (Wang et al., 2021); no performance comparison with that pipeline is claimed here.

Let p be the clean predicted class and m the modal predicted class across the 18 probes. Write $v_a(c)$ for probe a ’s probability of class c and $v_0(c)$ for the clean probability. Define distractors $\mathcal{D} = \{a : \arg \max_c v_a(c) \notin \{p, m\}\}$, supporters $\mathcal{S} = \{a : \arg \max_c v_a(c) = p\}$ and dominators $\mathcal{G} = \{a : \arg \max_c v_a(c) = m\}$. The adapted score is

$$\begin{aligned} A^3 = & v_0(p) - \sum_{a \in \mathcal{D}} [\max_c v_a(c) - v_a(p)] + \sum_{a \in \mathcal{S}} [v_a(p) - v_a(m)] \\ & + \sum_{a \in \mathcal{G}} [v_a(p) - v_a(m) + v_0(m) - v_0(p)]. \end{aligned} \quad (12)$$

Low A^3 indicates high failure risk. When $p = m$, the supporter and dominator contributions vanish even though their index sets coincide. Modal-count ties are resolved by the mean maximum probability among probes voting for each tied class, then by class index. This specifies a deterministic version of the original confidence-based tie rule.

The calculation uses the common 200-class probability protocol and historical clean-correct eligibility, without real-outcome fitting or score selection. For four eligible model–image pairs, recomputation from the underlying cosine similarities or logits changes the highest-probability clean class. They remain in the primary common image set; excluding them in a predeclared numerical sensitivity leaves the conclusions unchanged. The adaptation and protocol were fixed after the earlier exploration of the image pool and before calculating these baseline results.

Table 33 gives the numerical results plotted in Figure 4.

Table 33: Two probe sets crossed with two scoring rules on identical mild-condition image sets. Each uses 18 transformed inputs; A^3 is the A3Rank scoring adaptation. Recall uses a 20% recapture budget. Difference intervals are in Appendix E.2.

Scoring rule	Natural transforms		Corruptions	
	ES	Diverse	ES	Diverse
<i>Failure recall at 20% budget</i>				
Probability mean	0.596	0.366	0.672	0.449
A^3 score	0.588	0.360	0.654	0.447
<i>AUROC</i>				
Probability mean	0.791	0.688	0.854	0.801
A^3 score	0.784	0.680	0.836	0.775

The same-corruption scores are close in Diverse coverage at the primary budget, while U has higher AUROC on both sources (Table 34). At 10% on Diverse, A^3 covers about 0.268 of failures versus 0.260 for U ; at 30%, U is better (Table 35). Thus this comparison supports the usefulness of the tested synthetic responses with more than one scoring construction and locates budget-dependent differences between them. Both probe variants are also evaluated across all tiers.

Table 34: Mild-condition differences between U and the A3Rank scoring adaptations. Differences and separate 95% resampling intervals are in percentage points. Group resampling uses 2,000 draws of ten model groups; class resampling uses 200 draws of 200 classes and recomputes metrics on weighted images.

Source	A3 probes	Metric	$U - A^3$	Group interval	Class interval
ES	Natural	Recall@.2	+8.38	[+7.15, +9.40]	[+6.72, +10.06]
ES	Natural	AUROC	+6.95	[+6.30, +7.48]	[+5.51, +8.47]
ES	Corruption	Recall@.2	+1.85	[+0.73, +2.74]	[+0.69, +2.86]
ES	Corruption	AUROC	+1.77	[+1.37, +2.07]	[+1.30, +2.31]
Diverse	Natural	Recall@.2	+8.91	[+7.41, +10.45]	[+7.06, +10.97]
Diverse	Natural	AUROC	+12.09	[+10.67, +13.04]	[+10.56, +14.00]
Diverse	Corruption	Recall@.2	+0.23	[-0.40, +1.18]	[-0.58, +1.09]
Diverse	Corruption	AUROC	+2.66	[+2.24, +3.14]	[+2.20, +3.22]

Table 35: Budget sensitivity of the corruption-based ranking adaptation. U and A^3 columns report failure recall; differences $U - A^3$ and their 95% model-group intervals are in percentage points. The primary budget is 20%; A^3 has higher recall on Diverse at 10%.

Source	Budget	U	A^3	Difference	Group interval
ES	10%	0.489	0.479	+0.93	[-0.84, +2.13]
ES	20%	0.672	0.654	+1.85	[+0.73, +2.74]
ES	30%	0.771	0.758	+1.29	[+0.71, +2.16]
Diverse	10%	0.260	0.268	-0.80	[-1.37, -0.44]
Diverse	20%	0.449	0.447	+0.23	[-0.40, +1.18]
Diverse	30%	0.591	0.577	+1.41	[+0.59, +2.64]

E.3 PROBE AND CAPTURE-CONDITION DIAGNOSTICS

These exploratory diagnostics use the same predictions and development-defined mild tiers as the primary comparison. We score each of the 18 corruptions separately, average the two severities within each of nine types, and average all nine probes of each severity. The clean-correct image sets, target labels, failure recall and tie proration match the primary comparison. These sets use one, two, nine or 18 probe evaluations respectively; only the full corruption and natural sets have equal counts. Table 36 gives the severity comparison, and Figure 6 displays every individual probe.

Table 36: Mild screening by probe set. Evaluations count transformed inputs beyond the common clean prediction; the clean-only row counts that prediction. The severity subsets use different numbers of transformed inputs. Differences are in recall units.

Source	Probe set	Evaluations	Recall@.2	AUROC	Δ vs. TTA
ES	Clean	1	0.578	0.778	-0.018
ES	Natural TTA	18	0.596	0.791	+0.000
ES	Severity 2	9	0.658	0.837	+0.062
ES	Severity 4	9	0.669	0.854	+0.073
ES	All corruptions	18	0.672	0.854	+0.076
Diverse	Clean	1	0.357	0.678	-0.009
Diverse	Natural TTA	18	0.366	0.688	+0.000
Diverse	Severity 2	9	0.416	0.760	+0.050
Diverse	Severity 4	9	0.461	0.811	+0.094
Diverse	All corruptions	18	0.449	0.801	+0.083

Every two-severity type average exceeds natural TTA in mean coverage on both sources (9/9 types), whereas only 8/18 ES and 16/18 Diverse individual probes do so. Increasing severity from 2 to 4 improves recall for 5/9 ES and 8/9 Diverse types. Severity-4 averaging reaches 0.669/0.461 compared




Figure 6: Failure recall at a 20% testing budget for each corruption probe on mild recaptures. Circles and squares distinguish severities 2 and 4. Vertical lines mark the 18-corruption average, 18-transform natural average and clean confidence. Each point uses one transformed input, while the averages use 18. The probe sets differ in both transformation family and response strength.

with 0.672/0.449 for the full set; adding more probes therefore need not improve the score. Mean development error rates, averaged across probes and models on the historical clean-correct set, are 2.03% for natural TTA, 6.45% for severity 2 and 13.71% for severity 4. These rates average the errors of individual transformed predictions. The natural and corruption sets differ in both family and response strength, so the observed advantage is attributed to the tested sets rather than to corruption type independently of dose.

For capture sensitivity, each mild condition contributes its paired $U - S$ and $U - TTA_{18}$ coverage difference, averaged over models. Both means are positive in all 44 ES and 51 Diverse mild conditions. Grouping by lighting, ISO, shutter or aperture, or deleting any one factor level before averaging, preserves positive means. These factors are crossed acquisition settings, not independent replication units. The positive means occur across the tested conditions; these results establish neither per-model improvement in every condition nor simultaneous significance across conditions. The model-group differences in Appendix E.4 remain relevant; these diagnostics reuse the same models and images.

Table 37 reports the corruption and natural-transformation comparison across all tiers.

Table 37: Corruption versus natural-transformation averages across all tiers, using the same model evaluations. Coverage is failure recall at $q = 0.2$; paired differences carry separate 95% group and class intervals.

Source	Tier	Coverage at $q=0.2$				$U_{18} - TTA_{18}$		AUROC		
		S	U_{18}	TTA_{18}	[groups]	[classes]		U_{18}	TTA_{18}	Δ [groups]
ES	mild	0.578	0.672	0.596	+0.076	[+0.063,+0.086]		0.854	0.791	+0.063 [+0.058,+0.067]
ES	severe	0.241	0.254	0.242	+0.013	[+0.010,+0.016]		0.647	0.596	+0.051 [+0.041,+0.059]
ES	extreme	0.208	0.210	0.208	+0.002	[+0.002,+0.003]		0.578	0.540	+0.038 [+0.026,+0.052]
Diverse	mild	0.357	0.449	0.366	+0.083	[+0.066,+0.098]		0.801	0.688	+0.114 [+0.100,+0.123]
Diverse	severe	0.248	0.274	0.250	+0.023	[+0.019,+0.028]		0.700	0.607	+0.093 [+0.078,+0.104]
Diverse	extreme	0.203	0.204	0.203	+0.001	[+0.001,+0.002]		0.512	0.504	+0.008 [-0.006,+0.026]

E.4 SIMPLE SCORING CONTROLS AND MODEL-GROUP DECOMPOSITION

These exploratory checks compare additional scores on the same image pool and model predictions as the primary analysis. The three added scores were fixed before calculation. Clean margin is the largest minus the second-largest probability in the 200-class candidate space; lower values indicate

greater failure risk. Clean entropy is $-\sum_c p_c \log p_c$, with higher values indicating risk. These are simple uncertainty controls for test prioritization (Weiss & Tonella, 2022). TTA agreement is the fraction of the fixed 18 natural transforms whose candidate prediction equals the recorded clean prediction, with lower agreement indicating risk. The reference is the clean prediction from the common re-inference; eligibility remains the historical clean-correct set. Agreement is measured against this fixed clean prediction.

Scores use double-precision probability calculations from single-precision cosine similarities or logits under the common 200-class protocol. All 9,504 evaluation cells reproduce the existing S , U_{18} and TTA_{18} AUROC and recall at $q \in \{0.1, 0.2, 0.3\}$ to within 10^{-10} , with identical sets of cells having undefined metrics. The comparisons use the same cells and tie rules. Table 38 reports the primary mild, $q = 0.2$ results. Group intervals use 2,000 whole-group draws; class intervals use 200 shared class draws. These intervals quantify sensitivity within the existing pool. No score direction, subset or transformation is selected using the new outcomes.

Table 38: Additional simple baselines on mild recaptures. Δ is the original mean recall difference U -baseline at $q = 0.2$; the final two columns give separate 95% group/class resampling intervals for that difference. AUROC is the secondary metric; all three baselines were specified before calculation.

Source	Score	Recall@.2	AUROC	U -score	Group CI	Class CI
ES	U	0.672	0.854	—	—	—
ES	S	0.578	0.778	+0.094	[+0.079,+0.106]	[+0.076,+0.115]
ES	TTA	0.596	0.791	+0.076	[+0.063,+0.086]	[+0.059,+0.088]
ES	Margin	0.577	0.779	+0.096	[+0.079,+0.110]	[+0.073,+0.115]
ES	Entropy	0.574	0.773	+0.098	[+0.079,+0.114]	[+0.081,+0.121]
ES	Agreement	0.423	0.648	+0.249	[+0.208,+0.284]	[+0.212,+0.283]
Diverse	U	0.449	0.801	—	—	—
Diverse	S	0.357	0.678	+0.092	[+0.076,+0.109]	[+0.074,+0.113]
Diverse	TTA	0.366	0.688	+0.083	[+0.066,+0.098]	[+0.066,+0.103]
Diverse	Margin	0.357	0.679	+0.092	[+0.076,+0.107]	[+0.073,+0.113]
Diverse	Entropy	0.355	0.676	+0.094	[+0.077,+0.114]	[+0.076,+0.113]
Diverse	Agreement	0.264	0.558	+0.185	[+0.153,+0.227]	[+0.161,+0.214]

The margin, entropy and agreement controls do not remove the mean advantage in either mild source. Table 39 decomposes the original primary comparisons. Every model-group mean is positive for $U - S$ and $U - TTA_{18}$. At the model level, $U - S$ is positive for all 44 models on both sources; $U - TTA_{18}$ is positive for 43/44 on ES and 44/44 on Diverse. AlexNet is the ES exception (-0.00321 recall); its U -margin difference is also negative (-0.00222). Group means therefore do not establish improvement for every model. No model is excluded for its comparison outcome.

Table 39: Mild-condition recall differences at $q = 0.2$ by the ten fixed model groups, with cells weighted equally within each group. The statistical groups organize the evaluated model pool and have unequal sizes.

Source	Group	Cells	$U - S$	$U - \text{TTA}$
Diverse	SSL	204	+0.085	+0.074
Diverse	DataComp	204	+0.107	+0.093
Diverse	DFN	102	+0.115	+0.091
Diverse	LAION	612	+0.093	+0.091
Diverse	MetaCLIP	153	+0.123	+0.115
Diverse	OpenAI	255	+0.072	+0.064
Diverse	Other CLIP	153	+0.046	+0.028
Diverse	PE-Core	102	+0.109	+0.090
Diverse	SigLIP	204	+0.145	+0.131
Diverse	Supervised	255	+0.053	+0.051
ES	SSL	176	+0.092	+0.089
ES	DataComp	176	+0.087	+0.062
ES	DFN	88	+0.159	+0.119
ES	LAION	528	+0.105	+0.086
ES	MetaCLIP	132	+0.105	+0.099
ES	OpenAI	220	+0.092	+0.066
ES	Other CLIP	132	+0.056	+0.026
ES	PE-Core	88	+0.057	+0.052
ES	SigLIP	176	+0.115	+0.087
ES	Supervised	220	+0.064	+0.062

F INFERENCE, SPLITS, AND THRESHOLD CONVENTIONS

Source overlap and tier counts. Syn and the real pool overlap in 209 images, including 63 Syn-development/real-evaluation overlaps; cross-source image populations are therefore not independent. The development-accuracy tiers contain 44/51 mild, 5/25 severe and 5/86 extreme ES/Diverse conditions. Model-level prediction uses all Syn images or Syn-B development images to predict real evaluation targets.

Inference and scoring. We evaluate models over the candidate classes defined for each dataset, using a common scoring protocol to obtain categorical probabilities. The study thus compares models under a shared scoring convention rather than assessing the native calibration of individual checkpoints. Predicted labels, correctness, true-class probabilities, and maximum predicted probabilities are derived from the same inference outputs.

Preprocessing and reproducibility. Clean and perturbed images undergo the same model-specific preprocessing. Although the original computational environment and preprocessing configurations were not fully documented, repeating the original inference procedure on the same clean and corrupted images exactly reproduced the stored prediction records for all 44 models, as reported in Appendix E. These records and the accompanying experimental documentation provide the basis for the reported analyses. Table 41 identifies the evaluated checkpoints.

Perturbations and data splits. We consider nine synthetic corruption types—brightness, fog, snow, contrast, JPEG compression, pixelation, defocus blur, Gaussian noise, and motion blur—at two severity levels, yielding 18 experimental conditions. Additional higher-severity Syn-B images are excluded from the primary analyses. The development and evaluation sets are stratified by class, with fixed image assignments. Because the original per-image corruption seeds were not retained, exact regeneration of the perturbed images is not guaranteed. The severity levels represent nominal experimental conditions rather than calibrated measures of physical perturbation intensity. Figure 7 illustrates the 18 corruption conditions, representative natural transformations used in Section 5, and mild-condition physical recaptures from ES and Diverse.




Figure 7: Examples of three perturbation families for the same base image. Rows 1–2 show synthetic corruptions used in Syn and Syn-B. Row 3 shows representative natural transformations used for comparison. Row 4 shows original physical recaptures from ImageNet-ES and ES Diverse.

Acceptance and ties. The primary fixed-coverage analysis evaluates risk among the highest-scoring 80% of target samples, with ties resolved to maintain the prescribed sample size. The frozen threshold is the lowest score among the highest-scoring 80% of clean development samples. All scores at or above this threshold are accepted, so ties may increase clean-development coverage beyond the nominal level. Fractional-coverage diagnostics instead average over ties at the acceptance boundary. The supplementary 5% risk rule selects the largest top-ranked subset with empirical error no greater than 5% and accepts all scores at or above its cutoff. Including all cutoff ties can change the empirical risk even on the data used to select the threshold. Neither this rule nor the primary frozen threshold guarantees risk control in deployment.

Consistency across evaluations. The transition, identification, and binary-score analyses use a single, internally consistent set of predictions and probabilities. Full multiclass Brier scores use true-class and collision probabilities from a separate, internally consistent evaluation, available only for Syn and ES; incompatible probabilities from earlier evaluations are not incorporated into these scores. The supplementary clean probability-gap analysis combines gaps from this second evaluation with outcomes from the primary evaluation. Across 484,000 clean prediction records, predicted labels and correctness agree exactly, with small probability differences confined to DINOv3. This agreement does not establish equality of the full probability vectors, and multiclass scores for perturbed inputs remain unavailable for the other sources.

Probability-gap analysis. The probability gap is the difference between the largest and second-largest predicted class probabilities. For each model, we define three groups using the one-third and two-thirds quantiles of the gap distribution among misclassified clean development samples, assigning boundary values to the higher group. A model is excluded from the corresponding analysis when fewer than six such errors are available. These cutpoints are defined relative to clean errors, rather than the overall clean population. The analysis does not control for initial confidence and does not support a causal interpretation.

F.1 ACCEPTANCE PROTOCOLS AND CALIBRATION

Platt scaling (logistic regression on the logit of S) and isotonic regression (Zadrozny & Elkan, 2002) are fitted on clean development records per model and source and applied to both sides. Under the quantile protocol of Section 3.3 (80% clean-development coverage), a strictly increasing calibrator cannot change any acceptance decision; Platt scaling reproduces the raw decisions in all 88 model-source pairs with zero difference, and isotonic steps would only create ties that inflate coverage. Table 40 shows that calibration does change H , L and selective risk under absolute thresholds: at a

threshold of 0.9, H falls by roughly 60% and selective risk from 7.9 to 5.4 points on ES. Whether calibration matters for a rejection rule is therefore decided by the protocol in this setting rather than by the model alone. No calibrator is fitted on the perturbed side.

Table 40: Acceptance events under the quantile protocol (Q80) and absolute-probability thresholds (A_p), for raw and Platt-scaled scores fitted on clean development records (real sources, all conditions, cells weighted equally). H , L and selective risk are expressed as percentages; coverage is the fraction of perturbed inputs accepted. Selective risk is the error rate among accepted perturbed inputs.

Source	Protocol	H		L		Sel. risk		Coverage	
		raw	Platt	raw	Platt	raw	Platt	raw	Platt
ES	Q80	1.39	1.39	9.90	9.90	10.48	10.48	0.531	0.531
ES	A0.9	0.65	0.26	9.48	10.81	7.92	5.44	0.484	0.476
ES	A0.7	2.31	1.82	7.48	6.45	14.03	13.26	0.602	0.608
ES	A0.5	5.39	5.27	4.20	3.26	19.78	20.60	0.703	0.712
Diverse	Q80	2.05	2.05	8.16	8.16	18.95	18.95	0.186	0.186
Diverse	A0.9	1.09	0.34	7.61	8.40	16.54	11.24	0.166	0.153
Diverse	A0.7	3.13	2.17	5.83	5.48	29.21	26.75	0.233	0.226
Diverse	A0.5	6.81	6.23	3.86	3.15	39.88	42.70	0.305	0.304

G MODEL POOL AND EVIDENCE PROVENANCE

ImageNet supplies the classification reference task (Russakovsky et al., 2015). Table 41 lists the evaluated checkpoints. The supervised models use AlexNet (Krizhevsky et al., 2012), ResNet (He et al., 2016), EfficientNet (Tan & Le, 2019), Vision Transformer (Dosovitskiy et al., 2021) and ConvNeXt (Liu et al., 2022) architectures. The self-supervised lineages are MAE (He et al., 2022), DINOv2 (Oquab et al., 2024) and DINOv3 (Siméoni et al., 2026); the identifiers distinguish fine-tuned MAE classifiers from DINO linear classifiers.

The image-text models include OpenAI CLIP (Radford et al., 2021), EVA-CLIP (Sun et al., 2023), Perception Encoder (PE-Core) (Bolya et al., 2025), SigLIP (Zhai et al., 2023), SigLIP 2 (Tschannen et al., 2025), MetaCLIP (Xu et al., 2024), Meta CLIP 2 (Chuang et al., 2025), CLIPA (Li et al., 2023a;b) and CoCa (Yu et al., 2022). Training-data and checkpoint provenance are distinguished from architecture: the pool includes DataComp (Gadre et al., 2023) and Data Filtering Networks (DFN) (Fang et al., 2024) releases, as well as OpenCLIP checkpoints trained on LAION-400M or LAION-2B (Schuhmann et al., 2021; 2022; Cherti et al., 2023). The two RN50 checkpoints labeled `cc12m` and `yfcc15m` are OpenCLIP releases using Conceptual 12M (Changpinyo et al., 2021) and a subset of YFCC100M (Thomee et al., 2016), respectively. OpenCLIP (Ilharco et al., 2021) and timm (Wightman, 2019) provide implementations and pretrained-model registries; their software citations are distinct from the original method and dataset references.

These citations document the model, training and data lineages represented; they do not imply that every evaluated checkpoint reproduces the original paper’s training recipe. Architectural variety does not make the pool a random sample of classifiers or isolate architecture from pretraining, scale, resolution or classifier construction. Model-group holdouts therefore assess transfer within this defined population.

Table 41: Complete model pool with checkpoint identifiers and parameter counts. Groups define the statistical holdouts and may contain checkpoints trained on different datasets.

Model identifier	Group	Params. / M
DINOv2-vitg14-lc__meta	SSL	1144
DINOv3-ViT7B16-lc__meta	SSL	6716
EVA02-L-14__merged2b_s4b_b131k	other-clip	428
MAE-ViT-B-ft__meta	SSL	87
MAE-ViT-L-ft__meta	SSL	304
PE-Core-L-14-336__meta	pe-core	671
PE-Core-bigG-14-448__meta	pe-core	2419

Table 41 (continued).

Model identifier	Group	Params. / M
RN101-quickgelu__openai	openai	120
RN50-quickgelu__cc12m	other-clip	102
RN50-quickgelu__openai	openai	102
RN50-quickgelu__yfcc15m	other-clip	102
ViT-B-16-SigLIP__webli	siglip	203
ViT-B-16-quickgelu__openai	openai	150
ViT-B-16__datacomp_xl_s13b_b90k	datacomp	150
ViT-B-16__dfn2b	dfn	150
ViT-B-16__laion2b_s34b_b88k	laion	150
ViT-B-16__laion400m_e32	laion	150
ViT-B-32-quickgelu__metaclip_fullcc	metaclip	151
ViT-B-32-quickgelu__openai	openai	151
ViT-B-32__datacomp_xl_s13b_b90k	datacomp	151
ViT-B-32__laion2b_s34b_b79k	laion	151
ViT-B-32__laion400m_e32	laion	151
ViT-H-14-CLIPA__datacomp1b	datacomp	968
ViT-H-14-quickgelu__dfn5b	dfn	986
ViT-H-14__laion2b_s32b_b79k	laion	986
ViT-L-14-quickgelu__metaclip_fullcc	metaclip	428
ViT-L-14-quickgelu__openai	openai	428
ViT-L-14__datacomp_xl_s13b_b90k	datacomp	428
ViT-L-14__laion2b_s32b_b82k	laion	428
ViT-L-14__laion400m_e32	laion	428
ViT-SO400M-14-SigLIP__webli	siglip	877
ViT-SO400M-16-SigLIP2-384__webli	siglip	1136
ViT-bigG-14-worldwide-378__metaclip2_worldwide	metaclip	3631
ViT-bigG-14__laion2b_s39b_b160k	laion	2540
ViT-g-14__laion2b_s34b_b88k	laion	1367
ViT-gopt-16-SigLIP2-384__webli	siglip	1872
alexnet-sup__tv	supervised	61
coca_ViT-L-14__laion2b_s13b_b90k	laion	638
convnext-b-sup__timm	supervised	89
convnext_base_w__laion2b_s13b_b82k	laion	179
convnext_large_d_320__laion2b_s29b_b131k_ft_soup	laion	352
efficientnet-b4-sup__timm	supervised	19
resnet50-sup__timm	supervised	26
vit-b16-sup__timm	supervised	87

Model sources and data-access information accompany the supplementary materials.

The stratified split seed is 20260908. Development thresholds and evaluation targets remain separate. Values are usually rounded to two decimals, with three for selected correlations or proportions; rounding does not change the original decision criteria. Whole-group-removal refitting is reported in Appendix I. Human review of recapture semantics and validation on additional models or images remain open directions; Appendix J reports the annotation-sensitivity analyses and planned human review.

H DEFINITIONS AND PREDICTION METHODS

The remaining-degree-of-freedom calculation supplements Section 3. The independent counterparts, feature sets and fitting procedures specify the prediction comparisons in Section 6 and Appendix I.

H.1 THE REMAINING DEGREE OF FREEDOM

The identities in Table 1 and the fact that the five proportions sum to one imply

$$h = a_0 - k, \quad r = a_1 - k, \quad w = F - a_0 - a_1 + 2k, \quad s = 1 - F - k. \quad (13)$$

Once a_0, a_1, F are included, adding four transition proportions introduces algebraic redundancy. We represent the remaining degree of freedom with k . This identity informs the comparison design.

H.2 CONSTRUCTING CLASS-CONDITIONAL INDEPENDENT COUNTERPARTS

Fix a model and condition. For true class y , let n_y be the number of base images, a_y, b_y the clean and perturbed correct counts, and μ_y, μ'_y the mean true-class probabilities among each side's correct images. Independent combination within classes gives

$$dM_{k,\text{ind}} = \frac{\sum_y (a_y b_y / n_y) (\mu_y - \mu'_y)}{\sum_y a_y b_y / n_y}. \quad (14)$$

Classes with zero correct images on either side receive zero weight and need no corresponding mean. This ratio of expected numerator and denominator is neither the difference between the two global correct-image means nor, in general, the expectation of a conditional mean under random permutation, because the denominator can vary. It requires class labels but no observed correspondence.

Each clean image is combined with every perturbed image of the same class, with weight $1/n_y$ per combination, preserving the total image weight. The empirical control instead uniformly samples within-class permutations, including the identity, moving each complete perturbed prediction record. The number of permutations is $\prod_y n_y!$; even two images per class across C classes yield 2^C combinations. Prediction errors are averaged within each model over 20 reproducible permutation replicates before comparison.

H.3 FEATURE SEQUENCE AND COMPARISONS

Table 42 defines the feature sequence used in these comparisons.

Table 42: Feature definitions. L_k^{syn} is the mass of synthetic retained-correct inputs that lose acceptance. All features are aggregated at the model level.

Set / step	Features
B_0	Clean accuracy on synthetic base images and real development base images
B_1	B_0 , synthetic a_1 , mean S on each side, mean M among each side's correct images, perturbed clipped log loss, and target-matched synthetic risk
B_{ind}	B_1 plus independent counterparts of $F, A, Q, k, dM_k, ds_s, ds_w, L_k^{\text{syn}}$
C1	Add F, A, Q to B_1
C2	Add k to C1
C3a	Add dM_k to C2 (primary hypothesis)
C3b	Add ds_s, ds_w to C3a
C4	Add L_k^{syn} to C3b

For preceding features B and current additions q , the total increment compares B with $B + q$. The primary controlled increment compares $B + q_{\text{ind}}$ with $B + q_{\text{ind}} + q$. The dimension-matched shuffle comparison uses $B + q_{\text{shuf}}$ versus $B + q$. Since B may contain preceding paired summaries, the primary sequence is not a comparison against a complete unpaired baseline at every step. C1 against B_{ind} directly probes that more demanding comparison.

For R_{80} and E_τ , B_1 includes the corresponding synthetic protocol quantity. For L_k , it includes only perturbed correct-and-rejected mass. No duplicate is added for a_1 . Clipped log loss is $-\mathbb{E}[\log(\max(M', 10^{-6}))]$. The true-class squared error $(1 - M)^2$ is excluded from the prediction features; it differs from the full multiclass Brier score.

H.4 FITTING, AGGREGATION, AND INTERVALS

The ridge grid is $\{0.1, 0.3, 1, 3, 10, 30, 100\}$. Percentage targets are divided by 100, clipped to $[10^{-4}, 1 - 10^{-4}]$, and transformed by the standard-normal quantile function. Inner selection minimizes MAE after returning to the original scale. Regularization is selected inside the training groups of each outer fold, so that selection optimism does not enter the outer estimate (Cawley & Talbot, 2010). Missing features are imputed using training-column medians, with zero for wholly missing columns. Means and standard deviations are also estimated within training folds. Every feature set uses the same grid and procedure.

Synthetic summaries are computed per condition and averaged equally. Real prediction targets are computed from evaluation-image counts per model and condition, then pooled by source and severity group. Pooling counts is generally different from averaging per-condition risk ratios. The diagnostic figure pools counts across all models; model-level medians are explicitly identified when used. Cross-source analyses use condition-weighted statistics; estimates based on different subsets or aggregation schemes are kept separate.

Group-bootstrap intervals resample groups of stored out-of-fold predictions and average per-model error differences without rerunning the nested fitting procedure. Appendix I separately reports whole-group deletion refits that exclude each designated group from both training and evaluation. These differ from the earlier evaluation-row deletion, which did not remove training groups.

I PREDICTION COMPARISONS AND FULL GROUP-REMOVAL REFITS

Compressing synthetic responses into per-model statistics and predicting mild real a_1, R_{80}, E_τ, L_k across held-out model groups gives target- and baseline-dependent gains. Here, R_{80} denotes the error rate among the highest-scoring 80% of perturbed inputs, using the number of selected inputs as the denominator. Against a baseline containing all class-conditional independent counterparts, simple paired statistics reduce Diverse accuracy MAE by 1.10 points and R_{80} MAE by 0.38. The ES R_{80} gain is not retained against the simpler unpaired baseline, which is better than the augmented baseline on three of four accuracy/risk targets (Tables 43 and 46). Retained-correct confidence dM_k shows no stable incremental benefit across the tested comparisons. The comparisons below include feature-order checks and whole-group refits. These comparisons show why the prediction target matters: gains in image-level screening do not imply stable gains in predicting model-level performance.

I.1 DISTINCT COMPARISONS AND FEATURE ORDER

Baseline B_1 includes clean accuracies, perturbed synthetic accuracy, both sides' confidence, true-class confidence among correct records, log loss, the matching synthetic risk protocol and labeled real development accuracy. For any summary q , its class-conditional independent version combines every clean record with every perturbed record of the same class without observed correspondence; the stronger baseline B_{ind} adds all eight independent counterparts of $F, A, Q, k, dM_k, ds_s, ds_w, L_k$ to B_1 , and Table 43 compares adding (F, A, Q) or dM_k to this baseline. Nested leave-one-group-out ridge regression selects regularization on training groups only, with imputation and scaling within folds; intervals resample ten groups of stored out-of-fold errors 2,000 times and are conditional summaries, not full-pipeline or new-population guarantees (Bengio & Grandvalet, 2004). Across the ten whole-group deletion refits, gains remain positive for Diverse accuracy (0.50–1.55 points) and R_{80} (0.30–1.67), whereas ES R_{80} gains change sign in three deletions; gains below the original practical threshold (10% of the target interquartile range) do not establish zero benefit. For dM_k , the sequential test leaves ES accuracy compatible with improvement (+0.52[−0.43, 2.56]) while the other seven interval upper endpoints fall below their thresholds, and paired and independent versions yield similar synthetic-to-real rank correlations and identical choices on the 38 Syn model pairs tested by the fixed tie-breaking rule.

The analysis includes the original C1 comparison, $B_1 + (F, A, Q)_{\text{ind}}$ versus that baseline plus (F, A, Q) , and the original sequential dM_k comparison after preceding C1 and k features plus $dM_{k,\text{ind}}$. Two further comparisons use the same stronger unpaired baseline: B_{ind} versus $B_{\text{ind}} + (F, A, Q)$, and separately B_{ind} versus $B_{\text{ind}} + dM_k$. The latter assesses feature-order sensitivity using the same model pool and outcomes. Compressed independent features do not exhaust the complete marginal records used in the identification theorem.

Table 43: Syn summaries predicting mild real targets. Baseline is B_{ind} ; changes are MAE reductions in pp, so positive is better. C1 adds (F, A, Q) ; the last column instead adds dM_k alone. Brackets are conditional group-reweighting intervals of stored out-of-fold errors, not full fitting-uncertainty intervals. All sources and deletion refits are in Tables 44 and 45 below.

Target source	Target	Baseline	C1 gain	C1 interval	dM_k gain
ES	a_1	2.88	-0.12	[-0.52, +0.15]	+0.11
ES	R_{80}	3.26	+0.22	[+0.12, +0.32]	+0.24
ES	E_τ	0.61	+0.00	[-0.09, +0.07]	-0.02
ES	L	2.42	-0.06	[-0.15, -0.00]	-0.00
Diverse	a_1	3.35	+1.10	[+0.40, +2.12]	+0.01
Diverse	R_{80}	2.60	+0.38	[-0.22, +1.29]	+0.02
Diverse	E_τ	0.77	-0.02	[-0.20, +0.11]	+0.03
Diverse	L	1.65	+0.03	[-0.00, +0.10]	+0.03

Table 44: All primary source/target settings: model-weighted MAE reductions (pp) with conditional OOF group-reweighting intervals. Original dM_k conditions on the preceding paired summaries and its independent counterpart; $B_{\text{ind}} + dM_k$ is a separate feature-order sensitivity. These are correlated comparisons on the same model pool.

Features	Source	Target	$B_{\text{ind}} + \text{C1}$	Original dM_k	$B_{\text{ind}} + dM_k$
Syn	ES	a_1	-0.12 [-0.52, +0.15]	+0.52 [-0.43, +2.56]	+0.11 [-0.00, +0.27]
Syn	ES	R_{80}	+0.22 [+0.12, +0.32]	+0.05 [-0.07, +0.22]	+0.24 [-0.00, +0.70]
Syn	ES	E_τ	+0.00 [-0.09, +0.07]	-0.04 [-0.11, +0.00]	-0.02 [-0.05, +0.00]
Syn	ES	L	-0.06 [-0.15, -0.00]	-0.55 [-1.88, +0.05]	-0.00 [-0.06, +0.04]
Syn	Diverse	a_1	+1.10 [+0.40, +2.12]	+0.02 [+0.00, +0.05]	+0.01 [-0.19, +0.13]
Syn	Diverse	R_{80}	+0.38 [-0.22, +1.29]	-0.03 [-0.11, +0.01]	+0.02 [-0.04, +0.07]
Syn	Diverse	E_τ	-0.02 [-0.20, +0.11]	-0.01 [-0.15, +0.08]	+0.03 [-0.01, +0.09]
Syn	Diverse	L	+0.03 [-0.00, +0.10]	-0.13 [-0.43, +0.00]	+0.03 [-0.02, +0.06]
Syn-B	ES	a_1	+0.62 [+0.23, +0.96]	+0.01 [-0.03, +0.07]	-0.06 [-0.18, +0.01]
Syn-B	ES	R_{80}	+0.68 [+0.21, +1.03]	+0.00 [-0.03, +0.04]	-0.11 [-0.71, +0.27]
Syn-B	ES	E_τ	-0.29 [-0.90, -0.03]	-0.04 [-0.12, +0.00]	-0.15 [-0.28, -0.04]
Syn-B	ES	L	+0.04 [+0.00, +0.09]	-0.01 [-0.05, +0.05]	+0.00 [-0.01, +0.03]
Syn-B	Diverse	a_1	+0.31 [-0.23, +0.81]	-0.23 [-0.78, +0.00]	+0.06 [-0.01, +0.19]
Syn-B	Diverse	R_{80}	+0.20 [-0.45, +0.75]	-0.04 [-0.08, +0.01]	-0.12 [-0.40, +0.03]
Syn-B	Diverse	E_τ	-0.21 [-0.58, -0.01]	-0.02 [-0.11, +0.03]	-0.24 [-0.60, -0.06]
Syn-B	Diverse	L	-0.12 [-0.26, -0.02]	-0.03 [-0.10, +0.01]	-0.04 [-0.15, +0.01]

I.2 DELETION REFITS AND WEIGHTING

For each of ten removals, the designated group is excluded from both outer evaluation and all training/inner-validation sets. The entire nested fit is then repeated on the remaining nine groups for all 16 source–target combinations. An earlier diagnostic deleted only evaluation records while retaining previously fitted predictions; it therefore does not assess dependence on a group included in training.

Table 45: C1 against B_{ind} : complete-source MAE and the range of MAE reductions after removing each group from both training and evaluation and refitting all inner/outer folds. The deletion range is a sensitivity range, not a confidence interval. Relative gain uses the matched baseline in that row.

Features	Source	Target	Baseline	C1	Gain (%)	Deletion gain (pp)	Positive
Syn	ES	a_1	2.88	3.00	-4.1	[-0.20, +0.19]	6/10
Syn	ES	R_{80}	3.26	3.04	+6.7	[-0.24, +0.34]	7/10
Syn	ES	E_τ	0.61	0.61	+0.0	[-0.01, +0.39]	6/10
Syn	ES	L	2.42	2.48	-2.5	[-0.16, +0.06]	2/10
Syn	Diverse	a_1	3.35	2.25	+33.0	[+0.50, +1.55]	10/10
Syn	Diverse	R_{80}	2.60	2.22	+14.5	[+0.30, +1.67]	10/10
Syn	Diverse	E_τ	0.77	0.80	-2.9	[-0.12, +0.02]	2/10
Syn	Diverse	L	1.65	1.61	+2.1	[-0.10, +0.09]	5/10
Syn-B	ES	a_1	4.12	3.49	+15.2	[-0.35, +0.70]	9/10
Syn-B	ES	R_{80}	3.83	3.15	+17.7	[+0.02, +1.09]	10/10
Syn-B	ES	E_τ	0.78	1.08	-37.3	[-0.31, +0.27]	4/10
Syn-B	ES	L	1.58	1.54	+2.4	[-0.01, +0.30]	9/10
Syn-B	Diverse	a_1	2.09	1.78	+15.0	[+0.08, +1.54]	10/10
Syn-B	Diverse	R_{80}	2.15	1.96	+9.1	[-0.06, +2.02]	8/10
Syn-B	Diverse	E_τ	1.82	2.03	-11.6	[-0.63, +0.53]	4/10
Syn-B	Diverse	L	1.34	1.46	-9.3	[-0.12, +0.21]	3/10

The prediction-error intervals continue to resample stored out-of-fold errors within each fixed fit; they do not repeat training in each bootstrap draw. The deletion experiments (Figure 8) are explicit changes of the training/evaluation population, not a fully refitted bootstrap. The model-equal summary weights each retained model equally; the group-equal summary first averages within each retained group. Inner regularization selection uses model-equal MAE in both cases. Neither treats the ten groups as guaranteed independent model populations. For Syn to Diverse under the stronger baseline, equal-group C1 gains are 1.41[0.67, 2.21] points for accuracy and 0.42[-0.18, 1.12] for R_{80} , compared with equal-model gains of 1.10 and 0.38. This weighting change preserves their respective positive and inconclusive conditional-interval patterns.

The original practical threshold is 0.1 times the full-pool target IQR. Supplementary analyses retain thresholds of 0.025/0.05/0.1/0.2 IQR and 5/10/20% of the matched baseline MAE. These thresholds assess sensitivity to the chosen practical effect size. For example, the Diverse R_{80} original controlled C1 comparison is 4.36 to 2.53 MAE, a 42% reduction, whereas the stronger-baseline comparison is 2.60 to 2.22, about 14.5%. Each relative gain is calculated against its corresponding baseline.




Figure 8: Syn-to-Diverse C1 sensitivity. Diamonds use all 44 models; dots remove one group from both training and evaluation and rerun nested fitting. Current-summary control is $B_1 + (F, A, Q)_{\text{ind}}$; all-summary control is B_{ind} . The dashed line is the original 0.1 IQR criterion. Dots show the individual group-deletion refits.

I.3 COMMON LOST-ACCEPTANCE TARGET

The observed L from the identification analysis and the real L_k used for prediction agree across all 88 model/source targets to 3.55×10^{-15} percentage points after restricting identification to the same mild conditions. On these conditions, mean per-cell L widths are 6.14 to 5.01 for ES and 5.68 to 4.05 for Diverse when overlap is added. These are compatible bounds on each fixed cell; a single common permutation across conditions is not required. The Syn-to-real prediction comparison instead receives source summaries and learns from other model groups' real targets. The contrast therefore connects the same event across two different tasks, without equating bound width with forecast error.

I.4 NUMERICAL VERIFICATION OF PREDICTION COMPARISONS

The analysis comprises 49,280 out-of-fold model predictions, with finite predictions and interval estimates for every planned fit. The full-cohort C1 and sequential dM_k gains agree with the earlier results to within 10^{-8} percentage points. Independent calculations verify training-only preprocessing and nested prediction, including whole-group exclusions; eight independently refitted prediction groups differ by at most 7.11×10^{-15} percentage points. The sensitivity analysis uses the existing model predictions and takes 199.84 seconds on CPU.

I.5 UNPAIRED SYNTHETIC INFORMATION IS A USEFUL STARTING POINT

Adding unpaired synthetic quantities reduces accuracy-prediction MAE by 2.18 percentage points for ES and 3.58 for Diverse; fixed-coverage risk improves by 2.65 and 4.11 points (Table 46). Prediction of accepted-error mass and lost acceptance among retained-correct inputs does not show similarly stable gains. These improvements show the predictive value of unpaired synthetic information for these targets.

Table 46: Unpaired synthetic information versus clean-performance features (Syn; nested prediction across held-out model groups). MAEs and improvements are in percentage points; intervals resample stored out-of-fold errors by model group.

Target	Source	B_0 MAE	B_1 MAE	Gain [95% interval]
a_1	ES	4.87	2.69	+2.18 [+0.68, +4.40]
R_{80}	ES	5.32	2.68	+2.65 [+1.19, +5.01]
a_1	DIV	6.62	3.03	+3.58 [+1.54, +6.87]
R_{80}	DIV	8.07	3.96	+4.11 [+1.59, +8.32]

J ANNOTATION SENSITIVITY AND SHARED PERSISTENT ERRORS

These checks address the label sensitivity discussed in Section 7, covering annotation changes, cross-model error agreement and the status of human recapture review.

J.1 MATCHED REAL EVALUATION AND CANDIDATE COMPATIBILITY

ReaL provides accepted-label sets for original ImageNet images (Beyer et al., 2020). We map the model’s 200-class prediction through its synset to the standard 1,000-class index, retain the original image identifier, and compare original and ReaL correctness on the same evaluation images. Of the shared 500 evaluation images, 473 have nonempty accepted-label sets; 27 are excluded from both sides of this matched comparison. This is distinct from the primary original-label analysis on all 500 images.

Of those 473 images, 435 have at least one accepted label among the 200 candidates and 38 have none. The latter remain in the main matched sensitivity analysis: every available prediction is wrong under their ReaL sets. A separate split gives 424 images whose original label is retained and 49 whose original label is removed. These partitions explain annotation sensitivity; the 435-image subgroup supplements the full matched analysis.

Table 47: Label sensitivity on the same 473 validation images with nonempty ReaL labels; percentages use the matched cohort rather than all 500 images.

Domain	Matched images	Original acc.	ReaL acc.	Δ (pp)	Original s	ReaL s
ES	473	66.88	63.33	-3.55	3.99	8.01
Diverse	473	26.11	24.96	-1.16	1.16	2.77

On the 473-image matched set (Table 47), mean s rises from 3.99% to 8.01% on ES and from 1.16% to 2.77% on Diverse. On the 435-image candidate-compatible subgroup, it falls by 0.37/0.15 points. Using the full matched denominator, target accuracy changes decompose as $-3.55 = +1.04 - 4.59$ points for ES and $-1.16 = +0.67 - 1.83$ for Diverse, where the positive and negative terms come from the 435 and 38 images. These are rounded additive contributions, not semantic judgments about the recaptures.

Let q_{agree} denote the fraction of matched images with unchanged predicted labels. Because multiple accepted labels permit two different correct answers, we split k into k_{equal} and $k_{\text{different}}$ and verify

$$q_{\text{agree}} - a_1 = s - r - k_{\text{different}}. \quad (15)$$

The primary five-state identities and finite bounds retain the original single-label definition. As a sensitivity check, we recompute the states with correctness attached to each record under its own ReaL set, on the 473 images with nonempty sets (Table 48). Relative to original labels, h falls by 2 to 4 points and s roughly doubles; H falls by 6 to 9% and L by about 5%; and dM_k , restricted to k pairs whose original label is in the ReaL set, changes by less than half a point. Between 10% and 18% of original h records and 16% to 19% of original w records change state; 10% of images have an original label absent from their ReaL set. Direct permutation enumeration over all 1,834,272 classes in the 9,504 real cells finds identical L and dM_k endpoints at $\mathcal{I}_k$ and $\mathcal{I}_5$ in every class, with strictly narrower five-state H bounds in 1,708 classes. This tests the algebra under record-attached correctness; it does not re-judge correctness after reassignment, and reusing original-image accepted labels on recaptures remains a sensitivity exercise that does not establish that the captured content is recognizable.

Table 48: Five-state shares and acceptance events under original versus ReaL record-attached correctness (original/ReaL, percentages of the 473 matched images, averaged over models and all conditions). The last two columns give the share of original h and w records that change state under ReaL.

Source	Labels	h	r	k	s	w	H	L	h moved (%)	w moved (%)
ES	original	24.17	1.55	65.33	3.99	4.96	1.40	9.93	–	–
ES	ReaL	22.02	1.30	62.03	8.01	6.64	1.27	9.38	18.4	16.0
Diverse	original	64.00	0.62	25.49	1.16	8.73	2.08	8.31	–	–
Diverse	ReaL	59.65	0.56	24.40	2.77	12.63	1.95	7.87	10.2	18.6

J.2 CROSS-MODEL SUPPORT FOR A CLEAN WRONG ANSWER

On the original-label 500-image evaluation pool, we select images a given model gets wrong when clean and measure how many *other* models predict that same clean wrong answer. We compare exclusion of the evaluated model, exclusion of its whole group, and equal weighting of other groups. Low/high support means agreement at most 0.25/at least 0.75; the middle group contains the remaining values. The outcome is whether the model retains that same wrong answer after perturbation, with each group’s clean-error events as denominator.

Table 49: Persistent same-wrong rate conditional on original-label clean-wrong events among all 500 images, stratified by other-family clean-side consensus (high ≥ 0.75 ; low ≤ 0.25).

Domain	High (%)	Low (%)	High events	Low events
ES	61.45	27.10	16416	79704
Diverse	18.69	6.40	49248	239112

Excluding the evaluated group (Table 49), high/low-support persistent-error rates are 61.45%/27.10% on ES and 18.69%/6.40% on Diverse. These rates weight model–condition–image events; they are neither the unconditional state proportion s nor independent-image probabilities. The association does not control clean confidence and cannot establish an independent effect, a new predictive increment, or label correctness. Shared model errors may also reflect shared biases (Geirhos et al., 2020).

J.3 EXTERNAL ANNOTATIONS AND PENDING HUMAN REVIEW

We match the detailed ImageNet-Mistakes resource by original image and the specific predicted label, not by image alone (Vasudevan et al., 2022). The matching yields 16 distinct model–image–resource combinations across two base images, represented by 32 source-specific matches because ES and Diverse share the clean images. This sparse coverage cannot explain persistent errors across the full pool.

The planned two-reviewer assessment comprises a stratified sample of 200 of the 27,537 events across 18 strata, with inclusion probabilities equal to each stratum’s sample-to-population ratio. Each event specifies a source, condition, base image and persistent wrong answer, and an image may recur across events. The 400 assigned ratings remain unannotated, so human assessment and adjudication results are pending. Reviewers are masked to model identity, consensus and ReaL annotations and evaluate the displayed candidate answer. Estimation will account for unequal inclusion probabilities and repeated images.