

Nearly Tight Rademacher Bounds for Sparsely Activated Neural Networks

Xiaoyu Li¹ Zhizhou Sha² Jiaojiao Jiang¹ Junbin Gao³ Andi Han³

¹University of New South Wales {xiaoyu.li2, jiaojiao.jiang}@unsw.edu.au

²University of Texas at Austin zhizhousha@utexas.edu

³University of Sydney {junbin.gao, andi.han}@sydney.edu.au

Abstract

An input may activate few hidden units even when different inputs collectively use an entire network. We study the statistical complexity of this input-dependent sparsity in the one-hidden-layer ReLU model of [Awasthi et al. \(COLT 2024\)](#). For width s , at most k active units per input, and effective weight and bias bounds W, B , every size- m sample in the class's fixed radius- R input domain satisfies $\mathcal{R}(S) \leq CWR \min\{k, \sqrt{sk/m} \log^{3/2}(2m)\} + kB/\sqrt{m}$. A support-preserving cover and a single normalized chaining argument remove the previous explicit dimension factor, up to logarithms. Lower bounds on appropriate i.i.d. marginals match up to those logarithms, showing how changing active units across inputs retains a width dependence. The input domain matters: zero-bias networks sparse on the entire ball have at most $2k$ nonzero units and complexity $O(kWR/\sqrt{m})$, whereas bias bounds comparable to WR restore the worst-case rate on that same domain in only logarithmic dimension. A spherical-cap construction proves the latter claim without assuming sparsity merely on the sampling support. For a specified normalized bounded loss and biases comparable to WR , we also obtain agnostic minimax excess-risk bounds of order $\min\{1, \sqrt{s/(km)}\}$ up to logarithms.

Keywords: Activation sparsity, Rademacher complexity, metric entropy, neural networks, generalization

1 Introduction

Activation sparsity limits how many hidden units a network uses on an input, while allowing the identities of those units to change across inputs. It limits the number of nonzero contributions without simply reducing the number of available parameters. The statistical question is whether this input-dependent constraint controls a network's capacity uniformly over all admissible activation patterns.

[Awasthi et al. \(2024\)](#), henceforth ADKM, formulated this question for one-hidden-layer ReLU networks. Their model is motivated by sparse hidden activations, but imposes an exact mathematical promise: at most k of the s hidden units are active on every point in a prescribed input set. For bounded weights and inputs, they obtained a Rademacher bound with dependence $\tilde{O}(\sqrt{snk/m})$, where n is the input dimension, and conjectured that the factor $\sqrt{n}$ could be removed (Conjecture 20). The challenge is to retain the sparsity improvement in width while avoiding a count of all halfspace activation patterns.

We establish the dimension-free rate up to $\log^{3/2}(2m)$ and ask when its remaining width dependence is necessary. Our analysis separates three questions: the worst-case capacity of the fixed-domain class, the effect of the domain on admissible activation regions, and the agnostic learning difficulty under a specified loss. The answers distinguish sparse computation on each input from a globally small collection of useful neurons.

1.1 Model and results

Let $n, s, m \geq 1$, $1 \leq k \leq s$, and $W, B, R \geq 0$. Fix a nonempty set $\mathcal{X}_0 \subseteq \{x \in \mathbb{R}^n : \|x\|_2 \leq R\}$ before sampling. Write $\sigma(z) = \max\{z, 0\}$.

Definition 1 (ADKM's class on a fixed input set). The class $\mathcal{H}_{n,s,k}^{W,B}(\mathcal{X}_0)$ consists of restrictions to $\mathcal{X}_0$ of functions

$$h(x) = \sum_{j=1}^s u_j \sigma(\langle w_j, x \rangle - b_j)$$

admitting a representation with

$$\|u\|_\infty \max_j \|w_j\|_2 \leq W, \quad \|u\|_\infty \max_j |b_j| \leq B, \quad \#\{j : \langle w_j, x \rangle > b_j\} \leq k \quad (x \in \mathcal{X}_0).$$

The input set is part of the class definition. Upper bounds hold on every $S = (x_1, \dots, x_m) \in \mathcal{X}_0^m$; a lower-bound construction is allowed to choose $\mathcal{X}_0$ and a distribution on it. Requiring sparsity on a larger set can give a smaller class. No assertion below identifies the support-wide class with a class chosen after seeing a sample.

For independent uniform signs $\zeta_i \in \{-1, 1\}$, define

$$\mathcal{R}_{\mathcal{H}}(S) = \frac{1}{m} \mathbb{E}_\zeta \sup_{h \in \mathcal{H}} \sum_{i=1}^m \zeta_i h(x_i), \quad A = WR, \quad \ell_m = \log(2m), \quad \rho_m = \frac{1}{m} \mathbb{E} \left| \sum_{i=1}^m \zeta_i \right|.$$

All logarithms are natural unless indicated otherwise. The elementary moment bound in Lemma 9 gives $1/\sqrt{3m} \leq \rho_m \leq 1/\sqrt{m}$.

Theorem 2 (Dimension-free upper bound with separated bias). *There is a universal constant $C \geq 1$ such that, for all parameters and input sets above and every $S \in \mathcal{X}_0^m$,*

$$\mathcal{R}_{\mathcal{H}_{n,s,k}^{W,B}(\mathcal{X}_0)}(S) \leq CA \min \left\{ k, \sqrt{\frac{sk}{m}} \ell_m^{3/2} \right\} + kB\rho_m. \quad (1)$$

In addition, $\mathcal{R}_{\mathcal{H}_{n,s,k}^{W,B}(\mathcal{X}_0)}(S) \leq k(A+B)$ and $\mathcal{R}_{\mathcal{H}_{n,s,k}^{W,B}(\mathcal{X}_0)}(S) \leq 2s(A+B)/\sqrt{m}$.

Thus one may always take the smallest of the three upper bounds. The last one is useful in the dense regime $k = s$, where it avoids a logarithmic loss. Dimension-free means that n does not appear separately from R ; on the unnormalized Boolean cube, $R = \sqrt{n}$ still carries a dimension dependence.

Theorem 3 (Lower bound on i.i.d. samples). *Let $q = \min\{\lfloor s/k \rfloor, m\}$ and suppose $n \geq q$. There are a finite input set $\mathcal{X}_0$ in the radius- R ball and a marginal D_x on it such that*

$$\mathbb{E}_{S \sim D_x^m} \mathcal{R}_{\mathcal{H}_{n,s,k}^{W,B}(\mathcal{X}_0)}(S) \geq \frac{1}{4\sqrt{2}} \left(A \min \left\{ k, \sqrt{\frac{sk}{m}} \right\} + \frac{kB}{\sqrt{m}} \right). \quad (2)$$

The same expression lower-bounds the supremum over all admissible input sets and samples.

For $n \geq q$ and $m \geq s/k$, these results determine the worst-case scaling $\tilde{\Theta}(A\sqrt{sk/m} + kB/\sqrt{m})$, with logarithmic slack only in the weight term. For $m \leq s/k$ and sufficiently large n , the weight term saturates at kA . The bounds cover arbitrary s, k, m without divisibility assumptions. They concern class complexity; Theorem 3 alone is not a lower bound on every learning algorithm.

The domain can change the answer. On the entire Euclidean ball, zero-bias k -sparsity forces at most $2k$ nonzero units, giving the smaller rate $\Theta(kA/\sqrt{m})$ in the worst case (Proposition 10). Positive thresholds restore the width dependence: Theorem 12 realizes the lower rate on that same full-ball class, using separated spherical caps in only logarithmic dimension when $B \geq (\sqrt{3}/2)A$. Thus the lower bound need not rely on imposing sparsity only at isolated sampling locations.

A same-loss learning characterization. We derive general bounded-loss guarantees and, separately, prove an agnostic minimax result for the normalized class and a fixed bounded linear loss. Under the explicit dimension and comparable-bias conditions of Theorem 14, its expected excess-risk rate is $\tilde{\Theta}(\min\{1, \sqrt{s/(km)}\})$. This lower bound is established directly in the learning experiment, not inferred from Rademacher complexity. It is not a claim of optimality for every loss or for realizable learning.

Comparison with the original bound. ADKM’s equation (15) has the displayed dependence $(WR + B)\sqrt{snk \log(km(R + B))}/\sqrt{m}$ in its parameter regime. Their conjectured dependence is $(WR + B)\sqrt{sk/m}$. Equation (1) removes the explicit $\sqrt{n}$ at a logarithmic cost and improves the bias coefficient from $\sqrt{sk}$ to k . The logarithm-free form of their conjecture remains unresolved here. Bounds based only on the sum of the individual neuron complexities give $O(s(A + B)/\sqrt{m})$; the point is to combine norm control with the shared activation budget.

1.2 Technique overview

The upper bound uses the total activation budget without fixing an activation pattern. The lower bounds then ask how many independently signed neuron clusters that budget permits, first on a discrete domain and then on the entire ball.

From a network to one normalized neuron process. By positive homogeneity, absorb each outer weight’s magnitude into its neuron, leaving an outer sign and parameters $\|v_j\|_2 \leq W$, $|\beta_j| \leq B$. If I_j is its active sample set, double-counting gives $\sum_j |I_j| \leq km$. Let $\mathcal{F}_t$ be the sample-output vectors of one neuron active on at most t coordinates, and put $Q = \max_{1 \leq t \leq m} t^{-1/2} \sup_{f \in \mathcal{F}_t} |\langle \zeta, f \rangle|$. Then

$$\sum_j \left| \sum_i \zeta_i \sigma(\langle v_j, x_i \rangle - \beta_j) \right| \leq Q \sum_j \sqrt{|I_j|} \leq Q \sqrt{skm}.$$

Inactive units contribute zero. After division by m and averaging, Lemma 4 bounds the network complexity by $\sqrt{sk/m} \mathbb{E}Q$. The displayed inequality holds for each sign vector: it does not require choosing the active sets before observing the signs. The remaining task is to control all activation counts simultaneously.

A cover that preserves inactive coordinates. A direct affine approximation followed by ReLU can turn zero coordinates into small positive ones, losing the sparse support in its Euclidean error. We instead shift every approximating pre-activation downward. If $\|g - \widehat{g}\|_\infty \leq \delta$, then $\widehat{f} = \sigma(\widehat{g} - \delta)$ vanishes wherever $f = \sigma(g)$ vanishes and differs from f by at most 2δ elsewhere. Hence $\|f - \widehat{f}\|_2 \leq 2\delta\sqrt{t}$ for $f \in \mathcal{F}_t$. Applying this transformation to a dimension-free affine cover gives Lemma 5, without counting halfspace activation patterns. The centers are allowed outside the parameter-constrained class; only their approximation error matters.

One chain, rather than separate bounds at each count. Normalize $\mathcal{F}_t$ by $\sqrt{t}$ and take the symmetric union

$$T = \bigcup_{t=1}^m \left(t^{-1/2} \mathcal{F}_t \cup -t^{-1/2} \mathcal{F}_t \right), \quad Q = \sup_{z \in T} \langle \zeta, z \rangle.$$

The normalization removes t from the cover’s scale-dependent entropy; selecting a member of the union costs only an additive $\log(2m)$. A single finite chaining argument therefore bounds the expectation of the maximum itself, without interchanging maximum and expectation. Truncating the chain at radius at most $(A + B)/\sqrt{m}$ controls its residual by $A + B$. The affine entropy contributes $\sqrt{\log(2m)}$, and summing over scales contributes another logarithm, giving $\mathbb{E}Q = O((A + B) \log^{3/2}(2m))$. This identifies the remaining logarithmic loss: removing the lower-order union cost alone would not remove it.

Clipping thresholds separates the constant part. The preceding argument initially charges both A and B at the network rate. To refine it, clip β to $\beta^\circ \in [-A, A]$ and use the identity

$$\sigma(\langle v, x \rangle - \beta) = \sigma(\langle v, x \rangle - \beta^\circ) + (-\beta - A)_+ \quad (\|x\|_2 \leq R).$$

Clipping creates no new activation. Every nonzero constant correction comes from a unit previously active everywhere, so at most k corrections occur. Thus $h = h_0 + c$, with clipped bias bound $\min\{A, B\}$ and $|c| \leq k(B - A)_+$ (Lemma 8). Applying the chain and the envelope bound to h_0 , and the exact constant-class complexity to c , yields Theorem 2.

Independent clusters and the geometry of the domain. For the discrete lower bound, use $q = \min\{\lfloor s/k \rfloor, m\}$ orthogonal input directions and k parallel neurons per direction. Each cluster carries its own sign. Under uniform i.i.d. sampling, its signed occupancy has absolute expectation of order $\sqrt{m/q}$, giving the weight lower bound without balanced-count or divisibility assumptions. The separate constant subclass supplies the bias term. On the full ball, however, a generic antipodal pair counts every nonzero zero-bias neuron, forcing at most $2k$ in total. To recover independent clusters there, we use disjoint spherical caps. Directions with pairwise inner product at most $1/2$, together with threshold τA for $\tau = \sqrt{3}/2$, prevent two clusters from activating at any point of the ball. A random-sign packing supplies the directions in $O(\log(2q))$ dimensions. When $B \geq \tau A$, each cap center still has output amplitude $(1 - \tau)kA$, so the same occupancy argument applies (Theorem 12).

Turning sign encoding into a learning lower bound. A complexity lower bound alone does not establish learning hardness. Under the conditions of Theorem 14, normalization by $k(A + B)$ makes the cap construction’s sign amplitude a positive universal constant. Assign binary labels small unknown means $\delta\theta_b$ at the q cap centers. Adjacent sign choices have joint-sample KL divergence at most $O(m\delta^2/q)$. Choosing δ as a sufficiently small constant times $\sqrt{q/m}$ keeps adjacent distributions hard to distinguish. Total variation then limits any learner’s correlation with the signs, including randomized and improper learners. For the specified bounded linear loss, this gives an expected excess-risk lower bound of order $\sqrt{q/m}$. Approximate ERM and the complexity upper bound give the corresponding upper rate for that same loss and normalized class; Appendix B supplies the testing calculation.

1.3 Related work

Our comparison uses the support-wide class and product norms of Awasthi et al. (2024). Their expressivity and computational results are distinct from the capacity question studied here. Norm-based analyses such as

Neyshabur et al. (2015); Golowich et al. (2018) control complexity without imposing this activation promise. We use an elementary neuronwise bound as the dimension-free baseline rather than asserting that all such norm-based results have identical specializations.

Other sparsity notions lead to different guarantees. Galanti et al. (2023) study compositionally sparse networks, in which each neuron has a limited number of inputs. Muthukumar and Sulam (2023) use activation stability and sensitivity analysis to obtain predictor-dependent, derandomized PAC-Bayes guarantees across multiple layers. Our result is a uniform complexity bound for an entire one-layer class with a fixed activation promise; it does not require stability under parameter perturbations.

Scale-sensitive covers of norm-constrained linear classes have a long history (Zhang, 2002). The affine cover used here is an application of dual Sudakov (Pajor and Tomczak-Jaegermann, 1986; Ledoux and Talagrand, 1991); the chain uses the familiar multiscale principle of Dudley (1967). The contribution of the covering step is its compatibility with sparse supports. We include the finite chaining argument and a proof of the required geometric covering estimate so that the proof interfaces can be checked directly.

2 A dimension-free upper bound

We first prove the bound with scale $M = A + B$. We then separate the contribution of large biases. Vectors of sample evaluations use the unnormalized Euclidean norm in $\mathbb{R}^m$. The covering number $N(T, \epsilon, \|\cdot\|)$ permits centers in the ambient vector space; all covers used below are finite and deterministic once the sample is fixed.

2.1 Reduction and the activation budget

Positive homogeneity gives the exact reduced representation

$$h(x) = \sum_{j=1}^s \varepsilon_j \sigma(\langle v_j, x \rangle - \beta_j), \quad \varepsilon_j \in \{-1, 1\}, \quad \|v_j\|_2 \leq W, \quad |\beta_j| \leq B. \quad (3)$$

For $u_j \neq 0$, take $v_j = |u_j|w_j$, $\beta_j = |u_j|b_j$, and $\varepsilon_j = \text{sign}(u_j)$. For $u_j = 0$, take $v_j = 0$, $\beta_j = 0$ and $\varepsilon_j = 1$; this only decreases the activation count. Conversely, (3) is realized in Definition 1 by $u_j = \varepsilon_j$, $w_j = v_j$, and $b_j = \beta_j$. Sparsity does not depend on the outer signs.

For $t \in [m]$, let

$$\mathcal{F}_t = \{(\sigma(\langle v, x_i \rangle - \beta))_{i=1}^m : \|v\|_2 \leq W, |\beta| \leq B, \#\{i : \langle v, x_i \rangle > \beta\} \leq t\},$$

and set $P(t) = \sup_{f \in \mathcal{F}_t} |\langle \zeta, f \rangle|$ and $Q = \max_{t \in [m]} P(t)/\sqrt{t}$. Each $f \in \mathcal{F}_t$ has entries in $[0, M]$ and satisfies $\|f\|_2 \leq M\sqrt{t}$.

Lemma 4 (Sample relaxation and budget). *For every $S \in \mathcal{X}_0^m$,*

$$\mathcal{R}_{\mathcal{H}_{n,s,k}^{W,B}(\mathcal{X}_0)}(S) \leq \sqrt{\frac{sk}{m}} \mathbb{E}_{\zeta} Q. \quad (4)$$

Proof. Enlarge the reduced parameter set by requiring sparsity only on S . For fixed parameters, maximizing over the outer signs yields $\sum_j |N_j|$, where $N_j = \sum_i \zeta_i \sigma(\langle v_j, x_i \rangle - \beta_j)$. Let $t_j = \#\{i : \langle v_j, x_i \rangle > \beta_j\}$. A unit with $t_j = 0$ contributes zero; otherwise $|N_j| \leq Q\sqrt{t_j}$. Double-counting active sample-unit pairs gives $\sum_j t_j \leq km$. Therefore, for every sign vector and admissible configuration,

$$\sum_j |N_j| \leq Q \sum_j \sqrt{t_j} \leq Q \sqrt{s \sum_j t_j} \leq Q\sqrt{skm}.$$

Take the supremum, divide by m , and average over the signs. $\square$

2.2 Covering sparse outputs

The affine evaluation class $\mathcal{A} = \{(\langle v, x_i \rangle - \beta)_i : \|v\|_2 \leq W, |\beta| \leq B\}$ obeys

$$\log N(\mathcal{A}, \delta, \|\cdot\|_\infty) \leq 80 \frac{A^2 \log(2m)}{\delta^2} + \log(1 + 4B/\delta), \quad \delta > 0. \quad (5)$$

For completeness, Lemma 15 proves this estimate using a Gaussian packing argument. Restricting to $\text{span}\{x_i\}$ deals with the fact that $\max_i |\langle v, x_i \rangle|$ need only be a seminorm on the original space.

Lemma 5 (Shifted cover). *For $t \in [m]$ and $\epsilon > 0$,*

$$\log N(\mathcal{F}_t, \epsilon, \|\cdot\|_2) \leq 320 \frac{A^2 t \log(2m)}{\epsilon^2} + \log(1 + 8B\sqrt{t}/\epsilon). \quad (6)$$

Proof. Put $\delta = \epsilon/(2\sqrt{t})$ and cover $\mathcal{A}$ in sup norm at radius δ . For $f = \sigma(g) \in \mathcal{F}_t$, choose a center $\widehat{g}$ with $\|g - \widehat{g}\|_\infty \leq \delta$ and use $\widehat{f} = \sigma(\widehat{g} - \delta)$. If $g_i \leq 0$, then $\widehat{g}_i - \delta \leq 0$, so $f_i = \widehat{f}_i = 0$. On the other coordinates, the 1-Lipschitz property of ReLU gives $|f_i - \widehat{f}_i| \leq 2\delta$. Thus $\|f - \widehat{f}\|_2 \leq 2\delta\sqrt{t} = \epsilon$. The transformed cover has no more centers than the affine cover; substituting δ in (5) proves the claim. The centers need not satisfy the bias constraint, which is why we use external covers. $\square$

2.3 One chain over all normalized scales

Define the symmetric set

$$T = \bigcup_{t=1}^m \left(t^{-1/2} \mathcal{F}_t \cup -t^{-1/2} \mathcal{F}_t \right).$$

It contains 0, has radius at most M , and satisfies $Q = \sup_{z \in T} \langle \zeta, z \rangle$. By scaling Lemma 5 and taking the union of $2m$ covers, we get the uniform estimate

$$\log N(T, \epsilon, \|\cdot\|_2) \leq \ell_m + 320 \frac{A^2 \ell_m}{\epsilon^2} + \log(1 + 8B/\epsilon). \quad (7)$$

The entropy cost of selecting an activation count is only $\log(2m)$, separate from the ϵ^{-2} term. No comparison of the expectations of different $P(t)$ is needed.

Lemma 6 (Finite Rademacher chaining). *Let $T \subseteq \mathbb{R}^m$ have radius at most $D > 0$ and put $r_j = D2^{-j}$. For an integer $J \geq 1$, suppose external r_j -nets exist with cardinalities N_j and $\log N_j \leq H_j$, where $0 \leq H_1 \leq \dots \leq H_J$. Then*

$$\mathbb{E} \sup_{z \in T} \langle \zeta, z \rangle \leq \sqrt{m} r_J + 6 \sum_{j=1}^J r_j \sqrt{H_j}. \quad (8)$$

Proof. Choose deterministic net maps π_j with $\|z - \pi_j z\|_2 \leq r_j$ and set $\pi_0 z = 0$, $N_0 = 1$. The edge set $E_j = \{\pi_j z - \pi_{j-1} z : z \in T\}$ has at most $N_j N_{j-1}$ elements, each with norm at most $r_j + r_{j-1} = 3r_j$. For every deterministic vector a ,

$$\mathbb{E} e^{\lambda \langle \zeta, a \rangle} = \prod_i \cosh(\lambda a_i) \leq e^{\lambda^2 \|a\|_2^2 / 2}.$$

The exponential-moment maximal inequality therefore gives

$$\mathbb{E} \max_{a \in E_j} \langle \zeta, a \rangle \leq 3r_j \sqrt{2 \log(N_j N_{j-1})} \leq 6r_j \sqrt{H_j}.$$

If the edge set is a singleton, its expected maximum is zero, so the same inequality applies. Telescope from 0 to $\pi_J z$ and use $\langle \zeta, z - \pi_J z \rangle \leq \sqrt{m} r_J$ for the residual. Taking the supremum and expectation proves (8). The process is defined at every point of $\mathbb{R}^m$, so external centers cause no change to the argument. $\square$

Proposition 7 (Unseparated bound). *There is a universal constant $C_0 \geq 1$ such that*

$$\mathbb{E}Q \leq C_0 M \ell_m^{3/2}, \quad \mathcal{R}_{\mathcal{H}_{n,s,k}^{W,B}(\mathcal{X}_0)}(S) \leq C_0 M \sqrt{sk/m} \ell_m^{3/2}.$$

Proof. If $M = 0$, both quantities vanish. Otherwise use Lemma 6 with $D = M$ and $J = \max\{1, \lceil \log_2 \sqrt{m} \rceil\}$. Then $\sqrt{m} r_J \leq M$ and $J \leq \ell_m / \log 2$. Since $B \leq M$, (7) permits

$$H_j = \ell_m + 320A^2 \ell_m / r_j^2 + (j+4) \log 2.$$

Subadditivity of the square root, $\sum_{j \geq 1} 2^{-j} = 1$, and $\sum_{j \geq 1} 2^{-j} \sqrt{j+4} \leq \sum_{j \geq 1} 2^{-j} (j+4) = 6$ give

$$\begin{aligned} \mathbb{E}Q &\leq M + 6M\sqrt{\ell_m} + 6\sqrt{320}A\sqrt{\ell_m}J + 36M\sqrt{\log 2} \\ &\leq C_0 M \ell_m^{3/2}. \end{aligned}$$

For example, one may take

$$C_0 = \frac{6\sqrt{320} + 6}{\log 2} + \frac{1 + 36\sqrt{\log 2}}{(\log 2)^{3/2}}.$$

The comparison uses only $A \leq M$ and $\ell_m \geq \log 2$, including $m = 1$. Lemma 4 yields the network bound. $\square$

2.4 Large biases contribute constants

Lemma 8 (Bias clipping). *Put $b_0 = \min\{B, A\}$ and $d = (B - A)_+$. Every $h \in \mathcal{H}_{n,s,k}^{W,B}(\mathcal{X}_0)$ can be written on $\mathcal{X}_0$ as $h = h_0 + c$, where*

$$h_0 \in \mathcal{H}_{n,s,k}^{W,b_0}(\mathcal{X}_0), \quad |c| \leq kd.$$

Proof. Use (3) and clip each β_j to $[-A, A]$. For $a \in [-A, A]$ and every $\beta \in \mathbb{R}$, the three cases $\beta < -A$, $-A \leq \beta \leq A$, and $\beta > A$ give

$$\sigma(a - \beta) = \sigma(a - \beta^\circ) + (-\beta - A)_+, \quad \beta^\circ = \max\{-A, \min\{\beta, A\}\}. \quad (9)$$

Clipping creates no active unit at any input in the ball. A unit with $\beta < -A$ was strictly active everywhere before clipping, and a unit with $\beta > A$ stays inactive. Hence $h_0 = \sum_j \varepsilon_j \sigma(\langle v_j, x \rangle - \beta_j^\circ)$ belongs to the stated class. Every nonzero summand of $c = \sum_j \varepsilon_j (-\beta_j - A)_+$ comes from a unit active everywhere. Because $\mathcal{X}_0$ is nonempty, there can be at most k such units, each contributing at most d in absolute value. $\square$

2.5 Proof of Theorem 2

Proof. The complexity of constants in $[-kd, kd]$ is $kd\rho_m$. Subadditivity and Lemma 8 give the slightly sharper intermediate bound

$$\mathcal{R}_{\mathcal{H}_{n,s,k}^{W,B}(\mathcal{X}_0)}(S) \leq (A + b_0) \min\{k, C_0 \sqrt{sk/m} \ell_m^{3/2}\} + kd\rho_m. \quad (10)$$

Here the two estimates for the clipped class are its pointwise envelope and Proposition 7. Using $A + b_0 \leq 2A$, $d \leq B$, and $C_0 \geq 1$ proves (1) with $C = 2C_0$. This also covers $A = 0$: the clipped class is then zero and the original class consists exactly of constants in $[-kB, kB]$.

The original envelope is $|h(x)| \leq kM$, proving the first additional bound. For the second, ignore sparsity and bound each signed neuron separately. Since the unsigned neuron class contains zero, sign symmetry and scalar contraction imply

$$\mathbb{E} \sup_{\|v\| \leq W, |\beta| \leq B} \left| \sum_i \zeta_i \sigma(\langle v, x_i \rangle - \beta) \right| \leq 2 \left(W \mathbb{E} \left\| \sum_i \zeta_i x_i \right\|_2 + B \mathbb{E} \left| \sum_i \zeta_i \right| \right) \leq 2M\sqrt{m}.$$

Summing over s neurons proves $2sM/\sqrt{m}$. $\square$

3 Lower bounds on the same class

The lower bound uses parallel neurons within each cluster and orthogonal directions between clusters. Parallelism allows k units to each attain value A on a single input while respecting the radius constraint. Orthogonality makes the output values of different clusters independent parameters on the constructed support.

Lemma 9 (A moment estimate). *If Z has finite fourth moment and $\mathbb{E}Z^2 > 0$, then*

$$\mathbb{E}|Z| \geq \frac{(\mathbb{E}Z^2)^{3/2}}{(\mathbb{E}Z^4)^{1/2}}.$$

In particular, $\mathbb{E}|\sum_{i=1}^m \zeta_i| \geq \sqrt{m/3}$.

Proof. Hölder applied to $|Z|^2 = |Z|^{2/3}|Z|^{4/3}$ gives $\mathbb{E}Z^2 \leq (\mathbb{E}|Z|)^{2/3}(\mathbb{E}|Z|^4)^{1/3}$. For the sign sum, $\mathbb{E}Z^2 = m$ and $\mathbb{E}Z^4 = 3m^2 - 2m \leq 3m^2$. $\square$

3.1 Proof of Theorem 3

Proof. First suppose $A > 0$. Choose orthonormal vectors $e_1, \dots, e_q \in \mathbb{R}^n$ and let D_x be uniform on $\mathcal{X}_0 = \{Re_1, \dots, Re_q\}$. Use q clusters of k neurons each, with weight We_b and zero bias in cluster b . There are at most s neurons; pad with inactive zero units when necessary. On Re_b , only cluster b is active. Choosing a common outer sign $\theta_b \in \{-1, 1\}$ in that cluster realizes $h_\theta(Re_b) = kA\theta_b$.

Write $X_i = Re_{J_i}$, where the J_i are i.i.d. uniform on $[q]$ and independent of the Rademacher signs. For each realized sample, optimizing over the cluster signs gives

$$\mathcal{R}_{\mathcal{H}_{n,s,k}^{W,B}(\mathcal{X}_0)}(S) \geq \frac{kA}{m} \sum_{b=1}^q \mathbb{E}_\zeta \left| \sum_{i=1}^m \zeta_i \mathbf{1}\{J_i = b\} \right|. \quad (11)$$

For a fixed b , set $Z_b = \sum_i \zeta_i \mathbf{1}\{J_i = b\}$ and $\lambda = m/q \geq 1$. Independence and centering give

$$\mathbb{E}Z_b^2 = \lambda, \quad \mathbb{E}Z_b^4 = \frac{m}{q} + \frac{3m(m-1)}{q^2} \leq \lambda + 3\lambda^2 \leq 4\lambda^2.$$

Lemma 9, followed by (11), yields

$$\mathbb{E}_S \mathcal{R}_{\mathcal{H}_{n,s,k}^{W,B}(\mathcal{X}_0)}(S) \geq \frac{kA}{2} \sqrt{q/m} \geq \frac{A}{2\sqrt{2}} \min\{k, \sqrt{sk/m}\}. \quad (12)$$

For the last step, $\lfloor s/k \rfloor \geq s/(2k)$ since $s/k \geq 1$, and hence $q \geq \frac{1}{2} \min\{s/k, m\}$.

The same class on the same support also contains the two constants $\pm kB$: use k zero-weight units with bias $-B$ and a common outer sign. Thus for every sample,

$$\mathcal{R}_{\mathcal{H}_{n,s,k}^{W,B}(X_0)}(S) \geq kB\rho_m \geq \frac{kB}{\sqrt{3m}}. \quad (13)$$

The two constructions are alternative subclasses; they need not fit simultaneously into one network. Taking the larger of (12) and (13) and using $\max\{a, b\} \geq (a + b)/2$ proves (2). If $A = 0$, take $X_0 = \{0\}$ and use only the constant subclass; the weight term is zero. Finally, a supremum over samples is at least their expectation under this marginal. $\square$

Interpretation of the regimes. When $m \leq s/k$, we may use one cluster per sample-sized support point; random repetitions only change constants in the lower bound. When $m \geq s/k$, the $\lfloor s/k \rfloor$ clusters are repeatedly observed and their signed sums have square-root fluctuations. The bias subclass has just one freely chosen sign, giving $m^{-1/2}$ decay independently of the number of available clusters. This explains the distinct width dependence in the upper bound. The dimensional condition is used to supply orthogonal cluster directions; it is not an assumption of Theorem 2, and no claim of sharpness for every smaller fixed dimension is made.

4 When does sparsity remove the width dependence?

The lower bound in Section 3 allows different neuron clusters to act independently on a discrete input set. Does its width dependence survive if sparsity is required throughout a full-dimensional convex domain? The answer depends on whether activation thresholds are available. Write $\mathbb{B}_R^n = \{x \in \mathbb{R}^n : \|x\|_2 \leq R\}$ and suppose $R > 0$ throughout this section.

Proposition 10 (Zero-threshold width collapse). *Every zero-bias network that is k -sparse on $\mathbb{B}_R^n$ has a reduced representation with at most $\min\{s, 2k\}$ nonzero units. Consequently, for every $S \in (\mathbb{B}_R^n)^m$,*

$$\mathcal{R}_{\mathcal{H}_{n,s,k}^{W,0}(\mathbb{B}_R^n)}(S) \leq \frac{4kA}{\sqrt{m}}.$$

The supremum over such samples is at least $kA\rho_m$, so its order is $kA/\sqrt{m}$.

Proof. Use the reduced parameters in (3) and discard $v_j = 0$ units. Choose a unit direction outside the finitely many hyperplanes $\langle v_j, x \rangle = 0$. Each remaining unit is strictly active at exactly one of the two antipodal radius- R points. Both points lie in the required input domain, so the number of remaining units is at most $2k$. The neuronwise estimate in Theorem 2 then gives the upper bound. For the lower bound, repeat Re_1 and use k parallel units with weight We_1 and a common outer sign. These networks are globally k -sparse and take values $\pm kA$ on the sample. The case $W = 0$ is immediate. $\square$

Central symmetry alone is insufficient. On the finite set $\{\pm Re_b : b \in [q]\}$, the zero-bias clusters from Section 3 remain admissible: most units can vanish on a given antipodal pair. The full-ball argument uses a pair that avoids every nonzero neuron's zero hyperplane simultaneously.

For a polytope $X_0 = \text{conv}(V)$ with finitely many vertices, a related count holds even with biases. Every unit active somewhere is active at a vertex, since an affine function attains its maximum there. Hence at most $k|V|$ units are nonzero on the domain, giving the neuronwise bound $2k|V|(A + B)/\sqrt{m}$. In particular, on an interval ($n = 1$), the width dependence disappears for every bias bound, not only for $B = 0$.

Positive thresholds can instead isolate disjoint caps of the ball. Set

$$\tau = \frac{\sqrt{3}}{2}, \quad d_q = \min\{q, \lceil 16 \log(2q) \rceil\}.$$

The following elementary packing suffices; we do not need sharp spherical-code bounds.

Lemma 11 (Separated directions). *If $n \geq d_q$, there are unit vectors $u_1, \dots, u_q \in \mathbb{R}^n$ with $\langle u_b, u_c \rangle \leq 1/2$ for $b \neq c$.*

Proof. If $n \geq q$, take orthogonal vectors. Otherwise $n \geq 16 \log(2q)$. Take independent vectors uniform on $\{\pm n^{-1/2}\}^n$. For a fixed pair, their inner product has the law of $n^{-1} \sum_{r=1}^n \xi_r$ for independent uniform signs. The bound $\mathbb{E} e^{\lambda \sum_r \xi_r} \leq e^{n\lambda^2/2}$ gives $\mathbb{P}[\langle u_b, u_c \rangle > 1/2] \leq e^{-n/8}$. A union bound over pairs has probability at most $q(q-1)e^{-n/8}/2 < 1$. Thus a configuration with the required separation exists. $\square$

Theorem 12 (A full-ball lower bound in logarithmic dimension). *Let $q = \min\{\lfloor s/k \rfloor, m\}$ and suppose $n \geq d_q$. Put $a = \min\{A, B/\tau\}$. There is a fixed marginal D_x on $\mathbb{B}_R^n$ such that*

$$\mathbb{E}_{S \sim D_x^m} \mathcal{R}_{\mathcal{H}_{n,s,k}^{W,B}(\mathbb{B}_R^n)}(S) \geq c_{\text{cap}} \left(a \min\{k, \sqrt{sk/m}\} + \frac{kB}{\sqrt{m}} \right), \quad c_{\text{cap}} = \frac{1-\tau}{4\sqrt{2}}. \quad (14)$$

In particular, if $B \geq \tau A$, the rate of Theorem 3 holds for the full-ball class itself, with only $O(\log(2q))$ dimensions sufficient.

Proof. Choose directions from Lemma 11 and put D_x uniform on $\{Ru_1, \dots, Ru_q\}$. Suppose first that $a > 0$. In cluster b , place k copies of the unit

$$v_b = (a/R)u_b, \quad \beta_b = \tau a,$$

with a common outer sign θ_b . These parameters obey the norm and bias bounds. If two distinct clusters were active at an input $x \in \mathbb{B}_R^n$, then

$$\langle u_b + u_c, x \rangle > 2\tau R, \quad \|u_b + u_c\|_2^2 = 2 + 2\langle u_b, u_c \rangle \leq 3 = 4\tau^2,$$

contradicting Cauchy–Schwarz. Thus the network is k -sparse at *every* point of the ball, not only at the sampling locations. At Ru_b , its value is $ka(1-\tau)\theta_b$; all other clusters are inactive because $1/2 < \tau$. Pad with inactive units to width s .

The moment calculation in (12), with amplitude $a(1-\tau)$ replacing A , now gives a lower bound of $a(1-\tau) \min\{k, \sqrt{sk/m}\}/(2\sqrt{2})$. The same full-ball class contains the constants $\pm kB$, contributing $kB\rho_m$. Taking the larger of these two subclass bounds proves (14). If $a = 0$, the constant subclass alone proves the assertion. $\square$

What changes between the regimes? The zero-bias proposition turns pointwise sparsity into a global bound on the number of useful units. The cap construction defeats that implication by assigning different clusters disjoint activation regions. It also shows that a finite-support marginal does not require a function class whose sparsity promise is restricted to that finite support. For $m \geq s/k$, the comparison is summarized in Table 1. The value τA is sufficient for the construction, not a proved critical threshold.

The logarithmic dimension order is necessary for constant-amplitude sign encoding. Indeed, every full-ball network is kW -Lipschitz: along any segment, the finitely many affine pieces have gradients bounded by kW . When $A + B > 0$, normalization by $k(A + B)$ gives a function that is at most $1/R$ -Lipschitz. If all signs on q inputs can be realized at amplitude $\alpha > 0$, each pair of inputs must be at distance at least $2\alpha R$. Disjoint open balls of radius αR around them lie inside the ball of radius $(1 + \alpha)R$, so volume comparison gives $q \leq (1 + 1/\alpha)^n$. This proves an $\Omega(\log q)$ requirement when α is constant; it is a statement about this encoding, not a necessary dimension condition for every complexity lower bound.

Table 1: Worst-case empirical complexity; $g = \lfloor s/k \rfloor$ and $m \geq s/k$. The lower bounds also hold in expectation for an appropriate i.i.d. marginal. $\tilde{\Theta}$ permits logarithms in m ; the middle row has none.

Sparsity domain and bias	Dimension	Complexity
Finite set, $B = 0$	$n \geq g$	$\tilde{\Theta}(A\sqrt{sk/m})$
Entire ball, $B = 0$	$n \geq 1$	$\Theta(kA/\sqrt{m})$
Entire ball, $B \geq \tau A$	$n \geq d_g$	$\tilde{\Theta}(A\sqrt{sk/m} + kB/\sqrt{m})$

5 Learning consequences

Fix the class $\mathcal{H} = \mathcal{H}_{n,s,k}^{W,B}(\mathcal{X}_0)$ before drawing data. In this section $\mathcal{X}_0$ is Borel, D is a probability distribution on $\mathcal{X}_0 \times \mathbb{R}$, and the loss $\ell : \mathbb{R} \times \mathbb{R} \rightarrow [0, b_\ell]$ is jointly Borel measurable and L -Lipschitz in its first argument. Write $\mathcal{L}_D(h) = \mathbb{E}\ell(h(X), Y)$ and $\hat{\mathcal{L}}_S(h) = m^{-1} \sum_i \ell(h(X_i), Y_i)$. Put

$$U_m = \min \left\{ k(A+B), \frac{2s(A+B)}{\sqrt{m}}, CA \min\{k, \sqrt{sk/m} \ell_m^{3/2}\} + kB\rho_m \right\}. \quad (15)$$

This is a deterministic upper bound on the empirical and expected complexity of the fixed class, for every admissible marginal.

Corollary 13 (Agnostic and realizable guarantees). *For any $\eta > 0$, there exists a measurable η -approximate empirical risk minimizer $\hat{h} \in \mathcal{H}$. For every $\delta \in (0, 1)$, with probability at least $1 - \delta$ over $S \sim D^m$ it satisfies*

$$\mathcal{L}_D(\hat{h}) - \inf_{h \in \mathcal{H}} \mathcal{L}_D(h) \leq 4LU_m + 2b_\ell \sqrt{\frac{\log(2/\delta)}{2m}} + \eta. \quad (16)$$

If $Y = h^*(X)$ almost surely for some $h^* \in \mathcal{H}$ and $\ell(y, y) = 0$, then with probability at least $1 - \delta$,

$$\mathcal{L}_D(\hat{h}) \leq 2LU_m + b_\ell \sqrt{\frac{\log(1/\delta)}{2m}} + \eta. \quad (17)$$

These statements give statistical guarantees, without an efficient optimization claim.

Proof. The parameter space in (3) with the support-wide sparsity constraint is compact. Indeed, having at most k strictly positive affine values at each fixed x is a closed condition, and arbitrary intersections of these conditions remain closed in the bounded parameter box. The finitely many outer sign vectors preserve compactness. The parameter-to-function map is continuous in the uniform norm on $\mathcal{X}_0$, since $\|x\|_2 \leq R$. Thus $\mathcal{H}$ is separable in that norm. Choose a fixed countable dense subclass. Lipschitz continuity of the loss makes its empirical and population infima agree with those of $\mathcal{H}$. Selecting the first element of this subclass with empirical loss within η of its countable infimum defines a measurable approximate ERM. This is an existence argument, not an effective search procedure.

Symmetrization, scalar contraction, and bounded differences give, simultaneously for all $h \in \mathcal{H}$, the one-sided bound

$$\mathcal{L}_D(h) - \hat{\mathcal{L}}_S(h) \leq 2LE_{S'} \mathcal{R}_{\mathcal{H}}(S') + b_\ell \sqrt{\log(1/\delta)/(2m)}.$$

Here S' is an independent input sample. This is the expected-complexity form of the standard Rademacher generalization inequality (Bartlett and Mendelson, 2002; Mohri et al., 2018). The countable dense subclass justifies the suprema, and subtracting $\ell(0, Y_i)$ before contraction does not change expected Rademacher complexity. Apply the same argument in the other direction and use a union bound to obtain uniform absolute deviation at most $2LU_m + b_\ell \sqrt{\log(2/\delta)/(2m)}$. The approximate ERM inequality then proves (16). In the realizable case, $\hat{\mathcal{L}}_S(\hat{h}) \leq \eta$ almost surely; the single one-sided event proves (17). $\square$

5.1 Agnostic minimax risk for a normalized bounded loss

We now fix one loss and match upper and lower bounds in the same statistical experiment. Suppose $A > 0$, set $g = \lfloor s/k \rfloor$, and normalize the full-ball class as

$$\overline{\mathcal{H}} = \{h/(k(A+B)) : h \in \mathcal{H}_{n,s,k}^{W,B}(\mathbb{B}_R^n)\} \subseteq [-1, 1]^{\mathbb{B}_R^n}.$$

For $y \in \{-1, 1\}$, use the bounded linear loss

$$\ell_{\text{lin}}(t, y) = \frac{1}{2}(1 - y \text{clip}(t)), \quad \text{clip}(t) = \max\{-1, \min\{t, 1\}\}.$$

It is $1/2$ -Lipschitz in t and takes values in $[0, 1]$; replacing y by $\text{clip}(y)$ extends it to all real labels. Let

$$\mathfrak{E}_m = \inf_{\widehat{f}} \sup_D \left(\mathbb{E}_{S \sim D^m} \mathcal{L}_D(\widehat{f}) - \inf_{f \in \overline{\mathcal{H}}} \mathcal{L}_D(f) \right),$$

where D ranges over all Borel distributions on $\mathbb{B}_R^n \times \{-1, 1\}$. The infimum allows measurable, randomized and improper learning rules; their internal randomness is included in the expectation. The rule receives the sample, not the unknown distribution. No computation restriction is imposed.

Theorem 14 (Agnostic minimax rate). *Suppose $A > 0$, $\tau A \leq B \leq A$, and $n \geq d_g$, where τ, d_g are defined in Section 4. There are universal constants $c_1, C_1 > 0$ such that, for all $m \geq 1$,*

$$c_1 \min\{1, \sqrt{s/(km)}\} \leq \mathfrak{E}_m \leq C_1 \min\{1, \sqrt{s/(km)}\} \log^{3/2}(2m). \quad (18)$$

The upper bound follows from approximate empirical risk minimization in the normalized class. For the lower bound, the spherical-cap construction realizes all independent signs on $q = \min\{g, m\}$ inputs with a constant normalized amplitude. Give the labels small, unknown signed means on those inputs. Adjacent sign choices have small joint-sample divergence, so no learning rule can reliably recover their correlations. Appendix B makes this testing argument explicit, including improper and randomized rules.

For this loss and model, (18) yields an expected-excess-risk sample-size order $\widetilde{\Theta}(s/(k\varepsilon^2))$ for sufficiently small ε . The ratio s/k reflects the explicit output normalization by $k(A+B)$; it is not an unnormalized improvement from sk to s/k . The theorem is loss-specific and agnostic. It does not establish a matching lower bound for the realizable guarantee above or for every bounded Lipschitz loss.

6 Scope and remaining questions

Activation sparsity does not by itself identify a globally small subnetwork. The full-ball comparison makes the distinction precise: zero thresholds force at most $2k$ nonzero units, whereas positive thresholds can isolate many independently signed caps, even in logarithmic dimension. Meanwhile, biases larger than the linear pre-activation range add only constants. These are different roles of thresholds, not conflicting statements about bias complexity.

The logarithmic gap remains. Our affine cover contributes $\sqrt{\log(2m)}$, and summing the entropy bound over scales contributes another logarithm. The finite union over activation counts has only a lower-order cost. Removing that union cost alone cannot prove the logarithm-free conjecture. A direct process estimate, or an analysis retaining the simultaneous feasibility of all neuron configurations, may avoid losses introduced by the present relaxation.

The domain results leave a more geometric question: how does complexity interpolate between the zero-bias collapse and the full-ball cap construction? The sufficient value $B = (\sqrt{3}/2)WR$ is not shown to be

a critical threshold. The constants in the spherical-code dimension estimate are not sharp. Understanding small positive thresholds and fixed low dimension would explain more than improving a universal upper bound alone.

Finally, the agnostic minimax characterization concerns one explicitly normalized bounded loss and comparable bias and weight scales. It does not settle realizable learning or every loss function. All classes here impose sparsity on a fixed input domain before data are drawn; observed training-set sparsity is not a substitute for that promise. Distribution-dependent sparsity and multilayer extensions require additional arguments.

References

- Pranjal Awasthi, Nishanth Dikkala, Pritish Kamath, and Raghu Meka. Learning neural networks with sparse activations. In *Proceedings of the 37th Conference on Learning Theory*, volume 247 of *Proceedings of Machine Learning Research*, pages 406–425. PMLR, 2024. URL <https://proceedings.mlr.press/v247/awasthi24a.html>.
- Peter L. Bartlett and Shahar Mendelson. Rademacher and Gaussian complexities: Risk bounds and structural results. *Journal of Machine Learning Research*, 3:463–482, 2002. URL <https://www.jmlr.org/papers/v3/bartlett02a.html>.
- Richard M. Dudley. The sizes of compact subsets of Hilbert space and continuity of Gaussian processes. *Journal of Functional Analysis*, 1(3):290–330, 1967. doi: 10.1016/0022-1236(67)90017-1.
- Tomer Galanti, Mengjia Xu, Liane Galanti, and Tomaso Poggio. Norm-based generalization bounds for sparse neural networks. In *Advances in Neural Information Processing Systems*, volume 36, pages 42482–42501. Curran Associates, Inc., 2023. doi: 10.52202/075280-1843. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/8493e190ff1bbe3837eca821190b61ff-Abstract-Conference.html.
- Noah Golowich, Alexander Rakhlin, and Ohad Shamir. Size-independent sample complexity of neural networks. In *Proceedings of the 31st Conference on Learning Theory*, volume 75 of *Proceedings of Machine Learning Research*, pages 297–299. PMLR, 2018. URL <https://proceedings.mlr.press/v75/golowich18a.html>.
- Michel Ledoux and Michel Talagrand. *Probability in Banach Spaces: Isoperimetry and Processes*, volume 23 of *Ergebnisse der Mathematik und ihrer Grenzgebiete*. Springer-Verlag, 1991.
- Mehryar Mohri, Afshin Rostamizadeh, and Ameet Talwalkar. *Foundations of Machine Learning*. MIT Press, second edition, 2018.
- Ramchandran Muthukumar and Jeremias Sulam. Sparsity-aware generalization theory for deep neural networks. In *Proceedings of the 36th Conference on Learning Theory*, volume 195 of *Proceedings of Machine Learning Research*, pages 5311–5342. PMLR, 2023. URL <https://proceedings.mlr.press/v195/muthukumar23a.html>.
- Behnam Neyshabur, Ryota Tomioka, and Nathan Srebro. Norm-based capacity control in neural networks. In *Proceedings of the 28th Conference on Learning Theory*, volume 40 of *Proceedings of Machine Learning Research*, pages 1376–1401. PMLR, 2015. URL <https://proceedings.mlr.press/v40/Neyshabur15.html>.
- Alain Pajor and Nicole Tomczak-Jaegermann. Subspaces of small codimension of finite-dimensional Banach spaces. *Proceedings of the American Mathematical Society*, 97(4):637–642, 1986. doi: 10.1090/S0002-9939-1986-0845980-8.

Alexandre B. Tsybakov. *Introduction to Nonparametric Estimation*. Springer Series in Statistics. Springer, 2009. doi: 10.1007/b13794.

Tong Zhang. Covering number bounds of certain regularized linear function classes. *Journal of Machine Learning Research*, 2:527–550, 2002. URL <https://www.jmlr.org/papers/v2/zhang02b.html>.

A The affine covering estimate

We give the finite-dimensional argument underlying (5). It is the usual Gaussian packing proof of dual Sudakov (Pajor and Tomczak-Jaegermann, 1986; Ledoux and Talagrand, 1991), specialized to the sample norm.

Lemma 15 (Samplewise affine covering). *For every radius- R sample, every $W, B \geq 0$, and every $\delta > 0$, the affine evaluation class satisfies (5).*

Proof. We first establish the linear bound. Let $V = \text{span}\{x_1, \dots, x_m\}$, $p(v) = \max_i |\langle v, x_i \rangle|$, and $L_X = \max_i \|x_i\|_2$. Orthogonal projection onto V preserves the sample evaluations and decreases the Euclidean norm. If $W = 0$ or $L_X = 0$, the linear class is a singleton. Otherwise p is a norm on V . Let G be a standard Gaussian in V , $a = \mathbb{E}p(G) > 0$, and $K = \{v : p(v) \leq 1\}$.

For any centrally symmetric Borel set K' and $z \in V$, Gaussian density integration gives

$$\gamma(K' + z) = e^{-\|z\|_2^2/2} \int_{K'} e^{-\langle z, y \rangle} d\gamma(y) \geq e^{-\|z\|_2^2/2} \gamma(K'). \quad (19)$$

Indeed, by symmetry the integral equals that of $\cosh(\langle z, y \rangle)$, which is at least $\gamma(K')$. This argument applies in the Euclidean space V with its own Gaussian density.

Fix a covering radius $r > 0$. Choose a maximal finite collection $v_1, \dots, v_N \in WB_2(V)$ with pairwise p -distance strictly larger than r . Such a collection exists because the ball is compact. Its closed r -balls cover the ball, and the sets $v_j + (r/2)K$ are disjoint. Put $\lambda = 4a/r$. The dilated sets remain disjoint, and Markov's inequality gives $\gamma((\lambda r/2)K) = \mathbb{P}[p(G) \leq 2a] \geq 1/2$. Using (19) and $\|v_j\|_2 \leq W$,

$$1 \geq \sum_{j=1}^N \gamma(\lambda v_j + (\lambda r/2)K) \geq \frac{N}{2} e^{-\lambda^2 W^2/2}.$$

It follows that $\log N \leq \log 2 + 8W^2 a^2 / r^2$. If $r \geq WL_X$, the single center 0 suffices instead. Otherwise, $a \geq \sqrt{2/\pi} L_X$, by choosing an input attaining L_X and taking the expected absolute value of its Gaussian projection. Hence $\log 2 \leq (\pi \log 2/2) W^2 a^2 / r^2$, and in both cases

$$\log N(WB_2(V), r, p) \leq 10W^2 a^2 / r^2. \quad (20)$$

Each of the $2m$ Gaussian variables $\pm \langle G, x_i \rangle$ has variance at most R^2 . The exponential-moment maximal inequality gives $a \leq R\sqrt{2\log(2m)}$. Setting $r = \delta/2$ in (20) bounds the logarithm of the linear covering number by $80A^2 \log(2m)/\delta^2$. Finally, a grid at spacing $\delta/2$, starting at $-B$ and ending at the last such grid point not exceeding B , covers $[-B, B]$ at radius $\delta/2$ using at most $\lfloor 4B/\delta \rfloor + 1$ points. Adding this grid to the linear cover makes a δ -cover of affine evaluations. Cardinalities multiply, proving (5). $\square$

Measurability and zero scales. For each fixed sample and t , the set of (v, β) with at most t positive sample pre-activations is closed in the compact parameter box: the violating set is the finite union of conditions under which $t+1$ specified coordinates are strictly positive. Its continuous image $\mathcal{F}_t$ is compact and contains zero. The normalized union T in Section 2 is a finite union of compact sets. Its suprema are finite; the sign probability space is itself finite. The proof handles $M = 0$ before invoking a positive covering radius and chooses at least one chaining level even when $m = 1$.

B Proof of the agnostic minimax bound

We prove Theorem 14 for its normalized class and bounded linear loss.

Upper bound. Use a measurable η -approximate empirical risk minimizer in $\overline{\mathcal{H}}$, whose existence follows from the compactness argument for Corollary 13. The class is symmetric and contains zero. On its prediction range, $\ell_{\text{lin}}(f(x), y) - 1/2 = -yf(x)/2$. Symmetrization and sign symmetry therefore give

$$\mathbb{E} \sup_{f \in \overline{\mathcal{H}}} |\mathcal{L}_D(f) - \widehat{\mathcal{L}}_S(f)| \leq \mathbb{E}_{S'} \mathcal{R}_{\overline{\mathcal{H}}}(S') \leq \frac{U_m}{k(A+B)}.$$

Multiplying the Rademacher signs by the labels preserves their conditional law; the loss's factor $1/2$ cancels the symmetrization factor 2. Approximate ERM thus has expected excess risk at most $2U_m/(k(A+B)) + \eta$, uniformly in D . Using (15), $s \geq k$, and $\rho_m \leq m^{-1/2}$, and taking the better of this bound and the trivial bound 1, proves the upper inequality in (18). Letting $\eta \downarrow 0$ is legitimate in the infimum over learning rules; no exact measurable minimizer is needed.

Lower bound: one fixed family before sampling. Put $q = \min\{g, m\}$. Since $d_q \leq d_g$, choose q cap directions as in Theorem 12. Its construction with $a = A$ yields functions $f_\theta \in \overline{\mathcal{H}}$ such that

$$f_\theta(Ru_b) = \alpha\theta_b, \quad \theta \in \{-1, 1\}^q, \quad \alpha = \frac{(1-\tau)A}{A+B} \geq \frac{1-\tau}{2}.$$

Set $\delta_0 = (\alpha/4)\sqrt{q/m} \leq 1/4$. For each fixed θ , define D_θ by drawing X uniformly from the cap centers and setting

$$\mathbb{P}_\theta[Y = 1 \mid X = Ru_b] = \frac{1 + \delta_0\theta_b}{2}.$$

This family is fixed before sampling. Let $P_\theta = D_\theta^m$, and let $\theta^{(b)}$ flip coordinate b . The common input marginal gives

$$\begin{aligned} \text{KL}(P_\theta \| P_{\theta^{(b)}}) &= \frac{m}{q} \delta_0 \log \frac{1 + \delta_0}{1 - \delta_0} \\ &\leq \frac{4m\delta_0^2}{q}. \end{aligned}$$

Here $\log((1+t)/(1-t)) \leq 4t$ for $0 \leq t \leq 1/2$, for example by integrating $2/(1-t^2) \leq 4$. Pinsker's inequality implies

$$\text{TV}(P_\theta, P_{\theta^{(b)}}) \leq \delta_0 \sqrt{2m/q} = \frac{\alpha}{2\sqrt{2}} \leq \frac{\alpha}{2}.$$

Fix any learning rule, including an improper or randomized one, and write $T_b = \text{clip}(\widehat{f}(Ru_b)) \in [-1, 1]$. Averaging over adjacent pairs and using the bounded-observable characterization of total variation,

$$2^{-q} \sum_{\theta} \theta_b \mathbb{E}_\theta T_b \leq \frac{\alpha}{2}.$$

For deterministic rules, pair each θ with $\theta_b = 1$ with its flipped neighbor and use $(\mathbb{E}_\theta T_b - \mathbb{E}_{\theta^{(b)}} T_b)/2 \leq \text{TV}(P_\theta, P_{\theta^{(b)}})$. Randomized post-processing cannot increase total variation, so the same inequality applies.

The comparator f_θ has risk $1/2 - \delta_0\alpha/2$. Thus the average, over this fixed family, of the learning rule's expected excess risk is at least

$$\begin{aligned} 2^{-q} \sum_{\theta} \left(\mathbb{E}_\theta \mathcal{L}_{D_\theta}(\widehat{f}) - \inf_{f \in \overline{\mathcal{H}}} \mathcal{L}_{D_\theta}(f) \right) &\geq \frac{\delta_0\alpha}{2} - \frac{\delta_0}{2q} \sum_{b=1}^q 2^{-q} \sum_{\theta} \theta_b \mathbb{E}_\theta T_b \\ &\geq \frac{\delta_0\alpha}{4} = \frac{\alpha^2}{16} \sqrt{q/m}. \end{aligned}$$

A supremum over D is at least this average. Finally, $q \geq \frac{1}{2} \min\{s/k, m\}$ and $\alpha \geq (1 - \tau)/2$, so one may take $c_1 = (1 - \tau)^2 / (64\sqrt{2})$. This Assouad-type argument (Tsybakov, 2009, Chapter 2) directly bounds excess risk for the full-ball class, rather than converting a complexity lower bound.

AI Disclosure

The original manuscript, including its activation-budget reduction and margin-shifted covering argument, was written by the authors. During subsequent revisions, we used OpenAI Codex, including GPT-5.6 Solar and GPT-6 Astra, to assist with proof checking, mathematical revisions, literature lookup, and exposition.

Specifically, the AI-assisted revisions replaced the per-scale concentration and dyadic peeling steps with a single chaining argument over the union of normalized single-neuron classes (Section 2); introduced the threshold-clipping decomposition that isolates the constant contribution and removes the width and logarithmic factors from the bias term (Lemma 8); extended the clustered lower-bound construction to i.i.d. samples without divisibility assumptions (Theorem 3); added the zero-bias width-collapse result and the disjoint-cap lower bound on the entire ball in logarithmic dimension (Section 4); and reformulated the learning lower bound as an Assouad-type argument for the normalized class under a specified bounded linear loss, so that the learning upper and lower bounds concern the same statistical model (Theorem 14). AI tools also assisted with edge-case checks, finite-instance verification scripts, and expansion of the technique overview. We take full responsibility for all content in the final manuscript, including AI-assisted material, and for its correctness, originality, attribution, and citations.