arXiv:2610.35488v1 [cs.SE] 26 Oct 2026

Tencent Hunyuan

FeatureLoop: Benchmarking Coding Agents under Evolving Requirements

Jia Feng[1], **Alyssa Wu**[1], **Cuiyun Gao**[2],
Yunlong Wang[1], **Songyuanyi Lu**[1], **Zhichao Hu**[1]

[1]Hunyuan Team, Tencent [2]The Chinese University of Hong Kong

{plusfeng, alyssawwu, joeyolwang, alinasyylu, frankiehu}@tencent.com
cygao@cse.cuhk.edu.hk

Abstract

Software development with coding agents often begins with a rough request that users refine after trying the implementation. Final correctness alone does not capture the repeated guidance this process requires. We introduce FeatureLoop, a benchmark of 61 human-reviewed tasks from 34 repositories across five primary programming languages and seven software forms. Each task follows one development goal in a persistent workspace through *evolution feedback*, which adds or clarifies requirements, and *completion feedback*, which reports failures of stated requirements. Cumulative executable checks track new behavior, repair, and preservation of earlier functionality. We evaluate 12 frontier models and find that the strongest completes 72.1% of tasks with both feedback types. Across models, however, only 15.4% of observed failed stages recover within two corrective revisions. Further analysis reveals incomplete repairs, regressions, and model-specific differences in feedback use and token efficiency, identifying obstacles to reliable, low-intervention development.

1 Introduction

Coding agents combine repository inspection and code editing (Yang et al., 2024a) with command execution in sandboxed environments (Wang et al., 2025). Real-user records show sustained development with repeated corrections and failure reports (Baumann et al., 2026). Initial requests can also omit information needed for implementation (Vijayvargiya et al., 2026). Delegating the opening request therefore leaves the user with further work: trying the implementation, explaining additional requirements, and reporting errors. Turning those reports into working code remains a separate challenge, since repair success depends on the quality of the feedback (Olausson et al., 2024). The practical question is: *how much repeated guidance does an agent need to turn an initial request into a complete, working implementation?*

Figure 1 illustrates two reasons for returning to a coding agent. After a Grow menu can create connected shapes, the user asks for connectors that reroute during dragging. This changes what the software should do. Once rerouting has been requested, a report that a connector stays in its old position instead identifies unfinished implementation work. We call the first kind of intervention *evolution feedback* and the second *completion feedback*. Across both, progress must accumulate: creating a correct connector is insufficient if the next edit breaks child creation or loses its bindings. Rechecking earlier behavior after changes is the purpose of regression testing (Yoo & Harman, 2012).

Existing benchmarks establish several parts of this evaluation. Executable tasks cover repository issue resolution (Jimenez et al., 2024), complex feature implementation (Zhou et al., 2026), technical terminal workflows (Merrill et al., 2026), and vulnerability reproduction (Wang et al., 2026b). Interactive evaluation measures responses to user requests and corrections (Wu et al., 2026), while sequential evaluation checks earlier requirements after continued modification (Shen et al., 2026). Conversational code generation further shows that solving more problems and solving them in fewer turns are distinct outcomes (Han et al., 2025). Our focus is how these demands interact: *when a user*

adds requirements or reports failures, does the next revision improve the complete implementation, and how much more guidance is still needed?

We introduce FeatureLoop to make this development path measurable. Each task follows one user-facing development goal from an initial request through successive refinements of the same repository implementation. Later requests specify its capabilities, constraints, and interactions, while each revision must retain the requirements already established. Executable checks determine which later requirements still need to be requested, which stated requirements need correction, and whether earlier functionality remains correct. The resulting record separates success on the latest request from success on everything requested so far. It also distinguishes eventual delivery from a development path that repeatedly leaves the user with an incomplete or broken implementation.



Figure 1: An Excalidraw interaction excerpt. The canvases show successive implementations; the faded shape marks the position before dragging.

FeatureLoop contains 61 tasks from 34 repositories, covering five primary programming languages and seven software forms. Its construction connects public development requests to staged, executable acceptance criteria. Tests and reference implementations are authored independently, each stage is checked for both added behavior and preservation of earlier requirements, and human reviewers inspect task quality before and after trial agent runs. This yields tasks with explicit user goals, feasible implementations, and requirement-level evidence across command-line tools, services, interactive applications, and libraries. The same feedback loop can therefore be evaluated across a broad range of software-engineering settings.

We evaluate 12 frontier models with complete requirements upfront, progressive requests alone, and progressive requests with corrective feedback. The results expose three complementary weaknesses. First, a model's final success rate does not describe how much correction it needs. Second, failure reports rarely yield a complete repair: only 15.4% of observed failed states recover within two revisions. Third, local success does not ensure reliable cumulative progress; even successful individual repairs leave other stated requirements unfinished in 20.9% of cases. Model-level analysis further separates responsiveness to correction, preservation of working behavior, and resource use. These differences identify where continued user intervention remains necessary.

Our contributions are threefold:

- We introduce an executable evaluation of iterative repository development that connects requirement evolution and corrective feedback to cumulative correctness and user guidance.
- We build FeatureLoop, a quality-reviewed benchmark of 61 multi-stage tasks from 34 repositories across five primary programming languages and seven software forms, with acceptance checks retained throughout development.
- We evaluate 12 frontier models and identify common gaps in complete repair and user-facing verification, alongside model-specific differences in preservation, failure patterns, and token efficiency.

2 FeatureLoop

2.1 Task Formulation

A FeatureLoop task develops one user-facing goal within an existing repository. The initial request establishes the direction; later requests specify further capabilities, constraints, and interactions that

refine the target software. All stages build on the same implementation, and each revision must satisfy the requirements accumulated so far.

Let W_0 be the initial repository. A *requirement group* collects related behaviors evaluated together, such as creating a child shape and binding its connector. The groups form a *directed acyclic graph* (DAG), where an edge $g \to h$ means that h depends on g. We unfold this graph into a fixed sequence of stages that respects its dependencies. At stage i, the newly introduced groups are A_i, and the *requirement state* Q_i contains all groups introduced so far:

$$Q_1 = A_1, \qquad Q_{i+1} = Q_i \cup A_{i+1}, \qquad Q_1 \subset \cdots \subset Q_K. \tag{1}$$

Each stage adds at least one group. Every earlier group remains part of the task through the final stage K.

Checking the complete implementation. Let $Z_g(W)$ indicate whether the implementation in workspace W passes the checks for group g. Let $b(W)$ indicate whether it passes the *baseline suite*, which checks the repository behavior that was working before the task. We evaluate the requested functionality and the baseline separately:

$$P_i(W) = \mathbf{1}[\forall g \in Q_i,\ Z_g(W) = 1], \qquad C_i(W) = b(W)P_i(W). \tag{2}$$

Here, $P_i = 1$ means that all requirements introduced so far pass; $C_i = 1$ also requires the original repository behavior to pass. For example, rerouting a connector correctly is only local progress if creating its bound child still fails. Regression testing checks that modifications preserve established behavior (Yoo & Harman, 2012). Here, the retained obligations include both the original baseline and every requirement introduced during the task.

Two forms of feedback. Evolution feedback introduces missing behavior from the next requirement group or groups A_{i+1}. Completion feedback reports a failure among requirements already in Q_i and asks the agent to repair its implementation. Before sending a later request, the evaluator checks whether the corresponding behavior already works and omits the parts already satisfied. Revisions then update the existing workspace. This makes feedback depend on the agent's progress while keeping the development target fixed.

Final task success requires every requested behavior and the baseline to pass:

$$\text{Success}(W_T) = C_K(W_T), \tag{3}$$

where W_T is the final workspace. Intermediate checks identify requirements completed immediately, repaired after feedback, left unfinished, or broken by later edits. Appendix B.1 defines the stored task components and the indexing of revisions. The complete six-stage Excalidraw walkthrough appears in Appendix B.2.

2.2 Three Development Scenarios

We compare three ways a user can delegate the same development task (Figure 2). They differ in when the user provides requirements and whether the user returns to report implementation problems.

Complete requirements upfront (Full). The user specifies the entire target at the outset and asks the agent to deliver it in one coding session. The agent inspects the repository, edits code, and uses its tools to check the result. This scenario evaluates implementation when the user has already described everything needed.

Progressive requests (Evo). The user starts with an initial request and introduces further requirements as development proceeds. Each



Figure 2: Three development scenarios. Green: new requests; orange: corrections.

new request gives the agent another opportunity to extend the existing implementation. The user supplies additional requirements but leaves debugging to the agent. This scenario evaluates whether the agent can integrate each request and preserve earlier functionality using its own verification.

Progressive requests with correction (Evo+Comp). The user also reports problems encountered in the current implementation. The agent can respond to those reports before receiving the next requirement. This is the main evaluation scenario: the user continues refining the task and checking the delivered software, while the benchmark measures how effectively the agent uses both kinds of feedback.

To keep the task comparable, all scenarios start from the same repository checkpoint and use the same final requirements and acceptance checks. The two progressive scenarios also share the requirement order. Within that order, the current implementation determines which requests are still needed and which failures can be reported. Figure 15 in Appendix D.3 gives the full protocol diagram, including disclosure checks and corrective-feedback paths.

2.3 Benchmark Construction

Construction must connect a realistic development goal to runnable stages and acceptance checks that faithfully test the requested behavior. Stronger tests can expose errors missed by weaker evaluation suites (Liu et al., 2023), motivating checks of both the new behavior and its interaction with earlier requirements. Our pipeline combines agent-assisted authoring, executable validation, and human review. Figure 3 gives a simplified overview; the complete author–critic workflow, including information boundaries and revision paths, appears in Figure 10 of Appendix B.3.



Figure 3: Construction stages and their output artifacts.

Ground the development goal in real requests. Each candidate begins with an exact repository checkpoint and at least two complete public issues supporting a common user-facing direction. These issues anchor the motivation and initial scope; repository evidence supports compatible extensions. We organize this shared goal into a dependency DAG of requirement groups, then select a stage sequence that respects the graph and follows the use scenarios that motivate further detail. A behavioral specification records the actions or inputs, expected outcomes, preserved behavior, and public observation points for each group. The corresponding user requests introduce that behavior in order. Appendices B.3.1–B.3.5 describe source selection, requirement planning, environment setup, and request authoring.

Check behavior and exclude known complete solutions. To evaluate functionality across different implementations, the Test author derives executable checks from the behavioral specification. These checks cover each requirement group, the requirements accumulated at each stage, and the repository baseline. Before constructing a reference solution, we run the frozen checks on later public repository history and remove candidates whose complete target is already implemented. This targets publicly available solutions while retaining the original repository context. The availability of public solutions is a source of evaluation contamination (Badertdinov et al., 2025); screening later history addresses this concern for the recorded repository window. Appendices B.3.6 and B.3.7 specify test construction and the history searched.

	Go	Rust	JS	TS	Py	Go/TS	All
CLI	3	14	–	1	3	–	21
Service	8	–	3	–	1	1	13
TUI	6	1	–	–	3	–	10
Browser	–	–	1	6	–	–	7
Library	1	–	6	–	–	–	7
Framework	–	–	–	2	–	–	2
Embedded	1	–	–	–	–	–	1
Total	19	15	10	9	7	1	61

(a)



(b)

Figure 4: Dataset composition and cumulative implementation size. (a) Task counts by programming language and software form, including one mixed Go/TypeScript task. (b) Means and interquartile ranges of cumulative test groups, nonblank test lines, and reference-code additions plus deletions. Stage i includes tasks that reach it; the final column includes all 61 tasks.

Verify that each stage adds feasible behavior and preserves earlier work. An independent Reference author implements the same specification, producing a working checkpoint W_i^* for each stage. Test and Reference authors use separate workspaces and review sessions, so the tests assess the shared specification rather than being copied from a reference patch. For every new group $g \in A_i$, its checks must fail on W_{i-1}^* and pass on W_i^* and all later checkpoints. Every checkpoint must also pass the baseline and earlier requirements. These checks establish both a meaningful increment and its continued compatibility with the accumulated implementation. Selected candidates additionally use valid alternative implementations and deliberately faulty variants to check acceptance and failure detection. Appendices B.3.8 and B.3.9 give the construction and validation rules.

Review task quality before and after trial agent runs. Human reviewers first inspect the requirements and requests, run every reference stage, and verify that the tests enforce the intended user-visible behavior. Candidates that pass this review are then implemented by four coding models. Reviewers examine the resulting conversations, edits, and execution evidence to identify task defects exposed by implementations beyond the reference solution. Defects return to the responsible construction stage for correction and revalidation. Final acceptance retains 61 tasks. Appendix B.3.10 specifies the human review, and Appendix C.1 records the candidate counts, trial models, and selection outcomes.

2.4 Dataset Characteristics

Broad software-engineering coverage. The 61 tasks cover 34 repositories and five primary programming languages: Go, Rust, JavaScript, TypeScript, and Python. They include command-line tools, terminal interfaces, browser applications, services, libraries, frameworks, and embedded software (Figure 4(a)). This coverage includes backend services, developer tooling, interactive software, and reusable components, each evaluated through its public commands, APIs, or user interface. Appendices C.2 and C.5 give the complete composition.

Successive stages add continuing obligations. Tasks contain two to eight stages. Each stage adds behavior that must continue to work as the implementation changes. Across the 61 tasks, the average number of active test groups grows from 1.15 at the first stage to 4.11 at the final stage (Figure 4(b)). Each new stage therefore expands the set of behaviors that must work together in the same implementation. Appendix C.4 reports stage counts, test sizes, and reference-edit volumes; Appendix C.3 defines the counting units.

Later requirements include both foreseeable extensions and new information. The 61 tasks contain 147 later requirement groups. Of these, 42 follow a direction supported by earlier requests. For 16 of these groups, earlier information also constrains the exact expected behavior, and implementing it early carries limited risk. Another 85 depend on new user information or a discovery unavailable in the earlier interaction. Underspecified requests can omit information that materially

changes the correct implementation (Vijayvargiya et al., 2026). We therefore distinguish two capabilities: completing well-supported behavior before another request is needed, and incorporating new requirements correctly once the user supplies them. The semantic annotation procedure, examples, and full labels are in Appendix C.6.

3 Experimental Setup and Evaluation

Setup. We evaluate 12 frontier models on all 61 tasks under the three development scenarios, yielding 2,196 runs. All models use Claude Code as the shared coding harness. Progressive runs retain the workspace and conversation; the corrective scenario uses a fixed feedback generator and permits at most two corrective revisions per stage. Each revision is a complete coding-agent response with its own tool calls. Appendix D gives the models, runtime configuration, and execution rules.

Measures. StrictPass measures final completion of all requirements and the repository baseline. We report new-requirement and corrective message counts (N_E, N_C), together with Feedback-Discounted Agent Completion (FDAC), which discounts successful delivery according to when intermediate states become correct; a state left incomplete within its response budget yields zero. Intermediate checks distinguish new-requirement uptake, complete repair, and preservation of earlier success. Agent Tokens measures reported input and output tokens. Trajectory analyses use both feedback types unless stated otherwise. Appendix E provides metric definitions, observation windows, token accounting, and uncertainty estimates.

4 Results

4.1 Intervention Changes the Model Comparison, Not Just the Average Score

The development process is part of the difficulty. Providing the entire specification at the outset does not produce the highest completion rate. Across models, final success rises from 40.3% with an upfront specification (Full), to 51.6% with progressive requests (Evo), and to 64.1% with progressive requests and correction (Evo+Comp). The target and final checks are the same, but the opportunities to focus on a new requirement or revisit a failure differ. Full-specification performance therefore does not adequately characterize iterative development.

Table 1: Main results, ordered by Evo+Comp FDAC. StrictPass and FDAC are percentages; N_E and N_C are mean messages per task, including failed runs. Each model is evaluated on the same 61 tasks. Best observed outcome values and the lowest correction count are bold.

	StrictPass ↑			Evo+Comp path		
Model	Full	Evo	Evo+Comp	FDAC ↑	N_E	N_C
GPT-6 Astra	**59.0**	**68.9**	**72.1**	**46.5**	2.25	2.00
GPT-5.6 Sol	52.5	62.3	70.5	45.4	2.23	1.89
Kimi K3	39.3	54.1	70.5	44.2	2.25	**1.87**
Hy4-Preview	47.5	52.5	68.9	42.7	2.28	2.08
DeepSeek V4 Flash	37.7	57.4	70.5	41.2	2.25	1.97
DeepSeek V4.1 Flash	42.6	57.4	70.5	40.8	2.28	2.07
GLM 5.3	44.3	50.8	65.6	40.5	2.23	2.02
Qwen 3.8 Flash	39.3	47.5	57.4	37.3	2.30	2.59
GLM 5.3 Flash	36.1	49.2	62.3	37.2	2.28	2.48
Grok 4.6	27.9	37.7	63.9	37.1	2.31	2.82
DeepSeek V4 Pro	36.1	49.2	60.7	36.7	2.30	2.44
Hy3	21.3	32.8	36.1	21.2	2.36	4.03
Pooled	40.3	51.6	64.1	39.2	2.27	2.35

Small gains can reflect very different starting points. GPT-6 Astra and Hy3 each gain only 3.3 percentage points when correction is enabled. For GPT-6 Astra, this follows already high success

without correction; for Hy3, it accompanies low success in both settings (Table 1). A small workflow gain alone cannot distinguish limited need for intervention from failure to make useful progress despite it. Models also respond differently to the type of intervention: DeepSeek V4 Flash gains most from staged requests, whereas Grok 4.6 gains most from the correction-enabled workflow. Appendix F.8 separates these outcome changes from direct repairs within individual runs.

Repeated correction is the larger source of variation in guidance. The shared requirement sequence produces similar numbers of new requests across models, while corrective messages range from fewer than two to about four per task. Even the four models tied at 43 successful deliveries receive different feedback-discounted scores. Thus, matching final success does not imply matching user involvement or timely intermediate completion. Appendix F.11 reports the message counts together with stalled and regressed states.

4.2 Local Progress Often Fails to Produce a Complete, Lasting Repair

Providing the missing information does not remove the implementation bottleneck. We first examine requirements that introduce information unavailable earlier in the task. Agents implement the newly requested behavior on the first response in 77.3% of observed cases. Yet some of those locally successful responses still leave earlier requirements unfinished. The difficulty is not simply understanding the latest request: the new behavior must coexist with everything the user has already asked for. Appendix F.7 separates local success from complete requirement-state success.

An explicit failure report rarely restores the whole state. We next follow stages that fail their checks after the first response and receive corrective feedback. Only 15.4% become fully correct within the two permitted revisions. Moreover, fixing an individual requirement is not always enough: 20.9% of successful individual repairs still leave another stated requirement unmet. Earlier work may have remained unfinished or been broken by a subsequent edit. The relevant stopping condition is therefore the complete set of active requirements, not disappearance of the latest symptom. Appendix F.10 gives state-level recovery, and Appendix F.7 gives the individual-repair breakdown.

Correct behavior must survive the next request. To examine preservation, we continue checking requirements that have already passed and are observed again during later stages. Of these previously working requirements, 11.4% fail at a subsequent check. In the NextChat example, an early repair is followed by a runtime error that persists while further capabilities are added. Continued feature development can thus conceal a broken execution path rather than repair it. The case appears in Appendix F.5; the complete retention counts and observation conditions are in Table 35. Together, these findings locate three separate demands on an agent: implement the new behavior, restore all stated behavior, and preserve that result through further edits.

4.3 Similar Final Scores Conceal Different Recovery and Preservation Profiles

Responsiveness to correction and preservation are distinct strengths. The two DeepSeek Flash models have the same final completion rate, but V4 repairs roughly twice the fraction of failed states that V4.1 repairs. V4.1, in contrast, preserves a larger fraction of its previously working requirements (Figure 5). Grok 4.6 shows another imbalance: it has the largest correction-enabled workflow gain and the highest observed direct-recovery fraction, yet the lowest observed retention. These profiles explain why final success alone cannot reveal whether a model reaches its result through stable progress or repeated repair. Each conditional rate follows the failures or previously passing requirements actually encoun-



Figure 5: Model-level recovery and retention under both feedback types. Recovery uses failed states; retention uses previously passing requirements with later observations.

tered by that model; Appendix F.10 provides the full model-level counts.

Tied scores do not imply the same unresolved tasks. The four models that each complete 43 tasks jointly cover 51 tasks, meaning that a task may fail for one of these models and succeed for another despite their tied aggregate results. This union measures the coverage of their independently recorded runs. Their failure profiles identify different obstacles: GPT-5.6 Sol more often leaves build or runtime failures than Kimi K3, while DeepSeek V4.1 Flash's remaining failures concentrate on behavioral compatibility rather than broken builds. Appendix F.4 reports the task-overlap calculation and all model profiles. Improving iterative coding consequently requires identifying which stage of implementation fails for a model, rather than treating a leaderboard score as a uniform capability.

4.4 Verification Often Misses the User's Actual Execution Path

Checking a convenient component is not checking the requested behavior. We inspect the requests, edits, actions, and execution evidence of every run that ends unsuccessfully. In 75.3% of these failures, the agent either omits a relevant user-path check or validates a helper, stub, or proxy instead. For example, an internal merge routine can pass a custom test while the live endpoint continues to use the old behavior. This explains how apparently reasonable code and repeated tool use coexist with an unresolved user report: the agent's check does not exercise the behavior being evaluated. Appendix F.2 documents the coding procedure, and Appendix F.5 traces representative examples.



Figure 6: Primary diagnoses within each task set's final failures. "Other" groups the remaining diagnoses.

Shared-state consistency characterizes the common hard cases. On tasks that no evaluated model completes, inconsistent state across components accounts for 32.4% of final failures, compared with 2.6% on tasks solved by some models (Figure 6). These traces involve registries, stores, parsers, renderers, or lifecycle handlers that do not agree on the same state. A local patch can leave that disagreement intact even when its own helper works. The common difficulty is therefore broader than writing a missing function: the change must reach the public entry point and remain consistent across the components that consume it.

Model-specific failures distinguish broken execution from incorrect behavior. Build and runtime problems form a large share of Hy3 and Grok 4.6 failures, while GLM 5.3 more often produces a runnable implementation with incorrect behavior or API details (Figure 7). DeepSeek V4.1 Flash has no final failure primarily attributed to a broken build, yet still misses legacy calling forms, timing bounds, or output representations. These are different verification needs: restoring executability, checking exact public behavior, and preserving compatibility. The model-level cases in Appendix F.4 identify the corresponding commands, interfaces, and state transitions. Appendix F.9 reports how these patterns are distributed across the sampled languages and software forms.



Figure 7: Primary diagnoses within each model's final failures; cell values are percentages.

4.5 Comparable Delivery Quality Can Carry Very Different Token Costs

Enabling correction increases average reported tokens per run by 47.2%. More successful final deliveries therefore come with substantially greater token expenditure during development. To compare models at the level of delivered outcomes, we charge all recorded runs, including failures, to their successful deliveries. Grok 4.6 and GLM 5.3 achieve similar final completion rates, but the latter uses about 7.1 times as many tokens per successful delivery (Figure 8). Similar outcome quality can consequently arise at very different resource expenditure.



Figure 8: Model-level completion and token expenditure under both feedback types. Cost includes tokens spent on failed runs.

This cost difference must be read alongside the development profile. Grok's lower token use coexists with weaker preservation of earlier behavior; GLM 5.3's greater expenditure still leaves exact interface requirements unresolved in several traces. Neither a low token total nor a high final score describes reliable, low-intervention development on its own. Appendix F.14 provides the complete token accounting, while Appendix F.13 reports the reliability of the full intermediate trajectory.

5 Scope and Limitations

FeatureLoop focuses on cumulative, executable requirements in existing repositories, with one predefined continuation per task. We use a fixed feedback policy and at most two corrective revisions per stage. The findings characterize the sampled tasks under these interaction settings; human collaboration may involve different requirement changes and feedback patterns. Correctness is assessed through executable checks, whose coverage is bounded by the specified behaviors.

6 Conclusion

We introduced FeatureLoop, a benchmark for iterative software development under evolving requirements. Each task follows one development goal in a persistent workspace, combining new requests and corrective feedback with cumulative executable checks. Our evaluation of 12 frontier models shows that interactive workflows improve final completion, while incomplete repairs and regressions remain recurring obstacles. Models with similar final success rates also differ in their reliance on correction, preservation of working functionality, and token expenditure. By evaluating both final outcomes and progress across revisions, FeatureLoop provides a testbed for advancing reliable coding agents that require less repeated user guidance.

References

Ibragim Badertdinov, Alexander Golubev, Maksim Nekrashevich, Anton Shevtsov, Simon Karasik, Andrei Andriushchenko, Maria Trofimova, Daria Litvintseva, and Boris Yangel. SWE-rebench: An Automated Pipeline for Task Collection and Decontaminated Evaluation of Software Engineering Agents, 2025. URL https://arxiv.org/abs/2505.20411.

Joachim Baumann, Vishakh Padmakumar, Xiang Li, John Yang, Diyi Yang, and Sanmi Koyejo. SWE-chat: Coding Agent Interactions From Real Users in the Wild, 2026. URL https://arxiv.org/abs/2604.20779.

Xinyun Chen, Maxwell Lin, Nathanael Schärli, and Denny Zhou. Teaching Large Language Models to Self-Debug, 2023. URL https://arxiv.org/abs/2304.05128.

Hojae Han, Seung won Hwang, Rajhans Samdani, and Yuxiong He. ConvCodeWorld: Benchmarking Conversational Code Generation in Reproducible Feedback Environments, 2025. URL https://arxiv.org/abs/2502.19852.

Naman Jain, Jaskirat Singh, Manish Shetty, Liang Zheng, Koushik Sen, and Ion Stoica. R2E-Gym: Procedural Environments and Hybrid Verifiers for Scaling Open-Weights SWE Agents, 2025. URL https://arxiv.org/abs/2504.07164.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can Language Models Resolve Real-World GitHub Issues?, 2024. URL https://arxiv.org/abs/2310.06770.

Tue Le, Minh V. T. Thai, Dung Nguyen Manh, Huy Phan Nhat, and Nghi D. Q. Bui. SWE-EVO: Benchmarking Coding Agents in Long-Horizon Software Evolution Scenarios, 2026. URL https://arxiv.org/abs/2512.18470.

Han Li, Zhemin Fang, Rili Feng, Yingqi Zhao, Jiaheng Liu, Pengfei Gao, He Ye, Dayi Lin, Qingwei Lin, Saravan Rajmohan, and Dongmei Zhang. LoopsBench: From Harness Engineering to Loop Engineering in Coding Agent Evaluation, 2026. URL https://arxiv.org/abs/2608.00267.

Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Lingming Zhang. Is Your Code Generated by ChatGPT Really Correct? Rigorous Evaluation of Large Language Models for Code Generation, 2023. URL https://arxiv.org/abs/2305.01210.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. Self-Refine: Iterative Refinement with Self-Feedback, 2023. URL https://arxiv.org/abs/2303.17651.

Mike A. Merrill, Alexander G. Shaw, Nicholas Carlini, Boxuan Li, Harsh Raj, Ivan Bercovich, Lin Shi, Jeong Yeon Shin, Thomas Walshe, E. Kelly Buchanan, Junhong Shen, Guanghao Ye, Haowei Lin, Jason Poulos, Maoyu Wang, Marianna Nezhurina, Jenia Jitsev, Di Lu, Orfeas Menis Mastromichalakis, Zhiwei Xu, Zizhao Chen, Yue Liu, Robert Zhang, Leon Liangyu Chen, Anurag Kashyap, Jan-Lucas Uslu, Jeffrey Li, Jianbo Wu, Minghao Yan, Song Bian, Vedang Sharma, Ke Sun, Steven Dillmann, Akshay Anand, Andrew Lanpouthakoun, Bardia Koopah, Changran Hu, Etash Guha, Gabriel H. S. Dreiman, Jiacheng Zhu, Karl Krauth, Li Zhong, Niklas Muennighoff, Robert Amanfu, Shangyin Tan, Shreyas Pimpalgaonkar, Tushar Aggarwal, Xiangning Lin, Xin Lan, Xuandong Zhao, Yiqing Liang, Yuanli Wang, Zilong Wang, Changzhi Zhou, David Heineman, Hange Liu, Harsh Trivedi, John Yang, Junhong Lin, Manish Shetty, Michael Yang, Nabil Omi, Negin Raoof, Shanda Li, Terry Yue Zhuo, Wuwei Lin, Yiwei Dai, Yuxin Wang, Wenhao Chai, Shang Zhou, Dariush Wahdany, Ziyu She, Jiaming Hu, Zhikang Dong, Yuxuan Zhu, Sasha Cui, Ahson Saiyed, Arinbjörn Kolbeinsson, Jesse Hu, Christopher Michael Rytting, Ryan Marten, Yixin Wang, Alex Dimakis, Andy Konwinski, and Ludwig Schmidt. Terminal-Bench: Benchmarking Agents on Hard, Realistic Tasks in Command Line Interfaces, 2026. URL https://arxiv.org/abs/2601.11868.

Samuel Miserendino, Michele Wang, Tejal Patwardhan, and Johannes Heidecke. SWE-Lancer: Can Frontier LLMs Earn $1 Million from Real-World Freelance Software Engineering?, 2025. URL https://arxiv.org/abs/2502.12115.

Niels Mündler, Mark Niklas Müller, Jingxuan He, and Martin Vechev. SWT-Bench: Testing and Validating Real-World Bug-Fixes with Code Agents, 2025. URL https://arxiv.org/abs/2406.12952.

Theo X. Olausson, Jeevana Priya Inala, Chenglong Wang, Jianfeng Gao, and Armando Solar-Lezama. Is Self-Repair a Silver Bullet for Code Generation?, 2024. URL https://arxiv.org/abs/2306.09896.

Gabriel Orlanski, Devjeet Roy, Alexander Yun, Changho Shin, Alex Gu, Albert Ge, Dyah Adila, Nicholas Roberts, Frederic Sala, and Aws Albarghouthi. SlopCodeBench: Benchmarking How Coding Agents Degrade Over Long-Horizon Iterative Tasks, 2026. URL https://arxiv.org/abs/2603.24755.

Jiayi Pan, Xingyao Wang, Graham Neubig, Navdeep Jaitly, Heng Ji, Alane Suhr, and Yizhe Zhang. Training Software Engineering Agents and Verifiers with SWE-Gym, 2025. URL https://arxiv.org/abs/2412.21139.

Zhongyuan Peng, Dan Huang, Chuyu Zhang, Caijun Xu, Changyi Xiao, Shibo Hong, David Lo, Lin Qiu, Xuezhi Cao, Jiyuan He, and Yixin Cao. ICAE-Bench: Evaluating Coding Agents as Interactive Project Builders, 2026. URL https://arxiv.org/abs/2607.21217.

Mohit Raghavendra, Anisha Gunjal, Aakash Sabharwal, and Yunzhong He. SWE-INTERACT: Reimagining SWE Benchmarks as User-Driven Long-Horizon Coding Sessions, 2026. URL https://arxiv.org/abs/2606.30573.

Muhammad Shihab Rashid, Christian Bock, Yuan Zhuang, Alexander Buchholz, Tim Esler, Simon Valentin, Luca Franceschi, Martin Wistuba, Prabhu Teja Sivaprasad, Woo Jung Kim, Anoop Deoras, Giovanni Zappella, and Laurent Callot. SWE-PolyBench: A multi-language benchmark for repository level evaluation of coding agents, 2025. URL https://arxiv.org/abs/2504.08703.

Sergio Segura, Gordon Fraser, Ana B. Sanchez, and Antonio Ruiz-Cortés. A survey on metamorphic testing. *IEEE Transactions on Software Engineering*, 42(9):805–824, 2016. doi: 10.1109/TSE.2016.2532875.

Haiyang Shen, Xuanzhong Chen, Wendong Xu, Yun Ma, Liang Chen, and Kuan Li. EvoCode-Bench: Evaluating Coding Agents in Multi-Turn Iterative Interactions, 2026. URL https://arxiv.org/abs/2605.24110.

Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language Agents with Verbal Reinforcement Learning, 2023. URL https://arxiv.org/abs/2303.11366.

Sanidhya Vijayvargiya, Xuhui Zhou, Akhila Yerukola, Maarten Sap, and Graham Neubig. AmbigSWE: Interactive Agents to Overcome Underspecificity in Software Engineering, 2026. URL https://arxiv.org/abs/2502.13069.

Xin Wang, Liangtai Sun, Yaoming Zhu, Shuang Zhou, Jiaxing Liu, Fengjiao Chen, Lin Qiu, Xuezhi Cao, Xunliang Cai, Licheng Zhang, and Zhendong Mao. Asuka-Bench: Benchmarking Code Agents on Underspecified User Intent and Multi-Round Refinement, 2026a. URL https://arxiv.org/abs/2606.05920.

Xingyao Wang, Boxuan Li, Yufan Song, Frank F. Xu, Xiangru Tang, Mingchen Zhuge, Jiayi Pan, Yueqi Song, Bowen Li, Jaskirat Singh, Hoang H. Tran, Fuqiang Li, Ren Ma, Mingzhang Zheng, Bill Qian, Yanjun Shao, Niklas Muennighoff, Yizhe Zhang, Binyuan Hui, Junyang Lin, Robert Brennan, Hao Peng, Heng Ji, and Graham Neubig. OpenHands: An Open Platform for AI Software Developers as Generalist Agents, 2025. URL https://arxiv.org/abs/2407.16741.

Zhun Wang, Tianneng Shi, Jingxuan He, Matthew Cai, Jialin Zhang, and Dawn Song. CyberGym: Evaluating AI Agents' Real-World Cybersecurity Capabilities at Scale, 2026b. URL https://arxiv.org/abs/2506.02548.

Edwin B. Wilson. Probable inference, the law of succession, and statistical inference. *Journal of the American Statistical Association*, 22(158):209–212, 1927. doi: 10.1080/01621459.1927.10502953. URL https://doi.org/10.1080/01621459.1927.10502953.

Yifan Wu, Zhuokai Zhao, Songlin Li, Ho Hin Lee, Jiacheng Zhu, Shirley Wu, Tianhe Yu, Serena Li, Lizhu Zhang, Xiangjun Fan, and Shengzhi Li. SWE-Together: Evaluating Coding Agents in Interactive User Sessions, 2026. URL https://arxiv.org/abs/2606.29957.

Lu Yan, Xuan Chen, and Xiangyu Zhang. When the Specification Emerges: Benchmarking Faithfulness Loss in Long-Horizon Coding Agents, 2026. URL https://arxiv.org/abs/2603.17104.

John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. SWE-agent: Agent-Computer Interfaces Enable Automated Software Engineering, 2024a. URL https://arxiv.org/abs/2405.15793.

John Yang, Carlos E. Jimenez, Alex L. Zhang, Kilian Lieret, Joyce Yang, Xindi Wu, Ori Press, Niklas Muennighoff, Gabriel Synnaeve, Karthik R. Narasimhan, Diyi Yang, Sida I. Wang, and Ofir Press. SWE-bench Multimodal: Do AI Systems Generalize to Visual Software Domains?, 2024b. URL https://arxiv.org/abs/2410.03859.

John Yang, Kilian Lieret, Carlos E. Jimenez, Alexander Wettig, Kabir Khandpur, Yanzhe Zhang, Binyuan Hui, Ofir Press, Ludwig Schmidt, and Diyi Yang. SWE-smith: Scaling Data for Software Engineering Agents, 2025. URL https://arxiv.org/abs/2504.21798.

S. Yoo and M. Harman. Regression testing minimization, selection and prioritization: A survey. *Software Testing Verification and Reliability*, 22(2):67–120, March 2012. ISSN 0960-0833. doi: 10.1002/stvr.430.

Daoguang Zan, Zhirong Huang, Wei Liu, Hanwu Chen, Linhao Zhang, Shulin Xin, Lu Chen, Qi Liu, Xiaojian Zhong, Aoyan Li, Siyao Liu, Yongsheng Xiao, Liangqiang Chen, Yuyu Zhang, Jing Su, Tianyu Liu, Rui Long, Kai Shen, and Liang Xiang. Multi-SWE-bench: A Multilingual Benchmark for Issue Resolving, 2025. URL https://arxiv.org/abs/2504.02605.

Zexun Zhan, Shuzheng Gao, Ruida Hu, and Cuiyun Gao. SR-Eval: Evaluating LLMs on Code Generation under Stepwise Requirement Refinement, 2026. URL https://arxiv.org/abs/2509.18808.

Lei Zhang, Jiaxi Yang, Min Yang, Jian Yang, Mouxiang Chen, Jiajun Zhang, Zeyu Cui, Binyuan Hui, and Junyang Lin. SWE-Flow: Synthesizing Software Engineering Data in a Test-Driven Manner, 2025a. URL https://arxiv.org/abs/2506.09003.

Linghao Zhang, Shilin He, Chaoyun Zhang, Yu Kang, Bowen Li, Chengxing Xie, Junhao Wang, Maoquan Wang, Yufan Huang, Shengyu Fu, Elsie Nallipogu, Qingwei Lin, Yingnong Dang, Saravan Rajmohan, and Dongmei Zhang. SWE-bench Goes Live!, 2025b. URL https://arxiv.org/abs/2505.23419.

Qixing Zhou, Jiacheng Zhang, Haiyang Wang, Rui Hao, Jiahe Wang, Minghao Han, Yuxue Yang, Shuzhe Wu, Feiyang Pan, Lue Fan, Dandan Tu, and Zhaoxiang Zhang. FeatureBench: Benchmarking Agentic Coding for Complex Feature Development, 2026. URL https://arxiv.org/abs/2602.10975.

A Related Work

A.1 Executable Benchmarks and Task Construction

Executable software-engineering benchmarks. SWE-bench (Jimenez et al., 2024) evaluates patches for issues in existing repositories. Multi-SWE-bench (Zan et al., 2025) and SWE-PolyBench (Rashid et al., 2025) extend repository-level evaluation across languages, while FeatureBench (Zhou et al., 2026) targets complex feature implementation. SWE-bench Multimodal (Yang et al., 2024b) includes visual software domains, and SWE-Lancer (Miserendino et al., 2025) grounds tasks in paid freelance work. Terminal-Bench (Merrill et al., 2026) broadens evaluation to hard technical tasks in command-line environments. CyberGym (Wang et al., 2026b) verifies vulnerability reproduction by executing generated proof-of-concept inputs. These benchmarks connect realistic work to checkable outcomes. FeatureLoop measures the path to an outcome as requirements accumulate, retaining intermediate implementation, correction, and preservation evidence.

Task construction and verifier quality. SWE-Gym (Pan et al., 2025) provides executable environments for training agents and verifiers. R2E-Gym (Jain et al., 2025) combines procedural environments with hybrid verification; SWE-smith (Yang et al., 2025) scales repository-based training tasks; and SWE-Flow (Zhang et al., 2025a) synthesizes tasks through test-driven construction. EvalPlus (Liu et al., 2023) demonstrates the effect of stronger test coverage on code evaluation, while SWT-Bench (Mündler et al., 2025) evaluates tests that reproduce bugs and validate fixes. FeatureLoop independently constructs tests and reference checkpoints, checks every new behavior across adjacent and later states, and combines executable evidence with human review. Its historical screening complements the fresh-task collection used by SWE-bench-Live (Zhang et al., 2025b) and SWE-rebench (Badertdinov et al., 2025).

A.2 Interaction and Continued Development

Table 2: Interaction and evaluation mechanisms in closely related benchmarks. Cumulative checks retain earlier requirements as active correctness obligations.

Benchmark	Later information	Behavioral evaluation	Interaction measure
SWE-Together	Session-conditioned requests and corrections	Final rubric with execution evidence	User Correction
Asuka-Bench	Feedback from browser checks	Repeated UI criteria	Per-round fix rates
EvoCode-Bench	Fixed instruction sequence	Cumulative tests	Per-round outcomes
LoopsBench	Upfront dependent units	Retained regression tests	Scheduling and loop diagnostics
FeatureLoop	State-conditioned disclosure and correction	Group, prefix, and baseline checks	Message counts and FDAC

Table 2 contrasts how benchmarks obtain later information, check evolving implementations, and measure interaction. The following definitions distinguish information acquisition, corrective feedback, and continued correctness.

Information and feedback. A clarification supplies missing information about an established objective. A new request adds or changes desired behavior. A corrective message reports a failure of already stated behavior. We call feedback *execution-grounded* when the user-facing message is derived from behavioral checks of the current implementation. This identifies the evidence supplied to the agent, separately from whether its final output is evaluated by execution.

Persistent correctness. Cumulative evaluation carries earlier, still-active requirements forward as correctness obligations. In FeatureLoop, requirement sets grow monotonically, so every introduced behavior remains active. Local checks identify whether the latest behavior works; cumulative checks require all active groups to work together; the baseline suite additionally checks retained repository behavior.

Ambig-SWE and ICAE-Bench: obtaining missing information. Ambig-SWE (Vijayvargiya et al., 2026) removes information from repository issues and lets an agent ask a user proxy for clarification. ICAE-Bench (Peng et al., 2026) starts from underspecified product requests and uses a constrained router to reveal information from a fixed product contract. Both make information acquisition part of the agent's task. In FeatureLoop, the controller visits a fixed state sequence and discloses requirements according to the behavior still missing from the current workspace.

SWE-Interact and SWE-Together: state-dependent user steering. SWE-Interact (Raghavendra et al., 2026) creates user-driven sessions from benchmark tasks using a simulator that can inspect repository content and changes. SWE-Together (Wu et al., 2026) conditions interventions on real-session evidence and the current trajectory. It distinguishes new requests from corrections, reports User Correction, and uses task-specific final rubrics with an agentic judge that can gather execution evidence. FeatureLoop ties each requirement group to fixed executable checks. Those checks determine both the missing information to disclose and the active failures to report, while intermediate evaluation records completion of individual requirements, all stated requirements, and the repository baseline.

Asuka-Bench: feedback from browser use. Asuka-Bench (Wang et al., 2026a) starts with an underspecified web-development request, checks the resulting interface through browser interaction, and converts the findings into feedback for another revision. Repeated evaluation measures improvement and repair over the interaction. FeatureLoop extends the evaluation setting across existing repositories and multiple software forms, with explicit cumulative requirement states and corrective revisions within each requirement stage. These states connect each message to the behavior that is newly requested or remains unfinished.

EvoCode-Bench and LoopsBench: continued development. EvoCode-Bench (Shen et al., 2026) presents extensions, corrections, conflicts, and supersessions in a persistent workspace. Its verifier retains requirements that remain valid, and its reference-predecessor comparison separates single-round implementation from persistent execution. LoopsBench (Li et al., 2026) organizes work into dependent development units whose activated tests remain regression obligations. FeatureLoop couples continued development to workspace-dependent user intervention: already implemented later behavior skips disclosure, whereas failed active behavior can receive completion feedback. The resulting trajectory records direct repairs and the preservation of earlier success.

Other forms of iterative development. SR-Eval (Zhan et al., 2026) studies stepwise requirement refinement. SlopCodeBench (Orlanski et al., 2026) examines code degradation over iterative development, while SLUMP (Yan et al., 2026) studies faithfulness as specifications emerge. SWE-EVO (Le et al., 2026) constructs multi-step, multi-file tasks from project release notes. At the program level, ConvCodeWorld (Han et al., 2025) compares reproducible feedback environments and distinguishes conversational efficiency from overall task completion. FeatureLoop connects an accumulating requirement sequence to state-dependent disclosure and correction, recording whether each response completes the active requirements and preserves earlier success.

Comparing complete development workflows. Our upfront, progressive, and corrective workflows target the same final contract from the same checkpoint. Each model–task pair is independently executed under all three workflows. A paired comparison measures the change in final outcome between those complete workflows; direct recovery is measured separately within the trajectory that receives the failure report. FDAC summarizes final completion and intermediate timeliness under a fixed discount schedule, while message counts report the actual number of delivered interventions.

A.3 Feedback-Driven Refinement and Repair

Self-Refine (Madaan et al., 2023) iteratively revises outputs using model-generated feedback. Reflexion (Shinn et al., 2023) stores verbal feedback to guide later attempts, and Self-Debugging (Chen et al., 2023) combines execution results with explanations of generated code. Olausson et al. (2024) find that self-repair gains depend on feedback quality and the computation spent obtaining them. These methods motivate treating feedback use as a measurable capability. In FeatureLoop, the repair target is the cumulative repository state: a correction succeeds only at the level specified by its local,

cumulative, or baseline-inclusive check. Previously satisfied behavior remains testable throughout later development.

B Construction Details and Excalidraw Case Study

B.1 From Task Formulation to the Stored Task Record

We extend the notation in Section 2.1 to identify individual revisions. Let $W_{i,0}$ be the first evaluated workspace at requirement state i: either a workspace that already passes before disclosure or the result of the first response. Let $W_{i,r}$ be the workspace after corrective revision r. The task record fixes the complete requirement sequence, and the evaluator delivers requests and feedback according to the current implementation. Table 3 maps the formal objects to the stored components.

Table 3: Mapping the task formulation to the stored task components used during evaluation.

Formal object	Stored task component	Role during evaluation
W_0	Repository checkpoint, frozen environment, and baseline	Gives every evaluated agent the same starting state.
Q_1	First active set of requirement groups	Produces the initial request.
$A_{i+1} = Q_{i+1} \setminus Q_i$	Groups activated at the next state and their use scenario	Provides candidate evolution feedback.
Public observations for groups in Q_i	Observation-to-check mapping	Grounds completion feedback when expressed behavior fails.
$Z_g(W)$	Frozen behavioral checks for group g	Determines whether a requirement is already satisfied.
$b(W)$	Baseline suite for the initial repository	Detects regressions in retained repository behavior.
W_i^*	Reference checkpoint	Demonstrates at least one feasible implementation of Q_i.

For $i < K$, let A_{i+1} denote the groups first activated by the next state. The frozen task record allows the controller to decide whether either type of user intervention is still needed in the current workspace:

$$\begin{aligned} \mathrm{Need}_{\mathrm{C}}(Q_i, W_{i,r}) &= \mathbf{1}[\exists g \in Q_i,\ Z_g(W_{i,r}) = 0]\,, \\ \mathrm{Need}_{\mathrm{E}}(A_{i+1}, W_{i,r}) &= \mathbf{1}[\exists g \in A_{i+1},\ Z_g(W_{i,r}) = 0]\,. \end{aligned} \tag{4}$$

The first indicator identifies failures of active requirements and the evidence used for completion feedback. The second identifies later groups that still need disclosure. The controller applies the protocol's revision budget and advances through the state sequence while retaining earlier obligations. Already implemented behavior is skipped, and partially satisfied groups produce a message covering the remaining behavior. The same development target can therefore require different messages as agents make different progress. Appendix D.5 specifies the treatment of unavailable observations.

B.2 The Complete Excalidraw Task

B.2.1 Provenance and Complete Goal

The case in Figure 1 is a FeatureLoop task titled *Grow and restyle connected Excalidraw shapes*. It is anchored to the public Excalidraw repository at checkpoint `a2ec2889babf7d2295469c6d90ebe77fae57df84` and task revision R003. Its source record joins five public requests: faster node and tree creation (#11508), converting existing shapes (#11585), improved arrows (#11283), blur effects (#11228), and using a shape as a clipping mask (#11349).

The scenario combines these public requests into a diagram-editing workflow: creating connected nodes, changing their types and relations, and preparing the result for sharing. The complete goal is to create a bound child from a selected shape, keep its connector bound and rerouted during dragging, convert shapes in place while preserving text, style, and connections, and compose blur and clipping on the canvas and in standard exports.



Figure 9: The complete six-stage Excalidraw case: successive user requests, illustrative code edits, and cumulative canvas behavior.

B.2.2 Six Cumulative States

The six states build on the same evolving implementation (Figure 9). Table 4 lists the new behavior and cumulative obligations at each state.

B.2.3 Feedback and Requirement Dependencies

The sequence begins with the Grow menu (Q_1), followed by the parent–child relation created through its action (Q_2). Dragging either endpoint makes routing a continuing geometric obligation in Q_3. In-place conversion (Q_4) preserves labels, styles, and bindings. Blur (Q_5) and clipping (Q_6) add product capabilities drawn from the source requests, with serialization, export, and composition included in their acceptance requirements.

These transitions produce evolution feedback only when the newly revealed behavior remains missing. Completion feedback instead stays within the current state. For example, it may report that a child has only one bound arrow endpoint in Q_2, that routing remains at the old position after a drag in Q_3, or that blur appears on the canvas but not in the SVG export in Q_5. The message describes what the user can observe, without exposing a hidden test identifier, internal function, or Reference implementation.

Table 4: The six cumulative states in the Excalidraw task.

State	Behavior made explicit	What must hold in the cumulative workspace
Q_1	Grow menu	A selected fillable shape exposes one contextual Grow entry with child-creation and conversion choices, while the existing context menu retains its entries, predicates, and ordering.
Q_2	Bound child	A child choice creates exactly one non-overlapping shape of the requested type and one arrow bound at both ends; the new elements remain valid after serialization and restoration.
Q_3	Drag-aware routing	The grown connector visibly bends or curves, follows both bound shapes through dragging and a change in relative direction, and leaves manually drawn arrows unchanged.
Q_4	In-place conversion	Converting a shape preserves element count, geometry, style, bound text, and existing arrow bindings; dragging the converted shape still updates and reroutes its connectors.
Q_5	Blur effects	Gaussian and pixelate modes with an adjustable radius survive serialization and appear on the interactive canvas and in image exports; scenes with blur disabled retain their prior rendering.
Q_6	Clipping and composition	A fillable shape clips higher-layer content to its rendered outline, including rotated shapes, while clipping composes with blur, grown children, and bound rerouting connectors.

In this case, each state introduces exactly one requirement group; writing G_i for the group first introduced at state i, the semantic dependencies form the following directed acyclic graph, and the six user-visible stages follow a dependency-respecting disclosure order:

$$G_1 \to G_2 \to G_3, \qquad G_1 \to G_4, \qquad G_1 \to G_5, \qquad \{G_2, G_5\} \to G_6. \tag{5}$$

Direct edges identify prerequisite capabilities. Preservation obligations carry every earlier active behavior forward even without a direct edge. Thus, although clipping directly composes with child creation and blur, success at Q_6 also requires retained rerouting, conversion, and baseline behavior.

B.2.4 Executable Behavioral Evidence

The executable checks cover six parts of the user-visible workflow:

1. **UI and reachability:** Grow, child and conversion choices, Effects, and clipping controls appear under the appropriate selections while existing menu and property-panel behavior remains available.
2. **Scene state:** element counts, types, finite geometry, layer order, bound text, arrow bindings, blur attributes, and clipping-mask state are inspected through public scene representations.
3. **Interaction:** parent and child dragging, direction changes, conversion, and layer reordering exercise the subsequent connector, selection, and mask behavior.
4. **Persistence:** serialize–restore checks preserve new attributes and relations while legacy scenes without them retain their previous semantics.
5. **Rendering and export:** the interactive canvas, SVG export, and canvas export exercise routing, blur, outline-aware clipping, and their composition.
6. **Baseline:** existing context-menu actions, manually created arrows, legacy scenes, frame clipping, and rendering with effects disabled remain valid.

Together, these checks implement $Z_g(W)$ and $b(W)$ and distinguish a failure in the current behavior from a regression in an earlier requirement or the initial repository baseline.

B.3 Construction Process

B.3.1 Repository Sources

To anchor each task in real development needs, the Source Author selects at least two complete public issues that support a common user-facing direction at an exact repository checkpoint. The



Figure 10: Complete author–critic workflow. Solid paths link construction artifacts and execution stages; dashed paths return review findings for revision. The Test and Reference views mark their separate information access.

source record preserves the issue text, user motivation, relevant public interfaces, and supporting repository evidence. An independent reviewer checks that these sources support the proposed target and its scope. Later task components retain links to the accepted sources; the semantic analysis in Appendix C.6 characterizes how closely each increment relates to earlier work.

B.3.2 Feature Specification

To give the construction roles a shared development target, the Feature Author states the complete user outcome, acceptance requirements, scope exclusions, and refinements supported by the accepted sources and repository. A requirement may come directly from a public request, follow the same direction through repository evidence, or describe how existing public capabilities must work together in the same workflow. This specification fixes the task's complete target; the dialogue determines when each part is revealed, and tests are authored separately.

B.3.3 Requirement Sequence

To turn the development target into actionable stages, the Trajectory Author groups related behaviors into nodes of a directed acyclic dependency graph. An edge records a prerequisite relation between groups. The author then selects a stage sequence from Q_1 to Q_K that respects these dependencies. Each state records the groups introduced there, all groups that remain active, direct dependencies, earlier behavior that must remain correct, and the use scenario that exposes the next gap. Source evidence informs a plausible development order; the frozen task record fixes the actual requirements and disclosure sequence used in evaluation.

B.3.4 Executable Environment

To make every stage reproducible, the Environment Author reconstructs an isolated environment from dependency locks, build configuration, and repository continuous-integration records. Validation includes independent clean runs, the original baseline, public entry points, offline execution, resource

limits, and workspace integrity. The runs use the same environment definition but fresh writable workspaces. This definition determines how the task executes reproducibly, while the frozen sources and contract determine its requirements and behavior.

B.3.5 Frozen Contract and Feedback Messages

The Contract Author combines the accepted sources, development target, requirement sequence, and environment into a versioned behavioral specification, called the contract Γ. This specification aligns the requests, tests, and reference implementations. Each group records the user action or input, expected and forbidden outcomes, earlier behavior that must remain correct, allowed implementation freedom, and a runnable check. An independent Contract Reviewer checks that the contract follows the sources, respects state dependencies, can be observed through public interfaces, leaves implementation choices open, and runs in the environment; deterministic validation checks the schema and every referenced file or check.

After Γ is frozen, a Dialogue Author produces u_0 and the candidate evolution messages. Review verifies that each message reveals only its corresponding state, is consistent with its documented use scenario, and contains no group identifier, hidden-test wording, Reference information, or future requirement. Completion feedback does not create a new contract state; it is generated at runtime from failed user-visible checks for currently active groups.

B.3.6 Isolated Test Construction

To evaluate the specified behavior independently of a solution, the Test Author works from the frozen contract, initial repository, environment, and complete state map in a separate workspace. It builds the group and cumulative-state checks, final suite, baseline checks, and transition checks. A Test Critic reviews their behavioral coverage, execution stability, and use of public interfaces. Reference code and execution results remain outside both roles' access.

B.3.7 Historical Implementation Screening

To exclude targets with an already published complete solution, we screened every candidate against public repository history after its checkpoint and before a recorded cutoff. Screening used the frozen Test package and preceded Reference construction. The frozen behavioral checks were replayed on later commits or trees: inexpensive deterministic checks covered the relevant history exhaustively, while expensive checks such as browser execution used recorded targeted coverage. Candidates whose later public history passed the complete recorded behavior set were removed. The screening record preserves the checkpoint, cutoff, searched history, executed checks, coverage, and decision; reviewers checked partial matches and environment incompatibilities individually to determine which behaviors the historical version implemented.

B.3.8 Isolated Reference Construction

To establish a feasible implementation at every stage, the Reference Author receives the frozen contract, initial repository, environment, and state graph in an isolated workspace. Tests, fixtures, assertions, and Test results remain outside its access. Starting from the baseline $W_0^* = W_0$, it constructs $W_1^*, \ldots, W_K^*$ in one persistent workspace, with each checkpoint adding the current requirement while preserving earlier behavior. A Reference Critic with the same restricted information reviews contract coverage, repository consistency, retained behavior, and the boundary between checkpoints.

B.3.9 Cross-State Validation

To verify that each increment is implemented at its intended stage and preserved afterward, the controller runs the frozen Test suite against the Reference checkpoints. For every $g \in A_i$, it requires

$$Z_g(W_{i-1}^*) = 0, \qquad Z_g(W_j^*) = 1 \quad \forall j \geq i. \tag{6}$$

Each checkpoint W_i^* must also pass the complete active suite and repository baseline, and every later checkpoint must preserve that behavior. Selected candidates receive two additional probes: contract-valid alternatives test acceptance across different implementations, and targeted faulty variants test

rejection of specific behavioral defects. The controller executed the constructed variants and recorded their outcomes alongside the required state-by-state checks. Additional checks can reveal defects missed by an original test suite (Liu et al., 2023); running a test against both faulty and corrected versions also assesses whether it distinguishes the intended behavior (Mündler et al., 2025). The two types of probe check complementary errors: rejecting valid behavior and accepting an implementation with a known defect.

B.3.10 Human Review and Task Acceptance

For every accepted task, human review began with the task semantics. Reviewers checked whether the Contract was coherent, source-grounded, observable through the public interface, and permissive of different valid implementations, then verified that its Summary and Evidence records represented the same behavior. They next simulated the evaluation turn by turn. At each turn, they inspected the dialogue shown to the agent, ran the project at the corresponding Reference checkpoint, executed the current and retained tests, and followed the public observation points to confirm that the Reference behavior matched the intended user semantics. They also inspected Test assertions on adjacent checkpoints to verify that each assertion followed from the required public behavior.

The reviewer recorded a final accept, revise, or discard decision with findings tied to the responsible construction stage. A requested change returned to that stage and reran every affected downstream check. Each accepted task revision records the exact Source, Environment, Contract, Summary, Evidence, Dialogue, Test, historical-screening, Reference, Cross, and human-review artifacts, preserving earlier revisions for traceability.

B.4 Roles and Information Boundaries

Table 5 separates the evidence available to each construction role. The key boundary is between Test and Reference: both receive the same approved task semantics and environment, but neither can inspect the other's private implementation or execution results.

Table 5: Construction roles and their information boundaries.

Role	May read	Must not read
Source/Feature	Frozen source records, checkpoint, repository evidence	Private Test or Reference material, or evaluated-agent solution content
Contract	Sources, feature specification, requirement sequence, environment report	Private Test or Reference material, or evaluated-agent solution content
Dialogue	Frozen Contract and user-facing narrative context	Hidden tests, Reference, or future evaluated-agent behavior
Test Author/Critic	Frozen Contract, W_0, environment, complete state map, and same-side Test files	Reference code, diffs, or execution results
Reference Author/Critic	Frozen Contract, W_0, environment, complete state map, and same-side workspace	Tests, fixtures, assertions, or Test results
Adjudicator	Contract, structured execution outcomes, suite summaries, and changed-file summaries	Joint write access or unrecorded transfer of one side's private implementation to the other
Human reviewer	Sources, Contract, Summary and Evidence, Dialogue, Reference checkpoints, Test, and execution records	Unrecorded edits that bypass revision and revalidation

Construction agents combine a foundation model with a workspace harness providing repository search, file editing, terminal execution, tests, and structured output. We use Claude Code, Codex, and CodeBuddy harnesses. Model–harness combinations follow each stage's role and compatibility requirements; repository views, tool permissions, and execution environments enforce the information boundaries.

Table 6 lists the shared model pool. Routing uses the stage's output, task difficulty, review findings, and revision history to select an Author or Critic.

Table 6: Model pool used for agent-assisted benchmark construction.

Tier	Models	Routing role
Low latency	Hy3; DeepSeek V4 Flash	High-throughput generation, organization, and low-risk revision
Medium	DeepSeek V4 Pro; GPT-5.6 Terra	Routine Author work and workspace-based revision
Strong	GLM 5.3; Kimi K3	Difficult Author work, independent semantic checks, and root-cause analysis
Flagship	GPT-5.6 Sol; Claude Opus 5	High-complexity Author work, final independent review, and support for disputed decisions

Strong and flagship models handle difficult semantic review, while low-latency models handle bounded generation and automated checks. Findings that require broader reasoning are escalated to a stronger model or a human reviewer. Deterministic checks govern schemas, artifact links, environment execution, state matrices, and result formatting.

Across semantic stages, Authors produce each stage's complete output from approved upstream evidence, while Critics work in independent contexts and return structured findings about source fidelity, observability, requirement completeness, implementation freedom, and execution evidence. The responsible Author revises that output, after which the stage and every affected later check are rerun. Test and Reference use separate authoring and review sessions and, by default, different model families. Separate repository views and tool permissions enforce this boundary for workspaces, conversation histories, and execution results.

Human reviewers remain responsible for feature direction, scope, interaction naturalness, and test fairness. They audit the Contract together with its Summary and Evidence, replay each dialogue turn at the corresponding Reference checkpoint, run the project and tests, compare the observed public behavior with the observation mapping, and verify that Test enforces the intended semantics. Human-requested changes return to the responsible stage and undergo every affected downstream check. The resulting audit supports the final decision to accept, revise, or discard the task.

B.5 Quality Evidence

Task acceptance combines feasibility, behavioral discrimination, preservation, historical screening, and semantic review. Table 7 specifies the evidence supporting each component.

Acceptance evidence comes from executable observations such as unit or integration tests, CLI or PTY interaction, service calls, browser automation, lifecycle events, restart, and persistence. Some requirements are checked through relations between executions, such as export/import, save/restart/load, encode/decode, idempotence, conservation, or monotonicity. These are metamorphic checks (Segura et al., 2016). Comparisons with an independent reference provide additional evidence. Browser, TUI, and visual tasks remain programmatically checkable when geometry, DOM or public state, pixel relations, or protocol statistics can be recomputed from fixed inputs. Each accepted task records the evidence used for every requirement.

B.6 Revision and Invalidation Rules

A task revision reruns every check whose conclusion may have changed. Table 8 makes this dependency explicit: wording-only edits require dialogue review and an updated evaluator mapping, whereas changes to requirements, environments, tests, or Reference checkpoints invalidate the corresponding executable evidence.

Before revising a task component, reviewers identify the source of a failed Test–Reference execution. A Test defect changes only Test-side files; a Reference defect rebuilds that checkpoint and the later Reference states; ambiguous requirements or states that cannot be separated create a new Contract revision; and environment failures are corrected before the evidence is rerun.

Table 7: Validation roles of the construction evidence.

Evidence	Validation role	Use in task acceptance
Historical screening	Checks later public repository history within a recorded cutoff and coverage	Required after Test is frozen and before Reference construction
Reference pass	Establishes a feasible implementation under the frozen Contract and environment	Required at every state
Adjacent-state check	Confirms that newly activated behavior distinguishes adjacent Reference checkpoints	Required for every state transition
Earlier-state suite	Checks earlier active behavior on later Reference checkpoints	Required through the Reference suffix
Baseline suite	Checks retained repository behavior at each Reference checkpoint	Required at every state
Targeted mutation	Probes failure sensitivity for a selected behavioral defect	Executed for constructed targeted faulty versions
Valid alternative	Probes acceptance of a different contract-valid implementation	Executed for constructed valid alternatives
Human review	Audits Contract, Summary and Evidence, dialogue turns, checkpoint behavior, observations, and Test semantics	Required for the final accept, revise, or discard decision

Table 8: Task components that must be updated after a substantive revision.

Modified component	Required regeneration or re-execution
Source or feature specification	Requirement sequence, Contract, Dialogue, Test, historical screening, Reference, Cross, and review
Requirement semantics, dependency, or public observation	New Contract revision and all later semantic components and executable checks
Wording only, with unchanged semantics	Presentation revision, evaluator mapping, and Dialogue review
Environment, dependency, or runner	Baseline, historical screening, Reference execution, and all Cross evidence that uses the environment
Test package	Historical screening and, for retained candidates, all Test–Reference executions
Reference checkpoint W_m^*	Reference suffix beginning at m and its Cross evidence
Feedback-observation mapping	Dialogue and feedback review, controller update, and affected feedback verification

B.7 Versioned Task Record

Every accepted task has a versioned manifest that records its repository and exact checkpoint together with the sources, Contract, Dialogue, environment, frozen Test package, historical-screening cutoff, coverage, and result, Reference checkpoints, final Cross evidence, and human-review decision. An update to requirements or executable conclusions creates a new revision and regenerates the affected downstream evidence; prior revisions remain unchanged. The FeatureLoop Excalidraw record links its task revision, environment, Test package, Reference sequence, and Cross evidence, allowing every state in Table 4 to be traced to the corresponding task record.

C Dataset Composition and Quality Evidence

This appendix reports the quality evidence and detailed composition behind Section 2.4. All dataset statistics use the final set of 61 FeatureLoop tasks.

Table 9: Distribution of the number of cumulative states per task.

States K	Tasks	States	Transitions	Acceptance checks
2	33	66	33	153
3	5	15	10	15
4	6	24	18	51
5	4	20	16	27
6	10	60	50	163
7	2	14	12	14
8	1	8	7	8
Total	61	207	146	431

C.1 Trajectory Review and Final Selection

Construction and initial human review produced 123 executable candidates with runnable task artifacts and state-by-state execution evidence. Hy3, DeepSeek V4 Flash, DeepSeek V4 Pro, and GLM 5.3 then ran every candidate under multiple protocols. Reviewers examined the complete messages, workspace changes, requirement-level scores, repeated runs, and execution errors, and compared failures with the frozen semantics and evidence.

Historical screening was completed after Test construction and before Reference construction (Appendix B.3.7). Each admission decision then replayed the dialogue and every Reference checkpoint, including the project, tests, and public observation points (Appendix B.3.10). Two independent automated checks by Hy3 and DeepSeek V4 Flash complemented this review. Confirmed task defects returned to the responsible stage, after which affected checks and model runs were repeated. The final 61 tasks passed this process and final human acceptance.

C.2 Language and Software-Form Coverage

FeatureLoop contains 19 Go, 15 Rust, 10 JavaScript, 9 TypeScript, 7 Python, and one Go/TypeScript task. Its software forms comprise 21 CLI, 13 service, ten TUI, seven browser, seven library, two framework, and one embedded task. These attributes describe overlapping repository settings: 14/15 Rust tasks are CLI tasks, 6/9 TypeScript tasks are browser tasks, and Go spans service, TUI, and CLI software (Figure 4(a)).

C.3 Requirement States and Acceptance Checks

For a task with K cumulative requirement states, adjacent states define $K - 1$ possible evolution transitions. Whether the associated feedback is delivered depends on the behavior already present in the agent's current workspace.



Figure 11: Acceptance-check distributions. (a) Checks per task by state count K; dots are tasks, ticks mark medians. (b) Checks per requirement group.

Table 10: Software form, number of states, and executable checks.

Form	Tasks	States	Mean K	Median K	$K \geq 5$	Checks
Browser	7	27	3.86	4	3	121
CLI	21	86	4.10	4	10	132
Embedded	1	2	2.00	2	0	4
Framework	2	12	6.00	6	2	12
Library	7	24	3.43	3	1	32
Service	13	29	2.23	2	0	52
TUI	10	27	2.70	2	1	78

Table 11: Executable checks and Reference edits by requirement-state position. Each row averages tasks that reach the corresponding state. Test LOC counts nonblank lines in the cumulative Test suite; Reference ΔLOC counts additions plus deletions from the base checkpoint.

State	Tasks	Test groups	Test LOC	Reference ΔLOC
1	61	1.15	101.8	82.9
2	61	2.28	212.2	180.5
3	28	4.04	408.1	394.0
4	23	5.61	598.8	563.5
5	17	6.47	732.8	557.2
6	13	8.08	804.8	608.9
7	3	7.00	827.7	457.7
8	1	8.00	863.0	465.0
Final	61	4.11	402.2	337.8

The 17 tasks with $K \geq 5$ account for 102/207 states and 85/146 possible transitions (Table 9). Ten six-state tasks contain 163 acceptance checks (37.8% of all checks), as shown in Figure 11(a). The number of states and the number of checks describe different aspects of task size.

The 207 states contain 209 requirement groups because a few states introduce more than one related group. The 431 acceptance checks correspond to a mean of 7.07 per task (median 5, range 2–32) and 2.06 per requirement group (median 1, range 1–9). As Figure 11(b) shows, 120/209 groups (57.4%) have one check, while 57/209 (27.3%) have at least three. The correlation between a task's state count and acceptance-check count is 0.49, so neither quantity alone captures how much behavior a task contains. Table 10 also shows that tasks with more states are concentrated in particular software forms.

C.4 Executable Evidence across Requirement States

We measure three quantities at each requirement state. *Test groups* counts groups in the cumulative suite. *Test LOC* counts nonblank lines in the unique source files used by that suite. *Reference ΔLOC* is the sum of additions and deletions relative to the initial checkpoint, including replacements.

A state-i mean uses tasks with $K \geq i$. The final-state summary uses the last checkpoint of all 61 tasks. Table 11 reports the means, and Figure 12 shows their task-level distributions and the relation between Test and Reference edit volume.

C.5 Repository Coverage

The 61 tasks come from 34 repositories. Twenty repositories contribute one task, the largest contributor contains six (9.8%), and the three and five largest contributors account for 23.0% and 32.8% of the benchmark, respectively (Figure 13). Table 12 gives the exact language, software form, state counts, and acceptance checks for every repository. Repository-clustered uncertainty estimates preserve these within-repository groups when resampling model outcomes.



Figure 12: Final-state executable evidence across 61 tasks. (a) Task-level values on a log scale, with interquartile ranges and medians. (b) Final Test LOC versus Reference ΔLOC, colored by state count K.



Figure 13: Tasks per repository. Both columns use the same count scale; blue marks indicate multiple-task repositories and teal marks indicate singletons.

C.6 Semantic Composition of Later Requirements

We audited all 147 later requirement groups to characterize the information available before disclosure. The rubric separates support for a general direction from support for the exact tested behavior. It also records the effect of the missing behavior on prior delivery, distance from the preceding workflow, discovery depth, implementation burden, and premature-commitment risk. The resulting labels stratify the trajectory analysis; task definitions and scores are fixed independently.

C.6.1 Two-stage annotation from the information available before each request

The annotation uses two stages to assess prior information separately from the later requirement. First, the auditor reads the information available to the agent before the target group is disclosed, referred to as the *prefix*. Assuming the previously requested behavior is implemented correctly, it records up to three plausible follow-up directions. Second, the target requirement and its behavioral

Table 12: Repository inventory for the 61 FeatureLoop tasks. "States" lists the number of cumulative requirement states for each task; "Checks" is the repository-level total of executable acceptance checks.

Repository	Tasks	Language	Form	States	Checks
micro-editor/micro	6	Go	TUI	6,2,2,2,2,2	62
sharkdp/bat	5	Rust	CLI	5,6,2,2,2	28
casey/just	3	Rust	CLI	2,3,2	9
gitleaks/gitleaks	3	Go	CLI	2,7,6	19
moment/moment	3	JavaScript	Library	4,4,2	14
prometheus/prometheus	3	Go	Service	4,3,2	12
socketio/socket.io	3	JavaScript	Service	2,2,2	11
typst/typst	3	Rust	CLI	2,5,4	11
1Panel-dev/1Panel	2	Go; Go/TS	Service	2,2	4
apache/echarts	2	TypeScript	Browser	2,2	20
gofiber/fiber	2	Go	Service	2,2	14
iamkun/dayjs	2	JavaScript	Library	2,3	8
pallets/click	2	Python	CLI	8,6	31
Textualize/textual	2	Python	TUI	2,3	7
chartjs/Chart.js	1	TypeScript	Browser	2	3
ChatGPTNextWeb/NextChat	1	TypeScript	Browser	6	30
dandavison/delta	1	Rust	CLI	5	5
excalidraw/excalidraw	1	TypeScript	Browser	6	32
fatedier/frp	1	Go	Service	2	4
Fission-AI/OpenSpec	1	TypeScript	CLI	6	17
gin-gonic/gin	1	Go	Service	2	5
Leaflet/Leaflet	1	JavaScript	Browser	4	24
mui/material-ui	1	JavaScript	Library	7	7
nuxt/nuxt	1	TypeScript	Framework	6	6
PrefectHQ/prefect	1	Python	Service	2	2
rtk-ai/rtk	1	Rust	CLI	6	6
sipeed/picoclaw	1	Go	Embedded	2	4
slidevjs/slidev	1	TypeScript	Browser	5	12
solidjs/solid	1	TypeScript	Framework	6	6
spf13/cobra	1	Go	Library	2	3
sxyazi/yazi	1	Rust	TUI	2	2
Textualize/rich	1	Python	TUI	4	7
Wilfred/difftastic	1	Rust	CLI	2	3
yt-dlp/yt-dlp	1	Python	CLI	3	3

contract are revealed, and the auditor assigns the eight labels. Reference-code changes are available at this stage to assess implementation burden.

Each judgment concerns the information available immediately before that group, including requests made during earlier turns. Implementation burden is assessed from the changes needed to satisfy the behavior. The evidence contains 138 reference diffs for individual increments and nine cumulative diffs used when an isolated increment is unavailable.

C.6.2 Annotation provenance and review

Three coding agents produced the initial annotations in batches of 49. In the first batch, the instructions enforced the two-stage reading order within a shared packet. The third batch used separate prefix and target packets and saved the first-stage output before revealing the target. Nine prefix packets in the second batch initially included the target because of an indexing error. We replaced those predictions: after correcting the generator, a fresh annotator read the corrected prefixes without seeing the targets. All 49 corrected packets were checked, and the nine replacement predictions were incorporated into the final labels.

One author reviewed all 147 items. A secondary model-assisted consistency audit then examined every item without solver identities, trajectories, pass/fail outcomes, scores, or rankings. It confirmed 134 items and recorded 13 changes: three substantive semantic corrections, one schema-delimiter correction, and nine provenance corrections for the replaced predictions. Six earlier adjudication

overrides are also retained in the review record. The final version, `semantic-v2-final`, resolves all 147 items. Confidence is high for 65, medium for 81, and low for one; 11 items have mixed semantics.

Thus every item received an initial model annotation, author review, and a second consistency check that hid the evaluated agents' identities and item-level results.

C.6.3 Rubric and cohort definitions

Table 13 defines the eight dimensions. Levels are ordered within each dimension. Separating need foreseeability from exact-contract determinacy accommodates requirements whose direction is evident while their API, default, output format, or policy remains open.

Table 13: Semantic annotation dimensions. The primary evolution type T is categorical; the other axes use ordered levels.

Axis	Question	Levels used in the audit
N	Is the need foreseeable?	0: new direction; 1: weakly suggested; 2: a small set of natural continuations; 3: already entailed.
X	Is exact behavior determined?	0: new information; 1: several plausible contracts; 2: key behavior constrained; 3: essentially fixed.
G	How incomplete is prior delivery?	0: no gap in stated scope; 1: limited gap; 2: material gap; 3: blocked core use.
W	How far is the new workflow?	0: same behavior; 1: same feature; 2: adjacent workflow; 3: only repository/product-level adjacency.
D	What reveals the need?	0: static reasoning; 1: basic trial; 2: realistic workflow; 3: edge cases or lifecycle use; 4: new user information.
T	What kind of evolution?	Ten categories covering completion, extension, composition, compatibility, robustness, lifecycle, observability, policy, and independent capability.
B	How much implementation work?	0: trivial; 1: bounded local change; 2: coupled implementation; 3: architectural change.
C	What is the risk of guessing?	0: low; 1: bounded or opt-in; 2: high-cost commitment to defaults, formats, policy, or shared behavior.

Table 14: Requirement cohorts used to analyze prior information. The strict proactive cohort is a subset of the direction-foreseeable cohort. Later-information identifies a type of requirement and applies across development scenarios.

Cohort	Rule	Groups	Interpretation
Direction foreseeable	$N \geq 2$	42	Prior support for the need's direction
Strict proactive	$N \geq 2,\ X \geq 2,\ C \leq 1$	16	Enough support for exact, low-risk coverage
Directional, underdetermined	$N \geq 2,\ X \leq 1,\ C \leq 1$	25	Direction supported, exact contract unclear
Later-information	$N = 0$ or $D = 4$	85	New direction or information unavailable earlier

Forty-two groups (28.6%) have a strongly supported direction, but only 16 (10.9%) meet the strict proactive criterion. The later-information cohort contains 85 groups (57.8%). The remaining 20 fall outside both the 42-group direction-foreseeable cohort and the 85-group later-information cohort. Implementation burden is coupled or architectural for 93 groups (63.3%); premature commitment is high-risk for 40 (27.2%). These cohorts identify when earlier implementation is supported by the available information and when completing the task requires further input.

Workflow breadth. Thirty-two groups have workflow-distance label $W3$: they share the repository or product with the preceding request and introduce a distinct capability. For example, one 1Panel

task combines OpenResty module validation with a duration-formatting helper. The corpus therefore spans both closely connected feature increments and broader cumulative repository development.

Figure 14: Need foreseeability (N) and exact-contract determinacy (X) across 147 later requirement groups. Cells are group counts. The outlined region has $N \geq 2$ and $X \geq 2$; the additional commitment-risk filter $C \leq 1$ selects the 16-group strict proactive cohort.

C.6.4 Complete label inventory

Table 15 lists all 147 final labels, identified by repository and the suffix of `REQEVO-LATER-`. Q/G gives the state and group number. Numeric columns give the level on each axis; + marks mixed semantics, and H/M/L indicates confidence. Evolution types are CC (contract completion), IE (interface extension), WE (workflow extension), CO (composition), CP (compatibility), RO (robustness), SL (state lifecycle), EO (error observability), PP (policy preference), and OC (orthogonal capability).

Table 15: Complete semantic labels for all 147 later requirement groups. See Table 13 for axis meanings.

ID	Repository	Q/G	N	X	G	W	D	B	C	T	Mix	Conf.
1	1Panel	2/2	0	0	0	3	4	1	1	OC	–	H
2	1Panel	2/2	0	0	0	3	4	1	1	OC	–	H
3	NextChat	2/2	1	0	0	1	4	2	1	IE	–	M
4	NextChat	3/3	1	0	0	1	4	3	1	IE	–	M
5	NextChat	4/4	1	0	0	2	4	3	1	WE	–	M
6	NextChat	5/5	3	1	3	0	3	2	0	EO	+	M
7	NextChat	6/6	0	0	0	2	4	2	1	PP	–	H
8	OpenSpec	2/2	0	0	0	2	4	2	1	WE	–	H
9	OpenSpec	3/3	2	1	2	0	2	3	2	SL	–	M
10	OpenSpec	4/4	1	0	1	1	4	2	2	WE	–	H
11	OpenSpec	5/5	0	0	0	2	4	2	1	WE	–	H
12	OpenSpec	6/6	0	0	0	2	4	2	1	WE	–	H
13	Leaflet	2/2	0	0	0	3	4	1	1	OC	–	H
14	Leaflet	3/3	0	0	0	3	4	3	1	OC	–	H
15	Leaflet	4/4	1	0	1	1	4	2	1	SL	–	M
16	prefect	2/2	2	1	3	0	0	1	0	RO	–	M
17	rich	2/3	0	0	0	2	4	1	1	IE	–	H
18	rich	3/4	1	0	1	2	2	2	1	CO	–	M
19	rich	4/5	1	0	0	1	4	2	1	WE	+	M
20	textual	2/2	1	0	0	2	3	2	1	SL	–	H

Table 15 continued

ID	Repository	Q/G	N	X	G	W	D	B	C	T	Mix	Conf.
21	textual	2/2	0	0	0	3	3	1	0	RO	–	H
22	textual	3/3	0	0	0	3	3	1	0	RO	–	H
23	difftastic	2/2	1	0	0	2	4	2	1	WE	–	M
24	echarts	2/2	3	2	3	0	2	2	0	CC	+	M
25	echarts	2/2	3	2	3	0	2	3	0	CC	–	H
26	just	2/2	1	0	0	1	4	2	1	IE	–	M
27	just	2/2	1	0	0	1	4	2	1	PP	–	M
28	just	3/3	0	0	0	3	4	2	1	OC	–	H
29	just	2/2	0	0	0	3	4	1	1	OC	–	H
30	Chart.js	2/2	0	0	0	3	4	1	0	OC	–	H
31	delta	2/2	1	0	1	1	2	3	1	PP	–	M
32	delta	3/3	1	0	1	1	3	3	1	RO	–	M
33	delta	4/4	3	3	3	0	1	3	0	CP	–	H
34	delta	5/5	2	1	2	1	0	1	0	CC	–	M
35	excalidraw	2/2	3	2	3	0	1	3	1	CC	+	H
36	excalidraw	3/3	1	0	2	0	1	2	1	CC	+	L
37	excalidraw	4/4	3	2	3	0	1	3	1	CC	+	H
38	excalidraw	5/5	0	0	0	3	4	3	2	OC	–	H
39	excalidraw	6/6	1	0	0	1	4	3	2	IE	–	M
40	frp	2/2	1	0	1	2	2	2	2	WE	–	M
41	gin	2/2	0	0	0	3	3	1	0	RO	–	H
42	gitleaks	2/2	1	0	0	0	2	2	2	CO	–	M
43	gitleaks	2/2	1	0	0	2	4	2	2	WE	–	M
44	gitleaks	3/3	0	0	0	2	4	1	2	WE	–	H
45	gitleaks	4/4	1	0	1	2	4	2	1	IE	–	M
46	gitleaks	5/5	1	0	1	2	3	2	1	RO	–	M
47	gitleaks	6/6	2	1	2	0	2	2	2	CP	+	M
48	gitleaks	7/7	0	0	0	2	4	1	0	IE	–	H
49	gitleaks	2/2	0	0	0	2	4	2	2	WE	–	H
50	gitleaks	3/3	2	1	1	0	3	2	2	CO	–	M
51	gitleaks	4/4	0	0	0	2	4	1	1	IE	–	H
52	gitleaks	5/5	2	1	2	0	3	1	0	EO	–	M
53	gitleaks	6/6	1	0	0	1	4	2	1	PP	–	M
54	fiber	2/2	0	0	0	3	4	1	1	OC	–	H
55	fiber	2/2	1	0	0	3	4	2	0	SL	–	H
56	dayjs	2/2	1	0	0	1	4	1	1	IE	–	H
57	dayjs	2/2	2	2	2	0	1	2	0	CC	–	M
58	dayjs	3/3	2	2	2	0	2	2	0	CO	–	M
59	micro	2/2	1	0	0	1	4	2	1	WE	–	M
60	micro	3/3	1	0	0	1	4	2	1	WE	–	M
61	micro	4/4	1	0	0	2	4	2	2	WE	–	M
62	micro	5/5	2	2	2	0	2	1	1	CP	–	M
63	micro	6/6	1	0	1	2	2	2	2	SL	–	M
64	micro	2/2	0	0	0	3	4	0	0	OC	–	H
65	micro	2/2	0	0	0	3	4	1	1	PP	–	H
66	micro	2/2	0	0	0	3	4	1	1	OC	–	H
67	micro	2/2	0	0	0	3	4	1	2	OC	–	H
68	micro	2/2	0	0	0	3	4	2	1	OC	–	H
69	moment	2/2	1	0	0	1	3	2	1	PP	–	M
70	moment	3/3	3	1	2	0	3	2	1	CO	+	M
71	moment	4/4	3	3	3	2	2	2	0	CC	–	H
72	moment	2/2	2	1	1	0	3	1	0	RO	–	M
73	moment	3/3	1	0	0	1	4	2	1	IE	–	M
74	moment	4/4	1	0	0	1	4	2	1	EO	–	H
75	moment	2/2	0	0	0	3	4	1	1	OC	–	H

Table 15 continued

ID	Repository	Q/G	N	X	G	W	D	B	C	T	Mix	Conf.
76	material-ui	2/2	2	1	2	1	1	2	1	CC	–	M
77	material-ui	3/3	1	0	0	1	4	2	1	PP	–	M
78	material-ui	4/4	1	0	0	1	4	2	1	PP	–	H
79	material-ui	5/5	1	1	0	2	2	1	0	CC	–	M
80	material-ui	6/6	1	1	0	2	2	1	2	CC	–	M
81	material-ui	7/7	1	0	0	1	4	2	1	IE	–	H
82	nuxt	2/2	3	3	3	0	1	2	0	CC	–	H
83	nuxt	3/3	2	1	1	0	3	1	2	CP	–	M
84	nuxt	4/4	1	0	0	2	4	2	2	PP	–	H
85	nuxt	5/5	1	0	1	2	2	2	2	IE	–	M
86	nuxt	6/6	0	0	0	2	4	2	2	IE	–	H
87	click	2/2	1	0	0	2	4	2	1	WE	–	M
88	click	3/3	2	1	1	2	2	2	2	CO	–	M
89	click	4/4	1	0	0	2	4	2	2	IE	–	H
90	click	5/5	2	1	2	1	3	1	1	CO	+	M
91	click	6/6	1	0	0	2	4	1	2	RO	–	M
92	click	7/7	0	0	0	2	4	3	2	IE	–	H
93	click	8/8	1	0	0	2	4	2	1	IE	–	H
94	click	2/2	1	0	0	2	4	2	1	WE	–	M
95	click	3/3	1	0	0	2	4	2	2	IE	–	H
96	click	4/4	2	1	1	1	2	2	2	EO	–	M
97	click	5/5	0	0	0	3	4	1	2	OC	–	H
98	click	6/6	1	0	0	2	4	3	2	IE	–	H
99	prometheus	2/2	1	0	0	1	4	1	1	WE	–	M
100	prometheus	3/3	2	1	0	1	3	1	0	RO	–	M
101	prometheus	4/4	1	0	0	1	4	1	1	IE	–	M
102	prometheus	2/2	2	2	2	0	2	1	0	EO	–	M
103	prometheus	3/3	0	0	0	3	4	3	1	OC	–	H
104	prometheus	2/2	0	0	0	2	3	1	0	RO	–	H
105	rtk	2/2	2	2	0	2	2	0	1	WE	–	H
106	rtk	3/3	1	0	0	2	4	2	1	IE	–	M
107	rtk	4/4	1	1	0	1	2	1	1	IE	–	M
108	rtk	5/5	1	0	0	2	4	2	1	IE	–	M
109	rtk	6/6	1	0	0	2	4	2	2	IE	–	M
110	bat	2/2	2	1	1	0	2	2	1	CC	–	M
111	bat	3/3	0	0	0	3	4	1	1	OC	–	H
112	bat	4/4	0	0	0	3	3	1	0	RO	–	H
113	bat	5/5	0	0	0	3	4	2	2	PP	–	H
114	bat	2/2	0	0	0	3	4	2	2	OC	–	H
115	bat	3/3	0	0	0	3	2	1	0	RO	–	H
116	bat	4/4	0	0	0	3	4	2	2	PP	–	H
117	bat	5/5	1	0	0	1	4	1	2	CP	–	M
118	bat	6/6	2	2	1	2	0	1	0	CC	–	H
119	bat	2/2	0	0	0	3	4	2	1	PP	–	H
120	bat	2/2	1	0	0	2	2	2	1	PP	–	M
121	bat	2/2	0	0	0	3	4	1	1	OC	–	H
122	picoclaw	2/2	1	0	0	2	3	1	0	RO	–	M
123	slidev	2/2	2	1	2	1	1	2	2	CC	–	M
124	slidev	2/3	2	1	1	1	1	2	1	IE	–	M
125	slidev	3/4	1	0	0	1	2	0	1	IE	–	M
126	slidev	4/5	1	0	0	2	3	1	0	SL	–	M
127	slidev	5/6	2	2	2	2	2	1	1	CO	–	H
128	socket.io	2/2	2	1	1	1	2	2	1	WE	–	M
129	socket.io	2/2	0	0	0	3	3	1	1	EO	–	H
130	socket.io	2/2	0	0	0	3	3	1	2	IE	–	H

Table 15 continued

ID	Repository	Q/G	N	X	G	W	D	B	C	T	Mix	Conf.
131	solid	2/2	2	1	2	1	2	2	1	WE	–	M
132	solid	3/3	3	1	3	0	2	2	0	CC	–	M
133	solid	4/4	2	1	2	2	3	3	1	CO	–	M
134	solid	5/5	2	1	1	1	2	2	1	SL	–	M
135	solid	6/6	2	2	2	0	0	1	0	CC	+	M
136	cobra	2/2	0	0	0	3	3	1	0	RO	–	H
137	yazi	2/2	1	0	0	1	4	1	1	IE	–	M
138	typst	2/2	2	2	2	0	2	2	2	CC	–	M
139	typst	2/2	2	1	1	0	2	2	1	RO	–	M
140	typst	3/3	1	0	0	2	4	2	2	WE	–	M
141	typst	4/4	1	0	0	2	3	2	2	RO	–	M
142	typst	5/5	1	0	0	1	4	2	1	IE	–	M
143	typst	2/2	1	0	0	2	3	3	2	IE	–	M
144	typst	3/3	1	0	0	2	4	3	2	IE	–	M
145	typst	4/4	1	0	0	1	4	3	2	WE	+	M
146	yt-dlp	2/2	2	1	2	0	3	1	0	RO	–	M
147	yt-dlp	3/3	3	3	3	0	3	0	0	CC	–	H

D Experimental Details and Protocol Implementation

D.1 Evaluated Models

We evaluate 12 models, with one result for each of the 61 tasks under each of the three workflows: 2,196 model–task–workflow runs in total. Table 16 records the releases or major updates used to define this July–September 2026 cohort and links the corresponding provider documentation.

Table 16: Evaluated models and their release or update dates. Dates use year–month–day or year–month. The linked pages identify the model. DeepSeek V4 dates refer to updates after the earlier preview.

Model	Provider	Release date	Source
DeepSeek V4 Flash	DeepSeek	2026-07-31	Model record
DeepSeek V4 Pro	DeepSeek	2026-08-13	Model record
DeepSeek V4.1 Flash	DeepSeek	2026-09-10	Model record
GLM 5.3	Zhipu AI	2026-08-19	Model record
GLM 5.3 Flash	Zhipu AI	2026-08-26	Release note
Hy3	Tencent Hunyuan	2026-07-06	Release note
Kimi K3	Moonshot AI	2026-07-19	Release note
Qwen 3.8 Flash	Alibaba Qwen	2026-08-26	Model record
GPT-5.6 Sol	OpenAI	2026-07-09	Release note
GPT-6 Astra	OpenAI	2026-09-03	Release note
Grok 4.6	xAI	2026-08-12	Release note
Hy4-Preview	Tencent Hunyuan	2026-08-28	Release note

D.2 Harness and Runtime Configuration

Agent interfaces affect repository-task performance (Yang et al., 2024a). We therefore use Claude Code 2.1.74 as the shared coding harness for all 2,196 model–task–scenario runs. Workspaces are isolated across model–task–protocol runs. Within each progressive run, the writable repository and conversation persist throughout development. The active context window is 200,000 tokens, with high reasoning effort where supported by the model route. Sampling uses each provider's default temperature and top-p. Table 17 records the shared configuration.

Table 17: Execution settings. A response can contain multiple model calls and tool interactions.

Setting	Value
Coding harness	Claude Code 2.1.74
Context window	200,000 tokens per active context
Reasoning effort	High in the recorded configuration
Temperature / top-p	Provider defaults
Full budget	One complete coding-agent session
Evo budget	One coding-agent response per disclosed state
Evo+Comp budget	Initial response and at most two completion revisions per state
Feedback generator	Hy4-Preview, high reasoning effort
Feedback-generation limit	20,000 tokens per generation
Observation selection	At most two predefined public observations per message
Evaluation environment	Frozen task environment; network-disabled execution

A complete run contains repeated model invocations and context reuse. The context limit applies to the active context of an invocation; Agent Tokens accumulates reported input and output tokens over every call in the run.

Feedback quality and revision compute affect code-repair outcomes (Olausson et al., 2024). To standardize these aspects, completion feedback is generated by a fixed Hy4-Preview model with high reasoning effort and a 20,000-token generation limit. Its input contains the current public check status and the task's predefined mapping from failed checks to observable problems. It selects up to two observations and expresses them as a natural-language report. This limit keeps the amount of information in each report comparable across models and focuses the next revision on a small set of concrete problems. The two-revision limit separately bounds repeated intervention at each stage. Executable checks determine correctness; the generator expresses the resulting evidence to the agent.

D.3 Protocol Execution



Figure 15: Full protocol information flow. Green paths carry requirement disclosures; orange paths carry reports of observed failures. The skip branches bypass behavior already implemented.

All three workflows target the same final requirement set Q_K and start from the same task checkpoint, but each is an independent execution. Their information schedules and opportunities for action differ.

Full Specification (Full). The controller supplies the complete final specification in the opening request. The agent explores, edits, and tests the repository within one coding session. The evaluator then checks the final workspace. This workflow measures implementation from complete upfront information.

Evolution-Only Feedback (Evo). The controller first supplies u_0. After the agent's response, it evaluates the persistent workspace against the next requirement state. Requirements already satisfied need not be disclosed. Otherwise, it supplies the corresponding evolution message and lets the agent modify the same workspace. The process continues through the fixed state sequence. Failures of previously stated behavior do not produce completion messages, but those requirements remain active in all subsequent cumulative checks.

Evolution + Completion Feedback (Evo+Comp). This protocol adds within-state correction. After a response, the evaluator checks the active cumulative requirements. When it obtains attributable failure evidence, the feedback generator expresses up to two predefined observations as a user-facing message. The agent can revise the workspace at most twice at that state. The controller then advances even if requirements remain unmet. Earlier failures remain active obligations in the agent's workspace.

Normal execution path. The controller performs the following steps:

1. Deliver the initial request and obtain a coding-agent response.
2. Execute the current cumulative checks. In Evo+Comp, an observed failure can trigger a completion message and another response, up to the two-revision limit.
3. Before each later disclosure, check the current workspace. Skip already satisfied behavior; otherwise disclose the missing requirement information for that state.
4. Obtain the agent's response, apply the protocol's within-state checking and correction rule, and advance to the next state.
5. After the final state and its permitted revisions, evaluate every active requirement group and the repository baseline.

The generator uses the predefined observations to describe public behavior, such as a command returning the wrong result or an interface failing after a specified action. Hidden test identifiers, assertions, reference code, and future requirements stay outside the message context. After two corrective revisions, the controller proceeds to the next requirement stage and keeps all earlier requirements in the cumulative checks.

D.4 Information and Response Opportunities

Table 18: Information and response opportunities. Earlier requirements remain final acceptance obligations in all protocols.

Protocol	Initial information	Subsequent information	Agent responses
Full	Complete final specification	None	One session
Evo	Initial request	Missing later requirements	One per disclosed state
Evo+Comp	Initial request	Missing later requirements and observed failures of active requirements	First response plus at most two revisions per state

Each comparison matches the same model and task across independently executed workflows. The paired change summarizes the complete development process; direct recovery measures a failed state repaired within one execution.

D.5 Observation Availability and Feedback-Event Accounting

The interaction ledger and the recovery denominator describe different units. The 732 Evo+Comp runs contain 2,484 state records and 1,723 delivered completion messages. Of these states, 733 have an observed first-response failure and qualify as recovery opportunities. One opportunity can receive either one or two messages. Table 19 reconciles these counts.

Table 19: Aggregate feedback-event accounting for Evo+Comp. Recovery eligibility requires an observed first-response failure; message counts record delivery regardless of eligibility.

Messages per state	Recovery-eligible	States	Delivered messages
0	No	1,564	0
1	Yes	95	95
2	Yes	638	1,276
1	No	22	22
2	No	165	330
Total		2,484	1,723

The 187 feedback-bearing states with unavailable first-response observations contribute 352 messages. The controller records typed execution or suite-availability outcomes for these states. Message accounting retains the delivered interaction, while recovery analysis uses the 733 observed failures. Terminal scoring uses each run's final execution result.

Metric-specific projections select the observations required by each definition. FDAC uses 2,390 states with usable scoring observations. The state-outcome summary contains 151 unobserved records and 140 delayed solutions; recovery additionally requires an observed first-response failure, selecting 113 repairs. Appendix E.6 defines the recovery unit, and Appendix E.3 gives FDAC's coverage rule.

E Metrics and Statistical Analysis

All metrics use the frozen task definitions and recorded trajectories. A model–task–protocol run is the unit of terminal evaluation. A requirement state is the unit of controller interaction and direct recovery. Requirement groups are the units of local correctness and the semantic analysis. The 207 states contain 209 groups, and the 146 later states contain 147 later groups.

E.1 Final Task Completion

For model m, task τ, and protocol p, let W_T be the final workspace, $b(W_T)$ its baseline result, and $Z_g(W_T)$ the result for requirement group g. Then

$$\mathrm{StrictPass}_{m,p}(\tau) = \mathbf{1}\left[b(W_T) = 1 \ \wedge \bigwedge_{g \in Q_K} Z_g(W_T) = 1\right]. \tag{7}$$

The model's StrictPass rate is the mean over 61 tasks. Partial completion is

$$\mathrm{NodeCredit}_{m,p}(\tau) = \frac{1}{|Q_K|} \sum_{g \in Q_K} Z_g(W_T). \tag{8}$$

NodeCredit gives each task equal weight and retains partial requirement completion. StrictPass additionally requires every group and the repository baseline to pass.

E.2 Initial Delivery

Initial-delivery results use runs with progressive requests and no corrective feedback. Let $\mathrm{precheck}_i$ indicate that a state passes at the pre-disclosure check, and let $\mathrm{firstpass}_i$ indicate that it passes after the first agent response at that state. Initial Usable Delivery (IUD) is

$$\mathrm{IUD}(\tau) = \mathbf{1}[\mathrm{precheck}_1 \vee \mathrm{firstpass}_1]. \tag{9}$$

It measures usability within the initial evaluation window, including pre-existing behavior. Initial Complete Delivery (ICD) additionally requires every later state to pass before its disclosure:

$$\mathrm{ICD}(\tau) = \mathrm{StrictPass}(\tau)\,\mathrm{IUD}(\tau)\prod_{i=2}^{K}\mathbf{1}[\mathrm{precheck}_i]. \tag{10}$$

ICD measures whether the initial delivery already satisfies the task's frozen final requirements. Proactive coverage is analyzed separately using the prior-information cohorts in Appendix C.6.

E.3 Feedback-Discounted Agent Completion

FDAC measures complete delivery while assigning less credit to requirements completed after additional follow-up. Let I_τ contain states whose required observations are usable. For $i \in I_\tau$, define

$$q_i = \begin{cases} 1, & \text{pre-disclosure pass, or initial-state first-response pass,} \\ 0.5, & \text{later-state pass immediately after disclosure,} \\ 0.5 \times 0.4^r, & \text{pass after completion revision } r \in \{1,2\}, \\ 0, & \text{no pass within the state's allowed responses.} \end{cases} \tag{11}$$

The task score is

$$\mathrm{FDAC}(\tau) = \mathrm{StrictPass}(\tau)\left(\prod_{i\in I_\tau} q_i\right)^{1/|I_\tau|}. \tag{12}$$

The geometric mean prevents a long task from being discounted merely by multiplying more factors, but still makes any unresolved usable state decisive. Model-level FDAC averages task scores. The state partition is fixed before evaluation.

Interpretation and edge cases. The state weights encode the benchmark's preference for earlier completion with fewer follow-ups: 1 before a later disclosure or after the initial response, 0.5 after a later disclosure, and an additional factor of 0.4 for each corrective revision. The same revision rule gives an initial state repaired on the first revision a weight of 0.2. A state unresolved within its local budget keeps weight zero even when later work repairs it. Thus FDAC incorporates timely intermediate delivery as well as final correctness.

For a successful three-state trajectory, $q = (1, 0.5, 0.5)$ gives FDAC $0.25^{1/3} \approx 0.630$. One correction at the second state changes this to $q = (1, 0.2, 0.5)$ and FDAC $0.1^{1/3} \approx 0.464$. Missing that state's budget yields $q = (1, 0, 0.5)$ and score zero.

Observation coverage. Across the 732 runs with both feedback types, 2,390 of 2,484 states have the observations required for FDAC. The geometric mean uses these states, with at least one usable state in every run. Table 20 reports per-model coverage.

Table 20: FDAC state coverage. Every model has 207 possible requirement states.

Model	Usable	Omitted
DeepSeek V4 Flash	205	2
DeepSeek V4 Pro	201	6
DeepSeek V4.1 Flash	207	0
GLM 5.3	202	5
GLM 5.3 Flash	197	10
Hy3	184	23
Kimi K3	204	3
Qwen 3.8 Flash	194	13
GPT-5.6 Sol	202	5
GPT-6 Astra	203	4
Grok 4.6	192	15
Hy4-Preview	199	8
Pooled	2,390	94

Partial-credit variant. FDAC-soft replaces strict final success with NodeCredit and uses an arithmetic mean:

$$\text{FDAC-soft}(\tau) = \text{NodeCredit}(\tau)\frac{1}{|I_\tau|}\sum_{i\in I_\tau} q_i. \tag{13}$$

This partial-credit diagnostic combines NodeCredit with the arithmetic mean of the state weights.

E.4 Paired Protocol Transitions

For two protocols, match runs by model and task. A pair is *both pass*, a *rescue* (only the second protocol passes), a *loss* (only the first passes), or *both fail*. The net rate difference is

$$\Delta_{b-a} = \frac{n_{\text{rescue}} - n_{\text{loss}}}{N_{\text{paired}}}. \tag{14}$$

The contrast compares independently executed workflows on matched model–task pairs. Direct repair and code regression are measured separately from within-run execution records.

E.5 Individual Requirement Completion and Cumulative Correctness

For a later group g activated at state i, local success is $Z_g(W)$ and cumulative success is $P_i(W) = \mathbf{1}[\forall h \in Q_i, Z_h(W) = 1]$ on the same workspace. The event $Z_g(W) = 1, P_i(W) = 0$ identifies a completed current requirement with at least one other stated requirement unfinished. Complete delivery additionally requires baseline preservation: $C_i(W) = b(W)P_i(W)$.

Pre-disclosure coverage checks whether a group already passes before its request. First-response completion evaluates disclosed groups after the agent's first response. Local Repair@2 and Prefix Closure@2 use the same 455 failed later-group instances: the group fails after the first response and its stage receives completion feedback. Local Repair@2 counts a subsequent pass of that group within two revisions. Prefix Closure@2 requires every group introduced so far to pass within the same window. The selected feedback observations concern the stage; an individual failed group may remain unmentioned.

The 147 later groups map to 146 states. Slidev's Q002 introduces two groups, so its execution result contributes one observation to each group. Message counts, token totals, and state recovery count this shared state once. Each metric uses records with the observations required by its definition.

E.6 Feedback Recovery and Requirement Preservation

A state-level recovery opportunity requires an observed first-response failure and completion feedback at that state. Recover@r is the fraction of such opportunities whose recorded cumulative state check passes within r revisions. Recover@1 and Recover@2 share the denominator of 733, including opportunities not recovered within the budget. The complete set of delivered messages is larger and includes fallback events without an attributable first-response observation (Appendix D.5).

Regression testing checks whether changes preserve existing behavior (Yoo & Harman, 2012). Observed retention uses groups that pass at least once and have a check at a later requirement stage. A group is retained when it remains passing at every such observation and at the final checkpoint.

State-Evolution Reliability (SER@r) measures cumulative-state completion along the 685 trajectories with usable results at every later state. A run counts when every cumulative state passes by its recorded checkpoint after at most r revisions. The three checkpoints reuse the same trajectory. Stalled responses add no progress under the cumulative checks; regression events record an earlier passing behavior failing after a later response.

E.7 Conditional Proactive Coverage

Proactive Contract Coverage (PCC) restricts pre-disclosure exact coverage to groups with $N \geq 2$, $X \geq 2$, and $C \leq 1$: sufficient prior support for the need and exact behavior, with limited premature-commitment risk. Labels use the information available immediately before each group is disclosed. Micro PCC pools usable model–group observations; macro PCC averages the within-group rates. The strict cohort comprises 16 groups in 14 tasks.

E.8 Interaction and Token Cost

N_E and N_C count delivered evolution and completion messages after the initial request. Agent Tokens sum the evaluated agent's reported input and output tokens across model calls. Cached-input usage is recorded separately to avoid double counting. These measurements characterize the interaction and solver-side token cost of the development path.

Let $\mathcal{R}_p$ be runs with reported telemetry under protocol p, and T_τ their token totals. We report

$$\mathrm{MeanTokens}_p = \frac{\sum_{\tau \in \mathcal{R}_p} T_\tau}{|\mathcal{R}_p|}, \qquad \mathrm{TokensPerSuccess}_p = \frac{\sum_{\tau \in \mathcal{R}_p} T_\tau}{\sum_{\tau \in \mathcal{R}_p} \mathrm{StrictPass}(\tau)}. \tag{15}$$

Tokens per success includes the cost of failed runs. The reported-telemetry subsets contain 726/732 runs for the upfront specification, 732/732 for progressive requirements, and 731/732 for progressive requirements with correction; their success denominators are 295, 378, and 468. The mean-token comparison uses these reported subsets. Thus the 47.2% increase measures the change in mean reported agent tokens per run.

E.9 Uncertainty and Rounding

Per-model task-completion intervals use the 95% Wilson interval (Wilson, 1927). Pooled rates and workflow differences use 10,000 repository-clustered bootstrap samples with seed 20260923. Resampling retains all tasks and model outcomes belonging to a selected repository, measuring sensitivity to the repository sample. Semantic subgroup sensitivity is reported separately. Percentages and differences are calculated from integer counts or unrounded scores and then rounded for display.

F Complete Results and Model-Level Analysis

The main text groups the results by implementation difficulty, model differences, and resource use. This appendix retains the corresponding event counts, full distributions, conditional populations, and uncertainty estimates. Table 21 provides a direct map from the main findings to their counting units.

Table 21: Observation populations behind the main findings. A requirement group can appear in several model runs; a state may contain several groups. Each row uses its own explicitly defined observation set.

Observation	Population and window	Count	Rate (%)
New requirement implemented	First responses to later-information groups after disclosure	717/927	77.3
Other requirements still unmet	Locally successful first responses above that do not satisfy all stated requirements	76/717	10.6
Complete state repaired	Observed failed states that receive feedback and pass within two revisions	113/733	15.4
Individual requirement repaired	Failed later groups at stages receiving correction, within two revisions	91/455	20.0
Other requirements still unmet after repair	Successful individual repairs above without cumulative completion within the same window	19/91	20.9
Previously correct behavior lost	Passing groups with later-stage observations that subsequently fail	73/642	11.4
User-path verification missing or misdirected	Final failed runs with the corresponding secondary forensic label	198/263	75.3

F.1 Final Task Completion

Final task completion and the path to that result reveal different model profiles (Table 22). GPT-6 Astra records the highest completion rate and feedback-discounted score. GPT-5.6 Sol, Kimi K3, DeepSeek V4 Flash, and DeepSeek V4.1 Flash each complete 43 tasks, while their path scores distinguish the guidance required along the way.

Table 22: Complete results, ordered by FDAC. Model StrictPass cells give successes/61 and percentages (the pooled denominator is 732); NodeCredit, FDAC, and FDAC-soft are percentages. Best observed model values in each column are bold.

	StrictPass ↑			Evo+Comp scores ↑		
Model	Full	Evo	Evo+Comp	NodeCredit	FDAC	FDAC-soft
GPT-6 Astra	**36/61 (59.0)**	**42/61 (68.9)**	**44/61 (72.1)**	82.2	**46.5**	**52.6**
GPT-5.6 Sol	32/61 (52.5)	38/61 (62.3)	43/61 (70.5)	79.3	45.4	51.9
Kimi K3	24/61 (39.3)	33/61 (54.1)	43/61 (70.5)	84.6	44.2	51.6
Hy4-Preview	29/61 (47.5)	32/61 (52.5)	42/61 (68.9)	81.2	42.7	49.6
DeepSeek V4 Flash	23/61 (37.7)	35/61 (57.4)	43/61 (70.5)	82.0	41.2	49.3
DeepSeek V4.1 Flash	26/61 (42.6)	35/61 (57.4)	43/61 (70.5)	**86.5**	40.8	50.3
GLM 5.3	27/61 (44.3)	31/61 (50.8)	40/61 (65.6)	79.0	40.5	47.8
Qwen 3.8 Flash	24/61 (39.3)	29/61 (47.5)	35/61 (57.4)	70.2	37.3	43.8
GLM 5.3 Flash	22/61 (36.1)	30/61 (49.2)	38/61 (62.3)	71.0	37.2	44.1
Grok 4.6	17/61 (27.9)	23/61 (37.7)	39/61 (63.9)	70.3	37.1	41.8
DeepSeek V4 Pro	22/61 (36.1)	30/61 (49.2)	37/61 (60.7)	76.3	36.7	44.8
Hy3	13/61 (21.3)	20/61 (32.8)	22/61 (36.1)	50.1	21.2	27.9
Pooled	**295/732 (40.3)**	**378/732 (51.6)**	**469/732 (64.1)**	**76.1**	**39.2**	**46.3**

Table 23 gives the per-model 95% Wilson intervals. The repository-clustered intervals for pooled final completion are $[29.9, 50.1]$ with an upfront specification, $[41.0, 61.5]$ with progressive requirements, and $[53.8, 72.8]$ with progressive requirements and correction.

Table 23: Per-model 95% Wilson intervals for StrictPass (%).

Model	Full	Evo	Evo+Comp
DeepSeek V4 Flash	26.6–50.3	44.9–69.0	58.1–80.4
DeepSeek V4 Pro	25.2–48.6	37.1–61.4	48.1–71.9
DeepSeek V4.1 Flash	31.0–55.1	44.9–69.0	58.1–80.4
GLM 5.3	32.5–56.7	38.6–62.9	53.0–76.3
GLM 5.3 Flash	25.2–48.6	37.1–61.4	49.7–73.4
Hy3	12.9–33.1	22.3–45.3	25.2–48.6
Kimi K3	28.1–51.9	41.7–66.0	58.1–80.4
Qwen 3.8 Flash	28.1–51.9	35.5–59.8	44.9–69.0
GPT-5.6 Sol	40.2–64.5	49.7–73.4	58.1–80.4
GPT-6 Astra	46.5–70.5	56.4–79.1	59.8–81.8
Grok 4.6	18.2–40.2	26.6–50.3	51.4–74.8
Hy4-Preview	35.5–59.8	40.2–64.5	56.4–79.1

Partial completion also separates models tied on final success. Averaged across all tasks, DeepSeek V4.1 Flash satisfies 86.5% of final requirement groups and Kimi K3 satisfies 84.6%, compared with 82.2% for GPT-6 Astra. Hy3 reaches 50.1%. These values retain progress on runs that fall short of complete delivery.

F.2 Failure Attribution Protocol

We reviewed all 263 final failures in the workflow with both feedback types. The review used the request, feedback, visible agent actions, workspace changes, response-level scores, and final execution evidence. In one exhaustive forensic pass, each failure received a primary label for the earliest supported mistake explaining the later outcome. Independently supported validation and repair problems received secondary labels. Table 24 gives the criteria; the evidence record links each decision to its trajectory.

Secondary labels capture validation aimed at a substitute for the public path, known failures carried forward, and further patching on an already broken workspace. Assignment uses the implementation and execution evidence, with tool calls and agent responses locating the relevant decisions in the trace.

Table 24: Primary-cause taxonomy for final failure attribution.

Code	Cause	Decision criterion
G1	Relevant code not found	The workspace exists, but the agent does not locate or use the relevant implementation area.
G2	User-path connection	Logic exists, but the real API, CLI, UI, registry, lifecycle, or consumer does not use it.
G3	Disclosed branch omitted	A behavior or compatibility branch already expressed to the agent remains unimplemented.
I1	Behavior or API mismatch	The implementation targets the right area but violates the required type, ordering, state, protocol, representation, or timing.
I2	Build, type, or runtime break	The agent's patch prevents compilation, startup, test entry, or execution through the user-facing path.
I3	Inconsistent shared state	Parallel registries, shims, generated interfaces, or state sources become inconsistent.
R3	Earlier behavior regressed	A previously passing behavior is broken by a later change and is not restored.
V3	No relevant implementation	The necessary information and workspace are available, but the run stops without implementing the requested behavior.

F.3 What Causes Final Failures

Table 25 gives the full primary-cause distribution. Behavior or API mismatches, build or runtime failures, and code that does not reach the user-facing path together account for 196/263 failures (74.5%). Build, type, or runtime failures are particularly severe: 65/69 satisfy none of the final requirement groups, whereas 58/70 behavior or API mismatches and 44/57 user-path failures retain partial credit.

Table 25: Primary causes across all final failures under Evo+Comp.

Primary cause	Failures	Share (%)
Behavior or API mismatch (I1)	70	26.6
Build, type, or runtime break (I2)	69	26.2
User-path connection (G2)	57	21.7
Inconsistent shared state (I3)	39	14.8
Disclosed branch omitted (G3)	13	4.9
Earlier behavior regressed (R3)	13	4.9
Relevant code not found (G1)	1	0.4
No relevant implementation (V3)	1	0.4
Total	263	100.0

The secondary labels locate recurring obstacles to repair: 198/263 failures omit a relevant public-path check or validate a substitute, 140 carry a known problem forward, and 59 continue patching before restoring a working version. These traces expose how a run can continue responding to feedback while leaving the user's failing behavior unchanged.

Separating tasks by whether any model solves them distinguishes common limitations from model-specific ones (Table 26). The 38 tasks solved by some models contribute 155 failures, of which 147 have direct execution evidence for the assigned cause. The nine tasks solved by none contribute 108 failures; because no successful peer run is available, their attribution relies on the request, implementation, and observed failing path. Table 27 shows why the distinction matters: inconsistent shared state is concentrated in tasks solved by no model, while behavior mismatches and build failures more often separate models.

F.4 Model-Level Failure Profiles

Task coverage among the tied models. GPT-5.6 Sol, Kimi K3, DeepSeek V4 Flash, and DeepSeek V4.1 Flash each succeed on 43 of 61 tasks. Intersecting their final failed-task sets leaves 10 tasks failed by all four, so the union of their successful-task sets contains $61 - 10 = 51$ tasks. Pairwise disagreement in task outcome ranges from 6 to 14 tasks. These counts are recomputed from the

Table 26: Task groups under Evo+Comp.

Outcome across models	Tasks	Failed runs
All models pass	14	0
Some models pass (1–11)	38	155
No model passes	9	108

Table 27: Detailed primary-cause counts by task group.

Task group	G1	G2	G3	I1	I2	I3	R3	V3
Some models pass ($n = 155$)	1	33	8	46	54	4	8	1
No model passes ($n = 108$)	0	24	5	24	15	35	5	0

263-row final-failure annotation table, with one model–task entry per failed run. They describe complementary coverage across the existing, independently recorded runs.

Equal final success rates conceal different failure sets. Among the four models completing 43/61 tasks, pairwise failure overlap on tasks solved by at least one model ranges from 12.5% to 50.0%, with a median of 20.0%. Figure 7 and Table 28 show which implementation problems account for each model's remaining failures.

Table 28: Grouped primary-cause counts by model. "None / some" separates failures on tasks solved by no model from failures on tasks solved by at least one model.

Model	Failures	None / some	Behavior/API	Build/runtime	User path	Shared state	Other
GPT-6 Astra	17	9 / 8	4	3	5	4	1
GPT-5.6 Sol	18	9 / 9	4	6	4	2	2
Kimi K3	18	9 / 9	7	1	4	4	2
Hy4-Preview	19	9 / 10	6	4	6	2	1
DeepSeek V4 Flash	18	9 / 9	5	4	3	4	2
DeepSeek V4.1 Flash	18	9 / 9	6	0	3	4	5
GLM 5.3	21	9 / 12	10	4	2	3	2
Qwen 3.8 Flash	26	9 / 17	5	8	8	3	2
GLM 5.3 Flash	23	9 / 14	6	8	5	1	3
Grok 4.6	22	9 / 13	3	9	3	3	4
DeepSeek V4 Pro	24	9 / 15	8	5	4	4	3
Hy3	39	9 / 30	6	17	10	5	1

The following profiles connect the numerical comparisons in Tables 28 and 35 to the implementation paths found in the failed runs.

GPT-6 Astra: strong delivery with remaining integration gaps. Remaining failures involve public entry-point integration, exact input representations, and inconsistent shared state. The model has the highest final completion and preserves every requirement in its retention-eligible subset. The broader event record still contains two regressions, outside that narrower retention population. Its remaining failures therefore concern specific end-to-end paths rather than a general inability to implement the requested behavior.

GPT-5.6 Sol: strong terminal results, limited direct recovery. Several unsuccessful traces investigate relevant code without producing a compilable implementation connected to the public interface. The strong final score coexists with a low observed repair fraction once a stage has failed. This profile calls attention to the transition from locating relevant code to validating a working repair, rather than repository exploration alone.

Kimi K3: partial implementations with public-interface gaps. The remaining gap often lies between functioning internal logic and the chart, output representation, or earlier format exposed to the user. Fifteen of its 18 final failures retain partial requirement credit. These traces distinguish incomplete public behavior from a wholly unsuccessful implementation.

Hy4-Preview: repairs coexist with incorrect validation targets. Failed traces include checks of an internal merge component while the live endpoint still uses the old behavior, and configuration changes that never reach rendering. Such checks leave the public failure intact despite progress elsewhere in the code. The issue is which execution path the agent validates, not simply whether it calls a test tool.

DeepSeek V4 Flash: substitute checks miss the default path. Failed traces often check a custom example, an explicitly registered component, or a helper instead of the default renderer, command, or required output. Frequent tool use consequently produces evidence about a substitute execution path. This pattern coexists with a relatively high recovery fraction among the model's observed failed stages.

DeepSeek V4.1 Flash: partial success with compatibility omissions. Legacy calling forms, timing bounds, output representations, and changes to earlier behavior account for the remaining compatibility gaps. Seventeen of its 18 final failures retain partial credit, and none has a build or runtime failure as its primary label. Its profile differs from models whose changes frequently leave the repository unable to execute.

GLM 5.3: exact behavior remains unresolved. Ordering, update timing, error text, naming, and boundary calculations remain incorrect in representative traces after feedback. Behavior or API mismatches account for ten of its 21 final failures. The unresolved work lies in exact public requirements within otherwise relevant implementations.

Qwen 3.8 Flash: build failures and disconnected implementations. Some runs continue using unverified interfaces or adding features after the workspace has stopped working. Build/runtime failures and disconnected public-path implementations each account for eight final failures. Continued activity in those runs does not resolve the problem blocking the requested behavior.

GLM 5.3 Flash: incomplete migrations affect later work. Traces include partial data-structure migrations and guessed signatures followed by unresolved compiler errors. Fourteen of the 23 final failures satisfy no final requirement group. An incomplete interface change can therefore affect both the current requirement and subsequent development, rather than remaining a local defect.

Grok 4.6: frequent recovery with subsequent regression. The model's relatively high repair fraction coexists with weak preservation of already working requirements. The NextChat trace in Appendix F.5 illustrates the contrast: an early repair is followed by a runtime error that persists while later capabilities are added. Responding effectively to some corrections does not ensure that the repaired implementation remains usable through later edits.

DeepSeek V4 Pro: unresolved obligations persist across stages. Some runs add new functionality while earlier command, interface, count, or build problems remain unresolved. Custom checks miss the actual execution path, allowing progress on a later requirement to coexist with an unfinished earlier obligation. The accumulated task remains incomplete even as the latest change appears plausible.

Hy3: basic execution failures dominate. The remaining failures concentrate on using existing repository interfaces, maintaining an executable workspace, and exposing the implementation through the intended entry point. Build/runtime errors and public-path integration failures account for 27 of its 39 failed runs. Repeated correction often encounters these execution-level obstacles before finer behavioral requirements can be validated.

Across models, the traces distinguish four obstacles to low-intervention development: exact behavior left unfinished, functionality disconnected from the public interface, repairs lost during later edits, and broken execution paths carried into subsequent work. These obstacles explain why terminal completion, direct repair, and retention provide complementary views of the same development process.

F.5 Failure Cases over Time

A concrete failure report leads to a lasting repair. In Qwen 3.8 Flash's 1Panel run, the initial endpoint depended on a global validator initialized only by server bootstrap and therefore failed under direct-router use. One completion-feedback revision moved binding and validation into the handler, recovered the first state, and left the second state correct on its first response; the repair remained valid at the final checkpoint.

One exact interface mismatch can stop an otherwise strong run. GPT-6 Astra treats a Socket.IO worker object as a process identifier. The implementation therefore returns and compares the wrong public data model, finishes only one of two requirements, and remains unresolved after two completion-feedback messages. Eight of the other 11 models pass this task, showing that this task is solvable by peers under the same evaluation. The execution trace localizes the failure to the public representation mismatch.



Figure 16: Grok 4.6's NextChat trajectory. Columns follow successive requirement stages; the lower track records the runtime status.

A local repair can still be lost during later work. Grok 4.6 recovers the first NextChat state after feedback, then introduces `message.content is not iterable` while revising the second state. The error persists through the remaining four states as the run continues to add profile, launch, status, and theme paths, producing 15 regressions and a final score of 1/6 (Figure 16). The trajectory shows how continued feature work can obscure the fact that the user-facing path stopped working several states earlier.

F.6 Initial Delivery

Initial usability and compatibility with the frozen final requirements are different outcomes. These initial-delivery results use the progressive-requirements workflow. Table 29 gives exact counts: the initial state is usable within the first evaluation window for 63.9–80.3% of runs by model, while no model already satisfies the eventual feature in more than 3.3%. All 14 ICD successes occur in two tasks (nine model successes on ECharts and five on Typst). Tasks containing at least one later-information group account for 0/540 ICD successes. Appendix C.6 characterizes the prior information available for each later requirement.

F.7 Local Uptake and Cumulative Closure



Figure 17: Local success and complete requirement-state success. The new-request population contains 927 first responses to later-information groups; the corrective population contains 455 failed later-group opportunities. The populations differ, while each row partitions its own observations into mutually exclusive outcomes.

Table 29: Initial Usable Delivery (IUD) and Initial Complete Delivery (ICD) under Evo. Each model has 61 runs.

Model	IUD	ICD
DeepSeek V4 Flash	47/61 (77.0)	2/61 (3.3)
DeepSeek V4 Pro	45/61 (73.8)	1/61 (1.6)
DeepSeek V4.1 Flash	49/61 (80.3)	1/61 (1.6)
GLM 5.3	48/61 (78.7)	0/61 (0.0)
GLM 5.3 Flash	45/61 (73.8)	1/61 (1.6)
Hy3	39/61 (63.9)	1/61 (1.6)
Kimi K3	47/61 (77.0)	2/61 (3.3)
Qwen 3.8 Flash	46/61 (75.4)	0/61 (0.0)
GPT-5.6 Sol	47/61 (77.0)	2/61 (3.3)
GPT-6 Astra	49/61 (80.3)	2/61 (3.3)
Grok 4.6	41/61 (67.2)	1/61 (1.6)
Hy4-Preview	48/61 (78.7)	1/61 (1.6)
Pooled	551/732 (75.3)	14/732 (1.9)

Table 30 combines the requirement labels with execution results. Pre-disclosure pass checks whether a later group already works before its request. First-response local success checks that group after the response; cumulative success checks all groups introduced so far. Local Repair@2 counts a failed group repaired within two revisions at a stage receiving completion feedback. Prefix Closure@2 additionally requires all previously introduced groups to pass. Each rate uses observations available for its specific check.

The 147 groups map to 146 disclosure states: Slidev Q002 contains two related groups in one state. Each Slidev row refers to a different requirement group within the same observed state.

Table 30: Early coverage and first-response outcomes by semantic cohort under Evo+Comp. Entries are successes/opportunities (percent).

Cohort	Pre-disclosure	First-response local	First-response cumulative
All groups	75/1660 (4.5)	1078/1533 (70.3)	942/1533 (61.4)
Strict proactive	44/179 (24.6)	67/134 (50.0)	44/134 (32.8)
Directional, unclear	5/291 (1.7)	170/276 (61.6)	146/276 (52.9)
Later-information	1/956 (0.1)	717/927 (77.3)	641/927 (69.1)

Table 31: Local repair and cumulative closure within two revisions. The two columns use the same observed failed-group opportunities within each cohort.

Cohort	Local Repair@2	Prefix Closure@2
All groups	91/455 (20.0)	72/455 (15.8)
Strict proactive	6/67 (9.0)	4/67 (6.0)
Directional, unclear	15/106 (14.2)	13/106 (12.3)
Later-information	50/210 (23.8)	38/210 (18.1)

Prior information separates two kinds of early coverage: 44/179 evaluations pass in the strict proactive cohort, compared with 1/956 in the later-information cohort. Once a requirement is disclosed, implementing it alone can still leave earlier work unfinished. This occurs in 76 of 717 locally successful first responses in the later-information cohort and 136 of 1,078 across all groups. Similarly, 19 of 91 successful individual repairs leave another stated requirement unmet within the same revision window. These incomplete implementations include both requirements that never passed and behavior broken by later edits.

F.8 Matched Protocol Transitions

The Full→Evo workflow contrast gives the largest net change for DeepSeek V4 Flash and the smallest for Hy4-Preview. The Evo→Evo+Comp contrast reverses that pattern for Hy4-Preview and gives



Figure 18: Final-outcome changes over 732 matched model–task pairs per comparison. Bars distinguish newly successful and newly unsuccessful runs; intervals resample repositories. Each comparison uses independent executions of the complete workflows.

its largest change for Grok 4.6, while changing little for GPT-6 Astra and Hy3. Table 32 gives the matched counts; Figures 19 and 20 show the complete model-level breakdown.

Table 32: Matched protocol transitions by model. Rescue/loss gives counts on the same 61 tasks; net change is in percentage points.

Model	Full → Evo		Evo → Evo+Comp	
	Rescue / loss	Net change	Rescue / loss	Net change
DeepSeek V4 Flash	14 / 2	+19.7	12 / 4	+13.1
DeepSeek V4 Pro	12 / 4	+13.1	10 / 3	+11.5
DeepSeek V4.1 Flash	14 / 5	+14.8	11 / 3	+13.1
GLM 5.3	10 / 6	+6.6	10 / 1	+14.8
GLM 5.3 Flash	15 / 7	+13.1	12 / 4	+13.1
Hy3	10 / 3	+11.5	3 / 1	+3.3
Kimi K3	11 / 2	+14.8	12 / 2	+16.4
Qwen 3.8 Flash	9 / 4	+8.2	9 / 3	+9.8
GPT-5.6 Sol	8 / 2	+9.8	8 / 3	+8.2
GPT-6 Astra	11 / 5	+9.8	5 / 3	+3.3
Grok 4.6	9 / 3	+9.8	16 / 0	+26.2
Hy4-Preview	7 / 4	+4.9	11 / 1	+16.4

At the pooled level, replacing the one-shot complete-contract workflow with progressive feature development gives a $+11.3$ point net change, with a repository-clustered 95% bootstrap interval of $[+6.1, +18.6]$. Enabling the completion-feedback workflow, including failure evidence and limited revisions, gives a $+12.4$ point net change, with interval $[+8.3, +17.1]$ (Figure 18).

Of the 119 model–task pairs rescued across the two independently executed progressive workflows, 57 receive no completion message in the successful run and 54 contain an observed same-state recovery. The paired table records changes in final outcomes; the within-run recovery counts identify repairs following failure feedback.

F.9 Outcomes by Implementation Language and Software Form

Table 33 reports the primary descriptive strata: five single-language slices and five software forms with at least seven tasks from at least three repositories. The point estimate of every matched Evo→Evo+Comp change is positive, but the intervals for TypeScript and Browser reach zero. Recovery, stability, and token use vary substantially (Table 34). Figure 21 shows that Service has the largest primary matched gain, whereas Browser has the smallest. Repository-clustered intervals describe sensitivity to the sampled repository mixture.

The mixed Go/TypeScript task, two Framework tasks, and one Embedded task are reported descriptively. Their matched changes are $+66.7$, 0.0, and $+41.7$ points, respectively, without inferential intervals. Language–form composition is sparse: 25 of 42 possible cells are empty, Rust is almost entirely CLI, and TypeScript is concentrated in Browser and Framework tasks. These strata describe the observed combinations of repository, language, software form, and task horizon.



Figure 19: Paired Full→Evo transitions over 61 tasks per model. Bars count lost successes and rescued failures; the right column gives net percentage-point gain.



Figure 20: Paired Evo→Evo+Comp transitions over 61 tasks per model. Bars count lost successes and rescued failures; the right column gives net percentage-point gain.

F.10 Recovery after Completion Feedback

Recovery and retention have different populations. Recovery starts from a failed first response and asks whether the current requirement state passes within its two corrective revisions. Retention starts only after an individual requirement has passed and asks whether it remains correct at later observed stages and the final check. Across models, 642 requirement-group instances have a passing observation and a subsequent-stage observation. Of these, 569 retain success and 73 subsequently fail. Thus $569/642 = 88.6\%$ is observed retention and $73/642 = 11.4\%$ is its complementary loss rate. These instances are requirements evaluated in model runs, not 642 distinct benchmark requirements.

Figure 23 shows that direct recovery varies substantially across models; Table 35 reports both feedback conversion and the separate group-level retention measure. Grok 4.6 and DeepSeek V4 Flash have the highest Recover@2, while GPT-5.6 Sol has a lower observed recovery fraction despite

Table 33: Final completion by primary language and software form. n is tasks, r repositories, and the denominator for each protocol is $12n$ runs. Δ is the paired Evo-to-Evo+Comp change in percentage points with a repository-clustered 95% interval.

Stratum	n	r	Full	Evo	Evo+Comp	Δ [95% CI]
Go	19	9	57.0	70.2	81.6	+11.4 [6.1, 19.7]
Rust	15	7	24.4	35.0	48.3	+13.3 [6.5, 20.5]
JavaScript	10	5	45.8	73.3	85.8	+12.5 [1.2, 22.4]
TypeScript	9	8	12.0	10.2	17.6	+7.4 [0.0, 18.8]
Python	7	5	58.3	66.7	78.6	+11.9 [1.7, 26.7]
CLI	21	10	36.5	43.3	57.5	+14.3 [9.3, 21.4]
Service	13	7	53.2	66.7	84.0	+17.3 [2.8, 31.9]
TUI	10	4	46.7	59.2	70.8	+11.7 [2.8, 26.7]
Browser	7	6	26.2	27.4	31.0	+3.6 [0.0, 12.5]
Library	7	4	50.0	83.3	90.5	+7.1 [1.2, 10.8]

Table 34: Evo+Comp diagnostics for the same primary strata. Recovery and SER cells give successes/eligible opportunities. Tokens are millions per reported run; telemetry reports available/total runs. Each stratum groups the sampled tasks by one attribute.

Stratum	Recover@2	SER@2	FDAC (%)	Tokens	Telemetry
Go	36/100	186/224	52.2	8.64	227/228
Rust	30/159	85/139	28.2	27.11	180/180
JavaScript	15/42	103/120	53.7	7.28	120/120
TypeScript	14/354	14/106	9.8	37.86	108/108
Python	11/63	65/84	47.1	13.47	84/84
CLI	42/224	137/209	32.4	25.56	252/252
Service	35/70	131/154	50.9	6.53	156/156
TUI	20/77	85/118	45.5	9.01	119/120
Browser	7/188	26/84	21.1	27.84	84/84
Library	5/23	76/84	59.5	8.99	84/84



Figure 21: Matched Evo→Evo+Comp change by implementation language and software form. Intervals use repository-clustered bootstrap samples; sparse descriptive-only strata are separated from the primary slices.

strong final completion. Each recovery rate uses the failed states encountered by that model. The second revision adds three recoveries for Grok 4.6, DeepSeek V4 Flash, and DeepSeek V4 Pro, but none for Hy3, Qwen 3.8 Flash, or GPT-6 Astra.



Figure 22: Recovery after a failed first response. Segments partition the 733 observed failed states by their first successful revision, with unresolved states shown separately.

Table 35: Completion-feedback conversion and observed requirement retention by model. Recover@1 and Recover@2 use feedback opportunities as their denominator. Retention uses only previously satisfied requirement groups with at least one later-state observation.

Model	Opportunities	Recover@1	Recover@2	Observed retention
DeepSeek V4 Flash	57	11 (19.3)	14 (24.6)	52/62 (83.9)
DeepSeek V4 Pro	68	8 (11.8)	11 (16.2)	46/53 (86.8)
DeepSeek V4.1 Flash	58	5 (8.6)	7 (12.1)	61/62 (98.4)
GLM 5.3	55	8 (14.5)	9 (16.4)	51/59 (86.4)
GLM 5.3 Flash	55	5 (9.1)	7 (12.7)	46/51 (90.2)
Hy3	92	12 (13.0)	12 (13.0)	27/33 (81.8)
Kimi K3	56	7 (12.5)	9 (16.1)	56/59 (94.9)
Qwen 3.8 Flash	58	4 (6.9)	4 (6.9)	46/50 (92.0)
GPT-5.6 Sol	47	3 (6.4)	4 (8.5)	47/55 (85.5)
GPT-6 Astra	58	7 (12.1)	7 (12.1)	57/57 (100.0)
Grok 4.6	73	15 (20.5)	18 (24.7)	33/46 (71.7)
Hy4-Preview	56	10 (17.9)	11 (19.6)	47/55 (85.5)
Pooled	733	95 (13.0)	113 (15.4)	569/642 (88.6)

Repository-clustered 95% bootstrap intervals are $[7.5, 20.0]$ for Recover@1 and $[9.2, 23.5]$ for Recover@2.



Figure 23: Completion-feedback recovery by model. Bars show fixes obtained after the first revision and those added by a second; the right columns give Recover@2 and opportunity counts.

F.11 State Outcomes and User Feedback Burden

With progressive requests and no correction, 56.3% of 2,484 requirement states pass after the first response, 3.5% are already satisfied before disclosure, 34.7% remain unresolved, and 5.4% are unobserved in the recorded trace. With corrective feedback, 59.5% pass on the first response, 5.6% pass after a revision, 3.5% are already satisfied, 25.3% remain unresolved, and 6.1% are unobserved. Figures 24 and 25 show how these outcomes vary by model.



Figure 24: State outcomes under Evo, over 207 possible states per model; Pooled aggregates all 12 models. Hatching denotes unobserved records.

Table 36: Feedback and path diagnostics under Evo+Comp. N_E and N_C are mean delivered messages per task. Triggered runs receive completion feedback; Success is their final StrictPass rate. Stalled is the percentage of responses with no observed cumulative progress; regressions are events, not distinct tasks.

Model	Mean N_E	Mean N_C	Triggered runs	Success (%)	Stalled (%)	Regressions
DeepSeek V4 Flash	2.25	1.97	31	41.9	43.9	9
DeepSeek V4 Pro	2.30	2.44	32	25.0	52.6	7
DeepSeek V4.1 Flash	2.28	2.07	29	37.9	44.3	6
GLM 5.3	2.23	2.02	28	25.0	45.2	8
GLM 5.3 Flash	2.28	2.48	32	28.1	49.8	6
Hy3	2.36	4.03	46	15.2	67.1	4
Kimi K3	2.25	1.87	26	30.8	45.8	5
Qwen 3.8 Flash	2.30	2.59	31	16.1	52.4	5
GPT-5.6 Sol	2.23	1.89	23	21.7	41.0	9
GPT-6 Astra	2.25	2.00	23	26.1	47.5	2
Grok 4.6	2.31	2.82	33	33.3	52.1	35
Hy4-Preview	2.28	2.08	29	34.5	44.8	8
Pooled	2.27	2.35	363	27.5	49.2	104

Evolution-feedback counts vary little because models follow the same task states, whereas completion-feedback burden depends on the current workspace (Table 36). Hy3 receives 4.03 completion-feedback messages per task and makes no observable progress on 67.1% of responses. GPT-5.6 Sol and Kimi K3 receive fewer than 1.9 completion messages per task, while DeepSeek V4 Flash has the highest final success rate among tasks that trigger completion feedback. Grok 4.6 combines a large between-protocol net gain with 35 within-run regression events.



Figure 25: State outcomes under Evo+Comp, over 207 possible states per model; Pooled aggregates all 12 models. After-feedback denotes delayed resolution; hatching denotes unobserved records.

F.12 Tasks That Separate Models

Across the three independently executed workflows, the number of tasks failed by all models decreases, while the number solved by some but not all models increases (Table 37). When both feedback types are available, 38 tasks are solved by some but not all models, and nine remain unsolved by all 12.

Table 37: How many tasks are solved by all, some, or none of the models under each protocol.

Protocol	All pass	Some pass	None pass
Full	6	35	20
Evo	10	37	14
Evo+Comp	14	38	9

F.13 Preserving Behavior across Later States

Table 38 checks the same 685 eligible runs at three points within each stage: after the first response, after the first correction, and after the second. At each checkpoint, trajectory reliability requires all cumulative stages to have passed by that point in their respective revision sequences. GPT-5.6 Sol and GPT-6 Astra have the highest observed SER@0. Hy4-Preview obtains the largest first-revision gain, while DeepSeek V4 Pro, GLM 5.3 Flash, and GPT-5.6 Sol gain the most from the second revision. Figure 26 makes the small and model-dependent contribution of the second revision visible.

F.14 Token Cost

Table 39 reports mean tokens per reported run and tokens per successful final delivery. GPT-6 Astra and Grok 4.6 use substantially fewer tokens per successful delivery than the remaining models. GLM 5.3 has the highest token cost when both feedback types are available, while Hy3's low mean run cost is offset by its low completion rate. Grok 4.6 and GLM 5.3 have similar SER@2 (67.9% and 67.2%), yet GLM 5.3 consumes about seven times as many tokens per successful delivery (Figure 27).

Table 38: Trajectory reliability at the first-response, first-revision, and second-revision checkpoints of the same runs. "Runs" counts trajectories with a usable result at every later state.

Model	SER@0	SER@1	SER@2	Runs
DeepSeek V4 Flash	59.3	69.5	71.2	59
DeepSeek V4 Pro	54.2	59.3	62.7	59
DeepSeek V4.1 Flash	57.4	65.6	67.2	61
GLM 5.3	62.1	67.2	67.2	58
GLM 5.3 Flash	56.4	61.8	65.5	55
Hy3	33.3	45.8	45.8	48
Kimi K3	65.0	70.0	71.7	60
Qwen 3.8 Flash	56.4	61.8	63.6	55
GPT-5.6 Sol	66.7	70.2	73.7	57
GPT-6 Astra	66.7	73.3	73.3	60
Grok 4.6	58.9	67.9	67.9	56
Hy4-Preview	61.4	73.7	73.7	57
Pooled	58.5	65.8	67.3	685



Figure 26: Trajectory reliability by model when both feedback types are available. Segments give the fraction of eligible runs that complete every cumulative stage by the first response, first corrective revision, or second corrective revision within that stage.



Figure 27: SER@2 versus reported tokens per successful final delivery across all models. Cost includes tokens from reported failed runs; the dashed line marks the observed Pareto frontier.

Table 39: Token consumption in millions using only runs with reported telemetry. Each protocol separates mean tokens per reported run from total reported tokens per reported StrictPass success, including tokens spent on failures. Coverage is 726/732 for Full, 732/732 for Evo, and 731/732 for Evo+Comp. Minimum reported token costs within each column are bold.

	Full		Evo		Evo+Comp	
Model	Mean	/ success	Mean	/ success	Mean	/ success
GPT-6 Astra	**1.55**	**2.63**	8.22	11.94	8.88	12.32
GPT-5.6 Sol	5.19	9.89	14.18	22.76	15.56	22.07
Kimi K3	6.63	16.85	13.31	24.60	16.82	23.86
Hy4-Preview	7.34	15.44	13.19	25.14	21.48	31.20
DeepSeek V4 Flash	11.47	29.91	14.18	24.71	21.40	30.36
DeepSeek V4.1 Flash	8.76	20.55	13.13	22.89	20.49	29.06
GLM 5.3	11.30	25.53	20.11	39.56	27.73	42.29
Qwen 3.8 Flash	7.34	18.35	13.04	27.44	21.15	36.86
GLM 5.3 Flash	6.64	18.42	12.42	25.26	19.87	31.90
Grok 4.6	1.93	6.92	**2.29**	**6.09**	**3.82**	**5.97**
DeepSeek V4 Pro	10.09	27.06	13.83	28.12	24.58	40.96
Hy3	4.77	21.67	7.23	22.05	11.97	33.19
Pooled	**6.91**	**17.00**	**12.09**	**23.42**	**17.80**	**27.81**

F.15 Conditional Proactive Coverage and Model Profiles

On the strict eligible cohort, micro PCC is 44/179 (24.6%). Averaging first within each of the 16 groups gives macro PCC of 22.9%. Excluding mixed-semantics items changes the micro result to 24/131 (18.3%) and macro PCC to 16.7%. Thus this diagnostic is sensitive to cohort composition. The heavy-implementation subset covers a small, distinct mixture of requirements and repositories.

Table 40 reports the complete model profile with its actual denominators. Every model has only 14–16 usable strict proactive opportunities. The profiles distinguish early implementation from completion after new information, individual repair, and successful completion of all stated requirements. Repair denominators consist of the groups that each model failed.

Table 40: Conditional model profiles under Evo+Comp. Each entry is successes/opportunities. Uptake uses the later-information cohort; repair and closure use all eligible failed later groups. Percentages can be recovered directly from the displayed counts.

Model	PCC	Uptake@1	Repair@2	Closure@2	Retention
DeepSeek V4 Flash	5/16	61/78	9/33	9/33	52/62
DeepSeek V4 Pro	2/15	63/79	9/43	7/43	46/53
DeepSeek V4.1 Flash	3/16	64/80	7/31	5/31	61/62
GLM 5.3	6/15	64/79	5/30	3/30	51/59
GLM 5.3 Flash	5/14	56/75	8/39	6/39	46/51
Hy3	0/14	36/67	13/65	9/65	27/33
Kimi K3	4/15	66/83	5/34	4/34	56/59
Qwen 3.8 Flash	4/14	59/76	5/39	3/39	46/50
GPT-5.6 Sol	6/16	63/78	6/30	4/30	47/55
GPT-6 Astra	5/15	66/81	6/36	5/36	57/57
Grok 4.6	1/14	57/75	10/42	9/42	33/46
Hy4-Preview	3/15	62/76	8/33	8/33	47/55

The macro-PCC analysis gives group-bootstrap intervals of 22.9% [8.9, 38.5] for the strict cohort and 16.7% [5.6, 29.9] without mixed items. These intervals summarize sensitivity to the sampled requirement groups. The resampling unit is the requirement group, using the finalized labels.