

Skill Issue: Are Skills Language-Invariant in LLMs?

Bobby Cheng^{△,†}, Adam Gaber[♣], Zhengyuan Liu[△], Catherine Arnett[♣], Omer Goldman[♣], Cheston Tan[△], Leshem Choshen^{♣,*,}

[△]A*STAR, [♣]Weizmann Institute of Science, [♣]MIT-IBM Watson AI Lab, [♣]University of Cambridge, [♣]EleutherAI

Large language models access knowledge inconsistently across languages, but to what extent do they differ in their skill sets when interacting with different languages? This work quantifies *cross-lingual skill inconsistency* orthogonally from knowledge and general benchmark performance. We do this via multilingual self-play: two instances of the same model compete in a text-based game, each interacting through a different language interface. Since the model, opponent, rules, state space, and available actions remain fixed, this setting isolates the effect of language on the model’s realized behavior. We build a multilingual extension to TextArena and evaluate three open-weight models across eight languages and six games covering spatial reasoning, imperfect information, resource allocation, and repeated interaction.¹ We find that the same model can exhibit markedly different playing strength across languages, with systematic variation in win-loss margins, invalid actions, and strategic tendencies. Detailed analyses reveal language-specific failures in spatial reasoning, card-conditioned decisions, and optimal move selection. In some settings, changing only the intermediate reasoning language recovers much of the lost performance, suggesting that language can affect different stages of the decision process. These results show that skill discrepancies are a measurable major roadblock in the development of truly multilingual models. Better understanding these discrepancies can help us design models that perform more equitably across languages.

1 Introduction

As large language models (LLMs) become more multilingual (e.g., [Xue et al., 2021](#); [Shi et al., 2022a](#)) it also becomes clearer that they perform unequally across languages ([Hu et al., 2020](#); [Ponti et al., 2020a](#); [Arnett and Bergen, 2025](#)). Understanding these differences is crucial for deploying multilingual LLMs fairly and reliably, and for identifying what prevents them from functioning as language-agnostic systems.

Much attention has been therefore given to cross-lingual inconsistency, where models respond differently to translations of the same input, but these works mostly focused on the discrepancy in *knowledge* accessibility (e.g., [Jiang et al., 2020](#); [Qi et al., 2023](#)), and pointed to the lack of cross-lingual transfer as its source ([Ifergan et al., 2024](#); [Goldman et al., 2025](#)). Equally consequential, and far less understood, is whether models exhibit a different set of *skills* depending on the language through which they interact. In other words, beyond retrieving different knowledge, can the same model reason, plan, and make decisions more effectively in some languages than in others? Answering this question requires isolating the effect of language on the model’s behavior independently of its stored knowledge or overall benchmark performance.

In this work we study *cross-lingual skill inconsistency* by letting models compete against themselves in multilingual text-based games. We let two instances of the same model interact via translations of the same environment into different languages, while the board states, cards, numerical information, action spaces, and game rules remain fixed. [Fig. 3](#) demonstrates a typical game played in German and English. If the model accesses and expresses the same underlying skills through both languages, then the two model instances should exhibit equal playing strengths and the wins and losses should distribute randomly as is the case when playing against oneself in the same language (see [Fig. 2](#)’s diagonals).

To support this and future studies, we introduce a large-scale multilingual extension to TextArena ([Guertler et al., 2025](#); see [Sec. 2](#)), **comprising 65 single-, two-, and multi-player games in 193 languages** of different tiers of translation and providing broad coverage for studying language effects in agentic gameplay. Out of these, we experiment with a subset of manually verified translations of six games into eight languages (see [Fig. 1](#)). We use this subset to explore cross-lingual skill inconsistency of three 4B-sized open-weights models: Gemma 4, Ministral 3, and Qwen 3.

We find LLMs to be behaviorally inconsistent across languages (see [Sec. 5.1](#), and [Fig. 2](#)). These differences appear in spatial reasoning, where the axis of failure varies by language; in strategic behavior, where different languages induce different risk profiles and er-

[†]Corresponding author: bobbycxy1994@gmail.com

^{*}Corresponding author: leshem.choshen@weizmann.ac.il

¹All the relevant code and data resources are publicly available at <https://github.com/TextArena/TextArena>.




Figure 1: The six game environments and the primary skill each probes; full rules in App. D.




Figure 2: Overall, wins of each language against others, per model. Each heatmap shows the role-pooled win-loss margin $\Delta(A > B) = (W_A - L_A)/N$ aggregated over all games, where positive values mean row language A outperforms column language B . The rightmost column reports each language’s mean margin $\bar{\Delta}_A$. Diagonal is same language games, with randomly assigned sides for comparison. Across models, English is consistently strong and Hebrew weak, with Qwen3-4B showing the sharpest hierarchy.

ror rates; and in unequal access to known knowledge, where models may retrieve or execute a known strategy reliably in one language but not another (see Sec. 5.2). We also observed that reasoning in a stronger language can recover substantial performance in some games, suggesting that language sensitivity may arise during reasoning, state interpretation, or both (see Sec. 5.3).

Finally, we show that these differences are partly explainable by multilingual benchmarks and agree with the uneven availability of languages across training data (see Sec. 5.4).




Figure 3: Illustration of Gemma-4-E4B-it playing Tic-Tac-Toe with itself in German and English respectively.

Tier	Resource class							Total
	5	4	3	2	1	0	–	
A	6	0	0	2	0	0	0	8
B	1	17	18	2	4	0	0	42
C	7	1	6	14	76	15	5	124
E	0	0	0	0	10	5	3	18
Total	14	18	24	18	90	20	8	192

Table 1: Languages by verification tier and resource class. We focus on the eight Tier-A languages.

2 Multilingual TextArena

TextArena TextArena (Guertler et al., 2025) is an open-source collection of 100+ competitive single-, two-, and multi-player text-based games for training and evaluating LLMs, released under the MIT License. We extend relevant games with multilingual support which allow players’ observations to be rendered in a different language without altering the rules, legal actions, rewards or transition dynamics. Examples of the game templates and starter code are in App. D.

Translation workflow. To translate TextArena games we used a multi-tiered translation and verification pipeline. Prioritizing diversity in typology, script, culture, and number of speakers, we chose eight languages as our Tier A: English, Arabic, German, Spanish, French, Hebrew, Malay, and Chinese. This selection ensures that at least two languages share a characteristic along each dimension. We translated six TextArena games to these languages with Claude Opus 4.8 (Anthropic, 2026) or GPT-5.2 (Singh et al., 2026) (see App. C for details), and assigned native speakers to manually verify the translations. This is the set of games and languages that were used in our

experiments.

For an additional 42 high and mid resource languages, Tier B, we constructed an automatic translation and verification pipeline. Due to budget constraints, we used the open-weights models of Llama-3.1-405B (Grattafiori et al., 2024) and Qwen2.5-72B (Qwen Team, 2024) to translate 65 games into these languages. Following Dobler et al. (2026), we back-translated the results to English again and let Claude Opus 4.8 to judge whether the back translations were faithful to the original English game. If the procedure failed to produce a faithful translation across four different seeds, the language was demoted to Tier C.

For the remaining 142 languages, where high-quality machine translations are harder to come by, we used NLLB-200 (Costa-Jussà et al., 2022) for translation and back-translation. Llama-3.1-405B and Qwen2.5-72B then independently assessed fidelity. If they both agree that the back-translation was faithful to the original text in 85% of the time, then the language is assigned to Tier C; otherwise Tier E.

Tab. 1 details the number of languages in each tier and in each resourcefulness class (from Joshi et al., 2020). See App. E for further details.

3 Experiment Setup

Evaluated Models. We focus on Gemma-4-E4B-it (Team et al., 2026), Qwen3-4B (Qwen Team, 2025), and Ministral3-3B-Instruct-2512 (Liu et al., 2026), which are comparably sized open-weight models that remain tractable for large-scale multilingual self-play. To determine the general multilingual capability of these models, we evaluate them on Global-MMLU (Singh et al., 2024) and Belebele (Bandarkar et al., 2024), and compare against our multilingual setup in Sec. 5.4.

Game Environments. Models were evaluated on six two-player games from TextArena spanning perfect-information (TicTacToe, Nim, and Simple-Tak), simultaneous resource allocation (Colonel Blotto), imperfect-information (Kuhn Poker), and repeated social interaction game (Iterated Prisoner’s Dilemma). Together, they test spatial and numerical reasoning, planning, allocation, bluffing, cooperation, and adaptation. More details of each game are covered in App. D.

Two-player multi-turn games. Each game g is implemented as an environment E_g that unfolds over multiple turns according to a Markov transition process. At step t , E_g is in state s_t , and the active player receives

an observation o_t containing the player-visible portion of the interaction history, including all publicly observable past actions $a_{<t}$. The player then selects an action a_t , after which E_g transitions to s_{t+1} . A trajectory is denoted $\tau = (s_0, o_0, a_0, s_1, o_1, a_1, \dots, s_H)$, where s_H is a terminal state corresponding to a win, loss, or draw. The outcomes for Player 0 and Player 1 are denoted $r_0(\tau)$ and $r_1(\tau)$, respectively. In standard competitive games, a win for one player is a loss for the other, while a draw yields zero outcome for both. In repeated social-interaction games such as Iterated Prisoner’s Dilemma, final outcomes are instead determined by E_g ’s cumulative scoring rule. If a model submits an invalid action, it is given an opportunity to correct it; otherwise, the game terminates as an immediate loss.

Language assignment. For each game g , Player 0 receives the game instructions and observations in language ℓ_0 and Player 1 in language ℓ_1 , where $\ell_i \in \mathcal{L} = \{\text{English (en), Arabic (ar), German (de), Spanish (es), French (fr), Hebrew (he), Malay (ms), Chinese (zh)}\}$. A language assignment is the ordered pair (ℓ_0, ℓ_1) . Where communication is relevant, each player observes the opponent’s messages in their original language, so a model may process both its interface language and the opponent’s communication language. A small number of language-independent strings are intentionally preserved across translations to maintain shared game mechanics and action formats. These include game-board symbols and coordinates, card ranks and suits, numerical values, and fixed action syntax such as “[bet]”; for example, TicTacToe displays available moves as bracketed indices such as “[1]”.

Action format and sampling parameters. We instruct model m via a system prompt to place its final action inside `\boxed{\}` so that the environment can reliably extract the submitted action (see App. A). During generation, tokens are sampled autoregressively using `temperature = 1.0`, `top_p = 0.95`, and `top_k = 64` to encourage diverse self-play trajectories.

Evaluation protocol. For each model m and game g , we evaluate every language pair, including same-language pairs, in both player-role assignments, with $n = 400$ self-play games per direction. With eight languages, this gives $\binom{8}{2} + 8 \times 2 \times 400 = 28,800$ games per model–game pair, or **86,400 games per game** across three models and **518,400 games overall** across six games. Evaluating both role assignments balances languages across player roles and avoids conflating language effects with structural advantages such as Player 0’s first-move advantage in TicTacToe.

4 Metrics

Role-pooled win–loss margin. For each model m , game g , and pair of languages A and B , we evaluate both role assignments, (A, B) and (B, A) . We pool outcomes from the perspective of language A : a Player 0 win in (A, B) and a Player 0 loss in (B, A) both count as wins for A , while the converse outcomes count as losses for A . Let $W_{m,g}(A, B)$ and $L_{m,g}(A, B)$ denote these pooled win and loss counts, and let $N_{m,g}(A, B)$ denote the total number of games across both assignments. We define the role-pooled win–loss margin as

$$\Delta_{m,g}(A, B) = \frac{W_{m,g}(A, B) - L_{m,g}(A, B)}{N_{m,g}(A, B)}. \quad (1)$$

The margin lies in $[-1, 1]$. Positive values indicate that language A outperforms language B , negative values indicate the reverse, and draws contribute zero. Pooling both assignments controls for structural player–role advantages. By construction, $\Delta_{m,g}(A, B) = -\Delta_{m,g}(B, A)$.

Mean language margin. We summarize the strength of language A for model m in game g by averaging its margin against every other language:

$$\mu_{m,g}(A) = \frac{1}{|\mathcal{L}| - 1} \sum_{B \in \mathcal{L} \setminus \{A\}} \Delta_{m,g}(A, B). \quad (2)$$

Higher values indicate stronger average self-play performance through language A .

Model-level mean language margin. We summarize the overall strength of language A for model m by macro-averaging its mean margin across games:

$$\bar{\mu}_m(A) = \frac{1}{|\mathcal{G}|} \sum_{g \in \mathcal{G}} \mu_{m,g}(A). \quad (3)$$

5 Results

In the following sections, we present our main findings. Unless otherwise specified, Gemma, Qwen, and Minis-tral refer to their 4B-sized models.

5.1 Capabilities Differ Across Languages

Fig. 2 shows that the same model can express substantially different capabilities depending on the language through which the game is presented, which we refer to as the *language interface*. This is striking because the

games are largely abstract: the boards, cards, numerical information, legal actions, and underlying strategies remain unchanged. Yet English is strongest on average across all three models, while Hebrew is consistently among the weakest. The magnitude of this effect is also model-dependent: Gemma is comparatively stable, whereas Qwen exhibits the sharpest language hierarchy. These results show that even when the core task information is non-linguistic, the language interface can affect which capabilities a model successfully expresses.

Model	Blotto	Nim	TTT	Tak	IPD	Kuhn	Avg.
Gemma	0.44	0.02	0.47	0.43	0.25	0.05	0.28
Qwen	1.48	0.85	0.32	0.44	0.03	0.13	0.54
Ministral	1.28	0.49	0.36	0.28	0.74	0.20	0.56
Avg.	1.07	0.45	0.38	0.38	0.34	0.13	0.46

Table 2: Language sensitivity by game, measured as language gap, $\max_{\ell} \mu_{\ell} - \min_{\ell} \mu_{\ell}$. **Bold** marks most language-sensitive model for each game. Bottom row shows the average across models.

Language sensitivity also varies across games (see Tab. 2). Colonel Blotto shows the largest language gap across all three models, whereas Kuhn Poker is consistently among the least sensitive. The remaining games show more model-dependent effects. For example, Iterated Prisoner’s Dilemma is relatively stable for Gemma and Qwen but is more sensitive for Ministral. We next summarise how these differences manifest across specific skills like spatial reasoning, strategic behavior and access to known strategies.

5.2 Language-Conditioned Skills Difference

Beyond aggregate game-playing strength, the language interface produces consistent differences in how models fail. In spatial games like TicTacToe and SimpleTak, the failure mode varies by language. We see that English interfaces tend to show a relatively balanced distribution of losses across rows, columns and diagonals, whereas non-Latin-script interfaces such as Arabic and Hebrew skew consistently toward column and diagonal defeats, with game trajectories revealing frequent mislabeling of cell sequences as lines. Strategic behavior shifts as well. In Kuhn Poker, the same model adopts different risk profiles depending on the interface language. Bluffing rates with the weakest card vary by more than twofold across languages for Qwen, while Gemma shows its largest cross-language variation when deciding how to play the intermediate card Q. More broadly, both the magnitude and the type of these language-conditioned shifts differ across models.

The starkest effect concerns access to pre-existing knowledge. Nim admits a complete algorithmic solution (reducing the Nim-sum to zero), which lets us test whether a known strategy is retrievable through each language interface. Mentions of the optimal strategy, optimal first-move execution, and win rates all drop sharply in Arabic and Hebrew for Qwen and Ministral, and a majority of the remaining strategy mentions in these languages originate from the small fraction of games in which the model spontaneously switched into a Latin script mid-reasoning. This indicates that the strategy is present in the model but not reliably accessible through every language: merely changing the processing language can retrieve knowledge that would otherwise be lost. Full per-game analyses, including defeat distributions, card-conditioned action rates, and the Nim strategy results, are provided in App. G.

5.3 Stronger Languages Enable Recovery

Game	Floor μ_{weak}	Reasoning language μ / recovery	Ceiling μ_{best}
Kuhn	−0.03 zh/zh	−0.01 zh/es / 37.6% −0.01 zh/fr / 49.3%	+0.02 es/es
ST	−0.21 de/de	+0.05 de/en / 60.5% −0.16 de/es / 11.6%	+0.22 en/en
TTT	−0.22 de/de	+0.20 de/en / 89.4% −0.14 de/es / 17.0%	+0.25 en/en

Table 3: Role-corrected strength μ under each interface/reasoning language pair. The middle column reports the strongest reasoning language, followed by the second strongest, while holding the weak interface language fixed. Recovery is $(\mu - \mu_{\text{weak}}) / (\mu_{\text{best}} - \mu_{\text{weak}})$. Kuhn, ST and TTT denote Kuhn Poker, SimpleTak and TicTacToe.

Prior works show that multilingual models can sometimes improve performance on non-English inputs by routing them through English. For example, self-translation and question-alignment methods improve multilingual task performance by translating non-English inputs into English before inference or reasoning (Zhu et al., 2024; Etxaniz et al., 2024; Mondshine et al., 2025). Here, we separate the language of the environment interface from the language of the intermediate reasoning and found that reasoning in a stronger language can recover some of the performance.

Tab. 3 shows that German is Gemma’s weakest interface language in TicTacToe, with $\mu = -0.22$. Holding the German interface fixed while switching the reasoning language to English increases the margin to

$\mu = +0.20$, recovering 89.4% of the reachable gap to the English-interface ceiling. We observe a similar effect in SimpleTak, where switching from German to English reasoning improves the margin from $\mu = -0.21$ to $\mu = +0.05$, recovering 60.5% of the reachable gap. Because these gains occur without translating or replacing the environment observations, they suggest that a substantial portion of the language effect in these games arises during the model’s intermediate reasoning process. However, recovery is limited and non-monotonic in Kuhn Poker, indicating that language sensitivity can arise at different stages of the agent’s decision process and cannot always be addressed by reasoning in a stronger language.

5.4 Explaining Outcome Differences

Finally, we ask whether the language-conditioned outcome differences can be explained by two external references: each model’s static multilingual competence, and the amount of multilingual text available on the web.

Lang.	Gemma-4 E4B-it	Qwen3-4B	Ministral3-3B
<i>Belebele</i>			
Arabic	78.0	75.0	73.7
German	79.1	75.3	82.8
English	82.4	84.1	83.8
Spanish	77.8	75.7	79.8
French	79.2	80.8	76.0
Hebrew	76.9	67.6	73.8
Malay	77.7	65.4	75.1
Chinese	78.2	78.7	82.2
Avg.	78.7$\pm$1.7	75.3 $\pm$ 6.3	78.4$\pm$4.2
<i>Global MMLU</i>			
Arabic	47.2	57.2	56.0
German	51.3	63.3	63.7
English	56.2	70.2	69.5
Spanish	51.7	65.5	64.8
French	51.3	65.2	64.3
Hebrew	45.5	49.4	54.2
Malay	48.3	59.4	58.9
Chinese	47.5	64.8	61.2
Avg.	49.9 $\pm$ 3.4	61.9$\pm$6.4	61.6$\pm$5.0

Table 4: Accuracy (%) on Belebele and 5-shot Global MMLU. Bold indicates the best-performing models for each language and benchmark average.


Static Benchmarks In spite there being only a sample size of 8 languages, there is noticeable correlation between the mean language margin and Global MMLU (5-shot) at r between 0.73 and 0.92 depending on the model, and likewise with Belebele at r between 0.71 and 0.79 (see Fig. 4a). The language ranking observed in interactive play is thus partly explainable from static benchmarks. Languages a model scores

well on in isolation are also, on average, the languages it wins with in self-play. What benchmark competence does *not* predict, however, is stability across language which is the max–min range of a model’s mean language margins. Gemma has the lowest Global MMLU mean of the three models yet the smallest cross-language spread, whereas Qwen has the highest mean and the largest spread. Benchmark level and cross-lingual consistency are therefore distinct axes, and being better on average does not imply behaving more uniformly across languages.


Data Availability Since the training data distributions of the models we evaluate are not publicly available, we cannot directly measure how much text each model was exposed to in each language. We therefore use the amount of publicly available web text as a proxy for language-level data availability, using per-language word counts from FineWeb-2 (Penedo et al., 2025). For English, which is not included in FineWeb-2, we estimate the corresponding word count from FineWeb (Penedo et al., 2024) using an English token-to-word fertility of approximately 1.3, consistent with values reported in FineWeb-2. We then relate each model’s mean language margin $\bar{\mu}_m(A)$ to this proxy (see Fig. 4b). The fit within each model is positive and strong, with r averaging 0.79. Languages with more available web text tend to be stronger interfaces, mirroring the benchmark correlations above.

The more informative pattern lies in the deviations from this trend, highlighted in Fig. 4b. Malay sits above the pooled fit for all three models despite having the smallest FineWeb-2 corpus, and in particular outperforms Hebrew for every model even though Hebrew has more available web text by this proxy. This asymmetry is consistent with ECLeKTic’s finding that cross-lingual transfer is stronger between languages sharing a writing system, and with prior work identifying script as a key factor in cross-lingual knowledge and skill transfer (Goldman et al., 2025; Ifergan et al., 2024; Malkin et al., 2022; Mittal et al., 2023; Diskind et al., 2026). This suggests that Latin-script Malay may benefit from transfer from higher-resource Latin-script languages, while Hebrew cannot exploit the same script-based transfer.

Chinese exposes the opposite limitation of a pure data account. Despite having roughly $20\times$ less available web text than English by this proxy, Qwen and Ministral reach near-English margins, while Gemma’s Chinese margin remains near zero. The same data availability thus supports very different realized strength depending on the model. Moreover, since Chinese achieves this without sharing a script with the other strong interfaces, script alone cannot account for



(a) Mean language margin against Belebele accuracy (left) and Global MMLU accuracy (right).



(b) Mean language margin against web-text availability, measured by $\log_{10}$ FineWeb-2 word count, with English estimated from FineWeb.

Figure 4: Relationship between within-model language strength and external measures of language capability and data availability. Each point represents one of eight languages for a given model, lines show per-model least-squares fits, and error bars show standard errors across the language’s seven pairwise margins. In **a**, Pearson r is reported in the legend ($n = 8$). In **b**, highlighted points mark the largest deviations from the fitted trends. Margins are comparable across languages within, but not across, models.

the results either. Data quantity and script each explain part of the language hierarchy, but the remaining variation is model-specific: how much strength a model realizes from a given language is not determined by how prevalent that language is in web data.

6 Related Works

6.1 Multilingual Language and Reasoning Evaluation

Multilingual benchmarks have progressed from evaluating language understanding tasks such as natural language inference, question answering, and common-sense reasoning (Ponti et al., 2020b; Lin et al., 2022), to covering broader capabilities including mathemat-

ical reasoning, reading comprehension, knowledge-intensive academic tasks, code generation and instruction following (Shi et al., 2022b; Bandarkar et al., 2024; Singh et al., 2024; Huang et al., 2025), with recent benchmarks evaluating regional and culturally situated knowledge by drawing questions from local sources (Romanou et al., 2024; Chang et al., 2026a).

These benchmarks primarily evaluate models through fixed inputs and predefined answers. They reveal whether accuracy varies across languages, but not whether a model expresses an equivalent policy over an evolving interaction. We use Belebele and Global-MMLU as reference for general multilingual competence (see Tab. 4), while Multilingual TextArena studies whether a fixed model accesses and expresses the same interactive skills when operating

in the same environment through different language interfaces.

6.2 Cross-Lingual Knowledge and Skill Transfer

Prior work suggests that multilingual models exhibit factual compartmentalization, where information acquired through one language might be irretrievable in another (Goldman et al., 2025; Asai et al., 2021; Chua et al., 2025; Limkonchotiawat et al., 2022; Litschko et al., 2025). Some offer post-hoc solutions, often following inference in multiple languages (Huang et al., 2023; Diskind et al., 2026). Even knowledge that seems to be consistent across languages is often shown to be stored twice rather than shared (Ifergan et al., 2024; Qi et al., 2023). At the same time, learning linguistic skills is cheap, with 100M parameter models showing equivalent performance to state-of-the-art 70B ones (Charpentier et al., 2025; Chang et al., 2026b). Together, these findings suggest that factual compartmentalization is more than a discrepancy in linguistic ability between languages within the same model.

Related work on skill transfer studies whether task competence acquired from supervision in one or few languages generalizes to others (Hu et al., 2020; Malkin et al., 2022; Shaham et al., 2024). For example, Turc et al. (2021) shows that the sourced language used for fine-tuning affects zero-shot transfer performance, with English not always providing the strongest transfer to other languages.

Our work is related to cross-lingual skill transfer, but differs from the standard source-fine-tuning setup. Instead, we focus on language-conditioned skill access and expression rather than acquiring a skill through one language.

6.3 Interactive and Game-Based Evaluation of LLMs

Interactive benchmarks evaluate LLMs as agents whose actions affect an evolving environment. Unlike static benchmarks, these settings test whether models can interpret changing states, select valid actions, and adapt over multiple turns. These include tool-use environments and game-based benchmarks that evaluate capabilities such as planning, spatial reasoning, learning from interaction, coordination, and goal-directed decision-making (Barres et al., 2025; Guertler et al., 2025; Wu et al., 2024; Gong et al., 2023; Qiao et al., 2023).

A related line of work uses strategic and game-theoretic environments to evaluate planning, decision-making, and social reasoning, including direct compe-

tition between LLMs (Duan et al., 2024; Costarelli et al., 2024; Yao et al., 2025).

Within this line of work, existing benchmarks primarily compare models, prompting methods, or agent architectures under a shared or fixed language interface. We instead use competitive environments to study language-conditioned variation *within* a fixed model by extending TextArena with multilingual interfaces.

7 Conclusion

In this paper, we introduced Multilingual TextArena and used controlled self-play to test whether the skills of an LLM remain consistent across language interfaces. Across three models, eight languages and six games, we found differences in their playing strength, strategic behavior and spatial features within the same model.

Reasoning in a stronger language recovered substantial performance in some games, but these were limited in other games, suggesting that language can affect multiple stages of interaction, including state interpretation, reasoning, knowledge retrieval, and action selection. Static multilingual benchmarks and relative web-data availability explained part of the variation, not all.

Overall, we showed that a *skill* a model has may not be equally applied in every language. Multilingual evaluation should assess not only whether models understand equivalent inputs, but also if they *behave* consistently across languages.

Limitations

Closed-data models While the models we evaluated have their technical reports published, their training data remains behind closed doors. This closed-data nature makes it hard for us to uncover what reasons and training approaches might have explained the difference in language performance per model. While there were models like Apertus (Hernández-Cano et al., 2025) which state clearly their pre-training data recipe and their multilingual distribution, Apertus produced several invalid moves which made it difficult to produce a viable score. Sticking with these models, the explainability of these results required assumptions and estimates, e.g. availability of multilingual data.

Model scale. Our evaluation is limited to models in the 3B to 4B parameter range. This scale enabled controlled and cost-efficient evaluation over more than half a million games. However, cross-lingual skill inconsistency may differ for larger models. Our results,

then, should therefore not be interpreted as establishing scale-invariant language effects.

Acknowledgements

We would like to thank the Shimon and Golde Picker–Weizmann Annual Grant and the Center for New Scientists at the Weizmann Institute of Science for supporting this research. Omer Goldman also acknowledges support from the Blavatnik Family Foundation.

References

- Anthropic. 2026. [Claude opus 4.8 system card](#). Technical report, Anthropic.
- Catherine Arnett and Benjamin Bergen. 2025. [Why do language models perform worse for morphologically complex languages?](#) In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 6607–6623, Abu Dhabi, UAE. Association for Computational Linguistics.
- Akari Asai, Jungo Kasai, Jonathan H. Clark, Kenton Lee, Eunsol Choi, and Hannaneh Hajishirzi. 2021. [Xor qa: Cross-lingual open-retrieval question answering](#). *Preprint*, arXiv:2010.11856.
- Robert Axelrod. 1984. *The Evolution of Cooperation*. Basic, New York.
- Lucas Bandarkar, Davis Liang, Benjamin Muller, Mikel Artetxe, Satya Narayan Shukla, Donald Husa, Naman Goyal, Abhinandan Krishnan, Luke Zettlemoyer, and Madian Khabisa. 2024. [The belebele benchmark: a parallel reading comprehension dataset in 122 language variants](#). In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 749–775, Bangkok, Thailand and virtual meeting. Association for Computational Linguistics.
- Victor Barres, Honghua Dong, Soham Ray, Xujie Si, and Karthik Narasimhan. 2025. [\$\tau^2\$ -bench: Evaluating conversational agents in a dual-control environment](#). *Preprint*, arXiv:2506.07982.
- Emile Borel. 1953. [The theory of play and integral equations with skew symmetric kernels](#). *Econometrica*, 21(1):97–100.
- Charles L. Bouton. 1901. [Nim, a game with a complete mathematical theory](#). *Annals of Mathematics*, 3(1/4):35–39.
- Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. 2016. [Openai gym](#). *Preprint*, arXiv:1606.01540.
- Tyler A. Chang, Catherine Arnett, Abdelrahman Sadallah, Abdelrahman Eldesokey, Abeer Kashar, Abolade Daud, Abosede Grace Olanihun, Adamu Labaran Mohammed, Adeyemi Praise, Adhikarimayum Meerajita Sharma, Aditi Gupta, Adril Putra Merin, Adwoa Bremang, Afitab Iyigun, Afonso Simplicio, Ahmed Essouaied, Aicha Chorana, Akhil Eppa, Akintunde Oladipo, and 361 others. 2026a. [Global PIQA: Evaluating commonsense reasoning across 100+ languages and cultures](#). *Preprint*.
- Tyler A. Chang, Catherine Arnett, Zhuowen Tu, and Benjamin Bergen. 2026b. [Goldfish: Monolingual language models for 350 languages](#). In *Proceedings of the Fifteenth Language Resources and Evaluation Conference (LREC 2026)*, pages 3750–3781, Palma, Mallorca, Spain. European Language Resources Association (ELRA).
- Lucas Georges Gabriel Charpentier, Leshem Choshen, Ryan Cotterell, Mustafa Omer Gul, Michael Y Hu, Jing Liu, Jaap Jumelet, Tal Linzen, Aaron Mueller, Candance Ross, et al. 2025. Findings of the third babylm challenge: Accelerating language modeling research with cognitively plausible data. In *Proceedings of the First BabyLM Workshop*, pages 399–420.
- Lynn Chua, Badih Ghazi, Yangsibo Huang, Pritish Kamath, Ravi Kumar, Pasin Manurangsi, Amer Sinha, Chulin Xie, and Chiyuan Zhang. 2025. [Crosslingual capabilities and knowledge barriers in multilingual large language models](#). *Preprint*, arXiv:2406.16135.
- Marta R Costa-Jussà, James Cross, Onur Çelebi, Maha Elbayad, Kenneth Heafield, Kevin Heffernan, Elahe Kalbassi, Janice Lam, Daniel Licht, Jean Maillard, et al. 2022. No language left behind: Scaling human-centered machine translation. *arXiv preprint arXiv:2207.04672*.
- Anthony Costarelli, Mat Allen, Roman Hauksson, Grace Sodunke, Suhas Hariharan, Carlson Cheng, Wenjie Li, Joshua Clymer, and Arjun Yadav. 2024. [Gamebench: Evaluating strategic reasoning abilities of llm agents](#). *Preprint*, arXiv:2406.06613.
- Elisha Diskind, Itamar Trainin, Uri Shaham, Leshem Choshen, Idan Szpektor, and Omri Abend. 2026. Cross-lingual exploration for parametric knowledge. *arXiv preprint arXiv:2606.24579*.

- Konstantin Dobler, Simon Lehnerer, Federico Scozzafava, Jonathan Janke, and Mohamed Ali. 2026. [Multilingual reasoning gym: Multilingual scaling of procedural reasoning environments](#). *Preprint*, arXiv:2603.10793.
- Jinhao Duan, Renming Zhang, James Diffenderfer, Bhavya Kailkhura, Lichao Sun, Elias Stengel-Eskin, Mohit Bansal, Tianlong Chen, and Kaidi Xu. 2024. [Gtbench: Uncovering the strategic reasoning limitations of llms via game-theoretic evaluations](#). *Preprint*, arXiv:2402.12348.
- AbdelRahim Elmadany, Ife Adebara, and Muhammad Abdul-Mageed. 2024. [Toucan: Many-to-many translation for 150 african language pairs](#). *Preprint*, arXiv:2407.04796.
- Julen Etxaniz, Gorka Azkune, Aitor Soroa, Oier Lopez de Lacalle, and Mikel Artetxe. 2024. [Do multilingual language models think better in English?](#) In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 2: Short Papers)*, pages 550–564, Mexico City, Mexico. Association for Computational Linguistics.
- Jay Gala, Pranjal A. Chitale, Raghavan AK, Varun Gumma, Sumanth Doddapaneni, Aswanth Kumar, Janki Nawale, Anupama Sujatha, Ratish Pudupully, Vivek Raghavan, Pratyush Kumar, Mitesh M. Khapra, Raj Dabre, and Anoop Kunchukuttan. 2023. [IndicTrans2: Towards high-quality and accessible machine translation models for all 22 scheduled indian languages](#). *Preprint*, arXiv:2305.16307.
- Leo Gao, Jonathan Tow, Baber Abbasi, Stella Biderman, Sid Black, Anthony DiPofi, Charles Foster, Laurence Golding, Jeffrey Hsu, Alain Le Noac’h, Haonan Li, Kyle McDonell, Niklas Muennighoff, Chris Ociepa, Jason Phang, Laria Reynolds, Hailey Schoelkopf, Aviya Skowron, Lintang Sutawika, and 5 others. 2024. [The language model evaluation harness](#).
- Omer Goldman, Uri Shaham, Dan Malkin, Sivan Eiger, Avinatan Hassidim, Yossi Matias, Joshua Maynez, Adi Mayrav Gilady, Jason Riesa, Shruti Rijhwani, Laura Rimell, Idan Szpektor, Reut Tsarfaty, and Matan Eyal. 2025. [Eclectic: a novel challenge set for evaluation of cross-lingual knowledge transfer](#). *Preprint*, arXiv:2502.21228.
- Ran Gong, Qiuyuan Huang, Xiaojian Ma, Hoi Vo, Zane Durante, Yusuke Noda, Zilong Zheng, Song-Chun Zhu, Demetri Terzopoulos, Li Fei-Fei, and Jianfeng Gao. 2023. [Mindagent: Emergent gaming interaction](#). *Preprint*, arXiv:2309.09971.
- Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. 2024. [The llama 3 herd of models](#). *Preprint*, arXiv:2407.21783.
- Leon Guertler, Bobby Cheng, Simon Yu, Bo Liu, Leshem Choshen, and Cheston Tan. 2025. [Textarena](#). *Preprint*, arXiv:2504.11442.
- Alejandro Hernández-Cano, Alexander Hägele, Allen Hao Huang, Angelika Romanou, Antoni-Joan Solergibert, Barna Pasztor, Bettina Messmer, Dhia Garbaya, Eduard Frank Ďurech, Ido Hakimi, Juan García Giraldo, Mete Ismayilzada, Negar Foroutan, Skander Moalla, Tiancheng Chen, Vinko Sabolčec, Yixuan Xu, Michael Aerni, Badr AlKhamissi, and 82 others. 2025. [Apertus: Democratizing Open and Compliant LLMs for Global Language Environments](#). <https://arxiv.org/abs/2509.14233>.
- Junjie Hu, Sebastian Ruder, Aditya Siddhant, Graham Neubig, Orhan Firat, and Melvin Johnson. 2020. [Xtreme: A massively multilingual multi-task benchmark for evaluating cross-lingual generalization](#). *Preprint*, arXiv:2003.11080.
- Haoyang Huang, Tianyi Tang, Dongdong Zhang, Xin Zhao, Ting Song, Yan Xia, and Furu Wei. 2023. [Not all languages are created equal in LLMs: Improving multilingual capability by cross-lingual-thought prompting](#). In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 12365–12394, Singapore. Association for Computational Linguistics.
- Xu Huang, Wenhao Zhu, Hanxu Hu, Conghui He, Lei Li, Shujian Huang, and Fei Yuan. 2025. [BenchMAX: A comprehensive multilingual evaluation suite for large language models](#). In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 16751–16774, Suzhou, China. Association for Computational Linguistics.
- Maxim Ifergan, Leshem Choshen, Roei Aharoni, Idan Szpektor, and Omri Abend. 2024. [Beneath the surface of consistency: Exploring cross-lingual knowledge representation sharing in llms](#). *Preprint*, arXiv:2408.10646.

- Zhengbao Jiang, Antonios Anastasopoulos, Jun Araki, Haibo Ding, and Graham Neubig. 2020. [X-FACTR: Multilingual factual knowledge retrieval from pre-trained language models](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 5943–5959, Online. Association for Computational Linguistics.
- Pratik Joshi, Sebastin Santy, Amar Budhiraja, Kalika Bali, and Monojit Choudhury. 2020. [The state and fate of linguistic diversity and inclusion in the NLP world](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, ACL 2020, Online, July 5-10, 2020*, pages 6282–6293. Association for Computational Linguistics.
- Sneha Kudugunta, Isaac Caswell, Biao Zhang, Xavier Garcia, Christopher A. Choquette-Choo, Katherine Lee, Derrick Xin, Aditya Kusupati, Romi Stella, Ankur Bapna, and Orhan Firat. 2023. [MADLAD-400: A multilingual and document-level large audited dataset](#). *Preprint*, arXiv:2309.04662.
- Harold W. Kuhn. 1951. A simplified two-person poker. *Contributions to the Theory of Games*.
- Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the ACM SIGOPS 29th Symposium on Operating Systems Principles*.
- Peerat Limkonchotiawat, Wuttikorn Ponwitayarat, Can Udomcharoenchaikit, Ekapol Chuangsuwanich, and Sarana Nutanong. 2022. [CL-ReLKT: Cross-lingual language knowledge transfer for multilingual retrieval question answering](#). In *Findings of the Association for Computational Linguistics: NAACL 2022*, pages 2141–2155, Seattle, United States. Association for Computational Linguistics.
- Xi Victoria Lin, Todor Mihaylov, Mikel Artetxe, Tianlu Wang, Shuohui Chen, Daniel Simig, Myle Ott, Naman Goyal, Shruti Bhosale, Jingfei Du, Ramakanth Pasunuru, Sam Shleifer, Punit Singh Koura, Vishrav Chaudhary, Brian O’Horo, Jeff Wang, Luke Zettlemoyer, Zornitsa Kozareva, Mona Diab, and 2 others. 2022. [Few-shot learning with multilingual generative language models](#). In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 9019–9052, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.
- Robert Litschko, Oliver Kraus, Verena Blaschke, and Barbara Plank. 2025. [Cross-dialect information retrieval: Information access in low-resource and high-variance languages](#). *Preprint*, arXiv:2412.12806.
- Alexander H. Liu, Kartik Khandelwal, Sandeep Subramanian, Victor Jouault, Abhinav Rastogi, Adrien Sadé, Alan Jeffares, Albert Jiang, Alexandre Cahill, Alexandre Gavaudan, Alexandre Sablayrolles, Amélie Héliou, Amos You, Andy Ehrenberg, Andy Lo, Anton Eliseev, Antonia Calvi, Avinash Sooriyarachchi, Baptiste Bout, and 101 others. 2026. [Ministral 3](#). *Preprint*, arXiv:2601.08584.
- Dan Malkin, Tomasz Limisiewicz, and Gabriel Stanovsky. 2022. [A balanced data approach for evaluating cross-lingual transfer: Mapping the linguistic blood bank](#). In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 4903–4915, Seattle, United States. Association for Computational Linguistics.
- Shubham Mittal, Keshav Kolluru, Soumen Chakrabarti, and Mausam. 2023. [mokb6: A multilingual open knowledge base completion benchmark](#). *Preprint*, arXiv:2211.06959.
- Itai Mondshine, Tzuf Paz-Argaman, and Reut Tsarfay. 2025. [Beyond English: The impact of prompt translation strategies across languages and tasks in multilingual LLMs](#). In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 1331–1354. Association for Computational Linguistics.
- Philipp Moritz, Robert Nishihara, Stephanie Wang, Alexey Tumanov, Richard Liaw, Eric Liang, Melih Elibol, Zongheng Yang, William Paul, Michael I. Jordan, and Ion Stoica. 2018. [Ray: A distributed framework for emerging ai applications](#). *Preprint*, arXiv:1712.05889.
- Guilherme Penedo, Hynek Kydlíček, Loubna Ben allal, Anton Lozhkov, Margaret Mitchell, Colin Raffel, Leandro Von Werra, and Thomas Wolf. 2024. [The fineweb datasets: Decanting the web for the finest text data at scale](#). In *The Thirty-eight Conference on Neural Information Processing Systems Datasets and Benchmarks Track*.
- Guilherme Penedo, Hynek Kydlíček, Vinko Sabolčec, Bettina Messmer, Negar Foroutan, Amir Hossein Kargaran, Colin Raffel, Martin Jaggi, Leandro Von Werra, and Thomas Wolf. 2025. [Fineweb2: One](#)

- pipeline to scale them all – adapting pre-training data processing to every language. *Preprint*, arXiv:2506.20920.
- Edoardo Maria Ponti, Goran Glavaš, Olga Majewska, Qianchu Liu, Ivan Vulić, and Anna Korhonen. 2020a. [XCOPA: A multilingual dataset for causal commonsense reasoning](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 2362–2376, Online. Association for Computational Linguistics.
- Edoardo Maria Ponti, Goran Glavaš, Olga Majewska, Qianchu Liu, Ivan Vulić, and Anna Korhonen. 2020b. [XCOPA: A multilingual dataset for causal commonsense reasoning](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 2362–2376, Online. Association for Computational Linguistics.
- Jirui Qi, Raquel Fernández, and Arianna Bisazza. 2023. [Cross-lingual consistency of factual knowledge in multilingual language models](#). In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, page 10650–10666. Association for Computational Linguistics.
- Dan Qiao, Chenfei Wu, Yaobo Liang, Juntao Li, and Nan Duan. 2023. [Gameeval: Evaluating llms on conversational games](#). *Preprint*, arXiv:2308.10032.
- Qwen Team. 2024. [Qwen2.5 technical report](#). *Preprint*, arXiv:2412.15115.
- Qwen Team. 2025. [Qwen3 technical report](#). *Preprint*, arXiv:2505.09388.
- Angelika Romanou, Negar Foroutan, Anna Sotnikova, Zeming Chen, Sree Harsha Nelaturu, Shivalika Singh, Rishabh Maheshwary, Micol Altomare, Mohamed A. Haggag, Snegha A, Alfonso Amayuelas, Azril Hafizi Amirudin, Viraat Aryabumi, Danylo Boiko, Michael Chang, Jenny Chim, Gal Cohen, Aditya Kumar Dalmia, Abraham Diress, and 40 others. 2024. [Include: Evaluating multilingual language understanding with regional knowledge](#). *Preprint*, arXiv:2411.19799.
- Patrick Rothfuss. 2011. *The Wise Man’s Fear*.
- Uri Shaham, Jonathan Herzig, Roee Aharoni, Idan Szpektor, Reut Tsarfaty, and Matan Eyal. 2024. [Multilingual instruction tuning with just a pinch of multilinguality](#). *Preprint*, arXiv:2401.01854.
- Freda Shi, Mirac Suzgun, Markus Freitag, Xuezhi Wang, Suraj Srivats, Soroush Vosoughi, Hyung Won Chung, Yi Tay, Sebastian Ruder, Denny Zhou, Dipanjan Das, and Jason Wei. 2022a. [Language models are multilingual chain-of-thought reasoners](#). *Preprint*, arXiv:2210.03057.
- Freda Shi, Mirac Suzgun, Markus Freitag, Xuezhi Wang, Suraj Srivats, Soroush Vosoughi, Hyung Won Chung, Yi Tay, Sebastian Ruder, Denny Zhou, Dipanjan Das, and Jason Wei. 2022b. [Language models are multilingual chain-of-thought reasoners](#). *ArXiv*, abs/2210.03057.
- Aaditya Singh, Adam Fry, Adam Perelman, Adam Tart, Adi Ganesh, Ahmed El-Kishky, Aidan McLaughlin, Aiden Low, AJ Ostrow, Akhila Ananthram, Akshay Nathan, Alan Luo, Alec Helyar, Aleksander Madry, Aleksandr Efremov, Aleksandra Spyra, Alex Baker-Whitcomb, Alex Beutel, Alex Karpenko, and 467 others. 2026. [Openai gpt-5 system card](#). *Preprint*, arXiv:2601.03267.
- Shivalika Singh, Angelika Romanou, Clémentine Fourrier, David I. Adelani, Jian Gang Ngui, Daniel Vila-Suero, Peerat Limkonchotiwat, Kelly Marchisio, Wei Qi Leong, Yosephine Susanto, Raymond Ng, Shayne Longpre, Wei-Yin Ko, Madeline Smith, Antoine Bosselut, Alice Oh, Andre F. T. Martins, Leshem Choshen, Daphne Ippolito, and 4 others. 2024. [Global mmlu: Understanding and addressing cultural and linguistic biases in multilingual evaluation](#). *Preprint*, arXiv:2412.03304.
- Gemma Team, Sherif El Abd, Vaibhav Aggarwal, Robin Algayres, Alek Andreev, Olivier Bachem, Ian Ballantyne, Cormac Brick, Victor Cărbune, Michelle Casbon, Mayank Chaturvedi, Victor Cotruta, Alice Coucke, Phil Culliton, Robert Dadashi, Lucas Dixon, Mohamed Elhawaty, Utku Evci, Clément Farabet, and 282 others. 2026. [Gemma 4 technical report](#). *Preprint*, arXiv:2607.02770.
- Iulia Turc, Kenton Lee, Jacob Eisenstein, Ming-Wei Chang, and Kristina Toutanova. 2021. [Revisiting the primacy of english in zero-shot cross-lingual transfer](#). *Preprint*, arXiv:2106.16171.
- Denny Vrandečić and Markus Krötzsch. 2014. [Wiki-data: a free collaborative knowledgebase](#). *Commun. ACM*, 57(10):78–85.
- Eric W. Weisstein. [Tic-tac-toe](#). MathWorld—A Wolfram Resource.
- Yue Wu, Xuan Tang, Tom M. Mitchell, and Yuanzhi Li. 2024. [Smartplay: A benchmark for llms as intelligent agents](#). *Preprint*, arXiv:2310.01557.

Linting Xue, Noah Constant, Adam Roberts, Mihir Kale, Rami Al-Rfou, Aditya Siddhant, Aditya Barua, and Colin Raffel. 2021. [mt5: A massively multilingual pre-trained text-to-text transformer](#). *Preprint*, arXiv:2010.11934.

Jianzhu Yao, Kevin Wang, Ryan Hsieh, Haisu Zhou, Tianqing Zou, Zerui Cheng, Zhangyang Wang, and Pramod Viswanath. 2025. [Spin-bench: How well do llms plan strategically and reason socially?](#) *Preprint*, arXiv:2503.12349.

Wenhao Zhu, Shujian Huang, Fei Yuan, Shuaijie She, Jiajun Chen, and Alexandra Birch. 2024. [Question translation training for better multilingual reasoning](#). In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 8411–8423, Bangkok, Thailand. Association for Computational Linguistics.

A Prompt Templates

We use model-specific chat wrappers to match each model’s expected input format, but keep the task instruction as consistent as possible across models. The scientifically relevant prompt variants are the default action prompt and the language-conditioned reasoning prompt used in our intervention experiments.

Default action prompt. This prompt is used when the model is asked to play the game without an explicit instruction to reason in the provided language.

You are a competitive game player. Make sure you read the game instructions carefully, and put your final answer within `\boxed{}`.

Language-conditioned reasoning prompt. This prompt is used in the main multilingual experiments. It instructs the model to reason in the language provided by the environment interface.

You are a competitive game player. Make sure you read the game instructions carefully, reason in the language provided, and put your final answer within `\boxed{}`.

B Experimental Setup

Our experiments involve inference only; no model training or hyperparameter search was performed. All models are served with vLLM (Kwon et al., 2023) and orchestrated with Ray (Moritz et al., 2018) for distributed rollout collection.

A primary experimental run evaluates one model m on one game g across all eight languages and comprises 28,800 self-play games. Each run uses two NVIDIA H200 GPUs. Across three models and six games, the primary evaluation comprises 18 runs and 518,400 games. Excluding Iterated Prisoner’s Dilemma, each primary run required approximately 6 H200 GPU-hours.

For Global-MMLU, we used the implementation provided in the LM-Evaluation-Harness (Gao et al., 2024) repository and retained its default task configuration and evaluation parameters. For Belebele (Bhandarkar et al., 2024), we used the official benchmark repository.

C Translation Workflow

Concretely, we used a one-shot prompt to extend each game with multilingual support. Claude Opus 4.8 (Anthropic, 2026) was given an original monolingual environment, a multilingual extension of a reference environment, and the corresponding English template. It was then prompted to generate the multilingual implementation and English template for a new game, given the target environment in its original monolingual form.

After validating this process across several games, we translated the resulting English templates using GPT-5.2 (Singh et al., 2026). Google Translate was used to produce back-translations, and native speakers reviewed their fidelity to the intended game interactions. Manual review by three native speakers rarely identified substantive issues.

D Game Environments

TextArena (Guertler et al., 2025) follows the OpenAI Gym (now Gymnasium) (Brockman et al., 2016) interface, enabling easy use and extension. For multilingual games, each player’s language is specified through a language mapping passed to the environment’s `reset` method, as illustrated below.

Multilingual game playing illustration

```
import textarena as ta

# initialize the players
agents = {
    0: ta.agents.OpenRouterAgent("g_
    ↪ oogle/gemma-4-31b-it"),
    1: ta.agents.OpenRouterAgent("g_
    ↪ oogle/gemma-4-31b-it"),
}
```

```
# initialize the environment
env = ta.make(env_id="TicTacToe-v0")
env.reset(num_players=len(agents),
          ↪ lang_mapping={0: "he", 1: "en"})

# main game loop
done = False
while not done:
    player_id, observation =
        ↪ env.get_observation()
    action = agents[player_id](obse_
        ↪ rvation)
    done, step_info =
        ↪ env.step(action=action)
    rewards, game_info = env.close()
    print(rewards)
    print(game_info)
```

D.1 Nim

Nim (Bouton, 1901) is a two-player strategy game played with several piles of objects. Players take turns removing one or more objects from a single pile. Under the standard rules, the player who removes the final object wins. The game requires players to reason about the configuration of the remaining piles and select moves that leave the opponent in a disadvantageous position.

Action format. Moves are submitted as [pile quantity], where pile indexes one of the piles and quantity is the number of objects to remove; e.g., [0 3] removes three objects from pile 0.

Examples of the starting game prompt:

Hebrew Translation

[משחק] 0! שחקן, לנימים הבא ברוך (משחק)
:חוקים
- המירעם דחא צפח תוחפל רסה, קרותב
↪ דבלב תחא.
- ידכ '[תומכ המיר-ע] טמרופב שמתשה
↪ '[0 3]'. המגודל, מיצפח ריסהל
- מנצח! האחרון החפץ את שלוקח מי
[משחק] הנוכחית: האבנים ערימת
ערימה 0: 3
ערימה 1: 4
ערימה 2: 5

Spanish Translation

[JUEGO] ¡Bienvenido a Nim, Jugador
↪ 0!
Reglas:
- En tu turno, elimina al menos un
↪ objeto de exactamente una
↪ pila.

- Usa el formato '[pila cantidad]'
↪ para eliminar objetos, por
↪ ejemplo '[0 3]'.
- ¡Quien tome el/los último(s)
↪ objeto(s) gana!
[JUEGO] Pila actual:
pila 0: 3
pila 1: 4
pila 2: 5

D.2 Tic Tac Toe

Tic Tac Toe (Weisstein) is a two-player game played on a (3×3) grid. Players alternate placing their symbol, either (X) or (O), in an empty cell. The first player to form a horizontal, vertical, or diagonal line of three symbols wins. If the grid is filled without either player completing such a line, the game ends in a draw.

Action format. Moves are submitted as [cell], where cell is the index (0–8) of an empty square; e.g., [4] places the player's mark in the center cell.

Examples of the starting game prompt:

Chinese Translation

[游戏] 你是井字棋游戏中的玩家 1。
你的目标是在棋盘上连成三个（横向、
↪ 纵向或对角线）。
轮到你时，请选择一个格子编号（0–8）
↪ 来放置你的标记。
例如，'[4]' 将你的标记放在棋盘中央格子。
作为玩家 1，你的标记是 'x'，对手的标记是
↪ 'o'。
[游戏] 当前棋盘：

```
0 | 1 | 2
---+---+---
3 | 4 | 5
---+---+---
6 | 7 | 8
```

可用落子位置: '[0]', '[1]', '[2]',
↪ '[3]', '[4]', '[5]', '[6]',
↪ '[7]', '[8]'

Hebrew Translation

סקיא קחשמב 0 וקחש התא [קחש]מ
↪ .לוגיע
קצרב השולש גישהל איה קלש הרטמה
↪ לע (ווסכלאב וא תיכנא, תיקפו)א
↪ חולה.
ובש (0–8) אתה רפסמ תא רחב, קרותב
↪ קלש ומיסה תא ביצהל הצרת.

קלש נמיסה תא ביצמ '[4]', המגודל
 → יזכרמה אתב.
 '0' אוה קלש נמיסה, 0 וקחש רותב,
 → 'X' אוה קלש ביריהו.
 הנוכחי: הלוח [משחק]

```

0 | 1 | 2
---+---+---
3 | 4 | 5
---+---+---
6 | 7 | 8
  
```

מינימז מיכלהמ: '[0]', '[1]',
 → '[2]', '[3]', '[4]', '[5]',
 → '[6]', '[7]', '[8]'

D.3 Colonel Blotto

Colonel Blotto (Borel, 1953) is a two-player resource-allocation game played across several battlefields. Each player simultaneously distributes a fixed number of troops among the battlefields. A battlefield is won by the player who assigns more troops to it, while equal allocations result in a tie. The player who wins the most battlefields wins the game.

Action format. Allocations are submitted as [A# B# C#], assigning a non-negative number of units to each field; the amounts must sum to exactly 20. E.g., [A7 B7 C6].

Examples of the starting game prompt:

Malay Translation

[PERMAINAN] Anda ialah Komander
 → Alpha dalam permainan Colonel
 → Blotto. Dalam setiap pusingan,
 → anda mesti mengagihkan tepat
 → 20 unit merentasi medan
 → berikut: A, B, C
 Format: '[A7 B7 C6]'
 Menangi majoriti medan untuk
 → memenangi pusingan!
 [PERMAINAN] === COLONEL BLOTTO -
 → Pusingan 1/9 ===
 Pusingan dimenangi - Komander
 → Alpha: 0, Komander Beta: 0

English Translation

[GAME] You are Commander Alpha in
 → a game of ColonelBlotto. Each
 → round, you have to allocate
 → exactly 20 units across
 → fields: A, B, C

Format: '[A7 B7 C6]'
 Win the majority of fields to win
 → the round!
 [GAME] === COLONEL BLOTTO - Round
 → 1/9 ===
 Rounds Won - Commander Alpha: 0,
 → Commander Beta: 0

D.4 Kuhn Poker

Kuhn Poker (Kuhn, 1951) is a simplified two-player poker game using only three cards: a Jack, Queen, and King. Each player is dealt one card, while the remaining card is hidden. Players then complete a single betting round in which they may check, bet, call, or fold. If neither player folds, the player holding the higher card wins.

Action format. Moves are submitted as one of [check], [bet], [call], or [fold], restricted to the actions legal at the current point of the betting sequence.

Examples of the starting game prompt:

French Translation

[JEU] Vous êtes le joueur 1 dans
 → une partie de Kuhn Poker en 3
 → manches.
 Règles du jeu :
 - Le Kuhn Poker utilise un jeu de
 → 3 cartes : J, Q, K (J est la
 → plus faible, K la plus forte)
 - Chaque joueur mise 1 jeton en
 → entrée et reçoit 1 carte à
 → chaque manche (remarque : les
 → cartes sont distribuées sans
 → remise, vous ne pouvez donc
 → pas avoir la même carte que
 → votre adversaire)
 - La partie se déroule sur 3
 → manches
 - Le joueur ayant le plus de
 → jetons à la fin de toutes les
 → manches gagne
 Règles des actions :
 - '[check]' : Passer sans miser
 → (uniquement si aucune mise n'
 → est en cours)
 - '[bet]' : Ajouter 1 jeton au pot
 → (uniquement si aucune mise n'
 → est en cours)
 - '[call]' : Suivre la mise de l'
 → adversaire en ajoutant 1 jeton
 - '[fold]' : Se coucher et laisser
 → l'adversaire remporter le pot

[JEU] ### Début de la manche 1 sur
 ↳ 3. Votre carte est : 'J'
 [JEU] Vos actions disponibles sont
 ↳ : '[check]', '[bet]'

German Translation

[SPIEL] Du bist Spieler 1 in einem
 ↳ 3-Runden-Spiel von Kuhn Poker.
 Spielregeln:
 - Kuhn Poker verwendet ein
 ↳ 3-Karten-Deck mit J, Q, K (J
 ↳ ist die niedrigste, K die
 ↳ höchste Karte)
 - Jeder Spieler zahlt 1 Chip als
 ↳ Einsatz und erhält in jeder
 ↳ Runde 1 Karte (Hinweis: Die
 ↳ Karten werden ohne Zurücklegen
 ↳ ausgeteilt, daher kannst du
 ↳ nicht dieselbe Karte wie dein
 ↳ Gegner haben)
 - Das Spiel geht über 3 Runden
 - Der Spieler mit den meisten
 ↳ Chips nach allen Runden
 ↳ gewinnt
 Aktionsregeln:
 - '[check]': Passen ohne zu setzen
 ↳ (nur wenn kein Einsatz auf dem
 ↳ Tisch liegt)
 - '[bet]': 1 Chip zum Pot
 ↳ hinzufügen (nur wenn kein
 ↳ Einsatz auf dem Tisch liegt)
 - '[call]': Einen gegnerischen
 ↳ Einsatz mit 1 Chip ausgleichen
 - '[fold]': Deine Hand aufgeben
 ↳ und dem Gegner den Pot
 ↳ überlassen
 [SPIEL] ### Runde 1 von 3 beginnt.
 ↳ Deine Karte ist: 'K'
 [SPIEL] Deine verfügbaren Aktionen
 ↳ sind: '[check]', '[bet]'

D.5 Simple Tak

Simple Tak (Rothfuss, 2011) is a simplified two-player connection game played on a square grid. Players take turns placing pieces on empty spaces, with the objective of forming a continuous path connecting two opposite sides of the board. Unlike standard Tak, pieces cannot be stacked or moved after placement. A player may therefore either extend their own path or block spaces needed by their opponent.

Action format. Moves are submitted as [cell], where cell is the index (0–15) of an empty cell; e.g., [12] places the player's stone in cell 12.

Examples of the starting game prompt:

Arabic Translation

يف 0 بع اللل تنأ [ةبع للل]
 ↳ SimpleTak.
 'O' زم رلاب لأراجحأ رهظت ،ةحول للا لىلع
 ↳ 'X'. زم رلاب لأمصخ راجحأ رهظتو

ةدحاو ةغراف ةناخ رتخا ،أرود يف
 ↳ .اهيف لأرجح عضو ،اهمقرر مادختساب
 لأرجح عضبي '[12]' ،لاشملال لىبس لىلع
 ↳ 12. ةناخلا يف

أراجحأ نم لمصتم راسم نىوؤت وه أصفده
 ↳ نم نىتلباقتم نىتفاح نىب طبرى
 ↳ لىل لىلعأل نم امإ ،ةحول للا
 ↳ لىل راسىلأ نم وأ لفسألأ
 ↳ نىمىلأ.
 الجحالة: اللوحة حالة [اللعبه]

0	1	2	3
4	5	6	7
8	9	10	11
12	13	14	15

حالاتملا تالأرجحلا
 ↳ : [0], [1], [2],
 ↳ [3], [4], [5], [6], [7], [8],
 ↳ [9], [10], [11], [12], [13],
 ↳ [14], [15]

English Translation

[GAME] You are Player 0 in
 ↳ SimpleTak.
 On the board, your stones appear
 ↳ as 'O' and your opponent's
 ↳ stones appear as 'X'.

On your turn, choose one empty
 ↳ cell (by its numbered index)
 ↳ and place your stone there.
 For example, '[12]' places your
 ↳ stone in cell 12.

Your objective is to form a
 ↳ continuous path of your stones
 ↳ that connects two opposite
 ↳ edges of the board
 ↳ (top-to-bottom or
 ↳ left-to-right).
 [GAME] Current Board:

0	1	2	3
4	5	6	7

```

+-----+-----+-----+-----+
| 8 | 9 | 10 | 11 |
+-----+-----+-----+-----+
| 12 | 13 | 14 | 15 |
+-----+-----+-----+-----+
Available Moves: [0], [1], [2],
↳ [3], [4], [5], [6], [7], [8],
↳ [9], [10], [11], [12], [13],
↳ [14], [15]

```

D.6 Iterated Prisoners Dilemma

The Iterated Prisoner’s Dilemma (Axelrod, 1984) is a repeated two-player mixed-motive game. In each round, both players simultaneously choose to cooperate or defect: mutual cooperation yields 3 points each, mutual defection 1 point each, and unilateral defection yields 5 points to the defector and 0 to the cooperator. Before each decision, players exchange free-form messages over a fixed number of communication turns, allowing negotiation, promises, and deception. The game spans 10 rounds, and the player with the higher cumulative score wins.

Action format. During communication turns, players exchange free-form text. In the decision phase, the message must contain [Cooperate] or [Defect].

Examples of the starting game prompt:

English Translation

```

[GAME] You are Player 0 in an
↳ Iterated Prisoner's Dilemma
↳ spanning 10 rounds.

Game Structure:
- Before each decision you have 1
↳ turns to communicate freely.
- After that, both players
↳ simultaneously choose to
↳ cooperate or defect.

Payoff Matrix (fixed each round):
- Both Cooperate -> each 3
- Both Defect -> each 1
- One Defects, one Cooperates 5
↳ Defector 5, Cooperator 0

How to Play:
- During conversation: type any
↳ text you wish.

```

```

- During decision phase: include
↳ '[Cooperate]' or '[Defect]'
↳ (case-insensitive). You may
↳ add extra text before/after
↳ the token.
[GAME] --- Starting Round 1 ---

```

Chinese Translation

[游戏] 你是玩家 0，正在进行一场持续 10
↳ 轮的重复囚徒困境游戏。

游戏结构：

- 在每次决策之前，你有 1
↳ 个回合可以自由交流。
- 之后，双方玩家同时选择合作或背叛。

收益矩阵，每轮固定：

- 双方合作 -> 每人获得 3
- 双方背叛 -> 每人获得 1
- 一方背叛，一方合作 5，背叛者获得 5，
↳ 合作者获得 0

玩法说明：

- 在交流阶段：输入任何你想说的文字。
 - 在决策阶段：包含 '[Cooperate]' 或
↳ '[Defect]'，不区分大小写。
↳ 你可以在该标记前后添加额外文本。
- [游戏] --- 第 1 轮开始 ---

E Multilingual UI Localization

The languages used in this paper’s experiments are localized with the manual, native-speaker-reviewed workflow of Sec. 2. This appendix documents the *separate*, fully automatic pipeline, with only sporadic manual verification, behind the released multilingual resource. It retains that workflow’s structural guarantees but drops systematic native review in order to scale across the resource spectrum. We contribute upstream adaptations to the open-source TextArena project (Guertler et al., 2025), making 65 games and one shared UI file translatable (64 locale files, roughly 1,000 player-facing strings carrying about 1,100 {placeholder} slots and 350 literal [action tokens]), spanning high-resource world languages such as Spanish through the low-resource frontier. These modifications are integrated into the main TextArena codebase and released under the project’s existing MIT License, which permits modification and redistribution; the original copyright and license notice are retained. Because a dropped or renamed placeholder crashes the runtime and a corrupted action token silently breaks playability, the requirement is not merely fluency but *verifiable struc-*

tural and semantic faithfulness; with no native reviewer to lean on, verifiability—not translation—is the binding constraint. Two coordinated pipelines share this requirement and a common determinism layer, differing only where the language’s resource level forces a different translator and verifier.

A determinism layer shared by both tracks. Before any model sees a string, every must-keep span—`{placeholder}`, escaped-brace literal, `[action token]`, backticked code, and card label—is replaced by an ordered sentinel and reinserted afterward. Token preservation thus becomes a property we *enforce and check* (the sentinel multiset in the output must equal the input’s) rather than hope a model respects. We thus retire token-corruption and placeholder-loss failures by construction for machine-translation and LLM outputs alike. A separate deterministic parser-token oracle re-derives each game’s action grammar from its environment code and confirms that every literal keyword and concrete example survives translation, which *guarantees structural playability independent of prose quality*. The sentinel form was chosen empirically: of twelve candidates only three survived machine translation verbatim across all tested scripts (including right-to-left Arabic), and of those only the CJK corner bracket avoids colliding with the corpus’s own `[tokens]` and `{placeholders}`.

Higher- and mid-resource languages. For languages that strong instruction models read well, translation uses a gateway serving Llama-3.1-405B and Qwen2.5-72B, and quality is enforced by a layered pipeline: cheap deterministic filters (script and homoglyph contamination, literal-keyword translation, brace-literal damage), the parser-token oracle, and a two-stage semantic gate—a full-corpus sweep by a generation-tier model followed by confirmation from an independent, more capable reviewer. Across the six-language batch we audit in detail here—a subset of the released higher/mid-resource set—the deterministic tiers eliminated the entire class of functional defects (0 keyword or example losses across 65×6 games), and the semantic sweep flagged 2.9% of game–language pairs, of which confirmation kept ten genuine *prose* mistranslations—an inverted objective, a wrong quantifier, a mislabeled domain term—all of them in games outside the hand-inspected sample—which is why the semantic sweep must be exhaustive rather than a spot-check. The pipeline was verified against the arabic translations that were manually verified and, the same detector found essentially zero residual defects in both the reference corpus and the fully automatic output while still catching real defects in an adversarial gener-

ation. While we cannot have guarantees, this strengthens the belief that the process is reliable.

The low-resource frontier. Below the band that gateway models read, two assumptions of the first track fail: no served model translates the language competently, and no author or judge can be assumed to read it. Translation therefore uses open multilingual machine translation (NLLB-200; Costa-Jussà et al., 2022), and verification must be *reader-free*. We localized 143 additional low-resource languages this way; the central methodological result of this track concerns the verifier, and it is cautionary.

Reader-free verification: what fails, and what works. The natural reader-free check—translate the candidate, back-translate it to English with independent models, and compare against the source—*over-flags severely* at the frontier, because the back-translation of a low-resource language *into* English is itself unreliable and injects spurious disagreement. Measured against a direct judge it reported 108, 162, and 317 divergences for Hausa, Yoruba, and Twi where essentially none are real. A fixed language identifier (`fastText lid.176`) is likewise unusable here, misclassifying fluent, correct Hausa as a different language. The reliable instrument is instead a *direct* bilingual fidelity judge: a capable instruction model reads the English source and the candidate together and scores faithfulness, run *carefully* (one string at a time, with an explicit instruction to check facts, quantities, and entities) and required to *agree across two model families*. Validated on the human-known control it reaches 100% sensitivity and specificity, whereas a batched version of the same judge catches only about a third of deliberately corrupted translations.

Tiered labeling. Every string that the verifier confirms wrong, or whose tokens cannot be restored safely, is reverted to English, so no known-wrong string ships; the cost is a measured English-fallback fraction reported per language rather than a silent error. Languages are tiered by measured meaning fidelity on a sampled audit: those at or above 85% (median 98%) are labeled certified-flagged, the remainder experimental. We are explicit that this is *machine verification, not native review*: each shipped language publishes its measured fidelity and target-language coverage, and a runtime helper warns when a non-certified locale is loaded. The residual weak tail—languages where even careful two-model judging is uncertain because the judge’s own competence is limited—marks the ceiling of open-model localization, beyond which native review, not further automation, is the only lever.

Consistent with this, a family-specialist study found only narrow gains: a purpose-built African translation model improved one of fifteen weak languages and was worse on the other fourteen, confirming that general machine translation with careful verification, not specialist translators, is the workhorse at this scale.

guage its tier.

Scale and cost. Localization compute is not the bottleneck; verifiability is. The full decode across the target languages is on the order of tens of GPU-hours, dominated by the low-resource machine translation; the scarce resource is a verifier trustworthy in languages no author reads, which the careful two-model direct judge supplies. All produced locale files and per-language confidence records are released with TextArena; the tooling that reproduces the pipeline is kept on a separate branch for reproducibility, but we did not ask the TextArena maintainers to merge it.

Language inventory. Tab. E.1 and Tab. E.2 enumerate every localized language with its ISO 639-3 code, dominant script (ISO 15924), the forward translation model, and two independent resource signals: the resource class of Joshi et al. (2020, 0 = least-resourced, 5 = most) and the number of speakers recorded in Wikidata (property P1098 Vrandečić and Krötzsch, 2014), with ‘–’ where a source has no entry. Both tables are ordered from higher- to lower-resource (by Joshi class, then speaker count), so the descent into the long tail is visible top-to-bottom. Table E.1 lists Track A: the 8 core experiment languages (localized with GPT-5.2 and Opus 4.8 under native-speaker review) and 42 higher/mid-resource expansion languages translated with Llama-3.1-405B (Grattafiori et al., 2024) (Qwen2.5-72B (Qwen Team, 2024) for CJK and Southeast-Asian scripts) and verified by an independent, more capable LLM rather than a native reviewer. Tab. E.2–E.4 list the 143 languages of Track B, the low-resource frontier. Here the forward translation is produced by the dedicated machine translation (MT) model NLLB-200 (Costa-Jussà et al., 2022) (Chokwe via the Toucan African-language model, Elmadany et al., 2024); meaning fidelity is then checked by a careful two-model LLM judge—Llama-3.1-405B (Grattafiori et al., 2024) and Qwen2.5-72B (Qwen Team, 2024), per-leaf concordance—rather than a native reviewer, with MADLAD-400 (Kudugunta et al., 2023) used alongside NLLB for back-translation calibration and family-specialist MT (IndicTrans2, Gala et al., 2023, Toucan, Elmadany et al., 2024) trialed on the Indic and African tails, where it gave only narrow gains over NLLB. For Track B we additionally report the measured meaning-fidelity and target-language coverage percentages that assign each lan-

Table E.1: Track A languages (higher/mid-resource): 8 core experiment languages plus 42 expansion languages, ordered higher- to lower-resource. *Translator* is the model that produced the localization; *Rev.* distinguishes native human review (*native*, core set) from LLM-only verification (*LLM*, expansion). *Class*: Joshi et al. (Joshi et al., 2020) resource class; *Speakers*: Wikidata P1098 (Vrandečić and Krötzsch, 2014).

Language	ISO	Script	Translator	Rev.	Tier	Class	Speakers
Chinese	zho	Hans	GPT-5.2 / Opus	native	A	5	1299.9M
English	eng	Latn	GPT-5.2 / Opus	native	A	5	753.4M
Spanish	spa	Latn	GPT-5.2 / Opus	native	A	5	485.0M
Arabic	ara	Arab	GPT-5.2 / Opus	native	A	5	315.4M
French	fra	Latn	GPT-5.2 / Opus	native	A	5	208.2M
Japanese	jpn	Jpan	Qwen2.5-72B	LLM	B	5	128.0M
German	deu	Latn	GPT-5.2 / Opus	native	A	5	76.5M
Hindi	hin	Deva	Llama-3.1-405B	LLM	B	4	341.0M
Portuguese	por	Latn	Llama-3.1-405B	LLM	B	4	254.3M
Russian	rus	Cyrl	Llama-3.1-405B	LLM	B	4	154.0M
Turkish	tur	Latn	Llama-3.1-405B	LLM	B	4	82.2M
Korean	kor	Kore	Qwen2.5-72B	LLM	B	4	77.3M
Vietnamese	vie	Latn	Qwen2.5-72B	LLM	B	4	76.0M
Italian	ita	Latn	Llama-3.1-405B	LLM	B	4	64.8M
Persian	fas	Arab	Llama-3.1-405B	LLM	B	4	45.0M
Polish	pol	Latn	Llama-3.1-405B	LLM	B	4	39.7M
Dutch	nld	Latn	Llama-3.1-405B	LLM	B	4	23.1M
Hungarian	hun	Latn	Llama-3.1-405B	LLM	B	4	12.6M
Czech	ces	Latn	Llama-3.1-405B	LLM	B	4	10.7M
Swedish	swe	Latn	Llama-3.1-405B	LLM	B	4	9.2M
Serbian (Cyrillic)	srp	Cyrl	Llama-3.1-405B	LLM	B	4	9.0M
Croatian	hrv	Latn	Llama-3.1-405B	LLM	B	4	7.0M
Finnish	fin	Latn	Llama-3.1-405B	LLM	B	4	5.4M
Catalan	cat	Latn	Llama-3.1-405B	LLM	B	4	4.9M
Bengali	ben	Beng	Llama-3.1-405B	LLM	B	3	300.0M
Indonesian	ind	Latn	Qwen2.5-72B	LLM	B	3	199.0M
Filipino	fil	Latn	Llama-3.1-405B	LLM	B	3	90.0M
Malay	msa	Latn	GPT-5.2 / Opus	native	A	3	77.0M
Tamil	tam	Taml	Llama-3.1-405B	LLM	B	3	75.0M
Urdu	urd	Arab	Llama-3.1-405B	LLM	B	3	68.6M
Ukrainian	ukr	Cyrl	Llama-3.1-405B	LLM	B	3	26.9M
Romanian	ron	Latn	Llama-3.1-405B	LLM	B	3	24.3M
Thai	tha	Thai	Qwen2.5-72B	LLM	B	3	20.7M
Greek	ell	Grek	Llama-3.1-405B	LLM	B	3	15.0M
Afrikaans	afr	Latn	Llama-3.1-405B	LLM	B	3	10.3M
Hebrew	heb	Hebr	GPT-5.2 / Opus	native	A	3	9.3M
Bulgarian	bul	Cyrl	Llama-3.1-405B	LLM	B	3	9.0M
Danish	dan	Latn	Llama-3.1-405B	LLM	B	3	6.0M
Slovak	slk	Latn	Llama-3.1-405B	LLM	B	3	6.0M
Lithuanian	lit	Latn	Llama-3.1-405B	LLM	B	3	4.0M
Galician	glg	Latn	Llama-3.1-405B	LLM	B	3	2.4M
Slovenian	slv	Latn	Llama-3.1-405B	LLM	B	3	2.4M
Latvian	lav	Latn	Llama-3.1-405B	LLM	B	3	1.5M
Estonian	est	Latn	Llama-3.1-405B	LLM	B	3	1.3M
Swahili	swa	Latn	Llama-3.1-405B	LLM	B	2	15.4M
Icelandic	isl	Latn	Llama-3.1-405B	LLM	B	2	321k
Azerbaijani	aze	Latn	Llama-3.1-405B	LLM	B	1	23.0M
Albanian	sqi	Latn	Llama-3.1-405B	LLM	B	1	6.2M
Norwegian Bokmål	nob	Latn	Llama-3.1-405B	LLM	B	1	4.0M
Macedonian	mkd	Cyrl	Llama-3.1-405B	LLM	B	1	2.0M

Table E.2: Track B languages (low-resource tier), ordered higher- to lower-resource. *Translator* is the forward MT model: NLLB-200 (Costa-Jussà et al., 2022) for all except Chokwe (Toucan (Elmadany et al., 2024)); meaning fidelity was then verified by a two-model LLM judge (Llama-3.1-405B (Grattafiori et al., 2024) + Qwen2.5-72B (Qwen Team, 2024)), not by a native reviewer. *Tier*: C = certified-flagged (fidelity $\geq 85\%$), E = experimental. *Class*: Joshi et al. (Joshi et al., 2020); *Speakers*: Wikidata P1098 (Vrandečić and Krötzsch, 2014). *Fid.*: measured meaning-fidelity %; *Cov.*: target-language coverage %.

Language	ISO	Script	Translator	Tier	Class	Speakers	Fid.	Cov.
North Levantine Arabic	apc	Arab	NLLB-200	C	5	44.0M	98	91
Moroccan Arabic	ary	Arab	NLLB-200	C	5	27.5M	100	91
Mesopotamian Arabic	acm	Latn	NLLB-200	C	5	15.7M	95	92
South Levantine Arabic	ajp	Latn	NLLB-200	C	5	11.6M	98	92
Tunisian Arabic	aeb	Arab	NLLB-200	C	5	11.6M	90	90
Taizzi-Adeni Arabic	acq	Latn	NLLB-200	C	5	10.5M	95	92
Najdi Arabic	ars	Arab	NLLB-200	C	5	–	98	93
Basque	eus	Latn	NLLB-200	C	4	750k	90	86
Egyptian Arabic	arz	Arab	NLLB-200	C	3	64.6M	100	92
Uzbek	uzb	Latn	NLLB-200	C	3	27.0M	100	95
Cebuano	ceb	Latn	NLLB-200	C	3	15.9M	98	91
Kazakh	kaz	Cyrl	NLLB-200	C	3	12.9M	98	93
Belarusian	bel	Cyrl	NLLB-200	C	3	7.6M	98	96
Georgian	kat	Geor	NLLB-200	C	3	3.7M	95	91
Punjabi	pan	Guru	NLLB-200	C	2	125.0M	100	97
Marathi	mar	Deva	NLLB-200	C	2	83.1M	100	97
Hausa	hau	Latn	NLLB-200	C	2	43.9M	98	95
Yoruba	yor	Latn	NLLB-200	C	2	37.8M	100	93
Amharic	amh	Ethi	NLLB-200	C	2	21.9M	98	85
Zulu	zul	Latn	NLLB-200	C	2	12.1M	98	95
Xhosa	xho	Latn	NLLB-200	C	2	8.2M	100	86
Tigrinya	tir	Ethi	NLLB-200	C	2	7.5M	95	78
Lao	lao	Laoo	NLLB-200	C	2	5.2M	100	95
Tswana	tsn	Latn	NLLB-200	C	2	4.5M	92	86
Wolof	wol	Latn	NLLB-200	C	2	3.7M	95	70
Maltese	mlt	Latn	NLLB-200	C	2	570k	100	86
Irish	gle	Latn	NLLB-200	C	2	141k	100	89
Sanskrit	san	Deva	NLLB-200	C	2	50k	98	86
Telugu	tel	Telu	NLLB-200	C	1	82.0M	98	95
Javanese	jav	Latn	NLLB-200	C	1	68.3M	100	93
Gujarati	guj	Gujr	NLLB-200	C	1	56.4M	100	96
Bhojpuri	bho	Deva	NLLB-200	C	1	52.2M	98	88
Kannada	kan	Knda	NLLB-200	C	1	43.6M	100	95
Pashto	pus	Arab	NLLB-200	C	1	39.0M	98	95
Malayalam	mal	Mlym	NLLB-200	C	1	37.1M	100	95
Odia	ori	Orya	NLLB-200	C	1	34.5M	100	94
Maithili	mai	Deva	NLLB-200	C	1	33.9M	100	91
Burmese	mya	Mymr	NLLB-200	C	1	32.9M	95	94
Sundanese	sun	Latn	NLLB-200	C	1	32.4M	95	94
Igbo	ibo	Latn	NLLB-200	C	1	27.0M	98	96
Sindhi	snd	Arab	NLLB-200	C	1	24.6M	100	96
Lingala	lin	Latn	NLLB-200	E	1	20.0M	80	85
Malagasy	mlg	Latn	NLLB-200	C	1	18.0M	95	94
Khmer	khm	Khmr	NLLB-200	C	1	16.6M	95	94
Somali	som	Latn	NLLB-200	C	1	16.2M	92	95
Turkmen	tuk	Latn	NLLB-200	C	1	16.0M	100	86
Nepali	nep	Deva	NLLB-200	C	1	15.8M	95	95
Assamese	asm	Beng	NLLB-200	C	1	15.3M	100	95

Table E.3: Track B languages (low-resource tier), *continued*.

Language	ISO	Script	Translator	Tier	Class	Speakers	Fid.	Cov.
Northern Kurdish	kmr	Latn	NLLB-200	C	1	14.6M	98	87
Tajik	tgk	Cyrl	NLLB-200	C	1	14.0M	100	90
South Azerbaijani	azb	Latn	NLLB-200	C	1	13.8M	95	82
Tsonga	tso	Latn	NLLB-200	C	1	13.0M	95	88
Kinyarwanda	kin	Latn	NLLB-200	C	1	12.1M	92	86
Nyanja	nya	Latn	NLLB-200	E	1	12.0M	82	90
Akan	aka	Latn	NLLB-200	C	1	11.0M	98	74
Uyghur	uig	Arab	NLLB-200	C	1	10.4M	92	82
Ilocano	ilo	Latn	NLLB-200	C	1	9.1M	100	89
Shona	sna	Latn	NLLB-200	C	1	8.3M	98	90
Central Kurdish	ckb	Arab	NLLB-200	C	1	7.2M	100	86
Santali	sat	Olck	NLLB-200	E	1	7.2M	80	75
Tumbuka	tum	Latn	NLLB-200	E	1	7.0M	72	82
Kashmiri	kas	Arab	NLLB-200	C	1	6.9M	88	84
Armenian	hye	Armn	NLLB-200	C	1	6.7M	95	95
Kikuyu	kik	Latn	NLLB-200	E	1	6.6M	78	79
Southern Sotho	sot	Latn	NLLB-200	C	1	6.0M	85	89
Kabyle	kab	Latn	NLLB-200	C	1	5.6M	90	80
Minangkabau	min	Latn	NLLB-200	C	1	5.5M	100	90
Mongolian	mon	Cyrl	NLLB-200	C	1	5.2M	98	90
Tatar	tat	Cyrl	NLLB-200	C	1	5.2M	100	86
Buginese	bug	Latn	NLLB-200	E	1	5.0M	80	86
Kikongo	kon	Latn	NLLB-200	E	1	5.0M	80	76
Sicilian	scn	Latn	NLLB-200	C	1	4.7M	100	92
Sango	sag	Latn	NLLB-200	E	1	4.6M	82	77
Kyrgyz	kir	Cyrl	NLLB-200	C	1	4.6M	98	94
Guarani	grn	Latn	NLLB-200	C	1	4.5M	90	84
Norwegian Nynorsk	nno	Latn	NLLB-200	C	1	4.3M	92	89
Bambara	bam	Latn	NLLB-200	E	1	4.2M	80	79
Ganda	lug	Latn	NLLB-200	C	1	4.1M	92	84
Northern Sotho	nso	Latn	NLLB-200	C	1	4.1M	88	85
Tok Pisin	tpi	Latn	NLLB-200	C	1	4.0M	90	84
Lombard	lmo	Latn	NLLB-200	C	1	3.9M	100	88
Acehnese	ace	Latn	NLLB-200	C	1	3.5M	100	92
Banjar	bjn	Latn	NLLB-200	C	1	3.5M	100	92
Waray	war	Latn	NLLB-200	C	1	3.1M	98	87
Ewe	ewe	Latn	NLLB-200	C	1	3.0M	90	79
Twi	twi	Latn	NLLB-200	C	1	3.0M	92	76
Swati	ssw	Latn	NLLB-200	C	1	2.0M	92	87
Esperanto	epo	Latn	NLLB-200	C	1	2.0M	100	94
Venetian	vec	Latn	NLLB-200	C	1	2.0M	100	92
Limburgish	lim	Latn	NLLB-200	C	1	1.6M	95	91
Sardinian	srd	Latn	NLLB-200	C	1	1.3M	100	88
Bashkir	bak	Cyrl	NLLB-200	C	1	1.2M	100	82
Standard Tibetan	bod	Tibt	NLLB-200	C	1	1.2M	95	75
Pangasinan	pag	Latn	NLLB-200	C	1	1.1M	88	86
Kabiye	kbp	Latn	NLLB-200	E	1	1.0M	78	64
Ayacucho Quechua	quy	Latn	NLLB-200	C	1	918k	90	79

Table E.4: Track B languages (low-resource tier), *continued*.

Language	ISO	Script	Translator	Tier	Class	Speakers	Fid.	Cov.
Welsh	cym	Latn	NLLB-200	C	1	724k	95	93
Crimean Tatar	crh	Cyrl	NLLB-200	C	1	553k	100	90
Occitan	oci	Latn	NLLB-200	C	1	542k	100	91
Ligurian	lij	Latn	NLLB-200	C	1	500k	100	87
Silesian	szl	Latn	NLLB-200	C	1	458k	98	91
Asturian	ast	Latn	NLLB-200	C	1	450k	98	84
Samoaan	smo	Latn	NLLB-200	C	1	416k	98	89
Luxembourgish	ltz	Latn	NLLB-200	C	1	391k	100	90
Fijian	fij	Latn	NLLB-200	C	1	341k	90	84
Friulian	fur	Latn	NLLB-200	C	1	300k	98	88
Dzongkha	dzo	Tibt	NLLB-200	C	1	237k	98	75
Maori	mri	Latn	NLLB-200	C	1	214k	100	90
Latgalian	ltg	Latn	NLLB-200	C	1	200k	95	87
Faroese	fao	Latn	NLLB-200	C	1	69k	98	91
Scottish Gaelic	gla	Latn	NLLB-200	C	1	60k	98	88
Central Aymara	ayr	Latn	NLLB-200	C	1	–	92	79
Eastern Yiddish	ydd	Hebr	NLLB-200	C	1	–	98	88
Southwestern Dinka	dik	Latn	NLLB-200	C	1	–	85	78
West Central Oromo	gaz	Latn	NLLB-200	E	1	–	75	79
Awadhi	awa	Deva	NLLB-200	C	0	22.0M	98	89
Magahi	mag	Deva	NLLB-200	C	0	20.7M	100	88
Central Atlas Tamazight	tzm	Latn	NLLB-200	C	0	17.0M	98	76
Sinhala	sin	Sinh	NLLB-200	C	0	15.3M	95	94
Nigerian Fulfulde	fuv	Latn	NLLB-200	C	0	14.5M	92	81
Rundi	run	Latn	NLLB-200	E	0	10.8M	80	86
Haitian Creole	hat	Latn	NLLB-200	C	0	9.6M	98	93
Central Kanuri	knc	Latn	NLLB-200	C	0	9.3M	92	76
Luba-Kasai	lua	Latn	NLLB-200	E	0	6.3M	65	82
Umbundu	umb	Latn	NLLB-200	E	0	6.0M	72	63
Balinese	ban	Latn	NLLB-200	C	0	4.0M	98	91
Kamba	kam	Latn	NLLB-200	E	0	3.9M	80	57
Bemba	bem	Latn	NLLB-200	C	0	3.6M	85	78
Shan	shn	Mymr	NLLB-200	C	0	3.0M	98	76
Dyula	dyu	Latn	NLLB-200	E	0	2.7M	82	68
Fon	fon	Latn	NLLB-200	C	0	1.9M	90	74
Jingpho	kac	Latn	NLLB-200	C	0	940k	98	71
Nuer	nus	Latn	NLLB-200	C	0	900k	88	79
Mizo	lus	Latn	NLLB-200	C	0	500k	98	78
Tamasheq	taq	Latn	NLLB-200	C	0	500k	98	71
Chhattisgarhi	hne	Deva	NLLB-200	C	–	16.3M	100	88
Mossi	mos	Latn	NLLB-200	C	–	7.6M	92	71
Luo	luo	Latn	NLLB-200	C	–	3.0M	92	84
Meitei	mni	Beng	NLLB-200	E	–	1.5M	78	69
Kabuverdianu	kea	Latn	NLLB-200	C	–	871k	95	87
Papiamentu	pap	Latn	NLLB-200	C	–	321k	100	92
Chokwe	cjk	Latn	Toucan	E	–	–	63	63
Kimbundu	kmb	Latn	NLLB-200	E	–	–	70	63

F Per-game language strength

Fig. F.1 decomposes each model’s language profile by game, reporting the mean language win-loss margin $\mu_{m,g}(A)$ for every model–game–language. $\Delta_{m,g}(A, B) = -\Delta_{m,g}(B, A)$, each row sums to zero by construction; cells therefore measure the *relative* strength of an interface within a model–game pair rather than absolute playing quality.

G Detailed Skill Analyses

In the following sections, we expand our findings on Sec. 5.2. Unless otherwise specified, Gemma, Qwen, and Ministral refer to their 4B-sized models.

G.1 Differences in Spatial Reasoning

Since text representations serialize content row by row, LLMs may track rows more easily than columns or diagonals. We therefore analyze losses in TicTacToe and SimpleTak, both of which present a 2D board in the observation o_t (see App. D.2 and App. D.5). Because losses often arise when a model fails to detect or respond to a positional threat, the rows, columns, or diagonals along which it loses provide a direct view of its spatial reasoning limitations.

TicTacToe When observing Gemma-4-E4B-it (Team et al., 2026) and Ministral3-3B (Liu et al., 2026) in TicTacToe, we find that non-English interfaces, and more so low-resource or non-Latin-script languages, show a skew towards column and diagonal losses compared to the English interface. We attribute this finding to the LLMs learning a better, more robust spatial understanding across the different spatial axes. Qwen3-4B (Qwen Team, 2025), however, shows a more stable defeat pattern across languages, with the exception of the Hebrew interface, suggesting a more balanced or generalized capability of spatial understanding.

For Gemma, English exhibits a relatively balanced distribution of losses across rows (28.5%), columns (34.8%), and diagonals (36.7%), implying a generalized spatial understanding capable of handling multi-dimensional threats. In contrast Arabic and Hebrew loss patterns skew away from rows, making them more susceptible to column and diagonal threats. Arabic’s loss pattern is rows (20.3%), columns (34.4%), diagonals (45.3%), and Hebrew follows similarly. This quantitative analysis, suggesting a spatial vulnerability, is strongly corroborated by our qualitative analysis, where Arabic and Hebrew game trajectories showed

Language	Row	Column	Diagonal
Gemma-4-E4B-it			
English	28.5%	34.8%	36.7%
Chinese	17.5%	28.0%	54.5%
Spanish	18.5%	34.4%	47.0%
French	22.6%	35.6%	41.7%
German	19.8%	37.5%	42.8%
Hebrew	21.1%	35.6%	43.3%
Arabic	20.3%	34.4%	45.3%
Malay	20.7%	29.0%	50.3%
Qwen3-4B			
English	45.3%	23.8%	30.9%
Chinese	44.0%	22.9%	33.1%
Spanish	49.8%	19.9%	30.3%
French	48.5%	22.6%	28.8%
German	48.0%	24.5%	27.4%
Hebrew	39.7%	31.3%	29.0%
Arabic	45.7%	23.8%	30.5%
Malay	46.8%	21.8%	31.3%
Ministral3-3B			
English	42.1%	35.3%	22.6%
Chinese	35.0%	33.4%	31.7%
Spanish	39.2%	31.7%	29.2%
French	37.9%	34.5%	27.6%
German	37.3%	33.9%	28.8%
Hebrew	33.4%	32.8%	33.9%
Arabic	35.0%	33.7%	31.4%
Malay	33.3%	33.8%	32.9%

Table G.1: Distribution of defeat types in TicTacToe by language and model. Each value is the percentage of defeats in which the opponent completed a row, column, or diagonal. These distributions indicate which spatial relationships each model fails to track under different language interfaces.

frequent “hallucination” or mislabeling of series of cells as columns or diagonals.

Language	Row	Column
English	53.2%	46.8%
Chinese	52.3%	47.7%
Spanish	51.5%	48.5%
French	46.0%	54.0%
German	39.7%	60.3%
Hebrew	42.8%	57.2%
Arabic	42.8%	57.2%
Malay	41.9%	58.1%

Table G.2: Distribution of loss types in SimpleTak by language for Gemma4-E4B-it: percentage of losses where the opponent completed a row or column.

Simple Tak Simple Tak’s winning lines can include both horizontal and vertical losses intertwined, which means analysis of its loss distribution should seemingly be more complex. However, in practice it seems




Figure F.1: Per-game language strength profiles for Gemma-4-E4B-it, Ministral-3-3B-Instruct, and Qwen3-4B. Each cell reports the mean language margin $\mu_{m,g}(A)$ for model m , game g , and language interface A , obtained by averaging the role-pooled pairwise margins of A against all other evaluated languages. Positive values indicate stronger average performance through language A , while negative values indicate weaker average performance.

Gemma-4-E4B-it favors straight lines (over 90% of wins), which permits associating horizontal and vertical lines with different aspects of spatial understanding as we did for TicTacToe. We present a detailed per-language breakdown of loss type distribution in Tab. G.2. Similarly to TicTacToe, some non-Latin and low-resource languages show a skew toward column losses compared to English. Specifically, while English loss distribution is rows 53.2% and columns 46.8%, Arabic and Hebrew show a skew towards columns with a loss distribution of rows 42.8% and columns 57.2%.

G.2 Differences in Strategy

Kuhn Poker Kuhn Poker is a three-card imperfect-information game in which each player receives J , Q , or K and chooses whether to bet, check, call, or fold; full rules are provided in App. D. Its actions are readily interpretable from the private card: betting with J is a bluff, betting with K seeks additional payoff from weaker hands, and folding K when facing a bet is a severe strategic error. Tab. G.3 shows that Gemma-4-E4B-it responds most consistently to these distinctions across languages, satisfying $P(\text{bet} | J) < P(\text{bet} | Q) < P(\text{bet} | K)$ throughout. It bets with K in at least 92.2% of eligible decisions, calls with K more than 90% of the time, and folds it in at most 2.0%, while bluffing with J in at most 2.4%. Gemma therefore

reliably distinguishes weak from strong private cards, although its near-zero bluffing rate reflects a conservative rather than necessarily optimal policy.

Gemma’s largest cross-language variation occurs for the intermediate card Q , whose betting rate ranges from 41.6% in Malay to 63.3% in Hebrew; its responses to clearly weak or strong cards are much more stable. English is also not uniformly strongest, yielding Gemma’s lowest overall betting rate, lowest Call_K rate, and highest BadFold_K rate. Qwen3-4B is more aggressive and more language-sensitive, with larger shifts in Bluff_J , ValueBet_K , and BadFold_K across languages. Ministral-3-3B-Instruct is less reliable overall, showing weaker separation between card strengths, higher invalid-action rates, and BadFold_K rates between 10.4% and 23.7%. Overall, Gemma is the most language-stable in strategically clear states, whereas Qwen and Ministral exhibit larger language-conditioned changes in both strategy and execution.

G.3 Differences in pre-existing knowledge

Nim Nim admits a complete algorithmic solution, related to a concept called “Nim-sum”. We therefore test whether models possess knowledge of this strategy and whether they can execute it through the different language interfaces. Tab. G.4 presents per-language game log mentions of the optimal strategy. We use named mentions as a proxy for optimal strategy knowl-

Lang.	Inv.	Bluff _J	Bet _Q	Value _K	Call _K	Fold _K
Gemma-4-E4B-it						
English	2.5%	1.3%	42.9%	92.2%	90.7%	2.0%
Chinese	2.4%	2.4%	57.0%	92.7%	93.7%	0.5%
Spanish	0.7%	0.9%	60.3%	98.2%	98.3%	0.1%
French	0.5%	1.3%	59.0%	98.3%	99.3%	0.3%
German	0.9%	1.9%	62.3%	96.8%	97.8%	0.4%
Hebrew	1.2%	2.4%	63.3%	96.0%	97.7%	0.0%
Arabic	2.0%	2.3%	54.1%	94.5%	96.5%	0.4%
Malay	1.1%	0.8%	41.6%	95.6%	97.8%	0.2%
Mean	1.4%	1.7%	55.1%	95.5%	96.5%	0.5%
SD	0.8%	0.7%	8.4%	2.3%	2.9%	0.6%
Qwen3-4B						
English	1.5%	23.3%	80.1%	94.7%	99.2%	0.2%
Chinese	1.8%	45.0%	81.2%	94.6%	98.6%	1.0%
Spanish	2.1%	22.5%	69.3%	86.0%	97.9%	1.9%
French	1.5%	26.2%	82.9%	95.2%	98.0%	2.0%
German	5.7%	33.7%	71.9%	86.4%	93.5%	3.5%
Hebrew	7.0%	44.4%	58.3%	75.3%	91.5%	6.1%
Arabic	3.5%	47.4%	68.2%	84.9%	94.5%	5.0%
Malay	0.8%	33.1%	61.4%	87.1%	94.3%	5.7%
Mean	3.0%	34.5%	71.7%	88.0%	95.9%	3.2%
SD	2.2%	10.1%	9.2%	6.7%	2.8%	2.2%
Ministral3-3B						
English	9.3%	47.7%	66.6%	85.6%	80.6%	16.3%
Chinese	8.8%	40.8%	59.3%	77.8%	75.7%	16.6%
Spanish	10.3%	48.2%	58.4%	77.3%	76.8%	11.7%
French	10.2%	36.8%	60.1%	82.4%	76.9%	10.4%
German	9.6%	52.6%	60.0%	76.1%	70.1%	18.9%
Hebrew	20.9%	41.4%	46.4%	55.1%	66.7%	23.7%
Arabic	13.7%	42.0%	49.6%	57.0%	71.8%	18.9%
Malay	15.6%	46.0%	52.8%	63.4%	76.9%	12.6%
Mean	12.3%	44.4%	56.7%	71.8%	74.4%	16.1%
SD	4.2%	5.1%	6.6%	11.7%	4.5%	4.4%

Table G.3: Card-conditioned behavior in KUHNPoker across languages and models. Inv. is the fraction of invalid actions. Bluff_J, Bet_Q, and Value_K denote the probabilities of betting with *J*, *Q*, and *K*, respectively, when [check] and [bet] are available. Call_K and Fold_K denote the probabilities of calling and folding with *K* when facing a bet. Higher Value_K and Call_K indicate more reliable play with the strongest card, whereas a high Fold_K indicates a severe strategic error. Mean and SD are computed across languages.

edge and find high variance across languages, with Qwen3-4B and Ministral3-3B showing rough alignment between optimal strategy mentions and win %, where high-mention languages perform better than low-mention languages.

We note that knowledge of the optimal strategy does not necessarily translate into the ability to execute it, as executing the nim-sum strategy requires mathematical skill that may be disjoint from its knowledge. We therefore look for first-player first moves- which given our board definition, allow only one optimal move. We find that while Gemma-4-E4B-it is consistently able to execute the optimal move, Qwen3-4B and Ministral3-3B show a more complex pattern. We find dramatic differences between strategy mentions and successful ex-

Language	Win %	Opt. Strategy Mentions	Opt. Move
Gemma-4-E4B-it			
English	50.2%	43,927	99.9%
Chinese	50.1%	32,207	99.8%
Spanish	50.3%	85,103	99.7%
French	50.1%	71,607	99.2%
German	50.3%	54,801	99.9%
Hebrew	49.8%	94,951	99.3%
Arabic	49.3%	139,797	99.4%
Malay	50.0%	53,813	99.5%
Qwen3-4B			
English	61.0%	150,005	80.8%
Chinese	69.8%	85,605	74.3%
Spanish	48.4%	103,517	38.5%
French	58.3%	159,675	24.6%
German	43.6%	100,722	34.1%
Hebrew	42.7%	20,002	4.0%
Arabic	32.4%	24,814	10.5%
Malay	43.8%	70,660	26.7%
Ministral3-3B			
English	57.3%	538,093	34.6%
Chinese	58.1%	537,476	20.8%
Spanish	52.7%	629,253	22.5%
French	52.1%	812,283	31.3%
German	48.2%	400,286	19.7%
Hebrew	48.9%	2,753	10.8%
Arabic	46.2%	14,610	8.0%
Malay	36.6%	236,289	15.6%

Table G.4: Cross-lingual NIM performance across three models. We report the overall win rate, the number of optimal strategy mentions, and the % of successful first move optimal plays (Opt. Move). Qwen3-4B and Ministral3-3B show rough alignment between mention count and win%, while interestingly mention count and execution % aren’t necessarily aligned.

ecution; while English and French logs contain a similar number of strategy mentions for Qwen3-4B, English executes the optimal first move 80.8% of the time while French does so only 24.6% of the time; similar patterns can be found across languages for both models. This result hints at substantial and differing knowledge and mathematical reasoning gaps between languages.

Analyzing languages with a low number of strategy mentions reveals an interesting effect. For Ministral3-3B, 70% of Arabic player optimal strategy mentions and 50% of Hebrew player optimal strategy mentions originated from game logs where the model naturally language-switched into a Latin script. While this language switching isn’t very common (3.7% of Arabic logs and 1% of Hebrew logs), it is responsible for many of the optimal strategy mentions of these language interfaces, implying that the differences in knowledge may even be larger than what we present. Moreover, these results showcase that even under the exact same game interface, simply switching the processing lan-

guage can retrieve crucial knowledge that otherwise would have been lost, and directly tie into the recovery strategy from Sec. 5.3.