

Improving the Sensitivity of Gravitational Wave Detection with Weighted Conformal Prediction

Ann-Kristin Malz

ANN-KRISTIN.MALZ@LIGO.ORG

Department of Physics, Royal Holloway, University of London

Gregory Ashton

GREGORY.ASHTON@LIGO.ORG

School of Mathematical Sciences, University of Southampton

Nicolo Colombo

NICOLO.COLOMBO@RHUL.AC.UK

Department of Computer Science, Royal Holloway University of London

Editor: Ernst Ahlberg, Ulf Johansson, Henrik Boström, Alberto Carlevaro, Johan Hallberg Szabadváry and Lars Carlsson

Abstract

In the last decade, kilometre-scale interferometric gravitational-wave detectors have observed hundreds of compact binary mergers, the majority of which are binary black holes. However, the data are noise-dominated, and multiple independent search algorithms (pipelines) are used to enhance sensitivity and improve robustness. Rather than the standard approach of selecting the most significant pipeline output, we combine the outputs from all pipelines using a conformal prediction-based framework to provide statistically rigorous confidence estimates for candidate events. While combining pipelines improves sensitivity and ranking robustness, it requires a principled statistical framework that remains valid as data properties evolve across observing runs. A key challenge is distribution shifts between simulated datasets used for training and calibration and the real, unlabelled, observations used for testing, which can invalidate coverage guarantees and bias confidence estimates. In this work, we address this challenge by incorporating likelihood-ratio reweighting into our conformal prediction framework to account for covariate shift. Using mock datasets containing simulated signals, we demonstrate that weighted conformal prediction restores well-calibrated coverage under covariate shift and increases the confidence of events near the detection threshold, recovering true signals that would otherwise be missed.

Keywords: Conformal Prediction, Gravitational Waves, Search Pipeline Combination, Uncertainty Quantification, Covariate Distribution Shift.

1. Introduction

Gravitational waves (GWs) are ripples in spacetime generated by accelerating massive objects, such as merging black holes or neutron stars. Their detection enables the study of astrophysical systems that are otherwise difficult or impossible to observe, offering a unique window into some of the most energetic events in the Universe and allowing us to test physical theories under extreme conditions. In practice, these signals are extremely weak and are embedded in noisy time-series data collected by ground-based interferometric detectors (Weiss, 1972).

The field of GW astronomy has grown rapidly since the first detection in 2015 (Abbott et al., 2016), and with the latest catalogue release, GWTC-5.0 (Abac et al., 2026a), the cumulative catalogue of events now contains almost 400 signals from compact binary

coalescence sources observed by the LIGO-Virgo-KAGRA (LVK) detector network (Aasi et al., 2015; Acernese et al., 2015; Akutsu et al., 2021). The majority of these detections correspond to binary black hole mergers, with a small number originating from neutron star black hole and binary neutron star systems.

GWs are detected by the LVK detectors, which are kilometre-scale laser interferometers that measure differential arm length variations induced by passing gravitational waves. For a review of GW data analysis, see Abbott et al. (2020). The data are continuously analysed using dedicated search algorithms (pipelines) that scan for candidate events. Some pipelines are based on matched filtering, searching for known signal morphologies by correlating the data against precomputed waveform templates, while others use unmodelled or coherence-based approaches that make no assumptions about the signal shape (Abac et al., 2026b). In either case, the common goal is to distinguish astrophysical signals from instrumental and environmental noise. The pipeline outputs consist of both significance statistics and (for the template-based searches) source-related quantities such as the masses of the merging compact objects.

To quantify significance, the pipelines assign each candidate a false alarm rate (FAR): a right-sided p-value normalised by time, measuring how often noise alone would produce an equally significant event by chance. Practically, this computation involves defining a test statistic ρ , empirically estimating the distribution of ρ under the null hypothesis (see Abac et al., 2026c,b), and then, for a candidate event with a measured test statistic of ρ^* , the FAR is

$$\text{FAR}(\rho^*) = \frac{\sum_{i=1}^n \mathbf{1}(\rho_i \geq \rho^*)}{T_{\text{obs}}}, \quad (1)$$

where the numerator represents the number of background events with detection statistic ρ_i exceeding ρ^* , and T_{obs} is the total effective background observation time (Capano et al., 2016).

The background is typically estimated by time-shifting data streams between detectors, ensuring any surviving coincidences are of terrestrial origin (Abac et al., 2026b). The exact form of the detection statistic varies between pipelines, with some using the matched-filter signal-to-noise ratio (SNR) and others a more general ranking statistic (Abac et al., 2026b). Candidates with a FAR below a given threshold, usually 1 per year, are classified as significant astrophysical signals (Abac et al., 2026b).

Within the LVK collaboration, there are multiple different search pipelines currently being routinely used. In this work we will consider four of them, due to data availability in the datasets we consider: **GstLAL** (Messick et al., 2017; Sachdev et al., 2019; Tsukada et al., 2023; Sakon et al., 2024; Joshi et al., 2025; Cannon et al., 2020; Hanna et al., 2020), **MBTA** (All  n   et al., 2025; Aubin et al., 2021; Adams et al., 2016), **PyCBC** (Allen et al., 2012; Dal Canton et al., 2014; Usman et al., 2016; Nitz et al., 2017; Allen, 2005; Davies et al., 2020), and **CWB** (Mishra et al., 2025; Klimentenko et al., 2005, 2008, 2016; Klimentenko and Mitselmakher, 2004; Klimentenko et al., 2011). The former three rely on matched filtering, while the latter performs an unmodelled, coherence-based search. Additional details are described in Abac et al. (2026b).

The use of multiple pipelines introduces challenges when their assessments of a given candidate are inconsistent, for example, due to differences in methodologies and configuration choices or variations in sensitivity across the parameter space. It is therefore essential

to combine the outputs of these pipelines into a single robust significance measure for each candidate.

In current LVK analyses, this is typically achieved by comparing the FAR across pipelines, and considering candidates as significant astrophysical signals if at least one pipeline reports a FAR below 1 per year (Abac et al., 2026a).

Since the FAR is a right-sided p-value normalised by time, combining FARs from multiple pipelines is analogous to the classical statistical problem of combining p-values. Therefore, possible alternative combination approaches include Fisher’s method (Fischer, 1925) or the harmonic mean; however, the computed FARs are not independent (since they analyse the same data), and no joint background exists across all pipelines to calibrate the harmonic mean. GW astronomers therefore adopt a simple, pragmatic approach and use the minimum FAR across all pipelines. This is easy to implement and conservative in that it makes the strongest claim supportable by any single pipeline, without inflating significance through combination.

This strategy is simple and computationally efficient. However, discrepancies between pipeline outputs can be informative, as they capture complementary aspects of candidate events and can be exploited to extract additional information. There are now several alternative approaches to combine pipelines, capturing correlations, see, for example Banagiri et al. (2023), Tsukamoto et al. (2026), and Ashton et al. (2026).

Of these, we focus on Ashton et al. (2026), where we introduced a framework that uses a simple machine learning (ML) model to learn correlations and combine outputs from multiple pipelines. Since ML classifiers alone do not provide calibrated uncertainty estimates, we augment the framework with conformal prediction (CP), which provides statistically rigorous, distribution-free prediction sets with guaranteed coverage (Vovk et al., 2005; Angelopoulos and Bates, 2021). To provide astronomers with a single interpretable significance measure, we use the *conditional confidence* defined in Ashton et al. (2024), an extension of the CP confidence (Shafer and Vovk, 2008) that can always be efficiently computed in practice. The conditional confidence quantifies how signal-like a candidate appears, and can be interpreted as the largest error rate for which the signal label remains admissible. The resulting conditional confidence measures are essential for trustworthy astrophysical interpretation, as a lack of quantified uncertainties can lead to unreliable scientific conclusions. Figure 1 illustrates the workflow, from astrophysical event to the conditional confidence output by our pipeline combination framework.

A central requirement for deploying such a method in practice is that it can be trained and calibrated on simulated mock data and then applied to real detector data, where the labels are unknown. However, existing mock data do not fully reproduce the complexity of real observations as they are constructed to stress-test the detection infrastructure rather than to reproduce accurate astrophysical distributions. For example, detector noise characteristics, pipeline behaviour, and astrophysical signal properties all differ from reality. In particular, signal rates and source-class fractions are not representative of what has actually been observed, injected mass and spin distributions are deliberately broader and more generic than inferred astrophysical populations, and a minimum-SNR cutoff on injections excludes low-SNR events that would still be present in the true signal distribution even if not currently detectable (Chaudhary et al., 2024, 2026). Such mismatches can lead to




Figure 1: Illustration of the workflow from astrophysical event to our search pipeline combination framework. Two merging compact objects, such as black holes, generate gravitational waves, which are detected by the LIGO-Virgo-KAGRA interferometers. The data is then analysed by several search pipelines, which output data products such as the FAR and SNR. This serves as input to our framework, applying an ML classifier and CP to combine pipeline outputs into a single conditional confidence value for each GW candidate. The figure was created using Gemini 3.

distribution shifts between calibration and testing datasets that invalidate the coverage guarantees of standard CP.

We model this discrepancy between datasets as a distributional shift in the pipeline outputs. A full characterisation would require estimating how the feature distributions shift for each class separately, which is not tractable without labels from the test dataset. We therefore consider several approximations to the class-conditional ratio, ranging from the marginal feature ratio estimated from unlabelled test data to heuristic approaches based on pseudo-labelled test samples, as described in Section 2. The marginal approximation is motivated by the observation that distributional shifts in pipeline outputs are expected to affect signal and noise events similarly, implying that the class-conditional and marginal ratios are approximately equal.

To correct for this shift, we apply the weighted CP method of Tibshirani et al. (2019), which reweights calibration points by the estimated likelihood ratio of the test to calibration feature distributions, restoring the coverage guarantee of standard CP without requiring retraining of the underlying classifier.

We first induce controlled covariate shifts of varying intensity in our mock data to systematically investigate how distributional differences affect coverage and conditional confidence estimates, and how weighted CP can mitigate their impact. We then apply the same framework to investigate the naturally occurring shift between two different mock datasets, using the controlled results as a reference to interpret and contextualise the observed behaviour in our astrophysical setting.

In this work, we apply the likelihood reweighting method of Tibshirani et al. (2019) to GW search pipeline combination using Mondrian (label-conditional) binary classification. Applying weighted CP to Mondrian classification is not novel in itself, e.g. Laghuvarapu et al. (2026) take a similar approach under covariate shift. However, we are not aware of any existing work explicitly addressing label-conditional covariate shift. Since exact correction is intractable without test labels, our methodological contribution is to introduce and empirically compare several practical approximations, ranging from marginal to pseudo-label-based approaches, as described in Section 2. The primary novelty of this work, however, lies

in the application to GW astronomy, where we demonstrate that weighted CP can correct for naturally occurring distribution shifts between datasets, with direct implications for the reliability of astrophysical conclusions.

2. Method

In this section, we describe the details of our GW pipeline combination framework, following the same approach as in [Ashton et al. \(2026\)](#). We take as input the open pipeline outputs produced by the LVK collaboration, combine them using a ML classifier, and subsequently apply CP to quantify the uncertainty and produce well-calibrated conditional confidence scores for each candidate. We then describe the extension to weighted CP ([Tibshirani et al., 2019](#)) to correct for distribution shift between the calibration and test distributions.

To train the classifier and calibrate CP, we use labelled (signal or noise) mock datasets constructed from simulated signals injected into detector noise and processed by each of the search pipelines. In this work, we consider two such datasets: the pre-fourth-observing-run mock data challenge (MDC) ([Chaudhary et al., 2024](#)) and the low-latency production integration challenge (LLPIC) dataset ([Chaudhary et al., 2026](#)), produced during the fourth observing run. The LVK detectors operate in coordinated observing runs, separated by commissioning periods during which both the detectors and analysis software (including the search pipelines) are upgraded, resulting in evolving data properties between runs. The MDC and LLPIC datasets are based on replayed data from the third and fourth observing runs, respectively, and therefore reflect differences in detector configuration and pipeline implementations between runs. The MDC dataset spans 40 days of data and contains 9948 candidates, of which 5910 are signals. In contrast, the LLPIC dataset we use covers 7 days and contains 1204 candidates, including 534 signals. We split the MDC data into training (80%), calibration (10%), and testing (10%) subsets, while reserving the entire LLPIC dataset for testing only.

We restrict our inputs to the reported FAR and SNR from each of the four pipelines. We use the logarithm of the inverse false alarm rate (IFAR; $\text{IFAR}=1/\text{FAR}$) in place of the FAR, as differences in statistical significance are meaningful on logarithmic scales. This choice also ensures that missing pipeline outputs, which we replace with zero, remain well defined.

In this work, we use a logistic regression (LR) classifier due to its simplicity and interpretability, see [Malz et al. \(2026\)](#) for discussion on different classifiers. The ML model is trained on sample-label pairs, $(\mathbf{X}, y)$, where $\mathbf{X}$ denotes the feature vector composed of the output from the pipelines and $y \in \{0, 1\}$ the corresponding label (0 for noise, 1 for signal). LR models the probability of a candidate being a signal as a sigmoid function of a linear combination of the input features, optimised via the binary cross-entropy loss. We then use the output probability of the trained classifier to define the nonconformity measure for CP.

2.1. Conformal prediction

We employ Mondrian (label-conditional) CP ([Vovk, 2013](#); [Ding et al., 2023](#)) to guarantee conditional coverage for each label, which is essential for our GW analysis to ensure reliable uncertainty quantification for both signal and noise events. Applying CP for binary

classification, we use the classifier output probability $p_y(\mathbf{X})$ for each label y and define the nonconformity score

$$s^y(\mathbf{X}) = 1 - p_y(\mathbf{X}). \quad (2)$$

We compute the calibration scores, $s^y(\mathbf{X}_i)$, $y = 0, 1$, for each calibration sample $\mathbf{X}_i$, group them by class label y , and within each class, sort them in increasing order. The corrected $(1 - \alpha)$ -th empirical quantile is then estimated as

$$\hat{q}_\alpha^y = s_{[(N_y+1)(1-\alpha)]}^y, \quad N_y = \sum_{i=1}^N \mathbf{1}(Y_i = y), \quad (3)$$

where $\alpha \in [0, 1]$ is the user-chosen error rate, and N_y is the number of calibration samples with label y , which, in general, may be different from $\frac{N}{2}$. For a new test sample $\mathbf{X}'$, we compute the nonconformity scores $s^y(\mathbf{X}')$ for all $y = 0, 1$, and let the prediction set be

$$\Gamma^\alpha(\mathbf{X}') = \{y \in \{0, 1\} : s^y(\mathbf{X}') \leq \hat{q}_\alpha^y\}. \quad (4)$$

CP guarantees finite-sample validity, ensuring that the true test label Y' satisfies

$$1 - \alpha \leq \Pr(Y' \in \Gamma^\alpha(\mathbf{X}') | Y' = y) \leq 1 - \alpha + \frac{1}{N_y + 1}. \quad (5)$$

For Mondrian CP, these guarantees hold conditionally within each class, in addition to marginal validity over the full dataset.

To determine the significance of each GW candidate, we use the conditional confidence of the signal class. Following [Ashton et al. \(2024\)](#), this quantity is defined as the value of α where the signal label becomes included in the prediction set Γ^α . Formally,

$$\text{conf}_{Y=1}(\mathbf{X}) = \max\{\alpha \in [0, 1] : 1 \in \Gamma^\alpha(\mathbf{X})\} = \max\{\alpha \in [0, 1] : 1 - p_1(\mathbf{X}) \leq q_\alpha^1\}. \quad (6)$$

Defining a threshold on $\text{conf}_{Y=1}$ (e.g. at 0.5) yields a catalogue with controlled purity.

2.2. Conformal prediction under distribution shift

Standard CP relies on the assumption of exchangeability between calibration and test data, which is violated when they come from different distributions, $P_{XY}^{\text{cal}} \neq P_{XY}^{\text{test}}$. A special case of distribution shift is covariate shift, where the marginal distribution of features differs between calibration and test data but the conditional distribution of the labels given the features remains unchanged, that is, $P_{XY}^{\text{cal}} = P_X^{\text{cal}} P_{Y|X}^{\text{cal}} \neq P_X^{\text{test}} P_{Y|X}^{\text{cal}} = P_{XY}^{\text{test}}$. [Tibshirani et al. \(2019\)](#) proposed to correct such a covariate shift by reweighting each calibration point with the likelihood ratio between test and calibration distributions.

The scheme does not apply straightforwardly to our setup, which requires conditioning on the labels. The distribution shift we need to address is

$$P_{X|Y=y}^{\text{test}} \neq P_{X|Y=y}^{\text{cal}}, \quad y = 0, 1. \quad (7)$$

As $P_{X|Y} = P_{Y|X} \frac{P_X}{P_Y}$, such a *conditional covariate shift* is implied by any non-trivial covariate shift ($P_{Y|X}$ invariant, P_X shifting).

Let the conditional calibration and test distributions be $P_{X|Y}$ and $\tilde{P}_{X|Y}$. For each $y = 0, 1$, the *conditional likelihood ratio* is then

$$w_y(\mathbf{X}) = \frac{d\tilde{P}_{X|Y=y}(\mathbf{X})}{dP_{X|Y=y}(\mathbf{X})}. \quad (8)$$

The idea is to weight up the calibration points whose covariates resemble the test points and down-weight those that do not. Similar to Tibshirani et al. (2019), reweighting the calibration samples fully restores validity when the likelihood ratios are known. On the one hand, this is remarkable: general distribution shifts could be resolved by combining sample reweighting and Mondrian (label-conditional) CP. As expected, however, this is impossible in any real-world scenarios where conditional likelihood ratios $w_y(\mathbf{X})$ are unknown and must be estimated (often by training a classifier that discriminates between calibration and test samples). Unlike the marginal likelihood ratios of Tibshirani et al. (2019), which can be learned consistently from unlabelled covariate data, defining an unbiased estimator of the conditional likelihood ratios is more challenging, because it would require knowing the test labels.

In non-conditional likelihood ratio estimation, we assign calibration and test points a set-class label, $C = 0, 1$, and train a probabilistic classifier, $\hat{p}_C(\mathbf{X})$, (we use a simple random forest as in Tibshirani et al. (2019)) on the combined set.

For conditional ratios, the procedure should be performed separately on the calibration and test samples with labels $y = 0$ and $y = 1$. Let $\hat{p}_{y,C}(\mathbf{X})$, $y = 0, 1$, be the binary classifiers trained for $y = 0$ and $y = 1$. The corresponding estimated likelihood ratio is

$$\hat{w}_y(\mathbf{X}) = \frac{\hat{p}_{y,C=1}(\mathbf{X})}{1 - \hat{p}_{y,C=1}(\mathbf{X})}, \quad (9)$$

where $\hat{p}_{y,C=1}(\mathbf{X}) = \hat{p}(C = 1 \mid \mathbf{X}, Y = y)$ is the estimated probability of a point belonging to the distribution of the test points with label y . Without knowing the test labels, selecting the test data needed to train the label-conditional weight estimator is not possible. We therefore approximate the conditional likelihood ratio $w_y(\mathbf{X}) \approx \tilde{w}_y(\mathbf{X})$ using one of the following strategies:

- **Marginal:** estimate $\tilde{w}_y(\mathbf{X}) = \frac{d\tilde{P}_X(\mathbf{X})}{dP_X(\mathbf{X})}$ using *all* test samples and *all* calibration samples.
- **Semi-conditional:** estimate $\tilde{w}_y(\mathbf{X}) = \frac{d\tilde{P}_X(\mathbf{X})}{dP_{X|Y=y}(\mathbf{X})}$ using *all* test samples and only the calibration samples *with label y*.

We also consider two heuristic approaches based on pseudo-labelling the test samples:

- **Classifier conditional:** estimate $\tilde{w}_y(\mathbf{X}) = \frac{d\tilde{P}_{X|\hat{Y}=y}(\mathbf{X})}{dP_{X|\hat{Y}=y}(\mathbf{X})}$, where $\hat{Y} = \mathbf{1}(p_1(\mathbf{X}) \geq \frac{1}{2})$ is the label predicted by the signal classifier.
- **maximum-log₁₀IFAR conditional:** estimate $\tilde{w}_y(\mathbf{X}) = \frac{d\tilde{P}_{X|\tilde{Y}=y}(\mathbf{X})}{dP_{X|\tilde{Y}=y}(\mathbf{X})}$, where $\tilde{Y} = \mathbf{1}(\max \log_{10} \text{IFAR} \gtrsim 7.5)$ is a proxy label based on the conventional FAR threshold of 1 per year.

Given one of these approximations, we denote the resulting estimated likelihood ratio as $\hat{w}(\mathbf{X})$ and proceed as in Tibshirani et al. (2019), applying $\hat{w}$ to both calibration and test data to obtain weights $w_{\text{cal}}(\mathbf{X}_i) = \hat{w}(\mathbf{X}_i)$ and $w_{\text{test}}(\mathbf{X}') = \hat{w}(\mathbf{X}')$, respectively.

The standard empirical quantile in Eq. (3) is replaced by a weighted quantile. For a test point $\mathbf{X}'$, the normalised weights of the calibration points with label y , are

$$p_i^{w,y}(\mathbf{X}') = \frac{w_{\text{cal}}(\mathbf{X}_i)}{\sum_{j=1}^{N_y} w_{\text{cal}}(\mathbf{X}_j) + w_{\text{test}}(\mathbf{X}')}, \quad i = 1, \dots, N_y, \quad (10)$$

and the weight for the test point is

$$p_{\text{test}}^{w,y}(\mathbf{X}') = \frac{w_{\text{test}}(\mathbf{X}')}{\sum_{j=1}^{N_y} w_{\text{cal}}(\mathbf{X}_j) + w_{\text{test}}(\mathbf{X}')}, \quad (11)$$

where $i = 1, \dots, N_y$ indexes calibration points with label y . The per-label weighted quantile threshold is then

$$\hat{q}_\alpha^{w,y}(\mathbf{X}') = \text{Quantile} \left(1 - \alpha; \sum_{i=1}^{N_y} p_i^{w,y}(\mathbf{X}') \delta_{s_i^y} + p_{\text{test}}^{w,y}(\mathbf{X}') \delta_\infty \right), \quad (12)$$

where δ_a denotes a point mass at a (the distribution assigning all of its probability to the value a), following Tibshirani et al. (2019), and the argument is a weighted discrete probability distribution over the nonconformity scores, where each score s_i^y gets weight $p_i^{w,y}$ and ∞ gets weight $p_{\text{test}}^{w,y}$ (the ∞ atom is a standard conformal trick to account for the test point having an unknown score). The weighted prediction set is then defined as

$$\Gamma_w^\alpha(\mathbf{X}') = \{y \in \{0, 1\} : s^y(\mathbf{X}') \leq \hat{q}_\alpha^{w,y}(\mathbf{X}')\}. \quad (13)$$

Thus, the weighted quantile, $\hat{q}_\alpha^{w,y}(\mathbf{X}')$, depends on the test point, $\mathbf{X}'$, through the sample weights, and must be recomputed for each new test sample.

Similar to Tibshirani et al. (2019), if oracle conditional ratios, $\bar{w}_y(\mathbf{X})$, $y = 0, 1$, were known (or consistently estimated), nominal coverage guarantees would hold as in Eq. (5). That is,

$$\Pr(Y' \in \Gamma_{\bar{w}_y}^\alpha(\mathbf{X}') \mid Y' = y) \geq 1 - \alpha. \quad (14)$$

Even in this ideal case, the finite-sample bound is less tight than in Eq. (5) because the effective number of calibration samples contributing to the quantile estimate is reduced. Following Tibshirani et al. (2019), we compute the effective sample size (Kish, 1965) for weighted CP as

$$\hat{n}_y = \frac{\left(\sum_{i=1}^{N_y} w_{\text{cal}}(\mathbf{X}_i) \right)^2}{\sum_{i=1}^{N_y} w_{\text{cal}}(\mathbf{X}_i)^2}. \quad (15)$$

Intuitively, $\hat{n}_y$ measures how many equally-weighted calibration points would yield equivalent precision in the quantile estimate. A highly concentrated test distribution (relative to the calibration distribution) will therefore result in a small $\hat{n}_y$, increasing the variance of the coverage.

Unlike the marginal covariate shift setting of [Tibshirani et al. \(2019\)](#), however, the conditional ratios $w_y(\mathbf{X}) = d\tilde{P}_{X|Y=y}/dP_{X|Y=y}$ cannot be consistently estimated without knowing the test labels, which would make the problem trivial. The approximations introduced above inevitably induce a bias in the weight estimates that cannot be bounded without further assumptions, and whose impact on coverage depends on the data. Our contribution is therefore to reduce the general problem of CP under unconstrained distribution shift in classification to a practical one: training a weight estimator classifier under approximate or partly unknown labels, and investigating empirically how well coverage is preserved. Providing theoretical guarantees under reasonable assumptions on the data distribution, for example, by bounding the divergence between $P_{X|Y=0}$ and $P_{X|Y=1}$, remains an important direction which we leave for future work.

3. Experiments

To investigate the impact of covariate shift and the effectiveness of weighted CP on our GW data, we run two experiments: first, we construct controlled distributional shifts in the MDC test data and, second, we explore the existing shift between the MDC and LLPIC datasets.

3.1. Controlled covariate shift

We split the MDC dataset into training, calibration, and test sets as described in [Section 2](#), and induce covariate shift by resampling the test set according to feature-dependent weights, preserving $P_{Y|X}$ while altering the marginal distribution P_X .

Simulating a scenario in which one of the pipelines exhibits distributional changes between mock and real data, we apply reweighting to the IFAR and SNR features of the selected pipeline, while leaving the features from other pipelines unchanged.

Since the IFAR and SNR are strongly correlated, we only consider the case where both features have the same weighting. Covariate shift is introduced by upweighting samples whose feature values lie within a specified percentile range, thereby biasing the resampled test distribution toward higher or lower regions of the feature space. The magnitude of this perturbation is governed by a multiplicative scaling parameter on the weights, which we refer to as the shift intensity.

We further restrict this setup by considering two types of shifts: one targeting lower feature values (resampling within the 10th–30th percentiles) and one targeting higher feature values (70th–90th percentiles). For each case, we vary the shift intensity over the values 2, 5, and 10, where a value of 1 corresponds to no shift, as it leaves the sampling distribution unchanged.

To illustrate the distribution shift, we plot the histogram of the nonconformity scores in [Figure 2](#), for two of the defined test cases together with those for the calibration data and the unshifted test data. As expected, the nonconformity scores of the calibration and unshifted test data agree well. The test set shifted to lower feature values results in higher nonconformity scores compared to the calibration and unshifted test, while the opposite holds for the test data shifted to higher feature values.

We quantify the induced covariate distribution shifts using the earth mover’s distance (EMD), which measures the distance between two distributions as the minimal cost of




Figure 2: Histogram showing the values of the nonconformity scores of the signal class for the calibration data, unshifted test data and two sets of shifted test data with shift intensity 5, resampled to higher and lower feature values, respectively.

transporting probability mass from one to the other (Rubner et al., 1998). Formally, the EMD between the calibration distribution P_X and the test distribution $\tilde{P}_X$ is defined as the first Wasserstein distance,

$$\text{EMD}(P_X, \tilde{P}_X) = \inf_{\pi \in \Gamma(P_X, \tilde{P}_X)} \int_{\mathbb{R} \times \mathbb{R}} |z - z'| d\pi(z, z'), \quad (16)$$

where $\Gamma(P_X, \tilde{P}_X)$ is the set of joint distributions on $\mathbb{R} \times \mathbb{R}$ with marginals P_X and $\tilde{P}_X$, and where z and z' are scalar feature values drawn from P_X and $\tilde{P}_X$ respectively (Ramdas et al., 2017). In practice, we compute this using the `scipy.stats.wasserstein_distance` (Virtanen et al., 2020) implementation, applied feature-wise and averaged across all input features.

Larger EMD values thus correspond to stronger shifts. The resulting average EMD values for each shift setting are reported in Table 1. The values demonstrate how a stronger shift intensity results in a higher EMD, and how resampling the test data in the region of higher feature values gives a slightly greater shift compared to resampling in lower feature values with the same shift intensity. The asymmetry between the lower and higher shift cases at the same intensity reflects the shape of the underlying feature distribution: shifting toward higher feature values moves the test distribution further into the tail, where the calibration density is low, resulting in a greater distributional distance.

Next, we compare the likelihood ratio approximations introduced in Section 2 empirically, applying each method to two of the defined test shifts and presenting the resulting coverage in Figure 3. We observe that only the marginal likelihood ratio, where the weight estimator is trained on all test and all calibration samples, successfully recovers

Table 1: EMD values, averaged over all features, quantifying the strength of the distribution shifts between the shifted test datasets compared to the calibration dataset. For each shift intensity, we resample in lower and higher regions of feature space, respectively, obtaining six shifted test sets. For comparison, the EMD value between the unshifted test and the calibration distributions is 0.040.

Shift intensity	lower	higher
2	0.22	0.17
5	0.36	0.43
10	0.40	0.55

well-calibrated coverage in both test cases. Interestingly, when we induce overcoverage by shifting the features to higher values in Figure 3(b), the approximate conditional likelihood ratio using the classifier prediction as the label of test data, also obtains valid coverage. However, methods that rely on a proxy for the true label, whether the classifier prediction or an alternative such as the maximum- $\log_{10}$ IFAR, introduce an additional source of error: any misclassification or inaccuracy in the proxy propagates into the weight estimates, and coverage guarantees are only recovered to the extent that the proxy is reliable. Since proxy quality cannot be guaranteed in general (as illustrated by Figure 3), and may degrade precisely in the regime where the distribution shift is most severe, and correction is most needed, we adopt the marginal likelihood ratio as the most robust and assumption-free choice. In the remainder of this work, we will apply the marginal weights only and refer to this as the *weighted CP* method.




Figure 3: Empirical coverage comparing different CP weighting methods, as obtained on the shifted test data for shift intensity 5, resampling features to lower (left) and higher (right) values, respectively. The shaded areas represent the 99% binomial confidence bands corresponding to the minimum per-label effective calibration size $\min_y \hat{n}_y$ for each weighting method, with wider bands corresponding to smaller effective sample sizes.

Having defined and validated the experimental setup, we apply our framework to each of the shifted datasets, using both standard, unweighted, CP and weighted CP. For each method, we compute the empirical coverage, and report the results in Figure 4.




Figure 4: Empirical coverage comparing standard Mondrian CP (left) and marginal weighted Mondrian CP (right), as obtained on the shifted test data for varying shift intensity. The shaded grey areas represent the 99% binomial confidence bands corresponding to the minimum per-label effective calibration size $\min_y \hat{n}_y$ for each shift intensity, with wider bands corresponding to larger shift intensities. For standard CP $\hat{n}_y$ reduces to N_y .

Figure 4(a) shows the effect of the covariate shift on the coverage when using standard CP. As expected, increasing the shift intensity moves the coverage curve further away from the diagonal. Shifting the test distribution toward lower feature values results in under-coverage, while shifting toward higher values leads to overcoverage. In our data, higher IFAR and SNR values indicate that an event is more likely to be a signal. Resampling the test distribution in the region of higher feature values increases the proportion of signal-like events, shifting the empirical distribution of test nonconformity scores downward, relative to the calibration set. Since the calibration quantile was computed from a different region of feature space, it becomes too permissive for the test set, resulting in overall larger average prediction sets and systematic overcoverage. Conversely, resampling toward lower feature values enriches the test set with noise-like events whose nonconformity scores are systematically higher, yielding overall smaller prediction sets and undercoverage.

Mondrian CP enforces coverage validity separately within each class under the assumption of exchangeability. However, this guarantee does not extend to covariate shift that alters the marginal feature distribution P_X , and consequently $P_{X|Y}$, within each class, since the per-class calibration quantiles are still computed under the assumption that calibration and test features are exchangeable within each class. We note that when using non-Mondrian CP, the under- and over-coverage obtained is more severe.

Figure 4(b) shows the empirical coverage obtained using weighted CP. For all shift intensities, the coverage is approximately diagonal within the expected binomial noise, indicating that the weighted CP returns well-calibrated prediction sets.

To quantify the expected deviation from the diagonal in Figure 4 due to finite sample size, we plot 99% binomial confidence bands corresponding to the minimum per-label

calibration size $\min_y N_y$ in Figure 4(a). For the weighted CP in Figure 4(b), the limiting uncertainty is the per-label effective calibration size $\hat{n}_y$, which decreases as the shift intensity increases and fewer calibration points contribute meaningfully to the quantile estimate. Thus, the expected deviation from the diagonal increases with shift intensity. Due to the symmetric nature of our set-up, $\hat{n}_y$ varies little between the lower and higher shift cases at the same shift intensity, and thus we only show one band per intensity level.

We observe that while all shifted coverage curves are outside the shaded band in Figure 4(a), the curves are well within the expected deviation from the diagonal when using the weighted CP in Figure 4(b), confirming that likelihood reweighting can successfully mitigate the covariate shift.

Having shown that the weighted CP can successfully mitigate our covariate shift examples, we now investigate how covariate shift and subsequent weighted CP affect the conditional confidence, as this is the output from our GW search pipeline combination analysis we are most interested in.

To investigate how the conditional confidence changes before and after applying the weighted CP, we plot the conditional confidence difference between the two, defined as $\Delta \text{conf}_{Y=1} = \text{conf}_{Y=1}^{q_\alpha^{w,y}(\mathbf{X}')} - \text{conf}_{Y=1}^{q_\alpha^y}$, in Figure 5. In the scenarios where features are shifted to lower values, we observe that the conditional confidence increases when using weighted CP versus the standard CP. The difference is also larger for a greater shift intensity. Conversely, when features are shifted to higher values, we observe that the conditional confidence decreases when using weighted CP versus the standard CP. In this scenario, there is also minor fluctuation around zero with some positive differences.

We plot the conditional confidence difference against the maximum- $\log_{10}$ IFAR, which represents a measure of candidate significance, to demonstrate the dependence on the underlying features. The conditional confidence varies the most for events with a maximum- $\log_{10}$ IFAR value close to the FAR threshold, the conventional but arbitrary boundary between signal and noise, where classification is most uncertain. Meanwhile, for events with high maximum- $\log_{10}$ IFAR the conditional confidence barely changes, since these are clear signals with conditional confidence values around one. Similarly, at very low maximum- $\log_{10}$ IFAR values we find noise events with consistently small conditional confidence.

3.2. Unknown shift between two datasets

We now evaluate the performance of the MDC-trained-and-calibrated framework on the LLPIC dataset, simulating a situation where our pre-trained framework is later applied to real data. A distribution shift between the two mock datasets is expected, as they originate from different observing runs with associated upgrades to detectors and analysis software (changes which are also expected to contribute to the shift between mock and real data), although the nature of the shift is not known. Motivated by the expectation that distributional shifts in pipeline outputs affect signal and noise events similarly, and by our empirical findings in the previous section, we again adopt the marginally weighted CP approach.

First, we quantify the shift using EMD, obtaining a value of 0.22 between the MDC calibration data and the LLPIC test set. This indicates a moderate shift, comparable to the induced covariate shifts with shift intensity 2 from Table 1.




Figure 5: Difference between the conditional confidence as obtained using weighted CP versus standard CP. A positive difference implies that the conditional confidence increases when applying the weighted CP. The dashed black vertical line indicates the FAR threshold of 1 per year.

We then apply both standard and weighted CP, and present the coverage results in Figure 6(a). We observe that standard CP leads to undercoverage. Using weighted CP improves the coverage toward the diagonal, but some undercoverage outside the expected binomial confidence band remains, suggesting that the observed distribution shift is not purely covariate.

The conditional confidence residual is plotted in Figure 6(b), showing that the conditional confidence increases when applying weighted CP compared to the standard CP. This is comparable to the induced covariate shift test case when resampling to lower feature values explored in Figure 5, suggesting that the LLPIC data contains a greater proportion of events with lower feature values relative to the MDC calibration data. Examining the raw feature distributions, we find that, overall, the features in the LLPIC data tend toward lower values than the corresponding MDC values; however, this trend is not uniform, and the direction and magnitude of the shift depend on the specific feature and class considered. Similar to the induced shift test cases, we also observe the greatest differences in conditional confidence for events with maximum- $\log_{10}$ IFAR values around the FAR threshold, while noise events with small maximum- $\log_{10}$ IFAR and signals with high maximum- $\log_{10}$ IFAR vary little.

Finally, we investigate how the physical interpretations change when applying the weighted CP. Defining a threshold of 0.5 on the conditional confidence to distinguish between signal and noise predictions, we compare the resulting classifications against the maximum- $\log_{10}$ IFAR threshold corresponding to a FAR of 1 per year, see Figure 7. The dataset




Figure 6: Coverage (left) and conditional confidence difference (right) as obtained on the LLPIC test data, when training the ML classifier and calibrating CP on the MDC data. The shaded grey area in the left plot represents the 99% binomial confidence band corresponding to the minimum per-label effective calibration size $\min_y \hat{n}_y$. The dashed black vertical line in the right figure indicates the FAR threshold of 1 per year.

contains a total of 534 injected signals, of which 356 are above the maximum- $\log_{10}\text{IFAR}$ threshold. Using standard CP, we obtain 333 predicted signals, corresponding to a true positive rate (TPR) of 61% and a false positive rate (FPR) of 2%. However, weighted CP gives 552 signal predictions, increasing the TPR to 84% at the cost of a higher FPR of 16%.

The regions of greatest interest for our GW analysis are the quadrants where the conditional confidence and maximum- $\log_{10}\text{IFAR}$ disagree. In the upper left quadrants, events are classified as noise by maximum- $\log_{10}\text{IFAR}$ but as signals by our framework. Using standard CP (see Figure 7(a)), there are 44 such events, of which 43 are true signals, while for the weighted CP (see Figure 7(b)), there are 141 true signals among 196 candidates. Thus, while the weighted CP results in six times as many false positives (from 16 to 106), we also find 98 new signals. In the bottom right quadrants, events with maximum- $\log_{10}\text{IFAR}$ above threshold but conditional confidence below threshold are located. We find 67 such events for the standard CP, including 31 signals, while there are none for the weighted CP.

Overall, weighted CP improves sensitivity to GW signals at the cost of a higher false positive rate. By correcting for the covariate shift between the training and test distributions, the weighted CP recovers many additional true signals that would otherwise be missed by standard CP, reducing the false negative rate from 39% to 16%. However, this comes at the expense of a sixfold increase in false positives, reflecting the reduced effective calibration sample size $\hat{n}_y$ incurred by the weighting procedure. The choice between standard and weighted CP therefore represents a trade-off between sensitivity and purity that depends on the scientific goal: based on our empirical results, standard CP is more conservative and better suited to constructing a high-purity catalogue, while weighted CP is preferable when maximising the recovery of true signals is the priority.




Figure 7: Conditional confidence versus maximum- $\log_{10}$ IFAR on the LLPIC test data, as trained and calibrated on the MDC data, using standard Mondrian CP (left) and weighted Mondrian CP (right). The data are coloured by the true label.

4. Conclusion

In this work, we have presented a framework for combining the outputs of multiple gravitational-wave search algorithms using Mondrian CP, extended to account for distribution shift by reweighting calibration points according to the estimated likelihood ratio between the test and calibration feature distributions. Using controlled distributional shifts in the simulated MDC dataset, we demonstrated that standard CP loses its coverage guarantee under covariate shift, with the degree of miscoverage scaling with the shift intensity. Weighted CP successfully restores well-calibrated coverage across all shift intensities considered, confirming that the reweighting procedure can fully correct for induced covariate shifts of the type explored here. We estimate the marginal likelihood ratio from unlabelled test data, which our empirical investigation shows to be the most robust choice, as class-conditional approximations rely on proxy labels whose accuracy cannot be guaranteed.

Applying the same framework to the unknown shift between two mock datasets, the MDC and LLPIC, we find that weighted CP improves coverage toward the diagonal, though some residual undercoverage remains. This suggests the distributional difference between the two datasets is not purely a covariate shift, and that violations of the assumption that the class-conditional and marginal ratios are approximately equal may be present. The reweighting of the CP quantile increases the conditional confidence of events, particularly for those near the FAR threshold where classification is most uncertain.

In terms of physical interpretation, weighted CP reduces the false negative rate, recovering signals that standard CP would miss, at the cost of a higher false positive rate. This reflects an inherent sensitivity-purity trade-off: based on our empirical results, weighted CP is well-suited to applications where completeness is paramount, such as population studies sensitive to selection effects, while the more conservative standard CP remains preferable for constructing high-purity catalogues. When applied in practice to real detector data with unknown labels, the choice of method carries direct scientific consequences, as both missed signals and false detections can bias astrophysical conclusions. Future work could

explore tighter control of this trade-off, for example, through adaptive conditional confidence thresholds or improved likelihood ratio estimation for more complex distributional shifts.

Acknowledgements

We want to thank Michael Coughlin, Deep Chatterjee, Tito Dal Canton, Reed Essick, Shaon Ghosh, Sushant Sharma-Chaudhary, Max Trevor, and Andrew Toivonen for the development of the MDC results used in this work. We use data from [Chaudhary et al. \(2026\)](#) and thank the authors for preparing this dataset, and Sushant Sharma-Chaudhary and Thomas Sainrat for their help and advice in utilising it. Implementation of our ML model was done using `scikit-learn` ([Buitinck et al., 2013](#)), while we utilise NumPy ([Harris et al., 2020](#)), Pandas ([pandas development team, 2020](#)), and Matplotlib ([Hunter, 2007](#)) for data handling and visualisation. This material is based upon work supported by NSF’s LIGO Laboratory, which is a major facility fully funded by the National Science Foundation. The authors are grateful for computational resources provided by the LIGO Laboratory and supported by National Science Foundation Grants PHY-0757058 and PHY-0823459. This work is supported by the Science and Technology Facilities Council (STFC) grant UKRI2488.

References

- J. Aasi et al. Advanced LIGO. *Class. Quant. Grav.*, 32:074001, 2015. doi: 10.1088/0264-9381/32/7/074001.
- A. G. Abac et al. GWTC-5.0: Observations from the Second Part of the Fourth LIGO-Virgo-KAGRA Observing Run and Updates to the Gravitational-Wave Transient Catalog. 5 2026a.
- A. G. Abac et al. GWTC-5.0: Methods for Identifying and Characterizing Gravitational-wave Transients. 5 2026b.
- A. G. Abac et al. GWTC-5.0: An Introduction to Version 5.0 of the Gravitational-Wave Transient Catalog. 5 2026c.
- B. P. Abbott et al. Observation of Gravitational Waves from a Binary Black Hole Merger. *Phys. Rev. Lett.*, 116(6):061102, 2016. doi: 10.1103/PhysRevLett.116.061102.
- B. P. Abbott et al. A guide to LIGO–Virgo detector noise and extraction of transient gravitational-wave signals. *Class. Quant. Grav.*, 37(5):055002, 2020. doi: 10.1088/1361-6382/ab685e.
- F. Acernese et al. Advanced Virgo: a second-generation interferometric gravitational wave detector. *Class. Quant. Grav.*, 32(2):024001, 2015. doi: 10.1088/0264-9381/32/2/024001.
- T. Adams, D. Buskulic, V. Germain, G. M. Guidi, F. Marion, M. Montani, B. Mours, F. Piergiovanni, and G. Wang. Low-latency analysis pipeline for compact binary coalescences in the advanced gravitational wave detector era. *Class. Quant. Grav.*, 33(17):175012, 2016. doi: 10.1088/0264-9381/33/17/175012.

- T. Akutsu et al. Overview of KAGRA: Detector design and construction history. *PTEP*, 2021(5):05A101, 2021. doi: 10.1093/ptep/ptaa125.
- B. Allen. χ^2 time-frequency discriminator for gravitational wave detection. *Phys. Rev. D*, 71:062001, 2005. doi: 10.1103/PhysRevD.71.062001.
- B. Allen, W. G. Anderson, P. R. Brady, D. A. Brown, and J. D. E. Creighton. FINDCHIRP: An Algorithm for detection of gravitational waves from inspiraling compact binaries. *Phys. Rev. D*, 85:122006, 2012. doi: 10.1103/PhysRevD.85.122006.
- C. All  n   et al. The MBTA pipeline for detecting compact binary coalescences in the fourth LIGO-Virgo-KAGRA observing run. *Class. Quant. Grav.*, 42(10):105009, 2025. doi: 10.1088/1361-6382/add234.
- A. N. Angelopoulos and S. Bates. A gentle introduction to conformal prediction and distribution-free uncertainty quantification. *arXiv preprint arXiv:2107.07511*, 2021.
- G. Ashton, N. Colombo, I. Harry, and S. Sachdev. Calibrating gravitational-wave search algorithms with conformal prediction. *Phys. Rev. D*, 109(12):123027, 2024. doi: 10.1103/PhysRevD.109.123027.
- G. Ashton, A.-K. Malz, and N. Colombo. Enhancing Gravitational-Wave Detection: A Machine Learning Pipeline Combination Approach with Robust Uncertainty Quantification. *Phys. Rev. Lett.*, 136(1):011402, 2026. doi: 10.1103/yfb3-fgf2.
- F. Aubin et al. The MBTA pipeline for detecting compact binary coalescences in the third LIGO-Virgo observing run. *Class. Quant. Grav.*, 38(9):095004, 2021. doi: 10.1088/1361-6382/abe913.
- S. Banagiri, C. P. L. Berry, G. S. Cabourn Davies, L. Tsukada, and Z. Doctor. Unified pastro for gravitational waves: Consistently combining information from multiple search pipelines. *Phys. Rev. D*, 108(8):083043, 2023. doi: 10.1103/PhysRevD.108.083043.
- L. Buitinck et al. API design for machine learning software: experiences from the scikit-learn project. 9 2013.
- K. Cannon et al. GstLAL: A software framework for gravitational wave discovery. 10 2020.
- C. Capano, T. Dent, Y.-M. Hu, M. Hendry, C. Messenger, and J. Veitch. Systematic errors in estimation of gravitational-wave candidate significance. 1 2016.
- S. S. Chaudhary et al. Low-latency gravitational wave alert products and their performance at the time of the fourth LIGO-Virgo-KAGRA observing run. *Proc. Nat. Acad. Sci.*, 121(18):e2316474121, 2024. doi: 10.1073/pnas.2316474121.
- S. S. Chaudhary et al. Low-latency gravitational wave alert infrastructure and new data products for multi-messenger astronomy during ligo-virgo-kagras fourth observing run. 2026. in preparation.

- T. Dal Canton et al. Implementing a search for aligned-spin neutron star-black hole systems with advanced ground based gravitational wave detectors. *Phys. Rev. D*, 90(8):082004, 2014. doi: 10.1103/PhysRevD.90.082004.
- G. S. Davies, T. Dent, M. Tápai, I. Harry, C. McIsaac, and A. H. Nitz. Extending the PyCBC search for gravitational waves from compact binary mergers to a global network. *Phys. Rev. D*, 102(2):022004, 2020. doi: 10.1103/PhysRevD.102.022004.
- T. Ding, A. N. Angelopoulos, S. Bates, M. I. Jordan, and R. J. Tibshirani. Class-conditional conformal prediction with many classes. *CoRR*, abs/2306.09335, 2023. doi: 10.48550/arXiv.2306.09335. URL <https://doi.org/10.48550/arXiv.2306.09335>.
- R. A. Fischer. *Statistical methods for research workers*. Edinburgh, Oliver and Boyd, 1925.
- C. Hanna et al. Fast evaluation of multidetector consistency for real-time gravitational wave searches. *Phys. Rev. D*, 101(2):022003, 2020. doi: 10.1103/PhysRevD.101.022003.
- C. R. Harris, K. J. Millman, S. J. van der Walt, R. Gommers, P. Virtanen, D. Cournapeau, E. Wieser, J. Taylor, S. Berg, N. J. Smith, et al. Array programming with numpy. *Nature*, 585(7825):357–362, 2020.
- J. D. Hunter. Matplotlib: A 2d graphics environment. *Computing In Science & Engineering*, 9(3):90–95, May-Jun 2007.
- P. Joshi et al. New Methods for Offline GstLAL Analyses. 6 2025.
- L. Kish. Survey sampling. *American Political Science Review*, 59(4):1025–1025, 1965. doi: 10.1017/S0003055400132113.
- S. Klimenko and G. Mitselmakher. A wavelet method for detection of gravitational wave bursts. *Class. Quant. Grav.*, 21:S1819–S1830, 2004. doi: 10.1088/0264-9381/21/20/025.
- S. Klimenko, S. Mohanty, M. Rakhmanov, and G. Mitselmakher. Constraint likelihood analysis for a network of gravitational wave detectors. *Phys. Rev. D*, 72:122002, 2005. doi: 10.1103/PhysRevD.72.122002.
- S. Klimenko, I. Yakushin, A. Mercer, and G. Mitselmakher. Coherent method for detection of gravitational wave bursts. *Class. Quant. Grav.*, 25:114029, 2008. doi: 10.1088/0264-9381/25/11/114029.
- S. Klimenko, G. Vedovato, M. Drago, G. Mazzolo, G. Mitselmakher, C. Pankow, G. Prodi, V. Re, F. Salemi, and I. Yakushin. Localization of gravitational wave sources with networks of advanced detectors. *Phys. Rev. D*, 83:102001, 2011. doi: 10.1103/PhysRevD.83.102001.
- S. Klimenko et al. Method for detection and reconstruction of gravitational wave transients with networks of advanced detectors. *Phys. Rev. D*, 93(4):042004, 2016. doi: 10.1103/PhysRevD.93.042004.

- S. Laghuvarapu, R. Deb, and J. Sun. Kmm-cp: Practical conformal prediction under covariate shift via selective kernel mean matching. *arXiv preprint arXiv:2603.26415*, 2026.
- A.-K. Malz, S. Russell, G. Ashton, and N. Colombo. Combining gravitational wave search pipelines to find subthreshold signals in GWTC-5.0. *arXiv preprint arXiv:2607.07272*, 7 2026.
- C. Messick et al. Analysis Framework for the Prompt Discovery of Compact Binary Mergers in Gravitational-wave Data. *Phys. Rev. D*, 95(4):042001, 2017. doi: 10.1103/PhysRevD.95.042001.
- T. Mishra, S. Bhaumik, V. Gayathri, M. J. Szczepańczyk, I. Bartos, and S. Klimenko. Gravitational waves detected by a burst search in LIGO/Virgo’s third observing run. *Phys. Rev. D*, 111(2):023054, 2025. doi: 10.1103/PhysRevD.111.023054.
- A. H. Nitz, T. Dent, T. Dal Canton, S. Fairhurst, and D. A. Brown. Detecting binary compact-object mergers with gravitational waves: Understanding and Improving the sensitivity of the PyCBC search. *Astrophys. J.*, 849(2):118, 2017. doi: 10.3847/1538-4357/aa8f50.
- The pandas development team. pandas-dev/pandas: Pandas, February 2020. URL <https://doi.org/10.5281/zenodo.3509134>.
- A. Ramdas, N. García Trillos, and M. Cuturi. On wasserstein two-sample testing and related families of nonparametric tests. *Entropy*, 19(2):47, 2017.
- Y. Rubner, C. Tomasi, and L.J. Guibas. A metric for distributions with applications to image databases. In *Sixth International Conference on Computer Vision (IEEE Cat. No.98CH36271)*, pages 59–66, 1998. doi: 10.1109/ICCV.1998.710701.
- S. Sachdev et al. The GstLAL Search Analysis Methods for Compact Binary Mergers in Advanced LIGO’s Second and Advanced Virgo’s First Observing Runs. 1 2019.
- S. Sakon et al. Template bank for compact binary mergers in the fourth observing run of Advanced LIGO, Advanced Virgo, and KAGRA. *Phys. Rev. D*, 109(4):044066, 2024. doi: 10.1103/PhysRevD.109.044066.
- G. Shafer and V. Vovk. A tutorial on conformal prediction. *Journal of Machine Learning Research*, 9:371–421, 2008. doi: 10.48550/arXiv.0706.3188.
- R. J. Tibshirani, R. Foygel Barber, E. Candès, and A. Ramdas. Conformal prediction under covariate shift. *Advances in neural information processing systems*, 32, 2019.
- L. Tsukada et al. Improved ranking statistics of the GstLAL inspiral search for compact binary coalescences. *Phys. Rev. D*, 108(4):043004, 2023. doi: 10.1103/PhysRevD.108.043004.

- S. Tsukamoto, A. Toivonen, H. Griffin, A. Raghuvanshi, M. Averill, F. Kerkow, M. W. Coughlin, M. L. Chan, and L. Singer. Astrophysical or Terrestrial: Machine Learning Classification of Gravitational-wave Candidates Using Multiple-search Information. *Publ. Astron. Soc. Pac.*, 138(1):014503, 2026. doi: 10.1088/1538-3873/ae1e2e.
- S. A. Usman et al. The PyCBC search for gravitational waves from compact binary coalescence. *Class. Quant. Grav.*, 33(21):215004, 2016. doi: 10.1088/0264-9381/33/21/215004.
- P. Virtanen, R. Gommers, T. E. Oliphant, M. Haberland, et al. SciPy 1.0: Fundamental algorithms for scientific computing in python. *Nature Methods*, 17(3):261–272, 2020. doi: 10.1038/s41592-019-0686-2.
- V. Vovk. Conditional validity of inductive conformal predictors. *Machine Learning*, 92, 2013.
- V. Vovk, A. Gammerman, and G. Shafer. *Algorithmic learning in a random world*, volume 29. Springer, 2005.
- R. Weiss. Electromagnetically coupled broadband gravitational antenna. *MIT Res. Lab. Electron. Q. Prog. Rep*, 105:54–76, 1972.