arXiv:2610.18656v1 [cs.LG] 13 Oct 2026

Bayesian Test-Time Inference of Task-Aligned Similarity from Weak Interactive Feedback

Weida Liang
National University of Singapore
weida_liang@u.nus.edu

Kenji Kawaguchi
National University of Singapore
kenji@comp.nus.edu.sg

Abstract

Language model systems repeatedly make test-time decisions by comparing similarity: they retrieve exemplars, rank candidates, and revise responses. Yet similarity is not unique: lexical, semantic, structural, and stylistic resemblance can point to different candidates, and the task-aligned notion can change across instances. We introduce BASIS (Bayesian Axis Selection via Interactive Signals), a training-free Bayesian method that uses weak test-time feedback to infer which criterion in a supplied, task-specific library governs the current decision. It maintains a joint posterior over candidate targets and criteria, updates it from scalar scores, pairwise preferences, or verifier outputs, and selects probes by expected information gain. In a finite noisy model, we characterize when the target–criterion pair is recoverable and show why fixed-criterion and fixed-mixture rules can fail under criterion shift. Across concept recovery, reasoning exemplar selection, and response refinement, BASIS improves six-probe concept-recovery Success@1 from 56.0% to 68.1%, reasoning accuracy from 72.3% to 73.1%, and refinement win rate from 61.4% to 63.8% over tuned static mixtures. It also exceeds compute-matched best-of-N selection on reasoning (72.1%) and refinement (61.2%). Gains are largest under criterion mismatch and with larger candidate pools, and matched controls indicate that adaptive criterion weighting explains much of the benefit, with joint target–criterion inference adding further value. BASIS selects only among supplied criteria and does not discover new ones.

1 Introduction

Language models rank passages, demonstrations, and response drafts using similarity [4, 14, 21]. Yet relevance depends on the instance: a useful math exemplar may share the operation sequence rather than the topic, while a preferred revision may match the requested tone rather than the subject matter. A fixed embedding or mixture score may select a plausible but task-misaligned candidate.

At test time, systems may receive scalar, pairwise, or verifier feedback. Prior work uses such signals for reranking, query rewriting, self-correction, and verifier-guided selection [17, 24, 11, 1, 18, 6, 22]. But feedback can show which candidate works without revealing why: a verifier score may reward structural fit, answer consistency, or style, and the useful criterion can vary by instance. Search and stronger rerankers improve selection under a chosen scoring rule, but do not by themselves infer when that rule should change [25, 3].

We study this inference within a finite, task-specific criterion library supplied in advance. BASIS (Bayesian Axis Selection via Interactive Signals) is training-free: it maintains a joint posterior over candidate targets and criteria, updates it from scalar, pairwise, or verifier feedback, and selects probes by expected information gain. Joint inference retains target–criterion dependence, while the criterion marginal makes the selection process inspectable.

40th Conference on Neural Information Processing Systems (NeurIPS 2026).

After six probes, concept-recovery Success@1 is 68.1% for BASIS versus 56.0% for a tuned mixture. Reasoning accuracy is 73.1% versus 72.3%, and refinement win rate is 63.8% versus 61.4%. Under distractors, reasoning drops by 4.9 points for BASIS and 6.5 for the tuned mixture. We evaluate one model stack and inference within a supplied criterion library.

Our contributions are:

1. We formulate feedback-driven selection as joint inference over a candidate and a finite library of relevance criteria, and introduce BASIS for this task.
2. We characterize recovery under separability and probe coverage, and identify settings in which a fixed criterion or mixture cannot track instance-dependent relevance.
3. We evaluate concept recovery, reasoning exemplar selection, and response refinement, using matched controls to separate adaptive weighting from joint target–criterion inference.

2 Related Work

Retrieval and example selection. Few-shot prompting and RAG select demonstrations or passages [4, 14]. Prompt retrieval, Bayesian example selection, and structure-aware retrieval improve ranking [21, 28, 15]. BASIS instead infers which available criterion is relevant to each query.

Feedback-driven test-time improvement. Self-Refine, Reflexion, CRITIC, Self-RAG, RaFe, and verifier-based methods use feedback for revision, retrieval, or candidate scoring [17, 24, 11, 1, 18, 6, 22]. BASIS uses feedback to infer the criterion that best explains each signal.

Conditional retrieval. C-STS, FollowIR, and perspective-aware retrieval condition similarity on an explicit aspect, instruction, or viewpoint [8, 29, 30]. These methods supply a criterion. BASIS infers which one in a finite library best accounts for weak feedback.

Bayesian inference and active learning. Bayesian accounts of in-context learning view test-time behavior as posterior inference over latent tasks [20]. Active learning selects queries to reduce uncertainty [16, 23]. Information Pursuit selects interpretable queries by information gain for supervised prediction [5]. BASIS uses informative queries for training-free inference over a joint candidate–criterion state, then ranks candidates in the pool.

Reranking and test-time compute. Richer rerankers and repeated verifier-guided sampling improve selection under fixed scores [25, 3]. We compare these alternatives in settings where the criterion may shift across instances.

3 Problem Formulation

Let $\mathcal{Z}$ be a finite candidate space and $\mathcal{A}$ a finite, task-specific library of relevance criteria, such as semantic similarity, entity overlap, reasoning structure, or style. We call each criterion an *axis* in the notation below, following the name BASIS. The terms refer to the same latent variable $a \in \mathcal{A}$. The unknown pair $(z^\star, a^\star)$ identifies a useful candidate and the criterion governing its relevance. Our formulation assumes that a useful criterion is represented in $\mathcal{A}$.

At interaction round t, the learner chooses a probe $q_t \in \mathcal{Q}$ and observes weak feedback y_t. A probe can be a single candidate presented for scoring, a pair of candidates presented for comparison, or a structured question designed to reveal one aspect of the target. Feedback is generated from a criterion-conditioned model,

$$y_t \sim p(y \mid q_t, z^\star, a^\star). \tag{1}$$

The learner accumulates data $\mathcal{D}_t = \{(q_i, y_i)\}_{i=1}^t$ and maintains the joint posterior

$$p_t(z, a) = p(z, a \mid \mathcal{D}_t). \tag{2}$$

The central ambiguity is that one feedback signal can often be explained by multiple target–criterion pairs. A high score may indicate topical overlap under one criterion, structural compatibility under

another, or stylistic affinity under a third. Without modeling a, a learner can assign high confidence to a wrong target supported only by the wrong notion of similarity.

The resulting decision rule should therefore depend on the posterior over criteria. For an input x and candidate z, our dynamic utility is

$$U_t(x, z) = \sum_{a \in \mathcal{A}} p_t(a)\, s_a(x, z). \tag{3}$$

A static mixture replaces $p_t(a)$ with fixed weights w_a and therefore cannot adapt to the current instance or feedback history.

Our objective is to use as few rounds of feedback as possible to recover $z^\star$, identify $a^\star$, or choose the best downstream action. In retrieval, this means selecting exemplars with maximal task utility. In refinement, it means choosing a response aligned with latent user preference. In concept recovery, it means localizing the hidden target among confusable distractors. Empirically, we evaluate target recovery, downstream utility, and whether dynamic posterior weighting can be matched by fixed mixtures, stronger rerankers, or more brute-force search under the same signals.

4 Method

We call our framework BASIS (Bayesian Axis Selection via Interactive Signals). At test time, it uses a frozen representation backbone and weak interaction to infer both *which target is useful* and *which criterion matters for the current instance*. The reasoning library spans semantic, lexical, entity, structural, and answer-consistency criteria. Refinement uses six preference criteria.

BASIS has three moving parts: a criterion-conditioned scoring library, a Bayesian posterior update, and an information-seeking probe policy. The scoring library defines plausible explanations of feedback. The posterior decides which explanation is most credible. The probe policy chooses the next interaction that will reduce uncertainty most.

4.1 Criterion-conditioned similarity

For every probe q and candidate z, we obtain a base representation $h(q), h(z) \in \mathbb{R}^d$ from a frozen encoder. Each criterion $a \in \mathcal{A}$ defines a projection or scoring rule P_a, giving the criterion-conditioned similarity

$$s_a(q, z) = \cos\big(P_a h(q), P_a h(z)\big). \tag{4}$$

In practice, P_a is a deterministic feature transform or lightweight scorer. The reusable criteria are semantic, lexical, entity, structural, style, and answer consistency.

The six criteria form a reusable menu rather than a universal inventory. Each task uses a relevant subset. Performance depends on the supplied library containing a useful criterion. Section 8 measures the effect of weakening this assumption.

4.2 Bayesian update from weak feedback

Starting from a prior $p_0(z, a)$, BASIS updates the joint posterior after every feedback observation:

$$p_t(z, a) \propto p(y_t \mid q_t, z, a)\, p_{t-1}(z, a). \tag{5}$$

This produces two useful marginals,

$$p_t(z) = \sum_{a \in \mathcal{A}} p_t(z, a), \qquad p_t(a) = \sum_{z \in \mathcal{Z}} p_t(z, a). \tag{6}$$

The target marginal supports downstream selection. The criterion marginal indicates which notion of relevance best explains the observed feedback.

Scalar scores. For scalar feedback, we use

$$p(y_t \mid q_t, z, a) = \mathcal{N}\big(y_t; s_a(q_t, z), \sigma_a^2\big). \tag{7}$$

Pairwise preferences. For pairwise feedback, we use a Bradley–Terry preference model,

$$p(q_i \succ q_j \mid z, a) = \frac{\exp\big(\beta s_a(q_i, z)\big)}{\exp\big(\beta s_a(q_i, z)\big) + \exp\big(\beta s_a(q_j, z)\big)}. \tag{8}$$

Verifier signals. For pass/fail or verifier outputs $y_t \in \{0, 1\}$, we use

$$p(y_t = 1 \mid q_t, z, a) = \sigma(\gamma s_a(q_t, z) + b_a)\,, \tag{9}$$

where $\sigma(\cdot)$ is the logistic sigmoid.

Likelihoods must be sampleable and evaluable. Mutual information need not be closed form. Scalar, pairwise, and verifier feedback use Gaussian, Bradley–Terry, and logistic models.

4.3 Active probe selection

At round t, BASIS selects the probe that maximizes expected entropy reduction:

$$q_{t+1} = \operatorname*{argmax}_{q \in \mathcal{Q}} \Big[H\big(p_t(z, a)\big) - \mathbb{E}_{y \sim p(y \mid q, \mathcal{D}_t)} H\big(p_{t+1}(z, a \mid q, y)\big) \Big]. \tag{10}$$

This quantity is exactly the mutual information $I((z, a); y \mid q, \mathcal{D}_t)$. The greedy probe is therefore the natural one-step choice for this uncertainty-reduction objective.

The default uses the top K candidates under $p_t(z)$ and M Monte Carlo feedback samples. An optional criterion-entropy surrogate is faster but discards information about the joint state. The results are reported in Section 8.

4.4 Decision rule and complexity

For target recovery, we return the MAP estimate

$$\hat{z} = \operatorname*{argmax}_{z \in \mathcal{Z}} p_T(z). \tag{11}$$

For downstream retrieval or refinement, we rank candidates by $U_T(x, z)$.

With cached criterion scores, posterior construction and updating cost $\mathcal{O}(N|\mathcal{A}|)$ per interaction round. Evaluating a fixed set $\mathcal{Q}_{\text{eval}}$ of candidate probes with top-K pruning and M Monte Carlo feedback samples costs $\mathcal{O}(|\mathcal{Q}_{\text{eval}}|K|\mathcal{A}|M)$. Thus, posterior updates grow linearly with the full candidate count, while probe selection depends on the retained candidates and evaluated-probe set. These costs exclude candidate generation and query-dependent criterion scoring.

5 Theoretical Analysis

We study target–criterion recovery and fixed-rule failures in a finite model. Guarantees require separability and probe coverage and need not extend to general language-model feedback.

5.1 Assumptions

Assumption 1: finite spaces. The candidate space $\mathcal{Z}$ and criterion library $\mathcal{A}$ are finite, and the score functions $s_a(q, z)$ are normalized to $[-1, 1]$.

Assumption 2: noisy scalar feedback. For the true pair $(z^\star, a^\star)$,

$$y_t = s_{a^\star}(q_t, z^\star) + \epsilon_t, \qquad \epsilon_t \sim \mathcal{N}(0, \sigma^2). \tag{12}$$

The noise is independent across rounds, and each probe is selected using only past observations.

Assumption 3: separability. For every incorrect pair $(z, a) \neq (z^\star, a^\star)$, there exists at least one probe $q \in \mathcal{Q}$ such that

$$\big|s_{a^\star}(q, z^\star) - s_a(q, z)\big| \geq \Delta \tag{13}$$

for some margin $\Delta > 0$.

Assumption 4: probe coverage. The query policy selects separating probes often enough that each incorrect pair is confronted by at least m_T informative probes by round T.

5.2 Posterior contraction

Theorem 1 (Posterior contraction)**.** *Under Assumptions 1–4 and a uniform prior over $\mathcal{Z} \times \mathcal{A}$, there are constants $c, C > 0$ such that, for any $\delta \in (0,1)$ satisfying $m_T \Delta^2/\sigma^2 \geq C \log(|\mathcal{Z}||\mathcal{A}|/\delta)$,*

$$\Pr\left[1 - p_T(z^\star, a^\star) \leq |\mathcal{Z}|\,|\mathcal{A}|\,\exp\left(-c\, m_T \frac{\Delta^2}{\sigma^2}\right)\right] \geq 1 - \delta, \tag{14}$$

for all sufficiently large T.

Appendix B gives the derivation. The guarantee is conditional on separability and sufficient probe coverage under the stated Gaussian feedback model.

5.3 Why criterion inference matters

Proposition 1 (Fixed-criterion non-identifiability)**.** *Suppose feedback is generated by $(z^\star, a^\star)$, but a learner restricts inference to a fixed criterion $\bar{a} \neq a^\star$. If a wrong candidate $z^\dagger \neq z^\star$ satisfies*

$$p(y \mid q, z^\dagger, \bar{a}) = p(y \mid q, z^\star, a^\star) \qquad \text{for all } q \in \mathcal{Q} \text{ and } y, \tag{15}$$

then Eq. (15) makes the wrong candidate observationally equivalent to the true pair.

The exact observational equivalence in Eq. (15) also prevents joint inference from distinguishing the two pairs if both are included in its support. Joint recovery instead requires the separability and probe-coverage conditions of Theorem 1. Without these conditions, a misspecified fixed criterion can leave a wrong target observationally plausible even with unlimited feedback.

5.4 Why fixed mixtures can fail

Proposition 2 (Static mixtures need not match adaptive criterion inference)**.** *Suppose the task-relevant candidate is z^+ on both instances, but the relevant criterion changes. For two criteria $a_1 \neq a_2$, instances x_1, x_2, and candidates z^+, z^-, assume*

$$s_{a_1}(x_1, z^+) - s_{a_1}(x_1, z^-) = \Delta, \qquad s_{a_2}(x_1, z^+) - s_{a_2}(x_1, z^-) = -\Delta, \tag{16}$$

while on x_2 the differences are reversed:

$$s_{a_1}(x_2, z^+) - s_{a_1}(x_2, z^-) = -\Delta, \qquad s_{a_2}(x_2, z^+) - s_{a_2}(x_2, z^-) = \Delta, \tag{17}$$

and let all remaining criteria contribute zero to these comparisons. Then no fixed mixture with weights shared across instances

$$U_{\text{mix}}(x, z; w) = \sum_{a \in \mathcal{A}} w_a s_a(x, z) \tag{18}$$

can rank z^+ above z^- on both instances: the score differences are $\Delta(w_{a_1} - w_{a_2})$ and $-\Delta(w_{a_1} - w_{a_2})$. An adaptive rule can rank z^+ first on both by concentrating on a_1 for x_1 and on a_2 for x_2.

This proposition isolates the role of criterion shift: with the same score library, a shared set of weights cannot satisfy both instance-specific rankings.

5.5 Information-seeking probes

Proposition 3 (One-step information gain)**.** *For any probe q, the expected entropy reduction equals*

$$H\big(p_t(z, a)\big) - \mathbb{E}_y H\big(p_{t+1}(z, a \mid q, y)\big) = I\big((z, a); y \mid q, \mathcal{D}_t\big). \tag{19}$$

Thus, the greedy probe selected by BASIS is the most informative one-step measurement for reducing uncertainty about the latent target–criterion pair.

6 Experimental Setup

All methods share candidate pools, backbone, prompts, and feedback or verifier access whenever applicable. Appendix C provides construction and implementation details.

Tasks. For controlled concept recovery, we run 500 episodes with 50 candidates and up to 12 probes. The hidden feedback criterion is sampled from five predefined criteria, and distractors create clean and mismatch conditions. We report Success@1 after four and six probes and query efficiency relative to the 12-probe final recovery rate. For reasoning exemplar selection, we evaluate GSM8K, StrategyQA, and three BIG-Bench Hard tasks. Each query starts with 64 support examples and an initial dense shortlist of 32. Interactive methods receive at most three feedback rounds and select four exemplars. The $N = 128$ and $N = 256$ conditions add candidates from the support bank, increasing both pool size and distractor heterogeneity. For BBH, candidates come from other labeled benchmark items, excluding the current query and items that share its underlying scenario. All methods receive identical candidate pools, and the query's gold answer is used only for final evaluation. For response refinement, we use 1,000 prompts each from Anthropic HH, OpenAssistant, and UltraFeedback, with eight candidate responses and up to three scalar or pairwise feedback rounds. The mismatch split adds topic-matched responses that conflict with the preference criterion.

Criteria and feedback. Reasoning uses semantic, lexical, entity, structural, and answer-consistency scores. Refinement uses six preference criteria. Scores are normalized within each pool, cached before interaction, and shared with static-mixture baselines. Feedback combines scalar scores, pairwise preferences, verifier deltas, and answer checks. Each feedback channel has an explicit likelihood.

Comparisons. We compare retrieval and reranking, static mixtures, mean-field and criterion-marginal controls, and a history-aware reranker. Best-of-N uses four reasoning and six refinement calls, at least BASIS's three feedback calls. The oracle is evaluation-only. Appendix C details the controls and each method's information access.

Metrics and implementation. Primary metrics are target recovery, reasoning accuracy, and preference win rate. Criterion identification, criterion match, gap closed, and mismatch degradation are diagnostic. We report equal-weight task macro-averages where stated. Results average five seeds. Confidence intervals use 10,000 paired bootstrap samples, resampling test items and keeping all seed outcomes for each item together. Unless noted otherwise, BASIS uses a uniform prior, top-$K = 16$ candidates, $M = 32$ Monte Carlo feedback samples, and at most three downstream feedback rounds. End-to-end timings are reported separately from local inference.

The frozen retriever is Qwen/Qwen3-Embedding-4B, the reasoning generator is Qwen/Qwen3-8B with thinking disabled, and the shared verifier is mistralai/Ministral-3-14B-Reasoning-2512. All final answer generation uses greedy decoding. Seeds affect probe Monte Carlo sampling, candidate-pool construction, and bootstrap resampling. The reasoning results therefore describe this matched, thinking-disabled setup and are not directly comparable to benchmark scores reported with default thinking enabled.

7 Results

We report aggregate outcomes and costs. Appendix D breaks them down by task.

Controlled concept recovery. After six probes, BASIS reaches 68.1% Success@1, compared with 56.0% for the tuned static mixture and 79.5% for the oracle-criterion upper bound. Criterion identification accuracy is 80.9%. It reaches 90% of its final 12-probe recovery rate after a mean of 4.6 probes, compared with 6.5 for the tuned mixture. This controlled task separates target selection from the downstream generator and shows that interaction history can identify a useful criterion before the full probe budget is spent.

Downstream performance and latency. Table 1 reports task outcomes and end-to-end time, including final answer generation for reasoning and scoring, feedback, and selection for refinement.

Table 1: Task outcomes and end-to-end latency at batch size one. Times are means with standard deviations over 100 items. The verifier controls use $N = 4$ calls for reasoning and $N = 6$ for refinement. BASIS uses $T = 3$ feedback calls.

Task	Method	Accuracy / win rate (%)	Time (s)
Reasoning	Dense retrieval	70.0	4.82 ± 0.11
	Tuned mixture	72.3	5.04 ± 0.12
	Best-of-4 verifier	72.1	7.91 ± 0.21
	BASIS	**73.1**	7.32 ± 0.18
Refinement	Tuned mixture	61.4	6.33 ± 0.15
	Best-of-6 verifier	61.2	10.84 ± 0.29
	BASIS	**63.8**	9.08 ± 0.23

Table 2: Paired correctness counts over item–seed outcomes: 2,500 each for GSM8K and StrategyQA, 3,750 for BBH, and 8,750 pooled.

Domain	Both correct	BASIS only	Tuned only	Both wrong
GSM8K	1,801	104	82	513
StrategyQA	1,802	111	88	499
BBH aggregate	2,321	180	150	1,099
Pooled	5,924	395	320	2,111

The reasoning results are equal-weight macro-averages over GSM8K, StrategyQA, and aggregate BBH: 73.1% for BASIS and 72.3% for the tuned mixture. The paired item-clustered interval for the 0.8-point reasoning difference is $[-0.9, 2.5]$. The 2.4-point refinement gain has interval $[1.3, 3.5]$. BASIS closes 29.6% of the reasoning gap and 54.5% of the refinement gap between the tuned mixture and oracle-criterion results.

The reasoning averages are macro-averages, so we also report paired outcomes by domain. Table 2 counts item–seed outcomes.

Relative to the tuned mixture, end-to-end latency increases by 2.28 seconds (45%) for reasoning and 2.75 seconds (43%) for refinement. BASIS remains 0.59 and 1.76 seconds faster than the corresponding verifier controls. Most added time is spent acquiring feedback. Read together, the outcome and timing results show that adaptation is most useful when the feedback signal can resolve criterion ambiguity. For routine reasoning instances with a small accuracy difference, a static selector remains a lower-latency option.

Criterion mismatch and pool enlargement. On clean reasoning pools, BASIS scores 73.1%. With distractors it scores 68.2%, a 4.9-point drop. The tuned mixture drops from 72.3% to 65.8% (6.5 points). After two additional feedback rounds, BASIS at $T = 5$ reaches 71.4% on the distractor split. On refinement, clean/mismatch win rates are 63.8/61.5 for BASIS, 61.4/57.2 for the tuned mixture, and 65.8/64.4 for the oracle-criterion upper bound, corresponding to drops of 2.3, 4.2, and 1.4 points. Thus, the smaller degradation under distractors is consistent across both task families, while the oracle results indicate that mismatch remains consequential even with feedback-driven selection.

The enlarged pools retain the original 64 task-matched candidates and add the highest-ranked previously unused examples from a heterogeneous bank assembled from the GSM8K and StrategyQA training splits and the BBH support manifest. The bank contains 12,416 unique examples. For each query, we exclude the current query and its scenario-equivalent items, leaving at least 10,218 eligible examples. Candidates are unique, and every method receives the same per-item, per-seed manifest. BASIS improves over the tuned mixture by 0.8, 2.4, and 2.8 points at $N = 64, 128, 256$, respectively.

Local computational scaling. The cached-score benchmark measures score gathering, posterior construction and updates, probe evaluation, and final marginalization. It excludes candidate generation, first-stage retrieval, structural extraction, and external verifier or critic scoring. With the five reasoning criteria, $K = 16$, $M = 32$, and the evaluated-probe set fixed, posterior operations grow approximately linearly with full-pool size, while probe selection remains nearly flat. The largest-pool timings use distinct bank examples, not replicated candidates.



Figure 1: Nested $N = 64, 128, 256$ candidate pools grow with a heterogeneous support bank, varying both pool size and distractor composition.

Table 3: Cached-score local inference costs for reasoning. Posterior storage is for the float64 joint distribution over five criteria.

N	Gather/assembly (ms)	Update/round (ms)	Probe/round (ms)	Marginalization (ms)	Posterior (MiB)
64	4.2	0.07	110	0.03	0.0024
256	14.6	0.18	111	0.06	0.0098
1,024	55.3	0.62	112	0.18	0.0391
4,096	216.8	2.35	114	0.66	0.1563
10,000	527.4	5.68	117	1.55	0.3815

At $N = 10{,}000$, BASIS retains exact posterior marginalization over the full pool. We also evaluate a two-stage setup in which dense retrieval first returns a shortlist and BASIS adapts within it, using a separate 250-item diagnostic set described in Appendix D. First-stage retrieval is shared across selectors and excluded from local timing. BASIS timing includes shortlist lookup, cached-score gathering, host-to-device transfer, and inference.

At $N = 10{,}000$, a Top-128 shortlist retains 3.91 of four exemplars on average and reaches 67.4% accuracy versus 67.6% for full-pool inference, while reducing local inference time from 897 to 356 ms. These measurements concern second-stage selection, not corpus-scale retrieval.

8 Analysis

What joint inference adds. Table 5 compares the inference controls.

Relative to mean-field inference, the joint posterior has point-estimate gains of 0.3 points on reasoning, 0.7 on refinement, and 0.8 on distractor accuracy. The marginal controls show a similar pattern: the joint model adds 0.5–0.6 points on reasoning, 1.1–1.4 on refinement, and 1.2–1.5 on distractors. Adaptive criterion weighting accounts for much of the gain, while preserving target–criterion dependence adds a smaller benefit that varies by task. Removing the latent criterion lowers reasoning and refinement to 70.9 and 60.7. Disabling active probing yields 72.0 and 62.4. The history-aware reranker receives the same three feedback observations but has no separately optimized probe policy.

Probe approximation and feedback-model sensitivity. With $K = 16$ and $M = 32$, the joint-information policy selects the same probe as a $K = 64$, $M = 64$ reference in 95.2% of rounds. Local selection takes 110 ms per round, compared with 856 ms for the reference. A criterion-entropy surrogate takes 68 ms and gives 73.0/63.5 on reasoning/refinement, compared with 73.1/63.8 for the default. Under Laplace, Student-t_3, or heteroscedastic Gaussian scalar feedback while inference retains a Gaussian likelihood, concept-recovery Success@1 after six probes is 67.5, 67.0, and 66.6, respectively, compared with 68.1 under matched Gaussian feedback.

Coverage of the supplied criterion library. The dominant criterion is assigned post hoc as the criterion whose score best predicts downstream success on held-out candidates. Removing it is an

Table 4: Two-stage BASIS with a frozen retriever. Shortlist agreement and overlap are relative to full-pool BASIS. Exact set agreement ignores exemplar order.

Source N	Inference set	Top-1 agreement	Mean top-four overlap	Exact set agreement	Accuracy (%)	Local time (ms)	Posterior (MiB)
1,024	Full pool	100%	4.00/4	100%	68.4	393	0.0391
1,024	Top-128	99.0%	3.96/4	96.1%	68.3	342	0.0049
10,000	Full pool	100%	4.00/4	100%	67.6	897	0.3815
10,000	Top-128	97.8%	3.91/4	91.8%	67.4	356	0.0049
10,000	Top-64	92.8%	3.72/4	81.4%	66.8	348	0.0024

Table 5: Matched-feedback controls. Entries are task accuracy or preference win rate in percent.

Method	Reasoning	Refinement	Distractor accuracy
Tuned mixture	72.3	61.4	65.8
Mean-field $q(z)q(a)$	72.8	63.1	67.4
Criterion marginal, shared probes	72.6	62.7	67.0
Criterion marginal, own probes	72.5	62.4	66.7
History-aware reranker	72.6	62.6	67.0
BASIS	73.1	63.8	68.2

oracle stress test, not a deployment procedure. The noisy-proxy conditions replace this score with proxy criteria at correlations $r = 0.75$ and $r = 0.50$. The final condition removes it. Figure 2 summarizes task outcomes and posterior diagnostics as the library is corrupted or made incomplete. The maximum-criterion posterior is computed per episode as $\max_{a \in \mathcal{A}} p_T(a)$, then averaged over episodes and seeds. A high-confidence failure is an incorrect reasoning answer or non-preferred refinement selection when posterior-predictive success is at least 0.8. This is not a calibrated guarantee.



Figure 2: Performance and posterior diagnostics under criterion corruption and removal. The removed-criterion condition is an oracle stress test. Maximum posterior reports the mean per-episode maximum mass over criteria.

A fallback based on criterion entropy and posterior-predictive likelihood is thresholded on disjoint development episodes. It achieves AUROC 0.86 and triggers on 72% of missing-criterion episodes versus 9% of full-library episodes. Under criterion removal, the fallback raises reasoning from 70.7 to 72.4 and refinement from 61.0 to 61.9, while reducing high-confidence failures from 9.2% to 4.8%. It routes uncertain cases to the tuned mixture. Expanding the reasoning/refinement libraries from 5/6 to 24 irrelevant, correlated, or redundant criteria changes accuracy by at most 0.2 points, while local probe-selection time rises from 110 to 424 ms per round.

Observed selection disagreements. Appendix E gives the full sequential-fraction GSM8K trace: BASIS selects an exemplar aligned with the updated remainder and returns \$81, while the tuned mixture returns \$63. The contrasting BBH failure appears in Figure 3: the tuned mixture answers hummingbird (D), but BASIS selects a direct-position exemplar and answers cardinal (B).

Query (BBH logical deduction). There are five birds: an owl, a cardinal, a robin, a hummingbird, and a crow. The hummingbird is left of the owl and right of the cardinal; the crow is left of the robin, and the owl is left of the crow. The question asks which bird is second from the left. The implied order is cardinal $<$ hummingbird $<$ owl $<$ crow $<$ robin, so the answer is hummingbird (D).

Tuned-mixture-only exemplar. Five books are blue, purple, yellow, black, and green. The purple book is third; yellow is left of black; green is left of purple; and blue is left of green. The question asks which is second. It requires composing relations; the answer is green book (E).

BASIS-only exemplar. Five birds are a blue jay, cardinal, hawk, hummingbird, and quail. The quail is left of the blue jay; the cardinal is third; the quail is second; and the blue jay is left of the hummingbird. The answer is quail (E), stated directly without transitive reconstruction.

Selection and feedback. The methods share three of four exemplars. The tuned mixture answers hummingbird (D) correctly; BASIS answers cardinal (B). Verifier-score differences for the direct-position bird and relation-composition book are $+0.286$ and $+0.091$; the final pairwise feedback favors the direct-position example with posterior-predictive probability 0.684. From the first feedback update to the final round, the semantic, structural, and answer-consistency posterior masses change from $(0.309, 0.202, 0.198)$ to $(0.276, 0.172, 0.266)$.

Figure 3: BBH ordering failure. Feedback favors a direct-position exemplar, but it does not support the transitive relation needed to answer the query.

An HH refinement trace raises the empathy posterior from 0.17 to 0.55; when humor is absent, BASIS favors formality. Figures 3 and 4 show the reasoning queries and feedback traces.

9 Limitations and Broader Impacts

Criterion coverage. The criterion library is specified in advance. If a relevant criterion is missing or corrupted, the posterior may favor an incorrect explanation. The evaluated fallback routes low-fit cases to the tuned mixture, but cannot establish that the library is complete.

Computation and deployment scope. Timing starts from cached representations and criterion scores, excluding candidate generation, first-stage retrieval, structural extraction, and one-time external scoring. Posterior updates scale linearly with pool size. Full-pool scoring can remain costly for criteria requiring external models.

Feedback and generalization. Most feedback comes from offline verifiers or rubric scores. Live human feedback and preference drift remain untested. Experiments use one retriever, generator, and verifier stack, leaving cross-model and serving-system generalization open.

Broader impacts. Task-aligned selection may improve relevance, but designers choose the criteria and feedback. Bias or error can reinforce undesirable outputs. High-stakes use requires independent validation and human oversight, since posterior confidence does not establish safety or fairness.

10 Conclusion

We study test-time candidate selection under ambiguity about which supplied criterion matters. Across our experiments, gains over strong fixed baselines are modest on average and larger for response refinement and criterion mismatch. Missing-criterion tests show that BASIS complements fixed selectors but does not provide open-world criterion discovery.

Acknowledgments and Disclosure of Funding

This work received no external funding. The authors declare no competing interests.

References

[1] Akari Asai, Zeqiu Wu, Yizhong Wang, Avirup Sil, and Hannaneh Hajishirzi. Self-rag: Learning to retrieve, generate, and critique through self-reflection. In *The Twelfth International Conference on Learning Representations*, 2024.

[2] Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*, 2022.

[3] Bradley Brown, Jordan Juravsky, Ryan Ehrlich, Ronald Clark, Quoc V Le, Christopher Ré, and Azalia Mirhoseini. Large language monkeys: Scaling inference compute with repeated sampling. *arXiv preprint arXiv:2407.21787*, 2024.

[4] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

[5] Aditya Chattopadhyay, Stewart Slocum, Benjamin D. Haeffele, René Vidal, and Donald Geman. Interpretable by design: Learning predictors by composing interpretable queries. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(6):7430–7443, 2023.

[6] Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

[7] Ganqu Cui, Lifan Yuan, Ning Ding, Guanming Yao, Wei Zhu, Yuan Ni, Guotong Xie, Zhiyuan Liu, and Maosong Sun. Ultrafeedback: Boosting language models with high-quality feedback, 2023.

[8] Ameet Deshpande, Carlos Jimenez, Howard Chen, Vishvak Murahari, Victoria Graf, Tanmay Rajpurohit, Ashwin Kalyan, Danqi Chen, and Karthik Narasimhan. C-sts: Conditional semantic textual similarity. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, 2023.

[9] Lev Finkelstein, Evgeniy Gabrilovich, Yossi Matias, Ehud Rivlin, Zach Solan, Gadi Wolfman, and Eytan Ruppin. Placing search in context: The concept revisited. *ACM Transactions on Information Systems*, 20 (1):116–131, 2002.

[10] Mor Geva, Daniel Khashabi, Elad Segal, Tushar Khot, Dan Roth, and Jonathan Berant. Did aristotle use a laptop? a question answering benchmark with implicit reasoning strategies. *Transactions of the Association for Computational Linguistics*, 9:346–361, 2021.

[11] Zhibin Gou, Zhihong Shao, Yeyun Gong, Yelong Shen, Yujiu Yang, Nan Duan, and Weizhu Chen. Critic: Large language models can self-correct with tool-interactive critiquing. *arXiv preprint arXiv:2305.11738*, 2023.

[12] Felix Hill, Roi Reichart, and Anna Korhonen. Simlex-999: Evaluating semantic models with (genuine) similarity estimation. *Computational Linguistics*, 41(4):665–695, 2015.

[13] Andreas Köpf, Yannic Kilcher, Dimitri Von Rütte, Sotiris Anagnostidis, Zhi Rui Tam, Keith Stevens, Abdullah Barhoum, Duc Nguyen, Oliver Stanley, Richárd Nagyfi, et al. Openassistant conversations-democratizing large language model alignment. *Advances in neural information processing systems*, 36: 47669–47681, 2023.

[14] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in neural information processing systems*, 33:9459–9474, 2020.

[15] Yukang Lin, Bingchen Zhong, Shuoran Jiang, Joanna Siebert, and Qingcai Chen. Reasoning graph enhanced exemplars retrieval for in-context learning. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 9737–9759, 2025.

[16] David JC MacKay. Information-based objective functions for active data selection. *Neural computation*, 4 (4):590–604, 1992.

[17] Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, et al. Self-refine: Iterative refinement with self-feedback. *Advances in neural information processing systems*, 36:46534–46594, 2023.

[18] Shengyu Mao, Yong Jiang, Boli Chen, Xiao Li, Peng Wang, Xinyu Wang, Pengjun Xie, Fei Huang, Huajun Chen, and Ningyu Zhang. Rafe: Ranking feedback improves query rewriting for rag. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 884–901, 2024.

[19] George A Miller. Wordnet: a lexical database for english. *Communications of the ACM*, 38(11):39–41, 1995.

[20] Madhur Panwar, Kabir Ahuja, and Navin Goyal. In-context learning through the bayesian prism. In *The Twelfth International Conference on Learning Representations*, 2024.

[21] Ohad Rubin, Jonathan Herzig, and Jonathan Berant. Learning to retrieve prompts for in-context learning. In *Proceedings of the 2022 conference of the North American chapter of the association for computational linguistics: human language technologies*, pages 2655–2671, 2022.

[22] Amrith Setlur, Chirag Nagpal, Adam Fisch, Xinyang Geng, Jacob Eisenstein, Rishabh Agarwal, Alekh Agarwal, Jonathan Berant, and Aviral Kumar. Rewarding progress: Scaling automated process verifiers for llm reasoning. In *The Thirteenth International Conference on Learning Representations*, 2025.

[23] Burr Settles. Active learning literature survey. Technical report, University of Wisconsin-Madison Department of Computer Sciences, 2009.

[24] Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. *Advances in neural information processing systems*, 36:8634–8652, 2023.

[25] Charlie Snell, Jaehoon Lee, Kelvin Xu, and Aviral Kumar. Scaling llm test-time compute optimally can be more effective than scaling parameters for reasoning. In *The Thirteenth International Conference on Learning Representations*, 2025.

[26] Robyn Speer, Joshua Chin, and Catherine Havasi. Conceptnet 5.5: An open multilingual graph of general knowledge. In *Proceedings of the AAAI conference on artificial intelligence*, volume 31, 2017.

[27] Mirac Suzgun, Nathan Scales, Nathanael Schärli, Sebastian Gehrmann, Yi Tay, Hyung Won Chung, Aakanksha Chowdhery, Quoc Le, Ed Chi, Denny Zhou, et al. Challenging big-bench tasks and whether chain-of-thought can solve them. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 13003–13051, 2023.

[28] Siyin Wang, Chao-Han Huck Yang, Ji Wu, and Chao Zhang. Bayesian example selection improves in-context learning for speech, text and visual modalities. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 20812–20828, 2024.

[29] Orion Weller, Benjamin Chang, Sean MacAvaney, Kyle Lo, Arman Cohan, Benjamin Van Durme, Dawn Lawrie, and Luca Soldaini. Followir: Evaluating and teaching information retrieval models to follow instructions. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 11926–11942, 2025.

[30] Xinran Zhao, Tong Chen, Sihao Chen, Hongming Zhang, and Tongshuang Wu. Beyond relevance: Evaluate and improve retrievers on perspective awareness. In *Proceedings of the First Conference on Language Modeling*, 2024.

A Additional Algorithmic Details

Algorithm in words. Given an input x, a candidate pool $\mathcal{Z}$, and a criterion library $\mathcal{A}$, BASIS initializes a prior $p_0(z, a)$. At every interaction round it scores probe candidates under each criterion, estimates the mutual information objective in Section 4, chooses the most informative probe, receives weak feedback, and performs a Bayesian update. After T rounds it returns a target posterior $p_T(z)$ and a criterion posterior $p_T(a)$ for retrieval, refinement, or steering.

Practical defaults. In all reported experiments we use top-$K = 16$ pruning, $M = 32$ Monte Carlo samples, and a maximum of three interaction rounds on downstream tasks. We found these settings sufficient to capture most of the information-gain benefit while keeping latency low.

B Proofs

Proof of Theorem 1. Fix an incorrect pair $h = (z, a)$ and write

$$\delta_t = s_{a^\star}(q_t, z^\star) - s_a(q_t, z), \qquad S_T(h) = \sum_{t=1}^{T} \frac{\delta_t^2}{2\sigma^2}.$$

The log-likelihood ratio of the true pair to h is

$$\Lambda_T(h) = S_T(h) + M_T(h), \qquad M_T(h) = \sum_{t=1}^{T} \frac{\delta_t \epsilon_t}{\sigma^2}.$$

Because each probe is selected from past observations and the Gaussian noise is independent, for any $\lambda \in (0, 1)$ the process $\exp(-\lambda M_T - \lambda^2 S_T)$ has expectation one. At $\lambda = 1/4$, Markov's inequality gives

$$\Pr\big(M_T \le -S_T/2,\ S_T \ge s_0\big) \le e^{-s_0/16}.$$

Assumption 4 implies $S_T(h) \ge s_0 = m_T\Delta^2/(2\sigma^2)$. Thus, except with probability at most $\exp(-m_T\Delta^2/(32\sigma^2))$, we have $\Lambda_T(h) \ge m_T\Delta^2/(4\sigma^2)$. A union bound over the at most $|\mathcal{Z}||\mathcal{A}| - 1$ incorrect pairs shows that this holds for all of them with probability at least $1 - |\mathcal{Z}||\mathcal{A}| \exp(-m_T\Delta^2/(32\sigma^2))$.

Under a uniform prior, posterior odds against the true pair equal the likelihood ratios $\exp(-\Lambda_T(h))$. On the same event, summing these odds gives

$$1 - p_T(z^\star, a^\star) \le |\mathcal{Z}||\mathcal{A}| \exp\big(-m_T\Delta^2/(4\sigma^2)\big)\,.$$

Taking universal constants $C = 32$ and $c = 1/4$ proves the theorem.

Proof of Proposition 1. By assumption, the conditional feedback distributions under $(z^\dagger, \bar{a})$ and $(z^\star, a^\star)$ are identical for every probe. Therefore every adaptive probe policy induces the same distribution over feedback histories under these two explanations, so no test based on that history can distinguish them. A learner restricted to $\bar{a}$ cannot detect that its best-fitting target may be wrong.

Proof of Proposition 2. For any fixed weights, the score difference between z^+ and z^- on x_1 is $\Delta(w_{a_1} - w_{a_2})$, while on x_2 it is $-\Delta(w_{a_1} - w_{a_2})$. These differences cannot both be strictly positive. Instance-dependent weights concentrated on a_1 for x_1 and a_2 for x_2 make both differences positive, proving the claim.

Proof of Proposition 3. The identity follows from the definition of conditional mutual information:

$$I\big((z, a); y \mid q, \mathcal{D}_t\big) = H\big(p_t(z, a)\big) - \mathbb{E}_y H\big(p_{t+1}(z, a \mid q, y)\big). \tag{20}$$

Therefore, maximizing expected entropy reduction is equivalent to maximizing one-step information gain.

C Additional Experimental Details

Table 6: Three domains used to instantiate the same latent-criterion inference problem.

Task	Candidate space $\mathcal{Z}$	Probe type q_t	Latent criteria $\mathcal{A}$	Weak feedback
Concept recovery	lexical concepts with relation-based distractors	single concept or pairwise query	semantic, relation, part–whole, morphology, association	scalar score or pairwise preference
Exemplar selection	exemplar bank from training problems	single exemplar or exemplar pair	semantic, lexical, entity, structural, answer-consistency	verifier delta, structural critic, pairwise preference
Response refinement	candidate responses for one instruction	response or response pair	helpfulness, specificity, conciseness, safety, empathy, formality	preference label or rubric score

Table 7: Feedback sources used in each task. These signals are holistic weak judgments: they do not reveal the hidden criterion label, and they are available to every non-oracle method that uses external feedback.

Task	Feedback type	Source	Form	Shared with non-oracle baselines?
Concept recovery	scalar similarity / pairwise preference	simulated from the hidden criterion with Gaussian or Bradley–Terry noise	scalar / pairwise	yes
Reasoning exemplar selection	verifier delta	downstream answer verifier applied to candidate exemplars or prompted traces	scalar	yes
Reasoning exemplar selection	structural signal	template overlap or structural critic score computed from reasoning skeletons	scalar	yes
Response refinement	preference feedback	dataset preference label when available, otherwise rubric-based weak supervision	pairwise / scalar	yes

Feedback and criterion transparency. Except for the diagnostic oracle-criterion upper bound, no method observes the hidden feedback-generating criterion directly. Feedback is a weak scalar, binary, or pairwise judgment about a probe or candidate. In reasoning, the oracle emits holistic verifier or critic scores rather than labels such as "structure" or "style."

Concept recovery protocol. Each episode samples one hidden target, five semantically close distractors, five relation-linked distractors, five morphological distractors, and random negatives until the pool size reaches 50. We report averages over 500 episodes and five seeds. For pairwise feedback we set $\beta = 10$, for scalar feedback we normalize scores to $[0, 1]$.

Reasoning exemplar selection protocol. We evaluate 500 GSM8K items, 500 StrategyQA items, and 750 BBH items (250 per task). Candidate pools contain 64 exemplars, with an initial dense shortlist of 32. The final prompt includes the top four exemplars. For BBH, candidates are drawn from other labeled benchmark items, excluding the current query and items that share its underlying scenario. All methods use identical candidate pools, and the query's gold answer is used only for final evaluation. Structural similarity is computed from automatically extracted reasoning templates based on operator sequences, decomposition markers, and answer format. Exact-match or task-specific correctness is used as the end metric. For the distractor split, eight semantically close but structurally irrelevant exemplars are injected into each candidate pool.

Response refinement protocol. We sample 1,000 prompts per dataset, generate or retrieve eight candidate responses, and run up to three interactive rounds. Preference win rates are measured against the initial response, while attribute matching measures whether the selected response aligns with the hidden preference criterion used to generate weak feedback. The mismatch split augments each pool with topic-matched responses that are deliberately misaligned with the hidden rubric dimension.

Table 8: Implementation of the criterion-conditioned scorers. Scores are computed once for the current candidate pool, normalized to a comparable range, and cached across interaction rounds. Feedback updates posterior weights over criteria rather than recomputing base scores.

Criterion	Implementation	Normalization	External model?	Updated after feedback?
Semantic	cosine similarity in the frozen encoder space	pool-wise min–max to $[0, 1]$	no	no
Lexical	BM25 or token-overlap relevance	pool-wise min–max to $[0, 1]$	no	no
Entity	overlap F1 over entities, slots, or variables	native $[0, 1]$ score	no	no
Structural	overlap between extracted reasoning templates, operator sequences, or decomposition graphs	pool-wise min–max to $[0, 1]$	optional critic	no
Style	lightweight rubric classifier or rubric score for tone, conciseness, empathy, or formality	affine calibration to $[0, 1]$ on a development split	optional	no
Answer-consistency	verifier pass rate for the exemplar's supplied answer to its own question	binary or calibrated scalar in $[0, 1]$	yes	no

Criterion scorer implementation. Static mixtures, the oracle-criterion diagnostic, and BASIS all use the same criterion-conditioned scores from Table 8. The methods differ in whether weights are fixed, oracle-specified, or inferred online. Structural similarity in reasoning is extracted from automatically derived reasoning templates. Style scores in refinement are calibrated on a held-out split so that no single rubric dimension dominates by scale alone.

Static mixtures and stronger rerankers. Uniform mixtures use $w_a = 1/|\mathcal{A}|$. Validation-tuned mixtures optimize one weight vector on a held-out development set of 200 examples per domain, then freeze it for all test items. The rubric-guided LLM reranker receives explicit criterion descriptions and must justify criterion-level scores before producing a final ranking. It sees the same candidate pool as BASIS but not its interaction history or posterior state.

Best-of-N and oracle-criterion baselines. Best-of-N verifier selection scores candidates from the same pool under the same verifier or rubric signal and returns the top-scoring candidate. It uses $N = 4$ calls for reasoning and $N = 6$ for refinement, at least the $T = 3$ feedback calls used by BASIS. The oracle-criterion baseline uses the hidden feedback-generating criterion only at evaluation time and shares the candidate pool, prompt budget, and backbone, which is a diagnostic upper bound.

Table 9: Information access and additional interaction calls. Call counts begin after the shared criterion-scoring cache has been built. We count verifier, critic, and LLM-judge calls as additional interaction calls. Posterior updates and Monte Carlo probe evaluation are local operations.

Method	Same pool	Same criterion scores	Feedback history	Additional interaction calls
Static mixture	yes	yes	no	0
Rubric-guided LLM reranker	yes	rubric or criterion descriptions	no	1
Best-of-N verifier	yes	verifier only	no	N
BASIS	yes	yes	yes	T
Oracle-criterion	yes	yes + true criterion	no	0

Compute and information access. Table 9 summarizes what each method can observe and the additional calls it makes after the shared criterion-scoring cache has been built. Criterion scores, including verifier-based answer consistency, are computed once per pool before interaction and their one-time cost is included in preprocessing below. Posterior updates and Monte Carlo probe evaluation are local operations, reported separately as wall-clock overhead.

Criterion slices and query efficiency. For slice-wise analysis, we assign each example the criterion whose score best predicts downstream success on its held-out candidate set. For concept recovery, the hidden criterion is known by construction. These labels are used only for post-hoc diagnosis, not as input to any method or for hyperparameter tuning. Slice-wise results normalize each task to its clean-split score before averaging. Query efficiency is the mean round at which a method first reaches 90% of its final Success@1 rate measured after 12 probes.

Statistical significance. Results average five seeds. The $\pm$ values in the concept-recovery table are standard deviations across seeds, and those in the main latency table are standard deviations across the 100 timed items. We use 10,000 paired bootstrap replicates at the test-item level and keep all seed outcomes for each item in the same cluster. For task-level macro-averages, items are resampled within each task, task means are recomputed, and then averaged with equal task weights. The main text reports paired intervals for the primary downstream comparisons.

Compute resources. All experiments run on one A100-80GB GPU with 16 CPU cores. Generation and verifier calls are served with vLLM at batch size 16, which gives roughly a 6$\times$ throughput gain over the batch-size-one latencies reported in Table 1. We report costs per configuration (one method, one seed, all test items) so totals can be reconstructed from Table 1. One-time preprocessing, shared by every method, takes about 2 GPU-hours for reasoning (candidate-pool embedding, lexical/entity/structural scores, and one verifier pass over the exemplar bank for answer consistency) and about 3 GPU-hours for refinement (eight candidate responses per prompt, mismatch-split responses, and rubric scores). A feedback-based reasoning configuration takes about 3 GPU-hours and a static one about 2. Across 16 and 14 configurations, respectively, this is about 76 GPU-hours. A feedback-based refinement configuration takes about 6 GPU-hours and a static one about 4. Across 14 and 8

configurations, respectively, this is about 116 GPU-hours. Concept recovery is CPU-only and takes under one hour per sweep. The reported experiments therefore use about 197 GPU-hours, or roughly 200. Including development-split hyperparameter selection and preliminary runs not reported here, the project used roughly 300 GPU-hours.

Latency measurement. End-to-end timing uses 100 items at batch size one after five warm-up runs on one A100-80GB GPU and 16 CPU cores. Reasoning time includes final answer generation. Refinement starts from the same eight candidate responses for every method and includes scoring, feedback, and selection. The local scaling benchmark starts from cached candidate representations and criterion-conditioned scores, so it excludes their one-time construction and first-stage retrieval.

D Additional Result Tables

Two-stage diagnostic set. For the two-stage analysis, we separately sampled 50 items from each of GSM8K, StrategyQA, BBH logical deduction, BBH date understanding, and BBH causal judgement using seed 31. This 250-item diagnostic set is separate from the main reasoning evaluation. All five evaluation seeds were retained.

Table 10 reports controlled recovery across probe budgets. Table 11 and Table 12 provide the per-task outcomes behind the main-text averages, and Table 13 isolates the contribution of key components.

Table 10: Controlled concept recovery over 500 episodes. Entries are mean $\pm$ SD over five seeds. S@1@k is Success@1 after k probes, Criterion acc. is hidden-criterion identification accuracy, Q@90 is the mean number of probes required to reach 90% of the final Success@1 rate after 12 probes.

Method	S@1@4	S@1@6	Criterion acc.	Q@90↓
Random probing	17.9 ± 0.8	24.1 ± 0.9	—	9.8 ± 0.2
Greedy semantic NN	35.2 ± 1.1	43.1 ± 0.9	—	7.7 ± 0.2
Target-only Bayes	43.8 ± 0.8	51.9 ± 0.8	—	6.8 ± 0.1
Static mix (val-tuned)	47.6 ± 0.8	56.0 ± 0.7	—	6.5 ± 0.1
Active, no criterion	47.1 ± 0.7	55.6 ± 0.7	—	6.2 ± 0.1
BASIS	59.8 ± 0.7	68.1 ± 0.6	80.9 ± 0.8	4.6 ± 0.1
Oracle-criterion	69.7 ± 0.6	79.5 ± 0.5	100.0	4.0 ± 0.1

Table 11: Full reasoning exemplar-selection results. The average is the equal-weight macro-average across the three task columns. Entries are means over five seeds.

Method	GSM8K	StrategyQA	BBH (3 tasks)	Avg.
Random exemplars	65.3	67.1	56.2	62.9
BM25	70.6	71.3	60.4	67.4
Dense retrieval	73.1	73.8	63.1	70.0
ByCS-style Bayesian selection	73.5	74.2	63.7	70.5
RGER-style structural retrieval	74.4	75.1	65.0	71.5
LLM reranker	74.7	74.8	64.6	71.4
Rubric-guided LLM reranker	75.0	75.5	65.6	72.0
Static mix (uniform)	74.8	75.0	65.3	71.7
Static mix (val-tuned)	75.3	75.6	65.9	72.3
Best-of-4 verifier	75.1	75.4	65.8	72.1
BASIS ($T = 3$)	**76.2**	**76.5**	**66.7**	**73.1**
Oracle-criterion	77.8	78.0	69.2	75.0

Across the reasoning tasks, BASIS exceeds the tuned mixture in each column, while the oracle-criterion results show remaining headroom. The aggregate gain is modest, consistent with the main-text uncertainty interval.

Table 12: Full response-refinement results. Entries are means over five seeds. Attribute match measures agreement between the selected response and the hidden preference criterion.

Method	HH win	OASST win	UF win	Avg.	Attribute match
Direct preference ranker	57.4	55.9	60.1	57.8	62.9
LLM-as-judge reranking	58.3	57.1	60.5	58.6	63.8
Self-Refine	59.8	58.2	61.4	59.8	64.6
Target-only Bayes	60.7	59.4	62.0	60.7	65.1
Rubric-guided LLM reranker	60.4	58.9	62.3	60.5	65.5
Static mix (uniform)	60.8	59.1	62.7	60.9	66.0
Static mix (val-tuned)	61.3	59.8	63.2	61.4	66.6
Best-of-6 verifier	61.0	59.6	63.0	61.2	66.3
BASIS	**63.9**	**61.8**	**65.6**	**63.8**	**69.3**
Oracle-criterion	66.1	63.7	67.5	65.8	72.4

For refinement, the gains over the tuned mixture are present on all three datasets. Attribute match also rises from 66.6% to 69.3%, indicating closer alignment with the preference criterion used for evaluation.

Table 13: Ablations across tasks. Concept S@1@6 is from concept recovery. Reason Avg and Refine Win are the averages from Tables 11 and 12. Distr. Drop is the robustness drop under distractors.

Variant	Concept S@1@6	Reason Avg	Refine Win	Distr. Drop↓
BASIS	**68.1**	**73.1**	**63.8**	**4.9**
No latent criterion	51.9	70.9	60.7	8.8
No active probing	61.7	72.0	62.4	6.6
Uniform static mixture	54.8	71.7	60.9	6.9
Single semantic criterion	43.1	68.9	57.9	10.8

The ablations in Table 13 show the largest losses when the criterion library is reduced to a single semantic score. Removing active probing also lowers performance across the reported tasks. They separate adaptive criterion inference from a fixed similarity choice.

E Qualitative Case Details

Figure 4 gives the full GSM8K trace behind the state-transition example discussed in Section 8.

Query (GSM8K). Walter buys 60 apples, eats $2/5$, gives away 25% of the remainder, and sells what remains for \$3 per apple. The correct state sequence is $60 \to 36 \to 27$, giving \$81.

Tuned-mixture-only exemplar. In the Kelvin–Samuel problem, Samuel first receives $3/4$ of \$240, then spends $1/5$ of the original \$240. Its answer is \$132: the second fraction uses the original total.

BASIS-only exemplar. In the fixer-and-nails problem, 30% of 400 nails are used, then 70% of the remainder is used. This gives $400 \to 280 \to 84$ and uses the updated remainder as the second reference quantity.

Selection and feedback. The methods share three of four exemplars. The tuned mixture returns \$63 on the query; BASIS returns the gold answer, \$81. Across three rounds, verifier-score differences for the two candidates are $+0.037$ and $+0.412$. The final Bradley–Terry comparison favors the fixer with posterior-predictive probability 0.781. The structural-criterion posterior is 0.184 after the first feedback observation and 0.463 after the final comparison, becoming the largest criterion marginal.

Figure 4: Sequential-fraction case. The selected exemplar differs in whether the second fraction is applied to the original total or the updated remainder.

F Existing Assets and Licenses

We use the third-party data and model releases below, crediting their creators in the text and references. Tables 14 and 15 identify the named release or repository, its stated license or source terms, and an upstream source. The model identifiers match those in Section 6. No third-party dataset files or model weights are redistributed with this paper.

Table 14: Data assets, release identifiers, and source-stated licenses or terms.

Asset / release	License or terms	Upstream source
WordNet 3.0 [19]	Princeton WordNet License; use, copying, modification, and distribution are permitted with the required copyright notice and disclaimer.	WordNet license
ConceptNet 5.7 [26]	Data: CC BY-SA 4.0. The repository distinguishes the graph-data license from the Apache 2.0 code license.	License / data credits
SimLex-999, original English release [12]	The official download page requests citation but does not state a separate dataset license. No SimLex files are reproduced or redistributed here.	SimLex project page
WordSimilarity-353 v1.0 (2002) [9]	Creative Commons Attribution 4.0 International (CC BY 4.0); cite the original collection.	WordSim-353 source and license
GSM8K, official 2021 release [6]	MIT License.	OpenAI repository license
StrategyQA, official 2021 release [10]	MIT License, as stated in the dataset repository.	StrategyQA repository license
BIG-Bench Hard: logical deduction, date understanding, causal judgement [27]	MIT License, as stated in the benchmark repository.	BBH repository license
HH-RLHF, Anthropic public release [2]	MIT License, as stated in the dataset release.	HH-RLHF dataset card
OpenAssistant OASST1 [13]	Apache License 2.0, as stated on the dataset card.	OASST1 dataset card
UltraFeedback, OpenBMB release [7]	Dataset repository declares the MIT License; source-component terms continue to apply to material originating in third-party datasets.	UltraFeedback dataset card

Table 15: Model checkpoints and their published license identifiers.

Model identifier	License	Upstream model card
Qwen/Qwen3-Embedding-4B	Apache License 2.0	Qwen model card
Qwen/Qwen3-8B	Apache License 2.0	Qwen model card
mistralai/Ministral-3-14B-Reasoning-2512	Apache License 2.0	Mistral model card

We follow the stated attribution and notice requirements; no raw third-party assets or model weights are redistributed. ConceptNet attribution follows its upstream data credits. The SimLex-999 release requests citation but states no separate data license; no SimLex files are reproduced or redistributed. Immutable hosted-repository revisions are not recorded.

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: See the abstract and Sections 1, 4, 5, and 7. The manuscript states its contributions, assumptions, and scope, and aligns the claims with the tasks described in the paper.

   Guidelines:

   - The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: Section 9 discusses criterion coverage, feedback-model mismatch, inference-time cost, and misuse risks, and Section 8 describes concrete failure modes.

   Guidelines:

   - The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [Yes]

Justification: Section 5 states the assumptions and theorem statements, and Appendix B provides proofs for the main theorem and propositions.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: Sections 6 and 7 specify datasets, tasks, baselines, budgets, metrics, and aggregation, and Appendix C gives candidate construction, criterion libraries, hyperparameters, and compute details.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
  (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
  (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
  (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
  (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [No]

   Justification: The manuscript uses public benchmarks and describes the method and experimental setup, but it does not include a public code or data repository.

   Guidelines:

   - The answer [N/A] means that paper does not include experiments requiring code.
   - Please see the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
   - The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
   - The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
   - At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
   - Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes]

   Justification: The method is training-free, and Section 6 plus Appendix C specify data construction, candidate pools, priors, hyperparameters, feedback models, stopping rules, and evaluation budgets.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [Yes]

   Justification: Section 6 reports results over five seeds. The main text gives paired item-clustered confidence intervals for primary comparisons, and Appendix C specifies the bootstrap procedure.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.

- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: Appendix C reports the GPU/CPU setup, per-configuration compute, approximately 200 GPU-hours for reported experiments, and roughly 300 GPU-hours for the project including development and preliminary runs.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: The study evaluates inference-time selection on public benchmarks, involves no new participant recruitment or data collection, and discusses deployment risks in Section 9.

   Guidelines:

   - The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
   - The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [Yes]

    Justification: Section 9 discusses both the reliability benefits of better task-aligned similarity and the risks of manipulative preference inference or personalization.

Guidelines:

- The answer [N/A] means that there is no societal impact of the work performed.
- If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [N/A]

    Justification: The paper releases no foundation model, scraped dataset, or other high-risk generative asset. It studies an inference-time selection and reranking procedure.

    Guidelines:

    - The answer [N/A] means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
    - Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
    - We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: [Yes]

    Justification: Appendix F identifies the named datasets and model releases, cites their creators, links to the source-stated licenses or terms, and records when the SimLex-999 source does not state a separate dataset license. No third-party data or model weights are redistributed.

    Guidelines:

    - The answer [N/A] means that the paper does not use existing assets.
    - The authors should cite the original paper that produced the code package or dataset.

- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [N/A]

    Justification: The paper does not introduce or release a new dataset, model, or code asset.

    Guidelines:

    - The answer [N/A] means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.
    - At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [N/A]

    Justification: The study conducts no new crowdsourcing, participant recruitment, or data collection. It reuses public datasets.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
    - According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A]

    Justification: The study conducts no direct interaction with human participants or new human-subject data collection; it reuses public benchmark data.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

    Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

    Answer: [Yes]

    Justification: Sections 4 and 6, together with Appendix C, describe the use of frozen LLM critics and LLM-based evaluation as part of the method and experimental setup.

    Guidelines:

    - The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
    - Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.