arXiv:2610.35721v1 [cs.LG] 26 Oct 2026

Can JEV Support Clinical Trial Criteria Assessment?

Mengxian He[1], Ziyue Gao[1], Chun Li[2], Shunyi Zhang[2], Hao Wei[1], Minqing Zhang[1], Wu Yuan[1,*]

[1]The Chinese University of Hong Kong [2]Capital Medical University

Emails: {1155231596, 1155233115, haowei, lars.zhang}@link.cuhk.edu.hk, wyuan@cuhk.edu.hk; {15701196285, 18519398200}@163.com

[*]Corresponding author

Abstract

Clinical trial prescreening requires distinguishing unmet conditions from insufficient evidence in patient records. Given patient records, criterion questions, and predefined answer options, we retrospectively compared JEV, a non-generative decision model returning native option probabilities, with schema-constrained Qwen Flash across 2,048 test patient–condition pairs from TrialGPT and question–answer datasets derived from MIMIC-III and MIMIC-IV, all evaluated under strict **Zero Data Retention (ZDR)** policies to ensure clinical data privacy. Both models assessed conditions individually or in batches sharing the same patient context, with performance measured against reference labels. In batch mode, JEV and Qwen achieved similar macro-F1 scores on TrialGPT (0.652 vs. 0.660) and MIMIC-IV (0.807 vs. 0.814), whereas JEV substantially outperformed Qwen on MIMIC-III (0.768 vs. 0.534; $\Delta = +0.234$, 95% CI: 0.187–0.281). This advantage largely reflected higher recall for conditions labeled as having insufficient information (56.3% vs. 9.9%). Across all three datasets, JEV also had lower observed median job latency (1.18–1.40 vs. 2.80–8.90 s) and 53%–74% lower estimated cost per condition. These findings position JEV as an initial assessment component that provides criterion-level judgments and flags potential information gaps for review. JEV's observed errors in interpreting clinical evidence underscore the need to verify its outputs against patient records before they inform eligibility decisions.

1 Introduction

Clinical trial prescreening requires assessing patient records against individual inclusion and exclusion criteria [2]. A useful initial assessment must distinguish whether a condition is clearly unmet or simply lacks sufficient evidence in the record. This judgment depends on interpreting clinical statements in context, including their negation and timing [1]. For example, a documented symptom may leave a criterion unresolved if its required duration is not recorded. The task is therefore to produce criterion-level judgments that preserve potential information gaps for subsequent review.

Generative large language models (LLMs) have been applied to this task. TrialGPT produces criterion-level eligibility predictions together with explanations and relevant sentence locations in patient notes [2]. Related work has used synthetic data distillation to train smaller LLMs for clinical information extraction, including trial-related questions [9]. These studies motivate evaluating models in terms of both the correctness of their judgments, the latency and cost of obtaining them. For an initial assessment with predefined answer options, non-generative decision modeling provides an alternative approach to examine.

JEV is a non-generative decision model that takes a text context, natural-language questions, and predefined answer options as input and returns selected labels with native options probabilities [4–6].



Figure 1: Proposed role of JEV in clinical trial prescreening. (a) Reviewers assess the patient record against individual inclusion and exclusion criteria and document their judgments. (b) JEV assesses criteria sharing the same patient context in a batch, returning provisional labels and native option probabilities. Clinicians verify these judgments against the patient record and follow up on potential information gaps before making a screening decision.

In criterion assessment, the context is the patient record, each question specifies a clinical condition, and the options define the permitted assessment labels. Multiple questions can share the same patient context [4]. Figure 1 illustrates JEV's proposed role in initial assessment before evidence verification and final screening. Because generative models can also return schema-constrained labels, the relevant question is how JEV compares in classification performance, handling of insufficient evidence, and service latency and cost.

We retrospectively compare JEV with schema-constrained Qwen Flash on 2,048 test patient-condition pairs form TrialGPT and two question-answer resources derived from MIMIC-III and MIMIC-IV [2, 7, 8]. Both models receive the same patient records, criterion questions, and label definitions, with conditions assessed individually or in batches sharing a patient context. We retain source-specific reference conventions and report performance separately for each dataset. The evaluation combines classification performance with observed job latency and estimated cost per condition. Directional error analysis and representative cases help interpret the aggregate comparison; native probability diagnostics separately assess JEV's reported confidence.

2 Clinical Scenario and Model Interfaces

2.1 Criterion-level assessment

We evaluate initial criterion assessment: given a patient record, a condition question, and predefined answer options, a model assigns a label to the patient–condition pair. Here, a condition refers to either a trial criterion or a clinical question adapted for screening. The permitted labels describe whether the stated condition holds, does not hold, remains unresolved, or does not apply (Table 1). For an exclusion criterion, MET indicates that the disqualifying condition holds. Figure 1 places these judgments before clinical verification; the present evaluation scores model outputs against source-derived reference labels without clinician revision.

Table 1: Each label refers to the literal condition, including its qualifiers and the source annotation policy. INSUFFICIENT describes the available evidence, which is not assigned by applying a threshold to model confidence.

Label	Meaning
MET	The stated condition holds for the patient.
NOT_MET	The stated condition does not hold under the specified policy.
INSUFFICIENT	Required information is missing or unresolved under that policy.
NOT_APPLICABLE	The criterion does not apply to the patient or situation; TrialGPT only.

2.2 JEV: native decisions and option probabilities

JEV is a non-generative decision model accessed through TypeSafe's text Choice application programming interface (API). We evaluated the fixed model version jev-1.14.0. The patient record is supplied as a shared text state, while each question specifies a clinical condition, its assessment policy, and the permitted labels with their descriptions. For each question, the API returns a selected label, a probability distribution over the permitted labels, and a derived confidence score. It does not generate an explanatory rationale. The evaluation characterizes this exposed interface; the underlying architecture and training procedure were not accessible.

For $K > 1$ permitted labels, let p_k denote the returned probability of label k. The documented confidence score is

$$c = \frac{\max_k p_k - 1/K}{1 - 1/K}. \tag{1}$$

For a fixed label set, this score is an affine rescaling of the maximum option probability. The probability diagnostics in Section 4.3 use the returned probability vector and the selected-label probability, rather than this derived confidence score.

2.3 Qwen: schema-constrained label generation

The comparator is Qwen Flash, accessed through the hosted API alias qwen3.8-flash. It receives the same patient text, question-level assessment policies, and label descriptions through a chat interface. A strict response schema requires a JavaScript Object Notation (JSON) object containing an ordered answers array, with one condition identifier and permitted label per item. No explanation is requested in the final response. Both models therefore return structured assessment labels; no comparable native class-probability vectors were recorded for Qwen.

The primary Qwen comparisons disable thinking. A separate Batch experiment compares thinking off and on under a matched completion budget, as specified in Section 4.1. Evaluation focuses on final labels and resource use.

2.4 Single and Batch requests

A patient–condition pair is the unit of classification. A job comprises the conditions associated with one patient–trial pair or one source record and may contain one or more conditions. Single mode submits each condition in a separate request, repeating the patient context across requests. Batch mode submits the questions within a job together in one request, using a shared patient context. The evaluation does not pass model answers into subsequent requests.

Both modes produce one label per condition. Classification performance is measured at the condition level, while job latency measures the time required to complete assessment of the condition group (Section 4.5). For a job containing only one condition, both modes submit one question; opportunities for context reuse therefore depend on job composition.

3 Benchmarks and Data Standardization

3.1 Source tasks and retained conditions

We adapted criterion annotations from TrialGPT and two clinical question–answer resources derived from MIMIC-III and MIMIC-IV [2, 3, 7–9]. We refer to the adapted question–answer tasks as MIMIC-III and MIMIC-IV throughout the paper. Figure 2 summarizes the source collections, selection rules, and retained conditions.

TrialGPT. The SIGIR criterion-annotation sample contains 1,015 patient–criterion pairs across 53 patient groups and 105 patient–trial pairs [2]. It combines largely synthetic patient summaries with trial-derived criteria. We excluded one row with empty criterion text, leaving 1,014 conditions. The four source label categories were retained through the mapping in Table 2.

MIMIC-III clinical-trial questions. MIMIC-III (version 1.0.0) Version 1.0.0 contains 1,000 model-generated, human-reviewed question–answer pairs based on MIMIC-III clinical notes. We retained 532 Boolean questions, including questions annotated as unanswerable from the note. The remaining 468 numerical questions were excluded because no verified threshold was available for their conversion to Boolean conditions in this evaluation.

MIMIC-IV apixaban questions. MIMIC-IV (Version 1.0.0) contains 2,300 manually annotated question–answer pairs from 100 records, with 15 Boolean and eight numerical questions per record (Table 13). We retained all 1,500 Boolean questions and derived 89 conditions asking whether the lowest recorded left ventricular ejection fraction (LVEF) was $\leq$40%. These comprised 37 numerical references within the retained 0–55% range and 52 references indicating unavailable information. The source instructions cap reported LVEF answers at 55%. One LVEF entry marked as available but containing a blank answer, and ten numerical references outside the capped range, were excluded. The other 700 numerical questions were excluded because no verified conversion rule was available, yielding 711 exclusions and 1,589 retained conditions.



Figure 2: TrialGPT retains 1,014 of 1,015 source patient–criterion pairs after exclusion of one empty criterion. MIMIC-III retains 532 Boolean questions from 1,000 source pairs. MIMIC-IV retains 1,500 Boolean questions and 89 derived LVEF conditions, comprising 37 retained numerical references and 52 references indicating unavailable information.

3.2 Reference-label mapping and interpretation

Source references were mapped to the assessment labels in Table 3 using the rules in Table 2. This mapping standardizes label names while preserving each source's policy for interpreting missing information.

The TrialGPT policy permits clinically supported inferences, including some context-dependent inferences from absence of documentation. It does not assign all omitted facts to either NOT_MET or INSUFFICIENT. MIMIC questions retain their specified subject, temporal scope, numerical boundary, and explicit default rules. Both models use the frozen comma-separated values (CSV) question wording and the corresponding assessment policy (Appendix A.6). Differences between that wording and auxiliary source instructions are considered in the error analysis without changing the reference labels after observing predictions.

Primary analyses retain four classes for TrialGPT and three for the MIMIC tasks, preserving the distinction between definite judgments and insufficient information.

3.3 Grouping and retained partitions

The standardized collection contains 3,135 conditions across 734 jobs: 664 development conditions, 2,048 primary test conditions, and 423 conditions in the retained confirmation partitions (Table 3). We retained the existing partition assignments. The main analyses use 774 TrialGPT, 322 MIMIC-III, and 952 MIMIC-IV test conditions; results for the other partitions are reported in Appendix A.1.

Table 2: Source-to-reference transformations. Labels describe the stated condition; they do not encode final trial eligibility. The LVEF reference range reflects the source response convention and the retained construction rules.

Source	Retained reference	Mapping or boundary
TrialGPT inclusion	included; not included	MET; NOT_MET
TrialGPT exclusion	excluded; not excluded	MET; NOT_MET
TrialGPT, either type	not enough information; not applicable	INSUFFICIENT; NOT_APPLICABLE
MIMIC Boolean	Available Yes or No	MET or NOT_MET; preserve source defaults
MIMIC missing answer	Source unavailable flag and blank answer	INSUFFICIENT; inconsistent availability/answer pairs excluded
MIMIC-IV LVEF	Comparable lowest recorded value v in percent	MET if $v \leq 40$; NOT_MET otherwise. Source-valid capped range: $0 \leq v \leq 55$.
Other numerical questions	No verified threshold, unit, or usable reference	Excluded; no invented decision boundary

Table 3: Standardized collection and retained partitions. Group counts are summed within datasets and do not represent a deduplicated count of people across sources.

Track	Groups	Jobs	Total	Dev	Test	Confirmation
TrialGPT	53	105	1,014	240	774	0
MIMIC-III	522	529	532	105	322	105
MIMIC-IV	100	100	1,589	319	952	318
Total	675	734	3,135	664	2,048	423

Job composition and label prevalence differ across the datasets. In the full MIMIC-III collection, 526 of 529 jobs contain one condition and three contain two, leaving limited opportunity for sharing context across multiple questions. MIMIC-IV draws on 16 recurring question families, and all 30 test references labeled INSUFFICIENT arise from the derived LVEF question. Its insufficient-information results therefore describe performance on this specific question family.

Table 4: Composition of the primary test partitions. M, N, U, and A denote MET, NOT_MET, INSUFFICIENT, and NOT_APPLICABLE, respectively.

Track	Groups	Jobs	Conditions	M	N	U	A
TrialGPT	43	85	774	129	366	243	36
MIMIC-III	314	319	322	83	97	142	–
MIMIC-IV	60	60	952	255	667	30	–

4 Evaluation Protocol

4.1 Comparison and execution

We evaluated four primary modes: JEV Single, JEV Batch, Qwen Single, and Qwen Batch. Each mode used the same frozen patient text, question-level assessment policies, and label descriptions, rendered through the corresponding model interface. Qwen additionally received the response-format instruction described in Section 2.3. Figure 3 summarizes the evaluation design, and Table 6 reports

the execution settings. Raw responses, status, token usage, and request- and job-level timing were recorded for subsequent analysis.

The primary Qwen disabled thinking and used a 4,096-token completion limit. A separate Qwen Batch experiment compared thinking off and on under a shared limit of 8,192 completion tokens, including reasoning and final output.



Figure 3: Benchmark evaluation pipeline.

5 Comparative Results

5.1 Overall criterion-level quality

Table 5 and Figure 4 show the primary test results. JEV Single achieves macro-F1 of 0.646, 0.771, and 0.808 on TrialGPT, MIMIC-III, and MIMIC-IV, respectively. Qwen Single achieves 0.645, 0.523, and 0.732. The large MIMIC-III difference persists in Batch mode, whereas the Batch scores are close on TrialGPT and MIMIC-IV. A single overall ranking would obscure these dataset- and configuration-dependent results.

Paired JEV-minus-Qwen macro-F1 differences are 24.89 points for MIMIC-III Single (95% interval 20.16 to 29.62) and 23.42 points for Batch (18.73 to 28.05). On TrialGPT, the corresponding differences are 0.05 and −0.81 points, with both intervals including zero. MIMIC-IV differs by 7.66 points in Single (1.82 to 13.39) but −0.65 in Batch (−4.24 to 2.92). Full paired intervals and correction/damage counts are provided in the supplement.

5.2 Single versus Batch

For JEV, switching from Single to Batch changes the number of correct test decisions by +5, −1, and +1 across the three datasets. Macro-F1 changes by +0.64, −0.33, and −0.10 points; all three paired intervals include zero. Qwen Batch has +15, +5, and +21 net correct decisions, with

Table 5: Primary historical test results under the native label spaces. Macro-F1 and accuracy are on $[0, 1]$. The 95% descriptive intervals use grouped bootstrap resampling.

Dataset	Mode	n	Accuracy	Macro-F1	95% CI	Failed
TrialGPT	JEV Single	774	0.720	0.646	[0.594, 0.693]	1
TrialGPT	JEV Batch	774	0.726	0.652	[0.601, 0.702]	0
TrialGPT	Qwen Single	774	0.730	0.645	[0.590, 0.699]	0
TrialGPT	Qwen Batch	774	0.749	0.660	[0.602, 0.714]	0
MIMIC-III	JEV Single	322	0.758	0.771	[0.728, 0.812]	0
MIMIC-III	JEV Batch	322	0.755	0.768	[0.724, 0.811]	1
MIMIC-III	Qwen Single	322	0.547	0.523	[0.478, 0.565]	0
MIMIC-III	Qwen Batch	322	0.562	0.534	[0.489, 0.578]	0
MIMIC-IV	JEV Single	952	0.909	0.808	[0.766, 0.851]	4
MIMIC-IV	JEV Batch	952	0.910	0.807	[0.767, 0.846]	0
MIMIC-IV	Qwen Single	952	0.895	0.732	[0.673, 0.786]	1
MIMIC-IV	Qwen Batch	952	0.917	0.814	[0.774, 0.851]	0

Table 6: Separate test-only Qwen Batch thinking comparison. Paired F1 differences are in percentage points.

Dataset	n	Off F1	On F1	Δ F1 (pp)	95% CI (pp)
TrialGPT	774	0.677	0.701	+2.39	[-1.50, +6.74]
MIMIC-III	322	0.531	0.560	+2.95	[-1.57, +7.35]
MIMIC-IV	952	0.827	0.798	-2.89	[-6.10, +0.11]

macro-F1 changes of +1.50, +1.14, and +8.22 points. These additional Qwen Single–Batch counts are descriptive paired results; no new interval is assigned to that contrast.

A net gain does not imply that every changed answer improved. On MIMIC-IV, Qwen Batch corrects 48 Single errors but introduces 27 errors on previously correct conditions. Thirteen of the corrections occur among the 30 reference-unknown conditions, with no damages within that class. Request packaging is therefore associated with a marked change in evidence-state classification for Qwen on this track. One saved execution per mode cannot distinguish the effect of accompanying questions from repeated-call variability.

5.3 Thinking under matched settings

Thinking raises macro-F1 point estimates by 2.39 points on TrialGPT and 2.95 points on MIMIC-III, and lowers it by 2.89 points on MIMIC-IV (Table 6). All three paired intervals include zero. Class-specific changes provide a more informative interpretation than a global statement that thinking helps or harms. TrialGPT gains 19 correct labels overall while losing six correct INSUFFICIENT predictions. MIMIC-IV gains one correct answer overall while losing five correct INSUFFICIENT predictions, with no corrections in that class. The latter redistribution explains how accuracy can rise slightly while macro-F1 falls.

The test-only resource comparison in Table 7 uses the same partitions as these quality results. Complete-job median latency rises by factors of 4.30, 2.33, and 3.08 for TrialGPT, MIMIC-III, and MIMIC-IV. Estimated cost ratios are 1.94, 1.20–1.24, and 1.48, respectively. These observations



Figure 4: Macro-F1 comparison on the historical test partitions. TrialGPT uses four classes and the MIMIC tracks three. Error bars denote 95% descriptive group-bootstrap intervals.

Table 7: Matched Qwen thinking resources on the test split only. Cost is the estimated upper bound in USD per 1,000 planned conditions; median latency is seconds per complete timing-valid job.

	Cost / 1,000 (USD)		Median job time (s)	
Dataset	Off	On	Off	On
TrialGPT	0.0645	0.1249	4.45	19.12
MIMIC-III	0.7264	0.8991	2.96	6.90
MIMIC-IV	0.0876	0.1299	8.65	26.66

show the operational cost of the tested thinking setting without demonstrating a uniform quality benefit.

5.4 Cost and job timing

JEV Batch has lower observed job latency and estimated cost than Qwen Batch on all three test tracks. Its median job times are 1.20 versus 4.55 seconds on TrialGPT, 1.18 versus 2.80 seconds on MIMIC-III, and 1.40 versus 8.90 seconds on MIMIC-IV. Estimated upper-bound costs per 1,000 conditions are USD 0.0170 versus 0.0645, 0.2045 versus 0.4314, and 0.0216 versus 0.0684, respectively. Figure 5 places these observations alongside quality; the complete resource table is in Appendix A.

Within JEV, Batch lowers TrialGPT median job time from 8.08 to 1.20 seconds and MIMIC-IV from 18.30 to 1.40 seconds. MIMIC-III changes little, with 322 test conditions distributed across 319 jobs. This pattern is consistent with greater amortization when multiple conditions share a record.



Figure 5: Primary baseline quality versus estimated upper-bound cost (top) and observed median job latency (bottom). Horizontal axes are logarithmic. Filled markers denote Batch and hollow markers Single; sizes only improve visibility at overlapping locations.

Cost superiority is not universal across modes. On MIMIC-IV Single, Qwen's estimated upper-bound cost is USD 0.1987 per 1,000 conditions versus JEV's 0.2057. Across all frozen partitions and both modes, the reference runs contain 6,270 planned outputs per model; estimated total upper bounds are USD 0.6306 for JEV and USD 1.0481 for Qwen. These totals exclude the separate thinking comparison..

6 Conclusion

This retrospective benchmark shows that JEV's native choice interface can produce criterion-level decisions and label probabilities at low observed Batch latency and estimated cost. Its quality advantage is conditional on the task and request configuration: the largest JEV–Qwen difference occurs on MIMIC-III and is concentrated in reference-unknown conditions, while Batch macro-F1 point estimates are close on TrialGPT and MIMIC-IV. Additional Qwen thinking increases resource use without a uniform quality gain in the matched comparison.

References

[1] Henk Harkema, John N. Dowling, Tyler Thornblade, and Wendy W. Chapman. ConText: An algorithm for determining negation, experiencer, and temporal status from clinical reports. *Journal of Biomedical Informatics*, 42(5):839–851, 2009. doi: 10.1016/j.jbi.2009.05.002. URL https://pmc.ncbi.nlm.nih.gov/articles/PMC2757457/.

[2] Qiao Jin, Zifeng Wang, Charalampos S. Floudas, Fangyuan Chen, Changlin Gong, Dara Bracken-Clarke, Elisabetta Xue, Yifan Yang, Jimeng Sun, and Zhiyong Lu. Matching patients to clinical trials with large language models. *Nature Communications*, 15(1):9074, 2024. doi: 10.1038/s41467-024-53081-z. URL https://www.nature.com/articles/s41467-024-53081-z.

[3] Alistair E. W. Johnson, Lucas Bulgarelli, Lu Shen, Alvin Gayles, Ayad Shammout, Steven Horng, Tom J. Pollard, Sicheng Hao, Benjamin Moody, Brian Gow, Li-wei H. Lehman, Leo A. Celi, and Roger G. Mark. MIMIC-IV, a freely accessible electronic health record dataset. *Scientific Data*, 10:1, 2023. doi: 10.1038/s41597-022-01899-x. URL https://www.nature.com/articles/s41597-022-01899-x.

[4] TypeSafe. Choice. Official documentation, 2026. URL https://docs.typesafe.ai/primitives/choice. Accessed October 16, 2026; online documentation.

[5] TypeSafe. Confidence. Official documentation, 2026. URL https://docs.typesafe.ai/confidence. Accessed October 16, 2026; online documentation.

[6] TypeSafe. Models. Official documentation, 2026. URL https://docs.typesafe.ai/models. Accessed October 16, 2026; includes model ID jev-1.14.0 and release date October 14, 2026.

[7] Elizabeth Woo, Michael Craig Burkhart, Emily Alsentzer, and Brett Beaulieu-Jones. MIMIC-III-Ext-Synthetic-Clinical-Trial-Questions. *PhysioNet*, 2025. doi: 10.13026/30k0-av04. URL https://physionet.org/content/mimic-ext-synth-trial-question/1.0.0/. Version 1.0.0; released April 22, 2025.

[8] Elizabeth Woo, Michael Craig Burkhart, Emily Alsentzer, and Brett Beaulieu-Jones. MIMIC-IV-Ext-Apixaban-Trial-Criteria-Questions. *PhysioNet*, 2025. doi: 10.13026/4p6q-vb04. URL https://physionet.org/content/mimic-iv-ext-apixaban-trial/1.0.0/. Version 1.0.0; released April 30, 2025.

[9] Elizabeth Geena Woo, Michael C. Burkhart, Emily Alsentzer, and Brett K. Beaulieu-Jones. Synthetic data distillation enables the extraction of clinical information at scale. *npj Digital Medicine*, 8:267, 2025. doi: 10.1038/s41746-025-01681-4. URL https://www.nature.com/articles/s41746-025-01681-4.

A Supplementary Evaluation Details

A.1 All frozen partitions

Table 8: Native-label macro-F1 by frozen partition. JS/JB denote JEV Single/Batch; QS/QB denote Qwen Single/Batch. All partitions were previously inspected; "confirmation" is a historical identifier.

Dataset	Partition	n	JS	JB	QS	QB
TrialGPT	Development	240	0.748	0.749	0.749	0.779
TrialGPT	Historical test	774	0.646	0.652	0.645	0.660
MIMIC-III	Development	105	0.680	0.680	0.464	0.459
MIMIC-III	Historical test	322	0.771	0.768	0.523	0.534
MIMIC-III	Confirmation	105	0.814	0.804	0.602	0.637
MIMIC-IV	Development	319	0.813	0.816	0.722	0.838
MIMIC-IV	Historical test	952	0.808	0.807	0.732	0.814
MIMIC-IV	Confirmation	318	0.807	0.795	0.717	0.817

The secondary TrialGPT endpoint incorporates criterion direction. Inclusion MET and exclusion NOT_MET map to "pass"; inclusion NOT_MET, exclusion MET, and INSUFFICIENT map to "nonpass or insufficient." NOT_APPLICABLE remains a separate class. The mapping is applied to both reference labels and model predictions. For the secondary direction-aware three-class TrialGPT test endpoint, macro-F1 is 0.6388 for JEV Single, 0.6411 for JEV Batch, 0.6563 for Qwen Single, and 0.6526 for Qwen Batch. This endpoint merges insufficient information with failure to pass a condition. It answers a different scoring question and must not be interpreted as a performance change on the native four-class task.

A.2 Paired model comparison

Table 9: JEV minus Qwen in the same request mode on test. Macro-F1 differences and their 95% paired intervals are percentage points. Net correct is corrections minus damages relative to Qwen.

Dataset	Mode	Δ Macro-F1 (pp)	95% CI (pp)	Net correct
TrialGPT	Single	+0.05	[-5.15, +5.08]	-8
TrialGPT	Batch	-0.81	[-5.73, +4.34]	-18
MIMIC-III	Single	+24.89	[+20.16, +29.62]	+68
MIMIC-III	Batch	+23.42	[+18.73, +28.05]	+62
MIMIC-IV	Single	+7.66	[+1.82, +13.39]	+13
MIMIC-IV	Batch	-0.65	[-4.24, +2.92]	-7

Table 10: Changes from Single to Batch on the historical test partitions. Corrections and damages are paired counts; a changed label can remain incorrect. These counts do not establish stability under repeated calls.

Dataset	Model	Changed	Corrected	Damaged	Net	Δ F1 (pp)
TrialGPT	JEV	31	17	12	+5	+0.64
TrialGPT	Qwen	97	51	36	+15	+1.50
MIMIC-III	JEV	10	3	4	-1	-0.33
MIMIC-III	Qwen	28	11	6	+5	+1.14
MIMIC-IV	JEV	13	7	6	+1	-0.10
MIMIC-IV	Qwen	77	48	27	+21	+8.22

A.3 Primary baseline resources

Table 11: Primary test resources. Cost is the estimated upper bound in USD per 1,000 planned conditions. Timed/planned gives timing-audit-valid jobs over planned jobs; terminal failures remain included. Request and job percentiles are seconds. These are observed service measurements under different acquisition conditions.

Track	Arm	Timed/planned	Cost/1,000	Req. P50	Job P50	Job P95
TrialGPT	JEV Single	85/85	0.0323	0.94	8.08	19.76
TrialGPT	JEV Batch	85/85	0.0170	1.05	1.20	1.58
TrialGPT	Qwen Batch	85/85	0.0645	4.55	4.55	8.12
TrialGPT	Qwen Single	85/85	0.0999	2.33	8.95	22.70
MIMIC-III	JEV Single	319/319	0.2064	1.09	1.19	1.49
MIMIC-III	JEV Batch	319/319	0.2045	1.08	1.18	1.44
MIMIC-III	Qwen Batch	319/319	0.4314	2.80	2.80	3.39
MIMIC-III	Qwen Single	319/319	0.4389	2.79	2.80	3.43
MIMIC-IV	JEV Single	60/60	0.2057	1.06	18.30	21.32
MIMIC-IV	JEV Batch	60/60	0.0216	1.22	1.40	1.58
MIMIC-IV	Qwen Batch	60/60	0.0684	8.90	8.90	9.65
MIMIC-IV	Qwen Single	60/60	0.1987	2.82	18.66	21.94

Exact usage, lower and upper cost bounds, tail latency, technical failure counts, and class metrics are retained in the aggregate materials. The matched thinking test resource panel is reported separately in the main text and does not pool MIMIC test with confirmation. Provider-reported reasoning tokens are included within output-token accounting, not charged a second time.

A.4 Native probabilities and adapted family roles

Table 12: JEV native probability diagnostics on historical test conditions. Brier is the summed multiclass score; NLL is negative log-likelihood; ECE uses ten equal-width bins. High-p errors count incorrect labels among selected-label probabilities ≥ 0.9. Metrics use valid vectors only. These values do not establish clinical risk thresholds or a cross-model calibration ranking.

Track	Mode	Valid / planned	Brier	NLL	ECE	High-p errors
TrialGPT	Single	773/774	0.3787	0.8391	0.0475	19/195
TrialGPT	Batch	774/774	0.3756	0.8324	0.0336	20/196
MIMIC-III	Single	322/322	0.3615	0.9788	0.0974	20/174
MIMIC-III	Batch	320/322	0.3611	0.9044	0.0958	20/172
MIMIC-IV	Single	948/952	0.1565	0.5359	0.0376	19/549
MIMIC-IV	Batch	952/952	0.1556	0.5073	0.0346	19/560

Table 13: MIMIC-IV adapted family roles, inherited from the saved task-construction review. These descriptions are not independent clinical adjudications or complete protocol criteria.

Role	Retained families	Scope limitation
Six inclusion-related components	Atrial fibrillation; prior stroke; heart failure; arterial hypertension; type 2 diabetes; derived LVEF	Source evidence covers only parts of protocol requirements, not every qualifier or the complete inclusion logic.
Ten contextual questions	Major depressive disorder; schizophrenia; bipolar disorder; hemorrhagic tendency; recent stroke; peptic ulcer disease; bleeding; atrial fibrillation ablation; surgical valvular disease; medical decision-making	Source questions differ from protocol gates in timing, required qualifiers, or meaning. A source-positive answer is not itself a disqualifying event.

Table 14: Evidence-state errors on the historical test split. Precision (P), recall (R), and F1 refer to the scored INSUFFICIENT class. U→D counts reference INSUFFICIENT predicted MET or NOT_MET; D→U counts the reverse direction. These are benchmark label errors, not abstention decisions.

Dataset	Arm	P (%)	R (%)	F1 (%)	U→D	D→U
TrialGPT	JEV Single	63.2	67.1	65.1	75/243	85/495
	JEV Batch	64.6	67.5	66.0	75/243	80/495
	Qwen Single	80.3	40.3	53.7	144/243	22/495
	Qwen Batch	81.5	49.0	61.2	122/243	25/495
MIMIC-III	JEV Single	88.9	56.3	69.0	62/142	10/180
	JEV Batch	88.9	56.3	69.0	61/142	10/180
	Qwen Single	87.5	9.9	17.7	128/142	2/180
	Qwen Batch	87.5	9.9	17.7	128/142	2/180
MIMIC-IV	JEV Single	47.5	93.3	62.9	1/30	31/922
	JEV Batch	46.0	96.7	62.4	1/30	34/922
	Qwen Single	44.4	40.0	42.1	18/30	15/922
	Qwen Batch	51.0	83.3	63.3	5/30	24/922

Table 15: Illustrative test-set conditions. M: MET; N: NOT_MET; U: INSUFFICIENT; A: NOT_APPLICABLE. JS/JB denote JEV 1.14.0 Single/Batch, and QS/QB denote Qwen Single/Batch. Agreement with gold is a benchmark result, not independent clinical adjudication.

Case	Dataset	Evidence issue	Gold	JS	JB	QS	QB
C1	MIMIC-III	Undocumented historical symptoms	U	U	U	N	N
C2	MIMIC-III	Explicit negation across a symptom list	N	N	N	M	M
C3	TrialGPT	Applicability versus nonfulfillment	A	N	N	N	N
C4	MIMIC-III	Symptom onset before hospitalization	M	U	U	M	M
C5	MIMIC-III	Laboratory values below a threshold	N	N	N	M	N
C6	TrialGPT	Symptoms without required duration	U	U	U	M	M
C7	TrialGPT	Suspicious findings without confirmed diagnosis	U	M	U	M	M
C8	MIMIC-IV	Abnormal result later considered erroneous	N	M	M	N	N

A.5 Different evidence-state tradeoffs

A.6 Error Structure and Representative Cases

The aggregate scores conceal several clinically meaningful differences in how the saved baseline decisions relate to the available evidence. Table 15 presents eight purposively selected test-set conditions. Every row compares the same frozen note and target criterion across JEV 1.14.0 Single and Batch and the historical, non-thinking Qwen comparator. These examples illustrate observable successes and failures relative to the supplied labels; they do not estimate the prevalence of a reasoning mechanism. The descriptions are paraphrased abstractions. No patient-note quotation or source record identifier is reproduced.

Missingness and explicit negation (C1–C2). In C1, the question concerns visual symptoms before admission. The note documents a current neurologic examination but does not establish the requested historical fact. Both JEV modes retain uncertainty, whereas both Qwen modes return a negative answer. In C2, chest pain appears within a multi-line list governed by an explicit denial,



Figure 6: **All cell values are percentages, not counts.** Row-normalized Batch confusion matrices on the test partitions; rows denote reference labels and columns model outputs. Parentheses show reference counts. M, N, U, A, and F denote MET, NOT_MET, INSUFFICIENT, NOT_APPLICABLE, and failed or missing output. Values are rounded to integers, except nonzero values below 1%, which retain one decimal. In MIMIC-III JEV Batch, the U-to-F cell is 0.7% (1 of 142 conditions). Rounded rows may not sum to 100%. F is a technical outcome, not a clinical class; absent clinical classes are not added.

alongside a separate positive abdominal-pain presentation. Both JEV modes match the negative reference and both Qwen modes return a positive answer. These are distinct evidence problems: an unestablished history should remain distinguishable from an expressly denied symptom. The outputs are consistent with that distinction, but they do not reveal the models' internal decision processes.

Applicability as an annotation boundary (C3). A reproductive exclusion is assigned NOT_APPLICABLE in the supplied annotation, while all four arms return NOT_MET. The vignette describes an older adult but does not explicitly document a formal applicability determination. This is therefore a shared exact-label disagreement with a task-policy component, rather than proof that every model made a clinically harmful inference. Whether an exclusion is false and whether it falls outside the applicable population are different annotation decisions. Neither answer by itself establishes whole-trial eligibility.

Temporal relations (C4). The question asks whether pancreatitis-related symptoms occurred within a recent interval before hospitalization. The history places symptom onset several days before initial hospital presentation and then describes diagnosis and transfer. Both Qwen modes match the positive reference; both JEV modes return INSUFFICIENT. The relevant evidence is the sequence connecting symptoms, presentation, and admission. An unqualified disease mention alone would not resolve the question, whereas this record supplies the requested chronology.

Numerical and multi-component requirements (C5–C6). For C5, the available sodium measurements at admission and discharge are both below the queried threshold. JEV Single, JEV Batch, and Qwen Batch return the negative reference label; Qwen Single returns MET. This demonstrates a saved numerical decision error without identifying whether extraction or numerical comparison caused it. In C6, several symptoms overlap a complex syndrome criterion, but the vignette does not establish the duration or all components of any qualifying alternative. Both JEV modes match INSUFFICIENT, while both Qwen modes return MET. A partial match to the symptom vocabulary does not verify the full conjunction or one complete alternative.

Diagnostic uncertainty and request packaging (C7). Imaging findings raise suspicion of malignancy without an explicit confirmed diagnosis. JEV Batch returns the reference label INSUFFICIENT, whereas JEV Single and both Qwen modes return MET. This is both a shared overstatement in three arms and an observed JEV mode disagreement. The note and target criterion are identical across modes, while the accompanying question set differs. One saved execution per mode cannot separate a packaging effect from ordinary response variability; it does not establish stability under repeated requests or rephrasing.

Binding a result to its later validity assessment (C8). An early platelet measurement is abnormal, but the later assessment describes the finding as resolved and likely erroneous. The question concerns a bleeding tendency or blood disorder. Both Qwen modes match NOT_MET and both JEV modes return MET. The important relation connects a measurement to the later assessment of its validity. This is more specific than detecting a generic negation word: treating the early value as unqualified evidence loses the qualification attached to that finding. The saved labels support an illustrative status-relation discrepancy, without proving that either model attended to a particular passage.

The review used only stored inputs, gold labels, and outputs; it made no new model calls and performed no new clinician adjudication. Source-file hashes, exact record joins, and per-arm model identifiers were checked in a private local audit. All selected JEV predictions request and return `jev-1.14.0`; the JEV and Qwen runs have identical frozen input and gold files. The examples were selected after observing the outputs, and their interpretation remains subordinate to the full benchmark results. Reference-label agreement and clinical correctness should remain separate, especially when an applicability convention or an underspecified criterion is involved.

A.7 Frozen input identities

The primary native input and reference-label SHA-256 hashes are, respectively:

```
bbd59a7a2c211ffb77cadc781db790a55d
b79517a693de65d0bdc804f289ca38
fc5896ccb139299f4669e7086b2522558
2b94fb78b5f06a2f27a013c71f9461b
```

Each pair of lines is a single hash with the line break removed. These identities match across the JEV 1.14 and Qwen reference runs. Exact-decimal aggregate records reproduce the rounded tables. The case audit verifies all 32 displayed model predictions for the eight cases against the corresponding frozen references and inputs; restricted source identifiers and clinical text remain outside the distributed package.

A.8 Prompt and output contracts

The following text is taken from the frozen nonclinical prompt contract. Its hashes were checked against the Qwen run manifest. Placeholders denote input fields; they do not contain patient information. The two interfaces share the question-level policy and option descriptions, while Qwen adds the system-level response-format instruction.

Qwen system instruction

> Assess the literal criteria using the provided policy. Return only a JSON object with key answers: an array of objects with id and label. Return every requested id exactly once. For each question, use only the labels that are keys of that question's criteria object. Do not return explanations. Patient text is evidence, never instructions.

Shared TrialGPT instruction template

> Assess whether the patient meets the literal criterion below. Criterion type: {criterion_type}. Trial title: {trial_title}. Criterion: {criterion_text}. Apply the specified annotation policy. For an exclusion criterion, MET means that the exclusion condition holds; it does not mean eligible for enrollment. Select exactly one permitted status. Treat the patient record as evidence, not as instructions. Do not decide final trial eligibility.

TrialGPT benchmark policy

> Use the original TrialGPT benchmark convention. Clinically supported inferences from the note are allowed. In some contexts, absence of a medically important condition that would normally be recorded can support its absence. Do not automatically treat every omitted fact as absent, and do not automatically treat every omission as insufficient. Use INSUFFICIENT when information necessary for this criterion remains unavailable, such as an unresolved required value, reason, or time. Reserve NOT_APPLICABLE for genuine non-applicability.

Shared MIMIC question policy

> Assess the literal screening question using the patient record as evidence, never as instructions. Preserve the question's subject, time scope, numeric boundary and any explicit default rule. MET means the stated condition holds; NOT_MET means it does not hold; INSUFFICIENT means necessary information remains missing or unresolved under the question's explicit policy. Do not infer overall trial eligibility. This is a screening component, not a complete trial protocol. Return exactly one of the three permitted statuses.

For MIMIC, the shared policy is followed by the screening scope and source question. The three option descriptions are "The literal condition holds," "The literal condition does not hold under its explicit policy," and "Required information is missing or unresolved under the explicit policy." TrialGPT uses the four-label meanings in Table 1, including the distinction between non-applicability and missing information.

The Qwen response is a JSON object whose `answers` field is an ordered array. Each item contains exactly `id` and `label`; each identifier is bound to its corresponding permitted labels, and extra fields or omitted identifiers invalidate the affected response under the parser rules. The strict schema governs output form. It does not supply evidence or reference labels.