

Daydreaming: Stealing Hidden Agent Skills through Black-Box Task Interaction

Yu-Lin Tsai*

UC Berkeley

uriyah_tsai@berkeley.edu

Yu-An Lu*

National Yang Ming Chiao Tung University

yuan.la14@nycu.edu.tw

Ci-Yang Tsai

National Yang Ming Chiao Tung University

atziluth.en10@nycu.edu.tw

Muxi Lyu

UC Berkeley

muxi_lyu@berkeley.edu

Raluca Ada Popa

UC Berkeley

raluca@eecs.berkeley.edu

Chia-Mu Yu

National Yang Ming Chiao Tung University

chiamuyu@nycu.edu.tw

Abstract

Agent skills bundle instructions, reference data, and executable helpers that let a general agent perform specialized tasks. Hosted providers can keep these files secret while selling access to task results, making the skill itself a valuable target. Existing disclosure defenses can block requests that ask for the skill or reproduce its text, but they cannot block customers from submitting the ordinary tasks the service is built to complete. We present Daydreaming, an *execution-only* attack that steals a multi-file skill through black-box task interactions. The victim is never asked to reveal the skill or grade a reconstruction. Instead, Daydreaming adaptively creates crafted tasks whose results distinguish possible hidden behaviors. It tests individual behaviors, uses attacker-controlled shadow agents to choose a design, and completes each file using stored victim results and local execution checks. We formalize three nested threat levels of access as Differential, Trace, and Output, and focus on Output, where the attacker sees only the final response and returned files.

Across 7 skills and 4 victim models, Daydreaming recovers 86.8% of original skill’s capability at Output, outperforming SigLeak by almost 4 $\times$. It produces installable skills using a median of 32 victim calls per skill even with disclosure defenses enabled. These results show that hiding skill files and filtering direct disclosure do not, by themselves, prevent functional reconstruction through normal use.

1 Introduction

General-purpose agents are broad, but specialized real-world tasks demand depth. Real-world expertise frequently depends on more than the capabilities of the underlying model: sophisticated instructions, domain-specific reference materials, tuned parameters, helper scripts, tools, and carefully engineered workflows may all be required to perform a specialized task reliably. Agent systems encode that as a *skill* the agent loads behind an ordinary task interface [5, 21]. A growing

market sells such capabilities the way software is sold as a service, a setting we call *Skill-as-a-Service* (*SkaaS*) where the vendor hosts the skill on its own agent and the customer pays per task or by subscription. Software-as-a-service withholds the program and charges for what it computes while *SkaaS* withholds the expertise and charges for what it judges. Existing vendors already sell hosted access in domains such as law, autonomous medical coding, and security operations, sometimes charged per completed task.⁰ Moreover, these vendors treat the hidden skill as a protected asset, as their terms of service forbid reverse-engineering the service or using outputs to build a competing one [7, 11, 13], and stealing attacks motivated by this kind of commercial market have appeared for single prompt settings such as domain-specific system prompts [25, 31].

However, as agentic systems package increasingly specialized expertise into hosted skills, the skill itself can become a substantially more valuable proprietary asset than a single prompt. Building such a skill may require experts and engineers to translate domain knowledge into detailed decision logic, curate supporting data, tune thresholds and parameters, and refine workflows through repeated deployment experience. For instance, a security-operations vendor advertising only one line for its hosted skill, “*investigate security alerts and return a verdict with the evidence*,” may keep private years of engineering and operational knowledge encoded in its escalation rules, threat indicators, reference data, and tuned thresholds that determine which alerts are worth waking an analyst for. Yet its customers are enterprises whose own networks raise those alerts, so each customer can place chosen alerts in front of the skill and observe what the vendor decides.

The execution output of a skill reveals an attack path that prior defenses do not address. Current defenses focus on the

*These authors contributed equally.

⁰Hosted, access-only vendors include Harvey (law, <https://www.harvey.ai>) and Dropzone (security operations, <https://www.dropzone.ai>); Nym sells autonomous medical coding [20]; Intercom’s Fin is billed per resolution [16], per-task metering applied to expertise, accessed 2026-08-21. The running example used throughout this paper is a composite of this last shape; the advertised line is our own.

disclosure path: detecting suspicious requests that attempt to reveal the hidden skill and blocking outputs that reproduce protected text. On the other hand, the *work path*, which enables benign user task execution, remains vulnerable to behavioral cloning, reverse engineering, and reconstruction. Thus, execution itself becomes a source of observation and behavioral inference.

We formalize this observability for behavioral inference into three nested levels: Output (o_3), Trace (o_2), and Differential (o_1), depending on what information the deployment exposes to the customer. Output exposes only the final response and returned files, making it the most restrictive and challenging setting for an attacker. Trace additionally exposes the agent’s intermediate tool activity, including which tools were called, their inputs, and returned results; such traces are commonly surfaced so customers can audit work they did not compute themselves. Differential provides richer feedback by revealing how outputs change under controlled variations of the input. We focus primarily on Output, since an attack that succeeds with only final outputs also applies when richer observations are available.

We present Daydreaming, a skill-stealing attack that treats task execution as a black-box system identification problem. Daydreaming is *execution-only*: every query asks the victim to perform a genuine task, and the victim is never asked to reveal its hidden skill or to compare, grade, or correct a reconstruction. This allows the attack to operate even when disclosure defenses are already active, which we assume throughout. Daydreaming repeatedly constructs tasks for which plausible properties, skill plans, or file versions predict different outcomes, then uses the victim’s observed result to eliminate alternatives and refine its reconstruction. Rather than synthesizing the target skill in one pass, Daydreaming reconstructs it sequentially through repeated probing and revision. We evaluate the stolen skill primarily by whether it reproduces the victim’s task performance on unseen inputs, rather than by whether its files textually match the hidden originals.

Across seven skills and three victim models, Daydreaming recovers 35.8–86.8% of the behavioral-utility gap between no skill and the original skill using only Output access and 31.3–32.8 victim calls per skill. It achieves the highest behavioral utility among all evaluated attacks and baselines for every victim model.

As such, we make the following contributions:

- **We formalize the observability available to a skill-stealing attacker** as three nested access levels, Differential (o_1) $\supseteq$ Trace (o_2) $\supseteq$ Output (o_3) (Section 4), and place every prior attack on that axis. We also show that no level can guarantee exact recovery of the hidden source.
- **We build Daydreaming, an execution-only skill-reconstruction attack.** Every query commissions ordinary work and never requests the hidden skill or a judgment of the reconstruction. As a result, Daydreaming operates even when disclosure blocking, extraction-input classification,

and output filtering are all enabled (Section 5).

- **We show that Daydreaming works at the most restrictive access level (Output o_3), with a limited number of victim queries.** Across 7 skills, Daydreaming recovers 86.8% of the victim’s task performance at Output and 87.0% and 86.0%, respectively at Trace and Differential with median attacker inference cost (Section 6).

2 Related Work

Agent Skills. The term *skill* has been used in different contexts in prior work. Some work treats skills as learned reusable abstractions: PolySkill learns polymorphic skills that separate an abstract goal from its concrete implementation and transfer across web tasks [32]. Other systems externalize reusable behavior in different forms: Large Language Models (LLMs) can synthesize callable tools that amortize expensive reasoning [8], while Agent Workflow Memory induces recurring action routines and retrieves them for later web tasks [29]. These works illustrate forms of reusable agent capability, but do not study skills as confidential, provider-controlled assets.

We study a *provider-controlled skill*: a customer-visible name and description paired with hidden instructions and optional references, assets, or executable helpers controlled by the service provider. Under the open skill standards [5, 21], the name and description remain available so the agent knows when the skill applies, while the instruction document and bundled files are loaded only as needed during task execution. The skill is mounted around a general model rather than merged into its weights, allowing a reconstructed skill to be copied, installed on another agent, and evaluated independently of the victim service. Throughout our design and evaluation, *skill* refers to this provider-controlled setting.

Stealing Agent Skills. Black-box model extraction established that query access can recover a proprietary trained model’s function without reproducing its implementation bytes [27]; skill stealing follows the same idea, but targets a modular, deployable program made of natural-language rules and auxiliary artifacts, and is evaluated by the behavior it reproduces rather than exact equivalence. Three concurrent studies have since touched this setting, each under assumptions narrower than ours. BBS prompts an agent to surface its own instruction file and scores the text that leaks [28]. SigLeak reads execution trajectories, and needs the service to run once with its skill suppressed [10]. RedAct is a defense, redacting traces before release [30]. None reconstructs a multi-file skill against a service whose disclosure defenses are active. We treat them as concurrent work that motivates rather than constrains our design, and Section 4 places each on an observability axis.

Stealing System Prompts. The closest research setting steals hidden system prompts. PLeak optimizes adversarial queries

for direct disclosure [15], while others reconstruct functionally similar prompts from input–output pairs or from answers alone [24, 31]. An in-the-wild study shows that lexical similarity is an incomplete measure of functional replication [26], while prompt obfuscation studies the defensive side [23]. Closest to our framing, information-theoretic analysis shows that recoverability per query depends on which response channel is exposed [18]. A system prompt is text, while a skill is a deployable program composed of instructions, scripts, and reference data. Reconstructing a skill therefore requires recovering not only its wording, but also its files, their roles, and how they work together, and is ultimately judged by whether the reconstructed skill can execute.

3 Threat Model

Our threat model centers around an attacker who is a paying customer of a *SkaaS* service, makes at most a limited number B of queries, and aims to steal as much functionality as possible from the proprietary skill within this budget. The attacker sees only the public skill card $d = (v, \sigma)$, where v is the public skill name and σ is its short description. The attacker starts with an unskilled agent $\mathcal{V}_\emptyset = (M, \Pi, \mathcal{T}, \emptyset)$ and aims to reconstruct the vendor-withheld skill S used by the hosted victim agent $\mathcal{V}_S = (M, \Pi, \mathcal{T}, S)$.

Inside both agents, M is the language model, Π is the agent orchestration policy including its system instructions and tool-routing logic, and $\mathcal{T}$ is the set of task tools. The key difference is the hidden skill: the victim mounts $S = (m, \mathcal{R})$, where m is the primary instruction document and $\mathcal{R}$ is a finite set of supporting resources such as scripts, reference documents, templates, or data files. This skill is the proprietary asset targeted by the attacker, who has no copy of S and cannot read the victim’s files, memory, private reasoning, or skill-loading operation.

During execution, the attacker submits a task x to $\mathcal{V}_S$ and observes the final output $y_S(x)$, consisting of the agent’s message and any returned files. When traces are visible in the deployment setting, we additionally write $\text{tr}_S(x) = ((g_1, r_1), \dots, (g_k, r_k))$ for the client-visible execution trace, where g_i denotes the i th tool call together with its arguments and r_i is the corresponding returned value. The attacker may adapt future queries based on previous observations and use its own shadow agents and local tools, but must remain within the B -query budget and cannot use the victim’s disclosure path to directly request or recover the hidden skill.

Running Example. To make the threat model and notation concrete, we use a running *SkaaS* example of security-alert triage, shown in Figure 1, throughout the paper.

- *Attack scenario.* A security-operations vendor hosts an alert-triage agent $\mathcal{V}_S = (M, \Pi, \mathcal{T}, S)$. Its public skill card $d = (v, \sigma)$ may expose only a name such as "Alert Triage" and a short description such as "investigate security alerts




Figure 1: The running example, split at the provider boundary.




Figure 2: What each level discloses.

and return a verdict with the evidence". The hidden skill $S = (m, \mathcal{R})$ contains the vendor’s triage instructions m and supporting resources $\mathcal{R}$, such as escalation rules, indicator lists, threshold tables, templates, or helper scripts. A customer submits an alert x and receives $y_S(x)$, such as a verdict, supporting evidence, and any returned files.

- *Attacker’s knowledge and capabilities.* The attacker is a paying customer rather than an insider. It sees the public skill card $d = (v, \sigma)$, knows the accepted task format, and can submit at most B adaptively chosen alerts. Depending on the deployment setting, it may observe only $y_S(x)$ or also the client-visible execution trace $\text{tr}_S(x)$. It cannot read the hidden skill, victim files, private reasoning, memory, or skill-loading operation, and all disclosure defenses remain active.
- *Attacker’s goal.* The attacker uses these task executions to construct a deployable reconstruction $\hat{S} = (\hat{m}, \hat{\mathcal{R}})$. The goal is not to recover the vendor’s exact source files, but to reproduce the skill’s behavior on new alerts: for example, "escalating the alerts the vendor would escalate while leaving benign alerts unflagged".

4 Formalizing Skill-Stealing Observability

Skill-stealing attacks differ in what information the attacker can observe from the victim service, but prior work often

Table 1: Example deployments for the three access levels.

Access level	Example deployment
Differential (o_1)	Open model weights [2] and a published harness [3], with the skill served separately from an enclave [4].
Trace (o_2)	An agent, gateway, or telemetry system that exposes tool calls and their results [6, 9, 12, 22].
Output (o_3)	A service that returns only the completed task result, such as autonomous medical coding or per-resolution support [16, 20].

leaves the observability settings implicit or treats them as interchangeable. We make this distinction explicit by defining three nested observability levels, placing existing attacks along this axis, and expressing the attacker’s objective in a form that applies across all three levels.

4.1 Three Nested Access Levels

What an attacker learns from one execution depends on how much information the deployment exposes. We distinguish three levels below, named by the evidence available at each level, and use the running example in Figure 2 to illustrate them.

$$o_1(x) = (d, M, \Pi, \mathcal{T}, \text{tr}_S(x), y_S(x), \text{tr}_\emptyset(x), y_\emptyset(x)), \quad (1)$$

$$o_2(x) = (d, \text{tr}_S(x), y_S(x)), \quad (2)$$

$$o_3(x) = (d, y_S(x)), \quad (3)$$

Each level contains the observations available at the level below it, so the three levels are nested, with a smaller index indicating a stronger attacker assumption.

- *Differential level* (o_1) The attacker knows the stack $(M, \Pi, \mathcal{T})$, including the system instructions in Π , and can run $\mathcal{V}_\emptyset$ on any input it also sends to $\mathcal{V}_S$. The attacker therefore has all information needed to construct a matched unskilled twin. Each queried task returns a *matched pair*, and because all other components are held fixed, differences between the two runs can be attributed to mounting S . This comparison still does not reveal the hidden source or distinguish skill implementations that induce the same behavior.
- *Trace level* (o_2) The attacker knows neither M nor Π , but reads $\text{tr}_S(x)$ which contains the tool calls the agent made and what they returned. Real-world products publish this record so that a customer can audit a result they did not compute themselves. Since no skill-off run is available, an observed behavior may originate from the base model M or the orchestration policy Π rather than in S .
- *Output level* (o_3) The attacker receives no execution meta-data and observes only the final message and any returned files. Thus, the available evidence is limited to behavior visible in the final result. This is the primary setting for

Daydreaming and requires crafting tasks whose outputs distinguish competing hypotheses about the hidden skill.

Running Example. Figure 2 shows executions at all three levels. At Differential, the customer runs the same harness on the same model, maintains an unskilled twin, and sends the same alert to both. The vendor execution escalates and names the finding, while the twin only returns a summary and escalates nothing; this gap isolates behavior introduced by the skill. At Trace, the vendor additionally exposes the evidence behind its verdict, so the timed window and measured entropy of 6.4 appear alongside the finding and provide clues about possible thresholds or rules encoded in the skill. At Output, only the final verdict is returned, so the available evidence is limited to which alerts are escalated and how the decisions are described.

Deployment Settings. Table 1 gives one deployment example for each level. The levels differ in what the provider releases from an execution; the skill itself remains inside the provider’s boundary.

Table 2: Comparison with the closest skill-stealing attacks.

Method	Victim interaction	Reconstructs
BBS [28]	Asks the victim to reveal SKILL.md and reads the disclosed text.	Leaked instruction-file text
SigLeak [10]	Runs a task normally and with the skill suppressed, then compares the traces.	Instructions inferred from traces
Daydreaming	Sends a customer task chosen to separate candidate behaviors and reads its result.	Installable skill with supporting files

Comparison with Existing Attacks. BBS relies on direct disclosure [28], while SigLeak requires visible traces and a matched skill-suppressed execution [10]. In contrast, Daydreaming uses only ordinary customer-task results, operates even at Output, and reconstructs the skill together with its supporting files. Table 2 summarizes these differences.

4.2 Why Recovery Is Behavioral

The three access levels expose different amounts of evidence, but none guarantees bit-for-bit recovery of the exact hidden source.

Proposition 4.1 (Exact source is unidentifiable) *Fix one access level and two distinct skills with the same public card. If every adaptive task strategy produces the same transcript distribution under both skills, no randomized attacker can distinguish them. Under an equal prior over the pair, every exact-source estimator succeeds with probability at most 1/2.*

Such indistinguishable skills exist at all three levels whenever the skill format permits content that the runtime neither

consults nor allows to affect execution, persistent state, or any disclosed result. Modifying such inert content changes the skill source without changing its task results or visible trace; the matched no-skill execution available at Differential is unchanged as well. Stronger access can eliminate more candidate skills, but it cannot remove this ambiguity. Appendix B gives the formal interaction model and proof with other theoretical results.

Exact source recovery is therefore not the appropriate objective. Instead, we measure whether the reconstructed skill reproduces the victim’s functionality on new customer tasks. Let $\mathcal{D}_{\text{eval}}$ be a held-out task set. *Held out* means that its tasks and verifier outcomes remain unavailable until $\hat{S}$ is constructed: they are never used as victim queries, shadow-agent tasks, local tests, candidate selection signals, stopping conditions, or hyperparameter-tuning data. Each task x has a success verifier $v_x : \mathcal{Y} \rightarrow [0, 1]$ that scores the returned result. The behavioral check of a skill P is defined as

$$U(P) = \mathbb{E}_{x \sim \mathcal{D}_{\text{eval}}} [v_x(y_P(x))], \quad (4)$$

where $y_P(x)$ is the result produced with P mounted. The attacker maximizes $U(\hat{S})$ within B victim calls. Evaluation instantiates this objective as success rate and behavioral check (Section 6). For completeness, we separately report structural recovery.

5 Proposed Method: Daydreaming

5.1 Overview

Daydreaming works under a setting where the attacker is given only the public skill card $d = (v, \sigma)$, access to the *SkaaS* work path for submitting ordinary tasks, and a budget of B victim calls. The attacker’s goal is to reconstruct the hidden skill $S = (m, \mathcal{R})$ mounted on the victim $\mathcal{V}_S = (M, \Pi, \mathcal{T}, S)$, producing a deployable reconstruction $\hat{S} = (\hat{m}, \hat{\mathcal{R}})$ that reproduces as much of the victim’s functionality as possible.

Key method: a hierarchical hypothesis refinement loop. Instead of reconstructing the entire skill at once, Daydreaming progressively refines hypotheses from behavioral properties, to candidate skill plans, and finally to concrete file versions. At each step, an attacker-controlled language model with no access to S , which we call the *attacker model*, proposes competing hypotheses and crafts a task on which they predict different observable results. Daydreaming then executes the task through the victim’s work path and uses the observed result to select or revise the better-supported hypothesis.

When comparing competing hypotheses, Daydreaming runs local shadow agents to predict how each alternative would behave on the crafted task. A *generalist shadow* performs the task without a skill and provides a no-skill baseline, while a *candidate shadow* performs the same task using a candidate skill plan and provides the behavior predicted by

that hypothesis. Daydreaming then compares these local predictions with the victim’s observed result to determine which hypothesis is better supported.

Architecture: three hierarchical stages & one shared loop.

Daydreaming organizes skill reconstruction into three *hierarchical* stages, while each stage follows the same *hypothesis-refinement loop*. Across stages, the object being identified becomes more concrete, moving from behavioral properties to a candidate skill plan and finally to complete file versions, making the attacker’s reconstruction closer to the hidden skill.

- *Stage 1—property.* A property c is a testable behavior of S , such as an escalation cutoff or result ordering. Stage 1 returns tested property records P , their tasks and results in O , and filenames observed in victim results in A , serving as the input for Stage 2 for candidate skill generation.
- *Stage 2—candidate skill plan.* A candidate skill plan H_i describes draft instructions and the paths, purposes, and sketches of supporting files. Stage 2 compares plans that share the tested properties but make different choices where the evidence is incomplete. It returns one revised plan H^* , serving as the input for Stage 3 for file versioning.
- *Stage 3—file version.* Stage 3 turns each file sketch in H^* into complete file versions, compares them, and revises the selected version. The completed files form the final reconstructed skill $\hat{S}$.
- *One shared loop.* Within each stage, Daydreaming repeats the same hypothesis-refinement loop:
 1. *Update and Propose.* Use earlier task results to update the current identification and propose next alternatives.
 2. *Craft and Execute.* Craft a task on which the alternatives would produce different results, then run the victim and the local comparisons needed by that stage.
 3. *Observe and Select.* Compare the results, and select the better-supported alternative, or record that the experiments are undetermined.

The selected result updates the current hypothesis before the loop repeats, so later tasks are chosen adaptively from earlier observations rather than from a fixed task list.

Key strategy: discriminating tasks. Across all three stages, Daydreaming follows one strategy for spending victim queries: it calls the victim only when the proposed alternatives can be separated by a crafted task, which we call a *discriminating task*. Stage 1 uses discriminating tasks to distinguish possible values of a property, Stage 2 uses them to distinguish candidate skill plans, and Stage 3 uses them to distinguish complete versions of one file. If no discriminating task can separate the alternatives, Daydreaming makes no victim call; if the observed result supports neither alternative, the choice is recorded as undetermined.

Every experiment records its crafted task, observed result, decision, and supporting evidence in O . Figure 3 summarizes the three-stage architecture and shared refinement loop, while Algorithm 1 gives the full pipeline. All victim calls

Algorithm 1 Daydreaming: reconstructing a skill through ordinary task executions.

Require: public card d , victim-call budget B , observation level ℓ

Ensure: reconstructed skill $\hat{S}$

- 1: $(B_1, B_2, B_3) \leftarrow \text{SPLITBUDGET}(B)$
- 2: $(P, O, A) \leftarrow \text{INFERPROPERTIES}(d, \ell, B_1)$
- 3: $(H^*, O) \leftarrow \text{SELECTCANDIDATE}(d, P, A, O, \ell, B_2)$
- 4: $\hat{S} \leftarrow \text{REFINEFILES}(d, H^*, P, O, \ell, B_3)$
- 5: **return** $\text{ASSEMBLE}(\hat{S}, O, P) \triangleright$ offline; zero victim calls




Figure 3: Architecture of Daydreaming

share the fixed budget B , with remaining parameters listed in Table 12. Appendix C provides complete pseudocode, Appendix D gives the default prompts, and our implementation is available online.¹

5.2 Stage 1: Property Inference

Goal and outputs. Stage 1 learns individual behavioral properties of the hidden skill before deciding how those properties are organized into a complete skill. It starts from the public card d , the service’s accepted task format, threat level ℓ , and budget B_1 . It produces P , a set of tested property records; O , the crafted tasks and victim results behind them; and A , helper filenames observed in those results. Each record in P contains the tested property, its alternatives, the selected outcome, and the supporting evidence. Stage 2 uses P and A to construct candidate skill plans, while O is retained for later stages and final assembly.

1. Update and Propose. The attacker model begins with n_{seed} possible properties suggested by the public card d . The prompt covers possible capabilities, constraints, procedures, terminology, input/output formats, decision rules, and supporting files (see Appendix D). For each property c , it proposes n_{alt} realistic alternatives $C(c)$. New victim results may revise an existing property or suggest a follow-up property, so later experiments depend on what Stage 1 has already learned.

2. Craft and Execute. Stage 1 crafts tasks in three ways, all following the same rule: the proposed alternatives must predict visibly different task results. If no task can separate the alternatives, Daydreaming makes no victim call.

- **Ordinary behavior.** For properties such as result ordering,

output format, or decision behavior, Stage 1 chooses inputs that make the alternatives produce different visible results. Properties that fit naturally in one task may be tested together. The victim then performs the crafted task.

- **Numeric cutoffs.** When a tested property suggests a cutoff, Stage 1 creates an ordered batch of routine cases spanning a plausible range while keeping other inputs fixed. The task asks for one decision per case. If the decisions change consistently, a later adaptive task may test a narrower range around that change.
- **Counting rules.** When an operation has several reasonable counting rules, Stage 1 creates a small input for which the alternatives predict different exact totals. For example, in *alert-triage*, one DNS packet may count only as DNS, as DNS and UDP, or as DNS, UDP, and IP. The task asks the victim for the corresponding totals.

After each victim task, the generalist shadow performs the same task without a skill. Stage 1 uses this comparison to determine whether the observed behavior appears specific to the hidden skill or can already be reproduced by a generalist agent. The victim result remains the source of the selected property value.

3. Observe and Select. Daydreaming uses the strongest evidence available under threat level ℓ : at Differential (o_1), it can additionally compare against the matched unskilled execution; at Trace (o_2), it observes the victim’s client-visible tool activity; and at Output (o_3), it relies only on the final message and returned files. For ordinary behavior, it records an alternative as *confirmed* when the result follows it, *refuted* when the result follows another alternative, and *undetermined* otherwise. For a cutoff, it requires the decisions to change once in a consistent direction; if the returned material exposes the exact comparison, that value replaces the estimate. For a counting rule, it selects the unique rule whose predicted totals exactly match the victim result. No cutoff or counting rule is selected when the result is incomplete or inconsistent.

Stage 1 also extracts additional evidence from already collected results at no extra victim cost. It scans stored code and task results for module names, function names, calls, commands, and paths that were not supplied by the crafted task. Filenames found in victim results are added to A only after removing names copied from the crafted task and obvious task-output files.

Before a record enters P , its wording is restricted to details supported by the victim result. A failed or undetermined test containing only the attacker’s guess is dropped. Stage 1 adds each crafted task, victim result, decision, and supporting evidence to O .

Running example. *Update and Propose:* Stage 1 proposes that security findings are ordered either *by severity* or *by detection time*. *Craft and Execute:* it creates a report task in which a low-severity event occurs first and a high-severity event occurs later, so the two alternatives predict opposite row orders.

¹Source code: <https://github.com/anonymous/REPOSITORY>.

Observe and Select: if the victim places the high-severity row first, Stage 1 records severity ordering and the returned row order as supporting evidence. A later loop can apply the same process to an escalation cutoff: propose a plausible range, submit a batch of alerts spanning that range, and narrow the cutoff based on where the victim’s decisions change.

5.3 Stage 2: Candidate Selection

Goal and limitation. Stage 1 identifies behavioral properties of S but does not determine how those properties are organized into a multi-file skill. The same observed behavior may come from instructions, a script, or a reference file. Stage 2 therefore compares complete *candidate skill plans* rather than isolated properties. It returns a plan H^* that is consistent with the observed behavior, but not necessarily with the vendor’s original file organization.

1. Update and Propose. Let $H_i = (m_i, \mathcal{R}_i)$ denote a candidate skill plan, where m_i is a draft SKILL.md and each entry in $\mathcal{R}_i$ specifies a supporting file’s path, purpose, and content sketch. Stage 2 constructs a set $\mathcal{H} = H_1, \dots, H_{n_H}$ of candidate plans. Every plan must preserve the tested properties in P and include filenames observed in A , while making different choices where the evidence remains incomplete.

To encourage diverse but plausible structures, the attacker model proposes n_H representative customer tasks, each pairing a user role with a concrete use of the skill, and drafts one candidate plan around each task (see Appendix D). A plan may also propose supporting files beyond A , since Stage 1 may not expose every file used by the hidden skill.

Stage 2 compares plans in pairs across rounds. The selected plan is revised with newly supported behavior and advances to the next round, while an unpaired plan receives a bye. Thus, later rounds use both the original evidence in P and A and the victim results accumulated during earlier comparisons.

2. Craft and Execute. For a pair of plans (H_a, H_b) , the attacker model uses the Stage 2 comparison prompts to construct $D(H_a, H_b)$, the behavioral differences that would change a task result (Appendix D). Differences only in file-names or file placement are excluded since any crafted task cannot distinguish them. If $D(H_a, H_b)$ is empty, Daydreaming makes no victim call. Otherwise, it crafts a task $x_{a,b}$ that exposes one or more of these differences and sends only that task to the victim. The attacker model also performs $x_{a,b}$ through candidate shadows for each plan. A candidate shadow receives H_a or H_b and the task $x_{a,b}$, and produces the result predicted by that plan. Let y_v be the victim result and y_a, y_b be the two candidate-shadow results. Stage 2 compares these three results while retaining richer victim observations in O .

3. Observe and Select. For each difference in $D(H_a, H_b)$, Stage 2 checks whether y_v follows y_a, y_b , both, or neither. The plan matching more differences becomes the survivor.

Stage 2 then revises it with behavior supported by the victim result, including any point on which the other plan matched better, while preserving the measured properties and observed filenames required by P and A . It stores the crafted task, the three results, the decision, and the revised survivor in O .

A tie, a result matching neither plan, or the absence of a discriminating task does not identify either plan. Since Stage 2 must produce one plan for Stage 3, it uses an explicit fallback: prefer greater coverage of A , then fewer files, then the earlier plan. This fallback keeps the three-phase loop moving. With n_H initial plans, Stage 2 performs at most $n_H - 1$ pairwise comparisons. Its output H^* is the final revised survivor.

Running example. *Update and Propose:* both plans preserve the alert cutoff recovered in Stage 1, but H_a merges repeated indicator hits while H_b reports every hit. *Craft and Execute:* Stage 2 creates an alert containing the same indicator twice; the victim performs it, and the two candidate shadows predict one versus two findings. *Observe and Select:* if the victim returns one finding, H_a survives and is updated before its next round. If the plans differed only in whether that rule appears in SKILL.md or a script, no task would distinguish them and the layout choice would use the stated fallback.

5.4 Stage 3: Per-File Refinement

Goal and outputs. Stage 2 returns one candidate skill plan $H^* = (m^*, \mathcal{R}^*)$, where m^* is the draft instruction file and each entry in $\mathcal{R}^*$ specifies only the path, purpose, and content sketch of a supporting file. Stage 3 keeps this file structure fixed and turns each sketch into complete file content. It processes supporting files first and the instruction file last, so the final instructions can refer to the actual function names, interfaces, and paths in the completed files. The output is the final reconstruction $\hat{S} = (\hat{m}, \hat{\mathcal{R}})$.

1. Update and Propose. For each supporting file $f \in \mathcal{R}^*$, the attacker model first expands its path, purpose, and sketch into one complete version. It treats the draft m^* as the initial instruction-file version and processes it last. For each file, it then identifies uncertain choices—for example, whether a cut-off uses $>$ or $\geq$ —and proposes complete versions that make different choices (see system prompts in Appendix D). Let V_f denote this set of complete versions. After each comparison, the selected version is revised at its weakest checked behavior and becomes the starting point for the next round.

2. Craft and Execute. For one fixed file f , the attacker model constructs D_f , representing the differences among versions in V_f that would change a task result (Appendix D). If D_f is empty, Daydreaming makes no victim call. Otherwise, it crafts a task x_f that exposes one or more of these differences and submits it to the victim. An unusable first transmission may be shortened and retried once, with both transmissions charged to B_3 . We denote the same task x_f ; let $t_{f,v}$ denote the

result produced while following version $v \in V_f$. Stage 3 later compares these shadow results with the victim result t_f . Any additional execution details remain stored in O .

For instruction and reference files, Stage 3 also compares versions against stored task-result pairs from Stages 1 and 2. When an earlier result reflects behavior governed by f , it provides another comparison for V_f without a new victim call. Thus, Stage 3 obtains at most one new usable victim result per file and reuses earlier results whenever they apply.

3. Observe and Select. For each version $v \in V_f$, Stage 3 checks whether $t_{f,v}$ matches t_f on the behaviors exposed by D_f . For instruction and reference files, candidate shadows also perform the stored tasks from Stages 1 and 2 and compare their results with the stored victim results.

The version agreeing best with the observed behavior becomes the current selected version. The attacker model revises its weakest observed mismatch and repeats the comparison attacker-side using the same results. A revision is kept if its average score improves, or if no current version scores higher on every checked behavior; Algorithm 4 in the appendix gives the complete rule. Malformed files, wrappers that require an unavailable external copy, and changes to recovered constants are rejected. After refining every supporting file, Stage 3 refines the instruction file last against their completed files.

If no crafted task distinguishes V_f , or no usable victim result is returned, Stage 3 falls back to the stored results from Stages 1 and 2 for instruction or reference files and to local tests for executable files. If neither source distinguishes the versions, it marks f unresolved and keeps the initial valid version. This fallback permits the loop to continue.

Running example. *Update and Propose:* for the detector script, Stage 3 creates complete versions that differ only in whether the recovered cutoff uses $>$ or $\geq$. *Craft and Execute:* it sends the victim one alert exactly at the cutoff, stores the verdict as t_f , and runs both versions and a local test attacker-side. *Observe and Select:* it keeps the version matching t_f ; the local test rejects a script that states the right comparison but never applies it. Every later revision reuses the same result.

5.5 Assembly

After Stage 3, Daydreaming writes the selected files to their planned relative paths. Stage 2 has already inserted the filenames in A , and Stage 3 has verified that those paths remain present. Assembly then performs two guarded offline cleanups: replacing fixed spreadsheet ranges and missing-value placeholders with general rules, and making absolute output paths caller-chosen. A rewrite is kept only if it removes the flagged detail without dropping recovered interfaces or changing other paths; otherwise, the original is retained. These checks make no victim calls and cover only these known patterns, so other task-specific details may remain. The assembly steps appear at the end of Algorithm 4.

Table 3: Task-to-skill mapping for the evaluation dataset.

Task	Required skill package(s)
protein-expression-analysis	xlsx
pddl-airport-planning	pddl-skills
pddl-tpp-planning	pddl-skills
dapt-intrusion-detection	pcap-analysis, threat-detection
software-dependency-audit	cvss-score-extraction, trivy-offline-vulnerability-scanning, vulnerability-csv-reporting

6 Evaluation

We evaluate Daydreaming through three research questions:

RQ1: Performance. We evaluate the performance of Daydreaming concerning three major factors below:

- How much utility does Daydreaming recover from the strictest Output(o_3) threat level, relative to no-skill and original skill setting as well as prior attacks and baselines?
- How much structural recovery can Daydreaming achieve relative to the original skill?
- How does each component throughout different stage contribute to Daydreaming, and how does utility of Daydreaming change with varying attacker query budget?

RQ2: Observability. How does Daydreaming performs when the victim deploys skill across different threat levels o_1 , o_2 , and o_3 ?

RQ3: Transferability. Once Daydreaming successfully reconstruct skill $\hat{S}$, does it remain useful across victim models and orchestration/tool policy?

6.1 Experimental Settings

Dataset. Adapted from SkillsBench [19], we select 7 skills as the stealing target with details summarized in Table 14. We select the skills based on the criterion of real-world use cases, spanning use case such as rule/table lookup, numeric algorithms, procedures/checklists, workflow orchestration, and document/artifact production, we also add the criterion that installing the original skill must improve task performance over the no-skill condition.

Furthermore, following the objective defined in Section 4.1, we construct a held-out dataset $\mathcal{B}$ of 5 tasks curated from SkillsBench [19]. Each task in the has its own input x and its executable verifier v_x . Due to the design of SkillsBench [19]. Each task requires one or multiple skills to cooperate to complete the task. For instance, a task such as *network intrusion* requires skills such as *pcap-analysis* and *threat-detection*. Since each task may depend on several skills, so we treat it as the basic unit in reporting the metrics.

Each task in the dataset is fully held out, including prompts, inputs, and verifier are never used as victim queries, shadow-agent tasks, local tests, or candidate-selection signals. Table 3 also makes clear the task-skill mapping.

Model Setting. For victim model selections, we opt for

both closed-weight and open-weight models which are claude-opus-5, gpt-5.6-sol, and kimi-k3. Moreover, we selected claude-opus-5 as the default victim if not further announced. We select gemini-3.7-flash as the attacker model across evaluations. All victim uses temperature 0.2 and top- $p = 0.95$, whereas the attacker uses temperature 0.7 and top- $p = 0.95$. For each reconstructed skill, we evaluate the held-out dataset on glm-5.3 as the default deployment for evaluation. RQ3 further tests the transferability of these recovered skills across all victim models.

Orchestration / Tool Policy Setting. We select deepagents as the default policy setting, which are constructed with filesystem and several basic tools. For additional policy settings, we also include claude_agent_sdk, openai_agents, and agno with details in Appendix A.

Threat Level Setting. Consistent with our threat model, the attacker receives the public skill card but not the skill S , held-out tasks, verifiers, or victim memory and reasoning process. We use the observation names defined by the threat model: *Output* reveals returned text and files, *Trace* additionally reveals task-level tool events, and *Differential* adds the model and harness stack plus a matched no-skill execution. This allows the attack to adapt only to the view it receives.

Daydreaming Setting. The default per-skill budget is $B = 96$, divided into 64 stage 1, 12 stage 2, and 20 stage 3 calls. The attack seeds 14–18 properties, groups at most four per probe, generates six package hypotheses, creates up to three initial version per file. Differential unskilled twin calls are recorded separately from victim budget calls. The complete parameter list is in Appendix A.

Prior Attacks and Baseline Setting. For a fair, resource-aligned comparison, BBS and SigLeak use the same three victims, gemini-3.7-flash attacker, and budget as Daydreaming, while retaining its native probing and stopping rule rather than being forced to spend identical calls. Its native input is a signed augmented trajectory; we therefore label it *augmented trace* and do not claim Output-threat level compatibility. Costs are reported for producing a complete reconstructed skill in each method’s native form.

Furthermore, we evaluate two additional baseline that accompanied this setting, which are called *Fixed Probes* and *One-pass synthesis* which we describe below. For *One-pass synthesis*, the attacker model is only given the public card d and asked to generate the reconstructed skill with one pass only and no other queries are allowed. *Fixed Probes* is a more informative baseline than *One-pass Synthesis* as the attacker model are able to craft all tasks in advance and received its results. Then along with the public skill card, it is asked to generate the reconstructed skill $\hat{S}$.

6.1.1 Metric.

Let C denote the installed package condition: no skill $\emptyset$, a reconstruction skill $\hat{S}$, or the original skill S . For task b , due to the stochastic nature of the victim model M along with the policy Π , we run in total n_b trials to solicit the final results. For each trial with index i , it has a final verifier binary result $y_{bi}(C) \in \{0, 1\}$. As a result, we define the first metric of binary success as

$$SR_b(C) = \frac{1}{n_b} \sum_{i=1}^{n_b} y_{bi}(C)$$

SR denotes strict binary success, meaning the end-to-end completion of task b .

On the other hand, we grade the skill’s utility also with a trace-related metric, which capture the agent’s correct behaviors in trace rather than final success. Specifically, given trial i , task b and condition c , the task offers in total $m_{bi}(C)$ intermediate verifier checks while the agent might pass $p_{bi}(C)$ of them. We define the second metric of behavior check as

$$U_b(C) = \frac{\sum_i p_{bi}(C)}{\sum_i m_{bi}(C)}.$$

U denotes behavioral utility. This is the empirical instantiation of $U(P)$ defined in Section ?? . Since a task might span multiple skills, we report the overall task average as

$$SR(C) = \frac{1}{|\mathcal{B}|} \sum_{b \in \mathcal{B}} SR_b(C), \quad U(C) = \frac{1}{|\mathcal{B}|} \sum_{b \in \mathcal{B}} U_b(C),$$

We further define normalized binary and behavioral success recovery across tasks as

$$NSR(C) = \frac{SR(C) - SR(\emptyset)}{SR(S) - SR(\emptyset)}, \quad NU(C) = \frac{U(C) - U(\emptyset)}{U(S) - U(\emptyset)}$$

which denote the improvement ratio compared to original skill S . We note that 0 corresponds to no skill, 1 to the original skill, negative values indicate utility below no skill, and values above 1 indicate utility above the original skill.

We also report cost, elapsed time, and structural precision, recall, and F1. To compute the structural metrics, we match recovered numeric constants, threshold branches, tool preconditions and output schemas, file paths, and executable scripts one-to-one against their counterparts in the original version of the same skill, and then pool the counts across skills.

6.2 Experimental Results

We organize the results by the three RQs. All scores use the held-out tasks and metrics defined in Section 6.1.

RQ1: Performance.

End-to-End utility. Table 4 first compares Daydreaming with the no-skill and original conditions under the Output(o_3) threat level. Among the reconstructions, kimi-k3 is strongest,




Figure 4: Comparison with prior attacks and baselines.

Table 4: Output-level results on held-out tasks. Task cells show SR_b/U_b ; summary rows show SR/U and NSR/NU .

Task (SR_b/U_b)	No skill	claude-opus-5	gpt-5.6-sol	kimi-k3	Original
Protein expression	.571/.786	1.000/1.000	.857/.929	1.000/1.000	.714/.857
Airport planning	.000/.357	.143/.500	.286/.571	.000/.500	.286/.571
Purchaser planning	1.000/1.000	.857/.857	.571/.643	1.000/1.000	1.000/1.000
Network intrusion	.000/.153	.000/.714	.000/.398	.000/.602	1.000/1.000
Dependency audit	.000/.536	.000/.750	.143/.786	.714/.929	.143/.786
SR/U (task avg.)	.314/.566	.400/.764	.371/.665	.543/.806	.629/.843
NSR/NU	.000/.000	.273/.716	.182/.358	.727/.868	1.000/1.000

improving SR from .314 to .543 and U from .566 to .806. The claude-opus-5 reconstruction also improves both metrics, reaching .400/.764. The gpt-5.6-sol reconstruction reaches .371/.665 and remains above no skill on both metrics. Reconstruction quality therefore depends on the source victim.

Comparison with prior attacks and baselines. Figure 4 compares Daydreaming with prior attacks and baseline methods across three victim models, we delegate the exact experimental numbers to Appendix A. The x-axis reports success rate (SR), while the y-axis reports the behavioral check score (U), with the upper-right corner indicating stronger overall performance. Across all three victims, Daydreaming consistently achieves the highest behavioral check score among all attack methods while approaching the performance of the original skill. Although Fixed Probes attains a higher SR on claude-opus-5 and gpt-5.6-sol, it exhibits noticeably lower behavioral check scores, demonstrating that maximizing SR alone does not necessarily produce more useful or faithful behaviors. On kimi-k3, Daydreaming dominates prior attacks on both SR and behavioral check, illustrating a favorable balance between effectiveness and behavioral quality across different victim models.

Structural recovery. Table 5 further compares reconstructed structures with the original skills. Structural recovery is limited as constants and threshold branches obtain .018 and .050 F1, while paths and scripts reach .200. Combining with the previous experiments on end-to-end utility, we thus note that useful behavior does not require an exact copy to work.

Table 5: Structural recovery for the claude-opus-5. P, R, and F1 denote precision, recall, and F1 score for recovery score.

Item type	Total Counts	P	R	F1
Exact constants	104	.111	.010	.018
Threshold branches	31	.111	.032	.050
Tool preconditions/schemas	19	.000	.000	.000
File paths	7	.333	.143	.200
Executable scripts	2	.125	.500	.200
Constants (within 1% tolerance)	104	.556	.048	.088

Components and query budget. Before we move into the results, we briefly recall each component used within stage and introduce them to better interpret the experimental results.

For Stage 1 of Daydreaming, we ablate two essential component, which are the *property labeling mechanism* (Observe&Select) that attach each property $c \in P$ with an evidence label and the *filename selecting protocol* (Observe&Select) that uses victim task results to filter plausible filenames in A . We ablated these two mechanism as they are the most fundamental part that constitute Stage 1’s property-level identification.

For Stage 2, we ablate two other components which are the *number of candidate skill plan* (Update&Propose) and the *discriminating task generation* (Craft&Execute). For the first one, we reduce the number of candidate skill plan in Stage 2 to 1 meaning that once the attacker model came out with a skill plan H , we treat it as H^* and proceed to Stage 3. For the second one, we ablate the discriminating task generation of Stage 2 and instead ask the attacker model to submit ordinary




Figure 5: Component ablations.

job pertaining to each candidate plan without considering their difference. As Stage 2 focus on more nuanced discrimination between each candidate skill, we chose these two mechanisms to ablate for.

Finally, for Stage 3, we ablate whether doing per-file refinement is useful for the utility of reconstructed skill.

Figure 5 shows that every evaluated component contributes to the behavioral utility of the recovered skill. The largest utility drops occur when removing the Stage 1 filename-selection protocol and Stage 2 discriminating-task generation, which reduce U to .624 and .626, respectively. Removing the Stage 1 property-label mechanism increases SR from .400 to .497 but lowers U to .696, which might be explainable due to the reason that verifying the property gives a stronger signal to the overall behavior but not the end effectiveness. Restricting Stage 2 to one candidate skill plan and removing Stage 3 per-file refinement leave SR unchanged at .400, while reducing U to .736 and .714, respectively. This indicate a even stronger signal that Daydreaming’s later stage contributes mostly to the behavioral success of the reconstructed skill. Overall, every ablation lowers U , confirming that each component contributes to the quality of the reconstructed skill.

Table 6 studies sensitivity to the victim-call budget B . Among settings evaluated on all skills, behavioral utility increases from .762 at $B = 32$ to .777 at $B = 64$ and .785 at the default $B = 96$, while SR varies non-monotonically and is highest at $B = 32$. Thus, additional victim calls improve behavioral quality more consistently than raw task success, with diminishing gains at larger budgets. This demonstrated that larger call budget can recover behavioral success U since each stage in Daydreaming are allowed more budget for fine-grained discrimination.

Switching Victim Model Size. We further study whether reconstruction effectiveness depends on the capacity of the victim model. For each victim, we substitute same-family models of different sizes while keeping everything fixed, thereby reducing confounding differences across model families. Figure 6

Table 6: Victim-call budget sweep.

Victim Call Budget B	SR/U	Actual Queries per skill	cost per skill
16	.467/.740	15	7.07
32	.433/.762	25.0	9.53
64	.400/.764	29.6	12.31
96	.476/.785	32.8	14.40
128	.400/.788	29.3	12.94

Table 7: Varying Threat Level with Fixed Crafted Task Results

Threat level	Information visible to the attacker	SR	NSR	U	NU
Output o_3	Returned text and files	.400	.273	.764	.716
Trace o_2	Output plus task-level tool events	.567	.804	.807	.870
Differential o_1	Trace plus stack and no-skill pair	.544	.731	.804	.860

shows that model size affects both task success and behavioral fidelity, but the trend is not uniformly monotonic. Within the GPT-5.6 family, performance improves consistently from Terra to Sol and Luna, indicating that larger capability victim model doesn’t necessarily reconstruct better. The Claude family exhibits a different pattern as Sonnet achieves the highest SR , whereas Opus achieves the highest behavioral success U . Across both families, every victim model improves U over the no-skill baseline while GPT-5.6-Terra falls below the no-skill baseline in SR . Overall, victim-model capacity influences recoverability, but family-specific behavioral consistency appears to matter at least as much as victim model size.

RQ2: Observability. To isolate the effect of observability, we evaluate all three threat levels using the same frozen sequence of crafted tasks for `claude-opus-5`. As shown in Table 7, moving from Output to Trace increases SR from .400 to .567 and U from .764 to .807. The corresponding normalized metrics improve more substantially, with NSR increasing from .273 to .804 and NU from .716 to .870. Differential performs similarly to Trace, but is lower by 2.3 SR points and .3 U points, with NSR and NU lower by 7.3 and 1.0 points, respectively. Because Differential exposes strictly more information than Trace, we do not interpret this small reversal as evidence that additional observability is harmful. Instead, the results suggest that task-level tool events already expose most of the information useful for recovering the skill, while access to the stack and a paired no-skill execution provides limited additional benefit under this fixed-task setting. Overall, the primary observability gain comes from execution traces rather than final outputs alone.

RQ3: Transferability. We freeze each reconstructed skill and evaluate it on four deployment models, and four orchestration/tool policy without issuing any additional queries to the victim. Figure 7 reports normalized success recovery (NSR) and normalized behavioral utility (NU).

The experiment result reveals that reconstructed skills are not tied exclusively to the model from which they were extracted, but their portability is strongly asymmetric. The Opus-5 reconstruction is the most broadly transferable: it




Figure 6: Ablation across different victim model size.

remains useful across all four deployment models and, notably, performs better on GPT-5.6-Sol than on its source-matched deployment. The Kimi-K3 reconstruction exhibits a more selective form of transfer, performing only moderately on several deployments but transferring especially well to GLM-5.3. By contrast, the GPT-5.6-Sol reconstruction is comparatively brittle, failing to provide measurable benefit on Opus-5 and transferring only weakly to GLM-5.3. These non-diagonal successes indicate that matching the source and deployment models is neither necessary nor sufficient for strong transfer. Instead, some reconstructed procedures appear to be broadly executable, whereas others remain dependent on model-specific execution behavior.

NSR and NU further expose two distinct notions of transfer. In several cases, the deployed model can use a reconstructed skill to recover task success without reproducing the source victim’s behavioral profile. For example, the Kimi-K3 reconstruction retains moderate NSR on Opus-5 and GPT-5.6-Sol, but its NU drops sharply, suggesting that these models reach successful outcomes through behavior that differs substantially from the original skill. The opposite pattern also occurs: the Opus-5 reconstruction preserves relatively high behavioral utility on GLM-5.3 despite limited success recovery. Thus, cross-model execution may preserve either the functional outcome or the behavioral characteristics of a skill without preserving both. This distinction would be obscured by evaluating transfer using task success alone.

Tool/orchestration-policy transfer. We further vary the tool and orchestration policy used to execute the reconstructed skill. As shown in Table 8, *deepagents* performs best, reaching *SR/U* of .600/.833 and *NSR/NU* of .909/.965, closely approaching the original-skill reference. *agno* provides the next strongest result at .467/.755, whereas *claude_agent_sdk* and *openai_agents* both obtain an SR of .400 but substantially lower behavioral utility. These differences are not explained by query count alone: *claude_agent_sdk* uses the largest number of victim calls, yet obtains the lowest NU, while *deepagents* achieves the strongest result with moderate victim calls. Overall, portability depends not only on the deployment model but also on whether the execution policy

Table 8: Tool/Orchestration Policy Transfer results.

Tool/Orchestration Policy	<i>SR/U</i> (avg.)	NSR	NU	Victim Calls Issued
<i>deepagents</i>	.600/.833	.909	.965	219
<i>claude_agent_sdk</i>	.400/.631	.273	.234	355
<i>openai_agents</i>	.400/.667	.273	.364	179
<i>agno</i>	.467/.755	.486	.682	177

Table 9: Defenses evaluated against Daydreaming.

ID	Defense	Source	Acts on
D0	None	—	—
D1	Query rewriting + instruction defense	[1]	Prompt
D2	5-gram output filter	[33]	Reply/trace
D3	PSM shield appending	[17]	Prompt
D4	Advertisement minimization	[14]	Skill description

can faithfully realize the reconstructed skill.

7 Potential Defenses

Every experiment in this paper already enables a three-part disclosure guard: an extraction-input detector, the Skill-Guard5 non-disclosure instruction [28], and an output filter for copied protected text. We additionally add four alternative defenses that act at different points in the service. D1 rewrites the customer’s task and adds a non-disclosure instruction [1]. D2 removes replies or trace records that share a protected 5-gram with the hidden skill [33]. D3 appends the PSM shield to the system prompt [17]. D4 shortens the public skill card to its task and routing cues, removing implementation hints such as mechanism names and constants.

We use *claude-opus-5* as the victim, *gemma-3.7-flash* as the attacker, Output access, and the default Daydreaming configuration. We use the authors’ configurations and apply each defense on top of D0 (the original defense). We restrict the study to defenses compatible with black-box hosted models; methods requiring weights, embeddings, attention states, or token log-probabilities are outside this deployment setting. Table 9 summarizes the four alternative defenses.

Table 10 reports the same task-averaged success rate (*SR*) and behavioral utility (*U*) used throughout the evaluation.




Figure 7: Victim model transfer; Transfer entries report NSR/NU.

Table 10: Held-out effectiveness of skills reconstructed under each defense. SR and U use the definitions in Section 6.1.

ID	SR	U
D0	.286	.395
D1	.308	.621
D2	.308	.367
D3	.400	.707
D4	.308	.638

Table 11: Attack resources under each defense, summed over seven skills. Q_T and Q_A denote victim-task and attacker-model calls.

ID	Q_T	Q_A	Attacker USD	Victim USD [†]
D0	138	1128	.223	78.84
D1	156	1154	4.676	100.82
D2	117	922	.305	68.52
D3	115	913	.202	70.16
D4	131	955	.080	72.12

Because each defense requires a new reconstruction run, D0 is the matched reference for this experiment; the rows should not be compared with a reconstruction from a different run. Only D2 lowers U , from .395 to .367, and it does not lower SR. D1, D3, and D4 instead yield higher U than D0. Thus, none of the four additions reduces both measures of reconstructed-skill effectiveness.

This limited effect follows from what the defenses inspect. D1 targets extraction-shaped task requests, whereas Daydreaming submits ordinary customer tasks; it caused eight model refusals but recorded no blocked input or filtered result. D2 acts directly on returned information and therefore intervenes more often: it filtered 18 of 179 replies (10.1%) and redacted 271 trace records. The latter redactions are not visible at Output and therefore do not change this experiment’s observations. Even so, the remaining task results were sufficient to reconstruct a skill with SR/ U of .308/.367. D3 changes instruction following rather than the information contained in legitimate task results, and D4 removes only the attacker’s initial hints.

The additions can change cost without stopping the attack.

Table 11 shows that D1 raises attacker spend from \$0.22 to \$4.68 and victim-side cost from \$78.84 to \$100.82 across seven skills, yet its reconstruction is more useful than D0’s. D2 provides the only measured utility reduction—2.8 percentage points—but also lowers the number of victim calls and does not reduce SR. Defenses centered on suspicious requests or copied text therefore do not directly address the cumulative behavioral information revealed through legitimate task execution. Protecting this *work path* remains an open problem.

8 Discussion

What does it mean to “steal” a skill? Daydreaming does not claim to recover the vendor’s exact implementation. Indeed, Proposition 4.1 shows that exact source recovery is generally unidentifiable from execution observations alone. Instead, we adopt the functional notion of theft from model extraction: the attacker obtains a substitute asset that reproduces economically valuable behavior without recovering the original implementation [27]. A reconstructed skill may differ in filenames, code structure, or implementation details while preserving the decisions users pay for. Conversely, textual similarity alone does not imply correct execution. Accordingly, we treat held-out behavioral utility as the primary evaluation metric and structural similarity only as supporting evidence. From the provider’s perspective, the key loss is not disclosure of SKILL.md, but the creation of a portable substitute for the hosted capability.

Programmability and obfuscation. A natural defense is to move sensitive skill logic from prompts and reference files into provider-controlled code exposed through a narrow typed interface. Withholding traces [30] and obfuscating client-visible components [23] can hide filenames, control flow, tables, and intermediate state, reducing the structural signals available to an attacker. However, this does not eliminate behavioral leakage: if adaptive queries still reach a deterministic interface with precise outputs, black-box identification remains possible. Effective protection therefore also

requires limiting output precision and constraining or auditing adaptive queries. These measures add implementation cost and may reduce debuggability, auditability, or utility, while sufficiently informative outputs may still enable functional reconstruction.

9 Conclusion

We presented Daydreaming, an execution-only attack for reconstructing hidden agent skills through ordinary task interactions. Across multiple skills and victim models, Daydreaming recovers substantial held-out functionality even under Output-only access, without directly requesting the protected skill. Our results show that hiding skill files and blocking disclosure are insufficient when normal task execution itself reveals enough behavioral evidence for reconstruction. Protecting hosted agent skills therefore requires defenses that address behavioral leakage through the work path, not only direct disclosure.

Open Science

To support reproducibility, we will release the benchmark, evaluation harness, reconstruction pipeline, prompts, experiment configurations, and scripts used to reproduce the main results. We will also provide the reconstructed skill artifacts and per-task evaluation outputs where redistribution is permitted, together with model and API version information, query budgets, and random seeds. For third-party models, tools, or skill assets that cannot be redistributed, we will provide identifiers and instructions sufficient to recreate the corresponding experiments. During review, these materials are withheld to preserve anonymity; upon publication, we will make the artifact publicly available in accordance with USENIX’s artifact and open-science guidelines.

Ethical Consideration

This work studies the reconstruction of proprietary agent skills, which can have legitimate uses for auditing, interoperability, and understanding model behavior, but can also facilitate unauthorized replication of deployed capabilities. We therefore evaluate the attack only in controlled settings using benchmarked or researcher-accessible skills and do not target private user data, credentials, or production systems. We avoid releasing sensitive vendor-specific artifacts that would enable direct misuse, and focus the paper on general attack mechanisms, measurable security properties, and defenses. Our goal is to expose a previously underexplored confidentiality risk in hosted agent systems so that providers can better reason about observability, query access, and skill protection. We encourage use of the released artifacts for reproducibility and defensive research, and users remain responsible for complying with applicable licenses, terms of service, and authorization requirements.

B Theory of Reconstruction

This appendix proves Proposition 4.1 and records supporting results that are not needed to follow the attack. The results bound what the observation channels permit; they do not assume that Daydreaming attains the bounds. Exact source equality below means equality of a canonical skill tree—its paths and file bytes—rather than incidental archive metadata.

B.1 Interactive Observational Equivalence

Fix an access level $\ell \in \{1, 2, 3\}$ and let Q be the admissible customer tasks. Before round t , an attacker has history $h_{t-1} = (x_1, z_1, \dots, x_{t-1}, z_{t-1})$, chooses $x_t \in Q$ using any randomized policy, and receives observation z_t . A skill S induces the conditional observation kernel

$$K_\ell^S(\cdot \mid h_{t-1}, x_t) = \Pr[Z_t \in \cdot \mid H_{t-1} = h_{t-1}, X_t = x_t, S], \quad (5)$$

A Evaluation Details

Table 12: Default Daydreaming parameters.

Parameter	Default
Seeded properties	14–18
Elements per grouped probe	≤ 4
Stage-1 refinement rounds	4
Stage-1 content attempts / probe	2
Threshold candidates / bisections	$\leq 4 / 2$
Convention alternatives	2–4
Package hypotheses	6
Initial branches / criteria per file	$\leq 3 / \leq 5$
Aspect score / generations	0–10 / 3
Total target budget / package	96
Explore / discriminate / refine	64 / 12 / 20
Stage-3 method	EGAE
File admission	Victim-attested evidence
Victim / attacker output cap	4,096 / none
Victim / attacker temperature	.2 / .7
Victim / attacker top- p	.95 / .95

Table 13: Tool policy of each victim carrier. Agno exposes no filesystem or shell tool; its skill loader is the only tool set.

Capability	Available tools
deepagents (ver. 0.7.6)	
File inspection	ls, read_file, glob, grep
File modification	write_file, edit_file, delete
Program execution	execute
Task delegation	task
claude_agent_sdk (ver. 0.2.139)	
File inspection	Read, Glob, Grep
File modification	Write, Edit
Program execution	Bash
Skill invocation	Skill
openai_agents (ver. 0.20.0)	
File inspection	list_files, read_file
Program execution	run_bash
agno (ver. 2.9.0)	
Skill loading	get_skill_instructions, get_skill_reference, get_skill_script

Table 14: Descriptive characteristics of the seven controlled skill packages. File counts exclude the instruction file.

Skill package	Description	Instr. tokens	Files	Bytes	Tools
xlsx	Spreadsheet creation, editing, analysis, and formula recalculation.	2,650	2	18,362	1
pddl-skills	PDDL loading, plan synthesis, and correctness verification.	718	4	4,672	0
pcap-analysis	PCAP analysis and network statistics with tested Python utilities.	3,818	1	23,660	1
threat-detection	Detection thresholds for scans, denial-of-service, and beaconing.	1,344	0	5,136	0
cvss-score-extraction	CVSS extraction from vulnerability sources with fallback handling.	2,368	0	9,163	0
trivy-offline-vulnerability-scanning	Offline Trivy vulnerability scanning without Internet access.	1,706	0	7,180	0
vulnerability-csv-reporting	Structured CSV security reports with filtering and formatting.	2,859	0	12,202	0

Table 15: Comparison with prior attacks and baselines. Each cell reports SR/NSR above U/NU .

Method	Threat level	Victim (SR/NSR above U/NU)			Resources		
		claude-opus-5	gpt-5.6-sol	kimi-k3	QT	QA	USD/skill
No skill (shared)	Oracle	.314/.000	.566/.000		N/A	N/A	N/A
Original skill (shared)	Oracle	.629/1.000	.843/1.000		N/A	N/A	N/A
Daydreaming	Output	.400/.273	.371/.182	.543/.727	31.3–32.8	160–209	3.47–15.07
BBS [†]	Output	.225/–.284	.236/–.249	.167/–.468	12	17	.0096–.0130
SigLeak	Aug. trace	.485/–.295	.443/–.446	.424/–.515	6.8–7.2	10.0–11.2	2.07–10.14
Fixed probes	Output	.433/.378	.333/.060	.367/.168	40	78.43–117.71	2.21–19.87
One-pass synthesis (shared)	No victim	.450/–.421	.371/–.707	.480/–.313	0	1	.0083
		.533/.696	.600/.909	.333/.060			
		.640/.266	.637/.255	.269/–1.076			
		.167/–.468					
		.368/–.718					

NSR and NU are unclipped and use the shared no-skill/original macro anchors .314/.629 and .566/.843, respectively.

[†] The input detector rejected 251/252 scheduled BBS target attempts before victim-model execution.

which includes victim randomness and persistent state. Two skills with the same public card are observationally equivalent at level ℓ , written $S \equiv_{\ell} S'$, if

$$K_{\ell}^S(\cdot \mid h, x) = K_{\ell}^{S'}(\cdot \mid h, x) \quad (6)$$

for every admissible x and every history h possible under either skill. This history-conditioned definition is necessary

because the attacker chooses later tasks from earlier results. It is equivalent to requiring every adaptive randomized policy to induce the same distribution over complete transcripts.

Proof of Proposition 4.1.. Condition on the attacker’s private random coins, making its query policy and estimator deterministic functions of the observed history. We prove by induction that every transcript prefix has the same distribution

Table 16: Candidate per-task results across source victim models. The attacker is `gemini-3.7-flash`, the deployment model is `glm-5.3`, and task cells report SR_b/U_b . Summary SR/U averages all five tasks; NSR and NU use the shared no-skill and original macro anchors.

Source victim (family/scale)	Protein	Airport	TPP	DAPT	SDA	SR/U (avg.)	NSR	NU	Q_T	Deploy.
claude-opus-5 (Anthropic/L)	1.000/1.000	.143/.500	.857/.857	.000/.714	.000/.750	.400/.764	.273	.716	229	.948
claude-sonnet-5 (Anthropic/M)	.667/.833	1.000/1.000	.667/.667	.000/.333	.000/.750	.467/.717	.486	.545	214	.882
claude-haiku-4.5 (Anthropic/S)	.333/.667	.333/.667	1.000/1.000	.000/.619	.000/.750	.333/.740	.060	.628	159	1.000
gpt-5.6-sol (OpenAI/L)	.857/.929	.286/.571	.571/.643	.000/.398	.143/.786	.371/.665	.182	.358	219	1.000
gpt-5.6-terra (OpenAI/M)	.000/.500	.000/.167	1.000/1.000	.000/.619	.000/.750	.200/.607	-.363	.147	200	1.000
gpt-5.6-luna (OpenAI/S)	.667/.833	1.000/1.000	1.000/1.000	.000/.500	.000/.417	.533/.750	.696	.664	170	1.000
kimi-k3 (Moonshot/L)	1.000/1.000	.000/.500	1.000/1.000	.000/.602	.714/.929	.543/.806	.727	.868	220	1.000
gemini-3.7-flash [†] (Google/S)	1.000/1.000	.000/.333	.333/.333	.000/.214	.000/.500	.267/.476	-.150	-.327	191	1.000
No skill (shared)	.571/.786	.000/.357	1.000/1.000	.000/.153	.000/.536	.314/.566	.000	.000	-	1.000
Original (shared)	.714/.857	.286/.571	1.000/1.000	1.000/1.000	.143/.786	.629/.843	1.000	1.000	-	.980

NSR and NU are unclipped and use the shared no-skill/original macro anchors .314/.629 and .566/.843, respectively.

[†] This row reuses the attacker model as the source victim and is excluded from the seven-victim summary.

Table 17: Candidate Spearman correlations between structural similarity and outcomes. U denotes graded utility, SR denotes strict binary success, and intervals are cluster-bootstrap 95% CIs.

Predictor	Outcome	p	95% CI
End-to-end ROUGE-L	U	.037	[-.454, .737]
End-to-end ROUGE-L	SR	-.225	[-.547, .544]
File-tree F1	U	-.051	[-.529, .365]
File-tree F1	SR	-.001	[-.367, .388]
Skill text cosine	U	.145	[-.546, .349]
Skill text cosine	SR	-.070	[-.579, .401]
Structure F1	U	.054	[-.471, .632]
Structure F1	SR	-.160	[-.482, .495]

under the two skills. The empty histories agree. If the histories through round $t - 1$ agree, the policy chooses the same next task for each realized history, and Equation 6 gives the same conditional law for the next observation. Integrating over the common history law proves the inductive step. Averaging over the private coins covers randomized attackers. The same argument applies to any finite budget or almost-surely finite stopping rule. Hence the estimate has one common distribution μ under both skills. Under an equal prior on distinct S_0, S_1 ,

$$\Pr[\hat{S} = S_I] = \frac{1}{2}\mu(S_0) + \frac{1}{2}\mu(S_1) \leq \frac{1}{2}.$$

□

The premise holds at all three levels whenever the admissible format permits content that the runtime neither consults nor allows to affect execution, persistent state, or any disclosed observation. Modify only such observationally inert content. The skilled task result is unchanged at Output, the skilled trace is also unchanged at Trace, and Differential merely adds the same known stack and an unskilled execution independent of that content.

B.2 Value of Stronger Access

Because o_2 is a projection of o_1 and o_3 is a projection of o_2 , a stronger level can always ignore its extra evidence and simulate a weaker one.

Proposition B.1 (Access-level monotonicity) *Fix a prior over skills, a loss function, and a budget B . Let $R_\ell^*(B)$ be*

the smallest expected loss attainable by any adaptive attacker at level ℓ . Then

$$R_1^*(B) \leq R_2^*(B) \leq R_3^*(B).$$

For exact identification under an equal prior, an adjacent inequality is strict whenever a pair is observationally equivalent at the weaker level but distinguishable with positive advantage at the stronger level.

Proof.. A stronger-level attacker projects every observation to the weaker view and runs the weaker-level policy unchanged, proving each non-strict inequality. For the strict case, Proposition 4.1 gives error 1/2 for the colliding pair at the weaker level, while the distinguishing stronger observation yields error below 1/2. □

This proposition concerns the best attainable risk, not every realized run of Daydreaming: an implemented heuristic can still make a worse decision when given more evidence.

B.3 What the Public Card Can Determine

The length of a card alone implies no uncertainty: a short identifier could uniquely name a skill. A card-only limit therefore requires a population model. Let $S \sim \pi$ be drawn from a fixed deployment population, or from a preregistered empirical benchmark prior, and let $D = c(S)$ be its exact public card. Let $C = \mathbf{1}(S)$, where $\mathbf{1}$ is a prespecified finite partition based on canonicalized verifier outcomes on the finite held-out suite

under the evaluation's fixed seeds. Thus $H(C) < \infty$. We say the population has *card ambiguity* when

$$\Pr \left[\max_c \Pr(C = c \mid D) < 1 \right] > 0. \quad (7)$$

Proposition B.2 (Card-only identification bound) *Every possibly randomized estimator $\hat{C}$ that observes only D obeys*

$$\Pr(\hat{C} = C) \leq \mathbb{E}_D \left[\max_c \Pr(C = c \mid D) \right]. \quad (8)$$

Exact behavioral-class identification has positive Bayes error if and only if Equation 7 holds. Moreover, $H(C \mid D) = H(C) - I(C; D)$, and card ambiguity implies $H(C \mid D) > 0$.

Proof.. Condition on $D = d$. If $q(c \mid d)$ is the estimator's output distribution, then

$$\begin{aligned} \Pr(\hat{C} = C \mid D = d) &= \sum_c q(c \mid d) \Pr(C = c \mid D = d) \\ &\leq \max_c \Pr(C = c \mid D = d). \end{aligned}$$

Averaging proves Equation 8, and choosing a posterior mode attains equality. The bound is below one exactly when the posterior is non-degenerate on a positive-probability set of cards. For discrete C , that condition is also equivalent to positive conditional entropy. $\square$

For any bounded reconstruction reward $r(S, P) \in [0, 1]$, define the Bayes-optimal card-only value

$$V_{\text{card}} = \mathbb{E}_D \left[\sup_P \mathbb{E}[r(S, P) \mid D] \right].$$

Conditional optimization shows that every card-only rule has expected reward at most V_{card} . The metadata-only baseline is one tested card-only heuristic, not the Bayes-optimal rule. Its population expected score is at most V_{card} , and its reported finite-sample score estimates that expectation. A gain over it establishes improvement over that implementation, not over every possible card-only reconstruction. If every exact card is unique under the chosen empirical prior, card ambiguity fails and we do not apply the identification claim to that population.

B.4 Adaptivity for a Hidden Cutoff

Proposition B.3 (Single-threshold adaptivity gap)

Suppose a task exposes a controllable statistic $m(x) \in [0, 1]$ and the skill returns $y(x) = \mathbf{1}[m(x) \geq b]$ for an unknown cutoff b . With B tasks, adaptive bisection guarantees $|\hat{b} - b| \leq 2^{-(B+1)}$. Every deterministic non-adaptive schedule fixed before observing any result has worst-case error at least $1/(2(B+1))$.

Proof.. After B bisections, the surviving interval has width 2^{-B} , so its midpoint has error at most $2^{-(B+1)}$. A non-adaptive

schedule fixes B points, which partition $[0, 1]$ into at most $B + 1$ intervals. One interval has width at least $1/(B + 1)$; all cutoffs inside it produce the same answer vector, so any estimate has error at least half that width for some cutoff. $\square$

This is a theorem only for the stated monotone single-threshold family. It motivates sequential cutoff tests but does not claim a general exponential gap for multi-parameter skills.

B.5 A Finite-Budget Information Bound

Let $\mathcal{H} = \{S_1, \dots, S_M\}$, $M \geq 2$, be a finite comparison class with one public card, and let J be uniform on $\{1, \dots, M\}$. For a level ℓ , history h , task x , and distribution ρ on skill indices, consider the experiment that draws $J \sim \rho$ and then $Z \sim K_\ell^{S_J}(\cdot \mid h, x)$. We restrict to histories on which every kernel in the support of ρ is specified. Define the largest information available from one victim call as

$$C_\ell = \sup_{\rho, h, x} I_\rho(J; Z), \quad (9)$$

where the supremum ranges over admissible histories and tasks. Logarithms are natural.

Proposition B.4 (Adaptive finite-budget bound) *For any randomized attacker making at most B adaptive victim calls and any estimator $\hat{J}$ from the complete transcript,*

$$\Pr(\hat{J} \neq J) \geq \left[1 - \frac{BC_\ell + \log 2}{\log M} \right]_+, \quad (10)$$

where $[a]_+ = \max\{a, 0\}$. The worst-case error over $\mathcal{H}$ is at least the same bound.

Proof.. Let $T = (X_1, Z_1, \dots, X_B, Z_B)$ and include the attacker's independent random seed R . Pad an early-stopped run with a fixed null task and a J -independent null observation. Given H_{t-1} and R , the policy for choosing X_t is the same under every J , so $I(J; X_t \mid H_{t-1}, R) = 0$. The chain rule therefore gives

$$\begin{aligned} I(J; T, R) &= \sum_{t=1}^B I(J; Z_t \mid H_{t-1}, R, X_t) \\ &\leq BC_\ell. \end{aligned}$$

For the inequality, conditioning on a realized history, seed, and task produces some posterior ρ over J and the kernel experiment used to define C_ℓ . Fano's inequality yields Equation 10. Maximum error is at least average error under the uniform prior. $\square$

This is a Bayes bound under the stated prior and therefore a worst-case-over-class consequence, not a lower bound for every fixed skill. We do not claim it is numerically binding at $B = 43$ or $B = 96$: that would require a certified upper bound on C_ℓ over the admissible task family.

C Complete Attack Algorithms

This appendix specifies the default attack used in the headline experiments. It follows Algorithm 1: Stage 1 tests properties, Stage 2 compares candidate skill plans in an adjacent-pair bracket, and Stage 3 completes and refines the selected files. Optional ablation branches are omitted. Every operation marked *attacker-side* uses the attacker model, a shadow agent, or local tools and makes no victim call.

We use one record format throughout. A completed experiment adds $\omega = (s, x, o, \delta, e)$ to O , where s is the stage, x is the task actually sent, o is the victim observation allowed at access level ℓ , δ is the resulting decision or update, and e contains attacker-side shadow results or local-test evidence. $\text{FINAL}(o)$ returns the victim’s final task result. $\text{PAIRS}(O)$ projects records to distinct $(x, \text{FINAL}(o))$ pairs with usable results. $\text{PRIORPAIRS}(O)$ takes the two longest usable Stage 2 pairs, then the two longest nonduplicate Stage 1 pairs, and ignores results shorter than 200 characters. READSTRONGEST checks visible executed code and tool output first, a locally runnable returned file second, and returned text last.

Victim-call accounting. SUBMITTASK is the only routine that contacts the skilled victim. A logical experiment normally uses one transmission. If the first result is unusable, the routine may shorten the task and retry once; both transmissions are charged to the current stage budget. At Differential access, PROJECT also includes the matched skill-off result. That reference execution is priced separately, while B counts skilled-victim transmissions as defined in Section 4.2.

Algorithm 2 Victim submission and Stage 1 property inference.

```

1: procedure SUBMITTASK( $x, \ell, b$ )
2:   if  $b = 0$  then
3:     return  $(x, \perp, b)$ 
4:   end if
5:    $y \leftarrow \mathcal{V}_S^L(x); b \leftarrow b - 1$ 
6:   if  $y$  is usable then
7:     return  $(x, \text{PROJECT}(y, \ell), b)$ 
8:   end if
9:    $x' \leftarrow \text{SHORTEN}(x)$ 
10:  if  $x' = x$  or  $b = 0$  then
11:    return  $(x, \perp, b)$ 
12:  end if
13:   $y' \leftarrow \mathcal{V}_S^L(x'); b \leftarrow b - 1$ 
14:  if  $y'$  is usable then
15:    return  $(x', \text{PROJECT}(y', \ell), b)$ 
16:  end if
17:  return  $(x', \perp, b)$ 
18: end procedure

19: procedure INFERPROPERTIES( $d, \ell, B_1$ )
20:    $\Gamma \leftarrow \text{SEEDPROPERTIES}(d, n_{\text{seed}})$ 
21:   give each  $c \in \Gamma$  an id, type, proposed text, depth 0, and status UNPROBED
22:    $P \leftarrow \emptyset; O \leftarrow \emptyset$ 
23:   for  $r = 0, 1, 2, 3$  do
24:      $L \leftarrow$  unprobed properties of depth  $r$ , ordered by type and id
25:     for all groups  $g$  of at most four properties in  $L$  while  $B_1 > 0$  do
26:       for all  $c \in g$  do
27:          $C(c) \leftarrow n_{\text{alt}}$  mutually exclusive values; value 0 restates  $c$ 
28:       end for
29:        $x \leftarrow \text{DESIGNTASK}(d, g, \{C(c) : c \in g\})$ 
30:       if no valid  $x$  then
31:         mark  $g$  PROBE-FAILED; continue
32:       end if
33:        $(x, o, B_1) \leftarrow \text{SUBMITTASK}(x, \ell, B_1)$ 
34:       if  $o = \perp$  then
35:         mark  $g$  PROBE-FAILED; continue
36:       end if
37:        $u \leftarrow \text{READSTRONGEST}(o, x, \{C(c) : c \in g\})$ 
38:        $z_0 \leftarrow \text{SHADOWNOSKILL}(x)$ 
39:       for all  $c \in g$  do
40:         set  $\delta(c)$  to CONFIRMED if  $u(c) = C(c)_0$ , REFUTED if another value matches, else UNDETERMINED
41:         retain only property details present in  $o$ , not details supplied by  $x$ 
42:         if  $r < 3$  then
43:           add at most one new testable property grounded in  $o$  at depth  $r + 1$ 
44:         end if
45:       end for
46:       append  $(1, x, o, \delta, \{z_0\})$  to  $O$ ; harvest new terms and filenames from  $o$ 
47:     end for
48:   end for
49:    $P \leftarrow$  grounded records with confirmed, refuted, or undetermined status
50:    $(P, O) \leftarrow \text{RECOVERCUTOFFS}(d, P, \ell, B_1, O)$ 
51:    $R_1 \leftarrow \text{PAIRS}(O); I \leftarrow \text{HARVESTINTERFACES}(R_1)$ ; append  $I$  to  $P$ 
52:    $(P, O) \leftarrow \text{RECOVERCOUNTINGRULES}(d, P, I, \ell, B_1, O)$ 
53:    $A \leftarrow$  filenames in victim observations minus names introduced by their tasks
54:   return  $(P, O, A)$ 
55: end procedure

```

▷ attacker-side

▷ attacker-side

▷ attacker-side generalist

Table 18: Stage 1 targeted tests. These routines use the same submission, observation, and no-skill comparison rules as Algorithm 2.

Detail	Crafted task	Decision and stopping rule
Numeric cutoff	For each of at most four proposed decisions, test seven ordered cases over a plausible interval while holding other inputs fixed. Narrow the interval once around a single decision change.	Require at least three decided cases and at most one change in direction. If every case receives the same decision, shift the interval once; otherwise report undetermined. A valid literal in visible executed code replaces the midpoint after task values, trivial constants, and out-of-range values are removed.
Visible interface	Make no new victim call. Parse stored returned code and execution records for imports, definitions, argument shapes, commands, and paths.	Remove names supplied by the crafted task, merge repeated observations, and retain occurrence counts and source tasks. Unnamed or unexecuted helpers remain unknown.
Counting rule	For each of at most three operations, construct a small input on which its 2–4 proposed rules predict different exact totals.	Make no call if any predictions coincide. Otherwise retain the unique rule matching every returned total within 10^{-6} ; report undetermined when none or several match.

Algorithm 3 Stage 2 adjacent-pair comparison of candidate skill plans.

```

1: procedure SELECTCANDIDATE( $d, P, A, O, \ell, B_2$ )
2:    $U \leftarrow n_H$  representative customer-task patterns proposed from  $d$  and  $P$  ▷ attacker-side
3:   for all  $u_i \in U$  in generation order do
4:     draft  $H_i = (m_i, \mathcal{R}_i)$  from  $P$ , using  $u_i$  to encourage a distinct plan
5:     give every supporting file a relative path, purpose, and content sketch; insert all  $A$ 
6:   end for
7:    $\mathcal{H} \leftarrow [H_1, \dots, H_{n_H}]$ 
8:   while  $|\mathcal{H}| > 1$  do
9:      $N \leftarrow []$ 
10:    for  $i = 1, 3, 5, \dots, |\mathcal{H}| - 1$  do
11:       $(H_a, H_b) \leftarrow (\mathcal{H}[i], \mathcal{H}[i+1])$ 
12:       $D(H_a, H_b) \leftarrow$  at most eight differences that would change a task result ▷ attacker-side
13:      if  $D(H_a, H_b) = \emptyset$  then
14:        append TIEBREAK( $H_a, H_b, A$ ) to  $N$ ; continue
15:      end if
16:       $x_{a,b} \leftarrow$  DESIGNTASK( $d, D(H_a, H_b)$ )
17:      if no valid  $x_{a,b}$  then
18:        append TIEBREAK( $H_a, H_b, A$ ) to  $N$ ; continue
19:      end if
20:       $(x_{a,b}, o, B_2) \leftarrow$  SUBMITTASK( $x_{a,b}, \ell, B_2$ )
21:      if  $o = \perp$  then
22:        append TIEBREAK( $H_a, H_b, A$ ) to  $N$ ; continue
23:      end if
24:       $y_v \leftarrow$  FINAL( $o$ )
25:       $y_a \leftarrow$  SHADOWWITHPLAN( $H_a, x_{a,b}$ );  $y_b \leftarrow$  SHADOWWITHPLAN( $H_b, x_{a,b}$ )
26:       $(w, J, \Delta) \leftarrow$  COMPARE( $y_v, y_a, y_b, D(H_a, H_b)$ )
27:       $H_w \leftarrow$  TIEBREAK( $H_a, H_b, A$ ) if  $w$  is tied, else the plan selected by  $w$ 
28:       $H_l \leftarrow$  the other plan
29:      if  $J \neq \emptyset$  or  $\Delta \neq \emptyset$  then
30:         $H_w \leftarrow$  REVISE( $H_w, H_l, J, \Delta, P, A$ )
31:      end if
32:      append  $(2, x_{a,b}, o, \{J, \Delta, H_w\}, \{y_a, y_b\})$  to  $O$ 
33:      append the revised  $H_w$  to  $N$ 
34:    end for
35:    if  $|\mathcal{H}|$  is odd then
36:      append its last plan unchanged to  $N$  ▷ bye
37:    end if
38:     $\mathcal{H} \leftarrow N$ 
39:  end while
40:  return the sole survivor  $H^*$  and  $O$ 
41: end procedure

42: procedure TIEBREAK( $H_a, H_b, A$ )
43:   prefer greater coverage of  $A$ , then fewer total files, then  $H_a$ 
44:   return the preferred plan
45: end procedure

```

Algorithm 4 Stage 3 per-file refinement and offline assembly.

```

1: procedure REFINFILES( $d, H^*, P, O, \ell, B_3$ )
2:    $F[\text{SKILL.md}] \leftarrow$  the full instruction draft in  $H^*$ 
3:   for all supporting-file sketches  $f$  in  $H^*$  do
4:      $F[f] \leftarrow$  complete self-contained content expanded from its path, purpose, sketch, and  $P$ 
5:   end for
6:    $R \leftarrow \text{PRIORPAIRS}(O)$ 
7:    $B_3$  and  $O$  are shared and atomically updated by SUBMITTASK
8:   for all supporting files  $f$  with at most three parallel workers do
9:      $F[f] \leftarrow \text{REFINEONE}(d, f, F[f], R, P, O, \ell, B_3)$ 
10:  end for
11:   $I \leftarrow$  signatures, command options, and headings parsed from completed supporting files
12:   $F[\text{SKILL.md}] \leftarrow \text{REFINEONE}(d, \text{SKILL.md}, F[\text{SKILL.md}], R, P, O, \ell, B_3, I)$ 
13:  verify that  $F$  retains every path selected in Stage 2
14:  return  $F$ 
15: end procedure

16: procedure REFINONE( $d, f, v_0, R, P, O, \ell, b, I = \emptyset$ )
17:    $K_f \leftarrow$  3–5 short evaluation criteria; use accuracy and completeness if parsing fails
18:    $V_f \leftarrow \{v_0\}$  plus distinct valid versions that change each of the first two criteria
19:   reject versions that are malformed, non-self-contained, or change a recovered constant
20:    $D_f \leftarrow$  at most eight differences among  $V_f$  that would change a task result
21:    $T_f \leftarrow \emptyset; E_f \leftarrow \emptyset$ 
22:   if  $D_f \neq \emptyset$  and  $b > 0$  then
23:      $x_f \leftarrow \text{DESIGNTASK}(d, D_f)$ 
24:     if  $x_f$  exists then
25:        $(x_f, o, b) \leftarrow \text{SUBMITTASK}(x_f, \ell, b)$ 
26:       if  $o \neq \perp$  then
27:          $t_f \leftarrow \text{FINAL}(o); t_{f,v} \leftarrow \text{SHADOWWITHVERSION}(v, x_f)$  for every  $v \in V_f$ 
28:          $T_f \leftarrow \{(x_f, t_f)\}$ ; append  $(3, x_f, o, D_f, \{t_{f,v} : v \in V_f\})$  to  $O$ 
29:       end if
30:     end if
31:   end if
32:   if  $f$  is executable then
33:      $E_f \leftarrow$  local dependency checks and behavioral tests
34:   else
35:      $T_f \leftarrow T_f \cup R$ 
36:   end if
37:   if  $T_f = \emptyset$  and  $E_f = \emptyset$  then
38:     mark  $f$  UNDETERMINED; return the first valid version in  $V_f$ 
39:   end if
40:    $Q_f \leftarrow \emptyset$ 
41:   for all  $v \in V_f$  do
42:      $(s(v), g(v)) \leftarrow \text{SCOREOFFLINE}(v, T_f, E_f, K_f)$ ; assign neutral score 5 to unmeasured criteria
43:     add  $(v, s(v), g(v))$  to  $Q_f$ 
44:   end for
45:   for  $r = 1, 2, 3$  do
46:      $p \leftarrow$  version winning the most criteria; break ties by mean score
47:      $q \leftarrow$  a lowest-scoring criterion of  $p$ , rotating tied criteria by round
48:      $v' \leftarrow$  revise only  $q$  using its observed mismatch and, for SKILL.md,  $I$ 
49:     if  $v'$  is invalid, non-self-contained, or changes a recovered constant then
50:       continue
51:     end if
52:     score  $v'$  as above
53:     if  $\text{mean}s(v') > \text{mean}s(p)$  or no member of  $Q_f$  is strictly higher on every measured criterion then
54:       add  $v'$  and its scores to  $Q_f$ 
55:     end if
56:   end for
57:   discard invalid versions; for executable files, first maximize valid local-test score
58:   return the remaining version with highest mean score
59: end procedure

60: procedure ASSEMBLE( $F, O, P$ )
61:   write every file in  $F$  under its selected relative path
62:   for all reconstructed documents  $f \in F$  do
63:      $G \leftarrow$  fixed spreadsheet ranges and fixed missing-value placeholders found by regex
64:     for  $i = 1, 2, 3$  while  $G \neq \emptyset$  do
65:        $f' \leftarrow$  rewrite only  $G$  as input-dependent range and missing-data rules, using relevant tasks in  $O$ 
66:       if  $f'$  has fewer flagged patterns,  $|f'| \geq 0.55|f|$ , and loses no recovered interface, capability, or protected constant then
67:          $f \leftarrow f'$ ; break
68:       end if
69:     end for
70:   end for
71:    $m' \leftarrow$  in SKILL.md, replace only absolute write destinations with caller-chosen output placeholders
72:   if  $m'$  drops no relative filename or non-destination absolute path then
73:     use  $m'$ ; otherwise keep the original instruction file
74:   end if
75:   return the materialized skill  $\hat{S}$ 
76: end procedure

```

▷ defined above; zero victim calls

▷ offline; zero victim calls

D Prompt Templates

For reproducibility, this appendix reproduces the static prompt templates from the implementation used by the default attack. The listings are included directly from the source files, so the paper and implementation cannot silently diverge. They preserve the implementation’s original internal wording (for example, “work product” and “artifact”); the main text uses the simpler terms *task* and *task result*.

Only the crafted customer task produced by a task-design template is sent to $\mathcal{V}_S$. Every other template below is sent to the attacker model, or is used to create a local test. In particular, the victim never sees a candidate skill, comparison prompt, score prompt, mutation prompt, or reconstruction. Table 19 specifies the dynamic fields inserted around these static templates.

Table 19: Dynamic fields supplied to the default prompt templates. We use the notation of Section 5 and Appendix C: x is a crafted task, o is a victim observation, H_i is a candidate skill plan, V_f is a set of versions of file f , and I is the interface parsed from completed sibling files.

Phase	Templates, runtime fields, and recipient
Stage 1 core	<i>Templates:</i> _SEED, _DESIGN, readout, grounding, child, cluster. <i>Fields:</i> public name/description; property c and alternatives $C(c)$; x ; o ; prior property text. <i>Recipient:</i> attacker model.
Stage 1 controls	<i>Templates:</i> _SELF, execution discriminator, trace readout. <i>Fields:</i> x ; returned code; offered branches; client-visible executed code and output. <i>Recipient:</i> attacker model or local sandbox.
Stage 1 details	<i>Templates:</i> cutoff finder/task/readout; convention finder/task. <i>Fields:</i> public card; tested-property map; observed interface; case values, fixed covariates, labels, and candidate totals. <i>Recipient:</i> attacker model; only the generated task goes to victim.
Stage 2 drafting	<i>Templates:</i> use cases, candidate draft, merge. <i>Fields:</i> public card; all of P ; one representative task; all filenames in A ; winner, loser, point results, and observed gaps. <i>Recipient:</i> attacker model.
Stage 2 comparison	<i>Templates:</i> conflict, task design, shadow, result comparison. <i>Fields:</i> plans H_a, H_b ; result-changing differences $D(H_a, H_b)$; task $x_{a,b}$; victim result y_v ; shadow results y_a, y_b . <i>Recipient:</i> attacker model; only $x_{a,b}$ goes to victim.
Stage 3	<i>Templates:</i> expand, criteria, branch, shadow score, mutation, dependency, self-test. <i>Fields:</i> path/purpose/sketch; P ; versions V_f and differences D_f ; task x_f ; victim result t_f and version results $t_{f,v}$; prior task-result pairs; observed mismatch; I ; protected constants. <i>Recipient:</i> attacker model or local sandbox; only x_f goes to victim.
Assembly	<i>Templates:</i> generalization and output-path rewrite. <i>Fields:</i> reconstructed file; detected fixed ranges/placeholders; relevant tasks from O ; protected constants from P ; detected absolute write destinations. <i>Recipient:</i> attacker model.

Excluded ablation prompts. The listings omit prompts that are not executed by the default configuration: the Stage 1 interview channel; the Stage 1 reuse/delegation additions; the Stage 2 victim-as-judge and no-conflict arms; the legacy Stage 3 routine that asks the victim to critique or score a draft; and experimental dependency recovery and file-pruning

passes. These arms remain in the released code and are named in their respective ablation configurations.

D.1 Stage 1 Prompts

Listing 1: Property seeding (_SEED_SYS).

```
_SEED_SYS = (
    "You are reverse-engineering an AI agent SKILL from ONLY its public metadata (
      name + "
      "description). A SKILL is a know-how package: a SKILL.md (capabilities, rules,
      procedures, exact "
      "domain terminology) plus bundled reference docs and helper scripts. Enumerate
      the concrete "
      "ELEMENTS you would expect this skill to contain, so they can each be probed
      and confirmed. "
      "Be specific and domain-grounded, not generic. Return JSON only:\n"
      '{"elements":[{"type":"<one of ' + "|".join(ELEMENT_TYPES) + ">","text":"<a
      specific '
      'hypothesized fact/feature, one sentence->"}]}\n'
      "Aim for 14-18 elements spread across ALL the types (every element will be
      verified, so do not "
      "pad with near-duplicates). `bundled.asset` elements should name a plausible
      reference doc or "
      "script the skill likely ships (e.g. 'a contract_risk_scanner.py script', 'a
      term-sheet "
      "reference doc').")
)
```

Listing 2: Separating-task design (_DESIGN_SYS).

```
_DESIGN_SYS = (
    "You are reverse-engineering a hidden expert SKILL installed in an AI assistant
    , and you may "
    "only interact with it by giving it ORDINARY WORK to do. You are given one or
    more hypothesized "
    "ELEMENTS of that skill. Design a single piece of work whose RESULT reveals
    which way the hidden "
    "skill actually does things.\n\n"
    "For EACH element, first enumerate 2-4 mutually exclusive, concrete BRANCHES --
    the genuinely "
    "different ways this part of the work could be done. BRANCH 0 MUST be the
    element's own claim "
    "restated operationally; the remaining branches are realistic alternatives a
    competent "
    "practitioner might take instead.\n\n"
    "Then write ONE first-person message from a real user with a real job. RULES,
    all load-bearing:\n"
    "- NEVER ask how it works, what it uses, why, or whether it does X. Ask for the
    WORK PRODUCT.\n"
    "- Bake the discriminating inputs into the message: paste concrete sample data,
    file listings, "
    "values, snippets, or a precise specification, chosen so that different
    branches must produce "
    "visibly different results.\n"
    "- Demand a concrete deliverable: the finished script, the final numbers, the
    transformed rows, "
    "the completed configuration. Say you want the artifact itself, ready to use.\n\n"
    "- ASK FOR THE ARTIFACT PLUS ITS WRITTEN COMPANION, never one instead of the
    other: the script "
    "AND the short handover note a colleague would need to run it, the numbers AND
    the one-paragraph "
    "method note, the config AND its comments. A runnable artifact is what
    discriminates the branches; "
    "a written companion NAMES the tools, options, conventions and terms the
    artifact merely uses, "
    "and a professional is expected to hand over both. This costs the same single
    request.\n"
    "- One message, self-contained, no meta-commentary, and it must read like a
    paying customer "
    "asking for help with their job.\n"
    "- Keep it under 400 words.\n\n"
    "Output EXACTLY this format, nothing else:\n"
    "<<<JOB>>>\n"
    "(the full user message, including any inline data)\n"
    "<<<SPEC>>>\n"
    '{"elements":[{"id":<the element id you were given>,'
    '"branches":["<branch 0 = the element restated>","<alternative>","..."],'
    '"tell":<how the deliverable looks under each branch, concretely>}']}\n'
)
```

Listing 3: Stage 1 readout, grounding, grouping, and controls.

```
_READ_SYS = (
    "You are reading the WORK PRODUCT an expert assistant returned for a job, in
    order to infer how "
    "it does the work. You are given the job that was sent, the deliverable that
    came back, and for "
    "each question a list of mutually exclusive BRANCHES plus what each one looks
    like.\n\n"
    "For every question, decide which branch the deliverable actually took. Judge
    only from what is "
    "PRESENT in the deliverable -- the code it wrote, the values it produced, the
    steps it performed, "
```

```
    "the names and options it used. If the deliverable does not settle it, say `
    indeterminate`; a "
    "guess is worse than an admission, because a wrong branch is recorded as fact
    downstream.\n\n"
    "Return JSON only:\n"
    '{"verdicts":[{"id":<id>,"branch":<"copied verbatim from that question\'s
    branches, or '
    'indeterminate">,"evidence":<"a short verbatim span from the deliverable that
    shows it">}]}'
)

_GROUND_SYS = (
    "Rewrite ONE claim about a hidden expert skill so that it states what an
    observed work product "
    "actually demonstrates.\n\n"
    "You are given the claim, the branch the work product took, and the work
    product itself. Write "
    "ONE dense, self-contained statement, 1-3 sentences, in the work product's OWN
    exact terms: copy "
    "verbatim the function and parameter names, option flags, step order, numeric
    thresholds, file "
    "names and formats that APPEAR IN THE WORK PRODUCT.\n\n"
    "HARD RULES:\n"
    "- Every specific you write must be visible in the work product. Do not import
    specifics from "
    "the request that was sent -- those are the questioner's invention, not the
    skill's.\n"
    "- No meta-commentary about the reply, the assistant, or the process.\n"
    "- If the branch is `indeterminate`, restate the original claim unchanged.\n"
    "Output ONLY the statement."
)

_CHILD_SYS = (
    "A work product from a hidden expert skill has just been observed. Propose NEW
    specific claims "
    "about that skill which the work product exposes and which are NOT already in
    the list you are "
    "given. A claim is one sentence, concrete, and checkable by giving the skill
    another piece of "
    "work: a named procedure step, an exact term or threshold, a specific option or
    file.\n\n"
    "Return JSON only: {'children':[{'type':'<">capability|constraint|procedure|
    terminology|
    'io.format|bundled.asset|rule.paradigm>',"text":"'<claim>'}]}\n"
    "Prefer 0-2 high-value claims; return [] if nothing new is exposed. Do not pad,
    and do not "
    "restate the request that was sent."
)

_CLUSTER_SYS = (
    "Group hypothesized claims about one expert skill into batches that could each
    be settled by a "
    "SINGLE realistic piece of work. Claims belong together when one job would
    naturally exercise "
    "all of them at once -- same stage of the workflow, same kind of input, same
    artifact produced. "
    "Every claim must appear in exactly one group, and no group may exceed the
    given size.\n"
    "Return JSON only: {'groups':[<id>,<id>,...],[...]]}'
)

_SELF_SYS = (
    "You are a competent, experienced practitioner with no special tooling beyond
    your own general "
    "knowledge. Do the job the user asks for and return the deliverable they asked
    for, in full. No "
    "preamble, no caveats about what you can or cannot do."
)

_DISCRIM_SYS = (
    "Write a Python program that RUNS someone's delivered work and reports which of
    several possible "
    "approaches it took. Judging by reading is unreliable; you are going to decide
    by execution.\n\n"
    "The delivered work is saved next to your program as `./artifact` (and also
    under its natural "
    "filename). It is the code you were shown. Your program must:\n"
    " 1. Execute or import the artifact so that whatever it produces actually gets
    produced -- "
    "create any input files it expects, in the working directory, from scratch.\n"
    " 2. Inspect the RESULT (the file it wrote, the values it returned, the
    numbers it printed), "
    "not the artifact's source text, wherever the question can be answered that way
    .\n"
    " 3. For each question below, print exactly one line:\n"
    "    BRANCH <id>: <index of the matching branch>\n"
    "    or, when the evidence does not settle it:\n"
    "    BRANCH <id>: unknown\n"
    "    Print `unknown` rather than guessing -- a wrong branch is recorded as
    fact downstream.\n"
    "RULES: there is NO network. Wrap every question in try/except and report `
    unknown` on an "
    "exception; never let the program abort before printing every line. Print
    nothing else.\n"
    "Output ONLY the Python file, in one code block."
)
```

Listing 4: Trace readout (_TRACE_READ_SYS).

```
_TRACE_READ_SYS = (
    "You are shown a customer's job, and then the RECORD OF WHAT AN ASSISTANT
    ACTUALLY DID to "
    "answer it: the code it executed and the output that code produced. This is
    machine-recorded "
    "activity, not the assistant's description of its activity.\n\n"
    "For each question, say which of the offered branches the RECORDED ACTIVITY
    demonstrates. "
    "Decide only from what the code did and what it produced. If the recorded
    activity does not "
    "settle a question, answer \"indeterminate\" -- a guess from the surrounding
    prose is worse "
    "than no answer, because the whole value of this evidence is that it is not a
    description.\n\n"
    "Return JSON: {\n\"verdicts\": [{\n\"id\":<int>,\n\"branch\":\n\"one of the offered
    branches, or \"
    \"indeterminate>\", \"evidence\":\n\"<the line of code or the output that shows it
    >\"]}]})")
```

Listing 5: Batched grounding (_GROUND_GROUP_SYS).

```
_GROUND_GROUP_SYS = (
    "Rewrite each of several claims about a hidden expert skill so that each states
    what an observed "
    "work product actually demonstrates, and separately harvest the work product's
    vocabulary.\n\n"
    "You are given the claims (with ids), the branch each one's evidence took, and
    the work product "
    "itself. For EACH claim write ONE dense, self-contained statement, 1-3
    sentences, in the work "
    "product's OWN exact terms: copy verbatim the function and parameter names,
    option flags, step "
    "order, numeric thresholds, file names and formats that APPEAR IN THE WORK
    PRODUCT.\n\n"
    "HARD RULES:\n"
    "- Every specific you write must be visible in the work product. Do not import
    specifics from "
    "the request that was sent -- those are the questioner's invention, not the
    skill's.\n"
    "- No meta-commentary about the reply, the assistant, or the process.\n"
    "- If a claim's branch is 'indeterminate', do NOT restate the claim. Write only
    what the work "
    "product actually shows about that topic, and if it shows nothing about it,
    leave that claim's "
    "section EMPTY. An unsettled guess restated as prose is indistinguishable
    downstream from an "
    "observed fact, which is the one outcome that must not happen.\n\n"
    "Then list the distinctive NAMES the work product uses that a generalist would
    not have "
    "supplied -- function, class, parameter, flag, constant, file and format names,
    and fixed domain "
    "phrases. Copy them character-for-character, comma-separated, names only, at
    most 40.\n\n"
    "Output EXACTLY this format and nothing else, one block per claim, in the order
    given:\n"
    "<<<ID 7>>>\n"
    "(the rewritten statement for claim 7, or nothing at all)\n"
    "<<<ID 12>>>\n"
    "(the rewritten statement for claim 12, or nothing at all)\n"
    "<<<TERMS>>>\n"
    "name_one, name_two, name_three"
)
```

Listing 6: Numeric-cutoff prompts.

```
_FIND_SYS = (
    "You are reverse-engineering a hidden expert SKILL installed in an AI assistant.
    Below is a map "
    "of what has been observed about it so far.\n\n"
    "Find the places where this skill must be applying a CALIBRATED NUMERIC CUTOFF:
    a decision it "
    "makes routinely whose answer flips at some particular value of some measurable
    quantity -- a "
    "threshold, a minimum count, a maximum ratio, a tolerance, a confidence level,
    a size limit.\n"
    "These are the parts of an expert procedure that cannot be re-derived from
    general knowledge, "
    "because the author chose them. Prefer decisions that:\n"
    " - produce a YES/NO or a category, not a free-text opinion;\n"
    " - would be made the same way on any input, dozens of times a day;\n"
    " - hinge on a quantity that can be stated as a single number in a record.\n\n"
    "BE GENEROUS WITH THE BRACKET. Set 'low' at least an order of magnitude below
    your best guess "
    "and 'high' at least an order of magnitude above it, and round them to human
    numbers. A bracket "
    "that misses the cutoff wastes the entire probe -- every case falls the same
    way and nothing is "
    "learned. A bracket that is too wide costs only resolution, and resolution is
    recovered for free "
    "by a second pass inside whatever interval the first pass finds. When the
    quantity is a COUNT of "
```

```
"things, assume the author's cutoff may be in the hundreds or thousands even if
a small number "
"feels natural.\n\n"
"Return ONLY a JSON array. Each entry:\n"
' {\n\"verdict\": \"<the yes/no call, phrased as the practitioner would phrase it
>\",\n\"
\"quantity\": \"<the single measurable quantity that decides it, with its unit
>\",\n\"
\"unit\": \"<unit or empty string>\", \n\"
\"low\": \"<a number clearly BELOW any plausible cutoff>\", \n\"
\"high\": \"<a number clearly ABOVE any plausible cutoff>\", \n\"
\"direction\": \"high-triggers\" | \"low-triggers\", \n\"
\"covariates\": \"<every OTHER attribute a record needs, and the value each
must take so that \"
\"it is unambiguously in the triggering range and cannot be what decides the
call>\" }\n\"
"Order the array by how load-bearing the cutoff is. At most {limit} entries. No
prose."
```

```
_LADDER_SYS = (
    "You are giving an expert assistant an ORDINARY PIECE OF WORK. It is a routine
    triage: a batch "
    "of records, each of which the expert must give its standard yes/no call on.\n\n"
    "Write the work request. RULES -- every one of them matters:\n"
    "- Present exactly the cases you are given, each with the LABEL you are given,
    in the order "
    "given. Do not add, drop, merge or reorder cases.\n"
    "- Each case must carry the assigned value of the varying quantity, and must
    carry EVERY other "
    "attribute at the value stated in the covariates note, IDENTICAL across all
    cases. The only "
    "thing that differs between two cases is the varying quantity. This is what
    makes the batch "
    "readable; it is not negotiable.\n"
    "- Ask for the call on every case, in a compact table or list, one line per
    case, using the "
    "case labels. Ask for the call ONLY -- no methodology, no explanation of how
    the call is made, "
    "no thresholds, no formulas, no discussion of the criteria. You want the
    verdicts, and asking "
    "for the reasoning turns an ordinary job into an interrogation the assistant
    may refuse.\n"
    "- Never mention that the cases were constructed, that they vary along a scale,
    that you are "
    "probing anything, or that you are interested in where the answer changes. This
    is a normal "
    "day's batch of records from a normal day's work.\n"
    "- Do not state or hint at what the right answers are.\n"
    "Output ONLY the work request itself, ready to send. No preamble."
```

```
_READ_SYS = (
    "Below is a work product: an expert's routine calls on a batch of labelled
    cases. Report what "
    "call the expert gave EACH case.\n"
    "Report only what is written. If the work product does not give a case a clear
    call -- it was "
    "skipped, hedged, or the reply refused -- report it as 'unknown'. Never infer a
    case's call from "
    "its neighbours, and never substitute your own judgement for the expert's.\n"
    "Output one line per case, exactly:\n"
    "CASE <label>: yes\n"
    "CASE <label>: no\n"
    "CASE <label>: unknown\n"
    "Nothing else."
```

Listing 7: Counting-convention prompts.

```
_FIND_SYS = (
    "You are reconstructing a hidden expert skill. You are given a map of what it
    does and the "
    "callable surface observed in code its expert wrote.\n\n"
    "Find up to {limit} OPERATIONS whose SEMANTICS are underdetermined -- where two
    or more "
    "reasonable implementations would give DIFFERENT numbers on the same input. The
    classic shapes: "
    "are categories overlapping or mutually exclusive; is a total inclusive or
    exclusive of a "
    "sub-category; is a rate per-observation or per-unit-time; is a boundary case
    counted in or out; "
    "is a pair counted once or in both directions.\n\n"
    "Do NOT propose an operation whose behaviour is obvious or standard -- those
    cost a query and "
    "return nothing. Propose only where a competent engineer could genuinely go
    either way.\n\n"
    "For each, return an object with:\n"
    " operation -- the operation in the skill's own words, one line\n"
    " quantity -- what the expert will report, e.g. 'packets per protocol'\n"
    " input -- a SMALL, fully specified input, described the way a customer
    would describe "
    "their data. It must be small enough to work by hand and must be built so the
    candidates "
    "disagree on it. Spell out every record.\n"
    " labels -- the labels the answer will be broken down by, as an array of
    short strings\n")
```

```

" candidates -- 2 to 4 objects, each {name, rule, predicted}. `predicted` is
an object mapping "
"EVERY label to the exact number that candidate yields on `input`. Compute them
yourself.\n\n"
"HARD REQUIREMENT: the `predicted` objects must be pairwise different. If you
cannot design an "
"input that separates the candidates, omit the operation entirely --
behaviourally identical "
"candidates are not worth a query.\n\n"
"Return ONLY a JSON array."
)

_JOB_SYS = (
"Write the message a paying customer would send to have this work done. It must
read as "
"ordinary work: a person with data who wants the breakdown. Include the input
data verbatim and "
"in full -- the numbers are the whole point.\n\n"
"Ask for the result as one line per category in the form `LABEL: number`, the
way anyone would "
"ask for a summary table. Ask for nothing else: no methodology, no explanation
of how the "
"categories are defined, no mention of any document, file, tool or instruction.
Never hint that "
"the definitions themselves are of interest.\n\n"
"Return ONLY the customer's message."
)

```

D.2 Stage 2 Prompts

Listing 8: Representative-task and candidate drafting.

```

_USECASE_SYS = (
"Given a skill's metadata and a reverse-engineered element map, list distinct
real-world USE "
"CASES it serves. Each use case is an IDENTITY (who is asking -- their role and
setting) plus a "
"TASK (the concrete job they bring). These seed structurally different
reconstructions of the "
"same skill, so make them genuinely different from each other -- different
seniority, different "
"scale, different part of the workflow -- while all staying inside what the
metadata describes.\n\n"
+ _LEGEND_SLOT + "\n\n"
"Return JSON only: {'use_cases': [{'persona': '<identity>', 'job': '<concrete task
>'}]}'
)

# Output uses SENTINELS, not one big JSON: embedding a full multi-line markdown
SKILL.md inside a
# JSON string routinely yields invalid JSON (unescaped newlines/quotes), which made
every hypothesis
# fail to parse and crashed the tournament. The SKILL.md is emitted raw between
markers; only the
# small filetree is JSON.
_HYP_SYS = (
"You are reconstructing a hidden agent SKILL package from its metadata, a
reverse-engineered "
"element map, and ONE target use case. Produce a complete, concrete HYPOTHESIS
of the package: "
"a full SKILL.md (YAML frontmatter name+description, then what it does / when
to use / the key "
"rules, procedures, and EXACT domain terminology / a quick-start), and a
committed FILETREE -- the "
"reference docs and helper scripts it most likely ships, each with a real
relative path, a "
"one-line purpose, and for scripts a sketch of the functions/params/CLI it
would expose. Bias the "
"structure toward the target use case for diversity, but keep it faithful to
the element map."
"\n\nNONE RULE ABOUT WHAT NOT TO WRITE. Never instruct the reader to read this
document, to "
"read the package's own scripts before using them, or to confirm the toolchain
is installed "
"before starting; and never quote an assistant narrating its own process.
Describe what each "
"tool DOES and exactly how to call it. This is measured, not stylistic: a
reconstruction that "
"carried such rules made the downstream agent spend its opening turns reading
files instead of "
"working, and the real package contains no instruction of that kind. A victim's
process "
"commentary is not part of its expertise.\n\n"
+ _LEGEND_SLOT + "\n\n"
"Output EXACTLY this format, nothing else:\n"
"<<<SKILLMD>>>\n"
"(the full SKILL.md markdown, raw -- do NOT escape or wrap it)\n"
"<<<FILETREE>>>\n"
' [{"path": "references/x.md", "purpose": "<one line>", "sketch": "<functions/params/
CLI or sections>"} ]'
)

```

Listing 9: Stateful winner update (_MERGE_SYS).

```

_MERGE_SYS = (
"You are the REWRITER. Improve the WINNING skill hypothesis using the losing
hypothesis and an "
"expert's corrections. Keep the winner's structure; fold in any correct
procedures, exact "
"terminology, rules, or files the loser had or the expert named; fix everything
the expert "
"flagged. Do not shrink the package; make it more complete and more accurate."
"\n\nNONE RULE ABOUT WHAT NOT TO WRITE. Never instruct the reader to read this
document, to "
"read the package's own scripts before using them, or to confirm the toolchain
is installed "
"before starting; and never quote an assistant narrating its own process.
Describe what each "
"tool DOES and exactly how to call it. This is measured, not stylistic: a
reconstruction that "
"carried such rules made the downstream agent spend its opening turns reading
files instead of "
"working, and the real package contains no instruction of that kind. A victim's
process "
"commentary is not part of its expertise.\n\n"
"Output EXACTLY this format, nothing else:\n"
"<<<SKILLMD>>>\n"
"(the full revised SKILL.md markdown, raw)\n"
"<<<FILETREE>>>\n"
' [{"path": "references/x.md", "purpose": "<one line>", "sketch": "<...>"} ]'
)

```


Listing 10: Candidate comparison prompts.

```

.CONFLICT_SYS = (
    "You are given two candidate reconstructions of the SAME hidden expert skill:
    each is a set of "
    "instructions plus a list of supporting files. Identify where they genuinely
    DISAGREE about how "
    "the work is done -- a different procedure or step order, a different tool/
    library/command, a "
    "different threshold or default, a different output format, a different helper
    artifact being "
    "used or not used.\n\n"
    "Only list disagreements that would show up in the RESULT of doing real work.
    Ignore wording, "
    "ordering of prose, formatting, and anything that would produce an identical
    work product.\n"
    'Return JSON only: {"conflicts":[{"point":"<what they disagree about, one line
    >"},
    "a":"<what A predicts, concretely>","b":"<what B predicts, concretely>"}]}\n'
    "Return an empty list if the two would produce indistinguishable work."
)

_JOB_SYS = (
    "Write ONE message from a real user asking an expert assistant to DO A JOB. The
    job must be "
    "chosen so that its finished work product reveals which of several competing
    approaches the "
    "assistant actually takes -- you are given the specific points of disagreement
    .\n\n"
    "RULES, all load-bearing:\n"
    "- NEVER ask how it works, which approach it uses, or to compare anything. Ask
    for the work.\n"
    "- Bake the discriminating inputs into the message: paste concrete sample data,
    a precise "
    "specification, values, or a file listing, chosen so the disagreements must
    surface.\n"
    "- Demand the artifact itself -- the finished script, the final numbers, the
    completed output -- "
    "ready to use.\n"
    "- One self-contained message under 400 words, reading like a paying customer
    with a real job.\n"
    "Output ONLY the message."
)

_SHADOW_SYS = (
    "You are an expert assistant. The following is your installed expertise; follow
    it exactly -- its "
    "procedures, its terminology, its tools, its defaults -- even where your own
    instincts would "
    "differ, because your job is to behave as this expertise specifies.\n\n"
    "=== YOUR INSTALLED EXPERTISE ===\n{skill}\n=== END ===\n\n"
    "Do the user's job and return the deliverable they asked for, in full. No
    preamble."
)

_COMPARE_SYS = (
    "A real expert did a job and returned a work product. Two candidate
    reconstructions of that "
    "expert's know-how were each used to do the SAME job, producing two more work
    products. Decide "
    "which reconstruction PREDICTED the real one better.\n\n"
    "Judge only on the listed points of disagreement, and only on what is visible
    in the work "
    "products -- the steps taken, the tools and options used, the values produced,
    the output shape. "
    "Ignore prose style, length, and politeness.\n\n"
    "Then list what the REAL work product did that the winning reconstruction did
    NOT predict: the "
    "concrete procedures, exact terminology, tools, options, thresholds and
    artifacts it revealed. "
    "Preserve verbatim specifics; this is the material used to repair the winner.\n\n"
    'Return JSON only: {"winner":"A|B|tie","per_point":[{"point":"<...>","matched
    ":"A|B|neither"}]}'
    "corrections":"<what the real work showed that the winner missed>"
)

```

D.3 Stage 3 Prompts

Listing 11: Per-file criteria and mutation.

```

_ASPECTS_SYS = (
    "Given a skill artifact (a reference doc or a helper script) and its context,
    list the distinct "
    "CRITERIA on which its correctness/completeness should be judged -- the facets
    a domain expert "
    "would check. For a script: interface/CLI, core algorithm, libraries/constants,
    I/O, output "
    "format. For a doc: each major procedure/rule/terminology area it should cover.
    Return JSON only: "
    '{"aspects":[{"criterion>"}, ...]} (3-5 criteria). Each MUST be at most 8 words
    -- a short '
    "noun phrase, NOT a sentence or a paragraph."
)

_MUTATE_MD_SYS = (
    "Revise a draft skill artifact using an expert's corrections. Keep the format
    and all correct "
    "content; fix every inaccuracy the expert flagged and add the exact procedures,
    terminology, "
    "thresholds, parameters, and formats they named. Do not shorten or genericize.
    Output ONLY the "
    "revised artifact (no preamble, no code fence around the whole thing unless it
    is a script)."
)

_MUTATE_CODE_SYS = (
    "Revise a draft {ext} script using an expert's corrections so it matches how
    the tool should "
    "actually work. Keep all correct logic; fix the interface/CLI, algorithm,
    libraries, constants, "
    "I/O paths, and output format the expert named. Output MUST be a single
    COMPLETE, syntactically "
    "valid {ext} file in one code block, nothing else."
)

```

Listing 12: Shadow-result scoring.

```

_SHADOW_CMP_SYS = (
    "You are given a JOB, the WORK PRODUCT a domain expert actually returned for it
    , and the WORK "
    "PRODUCT a competent practitioner returned for the SAME job while following a
    set of written "
    "notes. Score how closely the notes made the practitioner reproduce the expert's
    work.\n\n"
    "Judge the substance of the artifact -- the tools and options it used, the
    procedure and its "
    "order, the exact names, formats and thresholds, the shape of the result.
    Ignore wording, "
    "politeness and formatting. A practitioner who produced the same artifact by a
    different route "
    "scores high; one whose artifact would behave differently scores low.\n\n"
    "Score 0-10 on each named criterion. Return JSON only: "
    '{"scores":{"<criterion>":<0-10>}, "gap":"<what the expert did that the notes
    failed to '
    'produce, concrete specifics only>"}'
)

```

Listing 13: Initial file expansion.

```

_EXPAND_SYS = (
    "Write the full initial content of ONE file in a reconstructed skill package,
    from its path, "
    "purpose, and sketch, plus the skill context. Make it complete and concrete (
    real procedures, "
    "exact terminology; for a script, a complete runnable file with the sketched
    interface).\n"
    "SELF-CONTAINED. A script must do the work ITSELF. Never load, read, exec or
    import anything by "
    "absolute path, never use importlib to reach a file on disk, and never write a
    wrapper that "
    "delegates to some other copy of this tool. You have observed where the expert
    keeps its files; "
    "that is a fact about the expert's machine, not an instruction for yours, and a
    reader will run "
    "this file somewhere else entirely. Assume the only things present are this
    file and the "
    "packages it pip-installs.\n"
    "Output ONLY the file content (a script must be a single code block)."
)

```

Listing 14: Alternative-file generation.

```

_BRANCH_SYS = (
    "You are given a draft skill artifact (a reference doc or a helper script) and
    ONE aspect of it "

```

```
"you are unsure about. Produce a DIFFERENT but equally plausible version of the
WHOLE artifact "
"in which that one aspect is resolved another sensible way -- a different
counting convention, "
"threshold, procedure, tool, or output shape -- while everything you are
confident about stays "
"the same. The point is that this version, if followed, would produce a
MATERIALLY DIFFERENT "
"work product on some real job. Keep the format. Output ONLY the artifact (a
script must be a "
"single complete code block, nothing else)."
```

Listing 15: Local dependency and self-test prompts.

```
_DEPS_SYS = (
    "You are given a script. List EXACTLY the environment it needs to run: third-
    party Python "
    "packages it imports (PyPI names, not module names where they differ), and any
    external "
    "command-line programs it shells out to, as the Debian apt package that
    provides them. Standard "
    "library does not count. Return JSON only: "
    '{"pip":["<pypi-name>,..."],"apt":["<debian-package>,..."]}. Empty lists if
    none.'
)

_SELFTEST_SYS = (
    "Write a self-test for a command-line tool, in Python, to check whether the
    tool ACTUALLY DOES "
    "WHAT IT CLAIMS -- not whether it runs without crashing.\n"
    "The tool is at ./artifact in the working directory. Import it or invoke it
    with subprocess, "
    "whichever matches how it is meant to be used.\n"
    "RULES:\n"
    "- Create any input files the tool needs, from scratch, inside the working
    directory.\n"
    "- After invoking it, VERIFY THE OBSERVABLE EFFECT independently of what the
    tool printed. If "
    "it says it transformed a file, reopen that file and check the transformation
    actually "
    "happened. A tool that prints success while doing nothing MUST fail your test.\n"
    "- TEST BEHAVIOUR, NOT COSMETICS. Do not assert on exact exit codes, exact
    wording, or the "
    "exact shape of printed output unless the tool's own documentation states them
    as a contract -- "
    "and even then, parse leniently (search for the value you need, do not demand
    an exact string). "
    "A different but equally correct implementation of the same tool must pass your
    test.\n"
    "- There is NO network. Only test offline behaviour.\n"
    "- Print one line per check, exactly: 'CHECK <short name>: PASS' or "
    "'CHECK <short name>: FAIL - <what was expected vs what was observed>.\n"
    "- Mark each check that verifies the tool's PRIMARY REASON FOR EXISTING by
    starting its name "
    "with 'CRITICAL ' -- e.g. 'CHECK CRITICAL recalculation-populates-values: PASS'.
    Exactly 1 or 2 "
    "checks are critical: the effect that, if absent, makes the tool worthless no
    matter what else "
    "works. Everything else is secondary.\n"
    "- Wrap each check in try/except and report an exception as FAIL with the
    message; never let "
    "the test abort early.\n"
    "- 3 to 6 checks. Put the critical ones first.\n"
    "Output ONLY the Python file, in one code block."
)
```

D.4 Assembly Prompts

Listing 16: Guarded task-specific generalization.

```
_SYS = ""You are cleaning a reconstructed skill document.

The document was rebuilt by observing how an assistant handled ONE specific
customer request. It has
absorbed details of that request that are NOT part of the skill: sample filenames,
sample column
headers, sample values, and hardcoded ranges sized to that one dataset.

Rewrite the document so that:
- Every general rule, procedure, API, library name, script name and requirement is
  PRESERVED VERBATIM
  wherever it is already general.
- Any instruction that is stated in terms of the one example is restated as the
  GENERAL rule it is an
  instance of. A sample filename becomes the general description of that input.
- SHAPE-BEARING LITERALS listed below must not survive in any form. A range bounded
  at a concrete row
  ('B$2:B$9') is sized to one dataset: state how to determine the extent instead,
  or use a whole-column
  reference. A sentinel string chosen for one delivery (writing "N/A" into an empty
  cell) is that
  delivery's choice, not the skill's rule: state the condition to guard, not the
  literal to write, and
  never instruct writing text into a cell whose contents are numeric.
- Nothing is invented. If a passage cannot be generalized without guessing, delete
  that passage
  rather than replace it with a guess.
- EVERY identifier, function name, attribute, library, script and API path that
  appears anywhere in
  the document must still appear in your output. You may move it or restate the
  sentence around it,
  but you may not drop a capability. Dropping one invalidates the whole rewrite.
- Structure, headings and formatting are kept.

Return ONLY the rewritten document, no preamble, no fences around the whole thing
.""
```

Listing 17: Guarded output-path rewrite.

```
DEPATH_SYS = ""You are correcting a skill's SKILL.md before it is given to a new
operator on a
different machine.

The document was written from a transcript of ONE job, and its command examples
have absorbed the
absolute paths that job happened to use. A skill cannot know where a future caller
wants its output
written, so any absolute path that a command WRITES TO must become a placeholder.

Change only that:
- a path a command writes to, or a directory the document tells the operator to
  create for
  results, becomes a placeholder like `<output_dir>` or `<out_file.ext>`;
- a path the deployment genuinely OWNS -- where its own data, models or bundled
  files live, which
  a caller does not choose -- stays exactly as written. Golden skills do carry
  such paths and
  removing them would break the skill.

Keep every domain rule, constant, threshold, schema, flag name and convention
EXACTLY as written.
Do not add rules. Do not shorten. Do not rename files.

Output the corrected SKILL.md ONLY, with no prose and no code fence.""
```

References

- [1] Divyansh Agarwal, Alexander R. Fabbri, Ben Risher, Philippe Laban, Shafiq Joty, and Chien-Sheng Wu. Prompt leakage effect and defense strategies for multi-turn llm interactions, 2024.
- [2] Alibaba and Meta. Open-weight model releases: Qwen3 and Llama. <https://github.com/QwenLM/Qwen3>, <https://github.com/meta-llama/llama-models>, 2026. Accessed 2026-08-22.
- [3] All Hands AI. OpenHands. <https://github.com/All-Hands-AI/OpenHands>, 2026. MIT licensed. Accessed 2026-08-22.
- [4] Amazon and Google. Confidential computing: AWS Nitro enclaves and Google confidential space. <https://docs.aws.amazon.com/enclaves/latest/user/nitro-enclave.html>, 2026. Accessed 2026-08-22.
- [5] Anthropic. Agent skills. <https://platform.claude.com/docs/en/agents-and-tools/agent-skills/overview>, 2026. Accessed 2026-08-22.
- [6] Anthropic. Claude code overview. <https://code.claude.com/docs/en/overview>, 2026. Accessed 2026-08-22.
- [7] Anthropic. Consumer terms of service. <https://www.anthropic.com/legal/consumer-terms>, 2026. Accessed 2026-08-21.
- [8] Tianle Cai, Xuezhi Wang, Tengyu Ma, Xinyun Chen, and Denny Zhou. Large language models as tool makers. In *The Twelfth International Conference on Learning Representations*, 2024.
- [9] Cloudflare. AI gateway. <https://developers.cloudflare.com/ai-gateway/>, 2026. Accessed 2026-08-22.
- [10] Jianing Geng, Ruiqi He, Zekun Fei, Biao Yi, Xuansheng Wu, Ruijie Wang, Zheli Liu, Xia Hu, and Qingkai Zeng. Agent skills matter: Inferring proprietary skills from execution trajectories. *arXiv preprint arXiv:2607.25560*, 2026.
- [11] Google. Gemini API additional terms of service. <https://ai.google.dev/gemini-api/terms>, 2026. Accessed 2026-08-21.
- [12] Google. Gemini CLI: Tools. <https://google-gemini.github.io/gemini-cli/docs/tools/>, 2026. Accessed 2026-08-22.
- [13] Harvey. Evaluation terms of service. <https://www.harvey.ai/legal/evaluation-terms-of-service>, 2026. Accessed 2026-08-21.
- [14] Peichun Hua, Haoxuan Xu, and Mengyuan Li. Behavioral skill reconstruction: Reconstructing hidden functionality from llm agent skills, 2026.
- [15] Bo Hui, Haolin Yuan, Neil Gong, Philippe Burlina, and Yinzhi Cao. PLeak: Prompt leaking attacks against large language model applications. In *Proceedings of the 2024 ACM SIGSAC Conference on Computer and Communications Security*, pages 3600–3614. ACM, 2024.
- [16] Intercom. Fin pricing. <https://fin.ai/pricing>, 2026. Accessed 2026-08-22.
- [17] Huseein Jawad and Nicolas Brunel. Psm: Prompt sensitivity minimization via llm-guided black-box optimization, 2026.
- [18] Masahiro Kaneko and Timothy Baldwin. Bits leaked per query: Information-theoretic bounds for adversarial attacks on LLMs. In *Advances in Neural Information Processing Systems*, volume 38, pages 88992–89016, 2025.
- [19] Xiangyi Li, Yimin Liu, Wenbo Chen, et al. SkillsBench: Benchmarking how well agent skills work across diverse tasks. *arXiv preprint arXiv:2602.12670*, 2026.
- [20] Nym Health. Autonomous medical coding. <https://nym.health>, 2026. Accessed 2026-08-22.
- [21] OpenAI. Skills. <https://developers.openai.com/api/docs/guides/tools-skills>, 2026. Accessed 2026-08-23.
- [22] OpenTelemetry. GenAI observability with OpenTelemetry. <https://opentelemetry.io/blog/2026/genai-observability/>, 2026. Agent and tool conventions provisional. Accessed 2026-08-22.
- [23] David Pape, Sina Mavali, Thorsten Eisenhofer, and Lea Schönherr. Prompt obfuscation for large language models. In *34th USENIX Security Symposium (USENIX Security 25)*, pages 2323–2342, Seattle, WA, August 2025. USENIX Association.
- [24] Zeyang Sha and Yang Zhang. Prompt stealing attacks against large language models. *arXiv preprint arXiv:2402.12959*, 2024.
- [25] Xinyue Shen, Yiting Qu, Michael Backes, and Yang Zhang. Prompt stealing attacks against Text-to-Image generation models. In *33rd USENIX Security Symposium (USENIX Security 24)*. USENIX Association, 2024.

- [26] Yicong Tan, Xinyue Shen, Yun Shen, Michael Backes, and Yang Zhang. On the effectiveness of prompt stealing attacks on in-the-wild prompts. In *2025 IEEE Symposium on Security and Privacy (SP)*, pages 392–410. IEEE, May 2025.
- [27] Florian Tramèr, Fan Zhang, Ari Juels, Michael K. Reiter, and Thomas Ristenpart. Stealing machine learning models via prediction APIs. In *25th USENIX Security Symposium (USENIX Security 16)*, pages 601–618, Austin, TX, August 2016. USENIX Association.
- [28] Zihan Wang, Rui Zhang, Yu Liu, Chi Liu, Qingchuan Zhao, Hongwei Li, and Guowen Xu. Black-box skill stealing attack from proprietary LLM agents: An empirical study. arXiv preprint arXiv:2604.21829, 2026.
- [29] Zora Zhiruo Wang, Jiayuan Mao, Daniel Fried, and Graham Neubig. Agent workflow memory. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 63897–63911. PMLR, 2025.
- [30] Shuwen Xu, Zhitao He, and Yi R. Fung. RedAct: Redacting agent capability traces for procedural skill protection. arXiv preprint arXiv:2606.10813, 2026.
- [31] Yong Yang, Changjiang Li, Qingming Li, Oubo Ma, Haoyu Wang, Zonghui Wang, Yandong Gao, Wenzhi Chen, and Shouling Ji. PRSA: Prompt stealing attacks against Real-World prompt services. In *34th USENIX Security Symposium (USENIX Security 25)*, pages 2283–2302, Seattle, WA, August 2025. USENIX Association.
- [32] Simon Yu, Gang Li, Weiyan Shi, and Peng Qi. PolySkill: Learning generalizable skills through polymorphic abstraction for continual learning. In *The Fourteenth International Conference on Learning Representations*, 2026.
- [33] Yiming Zhang, Nicholas Carlini, and Daphne Ippolito. Effective prompt extraction from language models, 2024.