

Orthogonal Ensembles and Tested Explanations for Performer-Independent Body-Motion Emotion Recognition

Naoto Nishida
The University of Tokyo
Tokyo, Japan
nawta@g.ecc.u-tokyo.ac.jp

Yoshio Ishiguro
The University of Tokyo
Tokyo, Japan
ishiy@acm.org

Abstract—We study body-only, 12-class acted-emotion classification from skeleton motion under leave-performer-out (LPO) evaluation, a hard, underdetermined setting: chance is 8.3%, and a protocol-matched reproduced STGCN++ baseline reaches only $25.73 \pm 4.03\%$ Macro-F1. We show that reliable gains come not from a new architecture but from combining eleven models with orthogonal error modes: under 10-fold LPO cross-validation on the labeled training performers, an equal-weight logit-mean ensemble reaches $36.80 \pm 4.00\%$ per-fold Macro-F1, a protocol-matched +11.07 pp (+43% relative) over the same-split reproduced baseline. Our central contribution is a tested explanation suite: for a strong ensemble member, part-masking and counterfactual edits show (rather than assert) that its decisions *depend* on motion-grounded body-region evidence, and this region saliency *aligns* with rule-based Laban Movement Analysis (LMA) attributes far more than with classical kinematics: region-level saliency–LMA Spearman $\rho = +0.500$ versus $+0.033$, roughly $15\times$, and the alignment holds for the submitted 11-way ensemble itself at $\rho = +0.517$; the audit is post hoc and needs no retraining. The same suite faithfully reports a negative: within-window temporal saliency is diffuse rather than localized.

Index Terms—affective computing, emotion recognition, body movement, skeleton motion, model ensemble, explainability, faithfulness, Laban Movement Analysis

I. INTRODUCTION

The DIEM-A challenge [1] asks for 12-class *acted* emotion recognition from *body motion alone*: no face, no audio, no scene, evaluated across *disjoint performers*. Together these make it underdetermined: chance is 8.3%, and a strong skeleton baseline (STGCN++) reaches only $\sim 25\%$ Macro-F1 under leave-performer-out (LPO) evaluation. Semantically related emotions share kinematic signatures (e.g. jealousy/contempt, shame/guilt) and each performer carries a movement idiolect,

This work was supported by JST BOOST Grant JPMJBS2418, JST Moonshot R&D Grant JPMJMS2012, JST CREST Grant JPMJCR17A3, the commissioned research by NICT Japan Grant JPJ012368C02901, Tateisi Science and Technology Foundation (C) and Telecommunications Advancement Foundation.

Accepted for publication in the 2026 14th International Conference on Affective Computing and Intelligent Interaction Workshops and Demos (ACHIW). © 2026 IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works.

so cross-performer within-class variance can rival within-performer cross-class variance.

Within this setting, intuitive single-model improvements largely do not transfer: supervised-contrastive heads, VLM distillation, post-hoc calibration, and other single-model upgrades failed or regressed under the protocol (§IV, Table I); these negatives shaped a deliberately conservative system.

What did transfer was diversity. Because four inductive-bias families (graph, attention, hybrid/MLP, external pretraining) make *different* mistakes, averaging their raw logits cancels errors that any single family repeats. This equal-weight *logit-mean* ensemble, with skeleton self-supervised pretraining, yields $36.80 \pm 4.00\%$ per-fold Macro-F1 under our study protocol, a protocol-matched +11.07 pp over the same 74-performer reproduced STGCN++ baseline, and the gain tracks the measured orthogonality of member errors, not any one architecture (§V).

Our central methodological contribution: we *test* attributions rather than assert them. For a strong ensemble member, part-masking and counterfactual edits show its decisions *depend* on motion-grounded body-region evidence, and this region saliency *aligns* with rule-based Laban Movement Analysis (LMA) attributes far more than with classical kinematics, at saliency–LMA $\rho = +0.500$ vs $+0.033$, a post-hoc audit needing no retraining; the same alignment holds for the submitted 11-way ensemble itself. The suite returns six explicit verdicts, five positive and one deliberately reported negative, plus a deterministic 0/50-audited narrator (§VI).

Contributions.

- A *tested* explanation suite for skeleton emotion models (part-masking faithfulness, perturbation stability, semantic LMA alignment, counterfactual edits, and a narration audit), returning six explicit verdicts: five positive, one reported negative. Part-masking shows a strong ensemble member’s decisions *depend* on motion-grounded body-region evidence, and that region saliency *aligns* with rule-based LMA attributes (saliency–LMA $\rho = +0.500$ vs $+0.033$), a post-hoc audit needing no retraining (§VI).
- The same suite faithfully reports a negative (diffuse tempo-




Fig. 1. The DIEM-A 12-emotion body-motion challenge (74 train / 18 test performer-disjoint performers; BVH/FBX/C3D + text scenarios) and the proposed pipeline: eleven models spanning four inductive biases (GCN, attention, hybrid/MLP, external pretraining) fused by equal-weight logit-mean, reaching $36.80 \pm 4.00\%$ per-fold Macro-F1 versus the same-split reproduced STGCN++ baseline ($25.73 \pm 4.03\%$). Protocol: 10-fold leave-performer-out on the 74-performer training split; per-fold mean $\pm$ SD throughout.

ral saliency) and a deterministic, audited motion→rationale narrator; we contribute the *method and audit*, not a dataset release (held pending consent/license review).

- A protocol-matched performance result: an orthogonal-error 11-way logit-mean ensemble, $+11.07$ pp / $+43\%$ over the same-split reproduced baseline, with the gain *explained* by measured error-space orthogonality (§V).
- A documented catalog of negative results (Table I) that motivated the conservative design.

Fig. 1 sketches the task and pipeline; the paper develops the two headlines above.

II. RELATED WORK

Skeleton-based recognition and body emotion. Graph-convolutional and attention architectures dominate skeleton action recognition (ST-GCN [2], CTR-GCN [3], STGCN++ and pose-heatmap variants [4], SkateFormer [5]); body-emotion datasets and emotion-from-motion analyses extend the action setting to acted affect [6]–[9]. These models set the single-network state of the art we build on but are typically evaluated within-performer; we report the harder leave-performer-out (LPO) regime.

Self-supervised skeleton pretraining. Masked motion prediction [10] and contrastive skeleton self-supervision [11], [12] transfer representations across datasets, and unified motion encoders pretrained on heterogeneous corpora [13] extend this transfer beyond single-task supervision. We treat frozen external pretraining as one orthogonal inductive-bias family within an ensemble, and report when such transfer does *not* help (Table I).

Explainability for motion models. Prior work explains motion and skeleton classifiers through perturbation and occlusion [14], gradient-based saliency [15], counterfactual edits [16], and semantic motion attributes (e.g. Laban Movement Analysis [9]); a parallel line studies attribution *faithfulness* and *stability* [17], [18]. Most motion-domain studies *assert*

that attributions are meaningful; few test whether the cited evidence actually drives predictions, and fewer still under performer shift. We contribute a *validated audit protocol* rather than a new attribution method: the probes above, screened for faithfulness and stability and reported together with the negatives they return.

III. TASK, DATA AND EVALUATION

Task and data. DIEM-A [1] is acted body-motion emotion recognition over 12 classes (anger, contempt, disgust, fear, joy, sadness, surprise, jealousy, shame, guilt, gratitude, pride). Each clip is a 24-joint skeleton sequence (BVH/FBX/C3D) with a text scenario; models consume a 25-node tensor (the 24 joints plus a virtual root node carrying global position), the resolution at which our part-masking and saliency analyses are reported. Performers are split 74 train / 18 test and are *disjoint* across the split [19]. The training split contains 7,992 clips from 40 Japanese and 34 Taiwanese performers (666 per emotion, balanced across classes) and the test split 1,944 clips from 18 disjoint performers (9 JP, 9 TW); recordings are at 120 Hz with median sequence length ≈ 845 frames, of which we feed every model a fixed 64-frame window ($\approx 7.5\%$ of the median, ≈ 0.53 s) for protocol parity with the official baseline.

Capture provenance. The corpus was recorded with two motion-capture systems: the five earliest Japanese performers (JP_01–JP_05) were captured with a 41-marker OptiTrack rig, and all remaining recordings use the production 57-marker Vicon system [1]. None of the five OptiTrack performers is in the 74-performer training split, so capture hardware is uniform within our cross-validation; the residual capture-*era* stratum is checked in §V by excluding the seven earliest-captured Japanese training performers (JP_06–JP_12).

Evaluation. We evaluate with 10-fold leave-performer-out (LPO) cross-validation on the 74-performer training split and report Macro-F1 (primary) and Accuracy. We fix *one* reporting convention and use it everywhere: scores combine member predictions by *logit-mean* (mean of raw logits, the canonical convention) and are reported as the *per-fold mean $\pm$ SD across the 10 LPO folds*; pooled out-of-fold (OOF) values appear only as a clearly labelled descriptive secondary. This convention is restated in every table and figure caption (Table II).¹

Protocol distinction (stated here, not deferred). The official STGCN++ baseline [19] is a 92-performer full-LPO result ($25.21 \pm 4.49\%$ Macro-F1). Our development numbers use the 74-performer training split (test labels are withheld by the challenge). *Within the same 74-performer protocol our reproduced STGCN++ baseline is $25.73 \pm 4.03\%$ (within one SD of the official $25.21 \pm 4.49\%$), so we treat the official number as an external anchor and report all improvements against the protocol-matched reproduction*; the held-out test score is pending the challenge leaderboard. Consequently the headline improvement is the protocol-matched $+11.07$ pp

¹Per-fold reporting matches the SD convention used by the official and reproduced STGCN++ baselines and supplies the fold-level error bars and bootstrap intervals used throughout ($B=1000$, seed 42); probability-domain aggregation is an internal ranking device only.

(36.80–25.73, same split, same logit-mean $\times$ per-fold convention), never a comparison to the 92-performer official figure.

IV. METHOD

A. Model pool: four inductive-bias families

The pool has eleven members spanning four families with deliberately *different* inductive biases, so their errors are unlikely to coincide: (i) graph-convolutional (STGCN++ [4], CTR-GCN [3], ProtoGCN [20], a Region-Aware ConvTr); (ii) attention (SkateFormer [5]); (iii) hybrid/MLP (Conv1D+Transformer, Keypoint-Pool-MLP); (iv) frozen external pretraining (MotionBERT-Lite [13], C3D-marker-stats, MAMP NTU60-xsub and NTU120-xset [10]). ProtoGCN is a CTR-GCN backbone with a learned per-body-part prototype-matching head; Region-Aware ConvTr and the hybrid/MLP family are part-aware variants of the same Conv1D+Transformer template. The four families encode complementary priors: kinematic-chain *locality*, *long-range position-insensitive co-occurrence*, *pooled spatiotemporal statistics*, and *transferred representations* from generic-motion corpora. The explained model in §VI (Region-Aware, strongest single at $30.05 \pm 3.48\%$) is itself a member of the submitted ensemble.

B. Fusion: equal-weight logit-mean

Given per-member logits $z_m \in \mathbb{R}^{12}$ for M members, the prediction is the argmax of the equal-weight mean of *raw* logits:

$$\hat{y} = \arg \max_c \frac{1}{M} \sum_{m=1}^M z_m^{(c)}. \quad (1)$$

Averaging raw logits before normalisation (a log-domain geometric mean of class scores) keeps confidently-wrong members from dominating. Empirically logit-mean fusion is +1.15 pp Macro-F1 over the probability-averaging variant at no cost; we therefore fix logit-mean as the canonical convention (§V).

C. Pretraining and protocol discipline

One family uses skeleton self-supervised pretraining (masked-motion, MAMP style) transferred frozen: two MAMP backbones pretrained on NTU60-xsub and NTU120-xset respectively, joined by a frozen MotionBERT-Lite encoder and a C3D-marker-statistics encoder. Training and selection follow a strict protocol: 10-fold LPO, fixed seed, fold-wise out-of-fold (OOF) prediction, model selection *within* the training split only, and no access to test labels (withheld by design); ensemble weights are equal (no fitted weighting). In-domain members share the data split, batch size 128, clip length 64 and seed 42, but use model-tuned optimisers: STGCN++, CTR-GCN and ProtoGCN train with SGD at lr 0.2 for 65 epochs without warmup; SkateFormer with AdamW at lr 5×10^{-4} for 65 epochs with a 5-epoch cosine warmup; Region-Aware ConvTr, Conv1D+Transformer and Keypoint-Pool-MLP with AdamW at lr $\in \{1, 4\} \times 10^{-3}$ for 80 epochs with the same warmup. The four frozen externals contribute features and

add < 0.01 M trainable parameters per branch (a linear classification head only). Each fold writes per-clip raw-logit out-of-fold (OOF) arrays in the canonical $(n, 12)$ shape that feeds Eq. 1.

Computational cost and reproducibility. The system is deliberately cheap for an eleven-member ensemble. Seven members are trained in-domain; the four external branches stay frozen with a linear head each, so the total trainable footprint is 12.98 M parameters (Table II), roughly the seven-model sum. Inference is eleven forward passes over a 64-frame clip followed by the parameter-free logit mean of Eq. 1; there are no fitted fusion weights, and a single GPU suffices for training any member and for inference. The explanation suite runs post hoc, at zero accuracy cost and with no retraining. Every number, table, and figure in this paper is produced by a single deterministic regeneration script over the stored per-member OOF arrays.

D. Negatives as design constraints

The conservative design above is what *survived* a broad search; the approaches that did not are reported as constraints, not omitted (Table I): supervised-contrastive, mixture-of-experts, scenario-text alignment and VLM zero-shot/distillation, multi-crop window inference, and post-hoc calibration each failed or regressed; C3D late fusion (-0.59 pp) was associated with a 69.8% country-leakage signal. Effect sizes and CIs live in the table.

V. PERFORMANCE RESULTS

Main result. Table II reports all systems under the single canonical convention defined in §III: logit-mean fusion, per-fold mean $\pm$ SD, 10-fold LPO on the 74-performer split. The submitted 11-way ensemble reaches $36.80 \pm 4.00\%$ per-fold Macro-F1, a protocol-matched +11.07 pp (+43% relative) over the same-split reproduced STGCN++ baseline of $25.73 \pm 4.03\%$; the pooled-OOF value 36.94% appears in Table II as a descriptive secondary. The bootstrap 95% CI [35.90, 37.94] clears the 7-way ensemble CI, and the paired-fold improvement excludes zero in 10/10 folds with a bootstrap 95% CI of [9.86, 12.33] pp. Resampling whole performers rather than folds widens this interval only to [9.14, 12.17] pp, so the gain is neither within ensemble noise nor an artifact of within-performer clip correlation.

Lift path and ablations. Fig. 3 traces the lift, under the one convention, as four stages: $25.7 \rightarrow 30.1 \rightarrow 33.9 \rightarrow 36.8\%$ (baseline $\rightarrow$ best single $\rightarrow$ 7-way $\rightarrow$ final 11-way logit-mean). The intermediate +0.7 pp from frozen external pretraining (MotionBERT-Lite, C3D-marker-stats) and +2.2 pp from two MAMP variants are absorbed into the final stage, justified by member-level orthogonality (quantified below). Two ablations matter. First, ensembling beats the best single model, $30.05 \pm 3.48\%$, by +6.8 pp. Second, logit-mean beats probability-averaging by a free +1.15 pp; the absolute value of the probability-averaging convention serves only for internal ranking and is not reported. This +1.15 pp is not a logit-scale artifact: z-scoring each member to unit variance neutralises any

TABLE I

APPROACHES THAT DID NOT IMPROVE THE SYSTEM, EACH PAIRED WITH ITS METHODOLOGICAL LESSON (NON-CAUSAL WORDING: ASSOCIATED WITH / REGRESSES / DOES NOT IMPROVE). $\Delta F1$ IS THE PAIRED CHANGE VERSUS THE MATCHED BASELINE. THE FULL CATALOGUE IS IN THE SUPPLEMENTARY MATERIAL.

Approach	Configuration	Outcome ($\Delta F1$)	Methodological lesson
Supervised contrastive head	pairwise SupCon, $\lambda=0.05$, batch 128	-11.53 pp, significant	12 classes at batch 128 give too few positives per class, suggesting a per-class center loss may fit better at this scale
Mixture-of-experts fusion	K=4, hand-crafted gradient-free routing	collapses to 6.55% F1	a shared head with random init and 21-D routing is associated with backbone collapse, suggesting a feature adapter, learned routing, and zero-init are needed
Scenario-text alignment	global InfoNCE, 3-fold	-1.42 pp	the projection collapses to performer identity (cross-group retrieval 10.6%)
Part-rationale alignment	cosine text alignment, 3-fold	-0.64 pp, CI [-1.30, -0.09]	the text bottleneck is associated with an F1 ceiling of 9–12%; shortcut-breaking works but yields no F1 lift
VLM zero-shot distillation	12-class, a recent VLM, preliminary	failed in preliminary zero-shot ranking	the true class ranked last (12/12); a vision-language model did not infer emotion reliably from faceless, scene-free skeleton renderings
Contact-marker late fusion	C3D 22-D contact stats, 3-fold	-0.59 pp	the contact features carry a 69.8% country signal, so some performers go out of distribution under LPO, suggesting a domain-invariance objective is needed
Multi-crop window inference	24-setting sweep window	-12 to -17 pp	the model is trained on full-span subsamples, so compact windows are a distribution shift
Post-hoc calibration	nested-LPO, ensemble	7-way 0 to -0.14 pp, not significant	equal-weight argmax is already near-optimal; bias-style calibration did not exceed it in this search




Fig. 2. 12×12 row-normalised pooled-OOF confusion of the 11-way logit-mean ensemble ($n = 7,992$ clips, 74-performer split; rows = true class, rows sum to 100%); the five strongest off-diagonal confusions are boxed. The per-class-by-country companion panel appears in the supplementary material.

single high-norm member yet retains +0.99 pp, and rank-only Borda fusion retains +0.69 pp. All 12 classes improve over the baseline, the weakest (sadness) by +6.1 pp (progression figure in the supplementary material).




Fig. 3. Diversity across the four families builds the gain: stage-by-stage Macro-F1 over the 11-model lift path (10-fold LPO mean $\pm$ SD), baseline $\rightarrow$ best single (Region-Aware) $\rightarrow$ 7-way $\rightarrow$ 11-way logit-mean. Per-class progression and paired-bootstrap CIs are in the supplementary material.

Why diversity helps: error-space orthogonality. The gain comes from disagreement, not from added capacity: the eleven members rarely fail on the same clip. Their pairwise per-sample error correlations are low, all off-diagonal values inside $[0.15, 0.43]$ and lowest for the frozen external-pretraining column, so averaging their logits cancels errors that a single family would share (correlation matrix in the supplementary material). The most-redundant pair, Conv1D+Tr $\leftrightarrow$ Keypoint-Pool-MLP, and the elevated MAMP-NTU60 $\leftrightarrow$ MAMP-NTU120 pair are consistent with the small or negative return of further homogeneous additions (Table I). A leave-one-out (LOO) check on the pooled-OOF logit-mean base of 36.94% confirms no member dominates the lift and no member is redundant: all

eleven per-member deltas are strictly negative, from -0.84 pp for MAMP-NTU60 down to -0.09 pp for CTR-GCN, and all within the $7 \rightarrow 11$ -way lift margin; the full per-member table (with per-stratum versions) appears in the supplementary material. The smallest losses come from graph-convolutional members whose errors a same-family sibling largely covers (CTR-GCN -0.09 , ProtoGCN -0.15 pp), yet the moderately correlated MAMP pair still includes the single largest contribution, -0.84 pp, with -0.61 pp for its sibling; moderate error correlation therefore does not imply redundancy. Removing the entire frozen external-pretraining block at once costs -2.91 pp, so the externals jointly supply essentially the whole $7 \rightarrow 11$ -way lift, distributed across branches rather than carried by one.

Error structure and strata. Fig. 2 shows where the residual errors go: they fall between *semantically confusable* emotions; the five strongest off-diagonal confusions, boxed, include jealousy $\rightarrow$ contempt and guilt $\rightarrow$ sadness/shame. This pattern is consistent with the model’s low maximum confidence ($\sim 62\%$) and the disagreement structure the ensemble exploits. Per-class F1 by performer country is charted in the supplementary material. The JP–TW macro gap (35.3 vs 38.9%) is a *dataset stratum*, not a cultural finding: it is entangled with capture era and performer idiolect. The five OptiTrack-captured performers are absent from the training split (§III), so capture hardware cannot explain the cross-validation gap; as a capture-era check, excluding the seven earliest-captured Japanese training performers shifts pooled-OOF Macro-F1 by only -0.44 pp (36.50 vs 36.94%), so neither the headline nor the stratum hinges on the earliest recordings.

VI. EXPLAINABILITY RESULTS

We do not just visualize what the model attends to; we *test* it. For every claim that the model uses a body region, we mask it, perturb it, or edit its motion and check that the prediction moves. The suite runs on the Region-Aware member of the submitted ensemble and its key tests re-run on the ensemble itself; Table III collects every value with its CI or null and a plain-language reading. Six verdicts, five positive and one deliberately negative: **faithful** (masking the parts ranked important degrades Macro-F1, §VI-A); **stable** (the ranking survives input noise, §VI-B); **semantically grounded** (region saliency matches the Laban vocabulary, for the member and the submitted ensemble alike, §VI-C, §VI-D); **behaviourally corroborated** (motion edits shift predictions in the same part ranking, §VI-E); **grounded narration** (no unsupported claims in the 50 audited cards, §VI-G); and **one reported negative** (within-window temporal saliency is diffuse, §VI-F). The suite is post hoc and adds no accuracy cost; its load-bearing LMA headline rests on the faithfulness and stability verdicts that precede it.

A. Faithfulness: masking the cited regions lowers accuracy

Positive. Masking the parts an attribution calls important degrades Macro-F1 more than masking the same number of “unimportant” parts: the important–reverse AUC gap is

$+0.124 \pm 0.031$ over 6 body parts ($+0.199$ at 25-joint resolution), positive in every fold. Nothing downstream would matter if attributions were decorative; this establishes they are not.

B. Stability: the ranking survives input noise

Positive. Under input noise the attribution ranking is preserved (Spearman $\rho = +0.983 \pm 0.039$ at $\sigma = 0.02$; the top part never flips), converting §VI-A from a possible artifact into a property.

C. What the model reads: body motion in Laban terms

Positive: the load-bearing result. The model reads body motion the way a movement analyst would name it. Region-level saliency aligns with rule-based Laban Movement Analysis (LMA) attributes far more than with classical kinematics (Spearman $\rho = +0.500$ vs $+0.033$, roughly $15\times$ stronger); for sadness, the salient regions track a bowed, sunken posture. The $+0.500$ is computed over the 48 emotion $\times$ region pairs. These pairs share a repeated 12×4 structure and are not 48 independent observations, so the interval estimate treats emotions as the resampling unit: the 95% CI of $[+0.150, +0.733]$ is an emotion-block bootstrap over the 12 emotion clusters, and the permutation null itself respects the structure, shuffling the four region scores *within* each emotion ($p < 0.001$, null mean $\rho \approx 0$). A cluster-level check agrees: the per-emotion alignment is positive for 10 of the 12 emotions, with median per-emotion $\rho = +0.70$ (exact sign test over emotions, two-sided $p = 0.039$). The rule-based export needs no model retraining, so the Macro-F1 cost is 0 pp by construction (the bold row of Table III); per-emotion LMA z-scores and the counterfactual deltas appear in the supplementary material. The order-of-magnitude gap over the classical-kinematics comparator anchors the body evidence in an established movement vocabulary rather than leaving it merely self-consistent.

How the per-emotion signature is built. Each clip yields a rule-based LMA attribute vector $a \in \mathbb{R}^{32}$ over the four Laban axes (Body, Effort, Shape, Space; the full 32-attribute schema is tabulated in the supplementary material). Each attribute k is standardised against the whole training pool and averaged within an emotion, giving a per-emotion *signature*: for emotion c ,

$$z_{c,k} = \frac{\bar{a}_{c,k} - \mu_k}{\sigma_k}, \quad \bar{a}_{c,k} = \frac{1}{|C_c|} \sum_{i \in C_c} a_{i,k}, \quad (2)$$

where μ_k, σ_k are the global mean and SD of attribute k over all clips and C_c is the set of clips of emotion c , so $z_{c,k}$ is how many SD attribute k departs from the corpus norm for that emotion. Grouping the 32 attributes into four body regions (head, arms, legs, torso; index sets R_r) gives a region-importance vector $\ell_{c,r} = \frac{1}{|R_r|} \sum_{k \in R_r} |z_{c,k}|$. The headline $\rho = +0.500$ is computed by flattening the 12 emotion $\times$ 4 region pairs and measuring the Spearman rank correlation between the LMA region score and the model’s region saliency; the classical-kinematics control (per-joint speed, acceleration, range of motion, and energy)

TABLE II

MAIN RESULTS ON DIEM-A (10-FOLD LPO, 74-PERFORMER TRAIN SPLIT). FINAL ROW = SUBMITTED MODEL. MACRO-F1 / ACCURACY = 10-FOLD LPO PER-FOLD MEAN $\pm$ SD (THE OFFICIAL CONVENTION); FUSION = LOGIT-MEAN (MEAN OF RAW LOGITS); 95% CI = SAMPLE-LEVEL PAIRED BOOTSTRAP, 1000 ITER, SEED 42, ON POOLED OOF. POOLED-OOF F1 IS A DESCRIPTIVE SECONDARY: 7-WAY 34.03%, 11-WAY LOGIT-MEAN 36.94%.

System	Trainable params (M) [‡]	Macro-F1 (mean $\pm$ SD)	Macro-F1 95% CI	Accuracy (mean $\pm$ SD)
STGCN++ official baseline	1.40*	25.21 $\pm$ 4.49*	n/a*	27.11 $\pm$ 3.67*
STGCN++ reproduced	1.41	25.73 $\pm$ 4.03	[25.37, 27.23]	27.54 $\pm$ 3.92
Best single (Region-Aware)	1.03	30.05 $\pm$ 3.48	[29.32, 31.15]	30.87 $\pm$ 3.43
7-way ensemble	12.98	33.86 $\pm$ 2.92	[33.01, 35.04]	34.68 $\pm$ 3.00
11-way logit-mean (submitted)	12.98	36.80 $\pm$ 4.00	[35.90, 37.94]	37.40 $\pm$ 4.06

* Challenge-reported (92-performer full LPO, official 25.2 % $\pm$ 4.5 %, no bootstrap CI), NOT re-evaluated with our script; our reproduction (25.73 $\pm$ 4.03) is within SD of the official number, so the official baseline serves only as an external anchor and all improvement numbers are same-split comparisons. [‡] The table reports trainable parameters; frozen external branches add fewer than 0.01 M trainable parameters each.

TABLE III

EXPLAINABILITY METRICS, WITH A PLAIN READING OF EACH ROW IN THE LAST COLUMN. SIX ROWS ARE POSITIVE EVIDENCE (FAITHFULNESS, STABILITY, COUNTERFACTUAL, NARRATOR, SUBMITTED ENSEMBLE, LMA); TEMPORAL SALIENCY IS A DELIBERATELY REPORTED NEGATIVE. ALL VALUES ARE RECOMPUTED ON THE SAME 10 LPO FOLDS AND OUT-OF-FOLD PREDICTIONS UNLESS OTHERWISE STATED (10/10 FOLDS FOR PART-MASKING/STABILITY). BOLD = HEADLINE CONTRAST.

Component	Metric	Value	95% CI / null	What it shows
Part-masking	Faithfulness AUC gap (important-reverse), zero-mask	+0.124 $\pm$ 0.031	10-fold SD; positive in all folds	Masking important parts lowers F1: attributions are faithful
Temporal saliency	AUC gap (salient-reverse), negative result	+0.002 ($\approx$ 0)	entropy 98.7% of log T ($\approx$ uniform) [†]	Frame importance is diffuse (a reported negative)
Stability	Spearman ρ vs $\sigma=0$ ref at $\sigma=0.02$	+0.983 $\pm$ 0.039	10-fold SD; top part never flips	Attribution ranking is stable under input noise
Counterfactual	Most-disruptive edit $\Delta p(\text{true})$: head+freeze	-0.0164	mean over 864 val $\times$ 10 folds	Perturbing motion changes predictions: motion-dependent
Narrator grounding	Unsupported claims in audited cards	0/50 cards	deterministic audit	No unsupported claims in the 50 audited cards
F1 cost	$\Delta F1$: baseline $\rightarrow$ with post-hoc saliency/LMA export	0.0 pp	post-hoc; no re-training	Explanations add no accuracy cost
Submitted ensemble	Part-masking + LMA under a shuffle (permutation-importance) mask	part gap +7.85 $\pm$ 1.76 pp; $\rho = +0.517$	part gap 10-fold SD; ρ 95% CI [+0.333, +0.700]; permutation $p = 0.001$	Part-masking faithfulness and LMA alignment also hold for the submitted 11-way logit-mean ensemble (baseline Macro-F1 34.65 $\pm$ 4.29%), not just one model
LMA correlation	Region-level saliency-LMA Spearman ρ	$\rho = +0.500$; kinematics control $\rho = +0.033$	permutation $p < 0.001$	Semantic alignment with the Laban vocabulary

[†] Per-sample entropy; the per-emotion class-mean is 99.5% of log T — two aggregations of the same near-uniform distribution.

under the identical pipeline reaches only +0.033. The signature is human-readable: sadness loads on `head_bow+`, `head_height-`, and `trunk_lean+`, a bowed, sunken posture that the model’s salient regions track. We treat this LMA correlation as semantic alignment, not causal evidence by itself; dependence is tested separately through part-masking and counterfactual perturbations (§VI-A, §VI-E).

D. The finding holds for the submitted ensemble

Positive, for the submitted system. Because these probes target a single member, we re-run the part-masking and LMA-alignment tests on the submitted 11-way logit-mean ensemble itself, using permutation-importance shuffling (zero-

masking collapses members that lack per-part gates). The important–reverse faithfulness gap stays positive in 10/10 folds (+8.5 pp partial-AUC at single-part resolution), and region-level part importance aligns with the rule-based LMA attributes at Spearman $\rho = +0.517$, with an emotion-block bootstrap 95% CI of [+0.333, +0.700] and permutation $p = 0.001$, *exceeding* the single-member +0.500; at the cluster level the per-emotion alignment is positive for 11 of the 12 emotions and negative for none (exact sign test, two-sided $p = 0.001$). The gap is smaller than the member’s +12.4 pp, since six of the seven skeleton members lack per-part gates, but it is consistently positive and above null: the body-evidence finding describes the system we submit, not one component.

E. Counterfactual edits move predictions as predicted

Positive, as observational corroboration. Pose-preserving, motion-perturbing edits shift logits in the *same* part ranking as masking: a head-freeze edit is the most disruptive, shifting the true-class probability by $\overline{\Delta p_{\text{true}}} = -0.0164$ on average over 864 validation clips $\times$ 10 folds and flipping 41% of predictions, and an arm-amplify edit flips 23.1%. This is convergent *observational* evidence (not causal identification) that the model relies on motion dynamics. The per-part saliency-vs-disruption agreement is positive but modest, at $\rho = +0.49$ with $n = 6$ and $p = 0.33$, and we treat it as suggestive corroboration; the load-bearing cross-method result remains the $\rho = +0.500$ vs $+0.033$ contrast with its real n .

F. What the explanations correctly refuse to claim

Negative: reported, by design. Temporal saliency is near-uniform for all 12 emotions (per-sample entropy $\approx 98.7\%$ of $\log T$; the class-mean is 99.5%, two aggregations of the same near-uniform distribution, reconciled in Table III), with an important–reverse AUC gap of only $\approx +0.002$: the model’s strongest evidence is *spatial*, in that within-window frame importance is diffuse (no single frame dominates). We report this frame-localization negative rather than hide it; it does not claim that temporal order carries no signal (saliency grids are in the supplementary material). Reverse/random masking separates cleanly from important-first. A faithfulness suite that only ever returned positive results would be unfalsifiable; reporting these negatives is what makes it a test. Per-row CIs/markers live in Table III and Table I.

One fused thesis: why diversity helps, explained. Inter-performer F1 varies $\sim 4\times$ and decomposes into roughly half intrinsic difficulty and half architecture-specific error, the same disagreement structure the ensemble exploits (§V): one mechanism behind both headlines.

G. Scoped qualitative cards (decoupled from the audit)

Qualitative narration is used only as a scoped interface to the audited saliency and LMA channels; no quantitative claim relies on it. A label-field audit of the narration cards is in the supplementary material.

VII. DISCUSSION AND LIMITATIONS

The following limitations are central to interpreting the benchmark; each carries the reason the load-bearing claim still stands. The system is a research probe under a fixed protocol, not a deployable affect recognizer.

Absolute accuracy. Macro-F1 is $\sim 37\%$, but the task is 12-way body-only LPO acted-emotion recognition (chance 8.3%; official baseline only 25%); the contribution is a protocol-matched +43% relative gain with all 12 classes improving (weakest +6.1 pp), not saturation.

Protocol gap. Our $36.80 \pm 4.00\%$ is a 74-performer cross-validation result; within the same 74-performer protocol our reproduced baseline is $25.73 \pm 4.03\%$, within one SD of the official 92-performer figure (§III), so the +11.07 pp lift is

protocol-matched and the held-out test score is pending the leaderboard (§III).

Temporal scope. Every model sees a fixed 64-frame window for parity with the official baseline (§III); longer and multi-window inference regressed under our protocol (Table I), so our claims concern this official short-window LPO setting and the within-window evidence it exposes, not full-sequence affect understanding.

Variance and confidence. Per-fold SD is ≈ 4 pp, but the bootstrap 95% CIs (Table II) show the ensemble interval clearing the 7-way interval, so the gain is not within ensemble noise; the low maximum confidence ($\sim 62\%$) is the sensible response to semantically confusable emotions, and is what the ensemble exploits.

Inter-performer range. Inter-performer F1 varies $\sim 4\times$; this bounds further homogeneous additions but does not threaten the result, since the external-pretraining column still lifts the ensemble (§V).

No human upper bound. No human or inter-rater ceiling exists for body-only 12-emotion acted recognition; the official STGCN++ result is the de-facto reference, against which the protocol-matched +11.07 pp lift remains the testable claim.

Country strata. JP/TW differences are not interpretable as cultural effects; we report them as a dataset stratum entangled with capture era and performer idiolect. The five OptiTrack-captured performers are absent from the training split (§III), and excluding the seven earliest-captured Japanese training performers moves the overall ensemble Macro-F1 by only -0.44 pp, 36.50 vs 36.94% pooled OOF, bounding the capture-era effect.

Triangulation and the held dataset. The saliency–counterfactual agreement is $n = 6$, $p = 0.33$; the load-bearing cross-method result is the $\rho = +0.500$ vs $+0.033$ contrast over the 48 emotion–region pairs, interval-estimated with emotion-block resampling ($p < 0.001$; §VI), and it reproduces on the submitted 11-way ensemble ($\rho = +0.517$, $p = 0.001$). We built an anonymized motion→rationale dataset but withhold release pending performer-consent/license review and because skeleton renders retain residual re-identifiability; we release the narrator method and audit so the results are reproducible.

VIII. CONCLUSION

Under performer-held-out evaluation of body-only 12-class acted-emotion recognition, reliable gains came not from a new architecture but from combining models with orthogonal error modes, a protocol-matched +11.07 pp over the same-split reproduced baseline. The harder contribution: part-masking, stability, and counterfactual tests showed that a strong member’s decisions, and those of the submitted ensemble, *depend* on motion-grounded body-region evidence, and that this saliency *aligns* with rule-based Laban attributes, while the suite faithfully reported a negative and a 0/50-audited narrator. The gain is cross-validated on the labeled training performers; the hidden-test leaderboard result is pending. Generalisation under performer shift needs both complementary predictions and faithful explanations of the motion evidence behind them.

Consent and approval. The DIEM-A corpus was collected by the dataset holder under their own ethics approval and explicit performer consent, as described in the dataset publication [1]. This work uses only the data released to MMAC challenge participants; we did not collect new recordings, identifiers, or auxiliary biometric attributes, and we did not contact or re-identify any performer.

Bias and limited generalizability. DIEM-A includes 40 Japanese and 34 Taiwanese performers in our LPO split, so the reported findings are bounded by an East-Asian acted-affect distribution; intercultural generalization beyond these two populations is not tested and should not be assumed. Acted emotion further differs from spontaneous expression along intensity, duration, and self-monitoring axes, which leaves an acted–spontaneous gap that limits transfer to in-the-wild affect inference. We inherit whatever demographic gaps (gender, age) exist in the source corpus. The JP–TW Macro-F1 difference reported in §V is a confounded dataset stratum, entangled with capture era and performer idiolect, and is not interpreted as a cultural effect; the dataset’s five OptiTrack-captured performers are absent from our training split (§III).

Potential misuse and mitigation. Body-only affect classifiers could be misused for affect surveillance or unconsented employment screening. We therefore release method and audit artifacts only, not a deployable affect detector, and the corpus is licensed for research use. As an additional disclosure to downstream users, the same skeleton features that yield 36.80% emotion Macro-F1 also support roughly 69.8% performer-country classification from the same inputs; that is, country identity is substantially more decodable than the target emotion. This exposes a re-identification and over-fitting risk for any deployment built on similar body-only features and motivates the held-data decision below.

Generalizability limits. The performer ceiling is small ($n = 92$ across the DIEM-A challenge subset, of which $n = 74$ are used in our LPO split). Inputs are skeleton-only (no face, audio, or scene cues), and the 64-frame analysis window covers about 7.5% of the median sequence. Macro-F1 of 36.80% on a 12-way task (chance 8.3%) remains far below any plausible threshold for human-usable affect inference. The ensemble is reported as a research probe of when ensemble diversity helps for body-only acted affect, not as a deployable emotion recognizer.

Held rationale dataset and residual re-identifiability. The anonymized motion-to-rationale natural-language dataset prepared alongside the explainability suite is deliberately withheld pending performer-consent and license review with the data holder. Skeleton renderings are derived motion: the data holder can in principle re-link a rendered clip back to its source identity, so full unlinkability is not achievable from artifacts in our pipeline. We therefore release only the narrator method and the audit needed to reproduce the explainability findings; the rationale dataset itself is held until the consent/license review is complete.

- [1] M. Cheng, C.-h. Tseng, K. Fujiwara, V. Schneider, and Y. Kitamura, “Asian emotional body movement database: Diverse intercultural Emotion database of asian performers (DIEM-A),” in *Proc. Int. Conf. Affective Computing and Intelligent Interaction (ACII)*, 2025.
- [2] S. Yan, Y. Xiong, and D. Lin, “Spatial temporal graph convolutional networks for skeleton-based action recognition,” in *Proc. AAAI Conf. Artificial Intelligence*, 2018, pp. 7444–7452.
- [3] Y. Chen, Z. Zhang, C. Yuan, B. Li, Y. Deng, and W. Hu, “Channel-wise topology refinement graph convolution for skeleton-based action recognition,” in *Proc. IEEE/CVF Int. Conf. Computer Vision (ICCV)*, 2021, pp. 13 359–13 368.
- [4] H. Duan, J. Wang, K. Chen, and D. Lin, “PYSKL: Towards good practices for skeleton action recognition,” in *Proc. 30th ACM Int. Conf. Multimedia (MM)*, 2022, pp. 7351–7354.
- [5] J. Do and M. Kim, “SkateFormer: Skeletal-temporal transformer for human action recognition,” in *Proc. European Conf. Computer Vision (ECCV)*, 2024, pp. 401–420.
- [6] H. Liu, Z. Zhu, N. Iwamoto, Y. Peng, Z. Li, Y. Zhou, E. Bozkurt, and B. Zheng, “BEAT: A large-scale semantic and emotional multi-modal dataset for conversational gestures synthesis,” in *Proc. European Conf. Computer Vision (ECCV)*, 2022, pp. 612–630.
- [7] N. Fourati and C. Pelachaud, “Emilya: Emotional body expression in daily actions database,” in *Proc. Int. Conf. Language Resources and Evaluation (LREC)*, 2014, pp. 3486–3493.
- [8] M. Karg, A.-A. Samadani, R. Gorbet, K. Kühnlenz, J. Hoey, and D. Kulić, “Body movements for affective expression: A survey of automatic recognition and generation,” *IEEE Trans. Affective Computing*, vol. 4, no. 4, pp. 341–359, 2013.
- [9] A. Aristidou, P. Charalambous, and Y. Chrysanthou, “Emotion analysis and classification: Understanding the performers’ emotions using the LMA entities,” *Computer Graphics Forum*, vol. 34, no. 6, pp. 262–276, 2015.
- [10] Y. Mao, J. Deng, W. Zhou, Y. Fang, W. Ouyang, and H. Li, “Masked motion predictors are strong 3D action representation learners,” in *Proc. IEEE/CVF Int. Conf. Computer Vision (ICCV)*, 2023, pp. 10 181–10 191.
- [11] W. Wu, Y. Hua, C. Zheng, S. Wu, C. Chen, and A. Lu, “SkeletonMAE: Spatial-temporal masked autoencoders for self-supervised skeleton action recognition,” in *Proc. IEEE Int. Conf. Multimedia and Expo Workshops (ICMEW)*, 2023, pp. 224–229.
- [12] F. M. Thoker, H. Doughty, and C. G. M. Snoek, “Skeleton-contrastive 3D action representation learning,” in *Proc. 29th ACM Int. Conf. Multimedia (MM)*, 2021, pp. 1655–1663.
- [13] W. Zhu, X. Ma, Z. Liu, L. Liu, W. Wu, and Y. Wang, “MotionBERT: A unified perspective on learning human motion representations,” in *Proc. IEEE/CVF Int. Conf. Computer Vision (ICCV)*, 2023, pp. 15 085–15 099.
- [14] M. D. Zeiler and R. Fergus, “Visualizing and understanding convolutional networks,” in *Proc. European Conf. Computer Vision (ECCV)*, 2014, pp. 818–833.
- [15] R. R. Selvaraju, M. Cogswell, A. Das, R. Vedantam, D. Parikh, and D. Batra, “Grad-CAM: Visual explanations from deep networks via gradient-based localization,” in *Proc. IEEE Int. Conf. Computer Vision (ICCV)*, 2017, pp. 618–626.
- [16] S. Wachter, B. Mittelstadt, and C. Russell, “Counterfactual explanations without opening the black box: Automated decisions and the GDPR,” *Harvard Journal of Law & Technology*, vol. 31, no. 2, pp. 841–887, 2018.
- [17] S. Hooker, D. Erhan, P.-J. Kindermans, and B. Kim, “A benchmark for interpretability methods in deep neural networks,” in *Advances in Neural Information Processing Systems (NeurIPS)*, 2019, pp. 9734–9745.
- [18] J. Adebayo, J. Gilmer, M. Muelly, I. Goodfellow, M. Hardt, and B. Kim, “Sanity checks for saliency maps,” in *Advances in Neural Information Processing Systems (NeurIPS)*, 2018, pp. 9525–9536.
- [19] “MMAC challenge: Cross-cultural emotion recognition from body movements — DIEM-A benchmark and baselines,” Official challenge benchmark (online resource), Int. Conf. Affective Computing and Intelligent Interaction (ACII), 2026, provides the DIEM-A challenge split and the official STGCN++ baseline.
- [20] H. Liu, Y. Liu, M. Ren, H. Wang, Y. Wang, and Z. Sun, “Revealing key details to see differences: A novel prototypical perspective for skeleton-based action recognition,” in *Proc. IEEE/CVF Conf. Computer Vision and Pattern Recognition (CVPR)*, 2025, pp. 29 248–29 257.





Fig. S1. (A) Stage-by-stage Macro-F1 over the 11-model lift path (bars = 10-fold LPO mean $\pm$ SD; sample-level paired bootstrap 95% CIs, $B=1000$, seed 42), every stage recomputed under the canonical logit-mean convention. (B) Per-class F1 progression (pooled OOF): STGCN++ $\rightarrow$ best single (Region-Aware) $\rightarrow$ 11-way logit-mean; all 12 classes improve, weakest sadness (+6.1 pp).

TABLE S1
LEAVE-ONE-OUT ABLATION OF THE 11-MEMBER ENSEMBLE: CHANGE IN POOLED-OOF MACRO-F1 (PP, $n = 7,992$, 74-PERFORMER SPLIT) WHEN ONE MEMBER IS REMOVED FROM THE LOGIT-MEAN FUSION (LAST ROW: THE WHOLE FROZEN EXTERNAL BLOCK). POOLED-OOF BASE 36.94% (PER-FOLD HEADLINE: 36.80 $\pm$ 4.00%). ALL DELTAS ARE NEGATIVE.

Member	Family	Δ Macro-F1 (pp)
MAMP-NTU60	External (frozen)	−0.84
SkateFormer	Attention	−0.68
MAMP-NTU120	External (frozen)	−0.61
Region-Aware ConvTr	Graph-conv.	−0.59
C3D-marker-stats	External (frozen)	−0.52
MotionBERT-Lite	External (frozen)	−0.47
Keypoint-Pool-MLP	Hybrid/MLP	−0.45
STGCN++	Graph-conv.	−0.42
Conv1D+Transformer	Hybrid/MLP	−0.30
ProtoGCN	Graph-conv.	−0.15
CTR-GCN	Graph-conv.	−0.09
All frozen externals (4)	External (frozen)	−2.91

SUPPLEMENTARY MATERIAL

S1. LIFT PATH

S2. CONFUSION AND COUNTRY STRATA

S3. LEAVE-ONE-OUT ABLATIONS

S4. LMA SCHEMA

S5. SALIENCY

S6. LMA AND COUNTERFACTUALS

S7. QUALITATIVE CARDS

S8. FULL NEGATIVE-RESULTS CATALOGUE

S9. MEMBER ERROR CORRELATION




Fig. S2. (A) 12×12 row-normalised pooled-OOF confusion of the 11-way logit-mean ensemble ($n = 7,992$ clips; rows = true class, rows sum to 100%); the five strongest off-diagonal confusions are boxed. (B) 11-way per-class F1 by performer country (JP $n=40$, TW $n=34$ training performers) with the signed JP–TW per-class strip in percentage points. The JP–TW macro gap (35.3 vs 38.9%) is a dataset stratum: the five OptiTrack-captured performers are absent from the training split, and excluding the seven earliest-captured Japanese training performers shifts pooled-OOF Macro-F1 by only -0.44 pp.

TABLE S2
PER-STRATUM LEAVE-ONE-OUT DELTAS (PP, POOLED OOF) FOR THE 11-MEMBER LOGIT-MEAN ENSEMBLE. ‘EXCL. EARLIEST JP’ SCORES AFTER REMOVING THE SEVEN EARLIEST-CAPTURED JAPANESE TRAINING PERFORMERS (JP_06–JP_12).

Member	Family	All	JP	TW	Excl. earliest JP
MAMP-NTU60	External (frozen)	−0.84	−1.65	−0.01	−0.84
SkateFormer	Attention	−0.68	−0.48	−0.93	−0.78
MAMP-NTU120	External (frozen)	−0.61	−0.90	−0.30	−0.62
Region-Aware ConvTr	Graph-conv.	−0.59	−0.62	−0.57	−0.65
C3D-marker-stats	External (frozen)	−0.52	−0.64	−0.42	−0.54
MotionBERT-Lite	External (frozen)	−0.47	−0.72	−0.23	−0.49
Keypoint-Pool-MLP	Hybrid/MLP	−0.45	−0.62	−0.28	−0.44
STGCN++	Graph-conv.	−0.42	−0.67	−0.14	−0.44
Conv1D+Transformer	Hybrid/MLP	−0.30	−0.40	−0.17	−0.27
ProtoGCN	Graph-conv.	−0.15	−0.10	−0.19	−0.20
CTR-GCN	Graph-conv.	−0.09	−0.15	−0.05	−0.05
All frozen externals (4)	External (frozen)	−2.91	−3.11	−2.75	−2.74

TABLE S3

RULE-BASED LABAN MOVEMENT ANALYSIS (LMA) ATTRIBUTE SCHEMA: 32 CLIP-LEVEL FEATURES ACROSS THE FOUR LABAN AXES, COMPUTED FROM BVH-24 FORWARD KINEMATICS. THE PER-EMOTION Z-SCORE SIGNATURE AND THE REGION AGGREGATION $\ell_{c,r}$ ARE DEFINED IN THE MAIN PAPER; THIS IS THE ESTABLISHED MOVEMENT VOCABULARY THE SALIENCY ALIGNMENT IS MEASURED AGAINST.

Laban axis	What it captures	Attributes (8 per axis)
Body	posture and bilateral form	head bow, trunk lean, arm openness, left–right speed asymmetry, left–right position asymmetry, stillness ratio, head lateral tilt, shoulder drop
Effort	motion quality (time/weight/flow)	suddenness, sustainedness, strong energy, light energy, bound flow, free flow, intensity peak, intensity variance
Shape	body volume and its change	body volume, shoulder width, head height, contraction change, rise/sink, spread change, arm enclosure, advance/recede
Space	trajectory and locomotion	directness, path curvature, horizontal root displacement, vertical root displacement, lateral sway, cumulative turn, dominant direction, locomotion ratio

Region importance is computed from the per-emotion z-scores defined in the main paper as the within-region mean of $|z_{c,k}|$; Spearman correlation over the 12×4 emotion-region pairs gives $\rho = +0.500$ vs. $+0.033$ for classical kinematics.

Supplementary Fig. 5: joint×frame saliency, all 12 emotions (joints grouped by body part)




Fig. S3. Per-emotion temporal and spatial saliency, full grid (companion to the temporal-saliency negative reported in the main paper).





Fig. S4. (A) Temporal saliency (mean over joints) is near-uniform for all 12 emotions; per-sample entropy $\approx 98.7\%$ of $\log(64)$ (class-mean 99.5%), the load-bearing negative. (B) Spatial saliency (row-normalised, joints in 6 body parts): Head is the top-1 joint for all 12 emotions (Head/Neck/Neck1 dominate). (C) For surprise (least-uniform), a joint×frame burst shows local structure survives class-averaged temporal uniformity. Colourblind-safe (viridis).



region saliency-LMA Spearman $\rho = +0.500$
(classical kinematics: $+0.033$, $15\times$ weaker)
triangulation: per-part saliency vs counterfactual
disruption Spearman $\rho = +0.49$ ($p=0.33$, $n=6$)

Fig. S5. (A) Mean LMA z-score per emotion (32 attrs: Body/Effort/Shape/Space); right strip = per-emotion saliency-LMA Spearman. Region saliency-LMA $\rho = +0.500$ vs $+0.033$ for classical kinematics ($15\times$ weaker). (B) Counterfactual motion edits (observational perturbations, not causal): mean Δp_{true} over 864 val $\times$ 10 folds; head-freeze most disruptive (-0.0164 , 41% flip), l_arm+amplify 23.1% flip. Per-part saliency vs disruption Spearman $\rho = +0.49$ ($n = 6$, $p = 0.33$), a positive but modest triangulation.

TABLE S4
SUPPLEMENTARY: FULL CATALOGUE OF NEGATIVE RESULTS (EXTENDS TABLE 2).

Approach	Configuration	Outcome ($\Delta F1$)	Methodological lesson
Supervised contrastive head	pairwise SupCon, $\lambda=0.05$, batch 128	-11.53 pp, significant	12 classes at batch 128 give too few positives per class, suggesting a per-class center loss may fit better at this scale
Mixture-of-experts fusion	K=4, hand-crafted gradient-free routing	collapses to 6.55% F1	a shared head with random init and 21-D routing is associated with backbone collapse, suggesting a feature adapter, learned routing, and zero-init are needed
Scenario-text alignment	global InfoNCE, 3-fold	-1.42 pp	the projection collapses to performer identity (cross-group retrieval 10.6%)
Part-rationale alignment	cosine text alignment, 3-fold	-0.64 pp, CI [-1.30, -0.09]	the text bottleneck is associated with an F1 ceiling of 9–12%; shortcut-breaking works but yields no F1 lift
VLM zero-shot distillation	12-class, a recent VLM, preliminary	failed in preliminary zero-shot ranking	the true class ranked last (12/12); a vision-language model did not infer emotion reliably from faceless, scene-free skeleton renderings
Contact-marker late fusion	C3D 22-D contact stats, 3-fold	-0.59 pp	the contact features carry a 69.8% country signal, so some performers go out of distribution under LPO, suggesting a domain-invariance objective is needed
Multi-crop window inference	24-setting window sweep	-12 to -17 pp	the model is trained on full-span subsamples, so compact windows are a distribution shift
Post-hoc calibration	nested-LPO, 7-way ensemble	0 to -0.14 pp, not significant	equal-weight argmax is already near-optimal; bias-style calibration did not exceed it in this search
Same-architecture stacking	8-way (six models + two ConvTr variants)	-0.29 pp	diversity saturates when stacking variants of a single architecture
Over-stacked SSL ensemble	13-way, three-plus MAMP checkpoints	-0.88 pp	one SSL family over-stacked dilutes the production members; two MAMP checkpoints is the sweet spot
Arithmetic-mean averaging	probability-domain averaging	-1.15 pp (forgone)	the canonical convention is logit-mean (raw-logit averaging); the arithmetic alternative leaves -1.15 pp on the table
PoseC3D heatmap 3D-CNN	preliminary evaluation	20.26% (below the 24% threshold)	architectural novelty is not error-space orthogonality; measure the contribution in error space
Joint-masking sparse model	options A/B, 3-fold	-0.33 pp (B); collapse (A)	attribution-driven sparse models are not ensemble-additive (the 7-way already sees those joints)
Joint-subset training	top-N joints only, 3-fold	top-4 19.83%, CI [17.67, 21.99]	input-driven sparsity converges to the same negative as joint-masking
Heavy regularisation, short horizon	Conv1D+Transformer, 40 epochs	-1.34 pp standalone, CI [-0.32, +0.35]	heavy regularisation needs a long horizon; it under-fits at 40 epochs
Focal loss	single-model variant	-0.48 F1 / -0.99 Acc	the class-balanced DIEM-A does not benefit from focal loss
SkateFormer with SGD ($\text{lr}=0.2$)	single-model variant	chance-level collapse	transformer backbones require AdamW
Joint dropout (0.1)	single-model variant	seed-dependent fold collapse	some folds collapse under some seeds; not adoptable
Long clip length (128)	STGCN++, clip 128 vs 64	regresses	the emotion signal concentrates in a short temporal window
Content/style dual head	GRL + style loss, default weights	-2.65 pp	GRL and a style loss obstruct backbone learning at default weights
Gradient temporal saliency	explainability probe	AUC gap +0.003 (≈ 0), not significant	within-window frame importance is near-uniform (entropy: per-sample 98.7%, class-mean 99.5% of log T); use the body-part axis instead

Full negative-results catalogue (supplementary); the main paper shows the curated eight (Table 2).

correct (high-conf)

Clip P08_fear_1_H — True: fear | Pred: fear (p=0.48) [correct]

Top-3 salient joints (§6):
Neck1 · Head · Spine3

Top-2 LMA |z| attr:
body.lr_asym_speed (z=+5.4) · shape.head_height (z=-4.9)

Narrator (§10, verbatim):
The classifier predicts fear with 48.3% confidence; matching the ground truth label fear (§1).

confident error

Clip P02_contempt_1_H — True: contempt | Pred: anger (p=0.46) [MISPREDICTED]

Top-3 salient joints (§6):
Neck1 · Head · Spine3

Top-2 LMA |z| attr:
shape.contraction_change (z=+1.3) · body.lr_asym_speed (z=+1.1)

Narrator (§10, verbatim):
The classifier predicts anger with 46.1% confidence; the ground truth is contempt (model's 2nd guess is jealousy at 9.2%) (§1).

semantic confusion

Clip P02_disgust_1_M — True: disgust | Pred: fear (p=0.43) [MISPREDICTED]

Top-3 salient joints (§6):
Neck1 · Head · Spine3

Top-2 LMA |z| attr:
shape.advance_recede (z=-2.9) · space.root_xy_disp (z=+2.4)

Narrator (§10, verbatim):
The classifier predicts fear with 42.7% confidence; the ground truth is disgust (model's 2nd guess is jealousy at 13.5%) (§1).

All 50 cards: 0 hallucinated claims (exp07.3 audit, grounded_ratio=1.0). Cards drawn from the 16 label-consistent cards (34/50 have a \$1-vs-filename label-mismatch — see selection JSON).

Fig. S6. Three explanation cards (correct / confident-error / semantic-confusion) from the 16 label-consistent cards; each cites source channels (salient joints, top-2 LMA |z|, verbatim deterministic narrator). All 50 cards pass the grounding audit (0 hallucinated claims, grounded-ratio = 1.0). Qualitative; per-card correctness is excluded pending a card-generator fix.




Fig. S7. Members make largely independent errors, the diversity the ensemble converts into its gain: off-diagonal error correlations stay in $[0.15, 0.43]$, lowest for the external-pretrain C3D-stats column ($\rho \approx 0.15\text{--}0.19$ to skeleton models); most-redundant pair Conv1D+Tr $\leftrightarrow$ KP-MLP ($\rho = 0.43$). Pairwise Pearson ($= \phi$), OOF $n = 7,992$; the diagonal is 1 by definition and the colour scale is capped at the off-diagonal maximum. KP-MLP = Keypoint-Pool-MLP; C3D-stats = C3D marker statistics, not a 3D CNN.