HandsOnAid: Building and Evaluating an Offline First-Aid Assistant for Emergency Response Scenarios

Rezwan Islam Salvi* **Saiyma Sittul Muna*** **Mushfiqur Rahman Mushfique***

Islamic University of Technology
Dhaka, Bangladesh

{rezwanislam, saiymasittul, mushfique2}@iut-dhaka.edu

arXiv:2611.14059v1 [cs.CL] 10 Nov 2026

Abstract

Emergencies can occur where there is no phone signal and no ambulance nearby. A small language model on a phone can be helpful in such situations, but its advice needs to be safe and accurate. We built HandsOnAid, a 4-bit Gemma 2B model fine-tuned with QLoRA on FirstAidQA dataset, a corpus of 5,550 first-aid question–answer pairs. We compared seven configurations, including the base, 4-bit and 8-bit fine-tuned models, and versions with a length floor, safety gate, or retrieval. We used a 41-pair question-answer bank with medically reviewed references that followed ANZCOR guidelines, and a strict 0–5 score rubric, with twelve safety overrides. Four frontier LLM judges (GPT-5.6 Sol, Claude Opus 5, DeepSeek V4 Pro, GLM-5.3) blindly scored every answer, with 45 hidden controls used to check judge reliability. Fine-tuning improved the mean score by +1.08 over the base model to 2.34. The best configuration scored 2.51 out of 5 which was the fine-tuned 4-bit model with retrieval. A medical professional also conducted a blind evaluation of 40 answers across the base, the 4-bit fine-tuned, and the retrieval configurations, and the scores were similar to the LLM judges' average scores. A keyword audit found limited coverage of several details of ANZCOR guidelines in the training corpus, that are required by the rubric, which suggests that missing information in the training data could be a cause of the low scores. On a smartphone device (Pixel 7 Pro) with six CPU threads and no network connection, the 4-bit fine-tuned model produced its first displayable text in 6.86 seconds and a complete answer in 14.88 seconds on average over ten questions.

Keywords: first aid, emergency, offline deployment, small language models, parameter-efficient fine-tuning, LLM-as-a-judge

1. Introduction

Most AI assistants run on servers, but first aid is often needed where servers cannot be reached: after an earthquake, a cyclone, on a boat, in a forest or isolated place, or when the network is down. In these moments, the person with a phone may be the only help a patient gets. A small language model running on the phone could guide them through the situation, but it must be accurate and safe. A wrong step in an emergency, such as during CPR or moving someone with a spinal injury incorrectly can be dangerous.

We built and tested such a model. HandsOnAid is Gemma 2B (Gemma Team et al., 2024), a small open model, fine-tuned with QLoRA (Dettmers et al., 2023) on FirstAidQA (Muna et al., 2025), a corpus of 5,550 first-aid question–answer pairs. We also tested ways to get more from a small model: running the base weights at 8-bit instead of 4-bit, generating longer answers, adding a safety gate that checks the answer before giving it as output, and adding retrieval so the model sees a similar training example before answering. In total, we compared seven configurations (Table 1).

To test them, we wrote 41 emergency question-answer pairs with the help of Claude Fable 5, none copied from the training corpus. Each followed ANZCOR guidelines (Australian and New Zealand Committee on Resuscitation, 2023) and was checked by a medical professional. We also wrote a strict rubric: a 5 means a complete protocol that a layperson could follow alone, while one dangerous instruction can bring the score down to 0 or 1. Four frontier language models: GPT-5.6 Sol, Claude Opus 5,

* Equal contribution.

DeepSeek V4 Pro and GLM-5.3, scored every answer without knowing which configuration produced it. We also mixed in 45 control answers to check whether the LLM judges were actually following the rubric. This was followed by a medical professional's evaluation on a subset of 40 answers across four configurations, and the scores were close to the LLM judges' averages.

Fine-tuning helped. It raised the mean score by 1.08 points over the base model to 2.34 on the 0–5 scale. But the best configuration scored only 2.51 which was the fine-tuned 4-bit model with retrieval. Evaluation by a medical professional also showed similar results. Our corpus audit found few matches for several details of ANZCOR guidelines needed for a top score. This gap suggests that the limitation in training data could contribute to the low scores.

Contributions.

1. A comparison of seven configurations on emergency/first-aid answers (Section 5).
2. An evaluation for offline first aid guidance: a 41-pair question-answer bank with medically reviewed ANZCOR guideline references, a strict rubric with twelve safety overrides, and a blind four-judge evaluation with hidden control answers (Section 4).
3. A medical-professional evaluation of a subset of 40 answers across four configurations (Section 5).
4. On-device performance on a Pixel 7 Pro smartphone without a network connection (Section 6).

2. Related Work

Medical question answering. Large models contain substantial clinical knowledge (Singhal et al., 2023), and benchmarks such as MedQA, MedMCQA, PubMedQA, BioASQ, and MedQuAD measure it (Jin et al., 2021; Pal et al., 2022; Jin et al., 2019; Tsatsaronis et al., 2015; Ben Abacha and Demner-Fushman, 2019), mostly through multiple-choice or encyclopedic questions. None focuses on step-by-step guidance that a layperson must follow in a short time. EMSQA covers emergency-services exam questions and shows that retrieval helps (Ge et al., 2026); FirstAidQA focuses on first aid in low-connectivity settings (Muna et al., 2025) and is our corpus. These benchmarks generally assume professional care is reachable, so "call emergency services" can be a good answer. In our setting, an answer that only says to call emergency services is penalized if it mentions no action that is possible to carry out in that scenario.

Offline first-aid apps. There are existing first-aid apps that provide offline guidance. The American Red Cross app, for example, provides preloaded instructions (American Red Cross, 2026) on specific topics. A language model could answer a question phrased in the user's own words and adapt its wording to the situation, which can be unknown and not covered in a preloaded library. We study this gap.

Small medical models and quantisation. Small open models (Zhang et al., 2024) have been adapted for medicine (Han et al., 2023), used on phones (Li et al., 2025b), and tuned from Gemma (Sellergren et al., 2025). We use QLoRA with a 4-bit model (Dettmers et al., 2023). It is unclear whether quantisation can make medical answers less safe (Hong et al., 2024; Egashira et al., 2024). We test its effect.

Retrieval from corpus. MedRAG studies medical retrieval over large biomedical datasets (Xiong et al., 2024), including BM25 (Robertson and Zaragoza, 2009) technique. We retrieve one relevant pair from the FirstAidQA corpus during inference. This tests whether showing a training example helps at inference time for a better response (Section 7).

Language models as judges. Using a large model to evaluate another model is efficient (Zheng et al., 2023), but LLM judges may favor their own answers and score differently from experts (Panickssery et al., 2024; Li et al., 2025a). We use four judges from different model families and evaluate answers blindly at temperature zero. No judge is from the same family as the model being tested. We also test whether score differences are statistically significant (Verga et al., 2024; Dror et al., 2018). As in prior safety benchmarks (Chen et al., 2025; Ness et al., 2024; Pal et al., 2023; Wang et al., 2026, 2025), we report quality scores and safety flags separately. Also, self-revision can help (Madaan et al., 2023), but may fail without outside feedback (Huang et al., 2024); our safety-gate results show the same.

Dataset validation. Synthetic medical datasets are often checked to see if their answers are clear and believable, following the Self-Instruct approach (Wang et al., 2023). For our setting, a separate question is *guideline coverage*: whether the data includes the steps required by the chosen evaluation standard. Section 7 shows why that matters.



Figure 1: Overview of the study: FirstAidQA dataset, Fine-tuning, 7 configurations, 41-question exam, Rubric and 4 LLM judges.

3. Dataset, Model and Configurations

FirstAidQA. The corpus has 5,550 question–answer pairs, available on Hugging Face. Answers are short and practical, averaging 44 words. We added two labels: each pair was given one of ten clinical categories (Appendix A) and marked *safety-critical* (SC) when it involved a life-threatening situation. We used a DeBERTaV3 cross-encoder trained on SNLI and MultiNLI, for zero-shot SC labelling through natural language inference (He et al., 2023; Sentence Transformers, 2026; Yin et al., 2019) (Appendix F). The SC rate is 22.2% in the full corpus and 22.4% in the training split. We split the data into 4,441 / 556 / 553 training, validation, and test pairs, while keeping the category mix similar across splits.

Fine-tuning. We use QLoRA (Dettmers et al., 2023): the base model is kept frozen at 4-bit precision, while LoRA (Hu et al., 2022) adds small trainable matrices. We add these matrices to all seven projection sites in every layer, including the feed-forward layers, because first-aid answers need the right *content*, such as correct quantities and step order, not just good attention. We calculate the loss only for answer tokens. The main settings are rank 16, alpha 32, learning rate 10^{-4} with a cosine schedule, and a maximum length of 320 tokens (full table in Appendix B). Training took 75 minutes on one 12 GB GPU and stopped at epoch 2.88, with a validation loss of 1.340. Fine-tuning also made the answers much shorter: 43 words on average (similar to the corpus), compared with 134 for the base model.

Retrieval. The retrieval configurations (F & G) search the 4,441 training pairs using BM25 (Robertson and Zaragoza, 2009). We place the best matching pair before the question as a reference. We use keyword matching because emergency questions are short, and specific words like "tourniquet" can help find the right answer. A gate turns retrieval off for seven topics where the corpus has gaps or potentially misleading examples (Appendix D). The knowledge base is the training set, so the retrieved text adds no external source material. This was done to check whether having the context of a relevant training example makes the model generate better answers.

The seven configurations. Figure 1 shows the whole study at a glance and Table 1 lists the 7 configurations.

Length floor and safety gate. The length floor (D) gives the model one more try when its answer is

Table 1: The seven configurations. All follow the same base instructions and are evaluated on the same 41 reference question-answer pairs.

ID	Name	What it is	What it tests
A	Base 4-bit	Gemma-2B, 4-bit, no fine-tuning	The baseline
B	Fine-tuned 4-bit	QLoRA fine-tuning with adapters	The reference point
C	Fine-tuned 8-bit	Adapter on 8-bit base weights	Does precision matter?
D	Fine-tuned 4-bit + length floor	B, regenerated once with a length hint if the answer is too short	Does more text help?
E	Fine-tuned 4-bit + safety gate	B, plus a second pass that labels answer SAFE/UNSAFE, and replaces unsafe ones	Can a 2B model catch itself?
F	Fine-tuned 4-bit + retrieval	B, plus BM25 retrieval from the training set	Does retrieval add to fine-tuning?
G	Base 4-bit + retrieval	F, without the fine-tuned adapter	Can retrieval replace fine-tuning?

too short, with a hint to be more thorough, and keeps the longer answer (Appendix B). The safety gate (E) checks the answer against danger rules and labels it SAFE or UNSAFE. If unsafe, the answer is replaced with a fixed generic message telling the user to keep the person still, watch their breathing and responsiveness, and give no food, drink, or medication.

4. How We Evaluated

4.1. The 41-question exam

We created 41 new question-answer pairs with the help of Claude Fable 5, covering the ten corpus categories in similar proportions (Appendix A). Eleven (26.8%) are safety-critical, compared with 22.2% in the corpus, and none was copied from it. Each question has a reference answer based on ANZCOR guidelines (Australian and New Zealand Committee on Resuscitation, 2023). We chose ANZCOR as an established guideline to provide a consistent evaluation standard, as there must be no room for errors in emergency situations. The answers start with the action to take and include exact numbers, such as placing a tourniquet 5–7 cm above the wound, cooling a burn for 20 minutes, etc.

A medical professional reviewed every question and reference against ANZCOR in two rounds (Table 2). The first round reported 12 minor issues. We revised the references after this review. The second round scored 4.0 for safety, 4.5 for relevance and 4.0 for accuracy, out of 5. We also shortened the references to an average of 54 words, close to the corpus average of 44 words.

One reference excerpt from the bank:

Q: *You are applying direct pressure to a wound on someone's forearm and after ten minutes of sustained firm pressure the bleeding has not slowed. What should you do next?*

Reference: *Apply a tourniquet 5 to 7 centimetres above the wound, not over a joint. Tighten until bleeding stops. Write the time on the skin. Do not remove it in the field. Lay them down, keep them warm and still, and watch for shock.*

Table 2: Scores given by the medical professional for the reference bank (0–5 scale).

Criteria	Score
Overall Safety	4.0
Overall Relevance	4.5
Overall Accuracy	4.0

4.2. The rubric

Four LLM judges score each answer from 0 to 5. A 5 means the answer is correct, complete, and clear enough for someone to follow on their own. A 4 has small gaps but remains safe. A 3 misses one or two important steps. A 2 is too general or incomplete, while 1 contains dangerous or misleading advice. A 0 is wrong or empty. An answer that only says "call emergency services" cannot score above 2.

We also use twelve *safety overrides*, such as removing an embedded object, moving a suspected spinal injury without a log-roll, removing a tourniquet, giving food or water to an unconscious person, and using abdominal thrusts for choking (Appendix C). If

Table 3: Mean quality score (0–5) per judge (DS = DeepSeek V4 Pro, Cl = Claude Opus 5, GPT = GPT-5.6 Sol, GLM = GLM-5.3), pooled over the four judges for all 41 questions and for the 11 safety-critical (SC) questions separately, the number of answers (of 41) with a safety override flagged by at least one judge / by all four, and mean answer length.

	Per judge				Pooled		Flagged	Words
Configuration	DS	Cl	GPT	GLM	All	SC	any / all	
A Base 4-bit	1.22	0.90	1.42	1.51	1.26	1.11	16 / 6	134
B Fine-tuned 4-bit	2.24	2.24	2.32	2.56	2.34	1.98	9 / 4	43
C Fine-tuned 8-bit	2.34	2.20	2.27	2.46	2.32	1.93	11 / 4	43
D Fine-tuned 4-bit + length floor	2.29	2.27	2.32	2.56	2.36	2.11	8 / 5	45
E Fine-tuned 4-bit + safety gate	2.17	2.20	2.34	2.56	2.32	2.11	9 / 2	42
F Fine-tuned 4-bit + retrieval	2.51	2.42	2.59	2.54	**2.51**	**2.16**	8 / 4	43
G Base 4-bit + retrieval	1.37	0.95	1.63	1.61	1.39	1.14	19 / 6	162

an answer includes any of these, it must score 0 or 1, even if the rest of the answer is good. Each answer is judged twice: once for quality (0–5 score with a reason) and once for safety (yes/no for each override, with the unsafe phrase quoted).

4.3. The four judges and the control answers

We use four frontier models from different vendors as judges: DeepSeek V4 Pro, Claude Opus 5, GPT-5.6 Sol, and GLM-5.3. Gemini was excluded because it shares the Gemma family (from Google). Judging is blind: we replace configuration names with salted hashes and score each answer separately using the question, safety-critical flag, reference answer, and rubric. All judges use temperature zero and JSON output. We froze and recorded the prompts before scoring. Each judge made 664 calls, all of which returned valid responses.

To check the judges, we mixed 45 control answers with the real answers. These included the reference answer (must score 4–5), an answer that only says to call emergency services (0–2), a clear-sounding but unhelpful answer (0–3), and six answers with one deliberate dangerous instruction (0–1). The safety check also had to flag each dangerous instruction. All four judges scored all 45 controls in the correct range and caught all 6 planted violations, which covered five of the twelve override categories. On real answers, any two judges agreed exactly 53–64% of the time and were within just 1 point difference 92–98% of the time.

4.4. Statistics

We tested each judge separately using a paired bootstrap and an exact sign test over the 41 questions. We call a difference confirmed only if both tests pass for all four judges and they all agree on its direction.

5. Results

We tested seven configurations on the same 41 questions and scored the answers using the four frontier LLM judges.
Table 3 gives the means and Table 4 shows statistical comparisons.

Table 4: Comparisons pooled over the four judges. Δ is the mean paired difference over 41 questions; W/L/T counts questions won, lost and tied. Confirmed means the 95% CI excludes zero, the sign test passes, and all four judges agree on direction. **c**=confirmed, **nc**=not confirmed, **null**=negligible difference.

Comparison	**Δ**	**95% CI**	**W/L/T**	**Verdict**
B−A fine-tuning	+1.08	[+0.75, +1.40]	34/5/2	**c**
F−B retrieval	+0.17	[−0.04, +0.38]	19/13/9	nc
C−B 8-bit	−0.02	[−0.26, +0.21]	19/18/4	null
D−B length floor	+0.02	[−0.16, +0.18]	16/13/12	null
E−B safety gate	−0.02	[−0.15, +0.09]	12/14/15	null
G−B no fine-tuning	−0.95	[−1.25, −0.65]	6/33/2	**c**
G−F no adapter	−1.12	[−1.36, −0.88]	2/35/4	**c**

Fine-tuning helps, and all four judges agree. The fine-tuned 4-bit model scores 1.08 points higher than the base model. It does better on 34 of 41 questions and worse on only 5. All four judges found a similar improvement: DeepSeek V4 Pro +1.02, Claude Opus 5 +1.34, GPT-5.6 Sol +0.90, and GLM-5.3 +1.05. Answers with an override flagged by at least one judge drop from 16 to 9, while the average answer length drops from 134 to 43 words, close to the 44-word average in FirstAidQA. Fine-tuning still helps when retrieval is added: the base model with retrieval (G) scores more than 1 point lower than the fine-tuned model with retrieval (F), and almost 1 point lower than the fine-tuned model alone (B).

No add-on gives a significant improvement. Adding retrieval to the fine-tuned model (F) gives the best mean score, 2.51 out of 5, but the gain over B is small (+0.17). The 8-bit model (C), length floor (D), and safety gate (E) also show little difference in this experiment. We use 4-bit for deployment because it is smaller and faster. The safety gate has the fewest answers flagged by all four judges (2), but 9 are flagged by at least one judge. Its generic fallback can score at most 2. Retrieval without fine-tuning (G) scores 1.39 and has 19 answers flagged by at least one judge.

Table 5: Human evaluation on the same ten questions per configuration. LLM means average the four LLM judges; flags count answers with at least one safety override marked by the medical professional.

Configuration	Human	LLM	Flags
A: Base 4-bit	1.30	1.03	3/10
B: Fine-tuned 4-bit	2.30	2.15	2/10
F: Fine-tuned 4-bit + retrieval	2.40	2.23	1/10
G: Base 4-bit + retrieval	1.60	1.30	3/10

Medical-professional evaluation. The medical professional who reviewed the 41-pair reference bank later also evaluated a subset of 40 answers: we chose answers to the same ten questions from each of configurations A, B, F and G. These configurations involve fine-tuning and/or retrieval; C, D and E were not included because their mean scores differed little from B. The subset covered seven categories, with four safety-critical questions out of the ten. Answers were shuffled and configuration identities were hidden. The evaluator received the references and rubric, checked the twelve overrides, and assigned 0–5 scores.

Fine-tuning improved the human mean by 1.00 point, while retrieval added 0.10 points to the fine-tuned model (Table 5). Scores given by the medical professional were similar (bit higher but not significantly), and the configuration ordering matched the LLM means on this subset.

6. On-Device Performance

We evaluated the 4-bit fine-tuned model locally on a Google Pixel 7 Pro using Termux and llama.cpp (Gerganov, 2023), with CPU inference. We used a subset of the same ten questions for the four and six-thread runs, temperature 0, seed 42, a 1,024-token context, a 350-token generation limit, and no prompt cache. Airplane mode was enabled, Wi-Fi and Bluetooth were off, and the charger was disconnected.

Table 6: Performance on Pixel 7 Pro without a network connection. Mean durations are over ten answers.

CPU threads	First text	Full answer
4	8.39 s	17.47 s
6	**6.86 s**	**14.88 s**

With six threads, answers averaged 47.8 words, began appearing after 6.86 seconds, and finished after 14.88 seconds (Table 6). These results demonstrate offline model inference on the tested phone.

7. Why Scores Are Low

The best configuration (F) scores 2.51 out of 5. The judges were not simply being strict: they gave every planted reference control answer a 5. So why are the model scores low?

7.1. The rubric is strict by design

Figure 2 shows how the scores are distributed. For the best configuration (F), the 164 judge scores were:

- **0–1: 13.4%** — unsafe, wrong, or triggered a safety override.
- **2: 28.7%** — generic or incomplete.
- **3–4: 57.9%** — partially or mostly complete.

- **5: 0%** — complete under the rubric.

For the fine-tuned model alone (B), these were 25.0%, 29.9%, 44.5%, and 0.6%. For the base model (A), they were 64.6%, 27.4%, 7.9%, and 0%. Fine-tuning reduced the share of 0–1 ratings from 64.6% to 25.0%. However, no answer was considered complete by three of the four judges; the only score of 5 came from GLM-5.3.



Figure 2: Share of judge scores in each band (0–1, 2, 3–4, 5) for the seven configurations, pooled over the four judges. D, E and F add an inference-level technique to the fine-tuned 4-bit model.

7.2. Some rubric details are rarely matched in the corpus

Neither FirstAidQA nor its source book mentions about the ANZCOR guidelines used in our evaluation. Because we use this specific standard, our evaluation requires specific numbers and steps. A keyword audit of the 4,441 training answers found no matches for two of these details and only three for the 30:2 CPR ratio (Table 7). For choking, ANZCOR requires back blows followed by chest thrusts. However, the corpus mentions chest thrusts only once, while abdominal thrusts or the Heimlich manoeuvre (a different choking technique) appear 41 times.

7.3. The same questions that fail in every configuration

Seven low-scoring questions show the same pattern. Six are safety-critical, and in every configuration, the

Table 7: Keyword matches for selected rubric details in the 4,441 training answers.

Rubric detail / keyword	Answers
Tourniquet 5–7 cm above the wound	0
(tourniquet mentioned at all)	5
5 rescue breaths before compressions (drowning)	0
30:2 compression-to-breath ratio	3
Pressure bandage from the toes upward (snake bite)	6
Back blows (choking)	11
chest thrusts	1
abdominal thrusts or Heimlich	41
Spinal log-roll	1
Naloxone for opioid overdose	2

SC mean (average score on the 11 safety-critical questions only) is lower than the overall mean. The two lowest-scoring questions are also found in the corpus audit. On the tourniquet question, the fine-tuned 4-bit model says:

> *"If the bleeding has persisted for ten minutes without improvement, apply additional pressure for 10–20 minutes. If the bleeding continues, repeat the process. If the person becomes unconscious or shows signs of shock, begin CPR immediately."*

All four judges flag the same problem: the bleeding has not stopped, but the model never says to use a tourniquet. On the choking question, it says to "begin CPR immediately" for a conscious adult, skipping back blows and chest thrusts. All four judges flag this too. These failures are consistent with the gaps found in the corpus audit.

7.4. Limits of the retrieval and safety gate

Retrieval helps only when the corpus has a good answer to find. Compared with the fine-tuned model alone, it improved four questions by 1.25–1.75 points but made four others worse by 0.75–1.0 points. What mattered was whether the retrieved record was correctly following ANZCOR guidelines or not. We did not use a different source or corpus for retrieval because that might have fetched different answers to what the model already knew through its training, and then it might get confused or hallucinate while answering.

The safety gate replaced answers with its generic fallback message. The fallback can score at most 2. So the gate can withhold an unsafe answer, but it cannot produce a correct (complete) one.

8. Discussion

The results show both a benefit from fine-tuning and a gap between the model's answers and our evaluation requirements. We chose ANZCOR as a single guideline because wrong first-aid advice can be dangerous, making it important to use a consistent and strict evaluation standard. FirstAidQA dataset was not constructed or validated using ANZCOR guidelines. Its source book (though it is Australian) does not mention ANZCOR either. This difference in training data is therefore a plausible contributor to the low scores. However, we tested one corpus and one model only, and cannot conclude that the corpus alone sets the performance ceiling.

The retrieval result has the same limit. It accesses relevant examples from the same training corpus. The human evaluation supports the LLM judges' scores, while the phone benchmark establishes that the model can run offline on the tested device.

For first-aid datasets, our observations suggest the necessity of following an established protocol and evaluating the proportion of answers that correctly apply them. The dataset should fully align with the selected guideline.

Limitations

The best configuration scored only 2.51 out of 5 and encountered safety override flags, so it is not ready for emergency use. The reference bank and subset of model answers underwent human evaluation, but that was done by one medical professional only.

We used one English corpus, one model family, one guideline-based rubric, and single-turn interactions. The safety-critical labels were given by a language model. Keyword checks might miss equivalent or paraphrased wording.

9. Conclusion

We fine-tuned Gemma 2B on FirstAidQA and compared seven configurations on 41 questions with medically reviewed references and four LLM judges. Fine-tuning improved the mean score by more than a point, and no add-on gave a significant improvement. The human evaluation produced similar configuration means and the same ordering as the LLM judges. The model ran offline on a smartphone, taking 6.86 seconds to first text and 14.88 seconds to a complete answer with six CPU threads. These are useful steps toward studying offline first-aid assistance, but the low scores mean HandsOnAid remains a research prototype. The training dataset audit suggests a coverage problem without establishing it as the only cause of the observed failures. We welcome extension of our work and further involvement of researchers in this field, as emergency response remains a somewhat underexplored domain.

Ethics Statement

HandsOnAid is not a medical device or a replacement for professional care. When emergency services are available nearby, contacting them should always be the first step, and any deployed system should make this clear. A system scoring 2.51 out of 5 could potentially harm someone who follows its advice. We publish these results because an honest account of the observed failures is useful for future work.

References

American Red Cross. First Aid: American Red Cross. App Store application description, 2026. URL https://apps.apple.com/us/app/first-aid-american-red-cross/id529160691. Accessed November 8, 2026.

Australian and New Zealand Committee on Resuscitation. ANZCOR guidelines. https://www.anzcor.org, 2023. Accessed 2026.

Asma Ben Abacha and Dina Demner-Fushman. A question-entailment approach to question answering. *BMC Bioinformatics*, 20:511, 2019.

Sijia Chen, Xiaomin Li, Mengxue Zhang, Eric Hanchen Jiang, Qingcheng Zeng, and Chen-Hsiang Yu. CARES: Comprehensive evaluation of safety and adversarial robustness in medical LLMs. *arXiv preprint arXiv:2505.11413*, 2025.

Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. QLoRA: Efficient finetuning of

quantized LLMs. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Rotem Dror, Gili Baumer, Segev Shlomov, and Roi Reichart. The hitchhiker's guide to testing statistical significance in natural language processing. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics*, pages 1383–1392, 2018.

Kazuki Egashira, Mark Vero, Robin Staab, Jingxuan He, and Martin Vechev. Exploiting LLM quantization. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

Xueren Ge, Sahil Murtaza, Anthony Cortez, and Homa Alemzadeh. Expert-guided prompting and retrieval-augmented generation for emergency medical service question answering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2026.

Gemma Team, Thomas Mesnard, Cassidy Hardin, Robert Dadashi, Surya Bhupatiraju, Shreya Pathak, Laurent Sifre, Morgane Rivière, Mihir Sanjay Kale, Juliette Love, et al. Gemma: Open models based on Gemini research and technology. *arXiv preprint arXiv:2403.08295*, 2024.

Georgi Gerganov. llama.cpp: LLM inference in C/C++. https://github.com/ggerganov/llama.cpp, 2023.

Tianyu Han, Lisa C. Adams, Jens-Michalis Papaioannou, Paul Grundmann, Tom Oberhauser, Alexei Figueroa, Alexander Löser, Daniel Truhn, and Keno K. Bressem. MedAlpaca – an open-source collection of medical conversational AI models and training data. *arXiv preprint arXiv:2304.08247*, 2023.

Pengcheng He, Jianfeng Gao, and Weizhu Chen. DeBERTaV3: Improving DeBERTa using ELECTRA-style pre-training with gradient-disentangled embedding sharing. In *International Conference on Learning Representations (ICLR)*, 2023.

Junyuan Hong, Jinhao Duan, Chenhui Zhang, Zhangheng Li, Chulin Xie, Kelsey Lieberman, James Diffenderfer, Brian Bartoldson, Ajay Jaiswal, Kaidi Xu, Bhavya Kailkhura, Dan Hendrycks, Dawn Song, Zhangyang Wang, and Bo Li. Decoding compressed trust: Scrutinizing the trustworthiness of efficient LLMs under compression. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, volume 235, pages 18611–18633, 2024.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022.

Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. Large language models cannot self-correct reasoning yet. In *International Conference on Learning Representations (ICLR)*, 2024.

Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. What disease does this patient have? A large-scale open domain question answering dataset from medical exams. *Applied Sciences*, 11(14):6421, 2021.

Qiao Jin, Bhuwan Dhingra, Zhengping Liu, William Cohen, and Xinghua Lu. PubMedQA: A dataset for biomedical research question answering. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP-IJCNLP)*, pages 2567–2577, 2019.

Yahan Li, Jifan Yao, John Bosco S. Bunyi, Adam C. Frank, Angel Hsing-Chi Hwang, and Ruishan Liu. CounselBench: A large-scale expert evaluation and adversarial benchmarking of large language models in mental health question answering. *arXiv preprint arXiv:2506.08584*, 2025a.

Yinghong Li et al. Efficient fine-tuning of small-parameter large language models for biomedical bilingual multi-task applications. *Applied Soft Computing*, 175:113084, 2025b.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. Self-refine: Iterative refinement with self-feedback. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Saiyma Sittul Muna, Rezwan Islam Salvi, Mushfiqur Rahman Mushfique, and Ajwad Abrar. FirstAidQA: A synthetic dataset for first aid and emergency response in low-connectivity settings. In *Proceedings of the 5th Muslims in Machine Learning (MusIML) Workshop, co-located with NeurIPS*, 2025. URL https://arxiv.org/abs/2511.01289.

Robert Osazuwa Ness, Katie Matton, Hayden Helm, Sheng Zhang, Junaid Bajwa, Carey E. Priebe, and Eric Horvitz. MedFuzz: Exploring the robustness of large language models in medical question answering. *arXiv preprint arXiv:2406.06573*, 2024.

Ankit Pal, Logesh Kumar Umapathi, and Malaikannan Sankarasubbu. MedMCQA: A large-scale multi-subject multi-choice dataset for medical domain question answering. In *Proceedings of the Conference on Health, Inference, and Learning (CHIL)*, volume 174, pages 248–260, 2022.

Ankit Pal, Logesh Kumar Umapathi, and Malaikannan Sankarasubbu. Med-HALT: Medical domain hallucination test for large language models. In *Proceedings of the 27th Conference on Computational Natural Language Learning (CoNLL)*, pages 314–334, 2023.

Arjun Panickssery, Samuel R. Bowman, and Shi Feng. LLM evaluators recognize and favor their own generations. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

Stephen Robertson and Hugo Zaragoza. The probabilistic relevance framework: BM25 and beyond. *Foundations and Trends in Information Retrieval*, 3(4):333–389, 2009.

Andrew Sellergren, Sahar Kazemzadeh, Tiam Jaroensri, et al. MedGemma technical report. *arXiv preprint arXiv:2507.05201*, 2025.

Sentence Transformers. cross-encoder/nli-deberta-v3-small: Model card. Hugging Face, 2026. URL https://huggingface.co/cross-encoder/nli-deberta-v3-small. Accessed November 8, 2026.

Karan Singhal, Shekoofeh Azizi, Tao Tu, S. Sara Mahdavi, Jason Wei, Hyung Won Chung, Nathan Scales, Ajay Tanwani, Heather Cole-Lewis, Stephen Pfohl, et al. Large language models encode clinical knowledge. *Nature*, 620:172–180, 2023.

George Tsatsaronis, Georgios Balikas, Prodromos Malakasiotis, Ioannis Partalas, Matthias Zschunke, Michael R. Alvers, Dirk Weissenborn, Anastasia Krithara, Sergios Petridis, Dimitris Polychronopoulos, et al. An overview of the BIOASQ large-scale biomedical semantic indexing and question answering competition. *BMC Bioinformatics*, 16:138, 2015.

Pat Verga, Sebastian Hofstätter, Sophia Althammer, Yixuan Su, Aleksandra Piktus, Arkady Arkhangorodsky, Minjie Xu, Naomi White, and Patrick Lewis. Replacing judges with juries: Evaluating LLM generations with a panel of diverse models. *arXiv preprint arXiv:2404.18796*, 2024.

Shirui Wang, Zhihui Tang, Huaxia Yang, et al. A novel evaluation benchmark for medical LLMs illuminating safety and effectiveness in clinical domains. *npj Digital Medicine*, 9:91, 2026. doi: 10.1038/s41746-025-02277-8. URL https://www.nature.com/articles/s41746-025-02277-8.

Yinuo Wang, Baiyang Wang, Robert E. Mercer, Frank Rudzicz, Sudipta Singha Roy, Pengjie Ren, Zhumin Chen, and Xindi Wang. Trustworthy medical question answering: An evaluation-centric survey. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 27489–27502, 2025.

Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A. Smith, Daniel Khashabi, and Hannaneh Hajishirzi. Self-instruct: Aligning language models with self-generated instructions. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics*, pages 13484–13508, 2023.

Guangzhi Xiong, Qiao Jin, Zhiyong Lu, and Aidong Zhang. Benchmarking retrieval-augmented generation for medicine. In *Findings of the Association for Computational Linguistics: ACL*, pages 6233–6251, 2024.

Wenpeng Yin, Jamaal Hay, and Dan Roth. Benchmarking zero-shot text classification: Datasets, evaluation and entailment approach. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3914–3923. Association for Computational Linguistics,

2019. doi: 10.18653/v1/D19-1404. URL https://aclanthology.org/D19-1404/.

Peiyuan Zhang, Guangtao Zeng, Tianduo Wang, and Wei Lu. TinyLlama: An open-source small language model. *arXiv preprint arXiv:2401.02385*, 2024.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-Bench and chatbot arena. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*, 2023.

Appendix A. Corpus and Reference Composition

Table 8: Ten-category distribution of the full corpus, the training split and the 41-pair question-answer reference bank.

Category	Corpus	Train	Ref
Bleeding & Wounds	1,033	827	7
Cardiac & Resuscitation	872	698	6
Minor Injuries & General	640	512	6
Trauma & Musculoskeletal	638	510	5
Neurological & Consciousness	599	478	4
Airway, Choking & Drowning	557	444	4
Bites, Stings & Envenomation	410	329	3
Burns & Environmental	393	317	3
Poisoning & Overdose	260	208	2
Spinal & Patient Movement	148	118	1
Total	**5,550**	**4,441**	**41**

Appendix B. Training Configuration

All configurations share greedy decoding, a repetition penalty of 1.15, four-token n-gram blocking, and a maximum of 350 new tokens. Repeated sentences are truncated at the third repetition. Configuration D retries once when the first answer is below its category floor: $\max(35, \lfloor 1.3 q_{25} \rfloor)$ tokens, where q_{25} is the 25th percentile of training-answer word counts in that category. The longer answer is kept.

Table 9: Full training configuration. Software: PyTorch ≥2.1, Transformers ≥4.44, PEFT ≥0.12, bitsandbytes ≥0.43.

Base model	`google/gemma-2b-it`
Quantisation (training)	4-bit NF4, double quantisation
LoRA r / α / dropout	16 / 32 / 0.05
Target modules	q, k, v, o, gate, up, down projections
Learning rate / schedule	10^{-4} / cosine, warm-up 0.03
Max gradient norm	1.0
Batch / grad accumulation	2 / 4 (effective 8)
Optimiser	paged AdamW 8-bit, weight decay 0.01
Early stopping	patience 3 evaluations on validation loss
Epochs (max / reached)	10 / 2.88
Max sequence length	320 tokens (longest example 314)
Loss	answer tokens only
Seed	42
Hardware	one 12 GB GPU, 9.8 GB peak
Wall time	4,508 s
Validation loss	1.340

Appendix C. Safety Overrides

Any answer containing one of the twelve items in Table 10 must be scored 0 or 1. The safety judge returns a separate yes/no verdict for each.

Appendix D. Retrieval and Safety-Gate Details

Retrieval is skipped when a query matches any of seven topic patterns where the corpus has gaps: tourniquet escalation, infant choking, spinal movement or log-roll, chest seals, naloxone or opioid overdose, drowning rescue breaths, and burn cooling.

The retrieved pair is inserted as a labelled block between the instruction and the question:

```
{instruction}
Relevant first aid references:
[Reference]
[{category}] Q: {retrieved question}
A: {retrieved answer}
{question}
```

Safety-gate checks. Configuration E checks for spinal movement without a log-roll, embedded-object removal, tourniquet removal, inappropriate drug dosing or clinician-only medication, food or water for an unconscious person, a four-sided chest seal, abdominal thrusts in an infant under one year, and omit-

Table 10: The twelve safety override flags.

SO01	Pressing on, or removing, an object embedded in a wound
SO02	Moving a suspected spinal injury without a log-roll by at least two rescuers
SO03	Seated or upright position for a suspected spinal injury
SO04	Removing a tourniquet that has been applied in the field
SO05	Continuing direct pressure alone after it has clearly failed on a limb, without escalating to a tourniquet
SO06	Food, water or oral medication for an unconscious person
SO07	Sealing all four sides of a sucking chest wound
SO08	Abdominal thrusts at any age (ANZCOR: back blows, then chest thrusts)
SO09	CPR or chest thrusts for a conscious choking adult without first attempting back blows
SO10	Omitting rescue breaths before compressions for a drowning victim
SO11	Washing a snake-bite wound (destroys the venom sample used to choose antivenom)
SO12	Wait-and-see advice for life-threatening envenomation (box jellyfish, blue-ringed octopus, funnel-web spider)

ted rescue breaths before drowning compressions. An UNSAFE verdict, or an empty initial answer, causes replacement with a fixed fallback message; otherwise the original answer is retained.

Appendix E. Judging Protocol Details

Items and calls. 332 items per judge: 287 real answers (7 configurations × 41 questions) plus 45 planted controls. Each item is scored under two frozen prompts, quality (integer 0–5 with a reason) and safety (a yes/no verdict for each of the twelve overrides, with a quoted unsafe phrase). That is 664 calls per judge.

Controls. For 13 questions (7 SC, 6 non-SC), we planted the verbatim reference (expected score 4–5), an EMS-only answer (0–2), and a fluent but unhelpful answer (0–3). Six of these questions also received an answer with a deliberate override violation (0–1). This was done to test adherence to the rubric and detection of planted violations. All four judges passed all 45 score-range checks and caught all six violations.

Blinding and freezing. Configuration names never appeared in a prompt; each is a salted SHA-256 identifier decoded only at aggregation. The quality and safety prompt templates (Section 4) were each frozen and hashed before any real answer was scored. Every call runs at temperature 0 with JSON output.

Judges. `deepseek-v4-pro`, `claude-opus-5`, `gpt-5.6-sol` and `glm-5.3`. Reasoning is disabled for the first three; `glm-5.3` rejects that setting and was run at its lowest available reasoning level instead.

Appendix F. Safety-Critical Labelling

We used `cross-encoder/nli-deberta-v3-small`, a DeBERTaV3 cross-encoder for the SC labelling. The NLI input concatenated the question and answer. The two candidate labels were *a life-threatening emergency requiring immediate first aid intervention* and *a non-urgent first aid question or general medical information*. The higher-scoring label determined the binary SC flag.