

Adversarial Training for Tabular Credit Scoring: A Multi-Attack Robustness Evaluation in P2P Lending

Gijs A. F. Niewzwaag^a, Marijn G. S. Veth^a, Manuele Massei^a, Marcos R. Machado^{a,*}

^a*University of Twente, Faculty of Behavioural, Management and Social Sciences, Department of High-Tech Business and Entrepreneurship, AE Enschede, 7500, Netherlands*

Abstract

Machine learning-based credit scoring is increasingly central to Peer-to-Peer (P2P) lending, yet its resilience to adversarial manipulation—where applicants strategically alter self-reported inputs to secure favourable decisions—remains poorly understood. Most adversarial-robustness evidence comes from image and text domains and evaluates a single attack against a matching defence, offering little guidance on how defences generalise across attack types in tabular credit data. We address this with a systematic train–test robustness benchmark on a large Lending Club subset, spanning three model families (logistic regression, a feed-forward neural network, and a transformer for tabular data) and four attacks confined to applicant-mutable features: Fast Gradient Sign Method (FGSM), Projected Gradient Descent (PGD), Salt-and-Pepper (S&P) noise, and DeepFool plus a mixed-attack regime. Across a full grid evaluated with stratified cross-validation, adversarial training sharply improves robustness against the attack it is trained on and transfers well within the gradient-based family, but transfers weakly to non-gradient corruption—so single-attack defences overstate real-world resilience. Mixed training delivers the most balanced robustness across heterogeneous attacks while preserving clean-test performance, supporting multi-attack stress testing in credit-model governance.

Keywords: Adversarial Machine Learning, Credit Risk Assessment, Peer-to-Peer Lending, Robustness

1. Introduction

Access to affordable credit is essential for economic mobility and social inclusion. Yet, globally, more than 1.4 billion adults remain unbanked and lack access to formal financial services (World Bank, 2022). Even in advanced economies, gaps persist, particularly among low-income households, immigrants, and minority groups. Roughly 11% of adults in the United States are either credit invisible or unscored, with Black and Hispanic communities disproportionately affected (Board of Governors of the Federal Reserve System, 2024). Digital lending channels and alternative finance have expanded credit provision, but they also intensify reliance on automated decision systems whose reliability depends on data integrity and model robustness.

Credit risk assessment remains a cornerstone of financial decision-making for both traditional institutions and emerging actors in alternative finance (Djeundje et al., 2021). While commercial banks have historically relied on proprietary scoring models and regulated data sources, Peer-to-Peer (P2P) lenders, crowdfunding platforms, and fintech startups increasingly leverage alternative data and Machine Learning (ML) models to evaluate creditworthiness (Zhang et al., 2020; Emekter et al., 2015). Irrespective of the institutional setting, the core task is to infer the likelihood that a borrower will repay a loan based on available information (Boyes et al., 1989). In practice, these inferences can be highly sensitive to feature engineering choices, model class, and noise or errors in the input data, making robustness a central concern for any operational credit scoring pipeline (Emekter et al., 2015).

*Corresponding author: Marcos R. Machado (m.r.machado@utwente.nl, Tel. +31 534899045).

Email addresses: g.a.f.niewzwaag@student.utwente.nl (Gijs A. F. Niewzwaag), m.g.s.veth@student.utwente.nl (Marijn G. S. Veth), manuele.massei@utwente.nl (Manuele Massei), m.r.machado@utwente.nl (Marcos R. Machado)

A growing and under-addressed dimension of robustness in credit scoring is vulnerability to deliberate input manipulation. As ML-based scoring becomes embedded in digital application flows, the attack surface expands: adversaries may strategically perturb input variables to obtain more favourable decisions or to degrade a lender’s risk models (Straus et al., 2025; Schwab & Kriebel, 2025). Such perturbations do not need to be large to be consequential; they can be small, targeted, and designed to exploit the geometry of a model’s decision boundary (Straus et al., 2025; Schwab & Kriebel, 2025). This connects credit scoring directly to Adversarial Machine Learning (AML), a field that studies how models behave under adversarially crafted inputs and how defences such as adversarial training can mitigate these risks (Straus et al., 2025; Schwab & Kriebel, 2025).

The rapid adoption of AI in credit underwriting has also prompted regulatory and supervisory attention. Credit scoring is widely considered a high-stakes application because it can constrain individuals’ financial opportunities and may lead to systemic risks when deployed at scale. In the European Union, the AI Act¹ designates credit scoring as a high-risk AI application, introducing obligations for risk management, documentation, transparency, and human oversight throughout the model lifecycle. Complementary legal regimes, including GDPR² provisions on automated decision-making and long-standing anti-discrimination and consumer protection rules, further shape how scoring models can be developed, monitored, and audited. Other jurisdictions, including the United States³, Brazil⁴, and China⁵, have likewise advanced governance frameworks for AI-enabled decision-making in finance. These developments underscore that credit scoring pipelines must be not only accurate under benign conditions, but also resilient to input perturbations and auditable under realistic threat scenarios.

From a methodological perspective, AML offers a diverse toolbox of attacks and defences. Gradient-based attacks such as the Fast Gradient Sign Method (FGSM) and Projected Gradient Descent (PGD) craft perturbations by exploiting local loss gradients, often under explicit norm constraints (Naseem, 2024; Naqvi et al., 2023; Gupta et al., 2018). Boundary-seeking methods such as DeepFool aim to identify small, targeted changes that flip predictions (Moosavi-Dezfooli et al., 2016), while non-gradient perturbations (e.g., noise-based manipulations such as Salt-and-Pepper) can approximate data corruption or opportunistic manipulation without requiring gradient access (Azzeh et al., 2018). On the defence side, adversarial training is a prominent approach, but its effectiveness depends on the attack model used during training and the extent to which robustness transfers to unseen attacks (Naseem, 2024; Naqvi et al., 2023; Gupta et al., 2018; Moosavi-Dezfooli et al., 2016; Azzeh et al., 2018). In applied financial settings, evidence remains limited on exhaustive, hybrid evaluations that mix multiple attacks during training and systematically assess cross-attack generalisation in out-of-sample data. This gap is consequential because operational attackers are unlikely to adhere to a single threat model, and robustness evaluated under one-to-one attack–defence pairings may overstate real-world resilience.

This study addresses these challenges by investigating whether adversarial training can enhance the robustness of credit scoring models in P2P lending. Using the Lending Club dataset⁶ and state-of-the-art AML techniques, we systematically evaluate model performance under multiple adversarial attack families, including gradient-based and non-gradient perturbations. The analysis is guided by the following central research question: *To what extent can adversarial training enhance the robustness of credit scoring models in P2P lending against both gradient-based and non-gradient adversarial attacks?*

The main contributions of this paper are threefold. First, we provide a comprehensive empirical evaluation of AML in P2P credit risk assessment by testing multiple attack algorithms, DeepFool, Salt-and-Pepper noise, FGSM, and PGD, thereby covering qualitatively different perturbation mechanisms, and by constraining perturbations to applicant-mutable features to reflect realistic manipulation of self-reported inputs. Second, we introduce and assess mixed training–testing strategies that intentionally vary the type of attack used during adversarial training and the type encountered at evaluation time. This design enables a systematic analysis of cross-attack generalisation (i.e., whether training for one threat improves robustness to other

¹<https://digital-strategy.ec.europa.eu/en/policies/regulatory-framework-ai>

²<https://gdpr-info.eu/>

³<https://www.congress.gov/crs-product/R48555>

⁴<https://www.gov.br/mcti/pt-br/acompanhe-o-mcti/transformacaodigital/arquivosinteligenciaartificial/>

⁵<https://www.twobirds.com/en/capabilities/artificial-intelligence/ai-legal-services/ai-regulatory-horizon-tracker/china>

⁶<https://www.lendingclub.com/>

threats) and whether robustness transfers across perturbation families. Third, by benchmarking adversarially trained models against standard baselines on real-world lending data, we derive practical guidance on which modelling and training choices preserve predictive performance when inputs are strategically manipulated.

The remainder of the paper is structured as follows. Section 2 reviews related literature on credit scoring, ML models, and adversarial machine learning. Section 3 outlines the methodological approach, including the CRISP-ML process, adversarial techniques, dataset, preprocessing, and model implementation. Section 4 presents and discusses the empirical findings. Finally, Section 5 concludes with key insights and directions for future research.

2. Literature Review

This section positions the study within three interrelated directions: (i) credit risk modelling in traditional and ML settings, with an emphasis on P2P lending; (ii) AML and robustness for tabular decision systems; and (iii) the security, ethical, and regulatory constraints that shape the deployment of AI in credit underwriting. We conclude by synthesising the key research gaps and the how this study adds to the literature in this field.

2.1. Traditional versus ML Methods for Credit Risk Assessment

Credit risk assessment has traditionally relied on structured, rule-based methodologies developed and refined over decades (Boyes et al., 1989; Masters, 1982; Altman, 1980). Classical approaches, often based on logistic regression or expert-driven scorecards, primarily use curated data from credit bureaus, loan performance histories, and manually engineered features (Siddiqi, 2017). Their strengths lie in interpretability, stability, and regulatory familiarity. However, such models are limited in their ability to adapt to complex borrower behaviours or capture subtle patterns in diverse and dynamic financial environments.

By contrast, ML approaches offer greater flexibility and predictive capacity. ML models can identify non-linear relationships and high-dimensional feature interactions, thereby improving decision-making speed and accuracy (Machado & Karray, 2022; Goldmann & Machado, 2025). Moreover, they can integrate alternative data sources such as mobile usage, utility payments, and digital footprints, which are especially valuable for applicants lacking formal credit histories (Svitla Systems, 2024). This data-driven adaptability has positioned ML as a powerful tool for expanding credit access in emerging and digital-first economies (van Braak et al., 2025).

Key distinctions between traditional and ML-based methods include (Machado & Karray, 2022; Machado et al., 2025; Goldmann & Machado, 2025; Boyes et al., 1989; Masters, 1982; Altman, 1980; Mokheleli & Museba, 2023):

- **Data Sources:** Traditional models rely on regulated and static datasets, while ML models expand the scope to dynamic, heterogeneous, and often real-time data streams.
- **Automation:** ML enables scalable and automated decision-making through APIs and intelligent scoring systems.
- **Pattern Recognition:** ML uncovers complex, nonlinear relationships often missed by linear models, improving performance across heterogeneous borrower pools.
- **Bias Handling:** Depending on design, ML can either amplify or mitigate biases. When fairness constraints are incorporated, ML has been shown to reduce discrimination more effectively than rule-based approaches.

Empirical evidence consistently shows that ML models, particularly ensemble methods such as random forests and gradient boosting, outperform traditional techniques across metrics including precision, recall, AUCPR, and F1-score (Mokheleli & Museba, 2023; West, 2000). Yet, these improvements come with trade-offs in interpretability, validation complexity, and regulatory compliance. Since credit decisions carry significant societal and legal implications, robustness and explainability remain critical dimensions alongside accuracy (Heng & Subramanian, 2022; Patil et al., 2024; Nallakaruppan et al., 2024). These tensions motivate closer attention to robustness in adversarial settings, particularly in digital lending contexts where inputs may be noisy or strategically manipulated (Yan et al., 2015; Caldieraro et al., 2018).

2.1.1. Credit Risk Assessment in P2P Lending

P2P lending platforms have redefined credit intermediation by directly connecting borrowers with lenders (Liang & He, 2020; Zhang et al., 2020; Laia, 2025; Del Sarto, 2025). These platforms rely heavily on algorithmic risk assessment to replace or supplement traditional underwriting. Compared to banks, which are subject to conservative regulation and rely on standardised scoring, P2P platforms often employ greater flexibility in data sourcing, feature engineering, and model experimentation. This allows rapid innovation, but also heightens exposure to risks concerning model quality, fairness, and security (Zhang & Yu, 2024). In particular, the predominantly digital and scalable nature of P2P underwriting can increase the likelihood that application inputs are incomplete, inconsistent, or intentionally distorted (Chen et al., 2025; Del Sarto, 2025).

Zhang & Yu (2024) propose a framework for understanding P2P credit risk models along three dimensions: classification algorithms, data traits, and learning methods. Among these, classification algorithms remain central. As summarised in Table 1, based on Zhang & Yu (2024)’s study, there are four broad algorithm categories that dominate the literature on this topic.

Table 1: Summary of classification algorithms.

Classification Algorithms	Advantages	Disadvantages
Traditional Single Classifiers	Interpretable, low complexity	Limited capacity for nonlinear data
Intelligent Single Classifiers	High accuracy on structured inputs	Sensitive to noise and parameter tuning
Hybrid Multiple Classifiers	Better generalization	High training complexity, reduced interpretability
Ensemble Multiple Classifiers	Robust and scalable	Black-box nature, difficult to audit

Beyond model choice, feature engineering is pivotal. In P2P contexts, borrowers often lack extensive credit histories, requiring reliance on diverse predictors. A review by Segun et al. (2024) identifies five recurring categories: (i) demographic variables, (ii) financial history, (iii) employment and income, (iv) loan and application characteristics, and (v) macroeconomic context. The richness of these features highlights both the opportunities and vulnerabilities of P2P models. Models that leverage diverse data may achieve high predictive power, but they can also become more susceptible to perturbations and gaming, especially when features are self-reported or weakly verifiable (Diao et al., 2025; Wang et al., 2025), a key motivation for this paper’s research question.

In this study, a Neural Network (NN) is selected as the baseline model, reflecting its ability to handle structured, high-dimensional inputs and its compatibility with adversarial training (West, 2000; He et al., 2025b). This methodological choice directly supports our objective of assessing how adversarial robustness can be integrated into practical P2P credit risk modelling.

2.2. Adversarial ML and Robustness

Adversarial Machine Learning (AML) investigates the vulnerability of ML systems to strategically crafted perturbations designed to mislead predictions (Sarkar et al., 2018; Holla et al., 2025). Such attacks are typically subtle and may remain undetected by standard validation processes that assume i.i.d. test conditions (Madry et al., 2017; Naqvi et al., 2023). Given the growing deployment of ML in high-stakes domains such as finance and healthcare, understanding and mitigating adversarial risk has become a critical research frontier (Jedrzejewski et al., 2024; Pelekis et al., 2025).

Attacks are commonly classified along four dimensions (Jedrzejewski et al., 2024; Holla et al., 2025):

- **Attacker Knowledge:** White-box (full access), black-box (no access), or gray-box (partial access).
- **Specificity:** Targeted (forcing a particular misclassification) or untargeted (any misclassification).
- **Objective:** Integrity (misleading predictions), availability (denying service), or privacy (extracting sensitive data).
- **Phase:** Evasion (during inference) or poisoning (during training).

This study implements five representative adversarial configurations: the Fast Gradient Sign Method (FGSM), Projected Gradient Descent (PGD), Salt-and-Pepper (S&P) noise, and DeepFool as a boundary-seeking attack. In addition, we employ a mixed training scheme that combines these techniques to more rigorously stress-test model robustness (Moosavi-Dezfooli et al., 2016; Naqvi et al., 2023; Madry et al., 2017). FGSM and PGD represent white-box evasion attacks exploiting gradient information (Naqvi et al., 2023; Madry et al., 2017), whereas S&P simulates non-gradient corruption through high-variance perturbations (Azzeh et al., 2018). Together, these attacks provide a testbed to evaluate the resilience of conventional and adversarially trained models in both gradient-based and non-gradient scenarios (Kabir et al., 2025; Niu et al., 2025).

Robustness in ML refers to the stability of predictions under unexpected, noisy, or adversarial inputs (Holla et al., 2025). In credit risk assessment, robustness failures may lead to serious consequences, such as granting loans to fraudulent applicants or mispricing risk under strategic behaviour (Heß & Damasio, 2025; Jakubik & Teleu, 2025). Thus, robustness must be considered alongside accuracy as a core performance dimension (Dubrov, 2023). Adversarial training, which augments datasets with perturbed examples, is among the most established defences. It encourages models to form smoother, more resilient decision boundaries (Pelekis et al., 2025; Madry et al., 2017), though often at the cost of reduced clean-data accuracy.

By evaluating how NNs trained with adversarial examples perform relative to standard models, this paper directly addresses the central research question on the potential of adversarial training to enhance robustness in P2P credit risk assessment.

2.3. Security, Ethics, and Regulatory Aspects of Credit Risk Assessment

The deployment of AI in credit scoring is not only a technical challenge but also an ethical and regulatory one (Mathen & Paul, 2025). Algorithmic decisions must safeguard fairness, privacy, and accountability to prevent exacerbating existing inequalities.

Adversarial attacks can compromise fairness by enabling certain applicants to exploit vulnerabilities, thereby disadvantaging honest borrowers (Meding & Hagendorff, 2024). Moreover, biases may be amplified if marginalised groups are disproportionately misclassified under attack (Kozodoi et al., 2021). Privacy risks arise when adversaries attempt to infer sensitive information or reconstruct training data, raising significant legal concerns under data protection regimes such as the GDPR. Beyond individual harms, robustness failures can undermine platform trust and increase losses through systematic misclassification of risky loans (Huang, 2025; Atahau et al., 2025).

Regulatory frameworks increasingly demand robust and transparent systems. In the EU, the AI Act designates credit scoring as “high-risk,” requiring strict documentation, explainability, and human oversight (AIA, 2024; European Parliament, 2025). In the United States, laws such as the Equal Credit Opportunity Act (ECOA) and the Fair Credit Reporting Act (FCRA) impose accountability and anti-discrimination obligations (Federal Reserve Board, 2024). Meeting these standards requires methods that strengthen robustness while preserving interpretability. Recent work suggests that integrating robustness evaluation into model governance and assurance processes can support compliance by making performance more stable and auditable under realistic stress scenarios (Huang, 2025; Atahau et al., 2025; Kozodoi et al., 2021; Sarkar et al., 2018). Advances in defence-oriented methods (including explanation-guided defences in credit settings) further indicate that robustness and accountability need not be mutually exclusive (Straus et al., 2025).

2.4. Research Gaps

Despite growing interest in AML, the credit risk literature still provides limited evidence on how to systematically evaluate and build robustness for structured credit datasets—particularly in P2P lending contexts. Three gaps are especially salient.

First, many AML studies are developed around image or text domains, and their evaluation protocols do not readily transfer to structured tabular decisioning where feature constraints, discreteness, and plausibility requirements matter (Azzeh et al., 2018; Naqvi et al., 2023). While recent benchmarking efforts for tabular attacks improve comparability and tooling, they are typically domain-agnostic and do not focus on credit-specific constraints or regulatory expectations (He et al., 2025b). This limits direct guidance for financial institutions and P2P platforms seeking to operationalise AML stress testing.

Second, work that does examine robustness in finance often evaluates a narrow set of attacks or relies on single-pair attack–defence assessments (e.g., training and testing on the same attack family), which provides limited insight into cross-attack generalisation (Madry et al., 2017; Pelekis et al., 2025; Jedrzejewski et al., 2024). In deployment, however, attackers may adapt, combine perturbation styles, or exploit the absence of gradient access, making robustness claims under one threat model potentially brittle (Nallakaruppan et al., 2024; Sarkar et al., 2018). A comprehensive assessment therefore requires testing multiple AML algorithms spanning different perturbation mechanisms and attacker assumptions.

Third, the literature rarely explores hybrid training–testing strategies that intentionally mix training attacks and evaluation attacks, or that assess whether robustness learned under one perturbation family transfers to others in out-of-sample data. This is a central practical question for model governance: if organisations can only afford to train against a subset of attacks, which subset (or specific model) offers the best overall resilience? Addressing this gap aligns directly with the contributions stated in Section 1, where we propose an exhaustive multi-attack evaluation and mixed training–testing design.

To make these gaps explicit and to connect prior work to our contribution, Table 2 summarises representative studies and indicates whether they (i) address credit risk, (ii) focus on P2P settings, (iii) consider AML, (iv) evaluate multiple AML attacks, and (v) test mixed training–testing across different AML algorithms, the final row reports the characteristics of this study.

Table 2: Overview of representative related studies and coverage of AML robustness dimensions (illustrative mapping based on stated focus of each work).

Study	Credit risk	P2P	AML	Multiple attacks	Mix train/test
Boyes et al. (1989)	Yes	No	No	No	No
Siddiqi (2017)	Yes	No	No	No	No
West (2000)	Yes	No	No	No	No
Emekter et al. (2015)	Yes	Yes	No	No	No
Zhang et al. (2020)	Yes	Yes	No	No	No
Liang & He (2020)	Yes	Yes	No	No	No
Zhang & Yu (2024)	Yes	No	No	No	No
Sarkar et al. (2018)	Yes	Yes	Yes	Yes	No
Naidu (2019)	Yes	No	Yes	No	No
Schwab & Kriebel (2025)	Yes	Yes	Yes	No	No
Straus et al. (2025)	Yes	Yes	Yes	No	No
He et al. (2025b)	No	No	Yes	Yes	No
Jedrzejewski et al. (2024)	No	No	Yes	Yes	No
Pelekis et al. (2025)	No	No	Yes	Yes	No
This study	Yes	Yes	Yes	Yes	Yes

Table 2 highlights then that prior work establishes the value of ML for credit scoring and highlights the emerging relevance of AML. However, the literature provides limited guidance on exhaustive and hybrid robustness evaluation for P2P credit risk models. Our study addresses this gap by systematically testing multiple AML algorithms (DeepFool, S&P, FGSM, PGD) and by evaluating mixed training–testing strategies to quantify cross-attack generalisation on real-world P2P lending data.

3. Materials and Methods

3.1. Overview and Process Model

Our experimental pipeline is inspired by the CRISP–ML lifecycle: Business Understanding, Data Understanding, Data Preparation, Modelling, Evaluation, and (optional) Deployment, which extends CRISP–DM for predictive ML systems and emphasises quality assurance, including robustness checks (Studer et al., 2021; Wirth & Hipp, 2000). Rather than reproducing CRISP–ML verbatim, we translate its principles into a step-by-step experimental design tailored to adversarial robustness in P2P credit risk assessment. Figure 1 provides an overview, moving from Data Collection and Data Preprocessing (cleaning, encoding, feature engineering, outlier handling, and scaling) to modelling and evaluation.

We benchmark three model families representative of common approaches for tabular credit scoring (Gouvêa & Gonçalves, 2007; Zhu et al., 2016; Machine): a linear model (logistic regression), a neural model (feed-forward neural network), and a transformer-based model for tabular data. To emulate manipulation of applicant inputs at inference time, we generate perturbed samples using four adversarial techniques: Fast Gradient Sign Method (FGSM), Projected Gradient Descent (PGD), DeepFool, and Salt-and-Pepper (S&P) noise (Azzeh et al., 2018; Naseem, 2024; Kabir et al., 2025). FGSM, PGD, and DeepFool capture gradient-based (white-box) perturbations, whereas S&P represents a non-gradient corruption mechanism; in addition, we define a mixed configuration that combines these perturbations within a single adversarial-augmentation scheme.

The experimental design follows a train and test matrix across perturbation types (see Figure 1). For each model family, we train on clean data and on adversarially augmented data produced by FGSM, PGD, S&P, DeepFool and the mixed scheme, and then evaluate on both clean and perturbed test sets generated by each attack type. This setup supports evaluation of same-attack robustness and cross-attack generalisation. Performance is measured using ROC AUC, accuracy, precision, recall, and F1-score on clean data, alongside adversarial accuracy on perturbed inputs, with stratified 5-fold cross-validation to obtain reliable estimates.




Figure 1: Experimental Setup of this Study.

3.2. Dataset and Data Exploration

We use a widely studied subset of the Lending Club loan dataset⁷, comprising nearly 400,000 observations and 28 features spanning borrower characteristics, loan terms, and credit history attributes (see Figures 2a–2b and Table 3)⁸. Consistent with prior work on consumer credit modelling (van Braak et al., 2025; Machado & Karray, 2022; Zhang et al., 2020), we include both numerical (e.g., loan_amnt, int_rate, dti) and categorical variables (e.g., term, grade, purpose). Exploratory analysis reveals a clear class imbalance: Fully Paid loans substantially outnumber Charged Off loans (Figure 2a), which motivates the use of robust validation procedures and threshold-insensitive metrics (e.g., ROC AUC) in addition to accuracy. The descriptive statistics (Table 3) further highlight typical operational data issues, including heavy-tailed distributions and extreme values (e.g., dti and revol_util), as well as limited missingness (notably in revol_util).

These dataset characteristics are directly relevant for adversarial ML. Figure 2b indicates that several numerical features exhibit non-negligible associations with loan status, with int_rate showing the strongest

⁷<https://www.kaggle.com/datasets/adarshsng/lending-club-loan-data-csv>

⁸The full dataset posed loading and preparation issues, given order of complexity of methods explored in the study; we therefore proceed with a curated subset that preserves the original schema and distributional properties.

(negative) correlation and variables such as `mort_acc` and `annual_inc` showing positive correlations, while most other features are weakly correlated. From a robustness perspective, this suggests that adversarial perturbations targeted at a small subset of influential variables may disproportionately affect predictions, even if the overall linear correlation structure appears modest (Azzeh et al., 2018; Naseem, 2024; Kabir et al., 2025). At the same time, the presence of outliers and implausible values underscores a practical challenge for AML on tabular credit data: unconstrained perturbations can easily generate unrealistic applicants, confounding robustness claims. This motivates the subsequent preprocessing and scaling choices, which aim to (i) stabilise model training and (ii) ensure that perturbed samples remain within a plausible numerical range when evaluating robustness under FGSM, PGD, S&P, DeepFool and Mixed perturbations.

Table 3: Descriptive statistics of numerical features

	Loan Amt	Int Rate	Install	Annual Inc	DTI	Open Acc	Pub Rec	Revol Bal	Revol Util	Total Acc
Count	396 030	396 030	396 030	396 030	396 030	396 030	396 030	396 030	395 754	396 030
Mean	14 113.89	13.63	431.84	74 203.17	17.37	11.31	0.17	15 844.53	53.79	25.41
STD	8 357.44	4.47	250.72	61 637.62	18.02	5.13	0.53	20 591.83	24.45	11.89
Min	500	5.32	16.08	0	0	0	0	0	0	0
25%	8 000	10.49	250.33	45 000	11.28	8	0	6 025	35.80	17
Median	12 000	13.33	375.43	64 000	16.91	10	0	11 181	54.80	24
75%	20 000	16.49	567.30	90 000	22.98	14	0	19 620	72.90	32
Max	40 000	30.99	1 533.81	8 706 582	9 999	90	86	1 743 266	892.30	151




Figure 2: Target distribution and correlation with relevant features in the dataset.

3.3. Preprocessing Pipeline

We implement a reproducible preprocessing pipeline that converts the raw Lending Club extract into an analysis-ready table for model training and adversarial evaluation. The steps below consolidate the data cleaning and feature construction decisions used throughout the study (van Braak et al., 2025; Machado & Karray, 2022; Zhang et al., 2020):

- **Target definition and imbalance:** The variable `loan_status` is binarised into Fully Paid versus Charged Off. The resulting class imbalance (Figure 2a) motivates the use of class weighting during training (Section 3.4).
- **Missing values:** Six variables exhibit missingness: `emp_title`, `emp_length`, `title`, `revol_util`, `mort_acc`, and `pub_rec_bankruptcies`. We drop `emp_title` due to high cardinality and more than 5% missingness, and we drop `emp_length` given its weak association with the target (Table 4). We drop `title` as it largely overlaps with `purpose`. For `mort_acc` (9.54% missing), we impute using the conditional mean within `total_acc` strata, leveraging their strong correlation (Figure 2b) (Zhang & Yu, 2024). Rows with missing `revol_util` (0.07%) and `pub_rec_bankruptcies` (0.14%) are removed.

- Categorical encoding: We apply binary encoding to `term` (36/60 months $\rightarrow$ {0,1}) and `initial_list_status` (w/f $\rightarrow$ {0,1}). We map `grade` and `sub_grade` ordinally (A1–G5 $\rightarrow$ 1–35) and then drop `grade` and the raw `sub_grade`. We apply one-hot encoding to `verification_status`, `purpose`, `home_ownership`, `application_type`, and `zip_code`.
- Leakage prevention: We drop `issue_d`, which would not be available at decision time.
- Outlier handling: We remove implausible values using threshold filters informed by Table 3, including anomalous values in `revol_util`, to reduce leverage effects while preserving the bulk of the distribution.
- Feature scaling: We apply Min-Max scaling to [0, 1] for all continuous inputs to ensure comparability across features and to support consistent adversarial perturbation magnitudes.

Table 4: Charged-off rates by employment length.

Employment length / loan status	Paid	Not paid
10+ years	0.8158	0.1842
9 years	0.7995	0.2005
8 years	0.8002	0.1998
7 years	0.8052	0.1948
6 years	0.8108	0.1891
5 years	0.8078	0.1922
4 years	0.8076	0.1923
3 years	0.8048	0.1952
2 years	0.8067	0.1932
1 year	0.8009	0.1991
< 1 year	0.7931	0.2069




Figure 3: Correlation between `mort_acc` and other numeric features

3.4. Model Specification, Training, Testing and Evaluating

We split the dataset into 80% training and 20% test sets. To account for class imbalance, we use class weighting in the loss function to penalise minority-class errors more heavily, preserving the original class distribution and avoiding potential artefacts introduced by resampling (van Braak et al., 2025; Gouvêa & Gonçalves, 2007). All reported results follow the same split logic and evaluation procedure to ensure comparability across models, training regimes, and attack conditions.

We evaluate three model families introduced in Section 2: logistic regression (linear baseline), a feed-forward neural network, and a transformer-based model for tabular data. Table 5 reports the hyperparameters for each architecture. The neural network uses batch normalisation and dropout in the input and hidden layers, a sigmoid output layer for binary classification, binary cross-entropy loss, the Adam optimiser, and early stopping to limit overfitting (West, 2000). Hyperparameters were selected through manual pilot tuning; the clean benchmark achieves a ROC AUC of 0.904, and we deliberately restrict exhaustive hyperparameter search to keep the focus on adversarial robustness rather than maximising clean-data performance.

Table 5: Hyperparameters setting for the different models

Hyperparameter	Neural network	FT-Transformer	Logistic regression
Hidden units	[150, 150, 150]	–	None
Dropout rate(s)	[0.1, 0, 0.1, 0]	0.1	None
Activation function	–	–	Sigmoid
Sequence length	–	4	–
Embedding dimension	–	32	–
Attention heads	–	2	–
Key dimension	–	16	–
Learning rate	$1e-3$	10^{-3}	10^{-3}
Training epochs	20	20	20
Batch size	32	32	32

We focus on evasion attacks at inference time under two attacker knowledge regimes: white-box attacks with gradient access and black-box attacks without gradient access. The attack set follows Section 2 and includes FGSM, PGD, DeepFool, and Salt-and-Pepper (S&P) noise, with an additional mixed condition (part of the major contributions of this work) used for adversarial augmentation and testing:

- FGSM and PGD: gradient-based white-box attacks that perturb inputs using the gradient sign (FGSM) or iterative projected updates (PGD) within an ℓ_∞ ball of radius ε (Sarkar et al., 2018; Holla et al., 2025; He et al., 2025b). We also implement targeted variants that push charged-off cases toward the fully-paid class to reflect incentives in adversarial lending contexts (Sarkar et al., 2018; Holla et al., 2025; He et al., 2025b).
- Salt-and-Pepper (S&P): a non-gradient perturbation that flips a proportion of feature values to extremes, approximating coarse manipulation or data quality shocks (Pelekis et al., 2025; Azzeh et al., 2018).
- DeepFool: a boundary-seeking adversarial attack that iteratively computes the minimal perturbation required to cross the model’s decision boundary under a local linear approximation (Moosavi-Dezfooli et al., 2016). Unlike FGSM and PGD, which operate within a predefined norm budget, DeepFool explicitly targets the closest decision boundary and therefore generates small, targeted perturbations that expose local geometric fragility in the classifier. Hence, not requiring attack strength parameter tuning.

To ensure that adversarial examples correspond to feasible applicant behaviour, we restrict all perturbations to features an applicant could plausibly manipulate: the continuous variables `annual_inc`, `dti`, `revol_bal`, and `revol_util`, and the mutable categorical variables `purpose` and `zip_code`. For the gradient-based attacks (FGSM, PGD, DeepFool), a binary mask zeroes the gradient of all immutable and remaining categorical features during the backward pass, so that only mutable features are updated and impossible feature states (e.g., fractional one-hot values) are never produced. For S&P, min/max flips are applied only to the allowed continuous variables, and categorical corruption is implemented as a structurally valid swap that respects the mutual exclusivity of each one-hot block, deactivating the active category and activating a single alternative within the same block.

Attack strength is tuned to achieve meaningful but plausible degradation without inducing model collapse (Table 6). We select the mid-range setting $\varepsilon = 0.1$ (FGSM/PGD) and `amount=0.1` (S&P). The sensitivity analysis in Table 6 is computed on unconstrained perturbations to bracket the attack budget; once perturbations are restricted to mutable features as described above, the resulting degradation at $\varepsilon = 0.1$ is milder, as reported in Section 4, while predictions remain stable.

Table 6: Attack strength parameter tuning

ϵ /Amount	Accuracy (FGSM)	Accuracy (PGD)	Accuracy (S&P)	ROC AUC (FGSM)	ROC AUC (PGD)	ROC AUC (S&P)
0.4	0.63	0.60	0.66	0.18	0.07	0.57
0.2	0.76	0.74	0.67	0.57	0.36	0.66
0.1	0.77	0.76	0.73 (0.74)	0.78	0.74	0.74 (0.75) ^w
0.05	0.78	0.78	0.77	0.84	0.83	0.81
0.02	0.81	0.81	0.82	0.86	0.86	0.89

Although the primary constraints on attack strength (ϵ and amount of corruption) are selected based on the parameter tuning outlined in Table 6, the internal parameters for iterative attacks are fixed to standard configurations established in the foundational literature. Table 7 reports these internal parameters set for adversarial attacks.

For PGD, 40 iterations are employed with a step size of $\alpha = 0.01$ (Madry et al., 2017). For DeepFool η is set to 0.025 to guarantee decision boundary crossing, slightly increasing overshoot as proposed by (Moosavi-Dezfooli et al., 2016), and the number of max iterations is set to 100 (He et al., 2025a).

Table 7: Hyperparameter settings for adversarial attacks

Attack	Hyperparameter	Value
<i>FGSM</i>	Attack budget (ϵ)	0.1
	Target class	1 (Fully Paid)
<i>PGD</i>	Attack budget (ϵ)	0.1
	Step size (α)	0.01
	Iterations	40
	Target class	1 (Fully Paid)
<i>DeepFool</i>	Max iterations	100
	Overshoot (η)	0.025
	Target class	1 (Fully Paid)
<i>Salt & Pepper</i>	Corruption amount	0.1
	Noise type	Min/Max flip

For each model family, we train one clean baseline and five adversarially augmented variants, using FGSM, PGD, S&P, DeepFool and a mixed augmentation scheme. Adversarial augmentation is implemented by combining 80% clean samples with 20% adversarial samples generated from the corresponding attack method (Figure 1). Each trained model is then evaluated on five test sets: clean, FGSM, PGD, DeepFool, and S&P perturbations. This design enables within-regime comparisons (clean versus attacked test sets) and cross-regime comparisons (training on one perturbation type and testing on another), supporting a direct assessment of robustness transfer across attacks (Sarkar et al., 2018; Holla et al., 2025; He et al., 2025b; Pelekis et al., 2025).

We report accuracy and ROC AUC, together with precision, recall, and F1-score. Given class imbalance, ROC AUC is used as the primary ranking metric (He et al., 2025b). To quantify robustness, we additionally compute adversarial accuracy, defined as predictive performance under perturbed inputs (Pelekis et al., 2025). Estimation stability is assessed via stratified 5-fold cross-validation, preserving class ratios within each fold (van Braak et al., 2025). Results are aggregated into a unified comparison table produced by a single evaluation script; confusion matrices and classification reports are generated for each model and test-set combination. The full experimental code and configuration files are available upon request and can be containerised for deterministic runs⁹.

4. Results and Discussions

This section compares model performance under clean and adversarial conditions, using the evaluation grid described in Section 3.4. We report ROC AUC, accuracy, precision, recall, and F1 for both classes,

⁹Please see repository: <https://github.com/Gijsn888/adversarialresearch>

together with the mean number of predicted non-defaults and defaults. Because misclassifying a default is typically more costly than misclassifying a non-default, we emphasise class-0 metrics (default detection), in particular Recall₀ and F1₀. Confusion matrices are generated for each configuration to support diagnostic interpretation beyond aggregate scores.

4.1. “Clean” Baseline Performance

Table 8 reports clean-train/clean-test results for the three model families. All models achieve strong discrimination (ROC AUC 0.903–0.906). Logistic regression and the transformer achieve the highest accuracy (0.826), while all three models obtain similar ROC AUC (0.903–0.906). Across models, class-1 metrics are higher than class-0 metrics, indicating that non-defaults are easier to classify than defaults. The neural network exhibits the highest Recall₀ (0.765) and the lowest Precision₀ (0.534), reflecting a more conservative tendency to label cases as default, whereas the transformer attains the highest Precision₀ (0.542); logistic regression is comparable to the transformer (Recall₀ 0.756, Precision₀ 0.541).

Table 8: Performance comparison of classification models evaluated on the same Clean Train–Clean Test split. Training and test identifiers are omitted as all metrics refer to an identical data partition.

Model	ROC AUC	Accuracy	Precision ₀	Recall ₀	F1 ₀	Precision ₁	Recall ₁	F1 ₁	Pred. Non-Defaults	Pred. Defaults
Logistic Regression	0.905	0.826	0.541	0.756	0.631	0.934	0.843	0.886	45,367.2	17,232.2
Neural Network	0.903	0.822	0.534	0.765	0.628	0.935	0.836	0.883	44,911.4	17,688.0
Transformer	0.906	0.826	0.542	0.758	0.632	0.934	0.843	0.886	45,341.8	17,257.6

4.2. Impact of adversarial attacks on clean-trained models

We next evaluate clean-trained models on perturbed test sets to measure vulnerability without any defensive training. Because perturbations are restricted to mutable features (Section 3.4), the clean rows in Tables 9, 10, and 11 show moderate rather than severe degradation. Logistic regression declines from ROC AUC 0.904 (clean) to 0.862 under FGSM and PGD and 0.870 under DeepFool. The neural network degrades comparably (ROC AUC 0.872–0.873 under FGSM/PGD and 0.878 under DeepFool), while for the transformer DeepFool is the most damaging attack (ROC AUC 0.856, versus 0.868 under FGSM/PGD). Across all three models, S&P produces a similar decline (ROC AUC 0.855–0.864), indicating that the constrained attacks reduce discrimination consistently but without model collapse.

To assess the stability of these findings, we also ran an extensive cross-validation study using 1-, 2-, 3-, 4-, and 5-fold stratified cross-validation across the same clean-train/attacked-test settings. Appendix A reports the fold-averaged metrics for all cross-validation experiments, summarised separately for A1 (logistic regression), A2 (neural network), and A3 (transformer). These additional results confirm that the observed vulnerability patterns are not driven by a single split and remain consistent across different validation granularities.

The direction of the effect is clearer when examining predicted class counts. Table 12 shows that, for all three models, FGSM and PGD reduce the number of predicted defaults relative to the clean test set (e.g., logistic regression from 17,232.2 to 15,946.8; the neural network from 17,688.0 to 16,617.2 under FGSM). This is consistent with targeted attacks that aim to move default cases toward the non-default class. In contrast, S&P increases the number of predicted defaults for all models and reduces both class-0 and class-1 performance, which is consistent with non-targeted corruption that broadly disrupts feature values rather than systematically inducing class flips.

4.3. Adversarial training and cross-attack generalisation

Adversarial training substantially improves robustness when the training and test perturbations match, especially for gradient-based attacks. For all model families, training on FGSM or PGD raises ROC AUC on FGSM and PGD test sets well above the clean-trained baseline. For example, the neural network reaches ROC AUC 0.952–0.959 on FGSM/PGD tests, with accuracy 0.867–0.882 (Table 10), and the transformer reaches up to ROC AUC 0.980 on FGSM/PGD tests, with accuracy 0.868–0.898 (Table 11). Logistic regression shows the same pattern, reaching ROC AUC 0.947–0.948 on matched tests (Table 9). Robustness also transfers well between FGSM and PGD: models trained on one perform almost identically when tested on the other, reflecting their shared gradient-based structure.

Table 9: Five fold evaluation of the Logistic Regression model trained and tested under different adversarial attack configurations.

Training Set	Test Set	ROC AUC	Accuracy	Prec ₀	Prec ₁	Rec ₀	Rec ₁	F1 ₀	F1 ₁	Pred ND	Pred D
Clean	Clean	0.904	0.823	0.535	0.934	0.758	0.839	0.628	0.884	45146	17453
Clean	FGSM	0.862	0.801	0.497	0.907	0.650	0.839	0.563	0.872	46481	16118
Clean	PGD	0.862	0.801	0.497	0.907	0.650	0.839	0.563	0.872	46481	16118
Clean	S&P	0.861	0.793	0.483	0.926	0.737	0.806	0.583	0.862	43782	18817
Clean	DeepFool	0.870	0.784	0.461	0.887	0.562	0.839	0.507	0.862	47557	15042
FGSM	Clean	0.898	0.831	0.554	0.924	0.710	0.860	0.623	0.891	46820	15779
FGSM	FGSM	0.947	0.862	0.603	0.964	0.868	0.860	0.712	0.909	44874	17725
FGSM	PGD	0.947	0.862	0.603	0.964	0.868	0.860	0.712	0.909	44874	17725
FGSM	S&P	0.855	0.802	0.497	0.915	0.687	0.830	0.577	0.870	45555	17044
FGSM	DeepFool	0.909	0.837	0.566	0.932	0.745	0.860	0.643	0.895	46388	16211
PGD	Clean	0.898	0.817	0.526	0.930	0.745	0.835	0.616	0.880	45129	17470
PGD	FGSM	0.948	0.848	0.572	0.971	0.899	0.835	0.699	0.898	43234	19365
PGD	PGD	0.948	0.848	0.572	0.971	0.899	0.835	0.699	0.898	43234	19365
PGD	S&P	0.855	0.789	0.476	0.922	0.722	0.805	0.573	0.859	43902	18697
PGD	DeepFool	0.910	0.822	0.533	0.936	0.768	0.835	0.629	0.883	44848	17751
S&P	Clean	0.903	0.825	0.539	0.933	0.753	0.842	0.628	0.885	45380	17219
S&P	FGSM	0.864	0.804	0.502	0.908	0.650	0.842	0.567	0.874	46649	15950
S&P	PGD	0.864	0.804	0.502	0.908	0.650	0.842	0.567	0.874	46649	15950
S&P	S&P	0.863	0.795	0.486	0.924	0.729	0.811	0.584	0.864	44114	18485
S&P	DeepFool	0.861	0.794	0.482	0.895	0.599	0.842	0.534	0.868	47280	15319
DeepFool	Clean	0.901	0.814	0.519	0.935	0.765	0.826	0.619	0.877	44440	18159
DeepFool	FGSM	0.918	0.824	0.534	0.947	0.813	0.826	0.645	0.883	43855	18744
DeepFool	PGD	0.918	0.824	0.534	0.947	0.813	0.826	0.645	0.883	43855	18744
DeepFool	S&P	0.858	0.785	0.470	0.926	0.741	0.795	0.576	0.856	43168	19431
DeepFool	DeepFool	0.904	0.815	0.520	0.936	0.768	0.826	0.621	0.878	44400	18199
Mixed	Clean	0.900	0.820	0.531	0.931	0.746	0.838	0.620	0.882	45262	17337
Mixed	FGSM	0.929	0.837	0.558	0.954	0.834	0.838	0.669	0.892	44178	18421
Mixed	PGD	0.929	0.837	0.558	0.954	0.834	0.838	0.669	0.892	44178	18421
Mixed	S&P	0.858	0.791	0.480	0.922	0.722	0.808	0.577	0.861	44060	18539
Mixed	DeepFool	0.906	0.823	0.535	0.934	0.759	0.838	0.628	0.884	45102	17497

Table 10: Five fold evaluation of the Neural Network model trained and tested under different adversarial attack configurations.

Training Set	Test Set	ROC AUC	Accuracy	Prec ₀	Prec ₁	Rec ₀	Rec ₁	F1 ₀	F1 ₁	Pred ND	Pred D
Clean	Clean	0.901	0.815	0.520	0.937	0.773	0.825	0.622	0.877	44274	18325
Clean	FGSM	0.873	0.800	0.494	0.918	0.698	0.825	0.579	0.869	45205	17394
Clean	PGD	0.872	0.800	0.494	0.917	0.697	0.825	0.578	0.869	45212	17387
Clean	S&P	0.855	0.786	0.472	0.928	0.748	0.795	0.579	0.856	43073	19526
Clean	DeepFool	0.878	0.810	0.513	0.931	0.751	0.825	0.610	0.875	44545	18054
FGSM	Clean	0.897	0.848	0.601	0.920	0.684	0.888	0.640	0.904	48555	14044
FGSM	FGSM	0.952	0.880	0.651	0.959	0.847	0.888	0.736	0.923	46549	16050
FGSM	PGD	0.954	0.882	0.653	0.961	0.854	0.888	0.740	0.923	46456	16143
FGSM	S&P	0.852	0.818	0.531	0.912	0.665	0.856	0.591	0.883	47154	15445
FGSM	DeepFool	0.891	0.837	0.580	0.907	0.629	0.888	0.604	0.898	49238	13361
PGD	Clean	0.895	0.835	0.565	0.925	0.713	0.865	0.631	0.894	47033	15566
PGD	FGSM	0.954	0.867	0.614	0.965	0.873	0.865	0.721	0.913	45064	17535
PGD	PGD	0.959	0.870	0.618	0.969	0.888	0.865	0.729	0.914	44885	17714
PGD	S&P	0.854	0.806	0.506	0.917	0.692	0.835	0.585	0.874	45753	16846
PGD	DeepFool	0.895	0.830	0.556	0.919	0.688	0.865	0.615	0.891	47341	15258
S&P	Clean	0.898	0.819	0.529	0.934	0.758	0.834	0.623	0.881	44915	17684
S&P	FGSM	0.863	0.801	0.497	0.911	0.667	0.834	0.569	0.871	46040	16559
S&P	PGD	0.862	0.801	0.496	0.910	0.665	0.834	0.568	0.871	46064	16535
S&P	S&P	0.873	0.798	0.492	0.925	0.732	0.814	0.588	0.866	44244	18355
S&P	DeepFool	0.872	0.810	0.512	0.921	0.709	0.834	0.595	0.876	45520	17079
DeepFool	Clean	0.900	0.806	0.504	0.939	0.787	0.810	0.615	0.870	43363	19236
DeepFool	FGSM	0.888	0.801	0.496	0.933	0.761	0.810	0.601	0.867	43676	18923
DeepFool	PGD	0.889	0.801	0.497	0.933	0.764	0.810	0.602	0.867	43649	18950
DeepFool	S&P	0.853	0.778	0.462	0.930	0.760	0.783	0.574	0.850	42304	20295
DeepFool	DeepFool	0.901	0.805	0.503	0.939	0.784	0.810	0.613	0.870	43396	19203
Mixed	Clean	0.899	0.834	0.562	0.926	0.719	0.862	0.631	0.893	46815	15784
Mixed	FGSM	0.912	0.842	0.574	0.935	0.757	0.862	0.653	0.897	46355	16244
Mixed	PGD	0.915	0.843	0.577	0.937	0.765	0.862	0.658	0.898	46247	16352
Mixed	S&P	0.867	0.807	0.508	0.918	0.696	0.835	0.588	0.874	45700	16899
Mixed	DeepFool	0.898	0.831	0.557	0.923	0.705	0.862	0.622	0.892	46991	15608

Table 11: Five fold evaluation of the Transformer model trained and tested under different adversarial attack combinations. For each training configuration.

Training Set	Test Set	ROC AUC	Accuracy	Prec ₀	Prec ₁	Rec ₀	Rec ₁	F1 ₀	F1 ₁	Pred ND	Pred D
Clean	Clean	0.905	0.824	0.538	0.934	0.759	0.840	0.630	0.885	45216	17383
Clean	FGSM	0.868	0.804	0.502	0.909	0.656	0.840	0.569	0.873	46486	16113
Clean	PGD	0.868	0.804	0.502	0.909	0.656	0.840	0.569	0.873	46486	16113
Clean	S&P	0.864	0.795	0.486	0.927	0.739	0.808	0.586	0.863	43862	18737
Clean	DeepFool	0.856	0.774	0.437	0.874	0.505	0.840	0.469	0.857	48342	14257
FGSM	Clean	0.901	0.846	0.596	0.920	0.684	0.886	0.637	0.903	48443	14156
FGSM	FGSM	0.980	0.898	0.670	0.985	0.944	0.886	0.784	0.933	45233	17366
FGSM	PGD	0.980	0.898	0.670	0.985	0.945	0.886	0.784	0.933	45232	17367
FGSM	S&P	0.858	0.816	0.526	0.912	0.664	0.853	0.587	0.882	47038	15561
FGSM	DeepFool	0.894	0.839	0.582	0.911	0.646	0.886	0.612	0.898	48911	13688
PGD	Clean	0.902	0.828	0.546	0.930	0.739	0.849	0.628	0.888	45920	16679
PGD	FGSM	0.976	0.868	0.606	0.984	0.943	0.849	0.738	0.912	43399	19200
PGD	PGD	0.976	0.868	0.606	0.984	0.943	0.849	0.738	0.912	43399	19200
PGD	S&P	0.861	0.798	0.491	0.922	0.716	0.818	0.582	0.867	44598	18001
PGD	DeepFool	0.911	0.826	0.543	0.927	0.729	0.849	0.622	0.887	46046	16553
S&P	Clean	0.904	0.834	0.561	0.927	0.725	0.861	0.633	0.893	46662	15937
S&P	FGSM	0.864	0.814	0.524	0.903	0.625	0.861	0.570	0.882	47901	14698
S&P	PGD	0.864	0.814	0.524	0.903	0.625	0.861	0.570	0.882	47901	14698
S&P	S&P	0.879	0.813	0.518	0.920	0.703	0.840	0.597	0.878	45876	16723
S&P	DeepFool	0.853	0.783	0.451	0.868	0.467	0.861	0.459	0.864	49847	12752
DeepFool	Clean	0.903	0.835	0.564	0.927	0.722	0.863	0.633	0.894	46818	15781
DeepFool	FGSM	0.894	0.833	0.560	0.924	0.711	0.863	0.627	0.893	46951	15648
DeepFool	PGD	0.894	0.833	0.560	0.924	0.711	0.863	0.627	0.893	46951	15648
DeepFool	S&P	0.864	0.805	0.504	0.920	0.706	0.830	0.588	0.872	45331	17268
DeepFool	DeepFool	0.907	0.832	0.559	0.923	0.707	0.863	0.624	0.892	46999	15600
Mixed	Clean	0.903	0.825	0.539	0.932	0.750	0.843	0.627	0.885	45467	17132
Mixed	FGSM	0.979	0.865	0.598	0.987	0.954	0.843	0.736	0.909	42945	19654
Mixed	PGD	0.979	0.865	0.598	0.987	0.954	0.843	0.736	0.909	42945	19654
Mixed	S&P	0.875	0.799	0.493	0.924	0.728	0.816	0.588	0.867	44379	18220
Mixed	DeepFool	0.917	0.826	0.541	0.934	0.756	0.843	0.631	0.886	45390	17209

Table 12: Mean predicted non-defaults and defaults for models trained on clean data and evaluated under different test-time perturbations. Values represent fold-averaged predictions.

Model	Training Set	Test Set	Predicted Non-Defaults	Predicted Defaults
Logistic Regression	Clean Train	Clean Test	45,367.2	17,232.2
Logistic Regression	Clean Train	DeepFool Test	47,770.4	14,829.0
Logistic Regression	Clean Train	FGSM Test	46,652.6	15,946.8
Logistic Regression	Clean Train	PGD Test	46,652.6	15,946.8
Logistic Regression	Clean Train	S&P Test	43,903.8	18,695.6
Neural Network	Clean Train	Clean Test	44,911.4	17,688.0
Neural Network	Clean Train	DeepFool Test	46,397.4	16,202.0
Neural Network	Clean Train	FGSM Test	45,982.2	16,617.2
Neural Network	Clean Train	PGD Test	45,983.8	16,615.6
Neural Network	Clean Train	S&P Test	43,479.6	19,119.8
Transformer	Clean Train	Clean Test	45,341.8	17,257.6
Transformer	Clean Train	DeepFool Test	47,260.8	15,338.6
Transformer	Clean Train	FGSM Test	46,553.2	16,046.2
Transformer	Clean Train	PGD Test	46,552.2	16,047.2
Transformer	Clean Train	S&P Test	43,923.4	18,676.0

The improvement of ROC AUC for models trained and tested on matching FGSM/PGD requires specific interpretation. Since these attacks apply a fixed-magnitude transformation ($\epsilon = 0.1$) to the mutable features, they introduce a partial structural shift in feature space that the adversarially trained model learns to recognise, making perturbed defaults easier to separate. Because the perturbations are confined to a small set of mutable features rather than the full input, this shift is limited, which is why matched training improves discrimination substantially but does not converge to a perfect score.

By contrast, DeepFool training improves robustness but by a smaller margin than FGSM/PGD. Since DeepFool computes the minimal perturbations required to cross the decision boundary, the adversarial examples remain close to the true class boundary. The resulting improvement therefore reflects genuine boundary hardening rather than recognition of a fixed perturbation pattern.

Cross-attack generalisation to S&P is weaker than within the gradient family, but it is stable rather than catastrophic. Gradient-based adversarial training does not markedly improve S&P robustness: for all three models, FGSM/PGD-trained models attain ROC AUC around 0.852–0.861 and accuracy around 0.79–0.82 on S&P tests, close to the clean-trained models. S&P-based training gives the strongest S&P performance (ROC AUC 0.863 for logistic regression, 0.873 for the neural network, and 0.879 for the transformer) but does not strengthen resistance to FGSM/PGD, consistent with S&P corruption having a different structure from the gradient-based attacks.

The mixed training regime provides the most balanced results for the neural network and transformer. It maintains clean performance while achieving strong robustness on FGSM/PGD and improved resilience under DeepFool. For the transformer, mixed training achieves accuracy 0.825 on the clean test set and 0.826 on the DeepFool test set, while reaching accuracy 0.865 and ROC AUC 0.979 on FGSM/PGD tests, essentially matching the best single-attack model (Table 11). For the neural network, mixed training improves performance under FGSM/PGD relative to clean training while maintaining stable behaviour under S&P (Table 10). These results support the use of multi-attack augmentation when the threat model is uncertain or heterogeneous. As an external robustness check, we reproduce this train–test grid on an independent P2P dataset (Prosper) in Appendix B; the same ordering, matched gradient-based training yields the largest gains, FGSM and PGD remain mutually interchangeable, cross-family transfer to S&P is weak, and mixed training is the most balanced, holds despite that dataset’s lower overall discrimination.

A common concern is that adversarial training may reduce clean-data performance. In our results, this trade-off is limited for the neural network and transformer, and sometimes favourable: adversarially trained variants remain close to the clean benchmarks on the clean test set (e.g., the transformer under FGSM training reaches accuracy 0.846 on the clean test set, slightly above the 0.824 of the clean-trained transformer, while PGD and mixed training reach 0.828 and 0.825, Table 11). Logistic regression shows smaller changes on clean tests and benefits less from adversarial training overall. Overall, the results suggest that, under the selected augmentation ratio and perturbation strengths, improved robustness does not require sacrificing clean performance for the higher-capacity models.

4.4. Comparison with the literature

The findings align with the broader AML literature in which adversarial training is most effective when the training threat model matches the evaluation threat model, particularly for gradient-based attacks (Madry et al., 2017; Pelekis et al., 2025). They also complement work examining adversarial vulnerability and defence mechanisms for credit risk and P2P settings (Sarkar et al., 2018; Schwab & Kriebel, 2025; Straus et al., 2025). The main contribution of this study is the systematic train–test grid across multiple perturbation families, which makes the limits of transfer explicit: robustness under FGSM/PGD does not automatically imply robustness to non-gradient corruption, while mixed training provides a more reliable default when the attacker strategy is unknown.

The study in Table 13 illustrates that augmenting training data with synthetic scenarios can improve predictive performance in credit risk settings (Zhang et al., 2025). While that work does not evaluate targeted evasion attacks, the broader message is consistent with our results: model improvements from augmented data depend on whether the augmented samples reflect the stress conditions a deployed system will face. Our findings extend this perspective by showing that adversarial augmentation produces large gains under the corresponding attack family, and that mixed augmentation is a practical route to stronger resilience under heterogeneous perturbations.

Table 13: Results study (Zhang et al., 2025)

Model	Accuracy	Recall	Precision	F1 Score
SVM	0.83	0.88	0.84	0.89
BPnetwork	0.88	0.93	0.88	0.94
RNN	0.90	0.96	0.90	0.95
LSTM	0.92	0.97	0.93	0.96
GANs	0.96	1.00	0.97	0.97

4.5. Managerial implications

First, the results indicate that clean benchmark performance is not a sufficient proxy for operational reliability. Models with strong clean ROC AUC and accuracy can exhibit sharp degradation under targeted perturbations, including a systematic reduction in predicted defaults under FGSM/PGD. For P2P platforms and lenders, this supports incorporating adversarial stress testing into model validation and ongoing monitoring, using both gradient-based attacks (to represent strategic manipulation) and non-gradient perturbations (to represent data quality shocks and coarse manipulation). Monitoring should prioritise default-sensitive metrics (Recall₀, F1₀) under stress, since these align more directly with credit losses than overall accuracy.

Second, the train–test grid shows that single-attack defences can create a false sense of security. FGSM- and PGD-trained models are highly robust to FGSM/PGD tests, yet this robustness does not fully transfer to non-gradient corruption such as S&P. A practical management response is to adopt mixed or multi-attack training as a default when the attacker strategy is uncertain, especially for higher-capacity models that maintain strong clean performance while gaining robustness across multiple threat conditions. This supports a risk-based hardening strategy: deploy mixed training for high-impact decision segments (large exposures, thin-file borrowers, automated approvals) and maintain periodic re-training as manipulation patterns evolve.

Third, robustness should be paired with operational controls. Because non-gradient perturbations can represent noisy or implausible inputs, lenders can reduce exposure by implementing plausibility checks, consistency rules, and verification against external sources where available, especially for features that are influential in the model. Combined with adversarial training, these controls can reduce both economic loss and model-governance risk by improving stability, auditability, and compliance alignment for high-stakes credit decision systems.

5. Conclusion

This paper examined whether adversarial machine learning can strengthen the robustness of credit risk models in peer-to-peer lending. Motivated by the risk that applicants may manipulate input information to obtain favourable lending decisions, we compared standard training with adversarial training on real-world Lending Club data. The study evaluated three model families commonly used for tabular credit scoring (logistic regression, a feed-forward neural network, and a transformer-based model) under clean conditions and under adversarially perturbed test sets. The central objective was to assess how adversarially trained models compare with traditionally trained models when predictions are made in environments that include targeted and non-targeted input manipulation.

Across models, the results show that adversarial training substantially improves robustness when the attack mechanism used at test time matches the perturbation family used during training. In particular, models trained with gradient-based perturbations show strong resilience to gradient-based attacks, with large improvements in discrimination and default-detection metrics relative to clean-trained baselines evaluated under attack. These robustness gains are achieved without a material deterioration in clean-test performance for the higher-capacity models, suggesting that robustness can be strengthened while maintaining predictive usefulness in normal operating conditions. In contrast, Salt-and-Pepper perturbations behave as coarse, non-gradient corruption and yield smaller robustness gains than the gradient-based attacks when used for training, and this robustness transfers less to the other attack families.

The main contributions of this work are threefold. First, it provides an empirical robustness benchmark for credit scoring on a large P2P dataset using a systematic train–test evaluation grid across multiple attack families. Second, it compares robustness behaviour across three distinct model classes, showing that robustness

profiles differ by architecture and by perturbation mechanism, and that strong clean accuracy does not guarantee resilience under manipulation. Third, it demonstrates the value of hybrid, mixed training strategies for improving robustness under heterogeneous conditions, which is closer to realistic deployment where attacker behaviour may vary and evolve. Together, these contributions help bridge the gap between AML methods developed in other domains and the practical requirements of robust financial decision systems.

5.1. Limitations and future research

This study has several limitations. First, the experiments rely on a curated subset of the Lending Club dataset and a fixed preprocessing pipeline; while this supports reproducibility and controlled comparison, the results may not fully generalise to other lenders, time periods, feature sets, or operational constraints. To probe external validity, Appendix B replicates the entire pipeline, the four attacks, the mutable-feature constraints, and the mixed regime, on an independent P2P dataset (Prosper). The qualitative robustness and cross-attack transfer patterns reported above are preserved on this structurally different and smaller subset, even though its absolute discrimination is markedly lower, which reinforces rather than removes the need for lender-specific validation. Second, the adversarial attacks applied here are stylised approximations of manipulation in tabular data. Although FGSM/PGD provide controlled gradient-based perturbations and S&P represents coarse corruption, these methods do not fully encode feasibility constraints, behavioural incentives, or institutional verification processes that shape real borrower fraud.

Future research should therefore move toward threat models that reflect plausible manipulation strategies in credit applications. This includes constraint-aware attacks that respect feature semantics (e.g., monotonicity, discreteness, and budgeted changes), stronger black-box attacks tailored to tabular finance settings, and scenario-based evaluation that couples AML with domain rules and verification signals. It would also be valuable to study robustness under distribution shift, temporal drift, and policy changes, and to integrate robustness assessment into model governance frameworks with clear decision thresholds and cost-sensitive objectives. Finally, evaluating robustness alongside explainability and compliance requirements, including post-deployment monitoring and incident response, would provide a more complete blueprint for deploying resilient credit risk models in practice.

References

- (2024). Regulation (eu) 2024/1361 of the european parliament and of the council of 13 march 2024 laying down harmonised rules on artificial intelligence (artificial intelligence act). *Official Journal of the European Union*, . URL: <https://eur-lex.europa.eu/eli/reg/2024/1361/oj>. Accessed: 2025-08-06.
- Altman, E. I. (1980). Commercial bank lending: process, credit scoring, and costs of errors in lending. *Journal of financial and quantitative analysis*, 15, 813–832.
- Atahau, A. D. R., Anggara, I. S., & Huruta, A. D. (2025). P2p lending: how does it affect indonesian bank's profitability? *Asian Journal of Accounting Research*, (pp. 1–18).
- Azzeh, J., Zahran, B., & Alqadi, Z. (2018). Salt and pepper noise: Effects and removal. *JOIV: International Journal on Informatics Visualization*, 2, 252–256.
- Board of Governors of the Federal Reserve System (2024). Economic well-being of u.s. households in 2023. URL: <https://www.federalreserve.gov/consumerscommunities/shed.htm> accessed: 2025-08-06.
- Boyes, W. J., Hoffman, D. L., & Low, S. A. (1989). An econometric analysis of the bank credit scoring problem. *Journal of Econometrics*, 40, 3–14.
- van Braak, B., Osterrieder, J. R., & Machado, M. R. (2025). How can consumers without credit history benefit from the use of information processing and machine learning tools by financial institutions? *Information Processing & Management*, 62, 103972.
- Caldieraro, F., Zhang, J. Z., Cunha Jr, M., & Shulman, J. D. (2018). Strategic information transmission in peer-to-peer lending markets. *Journal of Marketing*, 82, 42–63.
- Chen, D., Deakin, S., Johnston, A., & Wang, B. (2025). Too much technology and too little regulation? the spectacular demise of p2p lending in china. *Accounting, Economics, and Law: A Convivium*, 15, 347–394.
- Del Sarto, N. (2025). Exploring peer-to-peer lending: key influences of firm uncertainty, loan features and venture quality. *International Journal of Bank Marketing*, 43, 591–614.
- Diao, A., Chen, S., & Huang, Y. (2025). Misreporting and risk of loan default: Evidence from an online lending platform affiliated with a rural commercial bank in china. *Finance Research Letters*, (p. 109122).
- Djeundje, V. B., Crook, J., Calabrese, R., & Hamid, M. (2021). Enhancing credit scoring with alternative data. *Expert Systems with Applications*, 163, 113766.
- Dubrov, V. (2023). Understanding machine learning robustness: Why it matters and how it affects your models. <https://medium.com/@slavadubrov/understanding-machine-learning-robustness-why-it-matters-and-how-it-affects-your-models-5e2cb5838> Medium blog post.
- Emekter, R., Tu, Y., Jirasakuldech, B., & Lu, M. (2015). Evaluating credit risk and loan performance in online peer-to-peer (p2p) lending. *Applied Economics*, 47, 54–70.
- European Parliament (2025). Eu ai act: First regulation on artificial intelligence. <https://www.europarl.europa.eu/topics/en/article/20230601ST093804/eu-ai-act-first-regulation-on-artificial-intelligence>.

- Federal Reserve Board (2024). Equal credit opportunity (regulation b). https://www.federalreserve.gov/boarddocs/supmanual/cch/fair_lend_reg_b.pdf.
- Goldmann, S. H., & Machado, M. R. (2025). Advancing credit risk assessment in the retail banking industry: A hybrid approach using time series and supervised learning models. *Data & Knowledge Engineering*, 160, 102490. doi:10.1016/j.datak.2025.102490.
- Gouvêa, M. A., & Gonçalves, E. B. (2007). Credit risk analysis applying logistic regression, neural networks and genetic algorithms models. In *POMS 18th annual conference*.
- Gupta, H., Jin, K. H., Nguyen, H. Q., McCann, M. T., & Unser, M. (2018). Cnn-based projected gradient descent for consistent ct image reconstruction. *IEEE transactions on medical imaging*, 37, 1440–1453.
- He, Z., Ouyang, C., Alzubaidi, L., Barros, A., & Moreira, C. (2025a). Investigating imperceptibility of adversarial attacks on tabular data: An empirical analysis. *Intelligent Systems with Applications*, 25, 200461. URL: <https://www.sciencedirect.com/science/article/pii/S2667305324001352>. doi:<https://doi.org/10.1016/j.iswa.2024.200461>.
- He, Z., Ouyang, C., Wen, L., Liu, C., & Moreira, C. (2025b). Tabattackbench: A benchmark for adversarial attacks on tabular data. *arXiv preprint, arXiv:2505.21027*. URL: <https://arxiv.org/abs/2505.21027>.
- Heng, Y. S., & Subramanian, P. (2022). A systematic review of machine learning and explainable artificial intelligence (xai) in credit risk modelling. In *Proceedings of the Future Technologies Conference (FTC)* (pp. 596–614). Cham: Springer International Publishing. doi:10.1007/978-3-031-18461-1_39.
- Heß, V. L., & Damasio, B. (2025). Machine learning in banking risk management: Mapping a decade of evolution. *International Journal of Information Management Data Insights*, 5, 100324.
- Holla, H., Polepalli, S. R., & Sasikumar, A. A. (2025). Adversarial threats to cloud ids: Robust defense with adversarial training and feature selection. *IEEE Access*, . URL: <https://doi.org/10.1109/ACCESS.2025.3567038>. doi:10.1109/ACCESS.2025.3567038. Accepted for publication.
- Huang, W. (2025). The crystal ball of user-generated content: indication of p2p lending platform failure. *Information Systems Frontiers*, 27, 507–521.
- Jakubik, P., & Teleu, S. (2025). Improving credit risk assessment in uncertain times: Insights from ifrs 9. *Risks*, 13, 38.
- Jedrzejewski, F. V., Thode, L., Fischbach, J., Gorschek, T., Mendez, D., & Lavesson, N. (2024). Adversarial machine learning in industry: A systematic literature review. *Computers & Security*, (p. 103988).
- Kabir, F., Mowla, N. I., Rosenstatter, T., & Doh, I. (2025). Gliids-ar: End-to-end generalized intelligent intrusion detection system with adversarial robustness for heterogeneous uavs in uam. *Computer Networks*, (p. 111821).
- Kozodoi, N., Jacob, J., & Lessmann, S. (2021). Fairness in credit scoring: Assessment, implementation and profit implications. *European Journal of Operational Research*, 297, 1083–1094. doi:10.1016/j.ejor.2021.06.023.
- Laia, E. (2025). The role of peer-to-peer (p2p) lending in developing countries: a systematic literature review. *International Journal of Innovation Science*, .
- Liang, K., & He, J. (2020). Analyzing credit risk among chinese p2p-lending businesses by integrating text-related soft information. *Electronic Commerce Research and Applications*, 40, 100947.
- Machado, M. R., Chen, D. T., & Osterrieder, J. R. (2025). An analytical approach to credit risk assessment using machine learning models. *Decision Analytics Journal*, 16, 100605. doi:10.1016/j.dajour.2025.100605.
- Machado, M. R., & Karray, S. (2022). Assessing credit risk of commercial customers using hybrid machine learning algorithms. *Expert Systems with Applications*, 200, 116889. doi:10.1016/j.eswa.2022.116889.
- Machine, T. T.-B. (). Enhancing credit risk assessment through transformer-based machine learning models. *Artificial Intelligence Research*, (p. 124).
- Madry, A., Makelov, A., Schmidt, L., Tsipras, D., & Vladu, A. (2017). Towards deep learning models resistant to adversarial attacks. URL: <https://arxiv.org/abs/1706.06083> arXiv preprint.
- Masters, G. N. (1982). A rasch model for partial credit scoring. *Psychometrika*, 47, 149–174.
- Mathen, M. P., & Paul, A. (2025). Toward an evolving framework for responsible ai for credit scoring in the banking industry. *Journal of Information, Communication and Ethics in Society*, 23, 148–163.
- Meding, K., & Hagendorff, T. (2024). Fairness hacking: The malicious practice of shrouding. *Philosophy & Technology*, .
- Mokheleli, T., & Museba, T. (2023). *Machine Learning Approach for Credit Score Predictions*. Technical Report DRPM-UBD Johannesburg.
- Moosavi-Dezfooli, S.-M., Fawzi, A., & Frossard, P. (2016). Deepfool: a simple and accurate method to fool deep neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition* (pp. 2574–2582).
- Naidu, A. (2019). Adversarial robustness of credit scoring models: Leveraging gans for model improvement. *International Journal for Multidisciplinary Research*, .
- Nallakaruppan, M. K., Chaturvedi, H., Grover, V., Balusamy, B., Jaraut, P., Bahadur, J., Meena, V. P., & Hameed, I. A. (2024). Credit risk assessment and financial decision support using explainable artificial intelligence. *Risks*, 12, 164.
- Naqvi, S. M. A., Shabaz, M., Khan, M. A., & Hassan, S. I. (2023). Adversarial attacks on visual objects using the fast gradient sign method. *Journal of Grid Computing*, 21, 52.
- Naseem, M. L. (2024). Trans-ift-fgsm: a novel fast gradient sign method for adversarial attacks. *Multimedia Tools and Applications*, 83, 72279–72299.
- Niu, Z., Xie, W., Song, S., Yu, Z., Liu, F., & Shen, L. (2025). Enhancing adversarial transferability by balancing exploration and exploitation with gradient-guided sampling. In *Proceedings of the IEEE/CVF International Conference on Computer Vision* (pp. 3885–3894).
- Patil, N., Iyer, S., Lakhani, C., Shah, P., Patel, H., Bhatt, A., & Patel, D. (2024). Xai-credit risk analysis. *International Journal of Communication Networks and Information Security*, 16, 428–442.
- Pelekis, S., Koutroubas, T., Blika, A., Berdelis, A., Karakolis, E., Ntanos, C., & Askounis, D. (2025). Adversarial machine learning: A review of methods, tools, and critical industry sectors. *Artificial Intelligence Review*, 58, 226–250. doi:10.1007/s10462-025-11147-4.
- Sarkar, S. K., Oshiba, K., Giebisch, D., & Singer, Y. (2018). Robust classification of financial risk. URL: <https://arxiv.org/pdf/1811.11079>.
- Schwab, B., & Kriebel, J. (2025). Mitigating adversarial attacks on transformer models in credit scoring. *European Journal of Operational Research*, .

- Segun, M., Yemi-Peters, V., & Adewumi, S. E. (2024). Credit worthiness prediction: Approaches and methods. *Ukrainian Journal of Educational Studies and Information Technology*, 12, 15–31. doi:10.32919/uesit.2024.01.02.
- Siddiqi, N. (2017). *Intelligent Credit Scoring: Building and Implementing Better Credit Risk Scorecards*. (2nd ed.). Hoboken, NJ: Wiley.
- Straus, J. V., Andreev, V. K., Koeleman, T., Sepanosian, T., & Machado, M. R. (2025). Explaining to defend: Shap-based defense mechanism against adversarial attacks in p2p credit risk. *Expert Systems with Applications*, (p. 130432).
- Studer, S., Bui, T. B., Drescher, C., Hanuschkin, A., Winkler, L., Peters, S., & Müller, K.-R. (2021). Towards crisp-ml (q): a machine learning process model with quality assurance methodology. *Machine learning and knowledge extraction*, 3, 392–413.
- Svitla Systems (2024). Machine learning for credit scoring: Benefits, models, and implementation challenges. <https://svitla.com/blog/machine-learning-for-credit-scoring/>.
- Wang, R., Alam, N., Jones, S., & Zhou, S. (2025). The effectiveness of the uk's viability statement in providing early warning signs of corporate distress. *Available at SSRN 5761703*, .
- West, D. (2000). Neural network credit scoring models. *Computers & operations research*, 27, 1131–1152.
- Wirth, R., & Hipp, J. (2000). Crisp-dm: Towards a standard process model for data mining. In *Proceedings of the 4th international conference on the practical applications of knowledge discovery and data mining* (pp. 29–39). Manchester volume 1.
- World Bank (2022). The global finindex database 2021: Financial inclusion, digital payments, and resilience in the age of covid-19. URL: <https://www.worldbank.org/en/publication/globalfinindex> accessed: 2025-08-06.
- Yan, J., Yu, W., & Zhao, J. L. (2015). How signaling and search costs affect information asymmetry in p2p lending: the economics of big data. *Financial Innovation*, 1, 19.
- Zhang, W., Wang, C., Zhang, Y., & Wang, J. (2020). Credit risk evaluation model with textual features from loan descriptions for p2p lending. *Electronic commerce research and applications*, 42, 100989.
- Zhang, X., & Yu, L. (2024). Consumer credit risk assessment: A review from the state-of-the-art classification algorithms, data traits, and learning methods. *Expert Systems with Applications*, 237, 121484. doi:10.1016/j.eswa.2023.121484.
- Zhang, Z., Cheng, Y., Liu, Q., Li, X., & Chen, Z. (2025). Credit risk identification in supply chains using generative adversarial networks. Unpublished manuscript, vol. 7.
- Zhu, Y., Xie, C., Sun, B., Wang, G.-J., & Yan, X.-G. (2016). Predicting china's sme credit risk in supply chain financing by logistic regression, artificial neural network and hybrid models. *Sustainability*, 8, 433.

Appendix A. Cross-validation results

Table A.14: Mean performance of the Logistic Regression model across cross-validation folds under different adversarial training and testing configurations. All values represent fold-averaged metrics and are rounded to three decimal digits.

Training Set	Test Set	ROC AUC	Accuracy	Prec ₀	Prec ₁	Rec ₀	Rec ₁	F1 ₀	F1 ₁	Pred ND	Pred D
Clean	Clean	0.905	0.826	0.541	0.934	0.756	0.843	0.631	0.886	45367	17232
Clean	DeepFool	0.872	0.787	0.465	0.887	0.561	0.843	0.508	0.864	47770	14829
Clean	FGSM	0.864	0.805	0.504	0.908	0.652	0.843	0.569	0.874	46653	15947
Clean	PGD	0.864	0.805	0.504	0.908	0.652	0.843	0.569	0.874	46653	15947
Clean	S&P	0.862	0.795	0.486	0.926	0.737	0.809	0.586	0.863	43904	18696
DeepFool	Clean	0.903	0.814	0.520	0.936	0.771	0.825	0.620	0.877	44271	18328
DeepFool	DeepFool	0.905	0.815	0.521	0.937	0.774	0.825	0.622	0.877	44238	18362
DeepFool	FGSM	0.917	0.822	0.532	0.947	0.810	0.825	0.642	0.881	43796	18803
DeepFool	PGD	0.917	0.822	0.532	0.947	0.810	0.825	0.642	0.881	43796	18803
DeepFool	S&P	0.860	0.784	0.471	0.928	0.750	0.792	0.578	0.855	42919	19680
FGSM	Clean	0.899	0.827	0.548	0.927	0.728	0.852	0.624	0.888	46178	16421
FGSM	DeepFool	0.908	0.832	0.555	0.933	0.750	0.852	0.637	0.890	45904	16696
FGSM	FGSM	0.943	0.854	0.589	0.962	0.862	0.852	0.699	0.903	44526	18074
FGSM	PGD	0.943	0.854	0.589	0.962	0.862	0.852	0.699	0.903	44526	18074
FGSM	S&P	0.856	0.797	0.491	0.920	0.707	0.820	0.579	0.867	44813	17787
PGD	Clean	0.899	0.825	0.541	0.929	0.735	0.847	0.623	0.886	45848	16751
PGD	DeepFool	0.909	0.829	0.548	0.934	0.756	0.847	0.635	0.888	45589	17011
PGD	FGSM	0.945	0.852	0.583	0.965	0.873	0.847	0.699	0.902	44147	18452
PGD	PGD	0.945	0.852	0.583	0.965	0.873	0.847	0.699	0.902	44147	18452
PGD	S&P	0.857	0.795	0.487	0.921	0.714	0.815	0.579	0.865	44504	18095
S&P	Clean	0.905	0.823	0.535	0.935	0.764	0.837	0.629	0.883	44990	17609
S&P	DeepFool	0.860	0.796	0.486	0.902	0.630	0.837	0.548	0.868	46640	15959
S&P	FGSM	0.864	0.802	0.498	0.909	0.658	0.837	0.567	0.872	46289	16310
S&P	PGD	0.864	0.802	0.498	0.909	0.658	0.837	0.567	0.872	46289	16310
S&P	S&P	0.865	0.793	0.483	0.927	0.742	0.805	0.585	0.862	43669	18930
Mixed	Clean	0.901	0.822	0.534	0.932	0.750	0.839	0.624	0.883	45271	17328
Mixed	DeepFool	0.907	0.824	0.537	0.934	0.760	0.839	0.629	0.884	45154	17445
Mixed	FGSM	0.930	0.838	0.561	0.954	0.835	0.839	0.671	0.893	44227	18372
Mixed	PGD	0.930	0.838	0.561	0.954	0.835	0.839	0.671	0.893	44227	18372
Mixed	S&P	0.860	0.792	0.482	0.924	0.728	0.808	0.580	0.862	43985	18615

Table A.15: Mean performance of the Neural Network model across cross-validation folds under different adversarial training and testing configurations. All values represent fold-averaged metrics and are rounded to three decimal digits.

Training Set	Test Set	ROC AUC	Accuracy	Prec ₀	Prec ₁	Rec ₀	Rec ₁	F1 ₀	F1 ₁	Pred ND	Pred D
Clean	Clean	0.903	0.822	0.534	0.935	0.765	0.836	0.628	0.883	44911	17688
Clean	DeepFool	0.873	0.798	0.490	0.906	0.644	0.836	0.555	0.869	46397	16202
Clean	FGSM	0.871	0.805	0.504	0.914	0.678	0.836	0.577	0.873	45982	16617
Clean	PGD	0.871	0.804	0.504	0.914	0.678	0.836	0.577	0.873	45984	16616
Clean	S&P	0.858	0.790	0.480	0.927	0.743	0.802	0.583	0.860	43480	19120
DeepFool	Clean	0.901	0.825	0.542	0.933	0.753	0.843	0.629	0.885	45421	17178
DeepFool	DeepFool	0.905	0.823	0.539	0.931	0.743	0.843	0.624	0.884	45537	17062
DeepFool	FGSM	0.895	0.826	0.543	0.934	0.755	0.843	0.631	0.886	45387	17212
DeepFool	PGD	0.896	0.826	0.543	0.934	0.756	0.843	0.631	0.886	45380	17219
DeepFool	S&P	0.856	0.795	0.487	0.925	0.730	0.810	0.583	0.864	44059	18541
FGSM	Clean	0.899	0.840	0.579	0.925	0.711	0.872	0.637	0.898	47398	15201
FGSM	DeepFool	0.891	0.830	0.560	0.913	0.659	0.872	0.605	0.892	48040	14559
FGSM	FGSM	0.964	0.877	0.634	0.972	0.898	0.872	0.743	0.919	45095	17504
FGSM	PGD	0.965	0.877	0.634	0.973	0.899	0.872	0.743	0.919	45080	17519
FGSM	S&P	0.854	0.810	0.514	0.917	0.691	0.839	0.588	0.876	45985	16614
PGD	Clean	0.901	0.842	0.581	0.925	0.709	0.874	0.639	0.899	47537	15063
PGD	DeepFool	0.902	0.838	0.574	0.920	0.689	0.874	0.626	0.896	47790	14810
PGD	FGSM	0.970	0.883	0.642	0.977	0.917	0.874	0.755	0.923	44976	17623
PGD	PGD	0.971	0.883	0.643	0.978	0.920	0.874	0.757	0.923	44940	17659
PGD	S&P	0.857	0.811	0.515	0.917	0.689	0.840	0.589	0.877	46076	16524
S&P	Clean	0.901	0.817	0.525	0.937	0.771	0.829	0.625	0.879	44494	18105
S&P	DeepFool	0.871	0.801	0.496	0.916	0.687	0.829	0.576	0.870	45524	17076
S&P	FGSM	0.868	0.800	0.495	0.914	0.682	0.829	0.573	0.869	45586	17013
S&P	PGD	0.868	0.800	0.495	0.914	0.682	0.829	0.573	0.869	45591	17009
S&P	S&P	0.874	0.792	0.483	0.929	0.751	0.802	0.588	0.861	43413	19187
Mixed	Clean	0.901	0.829	0.550	0.930	0.740	0.851	0.631	0.889	45990	16609
Mixed	DeepFool	0.906	0.827	0.546	0.928	0.729	0.851	0.624	0.888	46127	16472
Mixed	FGSM	0.943	0.852	0.585	0.960	0.855	0.851	0.694	0.902	44577	18023
Mixed	PGD	0.943	0.852	0.585	0.960	0.856	0.851	0.695	0.902	44558	18041
Mixed	S&P	0.868	0.800	0.495	0.923	0.719	0.820	0.586	0.868	44679	17921

Table A.16: Mean performance of the Transformer model across cross-validation folds under different adversarial training and testing configurations. All values represent fold-averaged metrics and are rounded to three decimal digits.

Training Set	Test Set	ROC AUC	Accuracy	Prec ₀	Prec ₁	Rec ₀	Rec ₁	F1 ₀	F1 ₁	Pred ND	Pred D
Clean	Clean	0.906	0.826	0.542	0.934	0.758	0.843	0.632	0.886	45342	17258
Clean	DeepFool	0.872	0.795	0.482	0.897	0.602	0.843	0.535	0.869	47261	15339
Clean	FGSM	0.870	0.806	0.507	0.910	0.659	0.843	0.573	0.875	46553	16046
Clean	PGD	0.870	0.806	0.507	0.910	0.659	0.843	0.573	0.875	46552	16047
Clean	S&P	0.865	0.796	0.488	0.927	0.739	0.810	0.588	0.864	43923	18676
DeepFool	Clean	0.905	0.832	0.555	0.930	0.739	0.855	0.634	0.891	46188	16411
DeepFool	DeepFool	0.908	0.830	0.551	0.927	0.727	0.855	0.627	0.890	46325	16274
DeepFool	FGSM	0.897	0.830	0.551	0.927	0.727	0.855	0.627	0.890	46329	16271
DeepFool	PGD	0.897	0.830	0.551	0.927	0.727	0.855	0.627	0.890	46329	16271
DeepFool	S&P	0.864	0.801	0.497	0.923	0.721	0.821	0.588	0.869	44706	17893
FGSM	Clean	0.902	0.846	0.597	0.920	0.688	0.885	0.638	0.902	48337	14263
FGSM	DeepFool	0.905	0.846	0.596	0.920	0.687	0.885	0.637	0.902	48347	14253
FGSM	FGSM	0.975	0.893	0.665	0.980	0.927	0.885	0.774	0.930	45386	17214
FGSM	PGD	0.974	0.893	0.665	0.980	0.926	0.885	0.774	0.930	45400	17199
FGSM	S&P	0.860	0.815	0.526	0.914	0.671	0.851	0.589	0.881	46818	15781
PGD	Clean	0.903	0.840	0.578	0.925	0.710	0.872	0.637	0.898	47434	15165
PGD	DeepFool	0.911	0.840	0.577	0.924	0.706	0.872	0.635	0.897	47478	15121
PGD	FGSM	0.981	0.888	0.647	0.986	0.950	0.872	0.770	0.926	44474	18125
PGD	PGD	0.980	0.887	0.647	0.986	0.949	0.872	0.769	0.926	44493	18107
PGD	S&P	0.860	0.810	0.513	0.918	0.692	0.838	0.589	0.876	45942	16657
S&P	Clean	0.904	0.827	0.544	0.932	0.750	0.845	0.630	0.887	45587	17013
S&P	DeepFool	0.865	0.795	0.482	0.895	0.592	0.845	0.530	0.869	47535	15065
S&P	FGSM	0.869	0.809	0.511	0.910	0.659	0.845	0.575	0.876	46709	15890
S&P	PGD	0.869	0.809	0.511	0.910	0.659	0.845	0.575	0.876	46709	15891
S&P	S&P	0.879	0.804	0.502	0.925	0.730	0.822	0.594	0.871	44649	17950
Mixed	Clean	0.904	0.828	0.547	0.932	0.748	0.848	0.631	0.888	45728	16871
Mixed	DeepFool	0.913	0.827	0.544	0.930	0.740	0.848	0.627	0.887	45818	16781
Mixed	FGSM	0.974	0.866	0.602	0.983	0.939	0.848	0.734	0.910	43366	19233
Mixed	PGD	0.974	0.865	0.602	0.982	0.938	0.848	0.733	0.910	43381	19218
Mixed	S&P	0.876	0.802	0.499	0.925	0.728	0.820	0.592	0.869	44586	18014

Appendix B. External replication on a second P2P dataset (Prosper)

To assess whether the robustness and cross-attack transfer patterns reported in Section 4 are specific to Lending Club or reflect more general behaviour of adversarially trained tabular credit models, we replicate the entire study on an independent P2P dataset from the Prosper marketplace.¹⁰ The replication is deliberately constrained to be method-identical: the same three model families (logistic regression, feed-forward neural network, FT-Transformer), the same four attacks (FGSM, PGD, DeepFool, S&P) plus the mixed regime, the same 80/20 split with stratified 5-fold cross-validation, the same $\varepsilon = \text{amount} = 0.1$ budgets, and the same class-weighted training. Only the feature space is re-mapped to the Prosper schema. The mutable/immutable partition follows the identical philosophy used for Lending Club: the four self-reported financial variables (`annual_inc`, `dti`, `revol_bal`, `revol_util`) and two self-reported categorical blocks (`purpose`, `addr_state` in place of `zip_code`) are perturbable, while platform-generated scores (`ProsperRating`, `ProsperScore`), immutable credit-history facts, and contractually fixed terms are blocked via gradient masking and structurally valid one-hot swaps. The full feature-level constraint table is available in the project repository.

Two structural differences from the main analysis should be kept in mind when reading the results. First, the Prosper subset is roughly an order of magnitude smaller (test folds of $\approx 3,900$ observations versus $\approx 62,600$ for Lending Club), so fold-to-fold variability is larger. Second, and more importantly, the clean discriminative signal is weaker: all three models attain clean ROC AUC in the 0.70–0.71 range (Table B.17), well below the 0.90–0.91 obtained on Lending Club (Table 8). The replication therefore tests whether the *qualitative* robustness structure survives on a harder, differently constructed dataset, rather than whether absolute performance is reproduced.

Table B.17: Clean-train/clean-test performance of the three model families on the Prosper dataset (fold-averaged means). Compare with Table 8.

Model	ROC AUC	Accuracy	Prec ₀	Rec ₀	F1 ₀	Prec ₁	Rec ₁	F1 ₁	Pred. ND	Pred. D
Logistic Regression	0.702	0.633	0.379	0.674	0.485	0.847	0.619	0.715	2,113.6	1,769.6
Neural Network	0.698	0.641	0.381	0.646	0.479	0.840	0.639	0.726	2,198.6	1,684.6
FT-Transformer	0.711	0.691	0.423	0.546	0.474	0.827	0.740	0.780	2,590.0	1,293.0

Table B.18 reports the complete train×test grid using ROC AUC, the primary ranking metric in the main text, as fold-averaged mean with the cross-fold standard deviation in parentheses. Matched attack–defence cells (the diagonal of the attack rows) are shown in bold.

What replicates. Four of the main findings reappear cleanly. First, gradient-based attacks are the most damaging to clean-trained models, whereas S&P is comparatively mild: the clean-trained neural network falls from ROC AUC 0.698 to 0.588/0.587 under FGSM/PGD and to 0.545 under DeepFool, but only to 0.690 under S&P (Table B.18), echoing the main-text ordering in which S&P produced a broad but shallow decline. Second, matched-attack adversarial training recovers and improves discrimination, and does so most strongly for the gradient family and the higher-capacity neural network: FGSM- and PGD-trained neural networks reach ROC AUC 0.811 and 0.822 on their matched tests, far above the clean-trained 0.588 baseline, mirroring the large matched-training gains reported for Lending Club. Third, FGSM and PGD remain mutually interchangeable, with near-identical columns and cross-cells (e.g., FGSM-train/PGD-test 0.806 vs. PGD-train/FGSM-test 0.827 for the neural network), confirming that their shared gradient structure, and not dataset-specific artefacts, drives the transfer. Fourth, cross-family transfer is weak in both directions: S&P training leaves gradient robustness at clean-model levels (0.589/0.588 for the neural network), and gradient training barely moves S&P performance, exactly as in the main analysis.

What differs, and why it strengthens the generalisation claim. Two departures are worth stating plainly. The mixed regime is again the most balanced policy, delivering solid performance across all five test conditions (e.g., the neural network at 0.699–0.761 with no catastrophic cell) while preserving clean accuracy, but on this weaker-signal dataset it no longer strictly dominates the best single-attack model, since matched gradient training attains higher gradient-test scores. Likewise, the architecture that benefits most shifts: on

¹⁰Prosper Marketplace, <https://www.prosper.com/>.

Table B.18: Cross-attack robustness grid on the Prosper dataset: ROC AUC (fold-averaged mean, cross-fold standard deviation in parentheses) for every training regime (rows) $\times$ test perturbation (columns), for the three model families. Bold entries mark matched attack–defence cells. This is the Prosper analogue of Tables 9–11.

Training Set	Clean	DeepFool	FGSM	PGD	S&P
<i>Logistic Regression</i>					
Clean	0.702 (0.006)	0.635 (0.036)	0.666 (0.020)	0.666 (0.020)	0.700 (0.007)
DeepFool	0.685 (0.019)	0.724 (0.006)	0.712 (0.008)	0.712 (0.008)	0.684 (0.019)
FGSM	0.695 (0.012)	0.706 (0.013)	0.701 (0.011)	0.701 (0.011)	0.693 (0.012)
PGD	0.694 (0.010)	0.693 (0.025)	0.695 (0.019)	0.695 (0.019)	0.692 (0.010)
S&P	0.702 (0.011)	0.620 (0.028)	0.660 (0.011)	0.660 (0.011)	0.701 (0.011)
Mixed	0.689 (0.013)	0.693 (0.012)	0.692 (0.011)	0.692 (0.011)	0.687 (0.013)
<i>Neural Network</i>					
Clean	0.698 (0.023)	0.545 (0.061)	0.588 (0.029)	0.587 (0.030)	0.690 (0.020)
DeepFool	0.697 (0.010)	0.756 (0.010)	0.728 (0.020)	0.726 (0.023)	0.690 (0.011)
FGSM	0.705 (0.008)	0.767 (0.005)	0.811 (0.014)	0.806 (0.020)	0.697 (0.008)
PGD	0.703 (0.010)	0.766 (0.007)	0.827 (0.020)	0.822 (0.027)	0.695 (0.010)
S&P	0.709 (0.008)	0.539 (0.036)	0.589 (0.018)	0.588 (0.018)	0.701 (0.007)
Mixed	0.699 (0.010)	0.759 (0.009)	0.761 (0.015)	0.758 (0.020)	0.691 (0.008)
<i>FT-Transformer</i>					
Clean	0.711 (0.010)	0.638 (0.035)	0.643 (0.015)	0.643 (0.015)	0.708 (0.011)
DeepFool	0.705 (0.010)	0.712 (0.026)	0.708 (0.029)	0.708 (0.029)	0.703 (0.011)
FGSM	0.699 (0.010)	0.706 (0.013)	0.712 (0.014)	0.712 (0.015)	0.696 (0.011)
PGD	0.699 (0.011)	0.707 (0.013)	0.715 (0.015)	0.716 (0.016)	0.696 (0.012)
S&P	0.709 (0.012)	0.617 (0.062)	0.632 (0.020)	0.632 (0.021)	0.706 (0.013)
Mixed	0.701 (0.013)	0.699 (0.014)	0.704 (0.013)	0.704 (0.013)	0.698 (0.015)

Prosper the feed-forward network shows the largest adversarial-training gains, whereas the FT-Transformer, which led on Lending Club, improves only modestly (matched cells 0.712–0.716), and logistic regression again benefits least, in line with its main-text behaviour. The absolute levels and the best-performing architecture change, but the ordering of the training regimes does not: matched-attack training remains the strongest defence, transfer stays high within the gradient family and low across families, and mixed training remains the most balanced choice.