

Replicating TRACE: A Practitioner’s Guide to Its Threshold and Particle Budget

Alex Chadyuk* Alicia Zhang Roy Kucukates
LotusFlare Inc.

1 September 2026

Abstract

TRACE (Math and Lienhart, 2026) reads causal graphs over event types out of a pretrained autoregressive sequence model by thresholding a per-position conditional-mutual-information (CMI) estimate at a fixed τ . We report an independent replication of its headline synthetic result: with τ selected on a validation split, mean per-sequence $F1$ against exact interventional truth reaches 0.90–0.91 at $|\mathcal{X}| = 1000$ (the paper’s Table 2: ≈ 0.91) and 0.86–0.91 at every vocabulary size from 100 to 2000. Four findings inform the practical application of TRACE. First, the optimal CMI threshold is pinned to the truth margin rather than to any constant: at every vocabulary size the errors at τ^* straddle the $\delta = 0.05$ margin that defines ground truth—the true edges it gives up sit just above δ , the false edges it accepts, just below—and the blind optimum lands near $\delta/2$ times the estimator’s calibration, confirmed out of sample at $|\mathcal{X}| = 5000$. Second, when TRACE is operated at a single global threshold it mostly recovers a direct, adjacent-influence graph: lag-1 true edges are read at their generator KL and recalled at 0.97–0.99, while true edges at lag ≥ 2 read orders of magnitude lower—the reading-scale price of randomizing mediating positions, which an exact test of direct causal effect requires when the truth is unknown. A per-lag threshold family recovers a third to a half of lag-2 truth, and on lag-uniform data TRACE recalls every lag at 0.40–0.87 from one validated threshold, trailing an atomic-intervention control by 8–26 pp at lags 3–6. Third, the default lag decay of the synthetic benchmark the paper proposes in its appendix concentrates $\approx 85\%$ of interventional truth at lag 1 and pushes the remainder below the estimator’s noise floor, so headline $F1$ there certifies lag-1 recovery only and conflates the benchmark’s skew with the algorithm’s own limit; a flatter decay puts recallable truth at every lag and separates the two. Fourth, the $F1$ observable saturates from $N = 2$ particles at the selected threshold—a property of the threshold’s margin over the noise floor, not of the estimator, which converges as $N^{-1/2}$. We distill the findings into concrete guidance for practitioners applying TRACE to new data.

1 Introduction

TRACE (Math and Lienhart, 2026) belongs to a growing family of methods that read causal structure directly out of a pretrained autoregressive model: a decoder is trained on discrete event sequences, the CMI between a candidate cause and each downstream position is estimated by particle-based do-sampling, and edges are called by thresholding the resulting CMI at a fixed τ . Its central synthetic claim (paper’s Table 2) is $F1 \approx 0.91$ against interventional ground truth at vocabulary size $|\mathcal{X}| = 1000$ and sequence length $L = 64$.

*Corresponding author: alex.chadyuk@lotusflare.com

We replicated this claim from scratch and characterized how its two main free parameters—the threshold and the particle count—behave across regimes. The characterization surfaced two further findings. One is a lag-graded recall limit of TRACE’s staircase construction—its whole-tail randomization of mediating positions, which an exact test of direct causal effect requires. The other is a lag-1 skew of the paper’s synthetic benchmark that exaggerates this recall limit. Two properties of the study bear on how to read it. Ground truth is exact: we reimplemented the paper’s generator, so per-sequence interventional truth is computed from its conditionals rather than approximated. And every quantitative claim is made on at least two seeds with the cross-seed gap published, under thresholds selected on validation data and decision rules fixed before the runs (details in the Reproducibility statement).

Our contributions are:

1. **Replication.** An independent reimplementation, scored the paper’s own way against exact interventional truth, reproduces paper’s Table 2 at the paper’s regime (Section 5) and at every vocabulary size in $\{100, 500, 1000, 2000\}$ (Section 6).
2. **The threshold is margin-pinned.** In our redundancy-matched worlds the blind validation optimum straddles the truth margin δ : the errors at τ^* are margin-band pairs on both sides of δ , the optimum decelerates toward $\delta/2$ times the estimator’s calibration, and an out-of-sample probe at $|\mathcal{X}| = 5000$ confirms the margin reading against a power-law extrapolation of our own sweep. The transferable object is therefore the validation-selection protocol the paper already licenses, and the authors concur (personal communication; see Acknowledgments) (Section 6).
3. **A lag-graded recall limit of the staircase construction.** At any single global threshold, on data whose causal strength decays with lag, TRACE tends to recover a direct, adjacent-influence graph: lag-1 true edges are read at their generator KL and recalled at 0.97–0.99, while true edges at lag ≥ 2 read decades (orders of magnitude) low—traced to the collapse of the observed effect token’s factual probability when the staircase redraws every mediating position out of its factual context. The limit is graded, not absolute: a per-lag threshold family recovers a third to a half of lag-2 truth on the same runs, and an atomic-intervention instrument on lag-uniform data isolates the staircase’s own share of the deficit as a moderate, lag-graded residual (8–26 pp at lags 3–6) (Section 7).
4. **The default benchmark cannot show this limit.** The synthetic generator is specified in the paper’s evaluation appendix and is not part of the algorithm; its hard-coded lag decay skews the benchmark toward lag 1 twice over—about 85% of interventional-truth mass sits at lag 1, and the deep-lag remainder reads below the estimator’s noise floor—so the headline $F1$ is attainable by lag-1 recovery alone. Validation against the default generator therefore certifies adjacent-influence recovery only, and conflates the benchmark’s skew with the staircase’s limit; a flat-decay variant (one generator parameter) separates them (Section 8).
5. **Particle budget.** A particle sweep saturates from $N = 2$ at the selected threshold; we diagnose this as a threshold-margin property, not estimator saturation, and give a rule for choosing the particle budget (Section 9).

Section 10 collects the practical guidance.

2 Related work

Selecting a sparsity-controlling free parameter by a data-driven procedure rather than a fixed value is canonical—StARS (Liu et al., 2010) made stability-based selection the default for graphical-model regularization—and the sensitivity of headline benchmark numbers to tuning and setup choices is well documented across the causal-discovery literature (Reisach et al., 2021; Ng et al., 2024; Zhang et al., 2026). We claim no novelty for the lesson; what we add is a measured account of how one named 2026 method’s threshold and particle budget behave across regimes, together with a replication of its headline number. TRACE sits in a wider event-sequence causal-discovery literature (e.g. CASCADE (Cüppers et al., 2024), THPs (Cai et al., 2024), SHP (Qiao et al., 2023), CAUSE (Zhang et al., 2020)); an executed cross-method comparison is outside this note’s scope.

3 TRACE and its evaluation protocol

We summarize only what the replication needs; see Math and Lienhart (2026) and the dissertation (Math, 2026a).

Estimator. A decoder-only autoregressive model is pretrained on event sequences over a vocabulary $\mathcal{X}$. For a sequence s and a candidate cause position p , TRACE estimates the CMI between the event at p and each position q in a context window of size c after p by comparing the model’s predictive distributions under N particle do-interventions (the “staircase” construction): each particle redraws p and every position between p and q uniformly, the mediating draws shared across the two arms of the contrast. In intervention-calculus terms the construction recovers the *randomized controlled direct effect* of p on q under the model’s conditionals: each particle contrast is a controlled direct effect at a randomized mediator setting (Pearl, 2009, Def. 4.5.1, Eq. (3.14))—the do-semantics of graph surgery (Koller and Friedman, 2009, Def. 21.1)—and, the uniform redraw having full support (Peters et al., 2017, cf. Prop. 6.13), the particle average is, at the level of the compared distributions, an exact test of direct causal effect: zero when p is not a direct parent of q , positive when it is and the randomization reaches a witnessing context. It is thus a direct-edge estimand, carrying no mediated influence; what survives of its readings at lag ≥ 2 is measured in Section 7. Thresholding the per-position CMI matrix at τ and projecting onto event types yields the *sample summary causal graph* of s (paper’s Definition 3.2): a type edge is called if any supporting position pair crosses τ .

Ground truth and metric. The synthetic generator (paper’s Eq. 21, specified in its evaluation appendix) produces sequences from a known lagged mechanism over $\mathcal{X}$ with lag horizon h . Interventional truth is defined *per sequence*: each position is replaced by uniform draws over real event types (10 counterfactuals), the generator’s conditionals are recomputed at positions $q \in (p, p + h]$, and a type edge is true iff the mean KL divergence exceeds $\delta = 0.05$. This truth is itself a benchmark construction: it evaluates the direct effect at the factual mediator configuration—exactly computable from the generator’s conditionals and inexpensive at benchmark scale—whereas a factual configuration can mask a direct edge that a witnessing context elsewhere would reveal, which is what the estimator’s full-support randomization guards against in deployment, where no truth is available. The two constructions thus answer the same direct-effect question at different mediator configurations; Section 7 measures the consequences. Paper’s Table 2 reports the mean per-observation $F1$ of the sample summary graph against this truth. We stress, because it cost us a debug cycle, that the metric is per-observation—one sequence per summary graph, no corpus-level

aggregation. A corpus-level graph is a genuinely different and harder object, outside this note’s scope.

Threshold guidance in the paper. Four values bear on τ at $|\mathcal{X}| = 1000$: the paper’s Table 2 constant (3×10^{-5}); the sensitivity-sweep optimum ($\approx 1.4 \times 10^{-5}$, paper’s Fig. 9); the scaling law $\tau_{\text{opt}} \approx C |\mathcal{X}|^{-0.96}$ with $C = 1.72 \times 10^{-2}$, fit across $|\mathcal{X}| \in \{100, \dots, 2000\}$ at generator noise $\varepsilon = 0.04$ (paper’s Fig. 10), giving $1.7\text{--}2.3 \times 10^{-5}$; and the 10^{-4} of the qualitative experiments (paper’s Figs. 4–5). The paper thus treats τ as a swept, setup-dependent quantity, and our results below are best read as an elaboration of that stance.

4 Reimplementation and setup

Reimplementation. We reimplemented the full pipeline from scratch—generator, tokenizer, pretraining, staircase CMI, thresholding, graph projection, evaluation—transcribing the staircase and Bernoulli-KL algebra from the reference implementation (Math, 2026b).

Worlds. Two synthetic regimes, both at $|\mathcal{X}| = 1000$, $L = 64$, a decoder-only backbone at the paper’s scale, and $N = 128$ particles. The **redundancy-matched regime** (the replication target) uses generator sparsity 0.9, lag horizon $h = 6$, truth margin $\delta = 0.05$ with 10 counterfactuals, and a mechanism weight scale tuned so the measured redundancy matches the paper’s benchmark value $R \approx 0.58$ (measured $R = 0.593/0.590$, seeds 0/1); context $c = 6$ primary, $c = 20$ secondary. We match the paper on the redundancy axis only; other generator settings, such as the noise level, differ, which is part of why thresholds should be expected to move. The **high-redundancy regime** uses the same generator family at a mechanism scale yielding $R = 0.93$, $h = 3$, $c = 20$, $\sim 300\text{k}$ training sequences; it serves as an out-of-regime probe. Two follow-up worlds at $|\mathcal{X}| = 10^4$ and $2 \cdot 10^4$, run later under the same generator family and protocol (R-matched, default capacity), are quoted where they extend a finding. A last family, used only in Sections 7 and 8, generalizes the generator’s hard-coded lag decay to $e^{-r(k-1)}$ at $|\mathcal{X}| = 1000$ ($r \in \{0.3, 0.1, 0\}$; the paper’s Eq. 21 is $r = 1$), each world redundancy-re-matched under the same protocol.

Threshold selection and evaluation. Thresholds live on a fixed logarithmic grid from 10^{-6} to 10^{-1} containing the printed constant and the paper’s scaling-law anchor (12 points; the vocabulary and particle sweeps use a 23-point superset). One τ per seed is chosen by maximizing mean per-sequence $F1$ on the *validation* split and only then applied to the test split; test-side grids appear only as sensitivity curves. Evaluation is mean per-sequence $F1$ against exact per-sequence interventional truth, over 1,024 head test sequences per seed for the replication and sweep worlds ($64\times$ the paper’s per-run evaluation width) and 5,000 per seed for the high-redundancy world. Two seeds throughout; cross-seed gaps were ≤ 0.03 everywhere.

5 Replication at the paper’s regime

The results are shown in Table 1: with τ selected blindly on validation data the pipeline reaches $F1 = 0.9008/0.9051$ against the original paper’s Table 2 ≈ 0.91 —a clean replication on an independent reimplementation, against exact interventional truth, at the paper’s own redundancy, and stable in the context width. The selected threshold, however, is 3×10^{-2} , three orders of magnitude above the value used for the paper’s own setup; at that value our runs score $F1 \approx 0.46$, consistently across context widths and seeds. The optimal operating point is therefore reproduced for the *estimator*

Reading	τ	c	$F1$ (seed 0)	$F1$ (seed 1)
Val-selected (blind)	3×10^{-2}	6	0.9008	0.9051
Grid optimum (test)	3×10^{-2}	20	0.9004	0.9061
Paper’s constant	3×10^{-5}	6	0.4553	0.4647
Paper’s constant	3×10^{-5}	20	0.4650	0.4742
Published reference (Math and Lienhart, 2026, Table 2)			≈ 0.91	

Table 1: Matched-redundancy replication ($|\mathcal{X}| = 1000$, $L = 64$, $h = 6$, $R \approx 0.59$; exact per-sequence interventional truth; 1,024 test sequences per seed). Blind validation selection picks $\tau = 3 \times 10^{-2}$ on both seeds and at both context widths.

$ \mathcal{X} $	R (s0/s1/s2)	truth pairs/seq	τ^* (grid, s0/s1/s2)	$\tilde{\tau}^*$ (median)	test $F1@ \tau^*$ (s0/s1/s2)	$F1@C/ \mathcal{X} $
100	.594/.592/.582	30–39	0.10 / 0.178 / 0.10	0.14	.883/.859/.859	.245/.254/.249
500	.591/.592/.595	49–51	0.0562×3	0.046	.908/.889/.893	.301/.305/.296
1000	.593/.590/.603	50–52	$0.03 / 0.0562 / 0.03$	0.034	.901/.905/.897	.375/.384/.393
2000	.601/.598/.590	50–51	0.03×3	0.029	.899/.896/.900	.474/.487/.482

pooled exponent over the swept range (12 points, three seeds): $b = -0.552$ (per seed $-0.539 / -0.557 / -0.559$)
companion arm (fixed weight scale, R floating 0.42–0.60): $b = -0.489$ ($-0.495 / -0.484 / -0.488$)

Table 2: Vocabulary sweep, redundancy-matched arm ($h = 6$, $c = 6$, $N = 128$; 1,024 sequences per split; exact per-sequence truth). τ^* is the validation argmax; the test-side argmax coincided with it on all 21 test replicas of both arms. “Truth pairs/seq” counts type pairs after the Def.-3.2 projection; the position-level exact truth is flat at 50–53 pairs per sequence at every $|\mathcal{X}|$ (the rise from 30 reflects type collisions at $|\mathcal{X}| = 100$).

but not for the *constant*: blind validation selection recovers the published performance, while the threshold value attaining it does not transfer between setups—a regime dependence that the paper’s own sensitivity analysis anticipates, and that Section 6 quantifies.

6 How the threshold moves across regimes

A vocabulary sweep. To measure the dependence directly, we built new generators and pretraining per $(|\mathcal{X}|, \text{seed})$ for $|\mathcal{X}| \in \{100, 500, 2000\}$, identical to the replication world except $|\mathcal{X}|$ and the weight scale (re-matched to $|R - 0.59| \leq 0.015$); τ^* is the validation argmax, applied once to the test split, and the exponent of $\tau^*(|\mathcal{X}|) \propto |\mathcal{X}|^b$ is a pooled least-squares fit. A companion arm repeats the three new sizes at the paper’s own fixed weight scale (R floating), holding the mechanism family fixed as $|\mathcal{X}|$ varies.

Outcome. As shown in Table 2, the selection protocol replicates at every size—test $F1$ at the selected τ^* is 0.86–0.91, with validation-to-test drift within ± 0.003 —while any single fixed constant does not: transplanting a constant fit in one regime reads 0.25–0.48 here. Within the swept range the optimum falls with vocabulary size much more slowly than $1/|\mathcal{X}|$ (pooled $b = -0.552$), and the log–log curve is concave (local slope -0.88 at $|\mathcal{X}| = 100$ easing to -0.19 at 2000).

What sets the scale: the δ -straddle. Per-pair analysis of the emitted traces (32 per world, the generator’s exact per-pair KL replayed beside each estimate) shows that the optimum is pinned to the truth margin. At every vocabulary size the true pairs τ^* gives up have generator KL just

above the margin $\delta = 0.05$ (median 0.06–0.08) and the false pairs it accepts have KL just below it (median 0.02–0.03—real but sub-margin dependencies); from $|\mathcal{X}| = 500$ up all of both are lag-1 pairs, and the estimator reads lag-1 pairs at their KL (median $\log_{10}(\text{CMI}/\text{KL})$ within ≈ 0.1 in every KL band). Both error tails are therefore pinned to δ , and what moves τ^* along the sweep changes: from $|\mathcal{X}| = 100$ to 500 it is the collapse of the noise floor on null pairs ($\propto |\mathcal{X}|^{-1.2}$ in median); from 500 to 2000 it is the true-edge bulk drifting toward δ with the token-probability scale. Consistently, $\tilde{\tau}^*$ decelerates (segment slopes $-0.70/-0.41/-0.28$, curvature $+0.27 \pm 0.01$ over three seeds) toward a floor of order $\delta/2$ rather than following any power law. The companion arm, which holds the mechanism family fixed, differs only on the first segment ($b = -0.489$ vs -0.552): mechanism-scale conditioning is real but small.

An out-of-sample test. The two readings predict differently at the next size, so we wrote the predictions down before the run: $\tilde{\tau}^*(5000) > 0.021$ if the optimum is margin-pinned, 0.015 from our $|\mathcal{X}|^{-0.552}$ fit. The run read $\tilde{\tau}^* = 0.0230$, with the straddle signature unchanged (missed-truth KL median 0.086, accepted-FP KL 0.027, false positives 100% lag-1): the power law fit to our own twelve points is refuted one size out of sample, and the margin reading holds. The residual movement is itself measurable—the estimator’s level on margin-band pairs, ≈ 0 at $|\mathcal{X}| = 1000$ –2000, drifts to $-0.16/-0.20$ decades at 5000—so even the margin-pinned threshold inherits a slow calibration drift, to be re-measured per world rather than extrapolated.

Reading. The paper’s $\tau = C/|\mathcal{X}|$ law is a faithful fit within its own regime; what generalizes across regimes is the margin anchor. Writing b_1 for the estimator’s measured level on margin-band pairs, the blind optimum sits within $\times 1.7$ of $(\delta/2) \cdot 10^{b_1}$ at every size from 500 up, and within $\times 1.5$ from 1000 up (per-seed $\times 1.5$ –1.65 at $|\mathcal{X}| = 500$, where the noise floor is still receding; at $|\mathcal{X}| = 100$ the still-collapsing noise floor, not the margin, sets the optimum); the follow-up worlds read $\times 1.07$ at 10^4 and $\times 0.70$ at $2 \cdot 10^4$, where no absolute $\tau(|\mathcal{X}|)$ fit survives. Across 27 world-runs spanning six vocabulary sizes and three same-size capacity regimes, b_1 is predicted by the model’s residual fit error (the excess of final validation loss over the generator’s conditional-entropy floor; $R^2 = 0.78$) better than by $\log |\mathcal{X}|$ ($R^2 = 0.67$): the calibration drifts as the modeling problem gets harder, whatever the vocabulary. The operational conclusion, the authors’ as well as ours, is that the transferable object is the selection protocol—“ τ selected on held-out validation data by maximizing $F1$ ” reproduces the paper’s number at every size we tried—and that a quoted threshold is best stated relative to the truth margin and the estimator’s measured calibration, not as an absolute constant.

7 What TRACE recovers: a lag-graded recall limit of the staircase construction at a single global threshold

Recall is the lag-1 share. Every world in this section up to the flat-decay control of the closing paragraph carries the synthetic generator’s default lag decay ($e^{-(k-1)}$, the $r = 1$ member of the Section 4 family)—the regime the paper’s own evaluation runs in, and the default whose skew Section 8 measures. At the selected single global threshold the estimator recalls lag-1 true edges (cause immediately before effect) at 0.97–0.99 on every world in the sweep, while true edges at lag ≥ 2 are recalled at 0.15 ($|\mathcal{X}| = 100$), then 0.006, 0.004 and 0.000; false positives are 98–100% lag-1 from $|\mathcal{X}| = 500$. Overall recall therefore equals the lag-1 share of the truth on every world (0.81–0.84 observed vs. lag-1 shares 0.80–0.85). The mechanism is a level gap, not sampling noise: lag-1 pairs are read at their generator KL, while lag ≥ 2 true pairs read from one to over three

decades below it as $|\mathcal{X}|$ grows, three decades at $R = 0.93$ (median $\log_{10}(\text{CMI}/\text{KL}) -3.0$ at lag 2, -3.3 at lag 3), and about five decades in the follow-up worlds at $1-2 \cdot 10^4$, where lag ≥ 2 recall is exactly 0.000. No *single global* threshold can rescue a class that reads decades below the lag-1 scale the threshold is fit on. The class is, however, not wholly invisible: selecting τ per lag (validation argmax restricted to lag- k candidates) recovers 0.35/0.47 of lag-2 truth on the same replication runs, at $\tau_2 \approx 4-8 \times 10^{-4}$ —two orders of magnitude below the pooled optimum—while lags ≥ 3 remain unrecovered by any threshold family selectable on these runs: their truth reads below the lag’s own null floor, and the validation cells (6–23 true pairs) are too thin to select a threshold from.

Explaining the high-redundancy ceiling. In the high-redundancy world ($R = 0.93$) blind val-selected τ reaches per-sequence $F1 = 0.8271/0.8277$ against exact truth (5,000 test sequences per seed; cross-seed gap 0.0007), against 0.90–0.91 at $R \approx 0.59$. The lag decomposition accounts for the ceiling: lag-1 truth is saturated (recall 1.000; $\approx 99\%$ of lag-1 candidate pairs are true), the missed truth is entirely lag-2/3 pairs with margin-band KL (median 0.11), and the selected $\tau^* = 10^{-2}/3 \cdot 10^{-3}$ is the same δ -straddle one lag class down and three decades lower—61–70% of its false positives are lag-2 pairs. What the redundancy changed is the truth’s lag composition (0.70/0.21/0.09 at lags 1/2/3, vs. 0.84 lag-1 in the replication world): per-sequence recall is again the recallable-lag share. The practical point is one of score interpretation: the same protocol, reading each lag class the same way in both worlds, scores 0.91 where truth is 84% lag-1 and 0.83 where it is 70% lag-1, so the aggregate $F1$ carries the domain’s lag composition as much as the estimator’s quality, and a headline-score difference across datasets is not by itself evidence of better or worse recovery. Only per-lag recall separates a shift in the truth’s composition from a change in the estimator.

The mechanism: mediator randomization off the data distribution. The synthetic evaluation uses two different methods for the ground-truth discovery and for one-shot estimation at inference time. The ground-truth intervention is atomic and factual: only the cause position is re-drawn, and every other position, including the mediating events, is held at its observed value. Conditioning on the observed mediators blocks the mediated pathway, so a lag- ≥ 2 truth edge is a *direct* dependence, evaluated with the effect’s real context in place. The estimator’s randomized do-operator (Def. 4.6) re-draws the entire window tail after the intervention point, so the same observed effect token is predicted, on *both* sides of the CMI contrast, under a context of uniform noise—a mediator configuration far off the distribution the sequences are drawn from. Stripped of the real predecessors it was generated from, that token’s factual probability collapses toward its marginal rarity, and the CMI read from it falls by decades, whatever the strength of the direct dependence and at any particle count. (In intervention-semantics terms both constructions ask the direct-effect question—the truth evaluates it at the factual mediator configuration, the estimator averages it over uniform mediator draws—so the deep-lag deficit is a loss of reading scale, not a change of estimand. The factual configuration can itself mask an edge the randomization would witness: where the observed mediator values happen to suppress a direct dependence, the truth records no edge, and a real direct edge the one-shot estimate recovers is scored a false positive—the error is then the truth’s, not the estimator’s.) The gap carries the fingerprints of this probability-scale mechanism rather than of an estimation error or a scope exclusion: it widens with vocabulary (from under one decade at $|\mathcal{X}| = 100$ to five–six decades at $1-2 \cdot 10^4$, where the observed token is rarer under noise), and it moves by decades at fixed $|\mathcal{X}|$ when the marginal distribution or the model’s achieved fit changes. Consistently, an atomic variant of the estimator—noising only the candidate cause row, mediators left at their observed values, i.e. the truth’s own construction run

as an estimator—recovers 0.45/0.55 of the lag-2 truth the staircase misses at a single pooled τ (equal-particle paired rescore), because the factual context keeps the effect token’s probability at its observed scale; lags ≥ 4 stay at zero under either construction. We use it as an instrument sizing the staircase’s share of the deficit, not as a rival estimator. The operational implication for users of the algorithm in its published form, on data whose causal strength decays with lag: at a single global threshold, the graph TRACE recovers is a direct, adjacent-influence (lag-1) graph. Longer-range dependencies then appear only insofar as they are chains of lag-1 links, and per-lag recall should be reported so that the unrecovered class is visible.

A flat-decay control isolates the staircase’s own share. To size that share independently of the data’s lag profile, we generalize the generator’s decay to $e^{-r(k-1)}$ and re-match redundancy (Section 4). On a flat world ($r = 0$; truth now 15% lag-1 and $\approx 1.9\times$ denser), the same pipeline at its single validation-selected $\tilde{\tau}^* = 0.041$ recalls truth at 0.87/0.76/0.69/0.63/0.59/0.40 across lags 1–6 (test side, seed-replicated within 0.03 per lag): the limit is graded, not absolute. The δ -straddle of Section 6 transfers to the flat world ($\tilde{\tau}^*$ again between $\delta/2$ and δ ; missed-truth KL median $0.15 \in [\delta, 3\delta]$), though its false positives are no longer lag-1-dominated (34%). (The flat worlds run hotter on the residual fit error of Section 6, $\hat{\varepsilon} \approx 0.19$ vs. 0.13 in the sweep, consistent with their denser truth; we disclose this since calibration tracks $\hat{\varepsilon}$.) Even with lag-uniform truth, staircase recall declines with lag (0.87 $\rightarrow$ 0.40 above), while the atomic variant run on the same emits is essentially lag-flat—the staircase reads 13 pp *above* atomic at lag 1, parity at lag 2, and 8–26 pp below it at lags 3–6 (each construction at its own validation-swept pooled threshold). This lag-graded residual is the staircase’s own share of the deficit, and the only part of it that belongs to the algorithm. A second share belongs to the single shared threshold: it is the part the per-lag τ family above recovers. The third and the dominant share—the data’s own decay—belongs to the benchmark, and is estimated in the next section.

8 What validating on the default benchmark certifies: a practitioner warning

A doubly skewed default. The synthetic benchmark is specified in the paper’s evaluation appendix (Eq. 21) and is not a part of the algorithm per se, but it is where every headline number comes from. Its mechanism weights hard-code the exponential lag decay $e^{-(k-1)}$, and at that default the benchmark is skewed toward lag 1 twice over: $\approx 85\%$ of position-level interventional truth sits at lag 1, and the deep-lag truth that remains reads below the estimator’s noise floor—on our runs, below the lag’s own null floor from lag 3. The skew is dose-dependent, not incidental: recall at every deeper lag falls monotonically as the decay rate rises toward the default $r = 1$ (at lag 4: $0.63 \rightarrow 0.43 \rightarrow 0.06 \rightarrow 0.00$ for $r = 0, 0.1, 0.3, 1$).

What validating on it certifies—and conflates. Headline per-sequence $F1$ on this benchmark is attainable by lag-1 recovery alone: our replication scored 0.90–0.91 while recalling essentially no lag ≥ 2 truth. Validation against the default generator therefore certifies adjacent-influence recovery only—not the long-range dependencies that motivate event-sequence causal discovery, including the paper’s own motivating examples (server logs, medical records), where nothing guarantees that influence concentrates at lag 1. And it conflates the two findings this note separates: a practitioner who validates only on this default benchmark observes zero lag- ≥ 2 recall and may conclude, as we nearly did, that the method cannot recover it at all—although the dominant share of that deficit belongs to the benchmark’s decay compounded with the shared threshold, not to

the staircase construction, whose own share is the moderate, lag-graded residual of Section 7. The flat-decay generalization is a one-parameter control any user can run to separate the two on their own deployment.

9 The particle budget

The paper reports diminishing returns in N with no significant change beyond $N = 256$ (paper’s Fig. 8); the authors’ expectation, when asked, is saturation around 128, since density-estimation error should dominate the Monte-Carlo error of the particle average. We tested this at the paper’s regime: inference-only re-runs of the frozen replication models (1,024 test sequences, $c = 6$) at $N \in \{2, 4, \dots, 512\}$, read at the selected $\tau^* = 0.03$, with N_{sat} defined in advance as the smallest N such that $F1$ and recall stay within 0.01 of their $N = 512$ values for every larger N , on both seeds. **Outcome:** $N_{\text{sat}} = 2$ —a property of our operating point, not a universal constant; the transferable object is the rule this section ends with. Over the whole sweep $F1$ spans 0.0012 (0.8999 $\rightarrow$ 0.9011 / 0.9042 $\rightarrow$ 0.9054) and recall 0.0015, while inference wall time is linear in N (47s at $N = 2$ and 3,320s at 512).

Because flat-from-two invites the suspicion of a degenerate model, we diagnosed it on the persisted per-pair CMI matrices. *The estimator is not saturated; the observable is.* On exact-truth position pairs $|\text{CMI}_N - \text{CMI}_{512}|$ falls like $N^{-0.46}$ on both seeds—textbook Monte-Carlo behaviour—but the true-pair median sits 1.6 decades above τ^* and the non-true median 3 decades below it, so the noise almost never crosses the threshold: 13/12 of 28,320 position classifications change between $N = 2$ and 512, against 1,784/1,723 at $\tau = 3 \times 10^{-5}$ and 12,211/12,459 at 10^{-6} . *The published reference points are one curve:* applying the same rule at every grid τ gives $N_{\text{sat}} > 256$ for $\tau \in [1.7, 3.4] \times 10^{-5}$, 128–256 up to 1.7×10^{-4} , 64 at 3×10^{-4} , 8 at 10^{-3} , and 2 for every $\tau \geq 1.8 \times 10^{-3}$ —the paper’s “ ≥ 256 ”, the authors’ “ ≈ 128 ” and our “2” are indexed by the threshold’s distance to the non-edge noise floor. (Inside the floor, the right-skewed non-negative per-particle KL means *more* particles give *more* false positives: precision at 3×10^{-5} falls from 0.45 at $N = 2$ to 0.27 at 512.) *It is not model collapse:* the model’s predictive entropy is above the generator’s exact conditional entropy (median 3.10/3.14 vs. 2.88/2.83 nats), and $\approx 94\%$ of the particle variance sits on the intervention side. The authors’ reading is confirmed with one refinement: against the generator’s exact per-pair KL the estimate has an N -independent error floor of 0.7–0.9 nats RMS while the Monte-Carlo part is 0.40 nats at $N = 2$ and 0.05 at 256—density-estimation error dominates, and at a threshold three decades above the floor it does so from N of a few. The general rule: *set the particle budget by the selected threshold’s distance to the noise floor, not by a fixed N .*

10 Guidance for practitioners

For anyone applying TRACE to their own event sequences—or rebuilding it and validating the rebuild—our findings reduce to five rules.

1. **Select τ on held-out data, and expect it at the truth margin.** The validation sweep is inference-only—no retraining—and in our hands it is what carries the paper’s performance to every regime we tried, while any fixed constant transplanted across regimes loses 0.4–0.6 $F1$, and even a power law fit to our own sweep failed one size out of sample. The number the sweep returns has a meaning: for a level-calibrated model the optimum sits at roughly $\delta/2$ to δ —half to one of the effect-size margin that defines an edge worth calling—and its errors concentrate on both sides of that margin. Quote thresholds relative to the margin and the

measured calibration, never as absolute constants, and expect the calibration to drift as the modeling problem gets harder.

2. **Size the particle budget from the selected threshold’s margin, not from a fixed N .** Once τ^* is known, a handful of particles suffices if it sits decades above the non-edge noise floor—in our runs $N = 2$ matched $N = 512$ at $70\times$ less compute. Large particle counts pay only when the threshold approaches the floor, and *inside* the floor extra particles actively increase false positives.
3. **Know which observable you are computing.** TRACE’s headline metric is per-observation: one summary graph per sequence, scored per sequence. Aggregating evidence across a corpus into a single system-level graph is a different and harder estimation problem, and per-sequence numbers do not transfer to it.
4. **Under lag-decaying data and a single global threshold, read the graph as direct, adjacent (lag-1) influence—and report per-lag recall.** Lag-1 true edges are recalled at 0.97–0.99; true edges at lag ≥ 2 read decades low and are recalled near zero at any single global threshold, because the tail-randomized context collapses the observed effect token’s factual probability. Overall recall is then the lag-1 share of the domain’s true structure—our ≈ 0.83 ceiling at extreme redundancy is exactly that share falling—and aggregate $F1$ cannot distinguish that fall from estimator degradation. Before concluding the deeper signal is absent, sweep τ per lag: it recovered a third to a half of lag-2 truth in our runs, and the selected τ_k ladder is itself diagnostic (it falls $\sim 500\times$ over lags 1–6 under strong decay, $\sim 30\times$ when flat). If long-range recovery is the claim, run a flat-decay variant of the generator as a control—on ours, one validated threshold recalled every lag. Reporting per-lag recall makes the invisible class visible.
5. **Validate long-range recovery on a slowed or flattened decay, not on the default generator alone.** The default generator’s hard-coded lag decay ($e^{-(k-1)}$ in the mechanism weights) concentrates $\approx 85\%$ of interventional truth at lag 1 and pushes deep-lag truth below the estimator’s own noise floor, so the headline per-sequence $F1$ is attainable by lag-1 recovery alone: our replication scored 0.90–0.91 while recalling essentially no lag ≥ 2 truth. A rebuild validated only against this generator is therefore certified for adjacent-influence recovery, not for the long-range dependencies that motivate event-sequence causal discovery. To test the latter, slow or flatten the decay (one generator parameter, Section 8) so every lag carries recallable truth, and read per-lag recall against both the staircase and the atomic construction: on our flat control the staircase’s residual, lag-graded deficit (8–26 pp below atomic at lags 3–6) is the algorithm’s own share, cleanly separated from the generator’s.

11 Conclusion

Scored its own way and given its own regime, TRACE does what its paper says: an independent reimplementations reaches $F1 = 0.90\text{--}0.91$ against exact interventional truth, matching paper’s Table 2, and 0.86–0.91 at every vocabulary size from 100 to 2000 under the validation-sweep protocol the paper’s own sensitivity analysis licenses. Behind those numbers sit three regime facts and one warning. The selected threshold converges on the truth margin: its errors straddle δ , its residual movement is the estimator’s slowly drifting calibration, and a power-law extrapolation of it fails one size out of sample. At a single global threshold on lag-decaying data, the recovered graph is a direct, adjacent-influence graph: no such threshold reaches the class that reads decades below the lag-1

scale, a per-lag family recovers the nearest of it, and the staircase’s own share of the deficit—isolated on a flat-decay control the pipeline otherwise recovers at every lag—is a moderate, lag-graded residual. The particle budget is set by the selected threshold’s margin over the noise floor, not by a fixed count. The warning: the paper’s default benchmark is specified in its appendix and skewed toward lag 1 in both truth mass and CMI scale; validating on it certifies lag-1 recovery only and conflates the benchmark’s skew with the staircase’s limit—validate long-range claims on a slowed or flattened decay. *Thresholds, budgets and recall ceilings are regime properties; the protocol—select on validation, quote against the margin, report per-lag recall, and control the generator’s decay when long-range claims are at stake—is the method property practitioners should carry.*

Reproducibility statement

All experiment plans were committed before the runs they govern; gated numbers were produced under validation-frozen thresholds recorded in a versioned registry prior to any test-side run; outcome bands, saturation rules and escalation rules for the vocabulary and particle sweeps were committed before any of their runs existed. Experiments ran on single NVIDIA A10G instances (pretraining ~30–40 min per world; the particle sweep inference-only); the runs behind this note sum to under 40 GPU-hours excluding boot and setup, and the pipeline is bit-reproducible per configuration and seed on this hardware.

Acknowledgments

We contacted Hugo Math and Rainer Lienhart on 2026-08-14 describing the replication findings and asking about the threshold scale. Hugo Math replied on 2026-08-17 with clarifications that shaped Sections 6–9 (implementation checks we then ran, the local-sharpness hypothesis, and the particle-count expectation); we are grateful for the care of that engagement and cite the reply as personal communication with the authors’ permission. The per-pair tail analyses behind Sections 6 and 7—which deepen the authors’ local-sharpness hypothesis into the margin-straddle reading—and the particle-count diagnosis were run in response to that exchange. Two further replies (2026-08-24 and 2026-08-26) shared per-lag-threshold and flat-vs-decayed control experiments on the authors’ own generator; the per-lag threshold family and the flat-decay control of Sections 7 and 8 replicate those designs on ours.

References

- Ruichu Cai, Siyu Wu, Jie Qiao, Zhifeng Hao, Keli Zhang, and Xi Zhang. THPs: Topological Hawkes processes for learning causal structure on event sequences. *IEEE Transactions on Neural Networks and Learning Systems*, 35(1):479–493, 2024.
- Joscha Cüppers, Sascha Xu, Ahmed Musa, and Jilles Vreeken. Causal discovery from event sequences by local cause-effect attribution. In *Advances in Neural Information Processing Systems 37*, 2024.
- Daphne Koller and Nir Friedman. *Probabilistic Graphical Models: Principles and Techniques*. MIT Press, 2009.
- Han Liu, Kathryn Roeder, and Larry Wasserman. Stability approach to regularization selection (StARS) for high dimensional graphical models. In *Advances in Neural Information Processing Systems 23*, 2010.

- Hugo Math. *Learning to Predict, Discover, and Reason in High-Dimensional Event Sequences: Exploiting the Predictive-Causal Duality of Autoregressive Models for Vehicle Diagnostics Automation*. PhD thesis, University of Augsburg, 2026a. arXiv:2603.16313v2.
- Hugo Math. seq2cause, 2026b. URL <https://github.com/Mathugo/seq2cause>. MIT license; Zenodo doi:10.5281/zenodo.19068730.
- Hugo Math and Rainer Lienhart. Your autoregressive model already reveals the causal graph. In *ICML 2026 Workshop on Structured Probabilistic Inference & Generative Modeling (SPIGM)*, 2026. arXiv:2602.01135v4.
- Ignavier Ng, Biwei Huang, and Kun Zhang. Structure learning with continuous optimization: A sober look and beyond. In *Proceedings of the 3rd Conference on Causal Learning and Reasoning (CLearR)*, volume 236 of *Proceedings of Machine Learning Research*, pages 71–105, 2024. URL <https://proceedings.mlr.press/v236/ng24a.html>.
- Judea Pearl. *Causality: Models, Reasoning, and Inference*. Cambridge University Press, 2nd edition, 2009.
- Jonas Peters, Dominik Janzing, and Bernhard Schölkopf. *Elements of Causal Inference: Foundations and Learning Algorithms*. MIT Press, 2017.
- Jie Qiao, Ruichu Cai, Siyu Wu, Yu Xiang, Keli Zhang, and Zhifeng Hao. Structural Hawkes processes for learning causal structure from discrete-time event sequences. In *Proceedings of the 32nd International Joint Conference on Artificial Intelligence (IJCAI)*, pages 5702–5710, 2023.
- Alexander G. Reisach, Christof Seiler, and Sebastian Weichwald. Beware of the simulated DAG! Causal discovery benchmarks may be easy to game. In *Advances in Neural Information Processing Systems 34*, 2021.
- Wei Zhang, Thomas Kobber Panum, Somesh Jha, Prasad Chalasani, and David Page. CAUSE: Learning Granger causality from event sequences using attribution methods. In *Proceedings of the 37th International Conference on Machine Learning (ICML)*, pages 11235–11245, 2020.
- Yuzhe Zhang, Chihui Chen, Lina Yao, and Chen Wang. Consistency evaluation of benchmarks used for causal discovery, 2026. arXiv:2606.01789.