

Efficient Expert-Parallel Communication on PCIe-Connected Consumer GPUs

Jaehwan Lee
Dept. of Computer Science and
Engineering
Seoul National University
jaehwan@aces.snu.ac.kr

Sangmin Lee
Dept. of Computer Science and
Engineering
Seoul National University
sangmin.lee@snu.ac.kr

Chaewon Kim
Dept. of Computer Science and
Engineering
Seoul National University
chaewon@aces.snu.ac.kr

Junsik Shin
Dept. of Computer Science and
Engineering
Seoul National University
junsik@aces.snu.ac.kr

Jaejin Lee
Dept. of Computer Science and
Engineering
Graduate School of Data Science
Seoul National University
jaejin@snu.ac.kr

Abstract

Expert parallelism (EP) enables inference of large Mixture-of-Experts (MoE) models by placing their experts across multiple GPUs, but requires substantial communication between GPUs at every MoE layer. As contemporary MoE models activate more experts per token, this communication accounts for a growing fraction of inference time. The cost becomes particularly pronounced on PCIe-based consumer GPU systems, where all inter-GPU transfers traverse CPU memory. However, existing MoE-specialized EP communication libraries assume that direct GPU-to-GPU access is available, largely overlooking consumer GPUs. Therefore, most LLM frameworks instead rely on NCCL, whose CPU-staged communication incurs redundant PCIe transfers and competes with expert computation for GPU resources, limiting their overlap. We present ThunderEP, a novel communication design for such systems that removes the relay hops of traditional ring algorithm, moves data through DMA engines to avoid compute resource contention, and minimizes synchronization latency by reducing the polling overhead of completion flags in CPU memory. We integrate the proposed design into vLLM and evaluate it on three widely used MoE models. Experiments on two PCIe systems equipped with RTX 4090 and RTX 5090 GPUs show that ThunderEP achieves average speedups of 2.00 $\times$ and 1.53 $\times$ over NCCL for dispatch and combine, respectively, and up to 1.66 $\times$ end-to-end speedup over state-of-the-art MoE inference frameworks.

1 Introduction

Mixture-of-Experts (MoE) [19] has become a standard architecture for scaling frontier large language models (LLMs) [55, 57, 61]. The expert parameters of modern MoE-based LLMs, however, are often too large to reside on a single GPU [30]. Serving these models therefore commonly relies on expert parallelism (EP) [6, 21, 52, 63], which partitions experts

across GPUs and routes each input token to the GPUs hosting its selected experts.

EP introduces communication on both sides of every expert computation. Before the computation, token activations must be *dispatched* to the GPUs holding their selected experts. The resulting expert outputs must then be returned to and *combined* on the GPUs that own the tokens. These operations occur at every MoE layer in a Transformer layer and directly lie on the critical path of inference [63]. Moreover, recent MoE-based LLMs increasingly employ *fine-grained* experts and activate more experts per token [25]. Although this design improves model capacity and quality without proportionally increasing computation [30], it increases the number of destinations reached by each token and makes communication a growing fraction of MoE inference [12].

A number of EP communication systems have been developed to reduce this overhead, including DeepEP [2], HybridEP [35], pplx-kernels [3], NCCL EP [11], and NIXL [40]. These libraries provide routing-aware data movement and employ techniques such as device-initiated communication, fine-grained synchronization, and operation overlapping. Their designs, however, assume that GPUs can directly access one another through NVLink [42], GPUDirect Peer-to-Peer (P2P) or RDMA [41]. This assumption is fundamental to both their data transfer and synchronization mechanisms [31].

Such direct GPU access is unavailable on latest consumer GPUs (e.g., RTX 40 and 50 series) which lack NVLink and have PCIe P2P access disabled by the driver. Every inter-GPU transfer must instead be staged through a bounce buffer in CPU memory [16]. Consequently, existing EP communication libraries [2, 11, 32] cannot operate on these systems. Nevertheless, cost-efficient PCIe-based systems equipped with consumer-grade GPUs are widely used for LLM inference by researchers and moderate-scale institutions [5, 10, 24, 49, 54]. To our knowledge, all major LLM frameworks [26, 29, 46, 58, 65] thus fall back to NCCL [39], NVIDIA’s GPU communication library, that can run without P2P support. Notably,

NCCL’s newly introduced device API [36] also requires P2P connectivity and is therefore unavailable on consumer GPUs.

However, the conventional NCCL path available on these systems has several key limitations for MoE inference on consumer GPUs. A traditional ring algorithm [14] implemented in NCCL repeatedly relays data through host memory, causing the same data to traverse PCIe multiple times. In addition, NCCL communication kernels executed on streaming multiprocessors (SMs) compete with expert computation for execution resources [62], limiting their opportunity to overlap with computation [63]. In addition, inter-GPU synchronization must use completion flags placed in the CPU memory, making every poll a PCIe transaction.

In this paper, we present a novel EP communication design for MoE inference on PCIe-based consumer GPU systems. Our design treats host memory as a shared communication medium rather than merely as a bounce buffer between pairs of GPUs. It replaces multi-step data forwarding of conventional ring with single-step collective algorithm that reduce repeated PCIe transfers, executes bulk data movement on dedicated DMA engines to leave the SMs available for expert computation overlap, and employs lightweight synchronization that limits host memory polling and allows each transfer to proceed as soon as its dependency is satisfied. We integrate the proposed system into vLLM, a state-of-the-art LLM serving engine, and demonstrate that optimizing EP communication effectively translates into end-to-end inference gains on consumer GPU systems.

The key contributions of this paper are as follows:

- We characterize the inference of MoE models on consumer GPUs and identify the key communication bottlenecks caused by the lack of P2P access, including PCIe link contention, SM competition, and long-latency synchronization through host memory.
- We propose a novel single-step collective communication algorithm for dispatch and combine operations, which reduces redundant PCIe transfers incurred when conventional collective algorithms repeatedly relay data via a bounce buffer in CPU memory.
- We develop an efficient DMA engine-based transfer design and a lightweight synchronization scheme that reduce SM competition, exploit bidirectional PCIe bandwidth, and reduce synchronization overhead.
- We integrate the proposed design into vLLM and evaluate its performance at both the collective-operation level and in end-to-end inference on two PCIe-based systems equipped with NVIDIA RTX 4090 and RTX 5090 GPUs, respectively.

2 Background

In this section, we briefly overview communication patterns in distributed MoE and GPU communication mechanisms.




Figure 1. A single MoE layer (a) without and (b) with expert parallelism. I , E , O denote input tokens, experts, and outputs.




Figure 2. Expert granularity of a MoE layer.

2.1 Communication in MoE

Distributed MoE and expert parallelism. MoE replaces the dense feed-forward network (FFN) of a Transformer layer with E experts and a router. The router selects k experts per token ($k \ll E$), and only those experts compute on the token (Figure 1a). The experts of a modern MoE model typically do not fit in the memory of a single device [30], so they are partitioned across devices under EP [52], while attention and the other layers are replicated under data parallelism (DP) [47] with each device holding its own tokens. A token and the experts it needs thus sit on different devices. Each token is sent to the devices holding its selected experts before the expert computation, and the outputs are returned to the device that owns the token afterwards. As shown in Figure 1b, MoE on multiple devices with EP, occurs with two All-to-All collective communications in a single forward pass. The expert computation is thus enclosed by communication on both sides.

Recent trend of MoE architectures. Early MoE models such as Mixtral 8x7B [20] have few experts with small top- k routing (8 experts, top-2). Recent models increase the number of experts and use a larger top- k to activate more experts, with each having a smaller hidden dimension to match the same computation cost. DeepSeek-V3 [30] routes each token to 8 of 256 experts, and Qwen3.8-2.4T-A95B [45] to 10 of 512. Figure 2 shows an example of different levels of granularity in an MoE layer. Finer granularity leaves the per-token computation unchanged. However, communication does not: each token is copied to k destinations during




Figure 3. An All-Gather and Reduce-Scatter communication pattern for token dispatch and combine in a MoE layer. Top-2 routing with 2 experts on each of 3 devices, where each token selects one expert on each remote device.

dispatch and gathered back during *combine*, so the transfer volume grows in proportion to k until a token reaches every remote device, beyond which it cannot grow further. Communication therefore takes a larger share of the MoE layer as models move toward finer granularity, which makes optimizing the communication more important than it was for earlier models.

Communication patterns of dispatch and combine.

At the semantic level, token dispatch and combine operations form routing-dependent, variable-sized many-to-many communication patterns, which can be expressed as *All-to-Allv* [27]. Such an implementation transfers only the tokens and partial outputs required by the selected experts. An alternative is an All-Gather and Reduce-Scatter formulation [21]. During dispatch, each GPU gathers the input tokens from all other GPUs and locally retains the tokens assigned to its experts. During combine, each GPU places its partial expert outputs in a dense buffer ordered by the source tokens, and Reduce-Scatter returns the reduced outputs to their owning GPUs. Figure 3 illustrates this formulation.

The All-Gather and Reduce-Scatter formulation may transfer tokens that are not consumed by any expert on a receiving GPU. However, it avoids routing-dependent message sizes, CPU-GPU synchronization overhead, and irregular peer-to-peer exchanges and instead uses regular collective operations that can achieve higher communication efficiency [58]. As top- k increases relative to the number of EP devices (i.e., EP size), especially common in recent models, each token tends to cover more destination GPUs, reducing the redundant communication of the dense formulation. A recent study similarly reports that All-Gather followed by Reduce-Scatter outperforms two All-to-All collectives when top- k exceeds the number of GPUs [21]. Several state-of-the-art MoE systems, including Megatron-Core and vLLM [26, 34, 58, 65], therefore adopt an implementation of All-Gather and Reduce-Scatter as their default EP communication backend.




Figure 4. Communication between GPUs in a node.

2.2 GPU Communication Mechanisms

Communication between GPUs. GPUs within a same node communicate either directly, namely as *peer-to-peer* (P2P), or by staging in a bounce buffer in CPU memory, a transport which NCCL calls *shared memory* (SHM), depending on their interconnect and topology [16]. Figure 4a shows how intra-node GPUs in a PCIe system communicate with P2P mechanism. For NVIDIA GPUs, P2P is available in two cases. The first is when GPUs are interconnected with a high-bandwidth direct GPU-to-GPU interconnect such as NVLink [42]. The second is a PCIe-only system in which each device can expose its memory to the PCIe address space so that the other devices can access it directly [23]. On data-center and workstation GPUs, this direct path, called GPUDirect [41] P2P by NVIDIA, is the norm. It is used unless the two GPUs are far apart in the PCIe topology, for example, attached to different CPU root complexes. In that case, NCCL falls back to its SHM transport. Consumer GPUs, however, do not support P2P fundamentally [49]. Therefore, communication between consumer GPUs must pass through the CPU memory. As shown in Figure 4b, the sender writes the payload to a pinned host buffer, and the receiver reads it back, so every byte traverses PCIe bus twice [4].

Data transfer mechanisms. There are two ways of how GPUs can transfer data each other. First is the DMA or copy engine-based communication. Dedicated DMA engines in the device move data between two memory regions. The transfer is issued as an asynchronous copy such as `cudaMemcpyAsync`, which is staged through host memory when peer access (i.e., P2P) is unavailable. This mechanism reaches the peak bandwidth of the PCIe link for large messages, but it operates on contiguous or fixed-stride regions specified at issue time and cannot perform data-dependent gather or scatter, so tokens scattered at data-dependent locations must be packed into a contiguous region by a preceding kernel [37].

Next, we can use the load/store units (LSUs) in the SMs for GPU-to-GPU communication. Once the destination buffer is mapped into the address space of a device, a GPU kernel reads and writes it with ordinary load and store instructions. NCCL mainly uses this mechanism for some advantages over DMA transfers [16]. The transfer granularity is a single access rather than a buffer, which keeps the latency of

small messages low and lets a kernel gather or scatter tokens without a separate packing step. The cost is that the transfer occupies SMs that would otherwise run computation [44].

3 Related Work

This section provides related work on communication libraries, DMA engine-based collectives, and communication-centric optimizations for accelerating MoE.

Communication libraries. Most GPU communication libraries are designed for systems with direct GPU-to-GPU access. NCCL [16] executes communication operations using SM kernels and stages data through host memory when P2P access is unavailable. Its recent device API and DMA engine path [36] still require direct P2P connectivity. Communication libraries specialized for MoE EP, including DeepEP [2], pplx-kernels [3], NIXL-EP [40], NCCL EP [11], and UCCL-EP [32], similarly rely on NVLink, GPUDirect P2P, or RDMA for their optimized GPU-initiated paths. ThunderEP instead provides dispatch and combine operations over host memory for consumer GPUs where direct GPU access is unavailable.

Copy engine collectives. VCCL [62] and FiCCO [43] offload data movement from the SMs to DMA engines, but retain direct GPU-to-GPU transfers on P2P-capable systems. HFRReduce [4] and LLMQ [49] also use DMA engines and host memory, but target training communication. HFRReduce performs CPU-based All-Reduce for gradients, while LLMQ handles dense weight and gradient transfers for low-precision pretraining. TCCL [23] selects communication paths across PCIe and NUMA topologies, and llama.cpp [10] implements a host-staged two-GPU All-Reduce for tensor parallelism. ThunderEP targets a different setting by providing multi-GPU All-Gather and Reduce-Scatter for MoE inference, retaining reduction on the GPUs and exposing completion by source GPU to overlap communication with expert computation on consumer GPU systems without P2P access.

MoE communication optimizations. Prior work reduces the cost of EP communication through hierarchical exchange, as in DeepSpeed-MoE [46], Tutel [18], and HetuMoE [33], or through topology-aware routing, traffic reduction, and communication scheduling, as in TA-MoE [8], ExFlow [60], FasterMoE [15], Lina [28], and ScheMoE [53]. Flux [7] and Comet [63] overlap communication with computation at a finer granularity, but move data from GPU kernels over direct P2P links and use SM resources for communication. Framework techniques such as vLLM’s dual-batch overlap [56] and SGLang’s two-batch overlap [50] overlap different micro-batches but do not provide a communication path themselves. For MoE, their communication overlap relies on device-initiated EP libraries such as DeepEP [2], whose optimized paths require NVLink or RDMA. They therefore do not provide communication overlap on consumer GPU systems without P2P access. ThunderEP addresses the complementary

problem of providing an efficient path when communication must pass through CPU memory.

4 ThunderEP Design

This section first presents the key problems of optimizing EP communication for MoE on consumer GPUs and then describes how the proposed method addresses them.

4.1 Challenges

PCIe link contention. Without P2P access, communication between consumer GPUs is staged through CPU memory, causing concurrent transfers to contend for shared PCIe link and host memory resources. This contention is particularly costly for MoE EP because all GPUs communicate concurrently during dispatch and combine operations. Measurements in our PCIe-based RTX 5090 system (Table 1), a GPU communicating alone reaches 56.5 GB/s on PCIe Gen5, close to its theoretical bandwidth of 64 GB/s. When a second GPU under the same PCIe host bridge communicates concurrently, the bandwidth of each GPU falls to 35.5 GB/s. The bandwidth available to each GPU therefore decreases as more GPUs participate in a collective, making it important to minimize both the PCIe traffic volume and repeated transfers through host memory.

SM competition. NCCL performs its collective operations using kernels that occupy the GPU SMs. When communication overlaps with expert computation, the two operations compete for the same SM resources [49, 62]. We observe that co-scheduling an NCCL with a GEMM delays the communication kernel and stalls the progress. DMA engines avoid this contention by moving data without occupying the SMs, but each transfer incurs a fixed issue overhead and can access only contiguous or fixed stride regions. Data stored at routing-dependent locations must therefore be packed before transfer, and the issue overhead is particularly significant for the small transfers encountered during decoding. Although recent NCCL releases provide collective communication using DMA engines [36], this path requires P2P access and cannot operate on consumer GPU systems.

Long-latency synchronization. A collective communication further depends on synchronization among the participating GPUs, since a receiver must learn when a sender has finished writing the data destined for it. NCCL signals completion through a counter or flag buffer, and the collective kernel itself polls this buffer, occupying an SM and busy-waiting until the expected value appears. On consumer GPUs, where no GPU can address another GPU’s memory, the only memory both GPUs can map is the CPU memory. The completion flag buffer must therefore reside in pinned host memory, and every check of it is a round trip across the PCIe link, made by a kernel that remains resident on an SM.




Figure 5. All-Gather communication algorithm for dispatch in (a) NCCL and (b) ThunderEP.

ThunderEP’s approach. ThunderEP aims to enable efficient communication-computation overlap for MoE EP on consumer GPUs without P2P support. Our communication optimizations and collective design follow three principles. First, because concurrent GPU transfers contend for shared PCIe resources, it is important to minimize both the communication volume and the number of times data traverses PCIe. Second, because SM-resident communication competes with expert computation, communication should use as few SM resources as possible to enable effective overlap with expert GEMMs. Third, because inter-GPU synchronization relies on flags placed in host memory, it is essential to minimize expensive polling traffic and unnecessary waiting among GPUs. Based on these requirements, we design a new algorithm (§ 4.2), DMA engine-based communication design (§ 4.3), and efficient synchronization scheme (§ 4.4) for MoE communication on consumer GPUs.

4.2 Single-step Collective Algorithm

NCCL performs most of its collective communication operations primarily with a ring algorithm [16]. The traditional ring algorithm is a bandwidth-optimal, circular scheme in which each of the N GPUs in a node, where N is the number of GPUs, forwards the *shard* (i.e., one GPU’s data partition) it has just received on to its successor, so that after $N - 1$ steps every GPU holds the data of all N participants. On a system with NVLink or GPUDirect P2P mechanism available, this design reaches close to the system’s peak bandwidth,

because every link carries only the $(N - 1)/N$ fraction of the data that it must and each forwarding step is a direct GPU-to-GPU copy [16].

On a PCIe system, where the GPUs are commodity cards (e.g., NVIDIA GeForce RTX series) without P2P support, this reasoning no longer holds. Every transfer is staged through CPU memory, so a single step is not a direct copy but a round trip that writes the shard into host memory and then reads it back out on the next GPU, causing redundant data transfer as shown in Figure 5a. We further find that the effective PCIe bandwidth does not stay constant as more GPUs communicate at once, since the transfers contend for the shared PCIe link (e.g., host bridge) and the host memory behind it. Under this contention, spreading a collective across many links buys little, and it is more profitable to shorten the number of hops that each byte takes and to reduce the total volume that crosses the PCIe links in the first place.

To reduce the redundant transfer, we therefore replace the multi-step ring’s relay with a single-step broadcast via a bounce buffer on the CPU memory in All-Gather (i.e., dispatch), shown in Figure 5b. First, each GPU writes its own shard once into host memory buffer, and then, every GPU reads the remaining $N - 1$ shards back directly. No shard is ever forwarded between GPUs, so the pinned host memory serves as a single broadcast medium that each GPU writes to once and reads from as needed. The two schedules (i.e., NCCL’s ring and the single-step algorithm) differ in both the volume they move and the number of hops each byte travels.




Figure 6. Proposed Reduce-Scatter algorithm for combine with (a) GPU reduction and (b) CPU reduction.

Let S denote the size of one GPU’s shard. The ring transfers $2(N - 1)S$ bytes per GPU, one upload and one download at each of its $N - 1$ sequential steps, and a shard is relayed through as many as $N - 1$ host round trips before it reaches the farthest GPU. ThunderEP transfers $N \cdot S$ bytes per GPU, a single upload of its own shard and $N - 1$ downloads of the others, and it completes in a fixed two phases regardless of how many GPUs participate. The ratio of PCIe transfer volume between the two is $2(N - 1)/N$, which equals one at $N = 2$ and grows toward two as the node fills. Our design therefore breaks even at two GPUs compared to NCCL ring and begins to save once the node holds more than two, and the advantage widens as the GPU count grows.

Reduce-Scatter for combine operation follows the exact reverse data flow of All-Gather for dispatch, but must additionally sum the *blocks* (i.e., each GPU’s contribution to an output shard) produced by different GPUs. Figure 6 shows two choices for placing this reduction. With GPU reduction (Figure 6a), each GPU uploads the $N - 1$ blocks destined for other GPUs to CPU memory, and each destination GPU downloads the $N - 1$ remote blocks intended for it and sums them with its local block to form its output shard. This design eliminates the sequential relays and synchronization of the ring, but moves $2(N - 1)S$ bytes per GPU, the same analytic communication volume as NCCL. With partial CPU reduction (Figure 6b), the CPU first sums the remote GPUs’ blocks for each destination in host memory, so that the destination GPU downloads a single reduced result and adds its local contribution. This design uploads $(N - 1)S$ bytes and downloads S bytes per GPU, resulting in a total volume of $N \cdot S$, the same as ThunderEP’s single-step algorithm for All-Gather with the transfer directions reversed.




Figure 7. DMA engine-based communication for token dispatch and combine in MoE with EP.

4.3 DMA Engine-based Communication

NCCL drives the data transfer with SM-resident kernels that copy each shard through a bounce buffer in the CPU memory on a consumer-grade GPU node. This approach takes SMs away from computation, and the communication kernels must first be launched and scheduled onto those SMs, which adds latency and, when the SMs are occupied by the expert GEMM, stalls the transfer until they free up [48, 62]. Therefore, we instead issue transfers on the GPU’s DMA engines, the dedicated hardware that crosses PCIe with no SM and without waiting for other computation kernels.

Figure 7 describes a single MoE layer under this design. The dispatch and combine communication cross PCIe on the DMA engines, while the expert computation (i.e., grouped GEMM) between them runs on the SMs. On dispatch, each token must reach the GPUs that hold its experts. Our All-Gather realizes this by copying every GPU’s tokens to every other GPU on the DMA engine. Each GPU then groups the tokens by the experts it owns, runs its expert GEMMs, and




Figure 8. (a) Serialized and (b) pipelined bidirectional chunked data transfer over a full-duplex PCIe link.

returns the outputs to token order, a permutation that every grouped MoE performs and that stays local on the SMs. On combine, the DMA engine copies each GPU’s expert outputs back toward the tokens’ owners, and an SM adds the contributions that arrive for each token. This reduction must stay on an SM, since the DMA engine can only move bytes and has no ALUs to sum them [49]. Because the DMA engine carries both transfers as large contiguous regions [38], the SMs remain free to run the expert GEMMs while the bytes are in flight, and an SM is spent only on the combine’s reduction.

In these communications, every GPU sends and receives data at the same time, so both directions of its PCIe link are active together. A PCIe link is full-duplex, so it can carry a send on the upstream lane and a receive on the downstream lane at once. We exploit this by placing outgoing DMA transfers on one stream and incoming transfers on a second, and by splitting each transfer into chunks so that the upload of one chunk overlaps the download of the previous one, as illustrated in Figure 8b. The overlap comes from giving each direction its own execution context, an in-order stream or kernel, since a single context serializes the two directions whether it carries them on a DMA stream or an SM kernel, as in the single stream case of Figure 8a. The DMA engine then earns its place in two ways. It runs the two directions with no SM cost, leaving the processing units free for the expert GEMM, and a single DMA queue is deep enough to saturate its direction on its own, so two streams are enough.

However, NCCL does not reach this overlap on our fabric. It drives a collective from a GPU kernel using SMs, and a barrier within each communication channel forces the send of an internal chunk to complete before its receive begins. The two directions thus alternate chunk by chunk, while multiple channels increase bandwidth rather than overlap




Figure 9. Comparison of the synchronization protocols used by NCCL and the proposed method. (a) NCCL pairs every 4 bytes of data with a 4 byte completion flag. (b) ThunderEP stores completion flags separately from the data and uses a small number of threads to poll them. D denotes data, and F denotes a completion flag.

because each remains subject to the same barrier [16]. The NCCL collective therefore behaves like the serialized single stream transfer of Figure 8a. This behavior is specific to systems without P2P. With P2P a GPU’s peers write their chunks straight into its memory, so its own kernel only sends while the receiving takes care of itself, and the two directions overlap. Without P2P every chunk goes through host memory, so the kernel must both write its own out and read the incoming ones back in, and NCCL’s warp-group barrier orders the two phases rather than issuing them together.

The number of chunks has a trade-off. Too few and the pipeline spends most of its time filling and draining with one lane idle at each end, too many and the per-chunk handoff between the streams costs more than the overlap it buys, so we use the smallest chunk count that keeps both lanes busy through the steady state.

4.4 Efficient Synchronization Strategy

A GPU can read transferred data only after the sender finishes writing it, so every transfer requires a completion signal. Without P2P access, host memory is the only memory region accessible to both GPUs, and the signal must be stored there. Reading this signal requires a PCIe round trip. For large message transfers in prefill, this cost is hidden by the data transfer. However, for small transfers in decode, it can dominate the communication latency.

Figure 9 compares the completion signaling used by NCCL and ThunderEP. NCCL’s LL (Low Latency) protocol pairs every 4 bytes of data with a 4 byte flag, as shown in Figure 9a. An SM writes the data and its associated flag within a single instruction, so observing the flag also confirms that the data has arrived. This design is efficient with P2P access, where the data and flags reside in GPU memory. On consumer GPUs, NCCL stages both in host memory, turning every flag




Figure 10. Fine-grained synchronization policy for the Reduce-Scatter in combine, which mitigates the idle time when senders finish at different times because the router gives each device a different amount of expert work. (a) No receive begins before the last sender finishes. (b) Each begins on its own sender’s completion flag. G_pS_d is GPU p ’s contribution block for shard d , reduced on GPU d .

check into a PCIe round trip. The inline flags also double the space required for a given payload and split the data into small pieces. In addition, NCCL’s LL uses up to 512 threads per channel to check these flags, and an unsuccessful check still fetches the data associated with the flag.

The LL protocol’s inline flag format is not directly compatible with DMA-based transfers. A DMA engine copies a source buffer as laid out and cannot insert flag words between payload elements. Constructing the interleaved layout in advance would require an additional SM packing operation, defeating the purpose of using DMA to avoid SM contention. Even with such a layout, a DMA engine does not guarantee the arrival order of individual lines, so observing a flag would not ensure that its associated data had arrived. ThunderEP therefore keeps the payload contiguous and stores completion flags separately, as shown in Figure 9b. One thread per remote sender polls its flag with uncached loads and pauses between attempts, while the remaining threads wait on a word in GPU memory. Each flag has a single writer, so no atomic operation is required. The main benefit comes not from a faster individual flag check, but from avoiding repeated checks across the $N - 1$ hops of the ring through ThunderEP’s single-step algorithm.

ThunderEP also avoids waiting for all senders before receiving. Figure 10 illustrates this design, using combine as an example. Routing assigns different amounts of expert work to the GPUs, and PCIe contention can further increase the

difference in their completion times. With the global policy in Figure 10a, every GPU waits for the slowest sender. With the per-sender policy in Figure 10b, a GPU begins reading from each sender as soon as its completion flag is available. During combine, a sender also releases each destination’s portion as soon as it is written rather than waiting for its entire output. Transfers from ready senders can therefore proceed while slower senders are still working.

Removing such global synchronization requires preventing a fast sender from overwriting a host buffer that a slower receiver is still reading. ThunderEP alternates between two buffers and reuses a buffer only after the receivers report that they have consumed its previous contents. Receivers send these credits through PCIe writes. Writes do not wait for a response, whereas reads do and saturate earlier, so this notification avoids the more constrained read path. Because each buffer is reused only every other round, the credits normally arrive before it is needed again. This prevents overwrites without delaying the next upload.

These techniques benefit different phases. Separating the flags and limiting the polling threads primarily reduce decode latency because flag checks account for a large fraction of small transfer time. In prefill, this overhead is hidden by the larger data transfer. Per-sender waiting policy is more useful in prefill because the larger expert workload creates enough difference in completion time to overlap receiving with the remaining sends. Decode transfers are too small for this overlap to provide a comparable benefit.

4.5 Integration and Implementation

We integrate ThunderEP into vLLM [26], a state-of-the-art LLM inference engine, by replacing its NCCL-based All-Gather and Reduce-Scatter operations for EP dispatch and combine in both the prefill and decode phases. During decode, vLLM replays the execution with a CUDA graph to reduce launch overhead. ThunderEP alternates between two staging buffers in host memory so that the next communication round can begin while receivers finish reading the previous round, avoiding an additional synchronization between rounds. A captured `cudaMemcpyAsync` operation for a DMA transfer reuses the address recorded at capture time, so alternating buffers would require the host to update the graph before every replay. ThunderEP therefore performs the data transfers of the decode phase on the SMs, where the kernel itself reads the round number from device memory and picks the buffer, leaving the captured graph untouched. Little is lost by doing so, because at decoding batch sizes both the transfers and the expert GEMM are small and the SMs are not a contended resource. The router, expert placement, and computation kernels remain unchanged.

Communication-computation overlap. A prefill step carries enough tokens to pipeline communication and expert computation. Decode transfers only a few kilobytes per

GPU and provides too little work for such a pipeline, so ThunderEP applies overlap only during prefill. The host submits transfers and expert computation on each GPU’s token activations to separate CUDA streams and connects their dependencies with CUDA events. Computation begins on each GPU’s activations as soon as they arrive, while transfers from the remaining GPUs continue. The resulting outputs are returned to that GPU as soon as the computation finishes. Existing device-initiated EP libraries also support communication and computation overlap through hooks or separate send and completion interfaces [2, 32], but they require peer memory that device code can address or a NIC the GPU can drive. In addition, the caller observes completion only for an entire dispatch or combine operation, even when the communication kernel tracks individual peer arrivals internally. ThunderEP instead uses the fine-grained synchronization described in Section 4.4 to expose completion per sender. Computation can therefore begin upon each sender’s completion, without waiting for all senders.

Reduction placement. ThunderEP implements both GPU and partial CPU reduction for Reduce-Scatter, as shown in Figure 6. Partial CPU reduction combines remote partial results in host memory, allowing each GPU to download only a single reduced result and thereby reducing PCIe traffic. However, this reduction accesses the same host memory that serves concurrent GPU DMA transfers. On our systems, the aggregate PCIe bandwidth exceeds the available host DRAM bandwidth, leaving little bandwidth for CPU reduction. The resulting CPU reduction overhead exceeds the time saved by reducing PCIe traffic. We therefore adopt GPU reduction in ThunderEP.

Routing-aware communication. We also implement routing-aware dispatch and combine operation that transfer only the data required by each destination. On consumer GPUs, however, DMA transfers are issued through host APIs, while routing decisions are generated on the GPU. The CPU must therefore retrieve the routing metadata before issuing transfers at every MoE layer, introducing CPU-GPU synchronization [9] and numerous small DMA requests. In our measurements, these overheads offset the reduction in PCIe traffic. GPU-initiated EP libraries [2, 11, 13] avoid host coordination through NVLink or RDMA, which our target systems do not support. During decode, a fixed CUDA graph cannot replay routing-dependent DMA descriptors without host updates. ThunderEP therefore retains All-Gather and Reduce-Scatter and leaves efficient routing-aware All-to-All communication on consumer GPUs to future work.

5 Evaluation

We evaluate the communication and end-to-end performance of the proposed method on two PCIe-only consumer GPU systems. We first evaluate the communication performance

Table 1. System configurations used in our evaluation.

Systems	RTX 4090 system	RTX 5090 system
Mainboard	ASRock Rack GENOAD8X-2T	
CPU	1 × AMD EPYC 9124 (16-Core)	
Main memory	8 × DDR5-4800 32 GB	
GPU	6 × RTX 4090	6 × RTX 5090
GPU memory	24 GB	32 GB
GPU interconnect	PCIe 4.0 ×16	PCIe 5.0 ×16
OS / Kernel	Ubuntu 24.04.3 LTS / Linux 6.8.0-35	
GPU driver	580.65.06 (CUDA 13.0)	

of dispatch and combine, and then measure their impact on end-to-end LLM inference.

5.1 Experimental Environment

System configurations. We conduct the experiments on two single-node PCIe systems equipped with 6 × NVIDIA GeForce RTX 4090 and RTX 5090 GPUs, respectively. In each system, the GPUs are distributed across three PCIe host bridges, with two GPUs attached to each host bridge, while all devices belong to a single NUMA node. Neither system supports GPUDirect P2P access between any pair of GPUs. Consequently, communication between GPUs must be staged through host memory. Table 1 summarizes the details of our system configurations.

Comparison baselines. We use vLLM (v0.27.1) [26] as our primary baseline to evaluate the performance benefit of replacing its default EP communication backend with ThunderEP. vLLM performs MoE dispatch and combine using NCCL All-Gather and Reduce-Scatter, respectively. ThunderEP replaces only this communication path and all other computation kernels and execution settings remain unchanged.

We additionally compare end-to-end inference performance against SGLang (v0.5.18) [65] and Megatron-Core (v0.19.2) [58]. SGLang and Megatron-Core also employ an All-Gather and Reduce-Scatter communication pattern for EP rather than All-to-Allv. For each experiment, all systems use the same numerical precision for computation and communication with identical EP and DP configurations.

To our knowledge, existing EP-specialized communication libraries [2, 3, 11, 35, 40] cannot run on our target systems because they rely on NVLink, GPUDirect P2P, or GPUDirect RDMA. SGLang and Megatron-Core therefore also use NCCL backend for EP communication on our systems. For collective operation-level comparisons, we compare ThunderEP directly against the corresponding NCCL (v2.30.7) [39] primitives using identical message sizes and GPU counts.

Models and Workloads. We evaluate three popular open-weight MoE-based LLMs: Qwen3-30B-A3B [59] and two GPT-OSS models, GPT-OSS-20B and GPT-OSS-120B [1]. We use BF16 for Qwen3-30B-A3B, and use the native MXFP4 checkpoint for GPT-OSS models.




Figure 11. All-Gather performance for token dispatch on a single node (6 GPUs).




Figure 12. Reduce-Scatter performance for token combine on a single node (6 GPUs).

For workloads, we use both synthetic and real-world datasets. We primarily use synthetic prompts to vary prompt lengths and batch sizes, allowing us to comprehensively evaluate prefill and decode across a wide range of workload sizes. To verify that the observed performance trends are not specific to synthetic workloads, we additionally employ prompts sampled from ShareGPT [51] and LMSYS-Chat-1M [64], two widely used real-world LLM conversation datasets. All results report the average of five runs.

5.2 Communication Performance

We report messages from 1KB to 1MB in terms of latency, where startup and synchronization overheads dominate, and messages from 1MB to 1GB in terms of bandwidth, where data movement dominates [17, 22]. The two ranges represent the communication behavior of decode and prefill, respectively. Message size denotes the full array size for each collective operation. We observe consistent performance trends on both the RTX 4090 and RTX 5090 systems.

Dispatch. Figure 11 compares the All-Gather performance for token dispatch. Across the 1KB-1MB range, ThunderEP achieves average latency speedups of 2.30 $\times$ and 2.65 $\times$ on the RTX 4090 and RTX 5090 systems, respectively. The main benefit comes from eliminating the sequential relays of NCCL’s ring algorithm, thereby reducing both PCIe traffic and synchronization latency through pinned host memory. With total 6 GPUs and a per-GPU shard of size S , ThunderEP reduces the analytic PCIe traffic from $10S$ to $6S$, replaces the five steps of ring path with a direct host-staged transfer, and reduces the number of synchronization steps from five with

NCCL’s LL protocol to two. The reduced synchronization count dominates latency for small messages, whereas the lower traffic volume becomes the primary factor for large messages.

The bandwidth advantage persists throughout the 1MB-1GB range. At 1GB, where both implementations have reached their sustained bandwidth, ThunderEP reaches 26.5 GB/s and 35.3 GB/s on the RTX 4090 and RTX 5090 systems, respectively, compared with 20.8 GB/s and 23.0 GB/s for NCCL. In addition to moving 40% fewer bytes, ThunderEP overlaps D2H and H2D transfers on separate DMA streams and uses both directions of the full-duplex PCIe link. NCCL instead serializes the two directions within each ring channel.

Combine. Figure 12 compares the Reduce-Scatter performance for token combine. Across the 1KB-1MB range, ThunderEP achieves average latency speedups of 1.91 $\times$ and 2.14 $\times$ on the RTX 4090 and RTX 5090 systems, respectively. Unlike dispatch operation, NCCL and ThunderEP move the same analytic payload volume during Reduce-Scatter. The latency improvement therefore comes primarily from the shorter dependency chain. ThunderEP transfers its contribution for each destination directly to that destination, whereas NCCL forwards partial outputs around the ring and synchronizes between successive steps. Avoiding these sequential relays reduces synchronization counts through host memory and shortens the critical path for small messages.

The synchronization overhead is amortized as the message size increases. Consequently, ThunderEP and NCCL achieve similar bandwidth for large messages. At 1GB, ThunderEP and NCCL reach 21.0 GB/s and 21.3 GB/s on the RTX 4090



Figure 13. Comparison of prefill performance across different input sequence lengths.




Figure 14. Comparison of decode performance across different batch sizes.

system, and 24.5 GB/s and 23.2 GB/s on the RTX 5090 system. This result also supports the dispatch performance analysis because the bandwidth advantage largely disappears when the analytic traffic volume remains unchanged. The consistent trends across both PCIe-based consumer GPU systems further show that although conventional ring algorithm perform well on systems with direct GPU access, their multi-step relays become a substantial source of overhead when every data must be transferred via a bounce buffer in CPU memory.

5.3 End-to-end Performance

Overall speedup. Figures 13 and 14 compare end-to-end prefill latency and decode throughput on the RTX 5090 system. We include the experimental results for the RTX 4090 system in the supplementary material due to space constraints. For prefill, we use a batch size of 24 and vary the prompt length from 256 to 4K. For decode, we fix the prompt length at 4K and vary the batch size from 6 to 96. We generate 256 output tokens in all runs, which does not affect prefill latency and provides enough decoding steps for a stable throughput measurement.

ThunderEP achieves the lowest prefill latency for every model and prompt length. Compared with vLLM, it provides average speedups of 1.42 $\times$, 1.33 $\times$, and 1.22 $\times$ for Qwen3-30B-A3B, GPT-OSS-20B, and GPT-OSS-120B, respectively, with a maximum speedup of 1.66 $\times$. The smaller speedup for GPT-OSS-120B arises because distributing each shard’s tokens across more local experts increases aggregate padding, partially offsetting the communication gains. Averaged across the tested configurations, ThunderEP achieves prefill speedups




Figure 15. Latency breakdown of a Transformer layer.

of 1.58 $\times$ and 1.59 $\times$ over SGLang and Megatron-Core, respectively.

For decode, ThunderEP improves throughput over vLLM by an average of 1.17 $\times$, 1.12 $\times$, and 1.16 $\times$ for the three models, respectively, reaching up to 1.26 $\times$. Its average throughput speedups over SGLang and Megatron-Core are 1.28 $\times$ and 1.90 $\times$, respectively. Megatron-Core runs out of memory (OOM) on GPT-OSS-120B because it lacks native MXFP4 computation kernels and therefore requires the model weights to be converted to BF16, increasing the memory footprint.

Table 2. Speedup over vLLM with real-world prompts.

Datasets	Synthetic	ShareGPT	LMSYS-Chat-1M
Prefill speedup	1.42×	1.38×	1.38×
Decode speedup	1.16×	1.13×	1.14×

Performance breakdown. Figure 15 shows the forward latency breakdown of a Transformer layer for Qwen3-30B-A3B on the RTX 5090 system, using a batch size of 24 and a prompt length of 4,096. During prefill, ThunderEP’s communication designs reduce communication time compared with NCCL-based vLLM baseline. Overlapping part of the remaining transfers with expert computation provides an additional reduction in exposed latency. Together, ThunderEP reduces the exposed MoE communication latency by 64.4% and the total Transformer layer latency by 38.9%. Only a small fraction of expert computation remains exposed, while attention and other operations remain nearly unchanged.

During decode, compared with vLLM, ThunderEP reduces the exposed MoE communication latency by 50.1%, lowering the Transformer layer latency by 15.2%. Communication and expert computation are not overlapped in decode phase because each GPU processes too few tokens to form an effective pipeline. Dividing these tokens into smaller groups would add kernel launches and synchronization without providing enough computation to hide the transfers. The decode improvement therefore comes primarily from lower communication latency with the proposed single-step algorithm with efficient synchronization strategy.

Real-world datasets. Table 2 summarizes ThunderEP’s average speedup over vLLM for Qwen3-30B-A3B with prompts sampled from real-world LLM conversation datasets [51, 64] on the RTX 5090 system. We truncate them to the target input length and generate the target number of output tokens while ignoring EOS tokens. We use a batch size of 24 and input lengths from 256 to 4K for prefill, and an input length of 4K and batch sizes from 6 to 96 for decode.

ThunderEP achieves a prefill speedup of 1.38× on both datasets and decode speedups of 1.13× and 1.14× on ShareGPT and LMSYS-Chat-1M, respectively. These gains closely match those in the synthetic workload experiments, showing that ThunderEP remains effective with real conversation prompts.

5.4 Ablation Study

Table 3 reports an ablation study of the proposed methods applied in ThunderEP. We run Qwen3-30B-A3B on the RTX 5090 system with an input sequence length of 4K, an output sequence length of 256, and a batch size of 24. Each row adds optimizations to the preceding configuration. We use TTFT metric to measure prefill performance and TPOT to measure decode performance.

Algorithm and synchronization. Replacing NCCL’s ring algorithm with the proposed single-step algorithm improves

Table 3. Ablation study of the proposed method.

Method	TTFT (ms)	TPOT (ms)	Speedup	
			Prefill	Decode
Baseline (vLLM)	2115.9	10.10	1.00×	1.00×
+ Algorithm (§ 4.2) and synchronization (§ 4.4)	1844.7	8.77	1.15×	1.15×
+ DMA transfer (§ 4.3)	1722.8	8.78	1.23×	1.15×
+ DMA-based overlap (§ 4.5)	1436.4	8.78	1.47×	1.15×

prefill performance by 1.15×. Let S denote the amount of input data initially held by each of the N GPUs. NCCL’s ring All-Gather moves $2(N - 1)S$ bytes per GPU, whereas ThunderEP moves NS bytes. At $N = 2$, both algorithms transfer the same amount of data and provide similar performance. With 8 MB of input data per GPU, the speedup grows to 1.26× at $N = 4$ and 1.58× at $N = 6$. Reduce-Scatter moves the same analytic volume in both implementations, although ThunderEP removes the sequential relays of the ring.

Combining the single-step algorithm with ThunderEP’s synchronization scheme gives a 1.15× decode speedup over vLLM. Each data transfer in decode phase carries only a small message, so synchronization rather than data movement dominates its latency. On six GPUs, the single-step path reduces the number of completion checks from five to two compared with NCCL’s multi-step ring.

DMA transfer and computation overlap. Using the DMA engines provides a further 1.07× improvement in prefill performance. DMA and SM transfers provide similar bandwidth when executed alone. ThunderEP’s DMA path improves performance because the transfers no longer share the SMs with the polling kernels that wait on peers.

Overlapping communication with expert computation adds another 1.20× improvement and raises the overall prefill speedup to 1.47×. The fine-grained synchronization described in Section 4.4 makes each GPU’s shard available independently. Computation on its tokens can begin as soon as the shard arrives, while transfers from other GPUs continue. Using the DMA engines prevents these remaining transfers from competing with the expert GEMMs for SM resources.

On consumer GPUs, where EP communication libraries such as DeepEP cannot operate, vLLM invokes NCCL through PyTorch’s `torch.distributed` interface and schedules expert computation only after each collective completes, providing no communication-computation overlap. To isolate the benefit of ThunderEP’s fine-grained synchronization, we modify vLLM to provide such overlap using the same number of pipeline units as ThunderEP. The modified baseline invokes NCCL collectives using `async_op` and delays each wait until its output is needed, allowing communication for a later unit to overlap with computation for an earlier one. Even with this added overlap, ThunderEP achieves a 1.24× prefill speedup compared to the modified vLLM baseline. NCCL exposes each collective’s output only after data

from every rank has arrived, whereas ThunderEP can begin computation as soon as data from each sender arrives.

6 Conclusion

We introduce ThunderEP, a communication design for MoE inference on PCIe-based consumer GPU systems without P2P access. ThunderEP treats host memory as a shared communication medium rather than simply a staging buffer between GPUs. Its single-step All-Gather and Reduce-Scatter algorithms remove repeated PCIe relays, DMA engine transfers keep bulk data movement from competing with expert computation for SM resources, and fine-grained synchronization avoids waiting for unrelated GPUs. Across two PCIe systems equipped with two recent generations of consumer GPUs, ThunderEP improves dispatch and combine communication performance over NCCL by $2.00\times$ and $1.53\times$, respectively. For end-to-end inference, ThunderEP reduces prefill latency by up to $1.66\times$ and increases decode throughput by up to $1.26\times$ over vLLM, a state-of-the-art LLM serving engine. By addressing the communication bottlenecks specific to consumer GPUs, ThunderEP broadens the range of systems on which large MoE models can be served efficiently.

Acknowledgments

This work was partially supported by the National Research Foundation of Korea (NRF) under Grant No. RS-2023-00222663 (Center for Optimizing Hyperscale AI Models and Platforms) and under Grant No. A400-20260031, and by the Institute for Information and Communications Technology Promotion (IITP) under Grant No. 2018-0-00581 (CUDA Programming Environment for FPGA Clusters) and No. RS-2025-02304554 (Efficient and Scalable Framework for AI Heterogeneous Cluster Systems), all funded by the Ministry of Science and ICT (MSIT) of Korea. It was also partially supported by the Korea Health Industry Development Institute (KHIDI) under Grant No. RS-2025-25454559 (Frailty Risk Assessment and Intervention Leveraging Multimodal Intelligence for Networked Deployment in Community Care), funded by the Ministry of Health and Welfare (MOHW) of Korea. Additional support was provided by the BK21 Plus Program for Innovative Data Science Talent Education (Department of Data Science, Seoul National University, No. 5199990914569) and the BK21 FOUR Program for Intelligent Computing (Department of Computer Science and Engineering, Seoul National University, No. 4199990214639), both funded by the Ministry of Education (MOE) of Korea. This work was also partially supported by the Advanced GPU Utilization Support Program, funded by the Ministry of Science and ICT (MSIT) of Korea and operated by the National IT Industry Promotion Agency (NIPA). Research facilities were provided by the Institute of Computer Technology (ICT) at Seoul National University.

References

- [1] Sandhini Agarwal, Lama Ahmad, Jason Ai, Sam Altman, Andy Applebaum, Edwin Arbus, Rahul K Arora, Yu Bai, Bowen Baker, Haiming Bao, et al. 2025. gpt-oss-120b & gpt-oss-20b model card. *arXiv preprint arXiv:2508.10925* (2025).
- [2] DeepSeek AI. 2025. DeepEP. <https://github.com/deepseek-ai/DeepEP>
- [3] Perplexity AI. 2025. pplx-kernels. <https://github.com/perplexityai/pplx-kernels>
- [4] Wei An, Xiao Bi, Guanting Chen, Shanhuang Chen, Chengqi Deng, Honghui Ding, Kai Dong, Qiushi Du, Wenjun Gao, Kang Guan, et al. 2024. Fire-flyer AI-HPC: A cost-effective software-hardware co-design for deep learning. In *SC24: International Conference for High Performance Computing, Networking, Storage and Analysis*. IEEE, 1–23.
- [5] Alexander Borzunov, Dmitry Baranchuk, Tim Dettmers, Maksim Ribinin, Younes Belkada, Artem Chumachenko, Pavel Samygin, and Colin Raffel. 2023. Petals: Collaborative inference and fine-tuning of large models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations)*. 558–568.
- [6] Weilin Cai, Juyong Jiang, Le Qin, Junwei Cui, Sunghun Kim, and Jiayi Huang. 2024. Shortcut-connected expert parallelism for accelerating mixture-of-experts. *arXiv preprint arXiv:2404.05019* (2024).
- [7] Li-Wen Chang, Wenlei Bao, Qi Hou, Chengquan Jiang, Ningxin Zheng, Yinmin Zhong, Xuanrun Zhang, Zuquan Song, Chengji Yao, Ziheng Jiang, et al. 2024. Flux: Fast software-based communication overlap on gpus through kernel fusion. *arXiv preprint arXiv:2406.06858* (2024).
- [8] Chang Chen, Min Li, Zhihua Wu, Dianhai Yu, and Chao Yang. 2022. Tamoe: Topology-aware large scale mixture-of-expert training. *Advances in Neural Information Processing Systems* 35 (2022), 22173–22186.
- [9] Rachit Garg and Matthew Nicely. 2026. Boosting MoE Training Throughput with Advanced Fusion Kernels. NVIDIA Technical Blog. <https://developer.nvidia.com/blog/boosting-moe-training-throughput-with-advanced-fusion-kernels/>
- [10] GGML. 2023. llama.cpp. <https://github.com/ggml-org/llama.cpp>
- [11] Amos Goldman, Nimrod Boker, Maayan Sheraizin, Nimrod Admoni, Artem Polyakov, Subhadeep Bhattacharya, Fan Yu, Kai Sun, Georgios Theodorakis, Hsin-Chun Yin, et al. 2026. NCCL EP: Towards a Unified Expert Parallel Communication API for NCCL. *arXiv preprint arXiv:2603.13606* (2026).
- [12] Wentao Guo, Mayank Mishra, Xinle Cheng, Ion Stoica, and Tri Dao. 2026. Sonimoe: Accelerating moe with io and tile-aware optimizations. In *International Conference on Learning Representations*, Vol. 2026. 67814–67839.
- [13] Khaled Hamidouche, John Bachan, Pak Markthub, Peter-Jan Gootzen, Elena Agostini, Sylvain Jeaugey, Aamir Shafi, Georgios Theodorakis, and Manjunath Gorentla Venkata. 2025. GPU-initiated networking for NCCL. *arXiv preprint arXiv:2511.15076* (2025).
- [14] Sarah-Michelle Hammer, Stefan Schmid, Rachee Singh, and Vamsi Addanki. 2025. Short-circuiting Rings for Low-Latency AllReduce. *arXiv preprint arXiv:2510.03491* (2025).
- [15] Jiaao He, Jidong Zhai, Tiago Antunes, Haojie Wang, Fuwen Luo, Shangfeng Shi, and Qin Li. 2022. Fastermoe: modeling and optimizing training of large-scale dynamic pre-trained models. In *Proceedings of the 27th ACM SIGPLAN Symposium on Principles and Practice of Parallel Programming*. 120–134.
- [16] Zhiyi Hu, Siyuan Shen, Tommaso Bonato, Sylvain Jeaugey, Cedell Alexander, Eric Spada, James Dinan, Jeff Hammond, and Torsten Hoefler. 2025. Demystifying NCCL: An in-depth analysis of GPU communication protocols and algorithms. In *2025 IEEE Symposium on High-Performance Interconnects (HOTI)*. IEEE, 48–59.
- [17] Changho Hwang, Peng Cheng, Roshan Dathathri, Abhinav Jangda, Saeed Maleki, Madan Musuvathi, Olli Saarikivi, Aashaka Shah, Ziyue Yang, Binyang Li, et al. 2026. MSCCL++: Rethinking GPU communication abstractions for AI inference. In *Proceedings of the 31st ACM*

- International Conference on Architectural Support for Programming Languages and Operating Systems, Volume 2*. 1201–1215.
- [18] Changho Hwang, Wei Cui, Yifan Xiong, Ziyue Yang, Ze Liu, Han Hu, Zilong Wang, Rafael Salas, Jithin Jose, Prabhat Ram, et al. 2023. Tutel: Adaptive mixture-of-experts at scale. *Proceedings of Machine Learning and Systems* 5 (2023), 269–287.
 - [19] Robert A Jacobs, Michael I Jordan, Steven J Nowlan, and Geoffrey E Hinton. 1991. Adaptive mixtures of local experts. *Neural computation* 3, 1 (1991), 79–87.
 - [20] Albert Q Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Emma Bou Hanna, Florian Bressand, et al. 2024. Mixtral of experts. *arXiv preprint arXiv:2401.04088* (2024).
 - [21] Chao Jin, Ziheng Jiang, Zhihao Bai, Zheng Zhong, Juncai Liu, Xiang Li, Ningxin Zheng, Xi Wang, Cong Xie, Qi Huang, et al. 2026. Megascallmoe: Large-scale communication-efficient training of mixture-of-experts models in production. In *Proceedings of the 21st European Conference on Computer Systems*. 366–382.
 - [22] Heehoon Kim, Jaehwan Lee, Taejeoung Kim, Jongwon Park, Jinpyo Kim, Pyongwon Suh, Ryan H Choi, Sangwoo Lee, and Jaejin Lee. 2026. HetCCL: Accelerating LLM Training with Heterogeneous GPUs. *arXiv preprint arXiv:2601.22585* (2026).
 - [23] Heehoon Kim, Junyeol Ryu, and Jaejin Lee. 2024. Tccl: Discovering better communication paths for pci gpu clusters. In *Proceedings of the 29th ACM International Conference on Architectural Support for Programming Languages and Operating Systems, Volume 3*. 999–1015.
 - [24] Jonathan Knoop and Hendrik Holtmann. 2026. Private llm inference on consumer blackwell gpus: A practical guide for cost-effective local deployment in smes. *arXiv preprint arXiv:2601.09527* (2026).
 - [25] Jakub Krajewski, Jan Ludziejewski, Kamil Adamczewski, Maciej Pióro, Michał Krutul, Szymon Antoniak, Kamil Ciebia, Krystian Król, Tomasz Odrzygóźdź, Piotr Sankowski, et al. 2024. Scaling laws for fine-grained mixture of experts. *arXiv preprint arXiv:2402.07871* (2024).
 - [26] Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 29th symposium on operating systems principles*. 611–626.
 - [27] Yiran Lei, Dongjoo Lee, Liangyu Zhao, Daniar Kurniawan, Chanmyeong Kim, Heetaek Jeong, Changsu Kim, Hyeonseong Choi, Liangcheng Yu, Arvind Krishnamurthy, et al. 2026. {FAST}: An Efficient Scheduler for {All-to-All}{GPU} Communication. In *23rd USENIX Symposium on Networked Systems Design and Implementation (NSDI 26)*. 2515–2531.
 - [28] Jiamin Li, Yimin Jiang, Yibo Zhu, Cong Wang, and Hong Xu. 2023. Accelerating distributed {MoE} training and inference with lina. In *2023 USENIX Annual Technical Conference (USENIX ATC 23)*. 945–959.
 - [29] Wanchao Liang, Tianyu Liu, Less Wright, Will Constable, Andrew Gu, Chien-Chin Huang, Iris Zhang, Wei Feng, Howard Huang, Junjie Wang, et al. 2025. TorchTitan: One-stop pytorch native solution for production ready LLM pretraining. In *International Conference on Learning Representations*, Vol. 2025. 92161–92181.
 - [30] Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, et al. 2024. Deepseek-v3 technical report. *arXiv preprint arXiv:2412.19437* (2024).
 - [31] Yijun Ma, Siyuan Shen, Tiancheng Chen, Akhil Langer, Jiri Kraus, Benjamin Glick, Craig Belusar, Jeff Hammond, and Torsten Hoefler. 2026. Demystifying NVSHMEM: A System-Level Analysis on Symmetric Memory and Device-Initiated Operations in GPU Communication. *arXiv preprint arXiv:2606.05951* (2026).
 - [32] Ziming Mao, Yihan Zhang, Chihan Cui, Zhen Huang, Kaichao You, Zhongjie Chen, Zhiying Xu, Zhenyu Gu, Scott Shenker, Costin Raiciu, et al. 2025. UCCL-EP: Portable Expert-Parallel Communication. *arXiv preprint arXiv:2512.19849* (2025).
 - [33] Xiaonan Nie, Pinxue Zhao, Xupeng Miao, Tong Zhao, and Bin Cui. 2022. HetuMoE: An efficient trillion-scale mixture-of-expert distributed training system. *arXiv preprint arXiv:2203.14685* (2022).
 - [34] NVIDIA. 2023. TensorRT-LLM. <https://github.com/NVIDIA/TensorRT-LLM>
 - [35] NVIDIA. 2025. Hybrid-EP. <https://github.com/deepseek-ai/DeepEP/tree/hybrid-ep>
 - [36] NVIDIA. 2025. NVIDIA NCCL 2.28. NVIDIA Technical Blog. <https://developer.nvidia.com/blog/fusing-communication-and-compute-with-new-device-api-and-copy-engine-collectives-in-nvidia-nccl-2-28/>
 - [37] NVIDIA. 2026. CUDA C++ Best Practices Guide. <https://docs.nvidia.com/cuda/cuda-c-best-practices-guide/index.html#data-transfer-between-host-and-device>
 - [38] NVIDIA. 2026. CUDA C++ Best Practices Guide. <https://docs.nvidia.com/cuda/cuda-c-best-practices-guide/index.html>
 - [39] NVIDIA. 2026. NCCL. <https://github.com/NVIDIA/nccl>
 - [40] NVIDIA. 2026. NIXL. <https://github.com/ai-dynamo/nixl>
 - [41] NVIDIA. 2026. NVIDIA GPUDirect. <https://developer.nvidia.com/gpudirect>
 - [42] NVIDIA. 2026. NVLink. <https://www.nvidia.com/en-us/data-center/nvlink>
 - [43] Shagnik Pal, Shaizeen Aga, Suchita Pati, Mahzabeen Islam, and Lizy K John. 2025. Design Space Exploration of DMA based Finer-Grain Compute Communication Overlap. *arXiv preprint arXiv:2512.10236* (2025).
 - [44] Suchita Pati, Shaizeen Aga, Mahzabeen Islam, Nuwan Jayasena, and Matthew D Sinclair. 2024. T3: Transparent tracking & triggering for fine-grained overlap of compute & collectives. In *Proceedings of the 29th ACM International Conference on Architectural Support for Programming Languages and Operating Systems, Volume 2*. 1146–1164.
 - [45] Zihan Qiu, Zekun Wang, Xiao Li, Yanpeng Li, Yang Xu, Yixuan Wang, Huaqing Zhang, Rui Men, Bochao Mao, Chengruidong Zhang, et al. 2026. On the Design of Qwen3. 8-Next Architecture: Evaluation, Efficiency, and Training Stability. *arXiv preprint arXiv:2608.30320* (2026).
 - [46] Samyam Rajbhandari, Conglong Li, Zhewei Yao, Minjia Zhang, Reza Yazdani Aminabadi, Ammar Ahmad Awan, Jeff Rasley, and Yuxiong He. 2022. DeepSpeed-MoE: Advancing mixture-of-experts inference and training to power next-generation ai scale. In *International conference on machine learning*. PMLR, 18332–18346.
 - [47] Samyam Rajbhandari, Jeff Rasley, Olatunji Ruwase, and Yuxiong He. 2020. Zero: Memory optimizations toward training trillion parameter models. In *SC20: international conference for high performance computing, networking, storage and analysis*. IEEE, 1–16.
 - [48] Saeed Rashidi, Matthew Denton, Srinivas Sridharan, Sudarshan Srinivasan, Amoghavarsha Suresh, Jade Nie, and Tushar Krishna. 2021. Enabling compute-communication overlap in distributed deep learning training platforms. In *2021 ACM/IEEE 48th Annual International Symposium on Computer Architecture (ISCA)*. IEEE, 540–553.
 - [49] Erik Schultheis and Dan Alistarh. 2026. LLMQ: Efficient Lower-Precision LLM Training for Consumer GPUs. In *The Third Conference on Parsimony and Learning (Proceedings Track)*.
 - [50] SGLang. 2025. Two-Batch Overlap. <https://sgl-project-sglang-93.mintlify.app/distributed/expert-parallelism#two-batch-overlap-tbo>
 - [51] ShareGPT Team. 2023. ShareGPT. <https://sharegpt.com/>
 - [52] Noam Shazeer, Azalia Mirhoseini, Krzysztof Maziarz, Andy Davis, Quoc Le, Geoffrey Hinton, and Jeff Dean. 2017. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. *arXiv preprint arXiv:1701.06538* (2017).
 - [53] Shaohuai Shi, Xinglin Pan, Qiang Wang, Chengjian Liu, Xiaozhe Ren, Zhongzhe Hu, Yu Yang, Bo Li, and Xiaowen Chu. 2024. Schemoe: An extensible mixture-of-experts distributed training system with tasks

- scheduling. In *Proceedings of the Nineteenth European Conference on Computer Systems*. 236–249.
- [54] Yixin Song, Zeyu Mi, Haotong Xie, and Haibo Chen. 2024. PowerInfer: Fast large language model serving with a consumer-grade gpu. In *Proceedings of the ACM SIGOPS 30th Symposium on Operating Systems Principles*. 590–606.
 - [55] Kimi Team, Tongtong Bai, Yifan Bai, Yiping Bao, Jianfeng Cai, Xinyuan Cai, Peizhou Cao, Yuxuan Cao, Ziwei Chai, Y Charles, et al. 2026. Kimi K3: Open frontier intelligence. *arXiv preprint arXiv:2607.24653* (2026).
 - [56] vLLM. 2026. Dual Batch Overlap. <https://docs.vllm.ai/en/latest/design/dbo/>
 - [57] Anyi Xu, B Li, Bangcai Lin, Bing Xue, BingCheng Xian, Bingzheng Xu, Bochao Wu, Bowei Zhang, Boyi Deng, CC Yu, et al. 2026. DeepSeek-V4.1-Flash: Pushing the Limits of KV Cache Compression. *arXiv preprint arXiv:2609.19969* (2026).
 - [58] Zijie Yan, Hongxiao Bai, Xin Yao, Dennis Liu, Tong Liu, Hongbin Liu, Pingtian Li, Evan Wu, Shiqing Fan, Li Tao, et al. 2026. Scalable training of mixture-of-experts models with megatron core. *arXiv preprint arXiv:2603.07685* (2026).
 - [59] An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388* (2025).
 - [60] Jinghan Yao, Quentin Anthony, Aamir Shafi, Hari Subramoni, and Dhabaleswar K DK Panda. 2024. Exploiting inter-layer expert affinity for accelerating mixture-of-experts model inference. In *2024 IEEE International parallel and distributed processing symposium (IPDPS)*. IEEE, 915–925.
 - [61] Aohan Zeng, Xin Lv, Zhenyu Hou, Zhengxiao Du, Qinkai Zheng, Bin Chen, Da Yin, Chendi Ge, Chenghua Huang, Chengxing Xie, et al. 2026. Glm-5: from vibe coding to agentic engineering. *arXiv preprint arXiv:2602.15763* (2026).
 - [62] Mingjun Zhang, Xiaohe Hu, Menghao Zhang, Ziteng Chen, Yanmin Jia, Yan Zhang, Da Liu, Qing Chen, Fangzheng Jiao, Jun Chen, et al. 2025. An Efficient, Reliable and Observable Collective Communication Library in Large-scale GPU Training Clusters. *arXiv preprint arXiv:2510.00991* (2025).
 - [63] Shulai Zhang, Ningxin Zheng, Haibin Lin, Ziheng Jiang, Wenlei Bao, Chengquan Jiang, Qi Hou, Weihao Cui, Size Zheng, Li-Wen Chang, et al. 2025. Comet: Fine-grained computation-communication overlapping for mixture-of-experts. *Proceedings of Machine Learning and Systems* 7 (2025).
 - [64] Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Tianle Li, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zhuohan Li, Zi Lin, Eric Xing, et al. 2024. Lmsys-chat-1m: A large-scale real-world llm conversation dataset. In *International Conference on Learning Representations*, Vol. 2024. 22225–22257.
 - [65] Lianmin Zheng, Liangsheng Yin, Zhiqiang Xie, Chuyue Sun, Jeff Huang, Cody H Yu, Shiyi Cao, Christos Kozyrakis, Ion Stoica, Joseph E Gonzalez, et al. 2024. Sglang: Efficient execution of structured language model programs. *Advances in neural information processing systems* 37 (2024), 62557–62583.

A Additional Results




Figure 16. Comparison of prefill performance across different input sequence lengths on the RTX 4090 system. We use a batch size of 24 and 256 output tokens, and vary the prompt length from 256 to 4K. We exclude GPT-OSS-120B since all baselines run GPU OOM.




Figure 17. Comparison of decode performance across different batch sizes on the RTX 4090 system. We use a prompt length of 4K and 256 output tokens, and vary the batch size from 6 to 96. We exclude GPT-OSS-120B since all baselines run GPU OOM.