Drift Says When, Budget Says How Much: Rate-Controlled KV Re-selection for Long-Form Multimodal Generation

Bin Hu
Tsinghua University

Yingbo Xiao
The Chinese University of Hong Kong, Shenzhen

arXiv:2610.31433v1 [cs.LG] 22 Oct 2026

Abstract

KV cache compression for multimodal LLMs usually selects the visual tokens to keep once, at prefill, and reuses that selection for the whole generation. We show that this one-shot selection is severely limited on long-form generation: on detailed image description, even an oracle that selects with the attention of the uncompressed answer reaches only 0.44–0.52 ROUGE-L agreement with the uncompressed output at 32 retained prefix tokens per head, because the evidence the model reads moves as the description unfolds. Re-selecting whenever attention *drifts* out of the kept set is the natural remedy, but we find that a fixed drift threshold fails systematically: drift magnitudes are not comparable across samples, so low-drift samples are almost never refreshed although they benefit the most. We propose **Rate-Controlled Refresh** (RCR), which lets drift decide *when* and *where* to re-select while a per-sample controller regulates *how often*, combined with a low-rank drift detector, candidate-restricted re-selection, and a decision that stays on the GPU. With one setting for all models and tasks, RCR outperforms the per-step retrieval method InfiniGen by 1.6–3.8 ROUGE-L points on five of six model–task settings with no significant difference on the sixth, while staying within 1.7 points of exact per-step re-selection, with comparable estimated data movement per step and a 4× smaller GPU-resident detector. On DetailCaps, drift-chosen timing beats random timing at the same refresh rate and periodic timing even at a higher rate, by 2.0–5.0 points; the advantage over InfiniGen is largest at tight budgets and shrinks as the budget grows. On pre-registered video description, where drift is homogeneous across samples, RCR is on par with InfiniGen on Qwen2-VL and exceeds it on Qwen3-VL but no longer beats a fixed threshold at the nearest tested rates, consistent with the diagnosis; object-level evaluation shows that RCR achieves higher object F1 against the uncompressed output than InfiniGen on two of three models.

1 Introduction

The KV cache of a multimodal large language model (MLLM) is dominated by visual tokens: in our long-form benchmarks the prefix holds 640–2,300 tokens per sample, almost all of them image patches. Prefill-time eviction methods such as SnapKV (Li et al., 2024), PyramidKV (Cai et al., 2024), Ada-KV (Feng et al., 2025) and the multimodal BACON (Chen et al., 2026) score prefix tokens with the attention of an observation window and keep only the top few. On visual question answering one-shot selection can be close to lossless: with 64 KV entries per head, an oracle that scores with the true answer's attention matches the uncompressed model on TextVQA and DocVQA.

Long-form generation is different. On detailed captioning (DetailCaps; Dong et al., 2024) better scoring helps but cannot close the gap: even the answer-attention oracle keeps only 0.44–0.52 ROUGE-L agreement with the uncompressed output (§3). The reason is that attention *moves*: as the model describes the skateboarder, then the ramp, then the trash bin (Figure 1), the evidence it needs leaves the set chosen at prefill. With 32 slots per head, even an oracle-scored one-shot selection falls well short.

A natural remedy is to keep the full KV off the GPU and re-select whenever the attention mass on evicted tokens, which we call *drift*, exceeds a threshold. This already beats periodic refresh at equal refresh rates (Appendix D), yet it trails InfiniGen (Lee et al., 2024), which re-selects at every step, by 1.9 points on Qwen2-VL DetailCaps. A per-sample analysis (§4) shows where the gap comes from: on high-drift samples the threshold rule already matches exact per-step re-selection, but on low-drift samples it refreshes 1% of the time while exact re-selection would gain 30 points over

BACON. Drift tells *when* within a sample, but its magnitude is not comparable *across* samples.

We therefore decouple the two decisions. RCR keeps drift as the signal for when and in which layer to re-select, but adapts the threshold online per sample so that a target fraction ρ of layer-steps refresh. Three further components make refreshing accurate and cheap: drift is estimated from 8 SVD-rotated key channels, re-selection scores exactly only the detector's top candidates, and the trigger decision never leaves the GPU. Our contributions are:

- We quantify the limits of one-shot selection on long-form multimodal generation across three MLLMs (§3).
- We identify why fixed drift thresholds fail: the gap to per-step retrieval comes almost entirely from low-drift samples (§4); on video, where almost no sample is starved, the advantage of rate control over a fixed threshold disappears, consistent with this diagnosis.
- We propose RCR, which separates *when* (drift) from *how much* (a per-sample rate budget). One configuration outperforms InfiniGen on five of six model–task settings with no significant difference on the sixth, at comparable CPU traffic; with everything else fixed, drift-chosen timing beats random timing at the same rate and periodic timing even at a higher rate by 2.0–5.0 points (§6).
- We follow a develop-then-confirm protocol: components were chosen on a 100-sample development split and confirmed on held-out data under a pre-registered decision rule (Appendix A).

2 Related Work

One-shot KV eviction. H2O (Zhang et al., 2023) and Scissorhands (Liu et al., 2023) keep heavy hitters under a persistence-of-importance assumption; SnapKV (Li et al., 2024) votes with an observation window, and PyramidKV (Cai et al., 2024), AdaKV (Feng et al., 2025), HeadKV (Fu et al., 2025) and CAKE (Qin et al., 2025) redistribute budgets across layers and heads. Multimodal variants exploit modality structure (Wan et al., 2024; Liu et al., 2024c; Tu et al., 2025; Wan et al., 2025; Huang et al., 2025; Li et al., 2025; Wang et al., 2025a; Liu et al., 2026); BACON (Chen et al., 2026) is a strong low-budget selector that we use at prefill. Look-ahead methods (Wang et al., 2025b; Galim et al., 2026; Ahn et al., 2026) estimate future queries before a single eviction. All of them select once; we show this limits long-form fidelity even with oracle scores. Visual token reduction prunes or merges image tokens inside the model (Chen et al., 2024a; Zhang et al., 2025b; Xing et al., 2025; Yang et al., 2025b), with dynamic or recoverable variants for generation (Liang et al., 2025; Yang et al., 2026); these change the computation itself and are complementary to KV selection. For long outputs, several methods keep updating a compressed cache as text is generated (Wu et al., 2025; Ghadia et al., 2025; Liao et al., 2025; Zhang et al., 2025a; Cai et al., 2025); RCR instead re-selects among all prefix tokens from a full copy, so visual evidence evicted earlier can return.

Decode-time retrieval. Another line keeps the full KV (often offloaded) and retrieves a subset at every step: Quest (Tang et al., 2024) bounds page scores with channel-wise key extrema, ArkVale (Chen et al., 2024b) recalls pages by bounding-sphere digests, and InfiniGen (Lee et al., 2024) speculates attention from a few SVD-skewed key channels; related designs use low-rank keys, approximate nearest neighbours or hashing (Ribar et al., 2024; Singhania et al., 2024; Liu et al., 2024a; Chen et al., 2025; Sun et al., 2025a; Jie et al., 2025), share selections across layers (Yang et al., 2025a; Hao et al., 2025), or filter coarse-to-fine (Behnam et al., 2025). Twilight (Lin et al., 2025) replaces fixed top-k budgets with top-p pruning, and ParisKV (Qi et al., 2026) makes retrieval robust to query drift; both target per-step sparse attention rather than deciding when to re-select. RCR borrows InfiniGen's skewing for its detector and coarse-to-fine filtering for re-selection, but retrieves only on a budgeted fraction of layer-steps chosen by drift.

Deciding when to recompute. ReSA (Sun et al., 2025b), Tactic (Zhu et al., 2025) and RefreshKV (Xu et al., 2024) recompute at fixed intervals; dynamic variants trigger on query similarity (Xu et al., 2024; Yao et al., 2026), and DSTP (Kim et al., 2026) triggers when the attention distribution over kept visual tokens departs from a prefill anchor. All use fixed thresholds. Our trigger signal is the attention mass on evicted tokens, which directly bounds the eviction error (Feng et al., 2025; Shi and Gu, 2026) and is the online counter-



Figure 1: Illustration (not measured). While describing the image, attention moves from the skateboarder to the ramp and the trash bin. Drift d_t, the attention mass on evicted prefix tokens, stays low most of the time; when it crosses the threshold, the current query re-selects tokens from the full KV kept on the CPU and overwrites the GPU cache. In RCR the threshold is adapted online per sample so that a fraction ρ of layer-steps refresh.

DetailCaps fidelity	Qwen2	LLaVA	Qwen3
SnapKV	.389	.362	–
BACON	.388	.371	.409
Last-query	.367	.386	–
Look-ahead 8 steps	.448	.412	–
Prefill oracle (answer attn.)	.516	.440	.507
Exact re-selection every step	.613	.478	.571

Table 1: One-shot selection falls short on long descriptions even with oracle scores; re-selecting during decoding is not. –: not run.

part of QEvict's offline Future Missed Mass (Garg et al., 2026); our analysis shows that its threshold must adapt per sample.

3 The Limits of One-Shot Selection

Setup. We use Qwen2-VL-7B-Instruct (Wang et al., 2024), LLaVA-NeXT-Mistral-7B (Liu et al., 2024b) and Qwen3-VL-8B-Instruct (Bai et al., 2025) with FlashAttention-2. The budget is 64 KV entries per KV head: $c = 32$ selected prefix tokens plus the last $W = 32$ observation-window tokens; generated tokens are appended. Tasks are TextCaps (Sidorov et al., 2020) (500 validation images, one-sentence captions, $\leq$64 new tokens) and DetailCaps (Dong et al., 2024) (300 images, median 157–238 words, $\leq$512 new tokens). All runs use greedy decoding (details in Appendix M). Our metric is **fidelity**: ROUGE-L F1 between the compressed and the uncompressed output, which isolates the deviation caused by compression; confidence intervals are paired bootstrap 95%. Reference-based CIDEr and ROUGE-L separate one-shot from dynamic methods but not dynamic methods from each other (§6, Appendix H).

Better scoring is not enough. Table 1 compares one-shot selectors on DetailCaps. SnapKV, BACON and last-query scoring differ by at most 2.4 points; selecting with the attention of the first 8 answer tokens (decoded with full KV) adds 4–6 points over BACON, and even the prefill oracle, which scores with the uncompressed answer's own attention, stays at .44–.52. Re-selecting at every decoding step with the current query reaches .48–.61. On short-answer VQA the picture is the opposite: the prefill oracle loses no accuracy (Qwen2 TextVQA (Singh et al., 2019) .851 vs. .848 uncompressed; similarly on DocVQA (Mathew et al., 2021)), so the gap there is one of scoring. In long-form generation, we attribute the gap that remains even under oracle scoring to the *staleness* of the selection. Attention trajectories confirm this: the most-attended prefix position stays the same between adjacent steps only 41% (Qwen2) to 80% (LLaVA) of the time, and 37–44% of newly attended evidence in LLaVA lies far from all previous evidence.

4 Drift and Why Fixed Thresholds Fail

Drift. Let $\mathcal{S}_{l,h}$ be the c prefix tokens kept for KV head h of layer l, and $a_{t,j}$ the attention of step t on prefix token j, averaged over the query heads of the GQA group and normalised over the full prefix plus the rest of the cache. Drift is the attention mass the model would put on evicted prefix tokens,

$$d_{l,h}(t) = \sum_{j \notin \mathcal{S}_{l,h}} a_{t,j}, \quad d_l(t) = \frac{1}{H_{kv}} \sum_h d_{l,h}(t). \tag{1}$$

A *fixed-threshold* refresh re-selects layer l whenever an estimate $\hat{d}_l(t)$ exceeds τ, using the cur-



Figure 2: Qwen2-VL DetailCaps split into terciles by each sample's mean drift under the fixed threshold ($\tau = 0.03$). Numbers above bars are refresh rates. The fixed threshold matches exact re-selection on high-drift samples but starves low-drift ones; RCR closes this gap.

rent query's exact attention over the full prefix. With a cheap page-mean estimator (keys averaged over 16-token pages) this rule beats periodic refresh by 3.0–4.2 points at equal refresh rates on Qwen2-VL and LLaVA, but it needs a per-setting $\tau \in [0.02, 0.15]$ and trails InfiniGen on Qwen2-VL DetailCaps (.551 vs. .570).

Where the gap comes from. Figure 2 splits the 300 Qwen2-VL DetailCaps samples into terciles by their mean drift under $\tau = 0.03$. On **high-drift** samples the fixed threshold refreshes 35% of layer-steps and already matches exact per-step re-selection (.479 vs. .484), ahead of InfiniGen (.442). On **low-drift** samples it refreshes only 1% of the time, yet these samples gain the most from refreshing (BACON .462, exact .763), and InfiniGen leads by 16 points. Across samples, the gap to InfiniGen is unrelated to output length (Spearman -0.01) but clearly related to mean drift (-0.41; Appendix E). Normalising drift by the total prefix attention does not help: the two quantities have a sample-level rank correlation of 0.98. In low-drift samples little attention reaches evicted tokens, but that little matters.

Takeaway. Within a sample, drift is a good signal of *when* attention has moved; across samples its magnitude does not reflect how valuable a refresh is. A single threshold therefore cannot allocate refreshes well, which motivates controlling the refresh budget per sample.

5 Rate-Controlled Refresh

Cache layout. Prefill selects $\mathcal{S}_{l,h}$ with BACON. The full prefix KV (N_p tokens) is kept aside (in CPU memory in a deployment), and the GPU cache is laid out as [c selected | W window | generated]. A refresh overwrites only the first c slots; keys carry RoPE already, so no re-encoding is needed.

Per-sample rate control. RCR (Algorithm 1 in Figure 3) maintains one threshold τ per sample, shared by all layers and initialised to $\tau_0 = 0.03$. After layer l checks step t and refreshes a share $f \in [0, 1]$ of its heads, the threshold is updated multiplicatively,

$$\tau \leftarrow \tau \cdot \exp\big(\eta\,(f - \rho)\big), \qquad \eta = 0.05, \qquad (2)$$

a constant-gain Robbins–Monro step in $\log \tau$ that is stationary only when the trigger probability equals ρ, i.e. it tracks the slowly changing $(1-\rho)$-quantile of drift; a persistent trigger excess of 0.1 moves τ by 15–20% per decoding step (28–36 layers). Because τ is shared across layers, layers that drift more at a given moment still refresh preferentially; because it is reset for every sample, each sample receives roughly a ρ share of refreshes and low-drift samples are no longer starved. Within a step, layers update τ in forward order, so later layers see a threshold adjusted by earlier layers' triggers; we did not explore per-layer thresholds. We use $\rho = 0.4$ throughout.

Low-rank drift detector. At the end of prefill we take, per layer and KV head, the top $R = 8$ right singular vectors $P_R \in \mathbb{R}^{128\times R}$ of the prefix key matrix $K \in \mathbb{R}^{N_p\times 128}$ and keep KP_R on the GPU. Logits of evicted tokens are approximated by $(qP_R)(kP_R)^\top$ while kept tokens use exact logits. This costs the same as the page-mean estimator ($\approx N_p/16$ dot products per step) but resolves individual tokens and yields a token-level ranking. The skewing idea follows InfiniGen, which uses 32 channels for per-step selection; RCR uses 8 channels and only for detection and coarse ranking.

Candidate re-selection. When a layer triggers, RCR fetches the keys of the detector's top $4c$ tokens, computes their exact attention, keeps the top c, and fetches their values. A refresh thus reads $5c$ vectors instead of $N_p + 2c$ for a full-prefix scan.

GPU-side decision. A naive implementation copies the drift-vs-threshold comparison to the host in every layer and step to branch on it, which stalls the kernel pipeline. RCR instead computes the candidate selection in every layer and merges it with the old one under the trigger mask

Algorithm 1: RCR at decoding step t, layer l

1. $\hat{a} \leftarrow$ detector attention over the prefix, from logits that are exact for $\mathcal{S}_{l,h}$ and $(qP_R)(k_jP_R)^\top$ otherwise
2. $\hat{d}_{l,h} \leftarrow \sum_{j \notin \mathcal{S}_{l,h}} \hat{a}_j$; $\quad m \leftarrow [\frac{1}{H_{kv}} \sum_h \hat{d}_{l,h} > \tau]$
3. $\tau \leftarrow \tau \exp(\eta(m - \rho))$
4. $\mathcal{C}_h \leftarrow$ top-$4c$ of $\hat{a}$; $\quad \mathcal{S}'_{l,h} \leftarrow$ top-c of exact $qk_j^\top$, $j \in \mathcal{C}_h$
5. $\mathcal{S}_{l,h} \leftarrow m \,?\, \mathcal{S}'_{l,h} : \mathcal{S}_{l,h}$ $\quad$ (masked, no host sync)
6. write K/V of $\mathcal{S}_{l,h}$ into the first c cache slots; run attention

Figure 3: One RCR step. τ is shared by all layers and reset to τ_0 for every sample; with layer-level triggering, $m \in \{0, 1\}$ and $f = m$ in Eq. (2).

(`torch.where`); un-triggered heads write back their unchanged entries, so the cache contents are identical to the branching implementation, which we verify token-for-token (Appendix F). Offloading then requires a read conditioned on the mask (§7).

Cost. Per KV head and step, RCR performs $\approx N_p/16$ detector dot products and reads on average $5c\,r = 160\,r$ vectors from the CPU, where $r \approx \rho$ is the refresh rate. Quest, ArkVale and InfiniGen read $2c = 64$ vectors per step, two-stage Quest $5c = 160$, and the fixed-threshold rule $r(N_p + 2c)$. The GPU-resident detector of RCR holds $N_p/16$ key equivalents, versus $N_p/4$ for InfiniGen's 32 channels and for Quest's page extrema at page size 8.

6 Experiments

Baselines. All dynamic methods start from the same BACON selection and budget, and re-select with the current step's attention only. *Exact every step* re-selects from exact full-prefix attention at each step; it is the strongest current-query re-selection, not a strict bound (RCR slightly exceeds it on LLaVA DetailCaps). *Periodic* re-selects at step 1 and every T steps. *Quest*, *ArkVale* and *two-stage Quest* (page size 8; the latter scores $4c$ candidates exactly) retrieve at every step, as does *InfiniGen* (previous-layer input as query proxy, 32 of 128 skewed channels). *Fixed threshold* is the page-mean drift rule of §4 with τ chosen per setting by the rule we registered for Qwen3-VL (the most faithful threshold with a refresh rate of 10–30%; Appendix C). It also differs from RCR in its detector and full-prefix refresh (separated in Table 3).

Protocol. RCR's components were selected on a development split of 100 Qwen2-VL DetailCaps images that overlaps the 300-image test set in only two images (Appendix A). Three candidates were then evaluated on all six model–task settings under a decision rule registered in advance; we report RCR here and all candidates in Appendix B.

Main results. Table 2 reports fidelity on all six settings. **Apart from exact per-step re-selection, RCR is the best method in every setting.** It improves over BACON by 11.4–21.0 points on DetailCaps and stays within 1.7 points of exact per-step re-selection in every setting (and above it on LLaVA DetailCaps), while refreshing 40–48% of layer-steps. **It outperforms InfiniGen** with confidence intervals above zero on five settings (+1.6 to +3.8), and **is on par with it on Qwen3-VL DetailCaps** (+0.5, interval including zero). **One ρ fits all settings.** The fixed-threshold rule needs a tuned τ per setting, and on Qwen3-VL its pre-registered setting falls well behind the per-step methods (Appendix C); RCR uses the same configuration everywhere and improves over it by 2.0–4.8 points on DetailCaps. On TextCaps the realised refresh rate (41–48%) slightly exceeds ρ because outputs last only 12–29 steps, too few for the threshold to converge. Page-level retrieval is ineffective at this budget: with only four pages per step, Quest gains at most 6.0 points over BACON and ArkVale falls below BACON on Qwen2-VL.

Cost. Figure 4 places each method by its CPU-to-GPU traffic. RCR reads 63–77 vectors per step and head ($160\,r$), on par with InfiniGen and Quest (64), 39–48% of two-stage Quest (160), and at most half of the fixed-threshold rule, which scans the full prefix at every trigger. Its GPU-resident detector is 4× smaller than InfiniGen's, and it changes the cache on only ∼40% of layer-steps. The one-off extra cost is an SVD of an $N_p \times 128$ matrix per layer and head at the end of prefill. Our implementation keeps the full prefix on the GPU to simulate offloading, so we report traffic rather than wall-clock latency; moving the trigger decision onto the GPU alone speeds up our simulation by about 3.4× (Appendix F).

Component analysis. Table 3 compares RCR's components on the development split. At similar refresh rates the low-rank detector improves over page means by 1.3 points, and adding candidate re-selection still gives high fidelity while cutting

Method	Qwen2-VL-7B		LLaVA-NeXT-7B		Qwen3-VL-8B	
	DetailCaps	TextCaps	DetailCaps	TextCaps	DetailCaps	TextCaps
BACON (one-shot)	.388	.626	.371	.680	.409	.505
Prefill oracle (one-shot)	.516	.774	.440	.810	.507	.735
Periodic, T=4	.521 (25%)	.738 (28%)	.448 (25%)	.751 (29%)	.535 (25%)	.687 (27%)
Quest, page 8	.408	.644	.419	.735	.440	.565
ArkVale, page 8	.347	.535	.401	.697	.424	.510
Two-stage Quest, page 8	.508	.763	.468	.808	.550	.684
InfiniGen	.570	.779	.451	.773	.560	.733
Fixed threshold	.551 (25%)	.780 (29%)	.465 (14%)	.782 (28%)	.517 (18%)	.745 (44%)
RCR ($\rho = 0.4$)	**.598** (40%)	**.816** (48%)	**.485** (40%)	**.811** (48%)	**.565** (40%)	**.750** (41%)
Δ vs. InfiniGen	+2.8 [0.8,4.8]	+3.7 [2.1,5.4]	+3.4 [2.1,4.8]	+3.8 [1.8,5.9]	+0.5 [−1.1,2.1]	+1.6 [0.2,3.2]
Exact every step	.613	.826	.478	.822	.571	.767

Table 2: Fidelity (ROUGE-L to the uncompressed output) at a budget of 64 prefix KV entries per head (generated tokens are kept). Parentheses: share of layer-steps that re-select (per-step methods: 100%). Bold: best method other than exact every step. Δ: paired difference in points with 95% bootstrap CI.



Figure 4: Fidelity vs. average number of 128-d vectors read from CPU per step and KV head on DetailCaps (log scale; cost model of §5). At the traffic of a per-step method that fetches only the selected tokens, RCR reaches the highest fidelity.

Variant (dev split)	Refresh	Fid.	Δ vs. IG
Fixed τ=.03, page-mean	15%	.498	−5.0
+ per-head trigger	15%	.536	−1.2
Fixed τ=.02, page-mean	26%	.535	−1.3
Fixed τ=.03, low-rank	28%	.548	0.0
Fixed τ=.02, low-rank + cand.	37%	.558	+0.9
Rate ρ=.2, page-mean	20%	.529	−2.0
RCR: rate ρ=.4 + low-rank + cand.	40%	.584	+3.5
InfiniGen / exact every step	100%	.549 / .594	0 / +4.5

Table 3: Component analysis on the 100-image development split (Qwen2-VL DetailCaps). Δ: paired difference to InfiniGen in points. Full list with intervals in Appendix A.

each refresh from $N_p + 2c$ to $5c$ vectors, which is what makes a 40% refresh rate affordable. Rate control alone at $\rho = 0.2$ is about 1.6 points better than linearly interpolating the fixed-threshold sweep, but its main value is transfer: in the confirmation runs, the two fixed-threshold candidates

Trigger (same detector, cand.)	Refresh	Qwen2	LLaVA
Random	40%	.548 −5.0	.462 −2.3
Periodic, T=3	33%	.552 −4.6	–
Periodic, T=2	50%	.578 −2.0	–
Drift, rate-controlled (RCR)	40%	**.598**	**.485**

Table 4: Does drift decide *when*? DetailCaps fidelity when only the trigger changes; small numbers: paired difference to RCR (all 95% CIs exclude zero; Appendix G).

that refreshed 33–56% of layer-steps on the development split drifted to 21–100% on other models and tasks, whereas RCR stayed at 40–48% with similar fidelity (Appendix B). Per-head triggering helps at low refresh rates but did not transfer as predictably.

Does drift decide *when*? Table 4 keeps RCR's detector, candidate re-selection and merge and re-



Figure 5: Post-hoc sweeps on Qwen2-VL DetailCaps (300 test images, budget 64). RCR points vary only ρ (the main configuration uses ρ=0.4, fixed beforehand); fixed-threshold and periodic points vary τ and T and scan the full prefix at each refresh.

places only the trigger. At the same 40% rate, random timing loses 5.0 points on Qwen2-VL and 2.3 on LLaVA-NeXT, and on Qwen2-VL falls below InfiniGen (.548 vs. .570); periodic timing loses 2.0 points even when it refreshes more often (50%). The gains thus come from refreshing at the right moments, not merely often.

Sensitivity to ρ and to the budget. After the confirmation we swept ρ on the Qwen2-VL DetailCaps test set (Figure 5; full numbers in Appendix G). Fidelity rises monotonically with ρ (.538, .560, .598, .606 for $\rho = 0.1, 0.2, 0.4, 0.6$) and approaches exact per-step re-selection (.613), so ρ acts as a smooth quality–cost knob rather than a fragile hyperparameter. At $\rho = 0.2$ RCR is on par with InfiniGen (-1.0 [-2.9, $+1.0$]) while reading half as many vectors (32 vs. 64 per step and head); at $\rho = 0.1$ it trails InfiniGen by 3.2 points [-5.3, -1.0] but still exceeds the fixed threshold at $\tau = 0.03$ (.522) and periodic refresh with $T = 4$ (.521), which read 8.6 and 14 times more data. Larger budgets narrow all gaps: at 128 entries per head ($c = 96$), RCR still leads InfiniGen by 2.7 points [+1.3, +4.1] (.785 vs. .758; exact .788), but at 256 ($c = 224$) the lead shrinks to 1.2 [-0.1, +2.4] (.861 vs. .849; exact .874, BACON .785), so RCR matters most when the budget is tight.

6.1 Analysis

Does rate control fix the diagnosed failure? Figure 2 shows RCR on the same terciles. On low-drift samples it raises fidelity from .548 to .718, above InfiniGen (.707), while on high-drift samples it stays at the level of the fixed threshold (.473 vs. .479) and of exact re-selection (.484). The improvement comes from where the diagnosis predicted. On LLaVA-NeXT, whose fixed-threshold refresh rate is more uniform across terciles (10–18%), RCR improves the low and middle terciles (.455→.493, .472→.495) and leaves the high one unchanged (.469 vs. .466).



Figure 6: Where refreshes go (61 Qwen2-VL DetailCaps samples, layer-step traces). Left: refresh rate by position in the output. Right: refresh rate per layer. The fixed threshold (τ=0.03) spends its refreshes at the start of generation; RCR spreads them evenly over time while keeping the same preference over layers.



Figure 7: Drift, threshold and refreshes (ticks) for layer 11 on one Qwen2-VL DetailCaps image. RCR's threshold is replayed exactly from the traced decisions. The fixed threshold stops refreshing once drift decays; RCR keeps refreshing at a steady rate. Fidelity: fixed .36, RCR .55.

Where does RCR spend its refreshes? We traced every layer-step decision on the first 61 Qwen2-VL DetailCaps test images (Figure 6); tracing leaves all outputs unchanged, and these images drift more than average (fixed-threshold refresh 29% vs. 15% on the full test set). Two observations refine the diagnosis. First, drift is not comparable across *time* either: as generated tokens accumulate they absorb attention, so drift decays and the fixed threshold refreshes 70% of layer-steps in the first tenth of the output but only 3% in the last tenth. Because RCR's threshold tracks a running quantile, it follows this decay and refreshes 39–43% of layer-steps in every decile. Figure 7 shows this

on one image and layer: after step 130 drift stays below $\tau = 0.03$ on 99% of steps and the fixed rule refreshes only twice more in 380 steps, whereas RCR's threshold descends with the drift and keeps refreshing (69 times) until the end of the description. Second, rate control redistributes refreshes across samples and steps but not across layers: the per-layer refresh profiles of the two methods have a Spearman correlation of 0.93, with layers 4–7 almost never refreshing and layers 14 and 21 refreshing on most steps under RCR. Drift thus keeps deciding *where* to re-select, while the controller decides *how much*.

Why are gains smaller on Qwen3-VL? Qwen3-VL drifts less and has shorter prefixes (639 vs. 852 tokens), so InfiniGen loses less: exact re-selection is only 1.1 points above it (4.3 on Qwen2-VL), and RCR recovers about half of this.

Video: a test of the diagnosis. On 300 pre-registered ActivityNet videos of VideoDetailCaption (Caba Heilbron et al., 2015; Zhang et al., 2024) (32 frames, ∼2,300 prefix tokens; Appendix K), per-sample drift is far more homogeneous than on DetailCaps images (coefficient of variation 0.14–0.18 vs. 0.71–0.78 for the Qwen models), and the fixed threshold starves at most 1% of videos (vs. 21–45% of images for the Qwen models). RCR, unchanged, is on par with InfiniGen on Qwen2-VL (+0.9 [−0.6, +2.4]) and exceeds it on Qwen3-VL (+2.0 [+1.1, +2.8]), but at the nearest tested rates it is no better than the fixed threshold (−1.0 to +0.5, all intervals include zero), consistent with the diagnosis.

Reference metrics and object-level errors. Against human references, dynamic methods clearly beat BACON; CIDEr and ROUGE-L do not separate them from each other or from the uncompressed model (Appendix H), and CAPTURE, the object-level DetailCaps metric (Dong et al., 2024), separates them only by small margins (.631–.635 on Qwen2-VL; uncompressed .636). Parsing outputs into objects with CAPTURE's scene-graph parser and comparing them with the uncompressed output (Appendix L), RCR exceeds InfiniGen in object F1 by 1.3 [0.2, 2.3] points on Qwen2-VL and 2.5 [1.4, 3.5] on LLaVA-NeXT, is on par on Qwen3-VL (+0.7 [−0.1, 1.5]), and exceeds the fixed threshold by 1.3–2.2. On LLaVA-NeXT the gain is recall: RCR omits fewer of the uncompressed model's objects (+4.8 [3.3, 6.2]) at similar precision (−0.7 [−2.1, +0.7]), although its precision against the human references is 2.2 points below InfiniGen's. Appendix I shows an omission by InfiniGen and a counter-example.

7 Discussion

Why a rate rather than a better threshold? Drift is an uncalibrated score: its scale depends on the image, the model, and even the position in the output (Figure 6). Any fixed cut-off on such a score yields a refresh rate that varies severalfold across settings (Table 2, 14–44%; Appendix B, 21–100%). Tracking a quantile instead turns the score into a ranking, which is all the trigger needs, and turns the hard-to-set threshold into an interpretable budget. Other online triggers (Xu et al., 2024; Kim et al., 2026) also use fixed thresholds today.

Choosing ρ. Average traffic is $5c\rho$ vectors per layer, KV head and step, so ρ follows from a bandwidth budget: $\rho = 0.4$ matches InfiniGen's 64 vectors, and $\rho = 0.2$ halves them at a cost of 3.8 points on Qwen2-VL DetailCaps (Figure 5); a fixed threshold's traffic depends on each model's and task's drift statistics.

Deployment. Our simulation keeps the full prefix on the GPU. Offloaded, RCR must read candidate keys only for triggered heads without involving the host, e.g. with a kernel that reads pinned host memory through unified virtual addressing under the trigger mask; fetching candidates unconditionally would cost $5c = 160$ vectors per step, as two-stage Quest. Unlike InfiniGen, which speculates with the previous layer's input, RCR fetches on the critical path of a refreshing layer; combining the two in a real offloading system is future work.

8 Conclusion

One-shot KV selection limits long-form multimodal generation because the model's attention moves over the image; even an oracle keeps only .44–.52 fidelity. Re-selecting on drift is the natural remedy, but drift magnitudes are not comparable across samples, so a fixed threshold starves exactly the samples that need refreshing. RCR lets drift decide when and where to re-select and a per-sample budget decide how often. One configuration outperforms InfiniGen in five of six image settings at comparable traffic, beats random timing at the same refresh rate and periodic timing even when the latter refreshes more often, and exposes a knob

that maps to bandwidth; its advantage shrinks with larger budgets and, over a fixed threshold, vanishes on video, where drift is homogeneous.

Limitations

Scope. We evaluate two image captioning tasks on three 7–8B MLLMs and video description on two, at a prefix budget of 64 entries per head (generated tokens are kept), and budgets of 128 and 256 only on Qwen2-VL DetailCaps, where the advantage over InfiniGen is no longer significant at 256; larger models, multi-image generation, long document answers, multimodal reasoning chains and short-answer VQA are not covered. On video, RCR is not significantly better than InfiniGen on Qwen2-VL and not better than a fixed threshold at the nearest tested rates on either model; on LLaVA-NeXT images, whose drift is similarly homogeneous, its gain over a fixed threshold at a similar rate is borderline (+1.1 [−0.0, +2.3]). The ρ and budget sweeps were run after the confirmation and on the test set; they characterise the method but were not used to choose it. **Evaluation.** Fidelity measures deviation from the uncompressed output, not correctness. Reference-based metrics separate dynamic methods weakly at best (CAPTURE differences are below one point); our object-level analysis relies on an automatic scene-graph parser, and we run no human evaluation. **Baselines.** All baselines are our re-implementations in a shared simulation; we do not re-implement DSTP (Kim et al., 2026), whose trigger compares the attention over kept visual tokens with a prefill anchor, so our fixed-threshold baseline covers fixed thresholds on drift but not on DSTP's signal. **Gains vary by model.** RCR outperforms InfiniGen by 2.8–3.8 points on Qwen2-VL and LLaVA-NeXT but only by 1.6 on Qwen3-VL TextCaps and not significantly on Qwen3-VL DetailCaps, where drift is uniformly small; the fixed-threshold version is clearly weaker there (Appendix C). **Selection on a development split.** Components were chosen among 14 variants on 100 development images, and confidence intervals are not corrected for multiple comparisons; held-out confirmation mitigates but cannot fully remove selection bias, and the margin over InfiniGen shrank from 3.5 on the development split to 2.8 on the Qwen2-VL test set. **Latency.** Costs are traffic estimates from a simulation that keeps the full prefix on the GPU; we do not measure end-to-end latency of an offloading system, and RCR's fetch cannot be prefetched with the previous layer's input as in InfiniGen without modification (§7). **Short outputs.** On 12–29-step outputs the controller overshoots ρ (41–48%).

References

Jinwoo Ahn, Ingyu Seong, Akhil Kedia, Junhan Kim, Hyemi Jang, Kangwook Lee, and Yongkweon Jeon. 2026. LookaheadKV: Fast and Accurate KV Cache Eviction by Glimpsing into the Future without Generation. In *ICLR*. ArXiv:2603.10899.

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, et al. 2025. Qwen3-VL Technical Report. *arXiv preprint arXiv:2511.21631*.

Payman Behnam, Yaosheng Fu, Ritchie Zhao, Po-An Tsai, Zhiding Yu, and Alexey Tumanov. 2025. RocketKV: Accelerating Long-Context LLM Inference via Two-Stage KV Cache Compression. In *ICML*. ArXiv:2502.14051.

Fabian Caba Heilbron, Victor Escorcia, Bernard Ghanem, and Juan Carlos Niebles. 2015. ActivityNet: A Large-Scale Video Benchmark for Human Activity Understanding. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*.

Zefan Cai, Wen Xiao, Hanshi Sun, Cheng Luo, Yikai Zhang, Ke Wan, Yucheng Li, Yeyang Zhou, Li-Wen Chang, Jiuxiang Gu, et al. 2025. R-KV: Redundancy-aware KV Cache Compression for Reasoning Models. In *NeurIPS*. ArXiv:2505.24133.

Zefan Cai, Yichi Zhang, Bofei Gao, Yuliang Liu, Yucheng Li, Tianyu Liu, Keming Lu, Wayne Xiong, Yue Dong, Junjie Hu, et al. 2024. PyramidKV: Dynamic KV Cache Compression based on Pyramidal Information Funneling. *arXiv preprint arXiv:2406.02069*.

Liang Chen, Haozhe Zhao, Tianyu Liu, Shuai Bai, Junyang Lin, Chang Zhou, and Baobao Chang. 2024a. An Image is Worth 1/2 Tokens After Layer 2: Plug-and-Play Inference Acceleration for Large Vision-Language Models. In *ECCV*. ArXiv:2403.06764.

Renze Chen, Zhuofeng Wang, Beiquan Cao, Tong Wu, Size Zheng, Xiuhong Li, Xuechao Wei, Shengen Yan, Meng Li, and Yun Liang. 2024b. ArkVale: Efficient Generative LLM Inference with Recallable Key-Value Eviction. In *NeurIPS*.

Tianhao Chen, Yuheng Wu, Kelu Yao, Xiaogang Xu, Xiaobin Hu, and Dongman Lee. 2026. Last But Not Least: Boundary Attention CalibratiON for Multimodal KV Cache Compression. In *EMNLP*. ArXiv:2606.14782.

Zhuoming Chen, Ranajoy Sadhukhan, Zihao Ye, Yang Zhou, Jianyu Zhang, Niklas Nolte, Yuandong Tian, Matthijs Douze, Leon Bottou, Zhihao Jia, et al. 2025. MagicPIG: LSH Sampling for Efficient LLM Generation. In *ICLR*. ArXiv:2410.16179.

Hongyuan Dong, Jiawen Li, Bohong Wu, Jiacong Wang, Yuan Zhang, and Haoyuan Guo. 2024. Benchmarking and Improving Detail Image Caption. *arXiv preprint arXiv:2405.19092*.

Yuan Feng, Junlin Lv, Yukun Cao, Xike Xie, and S. Kevin Zhou. 2025. Ada-KV: Optimizing KV Cache Eviction by Adaptive Budget Allocation for Efficient LLM Inference. In *NeurIPS*. ArXiv:2407.11550.

Yu Fu, Zefan Cai, Abedelkadir Asi, Wayne Xiong, Yue Dong, and Wen Xiao. 2025. Not All Heads Matter: A Head-Level KV Cache Compression Method with Integrated Retrieval and Reasoning. In *ICLR*. ArXiv:2410.19258.

Kevin Galim, Ethan Ewer, Wonjun Kang, Minjae Lee, Hyung Il Koo, and Kangwook Lee. 2026. Draft-based Approximate Inference for LLMs. In *ICLR*. ArXiv:2506.08373.

Ayushman Garg, Akshita Gupta, Shaswata Bhattacharya, Abhishek Gupta, Sandeep Kumar, and Manoj Kumar. 2026. QEvict: Recoverable Quantized KV Eviction for Attention-Drift-Robust Long-Context Decoding. *arXiv preprint arXiv:2608.05326*.

Ravi Ghadia, Avinash Kumar, Gaurav Jain, Prashant Nair, and Poulami Das. 2025. Dialogue Without Limits: Constant-Sized KV Caches for Extended Responses in LLMs. In *ICML*. ArXiv:2503.00979.

Jitai Hao, Yuke Zhu, Tian Wang, Jun Yu, Xin Xin, Bo Zheng, Zhaochun Ren, and Sheng Guo. 2025. OmniKV: Dynamic Context Selection for Efficient Long-Context LLMs. In *ICLR*.

Kai Huang, Hao Zou, Bochen Wang, Ye Xi, Zhen Xie, and Hao Wang. 2025. AirCache: Activating Inter-modal Relevancy KV Cache Compression for Efficient Large Vision-Language Model Inference. In *ICCV*. ArXiv:2503.23956.

Shibo Jie, Yehui Tang, Kai Han, Zhi-Hong Deng, and Jing Han. 2025. SpeCache: Speculative Key-Value Caching for Efficient Generation of LLMs. In *ICML*. ArXiv:2503.16163.

Jiwan Kim, Kibum Kim, Wonjoong Kim, Byung-Kwan Lee, and Chanyoung Park. 2026. Why and When Visual Token Pruning Fails? A Study on Relevant Visual Information Shift in MLLMs Decoding. *arXiv preprint arXiv:2604.12358*.

Wonbeom Lee, Jungi Lee, Junghwan Seo, and Jaewoong Sim. 2024. InfiniGen: Efficient Generative Inference of Large Language Models with Dynamic KV Cache Management. In *OSDI*. ArXiv:2406.19707.

Kunxi Li, Zhonghua Jiang, Zhouzhou Shen, Zhaode Wang, Chengfei Lv, Shengyu Zhang, Fan Wu, and Fei Wu. 2025. MadaKV: Adaptive Modality-Perception KV Cache Eviction for Efficient Multimodal Long-Context Inference. *arXiv preprint arXiv:2506.15724*.

Yuhong Li, Yingbing Huang, Bowen Yang, Bharat Venkitesh, Acyr Locatelli, Hanchen Ye, Tianle Cai, Patrick Lewis, and Deming Chen. 2024. SnapKV: LLM Knows What You are Looking for Before Generation. In *NeurIPS*. ArXiv:2404.14469.

Xiaoyu Liang, Chaofeng Guan, Jiaying Lu, Huiyao Chen, Huan Wang, and Haoji Hu. 2025. Dynamic Token Reduction during Generation for Vision Language Models. *arXiv preprint arXiv:2501.14204*.

Mengqi Liao, Lu Wang, Chaoyun Zhang, Zekai Shen, Xiaowei Mao, Si Qin, Qingwei Lin, Saravan Rajmohan, Dongmei Zhang, and Huaiyu Wan. 2025. G-KV: Decoding-Time KV Cache Eviction with Global Attention. *arXiv preprint arXiv:2512.00504*.

Chaofan Lin, Jiaming Tang, Shuo Yang, Hanshuo Wang, Tian Tang, Boyu Tian, Ion Stoica, Song Han, and Mingyu Gao. 2025. Twilight: Adaptive Attention Sparsity with Hierarchical Top-p Pruning. In *NeurIPS*.

Di Liu, Meng Chen, Baotong Lu, Huiqiang Jiang, Zhenhua Han, Qianxi Zhang, Qi Chen, Chengruidong Zhang, Bailu Ding, Kai Zhang, et al. 2024a. RetrievalAttention: Accelerating Long-Context LLM Inference via Vector Retrieval. *arXiv preprint arXiv:2409.10516*.

Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. 2024b. LLaVA-NeXT: Improved Reasoning, OCR, and World Knowledge. https://llava-vl.github.io/blog/2024-01-30-llava-next/.

Xuyang Liu, Xiyan Gui, Yuchao Zhang, and Linfeng Zhang. 2026. Mixing Importance with Diversity: Joint Optimization for KV Cache Compression in Large Vision-Language Models. In *ICLR*. ArXiv:2510.20707.

Zichang Liu, Aditya Desai, Fangshuo Liao, Weitao Wang, Victor Xie, Zhaozhuo Xu, Anastasios Kyrillidis, and Anshumali Shrivastava. 2023. Scissorhands: Exploiting the Persistence of Importance Hypothesis for LLM KV Cache Compression at Test Time. In *NeurIPS*. ArXiv:2305.17118.

Zuyan Liu, Benlin Liu, Jiahui Wang, Yuhao Dong, Guangyi Chen, Yongming Rao, Ranjay Krishna, and Jiwen Lu. 2024c. Efficient Inference of Vision Instruction-Following Models with Elastic Cache. In *ECCV*. ArXiv:2407.18121.

Minesh Mathew, Dimosthenis Karatzas, and C. V. Jawahar. 2021. DocVQA: A Dataset for VQA on Document Images. In *WACV*. ArXiv:2007.00398.

Bradley McDanel, Steven Li, and Harshit Khaitan. 2026. CLAA: Cross-Layer Attention Aggregation for Accelerating LLM Prefill. *arXiv preprint arXiv:2602.16054*.

Yanlin Qi, Xinhang Chen, Huiqiang Jiang, Qitong Wang, Botao Peng, and Themis Palpanas. 2026. ParisKV: Fast and Drift-Robust KV-Cache Retrieval for Long-Context LLMs. *arXiv preprint arXiv:2602.07721*.

Ziran Qin, Yuchen Cao, Mingbao Lin, Wen Hu, Shixuan Fan, Ke Cheng, Weiyao Lin, and Jianguo Li. 2025. CAKE: Cascading and Adaptive KV Cache Eviction with Layer Preferences. In *ICLR*. ArXiv:2503.12491.

Luka Ribar, Ivan Chelombiev, Luke Hudlass-Galley, Charlie Blake, Carlo Luschi, and Douglas Orr. 2024. SparQ Attention: Bandwidth-Efficient LLM Inference. In *ICML*. ArXiv:2312.04985.

Jack Shi and Jerry Gu. 2026. Trust the Mass: Forced Weights in KV-Cache Eviction. *arXiv preprint arXiv:2608.25230*.

Oleksii Sidorov, Ronghang Hu, Marcus Rohrbach, and Amanpreet Singh. 2020. TextCaps: a Dataset for Image Captioning with Reading Comprehension. In *ECCV*. ArXiv:2003.12462.

Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. 2019. Towards VQA Models That Can Read. In *CVPR*. ArXiv:1904.08920.

Prajwal Singhania, Siddharth Singh, Shwai He, Soheil Feizi, and Abhinav Bhatele. 2024. Loki: Low-rank Keys for Efficient Sparse Attention. In *NeurIPS*. ArXiv:2406.02542.

Hanshi Sun, Li-Wen Chang, Wenlei Bao, Size Zheng, Ningxin Zheng, Xin Liu, Harry Dong, Yuejie Chi, and Beidi Chen. 2025a. ShadowKV: KV Cache in Shadows for High-Throughput Long-Context LLM Inference. In *ICML*. ArXiv:2410.21465.

Yutao Sun, Tianzhu Ye, Li Dong, Yuqing Xia, Jian Chen, Yizhao Gao, Shijie Cao, Jianyong Wang, and Furu Wei. 2025b. Rectified Sparse Attention. *arXiv preprint arXiv:2506.04108*.

Jiaming Tang, Yilong Zhao, Kan Zhu, Guangxuan Xiao, Baris Kasikci, and Song Han. 2024. Quest: Query-Aware Sparsity for Efficient Long-Context LLM Inference. In *ICML*. ArXiv:2406.10774.

Dezhan Tu, Danylo Vashchilenko, Yuzhe Lu, and Panpan Xu. 2025. VL-Cache: Sparsity and Modality-Aware KV Cache Compression for Vision-Language Model Inference Acceleration. In *ICLR*. ArXiv:2410.23317.

Zhongwei Wan, Hui Shen, Xin Wang, Che Liu, Zheda Mai, and Mi Zhang. 2025. MEDA: Dynamic KV Cache Allocation for Efficient Multimodal Long-Context Inference. *arXiv preprint arXiv:2502.17599*.

Zhongwei Wan, Ziang Wu, Che Liu, Jinfa Huang, Zhihong Zhu, Peng Jin, Longyue Wang, and Li Yuan. 2024. LOOK-M: Look-Once Optimization in KV Cache for Efficient Multimodal Long-Context Inference. In *Findings of EMNLP*. ArXiv:2406.18139.

Jiahui Wang, Zuyan Liu, Yongming Rao, and Jiwen Lu. 2025a. SparseMM: Head Sparsity Emerges from Visual Concept Responses in MLLMs. In *ICCV*. ArXiv:2506.05344.

Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, et al. 2024. Qwen2-VL: Enhancing Vision-Language Model's Perception of the World at Any Resolution. *arXiv preprint arXiv:2409.12191*.

Yixuan Wang, Shiyu Ji, Yijun Liu, Yuzhuang Xu, Yang Xu, Qingfu Zhu, and Wanxiang Che. 2025b. Lookahead Q-Cache: Achieving More Consistent KV Cache Eviction via Pseudo Query. *arXiv preprint arXiv:2505.20334*.

Jialong Wu, Zhenglin Wang, Linhai Zhang, Yilong Lai, Yulan He, and Deyu Zhou. 2025. SCOPE: Optimizing Key-Value Cache Compression in Long-context Generation. In *ACL*. ArXiv:2412.13649.

Long Xing, Qidong Huang, Xiaoyi Dong, Jiajie Lu, Pan Zhang, Yuhang Zang, Yuhang Cao, Conghui He, Jiaqi Wang, Feng Wu, et al. 2025. PyramidDrop: Accelerating Your Large Vision-Language Models via Pyramid Visual Redundancy Reduction. In *CVPR*. ArXiv:2410.17247.

Fangyuan Xu, Tanya Goyal, and Eunsol Choi. 2024. RefreshKV: Updating Small KV Cache During Long-form Generation. *arXiv preprint arXiv:2411.05787*.

Cheng-Yu Yang, Shao-Yuan Lo, and Yu-Lun Liu. 2026. Reroute, Don't Remove: Recoverable Visual Token Routing for Vision-Language Models. *arXiv preprint arXiv:2606.12412*.

Lijie Yang, Zhihao Zhang, Zhuofu Chen, Zikun Li, and Zhihao Jia. 2025a. TidalDecode: Fast and Accurate LLM Decoding with Position Persistent Sparse Attention. In *ICLR*. ArXiv:2410.05076.

Senqiao Yang, Yukang Chen, Zhuotao Tian, Chengyao Wang, Jingyao Li, Bei Yu, and Jiaya Jia. 2025b. VisionZip: Longer is Better but Not Necessary in Vision Language Models. In *CVPR*. ArXiv:2412.04467.

Wenshuai Yao, Wenyong Zhou, Hanyong Shao, Yizhe Chen, Zhiyuan Ning, Yuannuo Feng, Ru Huang, and Kechao Tang. 2026. Recall Before You Rank: Similarity-Guided Top-K Reuse for Efficient Long-Context Attention. *arXiv preprint arXiv:2607.27692*.

Haoyue Zhang, Hualei Zhang, Xiaosong Ma, Jie Zhang, and Song Guo. 2025a. LazyEviction: Lagged KV Eviction with Attention Pattern Observation for Efficient Long Reasoning. *arXiv preprint arXiv:2506.15969*.

Kaichen Zhang, Bo Li, Peiyuan Zhang, Fanyi Pu, Joshua Adrian Cahyono, Kairui Hu, Shuai Liu, Yuanhan Zhang, Jingkang Yang, Chunyuan Li, and Ziwei Liu. 2024. LMMs-Eval: Reality Check on the Evaluation of Large Multimodal Models. *arXiv preprint arXiv:2407.12772*.

Yuan Zhang, Chun-Kai Fan, Junpeng Ma, Wenzhao Zheng, Tao Huang, Kuan Cheng, Denis Gudovskiy, Tomoyuki Okuno, Yohei Nakata, Kurt Keutzer, et al. 2025b. SparseVLM: Visual Token Sparsification for Efficient Vision-Language Model Inference. In *ICML*. ArXiv:2410.04417.

Zhenyu Zhang, Ying Sheng, Tianyi Zhou, Tianlong Chen, Lianmin Zheng, Ruisi Cai, Zhao Song, Yuandong Tian, Christopher Ré, Clark Barrett, et al. 2023. H_2O: Heavy-Hitter Oracle for Efficient Generative Inference of Large Language Models. In *NeurIPS*. ArXiv:2306.14048.

Ge Zheng, Jiaye Qian, Jiajin Tang, and Sibei Yang. 2025. Why LVLMs Are More Prone to Hallucinations in Longer Responses: The Role of Context. In *ICCV*. ArXiv:2510.20229.

Kan Zhu, Tian Tang, Qinyu Xu, Yile Gu, Zhichen Zeng, Rohan Kadekodi, Liangyu Zhao, Ang Li, Arvind Krishnamurthy, and Baris Kasikci. 2025. Tactic: Adaptive Sparse Attention with Clustering and Distribution Fitting for Long-Context LLMs. *arXiv preprint arXiv:2502.12216*.

A Development and Confirmation Protocol

Development split. We compared 14 variants on 100 Qwen2-VL DetailCaps images sampled evenly over the 4,870-image set (indices from `linspace` with $n = 100$; only indices 0 and 4869 also appear in the 300-image test set). Reference methods were re-run on the same images. Table 5 lists every variant.

Selection. We advanced the most faithful fixed-threshold combination (`svd8c4_001`), the cheapest combination of similar fidelity (`svd8c4h_002`), and the only combination without a per-setting trigger threshold (`rate40_c4`, RCR). Forced refresh (`floor*`) performed similarly to rate control but adds a hyperparameter. Thresholds relative to the residual drift after the last refresh (`grow*`) almost never fired.

Pre-registered decision rule. Before running the confirmation, we fixed the three candidates, the six settings, the comparison to InfiniGen on identical samples, and the rule: a candidate becomes the main method if it is not significantly worse than InfiniGen (upper CI bound ≥ 0; this is not a non-inferiority test) in at least five of six settings; all results are reported regardless. RCR satisfies the rule in all six settings.

B Confirmation Results for All Candidates

Table 6 lists all three candidates. The two fixed-threshold candidates are as accurate as RCR or slightly more on TextCaps, but at 69–100% refresh, i.e. nearly per-step cost; their refresh rates range from 21% to 100% across settings, whereas RCR stays at 40–48%. Absolute fidelities on the evaluated subsets, together with InfiniGen, two-stage Quest, exact re-selection and BACON on the same samples, are in the released logs.

C Pre-registered Qwen3-VL Matrix for the Fixed-Threshold Version

Before exploring any of RCR's components, we registered a full Qwen3-VL-8B evaluation of the fixed-threshold version, including the rule for its headline setting (the most faithful threshold with refresh rate in 10–30%, else the one closest to 20%). Table 7 reports all results. By the rule, the headline settings are $\tau = 0.02$ on DetailCaps and $\tau = 0.05$ on TextCaps. On DetailCaps the fixed threshold trails InfiniGen by 4.3 points, two-stage Quest by 3.3 and periodic T=4 by 1.8; interpolated to a 25% refresh rate it reaches about +12.3 over BACON, on par with periodic refresh at the same rate (+12.5), i.e. the advantage over periodic refresh seen on Qwen2-VL and LLaVA does not appear. On TextCaps it is 1.2 points above InfiniGen. Qwen3-VL drifts less overall (τ=0.03 refreshes only 11% on DetailCaps), the low-drift regime diagnosed in §4. During the run, the τ=0.03 job was restarted with the GPU-side decision after 21 samples; its first 21 outputs were identical to the original implementation (Appendix F).

D Fixed-Threshold Version: Additional Results

Versus periodic refresh at equal rates. On Qwen2-VL and LLaVA the fixed threshold outperforms periodic refresh at matched refresh rates by +3.0 (Qwen2 DetailCaps, 24.7% vs. 25.1%), +4.2 (Qwen2 TextCaps, 28.9% vs. 28.1%), +3.6 (LLaVA DetailCaps, 13.7% vs. 12.7%) and +3.1 (LLaVA TextCaps, 28.2% vs. 28.6%). Its thresholds were 0.02, 0.12, 0.08 and 0.15 (chosen by the

Tag	Configuration	Refresh	Fidelity	Δ vs. InfiniGen
b64_bacon	BACON	–	.367	–
grow3_px	threshold = 3× residual drift after last refresh, $\tau_{\min}$=.005	0.5%	.396	–
grow2h_px	threshold = 2× residual drift, per head	0.6%	.430	–
async_px003	fixed τ=.03, page-mean (fixed-threshold version)	15.4%	.498	−5.0 [−8.4, −1.8]
head_px003	+ per-head trigger	15.3%	.536	−1.2 [−4.5, +1.9]
rate20_px	rate control ρ=.2, page-mean	19.7%	.529	−2.0 [−5.8, +1.6]
floor8_px003	τ=.03 + forced refresh after 8 steps	24.9%	.530	–
period14	periodic T=4	25.1%	.509	–
px002	fixed τ=.02, page-mean	26.4%	.535	−1.3 [−4.7, +1.9]
svd8_003	τ=.03, 8-channel low-rank detector	27.7%	.548	−0.0 [−3.5, +3.2]
svd8c4h_002	τ=.02, low-rank + 4c candidates + per head	32.5%	.572	+2.4 [−0.5, +5.3]
svd8c4_002	τ=.02, low-rank + 4c candidates	36.9%	.558	+0.9 [−2.3, +4.2]
rate40_c4	RCR: ρ=.4, low-rank + 4c candidates	39.7%	.584	+3.5 [+0.5, +6.7]
floor4_px002	τ=.02 + forced refresh after 4 steps	42.7%	.572	+2.4 [−0.9, +5.7]
floor8_c4_002	τ=.02, low-rank + candidates + forced after 8	43.3%	.574	+2.5 [−0.1, +5.3]
svd8c4_001	τ=.01, low-rank + 4c candidates	55.9%	.597	+4.8 [+1.6, +8.1]
questex8	two-stage Quest, page 8	100%	.530	−1.9 [−4.7, +1.0]
infinigen	InfiniGen	100%	.549	0
reveryd0	exact every step	100%	.594	+4.5 [+1.5, +7.5]

Table 5: All development-split results (Qwen2-VL DetailCaps, 100 images), sorted by refresh rate, except that the per-head variant directly follows its base configuration. "–": interval not computed.

Setting	RCR (ρ=.4)	τ=.01 + low-rank + cand.	τ=.02 + low-rank + cand. + per head
Qwen2 DetailCaps	+2.8 [+0.8, +4.8] (40%)	+2.8 [+0.9, +4.6] (54%)	+1.9 [−0.1, +3.8] (31%)
Qwen2 TextCaps	+3.7 [+2.1, +5.4] (48%)	+5.1 [+3.3, +6.8] (100%)	+4.8 [+3.0, +6.6] (92%)
LLaVA DetailCaps	+3.4 [+2.1, +4.8] (40%)	+3.5 [+2.1, +4.8] (96%)	+3.4 [+2.1, +4.8] (66%)
LLaVA TextCaps	+3.8 [+1.8, +5.9] (48%)	+4.4 [+2.4, +6.4] (100%)	+4.6 [+2.6, +6.7] (92%)
Qwen3 DetailCaps	+0.5 [−1.1, +2.1] (40%)	+0.9 [−0.7, +2.6] (40%)	+1.1 [−0.5, +2.9] (21%)
Qwen3 TextCaps	+1.6 [+0.2, +3.2] (41%)	+3.5 [+2.1, +4.9] (99%)	+3.6 [+2.1, +5.0] (69%)

Table 6: Paired fidelity difference to InfiniGen (points, 95% CI) and refresh rate for the three confirmed candidates.

Configuration	DetailCaps	TextCaps
BACON	.409	.505
Prefill oracle	.507	.735
Periodic T=8	.507 (13%)	.633 (14%)
Periodic T=4	.535 (25%)	.687 (27%)
Quest / ArkVale, page 8	.440 / .424	.565 / .510
Two-stage Quest, page 8	.550	.684
InfiniGen	.560	.733
Fixed τ=.05	.474 (5%)	**.745** (44%)
Fixed τ=.03	.492 (11%)	.759 (64%)
Fixed τ=.02	**.517** (18%)	.765 (79%)
Fixed τ=.01	.552 (34%)	.766 (94%)
Exact every step	.571	.767

Table 7: Pre-registered Qwen3-VL-8B matrix (all runs complete). Bold: headline settings chosen by the registered rule.

rule of Appendix C), with gains over BACON of +16.3 [14.4, 18.2], +15.4 [12.9, 17.9], +9.5 [8.2, 10.8] and +10.2 [8.1, 12.5].

Page-mean estimator. On 20–40 calibration samples per setting, page-mean drift has a step-level Spearman correlation of 0.90–0.96 with exact drift, and recalls 0.54–0.91 of the high-drift steps flagged by the exact detector at trigger rates of 3–50%.

EMA. Re-selecting from an exponential moving average of past attention (decay 0.8) instead of the current step hurts exact per-step re-selection (e.g. +19.4 vs. +22.5 over BACON on Qwen2 DetailCaps) and drift-triggered refresh (e.g. +6.8 vs. +7.9), and changes periodic refresh by at most ±0.8. All results in the paper use the current step only.

E Diagnosis Details

All numbers in this appendix use $\tau = 0.03$, as in Figure 2. On Qwen2-VL DetailCaps InfiniGen beats the fixed threshold (by more than 2 points) on 46% of samples and loses on 41%; on TextCaps, where the fixed threshold is ahead by 4.7 points on average, the gap is unrelated to drift (Spearman +0.01). Against two-stage Quest the DetailCaps gap is again concentrated in the low-drift tercile (+4.1 for two-stage Quest) and reversed in the high-drift one (−6.2). Exact re-selection beats the fixed threshold by 9.1 points on average; the per-sample gain correlates with refresh rate (−0.39) but not with output length (−0.02). Relative drift by tercile

is 0.025 / 0.049 / 0.094 and total prefix attention 0.265 / 0.295 / 0.330. In the layer-step traces of Figure 6, each refresh replaces about a third of the 32 kept tokens (35% for both methods), and per-sample refresh rates span 13–44% (10th–90th percentile) under the fixed threshold and 39.8–40.1% under RCR.

F GPU-Side Decision: Equivalence and Speed

The GPU-side decision computes the candidate selection in every layer and merges it with the old selection under the trigger mask; un-triggered heads rewrite their own entries, so the cache equals that of the branching implementation. On Qwen3-VL DetailCaps ($\tau = 0.03$), the first 21 samples have identical outputs, per-layer refresh counts, scan counts and mean drift under both implementations. On Qwen2-VL, the GPU-side fixed threshold and exact every-step re-selection (implemented as `drift:-1`) reproduce the original outputs on the two samples shared with the original runs. With 14 evaluation processes on a 4-core host, removing per-layer host synchronisation reduced Qwen3-VL evaluation time from about 137 to 40 seconds per sample; this reflects simulation efficiency, not deployment latency.

G Sensitivity Runs

Table 8 lists the post-hoc sweeps of Figure 5 with intervals and reference-based ROUGE-L (against the DetailCaps references). Reference ROUGE-L is noisy at this scale and not monotone in ρ (.277 to .285), while fidelity is.

H Reference-Based Metrics

Table 9 reports corpus CIDEr and ROUGE-L against the dataset references for the main methods on all six settings (same samples as Table 2). On DetailCaps, CIDEr is too small to rank methods (e.g. .004–.012 on Qwen3-VL).

I Qualitative Examples

Omitted or confabulated details are especially costly in long descriptions, which are already more prone to hallucination than short answers (Zheng et al., 2025). Table 10 shows two Qwen2-VL DetailCaps images, chosen from the two tails of the per-sample fidelity difference between RCR and InfiniGen (so neither is typical). Outputs are shortened with [...]; the shared opening sentence is omitted where identical. Over the 300 test images, RCR is closer to the uncompressed output than InfiniGen by more than 0.1 ROUGE-L on 70 images and farther by more than 0.1 on 41; the mean paired difference is +2.8 points (Table 2).

Qwen2-VL DetailCaps	Refresh	Fidelity	Δ vs. IG	Ref. R-L
Budget 64				
InfiniGen	100%	.570	0	.281
RCR ρ=0.1	9.8%	.538	−3.2 [−5.3, −1.0]	.277
RCR ρ=0.2	19.7%	.560	−1.0 [−2.9, +1.0]	.279
RCR ρ=0.4	39.6%	.598	+2.8 [+0.8, +4.8]	.285
RCR ρ=0.6	59.5%	.606	+3.6 [+1.6, +5.6]	.279
Exact every step	100%	.613	+4.3 [+2.4, +6.1]	.282
Budget 128				
BACON	–	.667	−9.1 [−10.8, −7.4]	.271
InfiniGen	100%	.758	0	.284
RCR ρ=0.4	39.7%	.785	+2.7 [+1.3, +4.1]	.285
Exact every step	100%	.788	+3.0 [+1.5, +4.6]	.287
Budget 256				
BACON	–	.785	−6.4 [−8.0, −5.0]	–
InfiniGen	100%	.849	0	–
RCR ρ=0.4	39.5%	.861	+1.2 [−0.1, +2.4]	–
Exact every step	100%	.874	+2.5 [+1.2, +3.8]	–
Budget 64, same detector and candidates, other triggers (Δ vs. RCR)				
Random (Qwen2)	40.2%	.548	−5.0 [−7.2, −2.6]	–
Periodic T=3 (Qwen2)	33.5%	.552	−4.6 [−6.5, −2.6]	–
Periodic T=2 (Qwen2)	50.1%	.578	−2.0 [−3.8, −0.2]	–
Random (LLaVA)	40.3%	.462	−2.3 [−3.7, −0.9]	–

Table 8: Post-hoc ρ, budget and trigger sweeps on DetailCaps (300 test images; Qwen2-VL unless noted). Δ is against InfiniGen except in the last block. Reference ROUGE-L was computed only for the first two blocks.

J Negative Results

- Scale-free thresholds relative to the residual drift after the last refresh ($\kappa = 2, 3$) almost never fire (0.5% refresh).
- Normalising drift by total prefix attention does not separate low-drift samples (rank correlation 0.98 with absolute drift).
- Geometric expansion of the first look-ahead position along the reading direction lowers TextVQA accuracy by 1.9–2.4 points; its added tokens have precision 7–20%, and key-similarity gating fails as well (precision .106–.146).
- Adaptive look-ahead lies on the same accuracy–cost curve as fixed look-ahead; look-ahead gains on short answers are largely evaluation leakage (on Qwen2 TextVQA, 58% of answers are complete within a 2-step look-ahead).
- Cross-layer averaging of last-query attention helps Qwen2 VQA slightly (+1.6 / +1.2 on TextVQA / DocVQA) but not LLaVA, and resembles CLAA (McDanel et al., 2026).

CIDEr / ROUGE-L	Qwen2-VL-7B		LLaVA-NeXT-7B		Qwen3-VL-8B	
Method	DetailCaps	TextCaps	DetailCaps	TextCaps	DetailCaps	TextCaps
Uncompressed	.067 / .287	1.524 / .550	.099 / .285	.777 / .445	.009 / .261	.376 / .384
BACON	.044 / .261	1.209 / .506	.073 / .262	.578 / .416	.004 / .249	.318 / .348
Two-stage Quest	.057 / .280	1.462 / .545	.091 / .279	.741 / .444	.005 / .256	.390 / .382
InfiniGen	.061 / .281	1.550 / .554	.099 / .279	.715 / .438	.004 / .256	.403 / .386
Fixed threshold	.054 / .281	1.439 / .538	.096 / .279	.716 / .433	.007 / .258	.384 / .385
RCR	.063 / .285	1.515 / .546	.099 / .279	.778 / .442	.012 / .258	.394 / .385
Exact every step	.063 / .282	1.538 / .553	.111 / .281	.784 / .445	.005 / .257	.387 / .388

Table 9: Reference-based CIDEr / ROUGE-L (budget 64). Dynamic methods are not separated reliably by references.

Image 2475 (forest with a dog), favourable to RCR	
Uncompressed	[. . .] The sunlight appears to be coming from behind the trees, creating a silhouette effect on the left side of the image, **where a dog is visible. The dog is standing still, facing towards the right side of the image**, and appears to be observing something in the distance. [. . .]
BACON (.33)	[. . .] with a dog prominently featured in the foreground. The dog appears to be a medium to large breed, possibly a Golden Retriever [. . .] capturing a moment of quiet companionship [. . .]
InfiniGen (.60)	[. . .] creating a silhouette effect on the left side of the image. The trees are mostly coniferous [. . .] The forest floor is not clearly visible [. . .] *(no dog is mentioned)*
RCR (1.00)	Identical to the uncompressed output.
Image 3142 (wristwatch), unfavourable to RCR	
Uncompressed	[. . .] The watch face is circular and also silver-colored, with a white background. **The hour markers on the watch face are small, circular, and also silver-colored** [. . .] The watch hands are thin and silver-colored [. . .]
BACON (.45)	[. . .] The watch face is encrusted with numerous small, round, clear gemstones [. . .] the hour markers are likely to be small, possibly diamond-like [. . .]
InfiniGen (1.00)	Identical to the uncompressed output.
RCR (.51)	[. . .] The watch face itself is circular and features a white background with **black hour markers and hands** [. . .] a small, round, and possibly decorative element at the top of the case [. . .]

Table 10: Outputs on two images; numbers are fidelity to the uncompressed output.

K Video Description (Pre-registered)

Registration and setup. Before any compressed-method video output was produced (only two full-KV smoke outputs had been seen), we registered the data, models, methods, the fixed-threshold headline rule of Appendix C, the primary comparison (fidelity, paired bootstrap against InfiniGen) and that all results are reported. Data: VideoDetailCaption from lmms-eval (Zhang et al., 2024) (499 ActivityNet (Caba Heilbron et al., 2015) videos with human detailed descriptions), 300 videos sampled evenly, benchmark prompt unchanged, 32 frames per video, frame size 448×252 for Qwen2-VL and 512×288 for Qwen3-VL (the same number of visual tokens per frame), `max_new_tokens`=512, greedy decoding. Mean prefixes are 2,205 and 2,342 tokens; uncompressed descriptions have a median of 123 and 303 words. The budget (64), BACON prefill and RCR's configuration are those of the image experiments; LLaVA-NeXT has no video input. Table 11 lists all runs.

VideoDetailCaption	Qwen2-VL	Qwen3-VL
BACON	.363 −7.9 [−9.2, −6.7]	.266 −12.6 [−13.5, −11.7]
Two-stage Quest, page 8	.423 −2.0 [−3.3, −0.7]	.365 −2.7 [−3.6, −1.9]
InfiniGen	.442	.392
Fixed τ=.12	.423 (7%) −1.9 [−3.1, −0.7]	.369 (6%) −2.3 [−3.2, −1.3]
Fixed τ=.08	**.438** (18%) −0.5 [−1.7, +0.9]	.394 (12%) +0.2 [−0.7, +1.1]
Fixed τ=.05	.461 (35%) +1.9 [+0.6, +3.2]	**.406** (23%) +1.4 [+0.6, +2.2]
Fixed τ=.03	.459 (56%) +1.6 [+0.1, +3.2]	.417 (39%) +2.5 [+1.7, +3.4]
RCR (ρ=.4)	.452 (40%) +0.9 [−0.6, +2.4]	.412 (40%) +2.0 [+1.1, +2.8]
Exact every step	.466 +2.4 [+0.9, +3.8]	.420 +2.8 [+1.9, +3.7]

Table 11: Video fidelity (300 videos, budget 64). Parentheses: refresh rate; small numbers: paired difference to InfiniGen with 95% CI. Bold: fixed-threshold headline chosen by the registered rule.

RCR versus the fixed threshold. At the nearest refresh rates, RCR minus the fixed threshold is −1.0 [−2.4, +0.5] (τ=.05, 35%) and −0.7 [−2.2, +0.8] (τ=.03, 56%) on Qwen2-VL, and −0.5 [−1.4, +0.3] (τ=.03, 39%) and +0.5 [−0.3, +1.4] (τ=.05, 23%) on Qwen3-VL. By the registered rule, the fixed-threshold headline is τ=.08 on Qwen2-VL and τ=.05 on Qwen3-VL, which RCR exceeds by 1.4 and 0.6 points at about twice their refresh rate. The correspond-

ing image comparisons at similar rates are +1.1 [−0.0, +2.3] (LLaVA DetailCaps, fixed 35%), +1.3 [−0.3, +2.9] (Qwen3 DetailCaps, 34%), +3.6 [+1.9, +5.2] (Qwen2 TextCaps, 29%), +2.9 [+1.2, +4.6] (LLaVA TextCaps, 28%) and +0.5 [−0.8, +1.7] (Qwen3 TextCaps, 44%); note that RCR also differs in detector and candidate re-selection.

Drift heterogeneity. Table 12 summarises how much per-sample mean drift varies under the fixed threshold at its headline setting.

Setting	CV	p90/p10	refresh <5%
Qwen2-VL DetailCaps	0.71	7.0	21%
Qwen3-VL DetailCaps	0.78	8.0	45%
LLaVA-NeXT DetailCaps	0.16	1.5	0%
Qwen2-VL video	0.18	1.5	1%
Qwen3-VL video	0.14	1.4	0%

Table 12: Spread of per-sample mean drift: coefficient of variation, 90th/10th percentile ratio, and share of samples refreshing on fewer than 5% of layer-steps.

L Object-Level Evaluation

We parse each output with the factual scene-graph parser used by CAPTURE (Dong et al., 2024) (FLAN-T5-base) and match objects, attributes and relations with CAPTURE's exact, synonym and embedding matching. We report CAPTURE against the three human references of each DetailCaps image, object precision and recall against the references (averaged over references), and object precision, recall and F1 against the uncompressed output of the same model. Against the uncompressed output, lower precision indicates added objects and lower recall indicates omitted ones. Table 13 lists all methods on the 300 test images; the fixed threshold is the headline setting of Table 2.

Paired differences of RCR minus InfiniGen (points, 95% CI): object F1 against the uncompressed output +1.3 [+0.2, +2.3] (Qwen2-VL), +2.5 [+1.4, +3.5] (LLaVA-NeXT), +0.7 [−0.1, +1.5] (Qwen3-VL); recall +1.2 [−0.2, +2.6], +4.8 [+3.3, +6.2], +0.9 [−0.0, +1.8]; precision +1.2 [−0.1, +2.5], −0.7 [−2.1, +0.7], +0.3 [−0.6, +1.3]; CAPTURE +0.4 [+0.1, +0.7], +0.8 [+0.4, +1.3], −0.1 [−0.3, +0.2]; object precision against the references +0.7 [−0.0, +1.4], −2.2 [−3.2, −1.2], −0.2 [−0.7, +0.4]. Against the fixed threshold, object F1 differs by +2.2 [+1.0, +3.3], +1.3 [+0.3, +2.3] and +1.9 [+1.1, +2.6].

M Implementation Details

All methods are implemented in a single module patched into the attention forward of each model (Hugging Face Transformers; Qwen2-VL and LLaVA in fp16, Qwen3-VL in bf16). RCR's configuration is: budget 64 ($c = W = 32$), BACON prefill, $\rho = 0.4$, $\tau_0 = 0.03$, $\eta = 0.05$, $R = 8$ detector channels, $4c$ candidates, and no EMA (decay 0; Appendix D). The threshold is reset for every sample, so results do not depend on sample order. Summing Eq. (2) over the N layer-level checks of a sample gives $\frac{1}{N}\sum_i m_i - \rho = (\log \tau_N - \log \tau_0)/(\eta N)$, so the realised rate approaches ρ only as N grows, consistent with the overshoot on short TextCaps outputs. DetailCaps uses 300 images sampled evenly from DetailCaps-4870 with `max_new_tokens`=512; TextCaps uses the first 500 validation images with 64. Mean prefix lengths are 852 / 1012 (Qwen2 DetailCaps / TextCaps), 1679 / 2310 (LLaVA) and 639 / 764 (Qwen3-VL). With refresh disabled, every model reproduces BACON token-for-token. With a mask-conditioned read from host memory, RCR's 64 vectors per layer, KV head and step amount to about 1.8 MB per token for Qwen2-VL-7B in fp16, or 75 μs at 25 GB/s. Code, logs and the registration files will be released.

	Qwen2-VL-7B			LLaVA-NeXT-7B			Qwen3-VL-8B		
Method	CAPTURE	P/R ref	P/R/F1 full	CAPTURE	P/R ref	P/R/F1 full	CAPTURE	P/R ref	P/R/F1 full
BACON	.602	.659/.634	.733/.702/.708	.554	.652/.539	.698/.632/.651	.611	.602/.720	.779/.721/.744
Two-stage Quest	.631	.684/.676	.802/.790/.786	.593	.694/.586	.774/.736/.745	.624	.594/.770	.818/.813/.812
InfiniGen	.631	.680/.676	.823/.815/.811	.590	.716/.573	.785/.708/.733	.627	.596/.778	.821/.819/.816
Fixed threshold	.634	.682/.686	.809/.811/.802	.592	.693/.594	.772/.737/.745	.626	.592/.777	.808/.809/.805
RCR	.635	.687/.682	.835/.827/.824	.598	.694/.597	.778/.756/.758	.626	.594/.777	.825/.827/.823
Exact every step	.634	.684/.681	.841/.835/.832	.597	.700/.596	.783/.754/.759	.626	.593/.776	.827/.831/.826
Uncompressed	.636	.683/.684	1/1/1	.607	.700/.618	.997/.997/.997	.628	.594/.780	1/1/1

Table 13: Object-level evaluation on DetailCaps (300 images, budget 64). “ref”: against the human references; “full”: against the uncompressed output. LLaVA’s uncompressed row is below 1 because one of its outputs yields no parsed objects and scores 0.