

Kolmogorov-Arnold Classifier Systems as Universal Approximators

Hiroki Shiraishi^{ID}, Hisao Ishibuchi^{ID}, *Fellow, IEEE*, and Masaya Nakata^{ID}, *Member, IEEE*

Abstract—As the input dimension n grows, rule-based machine learning, such as Learning Classifier Systems (LCSs), faces a fundamental scalability bottleneck for function approximation: both rule count and parameter count grow exponentially with n . Traditional LCSs partition the n -dimensional input space directly, requiring $O(m^n)$ rules for adequate coverage, where m is the per-variable resolution. This article breaks from this paradigm by reorganizing rules dimension-wise, guided by the Kolmogorov-Arnold representation theorem: any continuous n -dimensional function can be expressed as a finite superposition of one-dimensional functions. The proposed Kolmogorov-Arnold Classifier System (KACS) decomposes the target function into one-dimensional subproblems and assigns a dedicated ruleset to each, reducing the worst-case rule count from $O(m^n)$ to $O(mn^2)$ and replacing n -dimensional local models with one-dimensional models requiring only two parameters per rule, independent of n . We also provide the first constructive proof that an LCS, namely KACS, is a universal approximator for continuous functions on compact domains. Evaluated against a direct n -dimensional input space partitioning approach under otherwise identical conditions, KACS achieves competitive accuracy in many settings while using only 2% to 40% of the parameters. Our implementation is available at <https://github.com/YNU-NakataLab/KACS>.

Index Terms—Learning classifier systems, evolutionary rule-based machine learning, Kolmogorov-Arnold representation theorem, universal approximation, dimension-wise decomposition

I. INTRODUCTION

FUNCTION approximation, also known as regression, is the problem of constructing an approximation $\hat{f}: X \rightarrow \mathbb{R}$ from a set of training samples $\mathcal{D}_{\text{tr}} = \{(\mathbf{x}_i, y_i)\}_{i=1}^{N_{\text{tr}}}$, where $\mathbf{x}_i \in X \subseteq \mathbb{R}^n$ and $y_i \in \mathbb{R}$. The goal is to approximate an unknown target function f such that $\hat{f}(\mathbf{x}) \approx f(\mathbf{x})$ for all $\mathbf{x} \in X$. Ideally, $\hat{f}$ generalizes well to unseen inputs [1], [2]. Reliable function approximation is a core requirement in many real-world applications [3], where a model supports not only data fitting but also decision making, monitoring, and control [4], [5]. In such settings, approximation accuracy,

robustness, and multi-dimensional scalability directly affect overall performance and safety [3].

From an algorithmic viewpoint, function approximation becomes challenging when the target relationship $y = f(\mathbf{x})$ is complex. In particular, two difficulties are frequently observed:

- *Heterogeneity*: Different regions of the input space may exhibit different local behaviors, such as sharp changes, discontinuities, or region-specific nonlinearities [6], [7]. In such cases, a single global model can be difficult to train and may require high complexity to represent all local patterns simultaneously [8].
- *Multiple input variables*: Approximation becomes harder as the number of input variables increases (i.e., $n \geq 2$) [1]. Even when f is continuous, multi-dimensional spaces require many samples for adequate coverage [9], and the model class must scale without an explosive increase in parameters [2].

To address heterogeneity, local modeling and divide-and-conquer strategies have been widely studied (e.g., regression trees [10], Takagi-Sugeno fuzzy systems [11], and mixture-of-experts models [7]). Among these approaches, Learning Classifier Systems (LCSs) [12] are a representative family. LCSs are an evolutionary rule-based machine learning paradigm that represents a model as a population of IF-THEN rules [13]. Each rule covers a local region (IF-part or *antecedent*) and provides a local classification or approximation model (THEN-part or *consequent*); the final output is obtained by aggregating the predictions of matching rules. Because of this rule-based, adaptive local modeling nature, LCSs have been used as automated tools for designing classifiers and approximators [14]–[16]. For function approximation, to the best of our knowledge, all LCSs directly handle rules defined over the n -dimensional input space. For example, XCSF [17], the most widely studied Michigan-style LCS, combines evolutionary search for rule-antecedents with gradient-based online updates of rule-consequents. SupRB [18], a recently proposed Pittsburgh-style LCS, alternates between an evolutionary rule discovery phase and a batch supervised fitting of rule-consequents. Despite these architectural differences, both systems represent rules over the full n -dimensional input space.

While LCSs are effective in heterogeneous problems due to their local modeling nature [12], they still face a major scalability issue in multi-dimensional settings [19]–[22]. From a partitioning perspective, if each of the n input variables requires m effective subdivisions to achieve good accuracy, the number of local regions (and thus rules) can grow as $O(m^n)$ [19]. This growth makes both rule discovery and

Manuscript received 31 March 2026; revised 6 August 2026; accepted 11 September 2026. This work was supported by JSPS KAKENHI (Grant Nos. JP23KJ0993, JP25K03195), National Natural Science Foundation of China (Grant No. 62376115), and Guangdong Provincial Key Laboratory (Grant No. 2020B121201001). (Corresponding authors: Hisao Ishibuchi; Masaya Nakata.)

Hiroki Shiraishi was with the Graduate School of Engineering Science, Yokohama National University, Yokohama 240-8501, Japan, at the time of manuscript submission on 31 March 2026. He is now with the Digital Healthcare Research Department, Hitachi, Ltd., Tokyo 185-8601, Japan (e-mail: hiroki.shiraishi.we@hitachi.com).

Hisao Ishibuchi is with the Department of Computer Science and Engineering, Southern University of Science and Technology, Shenzhen 518055, China (e-mail: hisao@sustech.edu.cn).

Masaya Nakata is with the Faculty of Engineering, Yokohama National University, Yokohama 240-8501, Japan (e-mail: nakata-masaya-tb@ynu.ac.jp).

parameter learning increasingly costly [19], [23]. Moreover, when the rule-consequent is parameterized in an n -dimensional form (e.g., linear regression), each rule must estimate multiple parameters, which can be difficult when each local region contains limited data [1].

Based on these considerations, this article proposes a Kolmogorov-Arnold Classifier System (KACS), an LCS designed to address both heterogeneity and multi-dimensional scalability. KACS is guided by the Kolmogorov-Arnold (KA) representation theorem [24], [25]. The KA theorem states that any continuous function of n variables can be represented as a finite superposition of one-dimensional functions [25], [26]:

$$f(\mathbf{x}) = \sum_{q=1}^{2n+1} \Phi_q \left(\sum_{p=1}^n \psi_{q,p}(x_p) \right), \quad (1)$$

where $\psi_{q,p}$ are inner one-dimensional functions and Φ_q are outer one-dimensional functions.

KACS follows this KA structure and converts the original n -dimensional approximation task into learning a collection of one-dimensional functions: the inner functions $\{\psi_{q,p}\}$ and the outer functions $\{\Phi_q\}$. Instead of evolving an n -dimensional ruleset, KACS focuses on learning one-dimensional rulesets for these functions, which are then combined according to (1). Each one-dimensional ruleset is used to represent an inner or outer function. Thus, the total number of required rulesets is $n(2n+1) + (2n+1) = 2n^2 + 3n + 1$. If each ruleset has m rules, the total number of rules is $2mn^2 + 3mn + m$. This design has two advantages. First, under a fixed per-variable resolution (i.e., roughly m effective subdivisions per variable), the number of required rules is reduced from $O(m^n)$ to $O(mn^2)$ because KACS allocates rules to one-dimensional intervals rather than to n -dimensional regions (cf. Fig. 1)¹. Second, KACS replaces n -dimensional rule-consequent models with one-dimensional models, reducing the number of parameters per local model and making parameter estimation more reliable from the same training data [1]. Beyond these practical advantages, this article establishes the theoretical expressive power of KACS by proving that it is a universal approximator for continuous functions on compact domains (cf. Theorem 2) [27]. Specifically, we prove that for any continuous target function f and any desired accuracy level, there always exists a finite KACS model $\hat{f}$ that can approximate f within that accuracy.

Our contributions are as follows:

- 1) We propose KACS, a new paradigm for rule-based machine learning in which rules are organized dimension-wise rather than by partitioning only the input space (cf. Section IV). Unlike conventional LCSs (e.g., XCSF) that perform divide-and-conquer solely in the n -dimensional input space, KACS decomposes the problem into one-dimensional subproblems via the KA theorem, allocates dedicated rulesets to each subproblem, and composes them as a finite superposition. This reduces the worst-case rule count from $O(m^n)$ to $O(mn^2)$.

¹Here, m is an analytical measure of the effective resolution required by a problem, not a parameter set directly in XCSF or KACS. In practice, this resolution emerges from evolved rule coverage under the selected population budget. A larger effective m can capture finer variation but increases the rule count exponentially in n for XCSF and only linearly in m for KACS.

- 2) We prove that KACS is a universal approximator for continuous functions on compact domains. To our knowledge, this is the first universal approximation proof for any LCS (cf. Section V).
- 3) We empirically validate the proposed paradigm by holding all design choices constant except rule dimensionality. Specifically, we benchmark KACS against XCSF on artificial and real-world datasets (cf. Section VI). This controlled comparison evaluates KA-based rule organization under otherwise comparable LCS settings, and the results show consistent reductions in both approximation error and model complexity.

It should be noted that compactness and transparency are important practical properties of LCSs [18]. Predictive accuracy is not the sole objective of regression; when the target function is known, fidelity to its underlying structure may also be important. This article focuses on local modeling and scalability rather than on a comparative evaluation of global interpretability. Although individual KACS rules are one-dimensional, we do not claim that the composed KACS model is more globally interpretable than XCSF solely because it uses fewer rules or parameters. A systematic evaluation of global interpretability remains future work.

The rest of this article is organized as follows. Section II describes XCSF and the KA theorem. Section III reviews related work. Section IV presents KACS. Section V establishes the universal approximation theorem of KACS. Section VI reports experimental results, discussion, and analysis. Finally, Section VII concludes this article.

II. PRELIMINARIES

A. XCSF Classifier System

XCSF is one of the most successful Michigan-style LCSs for function approximation. It incrementally optimizes a population $\mathcal{P}$ of IF-THEN rules online, updating and evolving rules as new samples arrive. These rules collectively partition the input space, and each rule covers a local region with a linear prediction model. We next provide a brief overview of XCSF. For further details on XCSF, see [15], [17]; for complementary perspectives on LCSs, see [21], [22], [28].

1) *Rule Representation*: An n -dimensional XCSF rule² cl_k is written as

$$cl_k : \text{IF } \mathbf{x} \in C_k = \prod_{i=1}^n [l_{k,i}, u_{k,i}] \text{ THEN } P_k(\mathbf{x}) = \mathbf{w}_k^\top \mathbf{x}', \quad (2)$$

where the antecedent C_k is an n -dimensional hyperrectangle and the consequent P_k is a linear model with weight vector $\mathbf{w}_k \in \mathbb{R}^{n+1}$ and the augmented input vector $\mathbf{x}' = (1, x_1, \dots, x_n)^\top$ [17]. Alternative antecedent representations, including hyperellipsoids, are discussed in Section III-A. Each rule cl_k maintains seven bookkeeping parameters: (i) a fitness $F_k \in (0, 1]$, which represents the relative usefulness of the rule; (ii) a prediction error $\epsilon_k \geq 0$, which measures the absolute prediction error of the rule; (iii) an accuracy $\kappa_k \in (0, 1]$,

²Due to historical background, rules in LCSs, including XCSF, are called *classifiers*, though they work as approximators. To avoid this potential confusion, we use the term *rules* throughout this article.

which is computed from ϵ_k and quantifies the rule accuracy; (iv) a match set size estimate $ms_k \geq 1$, which estimates the average size of the match set in which the rule appears; (v) an experience $exp_k \in \mathbb{N}_0$, which counts how many updates the rule has received; (vi) a numerosity $num_k \in \mathbb{N}$, which records how many copies of the rule are represented by this rule; and (vii) a time stamp $ts_k \in \mathbb{N}_0$, which records when a steady-state genetic algorithm (GA) was last applied to the rule [29], [30].

2) *Algorithm*: XCSF processes one training sample $(\mathbf{x}_i, y_i)$ per iteration. First, it forms the *match set* $\mathcal{M} = \{cl_k \in \mathcal{P} \mid \mathbf{x}_i \in C_k\}$.³ If $\mathcal{M}$ is empty, a *covering* operator generates a new rule whose hyperrectangular antecedent is centered near $\mathbf{x}_i$ with random width controlled by a half-width parameter r_0 ; each dimension is independently set to the full domain $[0, 1]$ with probability $P_\#$ [31].

Each rule $cl_k \in \mathcal{M}$ then computes its prediction $\hat{y}_k = \mathbf{w}_k^\top \mathbf{x}'$ and updates its weight vector using a gradient-based method (e.g., the Widrow-Hoff delta rule [32], Adam [33]), based on the rule-specific error $y_i - \hat{y}_k$. We use Adam in XCSF to enable a fair comparison with KACS, which also uses Adam for weight updates. The prediction error ϵ_k is updated as a running mean of $|y_i - \hat{y}_k|$, and the accuracy κ_k is computed from ϵ_k relative to a threshold ϵ_0 . The fitness F_k is updated within $\mathcal{M}$ in proportion to accuracy and numerosity, so accurate rules accumulate high fitness over time [29]. The system output is the fitness-weighted average $\hat{f}(\mathbf{x}_i) = \sum_{k \in \mathcal{M}} P_k(\mathbf{x}_i) F_k / \sum_{k \in \mathcal{M}} F_k$ [17].

The GA is applied to $\mathcal{M}$ when the average time since the last GA application across rules in $\mathcal{M}$ exceeds θ_{GA} [30]. Two parents (i.e., two existing rules in $\mathcal{M}$) are chosen by tournament selection; two offspring (i.e., two new rules) are created by uniform antecedent crossover and bound mutation. The created offspring are added to the current population $\mathcal{P}$ unless a parent *subsumes* them: a parent subsumes an offspring when it is both more general (antecedent contains the offspring's) and sufficiently accurate and experienced [34]. When the total numerosity exceeds the population size limit N , rules with low fitness-adjusted deletion votes are deleted by roulette-wheel selection [29], [30].

B. Kolmogorov-Arnold Representation Theorem

The Kolmogorov-Arnold (KA) representation theorem [24], [25] gives a fundamental result about the structure of multi-variate continuous functions.

Theorem 1 (Kolmogorov-Arnold Representation Theorem). *Let $n \geq 2$ and $\mathcal{K} = [0, 1]^n$. For any continuous function $f \in C(\mathcal{K})$, there exist continuous one-dimensional functions $\psi_{q,p} : [0, 1] \rightarrow \mathbb{R}$ and $\Phi_q : \mathbb{R} \rightarrow \mathbb{R}$ such that*

$$f(\mathbf{x}) = \sum_{q=1}^{2n+1} \Phi_q \left(\sum_{p=1}^n \psi_{q,p}(x_p) \right), \quad (1)$$

where $\psi_{q,p}$ are called inner functions and Φ_q are called outer functions.

³In the LCS literature, the population and match sets are conventionally denoted by $[P]$ and $[M]$, respectively [12]; this article instead uses $\mathcal{P}$ and $\mathcal{M}$ to follow standard mathematical set notation.

Although Theorem 1 formally defines each outer function as $\Phi_q : \mathbb{R} \rightarrow \mathbb{R}$, in practice Φ_q is evaluated only at values taken by $z_q(\mathbf{x}) = \sum_{p=1}^n \psi_{q,p}(x_p)$ as $\mathbf{x}$ ranges over $\mathcal{K}$. Hence, Φ_q is only required on $\mathcal{K}_z^{(q)} := z_q(\mathcal{K}) \subseteq \mathbb{R}$. This image is a compact interval: it is compact because the continuous image of a compact set is compact [35], and it is an interval because the continuous image of the connected set $\mathcal{K}$ is connected [35], and every compact connected subset of $\mathbb{R}$ is a closed bounded interval [35].

Theorem 1 states that any n -dimensional continuous function can be represented exactly using only one-dimensional functions. Specifically, it requires $n(2n+1)$ inner functions and $2n+1$ outer functions, giving $2n^2+3n+1$ one-dimensional functions in total. This is quadratic in n , a much more favorable scaling than the exponential growth that appears in direct n -dimensional partitioning [19].

Two remarks are worth noting for the use of this theorem in KACS. First, the domain of f can always be mapped to $[0, 1]^n$ by a linear rescaling without loss of generality. Second, the theorem guarantees the *existence* of the representation, but does not specify a unique set of $\psi_{q,p}$ and Φ_q [26]; in practice, these functions need to be learned from data [36].

III. RELATED WORK

A. Multi-Dimensional Scalability in LCSs

The multi-dimensional scalability problem in LCSs, including XCSF [17], is well known. To approximate a target function with m effective subdivisions per variable in n dimensions, XCSF needs to maintain $O(m^n)$ rules in the worst case [19]. Several directions have been explored to ease this burden.

A first direction focuses on the *antecedent representation* (for a recent comprehensive review, cf. [37]). The standard hyperrectangular representation [38], [39] is axis-aligned, which forces the system to use many small rules when the true subproblem boundaries are tilted or curved [40]. Replacing hyperrectangles with hyperellipsoids via kernel functions reduces the rule count for curved boundaries [41]. Neural network-based conditions can represent even more flexible boundaries but raise the cost of rule evaluation and evolutionary search [42]. Code-fragment-based conditions, inspired by genetic programming, handle multi-dimensional problems where only a few variables are relevant [43], thereby yielding shorter and more interpretable conditions. Such representations are practically effective when real-world data have low effective dimensionality. The worst case instead corresponds to a target with strong joint dependence on all variables and fine-scale variation throughout the input space; for such problems, achieving a fixed per-variable resolution can still require exponentially many local models.

A second direction applies *dimensionality reduction* before passing the input to an LCS. Behdad et al. [44] showed that combining an LCS with principal component analysis (PCA) substantially reduces the required population size while maintaining accuracy on multi-dimensional classification tasks. Several approaches [45]–[47] have also been proposed to reduce the dimensionality of multi-dimensional inputs using autoencoders. A shared limitation is that preserving high

accuracy in the compressed representation is difficult, and any compression error can propagate into an LCS.

A third direction uses *feature selection* to reduce the effective input dimension before or during learning. Urbanowicz and Moore [48] introduced ExSTraCS 2.0, which improves scalability by incorporating expert knowledge scores based on TuRF [49] into the covering and mutation operators so that rules are biased toward more relevant features. ExSTraCS 2.0 was motivated in part by biomedical classification settings, where a multi-dimensional input may contain many irrelevant genetic attributes with only a small subset being predictive. This approach works well when many input variables are genuinely irrelevant to the target output. However, in function approximation, variables may interact and contribute jointly to the target output [50]. In such cases, feature selection cannot reduce the exponential rule count increase [19], [51], and the multi-dimensional scalability problem remains.

Unlike these approaches, KACS reorganizes rules according to the KA theorem (i.e., Theorem 1), reducing the worst-case rule count from $O(m^n)$ to $O(mn^2)$ without preprocessing.

B. Kolmogorov-Arnold Networks and Variants

A representative recent use of the KA theorem in machine learning is the Kolmogorov-Arnold Network (KAN) [36]. KAN brings the KA theorem into the neural network paradigm by replacing the fixed activation functions of a multi-layer perceptron (MLP) [27] with learnable univariate B-spline functions on the edges (i.e., connections between neurons).

Since then, several other KA-inspired variants have been proposed. Wav-KAN [52] replaces B-spline activation functions with wavelets to enable efficient capture of both high-frequency and low-frequency components through multiresolution analysis. Ensemble-KAN [53] builds multiple KANs, each using a different subset of input features, and aggregates their predictions. Chebyshev KAN [54] uses Chebyshev polynomials for improved parameter efficiency. Temporal-KAN [55] and Federated-KAN [56] extend the framework to sequential and federated learning settings, respectively.

Within the LCS community, X-KAN [14] exploits the divide-and-conquer nature of LCSs to optimize multiple local KAN models through evolutionary search. By placing a KAN model in the consequent of each n -dimensional XCSF rule, X-KAN achieves effective approximation of discontinuous functions and functions with high local complexity. These two types of functions are difficult for a single global KAN.

As explained in the brief literature review above, KAN and its variants apply the KA theorem to neural architecture design, and X-KAN uses it to design local models in rule-consequents. Our KACS in this article takes a different approach: it first applies the KA theorem to the rule organization itself within a rule-learning framework. That is, our approach in KACS and the above-mentioned approaches in existing studies operate at structurally different levels of KA application (i.e., neural architecture, rule-consequents, and rule organization).

C. Universal Approximation in Rule-Based Systems

Universal approximation has been studied across a range of model classes. For neural networks, Cybenko [27] and Hornik

et al. [57] showed that a single hidden layer of sigmoidal units is sufficient to approximate any continuous function on a compact set. Wang and Mendel [58] proved an analogous result for fuzzy systems using the Stone-Weierstrass theorem [59]. Ying [60] extended this to a broader class of fuzzy inference systems covering product, minimum, and other common t -norms. Kosko [61] gave a separate proof for additive fuzzy systems, and Castro [62] further showed that fuzzy logic controllers with arbitrary membership functions and a broad class of inference engines are universal approximators.

A practically important question is how the required number of rules scales with dimension n . Standard fuzzy systems with a uniform grid still need $O(m^n)$ rules, the same exponential cost as XCSF [19], [51]. Wang [63] showed that a hierarchical fuzzy system (HFS), which consists of several low-dimensional fuzzy systems connected in sequence, is a universal approximator whose rule count grows only linearly with n . This result is important because it shows that the exponential rule count is not an essential requirement for universal approximation.

KACS reaches a similar conclusion via the KA decomposition rather than a manually designed hierarchy, such as HFS; it achieves $O(mn^2)$ rules in a mathematically grounded two-layer structure. Furthermore, to our knowledge, no prior LCS has been proved to be a universal approximator. In contrast, this article provides the first constructive universal approximation proof for an LCS, namely KACS.

IV. KOLMOGOROV-ARNOLD CLASSIFIER SYSTEM

KACS has two main properties. First, it organizes the rule population into one-dimensional inner and outer submodels according to the KA structure. Second, it learns rule consequents through system-level backpropagation across the KA structure. The following subsections detail these characteristics.

A. Overview

Fig. 1 schematically illustrates XCSF and KACS. KACS is a Michigan-style LCS that inherits the structural framework of XCSF, including the covering mechanism, fitness-based prediction aggregation, GA, subsumption, and hyperparameter settings. By organizing rules via the KA decomposition (Theorem 1), KACS not only suppresses the exponential growth in the number of rules with dimension n , but also reduces the difficulty of optimizing consequents by learning one-dimensional local models with only two parameters per rule, independent of n . Like XCSF, KACS optimizes its rules online, updating and evolving them when a new sample arrives.

As visualized in Fig. 1, the KA decomposition in (1) reduces learning f to learning $n(2n+1)$ inner functions $\{\psi_{q,p} : [0, 1] \rightarrow \mathbb{R}\}$ and $(2n+1)$ outer functions $\{\Phi_q : \mathcal{K}_z^{(q)} \rightarrow \mathbb{R}\}$, all one-dimensional. KACS maintains a dedicated ruleset, called a *submodel*, for each one-dimensional function. All submodels live in a single population $\mathcal{P}$, partitioned into:

- $n(2n+1)$ *inner submodels* $\mathcal{P}_{q,p}^\psi$, each approximating $\psi_{q,p}$ using rules over the input domain $[0, 1]$;
- $(2n+1)$ *outer submodels* $\mathcal{P}_q^\Phi$, each approximating Φ_q using rules over the intermediate domain $\mathcal{K}_z^{(q)}$.




Fig. 1. Conceptual comparison of XCSF and KACS for $n = 2$ ($2n+1 = 5$ channels). The left panel illustrates 2-D rule regions used by XCSF, where each rule covers a rectangle in the (x_1, x_2) plane and maps $\mathbf{x}$ directly to $\hat{y}$, yielding $O(m^n)$ rules with $n+1$ consequent parameters per rule. The right panel illustrates the KACS architecture, where prediction is decomposed into one-dimensional inner submodels $\psi_{q,p}(x_p)$, intermediate sums $\hat{z}_q$, and one-dimensional outer submodels $\Phi_q(\hat{z}_q)$, which are finally summed to obtain $\hat{y}$, yielding $O(mn^2)$ rules with two consequent parameters per rule.

Given an input $\mathbf{x}$, KACS computes $\hat{y}$ through a two-stage feedforward pass. It then backpropagates the system-level loss through this structure to update the weights of all active rules jointly. This is a key departure from XCSF, which updates each rule independently using its own prediction error.

Although each inner submodel processes one variable, KACS captures epistasis through the potentially nonlinear outer function Φ_q applied to $z_q = \sum_p \psi_{q,p}(x_p)$, which couples the dimensions. This is not bi-level optimization: active inner and outer consequents are jointly updated from the system-level loss, allowing gradients through Φ_q to coordinate the inner submodels. Theorem 2 guarantees representation of continuous interactions in principle, although finite capacity and imperfect optimization may limit their learning. Algorithm 1 summarizes one complete training iteration of KACS; the following subsections describe each component in detail.

B. Rule Representation and Population

Every rule $cl_k \in \mathcal{P}$, regardless of which submodel it belongs to, has the same one-dimensional format:

$$cl_k : \text{IF } z \in C_k = [l_k, u_k] \text{ THEN } P_k(z) = w_{k,0} + w_{k,1} z, \quad (3)$$

where $C_k \subset \mathbb{R}$ is a compact interval and $\mathbf{w}_k = (w_{k,0}, w_{k,1})^T \in \mathbb{R}^2$. For inner rules $cl_k \in \mathcal{P}_{q,p}^\psi$, $z = x_p \in [0, 1]$. For outer rules $cl_k \in \mathcal{P}_q^\Phi$, $z = \hat{z}_q \in \mathcal{K}_z^{(q)}$.

A finite set of such local linear rules can represent a piecewise-linear function. This property is central to the universal approximation proof in Section V-B, but does not constrain KACS operation, permitting overlapping rules.

The weight vector always has exactly two elements regardless of n , in contrast to $n+1$ elements per rule in XCSF. Each rule cl_k maintains the same seven bookkeeping parameters as in XCSF: fitness F_k , prediction error ϵ_k , accuracy κ_k , match

set size estimate ms_k , experience exp_k , numerosity num_k , and GA time stamp ts_k .

A rule cl_k belongs to exactly one submodel, identified by its type (ψ or Φ) and index: (q, p) for inner submodels (channel index q and input-dimension index p), or q for outer submodels (channel index). The population size limit N constrains the total numerosity, i.e., $\sum_{cl_k \in \mathcal{P}} num_k \leq N$.

C. Feedforward Prediction and Covering

1) *Stage 1: Inner Function Evaluation:* For each pair (q, p) , where q is the channel index ($q \in \{1, \dots, 2n+1\}$) and p is the input-dimension index ($p \in \{1, \dots, n\}$), form the inner match set for a given input $\mathbf{x}$:

$$\mathcal{M}_{q,p}^\psi = \{cl_k \in \mathcal{P}_{q,p}^\psi \mid x_p \in C_k\}. \quad (4)$$

If $\mathcal{M}_{q,p}^\psi = \emptyset$, generate a covering rule according to (10), as described later in Section IV-C3. Compute the fitness-weighted prediction of $\psi_{q,p}$:

$$\hat{\psi}_{q,p}(x_p) = \frac{\sum_{cl_k \in \mathcal{M}_{q,p}^\psi} P_k(x_p) \cdot F_k}{\sum_{cl_k \in \mathcal{M}_{q,p}^\psi} F_k}. \quad (5)$$

Sum over p to obtain the intermediate value for channel q :

$$\hat{z}_q = \sum_{p=1}^n \hat{\psi}_{q,p}(x_p), \quad q = 1, \dots, 2n+1. \quad (6)$$

2) *Stage 2: Outer Function Evaluation:* For each channel index q , form the outer match set for the obtained intermediate value $\hat{z}_q$:

$$\mathcal{M}_q^\Phi = \{cl_k \in \mathcal{P}_q^\Phi \mid \hat{z}_q \in C_k\}. \quad (7)$$

Algorithm 1 One training iteration of KACS

Require: Sample $(\mathbf{x}, y)$, population $\mathcal{P}$, iteration t
Ensure: Updated $\mathcal{P}$

```

Step 1: Feedforward ▷ Section IV-C
1: for  $q = 1$  to  $2n + 1$  do
2:   for  $p = 1$  to  $n$  do
3:     Form  $\mathcal{M}_{q,p}^\psi$  (4); cover if empty (10)
4:     Compute  $\hat{\psi}_{q,p}(x_p)$  (5)
5:   end for
6:   Compute  $\hat{z}_q$  as  $\hat{z}_q \leftarrow \sum_p \hat{\psi}_{q,p}(x_p)$  (6)
7:   Form  $\mathcal{M}_q^\Phi$  (7); cover if empty (11)
8:   Compute  $\hat{\Phi}_q(\hat{z}_q)$  (8)
9: end for
10: Compute  $\hat{y}$  as  $\hat{y} \leftarrow \sum_q \hat{\Phi}_q(\hat{z}_q)$  (9)

Step 2: Backpropagation ▷ Section IV-D
11: Form  $\mathcal{M}_{\text{act}}$  as  $\mathcal{M}_{\text{act}} = (\bigcup_{q,p} \mathcal{M}_{q,p}^\psi) \cup (\bigcup_q \mathcal{M}_q^\Phi)$  (12)
12: for each  $cl_k \in \mathcal{M}_{\text{act}}$  do
13:   Compute  $\mathbf{g}_k$  via (13) or (14)
14:   Update  $\mathbf{w}_k$  via Adam (15)–(16)
15: end for

Step 3: Parameter update ▷ Section IV-E
16: for each  $cl_k \in \mathcal{M}_{\text{act}}$  do
17:   Update  $\text{exp}_k$  as  $\text{exp}_k \leftarrow \text{exp}_k + 1$ 
18:   Update  $\epsilon_k, \kappa_k, F_k, \text{ms}_k$  within submodel  $\mathcal{M}$  via (17)–(20)
19: end for

Step 4: GA and subsumption ▷ Section IV-F
20: for each  $\mathcal{M} \in \{\mathcal{M}_{q,p}^\psi\} \cup \{\mathcal{M}_q^\Phi\}$  do
21:   if  $t - \sum_{cl_k \in \mathcal{M}} \text{num}_k \cdot \text{ts}_k / \sum_{cl_k \in \mathcal{M}} \text{num}_k > \theta_{\text{GA}}$  then
22:     Update  $\text{ts}_k$  as  $\text{ts}_k \leftarrow t$  for  $cl_k \in \mathcal{M}$ 
23:     Select  $cl_{p_1}, cl_{p_2}$  by tournament
24:     Copy to  $cl_{o_1}, cl_{o_2}$ ; apply crossover and mutation
25:     Initialize offspring parameters
26:     Attempt subsumption by parents; add survivors to  $\mathcal{P}$ 
27:   while  $\sum_k \text{num}_k > N$  do
28:     Delete by roulette-wheel on (21)
29:   end while
30: end if
31: end for

```

If $\mathcal{M}_q^\Phi = \emptyset$, generate a covering rule according to (11), as described later in Section IV-C3. Compute the fitness-weighted prediction of Φ_q :

$$\hat{\Phi}_q(\hat{z}_q) = \frac{\sum_{cl_k \in \mathcal{M}_q^\Phi} P_k(\hat{z}_q) \cdot F_k}{\sum_{cl_k \in \mathcal{M}_q^\Phi} F_k}. \quad (8)$$

Sum over q to obtain the final system prediction:

$$\hat{y} = \hat{f}(\mathbf{x}) = \sum_{q=1}^{2n+1} \hat{\Phi}_q(\hat{z}_q). \quad (9)$$

Stage 2 requires the intermediate values $\hat{z}_q$ in (6). Thus, KACS first completes Stage 1 for all (q, p) pairs and then proceeds to Stage 2. Within each stage, the submodels are independent and can be evaluated in any order (and also in parallel).⁴

3) *Covering*: When a submodel match set is empty, a new rule cl_{cov} is generated to ensure every input is always matched.

For inner submodel $\mathcal{P}_{q,p}^\psi$ with uncovered $x_p \in [0, 1]$:

$$(l_{\text{cov}}, u_{\text{cov}}) = (\max(0, x_p - \mathcal{U}(0, r_0]), \min(1, x_p + \mathcal{U}(0, r_0])), \quad (10)$$

where $r_0 \in (0, 1]$ is the maximum covering half-width. With probability $P_\# \in [0, 1]$, a maximally general rule is generated instead, by setting $(l_{\text{cov}}, u_{\text{cov}}) = (0, 1)$ as in XCSF.

For outer submodel $\mathcal{P}_q^\Phi$ with uncovered $\hat{z}_q \in \mathcal{K}_z^{(q)} \subseteq \mathbb{R}$, the maximally general option is inapplicable because $\mathcal{K}_z^{(q)}$ is not known a priori. The antecedent is set to:

$$(l_{\text{cov}}, u_{\text{cov}}) = (\hat{z}_q - \mathcal{U}(0, r_0], \hat{z}_q + \mathcal{U}(0, r_0]). \quad (11)$$

In both cases, the new rule is initialized as follows: the consequent weight vector $\mathbf{w}_{\text{cov}}$ is sampled i.i.d. from $\mathcal{U}[-1, 1]$ for each element, $\epsilon_{\text{cov}} = 0$, $F_{\text{cov}} = 0.01$, $\text{ms}_{\text{cov}} = 1$, $\text{exp}_{\text{cov}} = 0$, $\text{num}_{\text{cov}} = 1$, with its time stamp ts_{cov} set to the current iteration t , and is added to both its submodel and $\mathcal{P}$.

D. Consequent Update by Backpropagation

After computing $\hat{y}$, KACS updates the weight vectors of all active rules by backpropagating the system-level loss through (9). Define the loss as $\mathcal{L} = \frac{1}{2}(y - \hat{y})^2$ and the set of all active rules as

$$\mathcal{M}_{\text{act}} = \left(\bigcup_{q,p} \mathcal{M}_{q,p}^\psi \right) \cup \left(\bigcup_q \mathcal{M}_q^\Phi \right). \quad (12)$$

1) *Gradient for Outer Rules*: For $cl_k \in \mathcal{M}_q^\Phi$, differentiating $\mathcal{L}$ through (9) and (8) gives:

$$\begin{aligned} \frac{\partial \mathcal{L}}{\partial \mathbf{w}_k} &= \frac{\partial \mathcal{L}}{\partial \hat{y}} \cdot \frac{\partial \hat{y}}{\partial \hat{\Phi}_q(\hat{z}_q)} \cdot \frac{\partial \hat{\Phi}_q(\hat{z}_q)}{\partial P_k(\hat{z}_q)} \cdot \frac{\partial P_k(\hat{z}_q)}{\partial \mathbf{w}_k} \\ &= -(y - \hat{y}) \cdot \frac{F_k}{\sum_{cl_{k'} \in \mathcal{M}_q^\Phi} F_{k'}} \cdot \hat{\mathbf{z}}'_q, \end{aligned} \quad (13)$$

where $\hat{\mathbf{z}}'_q = (1, \hat{z}_q)^\top$.

2) *Gradient for Inner Rules*: For $cl_k \in \mathcal{M}_{q,p}^\psi$, the gradient must pass through the outer stage because $\hat{z}_q$ enters (8). Applying the chain rule through (9)→(8)→(6)→(5):

$$\begin{aligned} \frac{\partial \mathcal{L}}{\partial \mathbf{w}_k} &= \frac{\partial \mathcal{L}}{\partial \hat{y}} \cdot \frac{\partial \hat{y}}{\partial \hat{\Phi}_q(\hat{z}_q)} \cdot \frac{\partial \hat{\Phi}_q(\hat{z}_q)}{\partial \hat{z}_q} \\ &\quad \cdot \frac{\partial \hat{z}_q}{\partial \hat{\psi}_{q,p}(x_p)} \cdot \frac{\partial \hat{\psi}_{q,p}(x_p)}{\partial P_k(x_p)} \cdot \frac{\partial P_k(x_p)}{\partial \mathbf{w}_k} \\ &= -(y - \hat{y}) \cdot \frac{\sum_{cl_j \in \mathcal{M}_q^\Phi} w_{j,1} \cdot F_j}{\sum_{cl_j \in \mathcal{M}_q^\Phi} F_j} \cdot \frac{F_k}{\sum_{cl_{k'} \in \mathcal{M}_{q,p}^\psi} F_{k'}} \cdot \mathbf{x}'_p, \end{aligned} \quad (14)$$

where $\mathbf{x}'_p = (1, x_p)^\top$.

3) *Adam Update*: Each rule $cl_k \in \mathcal{M}_{\text{act}}$ maintains its own first and second moment vectors $\mathbf{m}_k, \mathbf{v}_k \in \mathbb{R}^2$, both initialized to $\mathbf{0}$ when the rule is first created. Here, t_k denotes a *rule-local* Adam time step, defined as $t_k = \text{exp}_k + 1$ at the moment of updating cl_k . We use +1 because newly created rules (by covering or the GA) have $\text{exp}_k = 0$ before their first gradient update. At iteration t , after computing $\mathbf{g}_k = \partial \mathcal{L} / \partial \mathbf{w}_k$:

$$\mathbf{m}_k \leftarrow \beta_1 \mathbf{m}_k + (1 - \beta_1) \mathbf{g}_k, \quad \mathbf{v}_k \leftarrow \beta_2 \mathbf{v}_k + (1 - \beta_2) \mathbf{g}_k^2, \quad (15)$$

$$\mathbf{w}_k \leftarrow \mathbf{w}_k - \eta \frac{\mathbf{m}_k / (1 - \beta_1^{t_k})}{\sqrt{\mathbf{v}_k / (1 - \beta_2^{t_k}) + \epsilon_{\text{Adam}}}}, \quad (16)$$

where squaring and the square root in (15)–(16) are elementwise. We use the default values recommended in [33]: $\eta = 0.001$, $\beta_1 = 0.9$, $\beta_2 = 0.999$, and $\epsilon_{\text{Adam}} = 10^{-8}$.

⁴Under an idealized rule-allocation assumption with m rules per local region or KACS submodel, the worst-case inference complexities of XCSF and KACS scale as $\mathcal{O}(nm^m)$ and $\mathcal{O}(mn^2)$, respectively. For further details, see Section S1 of the supplementary material.

E. Parameter Update

After the gradient update, the following bookkeeping parameters are updated for all $cl_k \in \mathcal{M}_{\text{act}}$.

First, the experience is updated as $\exp_k \leftarrow \exp_k + 1$.

Next, the prediction error is updated. Unlike XCSF, which uses each rule's individual error $|y - \hat{y}_k|$, KACS uses the system-level error for all rules because each rule contributes to $\hat{y}$ as part of a larger structure, and its individual output is not directly comparable to y :

$$\epsilon_k \leftarrow \epsilon_k + \beta (|y - \hat{y}| - \epsilon_k), \quad (17)$$

with learning rate $\beta \in (0, 1]$.

Then, the accuracy is calculated as:

$$\kappa_k = \begin{cases} 1, & \text{if } \epsilon_k < \epsilon_0, \\ \alpha (\epsilon_k / \epsilon_0)^{-\nu}, & \text{otherwise,} \end{cases} \quad (18)$$

with error threshold $\epsilon_0 > 0$, accuracy fall-off rate $\alpha \in [0, 1]$, accuracy exponent $\nu > 0$.

After that, the fitness is updated within the *submodel* match set $\mathcal{M} \in \{\mathcal{M}_{q,p}^\psi\} \cup \{\mathcal{M}_q^\phi\}$, not across all active rules. For $cl_k \in \mathcal{M}$:

$$F_k \leftarrow F_k + \beta \left(\frac{\kappa_k \cdot \text{num}_k}{\sum_{cl_{k'} \in \mathcal{M}} \kappa_{k'} \cdot \text{num}_{k'}} - F_k \right). \quad (19)$$

This per-submodel update ensures that the fitness of a rule reflects its accuracy relative to other rules competing to approximate the same component function.

Finally, the match set size estimate is updated as:

$$\text{ms}_k \leftarrow \text{ms}_k + \beta \left(\sum_{cl_{k'} \in \mathcal{M}} \text{num}_{k'} - \text{ms}_k \right). \quad (20)$$

F. Genetic Algorithm and Subsumption

For each active submodel match set $\mathcal{M}$, the GA is activated when $t - \sum_{cl_k \in \mathcal{M}} \text{num}_k \cdot \text{ts}_k / \sum_{cl_k \in \mathcal{M}} \text{num}_k > \theta_{\text{GA}}$. When triggered, the time stamp is updated as $\text{ts}_k \leftarrow t$ for all $cl_k \in \mathcal{M}$. In the GA, two parents cl_{p_1} and cl_{p_2} are selected from $\mathcal{M}$ by tournament selection with tournament size τ . Two offspring cl_{o_1} and cl_{o_2} are initialized as copies of cl_{p_1} and cl_{p_2} . With probability χ , crossover is applied: l_{o_1} and l_{o_2} are swapped with probability 0.5, and the same is done for u_{o_1} and u_{o_2} . If crossover yields an invalid interval (i.e., $l_{o_i} > u_{o_i}$ for $i \in \{1, 2\}$), then l_{o_i} and u_{o_i} are swapped so that $l_{o_i} \leq u_{o_i}$. With probability μ per bound, mutation is applied: add $\mathcal{U}[-m_0, m_0]$ to each of l_{o_i} and u_{o_i} for $i \in \{1, 2\}$, where $m_0 > 0$ is the mutation magnitude. For inner rules, both bounds are clipped to $[0, 1]$. For outer rules, no clipping is applied. After crossover and mutation, for $i \in \{1, 2\}$, set $\epsilon_{o_i} \leftarrow \frac{1}{2}(\epsilon_{p_1} + \epsilon_{p_2})$, $F_{o_i} \leftarrow 0.1 \times \frac{1}{2}(F_{p_1} + F_{p_2})$, $\exp_{o_i} = 0$, and $\text{num}_{o_i} = 1$.

Before adding an offspring $cl_o \in \{cl_{o_1}, cl_{o_2}\}$ to $\mathcal{P}$, each parent cl_p attempts to subsume it. Subsumption occurs when all the following three conditions are satisfied: (i) $[l_o, u_o] \subseteq [l_p, u_p]$; (ii) $\epsilon_p < \epsilon_o$; and (iii) $\exp_p > \theta_{\text{sub}}$. If subsumed, $\text{num}_p \leftarrow \text{num}_p + \text{num}_o$ and cl_o is discarded.

After inserting surviving offspring, while $\sum_{cl_k \in \mathcal{P}} \text{num}_k > N$, one rule is deleted by roulette-wheel selection with vote

$$d_k = \begin{cases} \text{ms}_k \cdot \text{num}_k \cdot \bar{F} / F_k, & \exp_k > \theta_{\text{del}} \text{ and } F_k < \delta \bar{F}, \\ \text{ms}_k \cdot \text{num}_k, & \text{otherwise,} \end{cases} \quad (21)$$

where $\bar{F} = \sum_{k \in \mathcal{P}} F_k / N$, $\theta_{\text{del}} > 0$ is the deletion threshold, and $\delta \in (0, 1]$. The numerosity of the selected rule is decreased by one; any rule with $\text{num}_k = 0$ is removed from $\mathcal{P}$.

V. UNIVERSAL APPROXIMATION THEOREM OF KACS

A. Assumptions and Main Theorem

The proof in this section concerns the *expressive power* of KACS, not the behavior of its learning algorithm. The following two assumptions make this scope precise.

Assumption 1 (Target function). *The target function f is a real-valued continuous function defined on the compact set $\mathcal{K} = [0, 1]^n$, i.e., $f \in C(\mathcal{K})$.*

Assumption 2 (Existence (not learnability)). *This assumption concerns representational existence rather than algorithmic learnability. The proof is an existence theorem for the expressive power of KACS. We assume that KACS can represent and store any rule cl_k with any compact interval $C_k = [l_k, u_k]$ as its antecedent, any linear function $P_k(z) = w_{k,0} + w_{k,1}z$ as its consequent, and any fitness value $F_k \in (0, 1]$. This is the same standard assumption adopted in universal approximation proofs for neural networks [27] and fuzzy systems [60], where arbitrary weights or membership functions are assumed to be expressible. It does not guarantee that the online updates and GA find such rules.*

Under these assumptions, the main theorem is stated as follows.

Theorem 2 (Universal Approximation of KACS). *Let $\mathcal{F}_{\text{KACS}}$ be the set of all functions $\hat{f}$ expressible by KACS models on $\mathcal{K} = [0, 1]^n$ as defined in Section IV. Then $\mathcal{F}_{\text{KACS}}$ is dense in $C(\mathcal{K})$. That is, for any $f \in C(\mathcal{K})$ and any $\varepsilon > 0$, there exists $\hat{f} \in \mathcal{F}_{\text{KACS}}$ such that*

$$\sup_{\mathbf{x} \in \mathcal{K}} |f(\mathbf{x}) - \hat{f}(\mathbf{x})| < \varepsilon. \quad (22)$$

The proof uses the following two-step strategy.

- 1) Step 1 (Section V-B): We prove that a KACS ruleset operating on a one-dimensional compact interval, referred to as a *1D KACS submodel*, is itself a universal approximator for $C([a, b])$.
- 2) Step 2 (Section V-C): We apply the KA representation theorem (Theorem 1) to extend the one-dimensional result to n dimensions, thereby proving Theorem 2.

B. Step 1: 1D KACS Submodel as a Universal Approximator

A *1D KACS submodel* $\hat{g}$ is a KACS ruleset defined on a one-dimensional compact interval $I = [a, b] \subset \mathbb{R}$. Each rule $cl_k \in \mathcal{P}$ has the form given in (3), and the output for a given $z \in I$ is

$$\hat{g}(z) = \frac{\sum_{cl_k \in \mathcal{M}(z)} P_k(z) \cdot F_k}{\sum_{cl_k \in \mathcal{M}(z)} F_k}, \quad \mathcal{M}(z) = \{cl_k \in \mathcal{P} \mid z \in C_k\}, \quad (23)$$

which matches (5) and (8) in the one-dimensional case. Let $\mathcal{G}_{\text{KACS}}^{\text{1D}}$ denote the set of all functions expressible by 1D KACS submodels on I .

Theorem 3 (1D Universal Approximation). $\mathcal{G}_{\text{KACS}}^{\text{1D}}$ is dense in $C(I)$. That is, for any $g \in C(I)$ and any $\varepsilon > 0$, there exists $\hat{g} \in \mathcal{G}_{\text{KACS}}^{\text{1D}}$ such that $\sup_{z \in I} |g(z) - \hat{g}(z)| < \varepsilon$.

As noted in Section IV-B, the proof uses piecewise-linear approximation as a bridge from local linear rules to arbitrary continuous functions.

Theorem 4 (Piecewise Linear Approximation [35], [64]). For any $g \in C(I)$ and any $\varepsilon > 0$, there exists a continuous piecewise linear function $h \in \text{CPL}(I)$ such that $\sup_{z \in I} |g(z) - h(z)| < \varepsilon$, where $\text{CPL}(I)$ is the set of continuous functions on I that are linear on each subinterval of a finite partition of I .

Theorem 4 reduces the proof of Theorem 3 to the following lemma.

Lemma 1. For any $h \in \text{CPL}(I)$ and any $\varepsilon > 0$, there exists $\hat{g} \in \mathcal{G}_{\text{KACS}}^{\text{1D}}$ such that $\sup_{z \in I} |h(z) - \hat{g}(z)| < \varepsilon/2$.

Proof. Since $h \in \text{CPL}(I)$, there is a finite partition $a = z_0 < z_1 < \dots < z_M = b$ of I into M subintervals $R_j = [z_{j-1}, z_j]$ such that h restricts to a linear function $h_j(z) = a_j z + b_j$ on each R_j .

For each subinterval R_j ($j = 1, \dots, M$), we place a *reference rule* cl_j^* in $\mathcal{P}$ with antecedent $C_j^* = R_j$ and consequent $P_j^*(z) = h_j(z)$. Since h_j is linear, this satisfies (3) under Assumption 2. The ruleset $\mathcal{P}$ may additionally contain any finite number of rules $\{cl_k\}_{k \neq j}$ with arbitrary consequents, provided their antecedents are compact intervals and their fitnesses satisfy $F_k \in (0, 1]$.

Fix any $z \in I$. Since $z \in R_j$ for some j , the reference rule cl_j^* is guaranteed to match. If z lies on a breakpoint z_j , continuity of h gives $h_j(z_j) = h_{j+1}(z_j)$, so either reference rule yields the same value and the argument is unaffected. Applying the triangle inequality:

$$|h(z) - \hat{g}(z)| \leq \underbrace{|h_j(z) - P_j^*(z)|}_{(A)} + \underbrace{|P_j^*(z) - \hat{g}(z)|}_{(B)}. \quad (24)$$

Here, (A) denotes the *reference rule error*, which measures the local approximation error of the selected reference rule cl_j^* on the interval R_j ; (B) denotes the *aggregated error*, which captures the additional error induced by the fitness-weighted aggregation with the other matching rules $\{cl_k\}$. We show that both (A) and (B) can be made less than $\varepsilon/4$, so their sum is less than $\varepsilon/2$.

(A) *Reference Rule Error.* By construction $P_j^*(z) = h_j(z)$, so

$$(A) = |h_j(z) - P_j^*(z)| = 0 < \frac{\varepsilon}{4}. \quad (25)$$

(B) *Aggregated Error.* Substituting (23) and separating the reference rule cl_j^* :

$$\begin{aligned} |P_j^*(z) - \hat{g}(z)| &= \left| \frac{\sum_{cl_k \in \mathcal{M}(z)} (P_j^*(z) - P_k(z)) \cdot F_k}{\sum_{cl_k \in \mathcal{M}(z)} F_k} \right| \\ &\leq \frac{\sum_{cl_k \in \mathcal{M}(z) \setminus \{cl_j^*\}} |P_j^*(z) - P_k(z)| \cdot F_k}{F_j^* + \sum_{cl_k \in \mathcal{M}(z) \setminus \{cl_j^*\}} F_k}. \end{aligned} \quad (26)$$

Since all consequents are linear on the compact set I , the quantity $\Lambda = \max_{1 \leq j \leq M} \max_{1 \leq k \leq |\mathcal{P}|} \sup_{z \in I} |P_j^*(z) - P_k(z)|$ is finite. Set $F_j^* = F_{\text{ref}} \in (0, 1]$ and $F_k = \delta \in (0, 1]$ for all $k \neq j$. Since $|\mathcal{M}(z) \setminus \{cl_j^*\}| \leq |\mathcal{P}| - 1$, (26) gives

$$|P_j^*(z) - \hat{g}(z)| \leq \Lambda \cdot \frac{(|\mathcal{P}| - 1) \delta}{F_{\text{ref}} + (|\mathcal{P}| - 1) \delta} = \sigma(\gamma), \quad (27)$$

where $\gamma = \delta/F_{\text{ref}}$ and $\sigma(\gamma) = \Lambda \cdot \frac{(|\mathcal{P}| - 1)\gamma}{1 + (|\mathcal{P}| - 1)\gamma}$. Since $\lim_{\gamma \rightarrow 0^+} \sigma(\gamma) = 0$, the ε - δ definition of the limit guarantees that, for any $E > 0$, there exists $\Delta > 0$ such that $0 < \gamma < \Delta \Rightarrow \sigma(\gamma) < E$. In particular, setting $E = \varepsilon/4$ yields $0 < \gamma < \Delta \Rightarrow \sigma(\gamma) < \varepsilon/4$. Choosing $\delta > 0$ sufficiently small and F_{ref} sufficiently close to 1 so that $\gamma = \delta/F_{\text{ref}} < \Delta$ yields

$$(B) = |P_j^*(z) - \hat{g}(z)| \leq \sigma(\gamma) < \frac{\varepsilon}{4}. \quad (28)$$

Combining (A) and (B). Substituting (25) and (28) into (24) gives

$$\sup_{z \in I} |h(z) - \hat{g}(z)| < \frac{\varepsilon}{4} + \frac{\varepsilon}{4} = \frac{\varepsilon}{2}. \quad (29)$$

This completes the proof of Lemma 1. $\square$

Proof of Theorem 3. Let $g \in C(I)$ and $\varepsilon > 0$. By Theorem 4 with $\varepsilon/2$, there exists $h \in \text{CPL}(I)$ with $\sup_{z \in I} |g(z) - h(z)| < \varepsilon/2$. By Lemma 1 with ε , there exists $\hat{g} \in \mathcal{G}_{\text{KACS}}^{\text{1D}}$ with $\sup_{z \in I} |h(z) - \hat{g}(z)| < \varepsilon/2$. The triangle inequality gives

$$\begin{aligned} \sup_{z \in I} |g(z) - \hat{g}(z)| &\leq \sup_{z \in I} |g(z) - h(z)| + \sup_{z \in I} |h(z) - \hat{g}(z)| \\ &< \frac{\varepsilon}{2} + \frac{\varepsilon}{2} = \varepsilon. \end{aligned} \quad (30)$$

This completes the proof of Theorem 3. $\square$

C. Step 2: Extension to n Dimensions

Proof of Theorem 2. Let $f \in C(\mathcal{K})$ and $\varepsilon > 0$. By Theorem 1, there exist continuous functions $\psi_{q,p} : [0, 1] \rightarrow \mathbb{R}$ and $\Phi_q : \mathcal{K}_z^{(q)} \rightarrow \mathbb{R}$ such that $f(\mathbf{x}) = \sum_{q=1}^{2n+1} \Phi_q(z_q)$, where $z_q = \sum_{p=1}^n \psi_{q,p}(x_p)$ and $\mathcal{K}_z^{(q)} = \{\sum_{p=1}^n \psi_{q,p}(x_p) \mid \mathbf{x} \in \mathcal{K}\} \subset \mathbb{R}$ is a compact interval.

Define $\hat{f}(\mathbf{x}) = \sum_{q=1}^{2n+1} \hat{\Phi}_q(\hat{z}_q)$, where $\hat{z}_q = \sum_p \hat{\psi}_{q,p}(x_p)$. For all $\mathbf{x} \in \mathcal{K}$,

$$\begin{aligned} |f(\mathbf{x}) - \hat{f}(\mathbf{x})| &= \left| \sum_{q=1}^{2n+1} \Phi_q(z_q) - \sum_{q=1}^{2n+1} \hat{\Phi}_q(\hat{z}_q) \right| \\ &\leq \sum_{q=1}^{2n+1} \underbrace{|\Phi_q(z_q) - \Phi_q(\hat{z}_q)|}_{(C)} + \underbrace{|\Phi_q(\hat{z}_q) - \hat{\Phi}_q(\hat{z}_q)|}_{(D)}. \end{aligned} \quad (31)$$

Here, (C) is the *inner approximation error*: the error in Φ_q 's input caused by replacing the true intermediate value z_q with its approximation $\hat{z}_q$; (D) is the *outer approximation error*: the error from approximating Φ_q itself by the 1D KACS submodel $\hat{\Phi}_q$. We show that both (C) and (D) are bounded by $\varepsilon/(2(2n+1))$ for each q , so the total is at most ε .

(C) *Inner Approximation Error.* KACS computes intermediate values $z_q = \sum_p \psi_{q,p}(x_p)$ and feeds them into the outer

function Φ_q . Because each $\psi_{q,p}$ is replaced by an approximation $\hat{\psi}_{q,p}$, the resulting intermediate value $\hat{z}_q = \sum_p \hat{\psi}_{q,p}(x_p)$ may deviate from z_q and could fall outside the range $\mathcal{K}_z^{(q)}$ on which Φ_q was originally analyzed. Error (C) quantifies the impact of this deviation: $|\Phi_q(z_q) - \Phi_q(\hat{z}_q)|$. We now bound this error.

Fix any distance $r > 0$ as the enlargement width around $\mathcal{K}_z^{(q)}$, and define the *enlarged* compact interval

$$\tilde{\mathcal{K}}_z^{(q)} = \{t \in \mathbb{R} \mid \text{dist}(t, \mathcal{K}_z^{(q)}) \leq r\}, \quad (32)$$

where $\text{dist}(t, S) = \inf_{s \in S} |t - s|$ denotes the distance from the point t to the set S [35], [64]. Concretely, if $\mathcal{K}_z^{(q)} = [a, b]$, then $\tilde{\mathcal{K}}_z^{(q)} = [a - r, b + r]$, which is again a compact interval [35]. This enlarged set acts as a *safety buffer*: any $\hat{z}_q$ that stays within distance r of the true value z_q is guaranteed to remain inside $\tilde{\mathcal{K}}_z^{(q)}$, where Φ_q is still well-defined.

Since Φ_q is continuous on the compact set $\tilde{\mathcal{K}}_z^{(q)}$, it is *uniformly continuous* there by the Heine-Cantor theorem [35]. Precisely, for the target accuracy $\delta_\Phi = \varepsilon/(2(2n+1))$, there exists $\delta_z^* > 0$ such that

$$t_1, t_2 \in \tilde{\mathcal{K}}_z^{(q)}, \quad |t_1 - t_2| < \delta_z^* \implies |\Phi_q(t_1) - \Phi_q(t_2)| < \delta_\Phi. \quad (33)$$

Define $\delta_z = \min(\delta_z^*, r)$. Because $\delta_z \leq \delta_z^*$, condition (33) remains valid for any pair with $|t_1 - t_2| < \delta_z$. Because $\delta_z \leq r$, any deviation of $\hat{z}_q$ from z_q smaller than δ_z is also smaller than r , keeping $\hat{z}_q$ inside $\tilde{\mathcal{K}}_z^{(q)}$ (verified in the next paragraph). Distributing the budget equally among n inner functions, set $\delta_\psi = \delta_z/n$. By Theorem 3, for each pair (q, p) there exists a 1D submodel $\hat{\psi}_{q,p}$ with

$$\sup_{x_p \in [0,1]} |\psi_{q,p}(x_p) - \hat{\psi}_{q,p}(x_p)| < \delta_\psi. \quad (34)$$

Applying the triangle inequality gives

$$|z_q - \hat{z}_q| \leq \sum_{p=1}^n |\psi_{q,p}(x_p) - \hat{\psi}_{q,p}(x_p)| < n \cdot \delta_\psi = \delta_z \leq r. \quad (35)$$

Since $z_q \in \mathcal{K}_z^{(q)} \subseteq \tilde{\mathcal{K}}_z^{(q)}$ and the deviation is less than r , it follows that $\hat{z}_q \in \tilde{\mathcal{K}}_z^{(q)}$.

Both z_q and $\hat{z}_q$ lie in $\tilde{\mathcal{K}}_z^{(q)}$, and $|z_q - \hat{z}_q| < \delta_z \leq \delta_z^*$. Applying (33) with $t_1 = z_q$ and $t_2 = \hat{z}_q$ yields

$$(C) = |\Phi_q(z_q) - \Phi_q(\hat{z}_q)| < \delta_\Phi = \frac{\varepsilon}{2(2n+1)}. \quad (36)$$

(D) *Outer Approximation Error.* Since $\Phi_q \in C(\tilde{\mathcal{K}}_z^{(q)})$, Theorem 3 applied on the compact interval $\tilde{\mathcal{K}}_z^{(q)}$ gives a 1D submodel $\hat{\Phi}_q$ such that

$$\sup_{t \in \tilde{\mathcal{K}}_z^{(q)}} |\Phi_q(t) - \hat{\Phi}_q(t)| < \delta_\Phi = \frac{\varepsilon}{2(2n+1)}. \quad (37)$$

Since $\hat{z}_q(\mathbf{x}) \in \tilde{\mathcal{K}}_z^{(q)}$ for all $\mathbf{x} \in \mathcal{K}$ (established above), evaluating at $t = \hat{z}_q(\mathbf{x})$ yields

$$(D) = |\Phi_q(\hat{z}_q) - \hat{\Phi}_q(\hat{z}_q)| < \delta_\Phi = \frac{\varepsilon}{2(2n+1)}. \quad (38)$$

Total Error. Substituting into (31),

$$\begin{aligned} \sup_{\mathbf{x} \in \mathcal{K}} |f(\mathbf{x}) - \hat{f}(\mathbf{x})| &< \sum_{q=1}^{2n+1} \left[\frac{\varepsilon}{2(2n+1)} + \frac{\varepsilon}{2(2n+1)} \right] \\ &= \sum_{q=1}^{2n+1} \frac{\varepsilon}{2n+1} = \varepsilon. \end{aligned} \quad (39)$$

This completes the proof of Theorem 2.⁵ $\square$

Theorem 2 also holds for consequent models that represent linear functions exactly or approximate them arbitrarily well; see Section S2 of the supplementary material.

VI. EXPERIMENTS

A. Experimental Setup

1) *Methods, Metrics, and Objective:* We compare two LCSs: (i) XCSF, which uses n -dimensional rules with linear consequents, and (ii) KACS, which uses one-dimensional rules with linear consequents via KA-based decomposition.

We evaluate each method using three metrics: model accuracy, model complexity, and the accuracy-complexity trade-off.

- *Model Accuracy.* We track MAE (mean absolute error) on training and testing data.
- *Model Complexity.* We count the number of macro-rules $|\mathcal{P}|$ and the total number of parameters k in $\mathcal{P}$.
- *Accuracy-Complexity Trade-off.* We use AIC (Akaike Information Criterion) to capture the balance between accuracy and complexity. Under the Gaussian error assumption, AIC is computed as [65]:

$$\text{AIC} = N_{\text{tr}} \ln \left(\sum_{i=1}^{N_{\text{tr}}} (y_i - \hat{y}_i)^2 / N_{\text{tr}} \right) + 2(k+1), \quad (40)$$

where N_{tr} is the number of training samples, k is the number of model parameters, and the extra +1 accounts for the estimated noise variance $\hat{\sigma}^2$.

The parameter count k , also used in AIC, is defined as the total number of consequent weight parameters across all rules, i.e., $k = |\mathcal{P}| \times (d+1)$, where d is the input dimension of each rule ($d = n$ for XCSF; $d = 1$ for KACS). Hence, for fixed n , k scales linearly with $|\mathcal{P}|$ for both methods.

The objective of this comparison is to evaluate KA-based rule organization, which replaces n -dimensional XCSF rules with one-dimensional KACS rulesets while keeping the surrounding LCS framework as comparable as possible.

For this reason, XCSF is used as the primary baseline: it is the most established LCS for function approximation and enables a controlled comparison in which the key difference is rule dimensionality rather than unrelated architectural choices. Accordingly, we do not include KAN [36] in the main comparison, because it is a neural network with B-spline activations and is structurally distinct from LCSs. We also do not include

⁵Note that Theorem 2 does not imply that a KACS model with fixed capacity can achieve arbitrary accuracy. Although the construction uses finitely many rules for any $\varepsilon > 0$, the required rule count may increase as ε decreases. Thus, in practice, the population limit N imposes a trade-off among approximation accuracy, model compactness, and transparency.

TABLE I
BENCHMARK PROBLEMS USED

Abbr.	Name	#Samples	n
f_1	Rastrigin Function	1000	10
f_2	Rosenbrock Function	1000	10
f_3	Cross Function	1000	10
f_4	Styblinski-Tang Function	1000	10
ASN	Airfoil Self-Noise	1503	5
CCPP	Combined Cycle Power Plant	9568	4
CS	Concrete Strength	1030	8
EEC	Energy Efficiency Cooling	768	8

X-KAN [14] in the main comparison, because its KAN-based consequents substantially change the consequent model class and tuning space. We therefore interpret the experimental results as evidence for the effect of dimensional reorganization within the LCS framework, not as a universal ranking against all KA-inspired models. A systematic comparison with KAN and X-KAN is left for future work. For a comparison with SupRB [18], see Section S3 of the supplementary material.

2) *Benchmark Problems*: Table I summarizes four synthetic test functions and four real-world regression datasets used.

The synthetic functions are the multimodal Rastrigin function [66], the valley-shaped Rosenbrock function [67], the ridge-like Cross function [68], and the nonconvex Styblinski-Tang function [68], all evaluated in $n = 10$ dimensions with 1000 uniformly sampled points over $[0, 1]^n$. Fig. 2 illustrates each function for $n = 2$, and the corresponding mathematical formulations are provided in Section S4 of the supplementary material. The real-world datasets are taken from [18], and include two highly nonlinear problems (ASN and CS) and two nearly linear problems (CCPP and EEC).

3) *Hyperparameter Settings and Protocol*: We use the same hyperparameter settings for both XCSF and KACS. A detailed description of the hyperparameters is provided in Section S5 of the supplementary material. Unless otherwise stated, the main hyperparameters are set as follows: $N = 6400$, $\epsilon_0 = 0.01$, $\beta = 0.2$, $\alpha = 1$, $\nu = 1$, $\delta = 0.1$, $m_0 = 0.1$, $r_0 = 1.0$, $\{\theta_{\text{del}}, \theta_{\text{sub}}, \theta_{\text{GA}}\} = 50$, $\chi = 0.8$, $\mu = 0.04$, $\tau = 0.4$, where most values are typical defaults (e.g., [14], [15], [68]). For synthetic test functions, we set $P_{\#} = 0$ [68] so that covering always generates local rules, which quickly tile the uniformly sampled input space. For real-world datasets, we set $P_{\#} = 0.8$ [31] so that covering starts from globally-covering rules. This setting is more stable under highly non-uniform input distributions, which are frequently observed in real-world situations.

We run each method for 100,000 learning iterations and report results averaged over 30 independent runs. For each run, we use Monte Carlo cross-validation with 90% training data and 10% testing data, following [15]. Unlike online function-approximation protocols that continue learning during testing after a warm-up, we evaluate unseen test samples with learning disabled. For each split, min-max scaling parameters are estimated from the training data only and then applied to the test data, mapping inputs to $[0, 1]^n$ and targets to $[-1, 1]$. Thus, the reported MAEs are on the same normalized target scale across all problems. We use the Wilcoxon signed-rank test with significance level $\alpha = 0.05$. No post-training rule-compaction [14] or condensation [41] was applied. All experiments were

conducted using our Julia implementation, which is publicly available at <https://github.com/YNU-NakataLab/KACS>.

B. Main Results and Discussion

Table II reports the averages over 30 runs of model accuracy (training MAE and testing MAE), model complexity (number of rules and parameters), and their trade-off (AIC) at the end of learning for XCSF and KACS. Section S6 of the supplementary material provides the corresponding standard deviations, paired Wilcoxon p -values, and effect sizes for every benchmark and metric.

From Table II, we can see that there is no statistically significant difference in training MAE between XCSF and KACS ($p = 0.383$). In contrast, KACS is significantly better than XCSF in testing MAE, number of rules, number of parameters, and AIC ($p < 0.05$).

To assess the sensitivity of our conclusions to the evaluation protocol, we additionally compared XCSF and KACS using a protocol based on Heider’s evaluation design [18], with target standardization, MSE, a 75/25 train-test split, and eight Monte Carlo splits combined with eight random seeds per split. Under this alternative protocol, KACS achieved significantly lower training and testing MSE than XCSF on all eight benchmarks, while using fewer parameters and yielding lower AIC in every case. The details are provided in Section S7 of the supplementary material.

1) *Model Accuracy*: Fig. 3 shows the testing MAE learning curves across all four synthetic functions. The training and testing MAE learning curves across all eight problems are provided in Sections S8-A and S8-B of the supplementary material, respectively. From Table II and Fig. 3, KACS tends to achieve lower testing MAE than XCSF as training progresses, except on near-linear problems where both methods perform comparably. This indicates that reducing the problem to a set of one-dimensional subproblems allows KACS to improve prediction accuracy more efficiently than XCSF, which optimizes rules directly in the full n -dimensional space.

The magnitude of this performance gap depends on the problem characteristics, which are summarized below:

- All four artificial functions f_1 – f_4 are strongly nonlinear 10-dimensional problems. f_1 has strong local complexity in the form of multimodality. f_2 shares this local complexity in the form of a steep curved valley and also exhibits interactions between adjacent dimensions. f_3 has interactions across all dimensions. f_4 is challenging because function values rise steeply near the edges as dimensionality increases [68].
- Among the real-world datasets, ASN is the hardest to predict due to its strong nonlinearity [18]. CS is also nonlinear, but somewhat easier to predict [18]. CCPP and EEC are relatively straightforward problems with stronger linearity, where even simple linear models can achieve adequate prediction [18].

On all four artificial functions, KACS achieved significantly lower testing MAE than XCSF. f_1 is a notable case: XCSF recorded significantly lower training MAE, yet worse testing MAE than KACS. Since XCSF used roughly 17 times more


Fig. 2. Surface plots of the four synthetic test functions ($n = 2$) shown for visualization; throughout the experiments we fix $n = 10$.

TABLE II

SUMMARY OF MAIN RESULTS. GREEN INDICATES THE BEST VALUE. RANK IS THE AVERAGE RANK ACROSS PROBLEMS. FOR EACH PROBLEM, SYMBOLS $+/-/\sim$ DENOTE SIGNIFICANTLY BETTER/WORSE/SIMILAR PERFORMANCE COMPARED WITH KACS, BASED ON A PAIRED WILCOXON SIGNED-RANK TEST OVER 30 RUNS USING IDENTICAL DATA SPLITS. THE p -VALUES IN THE FINAL ROW ARE FROM ACROSS-PROBLEM PAIRED WILCOXON SIGNED-RANK TESTS APPLIED TO THE 30-RUN MEAN VALUES FOR THE EIGHT BENCHMARK PROBLEMS. ARROWS $\uparrow/\downarrow$ INDICATE RANK IMPROVEMENT/DECLINE RELATIVE TO KACS. STATISTICAL SIGNIFICANCE IS AT $\alpha = 0.05$ ($\dagger$)

	MODEL ACCURACY				MODEL COMPLEXITY				TRADE-OFF	
	Training MAE		Testing MAE		#Rules ($ \mathcal{P} $)		#Parameters (k)		AIC	
	XCSF	KACS	XCSF	KACS	XCSF	KACS	XCSF	KACS	XCSF	KACS
f_1	0.2033 +	0.2194	0.2642 -	0.2351	4162 -	1341	45780 -	2681	89210 -	3024
f_2	0.1124 ~	0.1157	0.1564 -	0.1253	4087 -	1462	44960 -	2924	86580 -	2342
f_3	0.2510 -	0.2097	0.3246 -	0.2329	4130 -	1429	45430 -	2857	88890 -	3324
f_4	0.1680 -	0.1334	0.2303 -	0.1430	4170 -	1414	45870 -	2829	89080 -	2412
ASN	0.1434 -	0.1094	0.1478 -	0.1144	2224 -	1417	13350 -	2834	22270 -	371.1
CCPP	0.0930 ~	0.0918	0.0929 ~	0.0926	1953 ~	1924	9764 -	3848	-17360 -	-29070
CS	0.1299 ~	0.1213	0.1350 ~	0.1288	2985 -	1425	26870 -	2851	50450 -	2237
EEC	0.0820 ~	0.0967	0.0847 ~	0.1020	2925 -	1012	26330 -	2023	49850 -	1125
Rank	1.62 $\downarrow$	1.38	1.88 $\downarrow^\dagger$	1.12	2.00 $\downarrow^\dagger$	1.00	2.00 $\downarrow^\dagger$	1.00	2.00 $\downarrow^\dagger$	1.00
$+/-/\sim$	1/3/4	-	0/5/3	-	0/7/1	-	0/8/0	-	0/8/0	-
p -value	0.383	-	0.0391	-	0.00781	-	0.00781	-	0.00781	-




Fig. 3. Testing MAE learning curves for all four synthetic functions. Curves show the mean over 30 runs, and shaded regions denote 95% confidence intervals.

parameters on this problem (45780 for XCSF vs. 2681 for KACS), this pattern points to overfitting driven by multi-dimensional rules on a multimodal function. A similar pattern appears on f_2 : the gap between training and testing MAE is much wider for XCSF ($0.1124 \rightarrow 0.1564$, $\Delta = 0.044$) than for KACS ($0.1157 \rightarrow 0.1253$, $\Delta = 0.010$), suggesting that steep curved valleys cause mild overfitting for n -dimensional rules. On f_3 , where interactions span all dimensions simultaneously, KACS outperformed XCSF in both training and testing MAE. XCSF must use n -dimensional rules to capture such interactions implicitly, whereas KACS represents them through nonlinear outer functions that aggregate all dimensions. On f_4 , the difficulty lies in approximating steep edge regions in 10-dimensional space, and KACS again showed a clear advantage.

Among the real-world datasets, KACS achieved significantly lower testing MAE than XCSF only on ASN. For CS

and CCPP, no statistically significant differences were found. For EEC, KACS showed higher testing MAE than XCSF (0.1020 vs. 0.0847), but the difference was not statistically significant. For CCPP and EEC, n -dimensional linear rules are already sufficient (testing MAE below 0.1). In such near-linear problems, the KA decomposition introduces unnecessary structural overhead: KACS must coordinate $n(2n + 1)$ inner submodels and compose their outputs through $2n + 1$ outer submodels to recover a function that XCSF can represent directly with multiple linear rules. This additional indirection accumulates approximation error in the outer stage, which outweighs the benefits of dimensional decomposition.

In Fig. 3, KACS started with higher testing MAE than XCSF in the early phase of training (0–20,000 iterations) across all problems. This is because KACS needs to initialize and tune many one-dimensional submodels at once, which pro-

duces inaccurate predictions early on and temporarily inflates the overall error. The GA-driven search is also distributed across all $2n^2 + 3n + 1$ submodels at the start, which slows convergence of the final output compared to XCSF.

The above findings can be summarized as follows:

- The accuracy advantage of KACS grows with problem nonlinearity, particularly when cross-dimensional interactions or sharp local structures are present, and fades when the problem is well-captured by linear approximations.
- In all cases, a warm-up period is needed at the start of KACS training, as coordinating many one-dimensional submodels from scratch inevitably raises early-stage error.

Finally, we evaluate rotated, translated, and scaled variants of f_3 to test sensitivity to ridge orientation, location, and scale. As reported in Section S9 of the supplementary material, KACS achieves significantly lower testing MAE than XCSF for all three variants, indicating that its advantage is not limited to the original axis-aligned structure of f_3 .

2) *Model Complexity and Accuracy-Complexity Trade-off:* One of the most significant results in this article is the large difference in model complexity. As shown in Table II, KACS achieved comparable or higher prediction accuracy using only roughly 6–40% of the parameters required by XCSF across all eight problems. The parameter-count learning curves are provided in Section S8-C of the supplementary material.

This gap reflects a fundamental difference in how each method constructs its rules. XCSF covers the input space with local linear models, each defined over the full n -dimensional space. As n grows, defining meaningful local regions and fitting reliable linear models within them both become harder, which tends to produce redundant or poorly fitted rules, driving up model size and the risk of overfitting (cf. Section VI-B1). KACS avoids this by decomposing the problem into one-dimensional subproblems, allowing it to represent multivariate functions compactly with far fewer parameters.

KACS achieved significantly lower AIC than XCSF on all eight problems, indicating that its models are statistically more efficient. On CS, where testing MAE is similar for both methods, the AIC advantage of KACS comes entirely from its smaller parameter count. On EEC, where KACS records slightly higher testing MAE than XCSF, KACS still achieves far better AIC, showing that its reduction in model complexity more than compensates for the small loss in accuracy.

C. Scalability Analysis

This subsection analyzes the scalability of XCSF and KACS. We use f_3 (Cross function) as the representative benchmark because it is the only synthetic function in our set that involves interactions across all dimensions, making it directly sensitive to changes in n .

1) *Experimental Design:* Unless otherwise noted, hyperparameter settings and training iterations follow the setup in Section VI-A. We report testing MAE and two complexity measures, $|\mathcal{P}|$ and k , as means with 95% confidence intervals.

2) *Results on Sample-Size Scaling:* We vary $N_S \in \{125, 250, 500, 1000, 2000, 4000, 8000\}$ while fixing $n = 10$. Fig. 4 summarizes how both methods respond to more data.

The detailed tabular results are provided in Section S10-A of the supplementary material.

Increasing N_S improves accuracy for both methods, but the gain is larger for KACS. XCSF testing MAE decreases from 0.416 ($N_S = 125$) to 0.312 ($N_S = 8000$), while KACS decreases from 0.380 to 0.216 and stabilizes after $N_S \approx 2000$. Complexity grows much more slowly for KACS: XCSF rules and parameters increase from 3164 to 4724 and from 34800 to 51960, respectively, whereas KACS stays around 1242–1430 rules and 2484–2860 parameters. Thus, more data mainly improves KACS accuracy without inducing comparable complexity growth.

3) *Results on Dimensional Scaling:* We vary $n \in \{2, 4, 6, 8, 10, 12, 14, 16, 18, 20\}$ while fixing $N_S = 1000$. Fig. 5 summarizes how both methods respond to increasing dimensionality. The detailed tabular results are provided in Section S10-B of the supplementary material.

As n increases, XCSF testing MAE rises from 0.158 at $n = 2$ to about 0.27–0.33 at $n = 4$ –20; KACS significantly outperforms XCSF from $n = 2$ to $n = 16$ (e.g., 0.233 vs. 0.325 at $n = 10$), but degrades sharply at higher dimensions (0.384 at $n = 18$, 1.25 at $n = 20$). Complexity trends are clearer: XCSF rules grow monotonically (1501 to 5283), and its parameter count grows from 4504 to 110900. KACS remains compact, with 1186–1955 rules and 2372–3909 parameters across most settings, with only a notable increase at $n \geq 18$.

4) *Discussion:* Figs. 4 and 5 together support two claims. First, KACS provides a better accuracy-complexity trade-off in the practical regime ($n \leq 14$ and all tested sample sizes), consistently using far fewer rules and parameters than XCSF. Second, under the default $N = 6400$, KACS shows a clear performance drop in higher dimensions ($n = 16$ –20): accuracy deteriorates sharply even though the model remains compact.

The failure at higher n stems from two related capacity bottlenecks. First, KACS decomposes the n -dimensional problem into $(2n + 1)(n + 1) = 2n^2 + 3n + 1$ one-dimensional subproblems, so the number of macro-rules per subproblem shrinks as n grows. At $n = 20$, for instance, this gives 861 subproblems, leaving at most $\lceil 6400/861 \rceil \approx 7$ macro-rules per subproblem on average, and typically fewer because individual rules can carry numerosity greater than one. Second, and more critically, the inner and outer submodels have fundamentally different input domains. The inner submodel input domain is fixed at $[0, 1]$ regardless of n , whereas the outer submodel input $\hat{z}_q = \sum_{p=1}^n \hat{\psi}_{q,p}(x_p)$ is a sum of n terms. Since inner rule weights are initialized from $\mathcal{U}[-1, 1]$, the output of each $\hat{\psi}_{q,p}$ can be negative, and the outer input domain can be written as $\hat{\mathcal{K}}_z^{(q)} := \{\hat{z}_q \mid \hat{z}_q = \sum_{p=1}^n \hat{\psi}_{q,p}(x_p), x_p \in [0, 1]\} \approx [-n, n]$, so its domain width scales as $|\hat{\mathcal{K}}_z^{(q)}| \approx 2n$. Consequently, outer submodels require $O(n)$ times more rules than inner submodels to achieve the same coverage density. When N is set without accounting for this difference, outer submodels are severely under-resourced at large n , triggering a *cover-delete cycle*⁶ in which newly generated covering rules are immediately deleted to maintain the population within N [69].

⁶A detailed analysis of covering dynamics and cover-delete behavior is provided in Section S11 of the supplementary material.




Fig. 4. Sample-size scaling results for XCSF and KACS on f_3 , where $N_S \in \{125, 250, 500, 1000, 2000, 4000, 8000\}$ and $n = 10$.




Fig. 5. Dimensional scaling results for XCSF and KACS on f_3 , where $n \in \{2, 4, 6, 8, 10, 12, 14, 16, 18, 20\}$ and $N_S = 1000$.




Fig. 6. Dimensional scaling results for XCSF and KACS on f_3 , where $n \in \{16, 18, 20\}$, $N \in \{12672, 15984, 19680\}$, and $N_S = 1000$.

A guideline for N should therefore distinguish between inner and outer coverage requirements. Let $k_{\min}$ denote the minimum number of macro-rules per unit of input domain width. Inner submodels, each with domain $[0, 1]$ of width 1, require $k_{\min}$ rules. Outer submodels, with domain $\approx [-n, n]$ of width $2n$, require $k_{\min} \cdot 2n$ rules. With $n(2n+1)$ inner submodels and $(2n+1)$ outer submodels, the total rule budget must satisfy

$$N \geq k_{\min} \cdot n(2n+1) + k_{\min} \cdot 2n \cdot (2n+1) = 3k_{\min} \cdot n(2n+1). \quad (41)$$

We estimate $k_{\min}$ from the last stable dimension $n = 14$:

$$k_{\min} \approx \frac{N}{3 \cdot n(2n+1)} \Big|_{n=14} = \frac{6400}{3 \times 14 \times 29} \approx 5.3.$$

Rounding up and adding a modest safety margin to account for problem-to-problem variation in the outer function range, we adopt $k_{\min} = 8$, which gives $N \geq 3 \times 8 \times n(2n+1) = 24n(2n+1)$, predicting $N \geq 12672, 15984, 19680$ for $n = 16, 18, 20$, respectively. To verify this, we ran additional experiments with these N values at the corresponding dimensions. As shown in Fig. 6, under this scaled budget, the severe degradation at $n \in \{16, 18, 20\}$ no longer appears. KACS attains significantly lower testing MAE than XCSF at all three dimensions (16:

0.2109 vs. 0.2768, 18: 0.2115 vs. 0.2768, 20: 0.1970 vs. 0.2833). KACS also remains much more compact, using significantly fewer macro-rules ($|\mathcal{P}|$: 2633, 3306, 4017 vs. 9520, 12310, 15690) and significantly fewer parameters (k : 5266, 6612, 8033 vs. 161800, 233900, 329600). In particular, at $n = 20$, KACS achieves lower testing MAE than XCSF using only about 2% as many parameters. This confirms that the higher-dimensional failure is a capacity issue attributable to under-resourced outer submodels, rather than an inherent limitation of KACS.

Note that $k_{\min}$ is not a universal constant: its value depends on the actual range of the outer submodel inputs, which varies with the problem and the learned inner functions. The estimate $k_{\min} \approx 5.3$ was derived empirically from a single benchmark (f_3), so (41) should be treated as a practical starting point rather than a tight bound; its transferability to other functions and real-world data remains to be validated.

VII. CONCLUSION

In this article, we proposed KACS, the first LCS that reorganizes rules dimension-wise according to the Kolmogorov-Arnold (KA) representation theorem. Instead of evolving rules directly in the n -dimensional input space, KACS decomposes the target function into one-dimensional subproblems and assigns a dedicated ruleset to each, optimized through evolutionary algorithms and gradient-based methods. This reduces the worst-case rule count from $O(m^n)$ to $O(mn^2)$, where m is the per-variable resolution. We also proved that KACS is a universal approximator for continuous functions on compact domains, which is the first such proof for any LCS. Experiments showed that KACS provides a parameter-efficient alternative for function approximation, with competitive accuracy across many tested settings.

These results suggest that KA-guided dimension-wise decomposition is a broadly applicable design principle. Any local

modeling framework that partitions the input space directly, such as fuzzy systems and other rule-based systems, may benefit from reorganizing its components into one-dimensional subproblems. KACS provides a concrete example of this principle and shows that such reorganization improves both accuracy and model compactness without sacrificing expressive power, as guaranteed by the universal approximation proof.

Several limitations remain. First, initializing many submodels simultaneously requires a warm-up period, during which prediction error temporarily exceeds that of XCSF. Second, reliable coverage requires a population budget of $N = O(n^2)$; a smaller budget triggers a cover-delete cycle that degrades performance. Third, the universal approximation proof guarantees only the *existence* of an accurate ruleset, not that the learning algorithm will converge to it in practice.

Future work should address these issues in order of practical impact. An adaptive mechanism that monitors submodel coverage and adjusts N dynamically would resolve both the warm-up and budget problems. On the theoretical side, deriving convergence rates for the joint GA and gradient-based optimization would connect the existence proof to algorithmic behavior. At a broader level, extending dimension-wise decomposition to other local modeling frameworks and identifying the conditions under which it outperforms direct partitioning is a direction that reaches beyond LCSs, and KACS provides a concrete foundation for that investigation. Within this direction, relaxing the strict KA structure may further improve approximation efficiency. For example, one can vary the number of inner and outer models, or stack multiple KA layers as in KAN [36]. Whether universal approximation is preserved under these modifications remains an open question. Future studies will also visualize the learned rules and submodels, evaluate structural fidelity by comparing learned models with known low-dimensional target functions, and compare KACS with KAN-based models [14], genetic programming variants [70], and neural- and code-fragment-based LCSs [42], [43] across broader problem suites.

REFERENCES

- [1] C. M. Bishop and N. M. Nasrabadi, *Pattern recognition and machine learning*. Springer, 2006, vol. 4, no. 4.
- [2] T. Hastie, R. Tibshirani, and J. H. Friedman, *The elements of statistical learning: data mining, inference, and prediction*. Springer, 2009, vol. 2.
- [3] I. Goodfellow, Y. Bengio, and A. Courville, *Deep learning*. MIT press Cambridge, 2016, vol. 1, no. 2.
- [4] R. S. Sutton and A. G. Barto, *Reinforcement learning: An introduction*. MIT press, 2018.
- [5] K. J. Åström, “Adaptive control,” in *Mathematical System Theory: The Influence of RE Kalman*. Springer, 1995, pp. 437–450.
- [6] S. Vijayakumar, A. D’souza, and S. Schaal, “Incremental online learning in high dimensions,” *Neural computation*, vol. 17, no. 12, pp. 2602–2634, 2005.
- [7] R. A. Jacobs, M. I. Jordan, S. J. Nowlan, and G. E. Hinton, “Adaptive mixtures of local experts,” *Neural Comput.*, vol. 3, no. 1, pp. 79–87, 1991.
- [8] H. D. Nguyen and F. Chamroukhi, “Practical and theoretical aspects of mixture-of-experts modeling: An overview,” *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery*, vol. 8, no. 4, p. e1246, 2018.
- [9] A. Hinrichs, E. Novak, and H. Woźniakowski, “The curse of dimensionality for monotone and convex functions of many variables,” *arXiv preprint arXiv:1011.3680*, 2010.
- [10] L. Breiman, J. Friedman, R. A. Olshen, and C. J. Stone, *Classification and regression trees*. Chapman and Hall/CRC, 2017.
- [11] T. Takagi and M. Sugeno, “Fuzzy identification of systems and its applications to modeling and control,” *IEEE Trans. Syst., Man, Cybern.*, no. 1, pp. 116–132, 1985.
- [12] R. J. Urbanowicz and W. N. Browne, *Introduction to Learning Classifier Systems*, 1st ed. Springer Publishing Company, Incorporated, 2017.
- [13] A. Siddique, M. Heider, M. Iqbal, and H. Shiraishi, “A survey on learning classifier systems from 2022 to 2024,” in *Proc. Genet. Evol. Comput. Conf. Companion*, 2024, pp. 1797–1806.
- [14] H. Shiraishi, H. Ishibuchi, and M. Nakata, “X-KAN: Optimizing local kolmogorov-arnold networks via evolutionary rule-based machine learning,” in *Proceedings of the Thirty-Fourth International Joint Conference on Artificial Intelligence, IJCAI-25*, 8 2025, pp. 8930–8938, Main Track.
- [15] R. J. Preen, S. W. Wilson, and L. Bull, “Autoencoding with a classifier system,” *IEEE Trans. Evol. Comput.*, vol. 25, no. 6, pp. 1079–1090, 2021.
- [16] H. H. Dam, H. A. Abbass, C. Lokan, and X. Yao, “Neural-based learning classifier systems,” *IEEE Trans. Knowl. Data Eng.*, vol. 20, no. 1, pp. 26–39, 2007.
- [17] S. W. Wilson, “Classifiers that approximate functions,” *Natural Comput.*, vol. 1, no. 2, pp. 211–234, 04 2002.
- [18] M. Heider, H. Stegherr, R. Sraj, D. Pätz, J. Wurth, and J. Hähner, “SupRB in the context of rule-based machine learning methods: A comparative study,” *Appl. Soft Comput.*, p. 110706, 2023.
- [19] E. Debie and K. Shafi, “Implications of the curse of dimensionality for supervised learning classifier systems: theoretical and empirical analyses,” *Pattern Anal. Appl.*, vol. 22, no. 2, pp. 519–536, 05 2019.
- [20] R. J. Urbanowicz and J. H. Moore, “Learning classifier systems: a complete introduction, review, and roadmap,” *J. Artif. Evol. Appl.*, vol. 2009, 2009.
- [21] M. Heider, D. Pätz, H. Stegherr, and J. Hähner, “A metaheuristic perspective on learning classifier systems,” in *Metaheuristics for Machine Learning: New Advances and Tools*. Springer, 2022, pp. 73–98.
- [22] J. Drugowitsch, *Design and Analysis of Learning Classifier Systems: A Probabilistic Approach*. Springer Science & Business Media, 2008, vol. 139.
- [23] P. O. Stalpf, X. Llorà, D. E. Goldberg, and M. V. Butz, “Resource management and scalability of the XCSF learning classifier system,” *Theoretical Computer Science*, vol. 425, pp. 126–141, 2012.
- [24] A. N. Kolmogorov, *On the representation of continuous functions of several variables by superpositions of continuous functions of a smaller number of variables*. American Mathematical Society, 1961.
- [25] V. I. Arnold, “On functions of three variables,” *Collected Works: Representations of Functions, Celestial Mechanics and KAM Theory, 1957–1965*, pp. 5–8, 2009.
- [26] J. Schmidt-Hieber, “The kolmogorov-arnold representation theorem revisited,” *Neural networks*, vol. 137, pp. 119–126, 2021.
- [27] G. Cybenko, “Approximation by superpositions of a sigmoidal function,” *Math. Control Signals Syst.*, vol. 2, no. 4, pp. 303–314, 1989.
- [28] P. L. Lanzi and D. Loiacono, “A proposal for a leaner narrative of learning classifier systems,” in *Proceedings of the Genetic and Evolutionary Computation Conference Companion*, 2025, pp. 2261–2268.
- [29] S. W. Wilson, “Classifier fitness based on accuracy,” *Evol. Comput.*, vol. 3, no. 2, p. 149–175, jun 1995.
- [30] M. V. Butz and S. W. Wilson, “An algorithmic description of XCS,” *Soft Comput.*, vol. 6, no. 3–4, pp. 144–153, 2002.
- [31] M. Nakata and W. N. Browne, “Learning optimality theory for accuracy-based learning classifier systems,” *IEEE Trans. Evol. Comput.*, vol. 25, no. 1, pp. 61–74, Feb 2021.
- [32] B. Widrow and M. E. Hoff, “Adaptive switching circuits,” Stanford Univ Ca Stanford Electronics Labs, Tech. Rep., 1960.
- [33] D. P. Kingma and J. Ba, “Adam: A Method for Stochastic Optimization. international conference on learning representations,” 2015.
- [34] S. W. Wilson, “Generalization in the XCS classifier system,” *Proc. Genetic Programming 1998*, 1998.
- [35] W. Rudin, “Principles of mathematical analysis,” 3rd ed., 1976.
- [36] Z. Liu, Y. Wang, S. Vaidya, F. Ruehle, J. Halverson, M. Soljagic, T. Y. Hou, and M. Tegmark, “KAN: Kolmogorov-arnold networks,” in *The Thirteenth International Conference on Learning Representations*, 2025.
- [37] H. Shiraishi, Y. Hayamizu, T. Hashiyama, K. Takadama, H. Ishibuchi, and M. Nakata, “Adapting rule representation with four-parameter beta distribution for learning classifier systems,” *IEEE Transactions on Evolutionary Computation*, vol. 30, no. 1, pp. 363–377, 2026.
- [38] S. W. Wilson, “Get real! XCS with continuous-valued inputs,” in *Int. Worksh. Learn. Classif. Syst.* Springer, 1999, pp. 209–219.
- [39] —, “Mining oblique data with XCS,” in *Int. Worksh. Learn. Classif. Syst.*, 2000, pp. 158–174.

- [40] H. Shiraishi, Y. Hayamizu, H. Sato, and K. Takadama, "Can the same rule representation change its matching area? enhancing representation in XCS for continuous space by probability distribution in multiple dimension," in *Proc. Genet. Evol. Comput. Conf.*, 2022, p. 431–439.
- [41] M. V. Butz, P. L. Lanzi, and S. W. Wilson, "Function approximation with XCS: Hyperellipsoidal conditions, recursive least squares, and compaction," *IEEE Trans. Evol. Comput.*, vol. 12, no. 3, pp. 355–376, June 2008.
- [42] L. Bull and T. O'Hara, "Accuracy-based neuro and neuro-fuzzy classifier systems," in *Proc. 4th Annu. Conf. Genet. Evol. Comput.*, 2002, p. 905–911.
- [43] M. H. Arif, J. Li, and M. Iqbal, "Solving social media text classification problems using code fragment-based XCSR," in *2017 IEEE 29th Int. Conf. Tools Artif. Intell. (ICTAI)*, Nov 2017, pp. 485–492.
- [44] M. Behdad, T. French, L. Barone, and M. Bennamoun, "PCA for improving the performance of XCSR in classification of high-dimensional problems," in *Proc. 13th Annu. Conf. Companion Genet. Evol. Comput.*, 2011, pp. 361–368.
- [45] H. Shiraishi, M. Tadokoro, Y. Hayamizu, Y. Fukumoto, H. Sato, and K. Takadama, "Increasing accuracy and interpretability of high-dimensional rules for learning classifier system," in *2021 IEEE Congress on Evolutionary Computation (CEC)*. IEEE, 2021, pp. 311–318.
- [46] N. Yatsu, H. Shiraishi, H. Sato, and K. Takadama, "Exploring high-dimensional rules indirectly via latent space through a dimensionality reduction for XCS," in *Proc. Genet. Evol. Comput. Conf.*, 2023, pp. 606–614.
- [47] C. Schönberger, A. Mackensen, and S. Tomforde, "Dimensionality reduction for enabling visual reinforcement learning with a classifier system," in *Proc. Genet. Evol. Comput. Conf. Companion*, 2025, pp. 2269–2278.
- [48] R. J. Urbanowicz and J. H. Moore, "ExSTraCS 2.0: description and evaluation of a scalable learning classifier system," *Evol. Intell.*, vol. 8, no. 2, pp. 89–116, 2015.
- [49] J. H. Moore and B. C. White, "Tuning relief for genome-wide genetic analysis," in *Proc. Eur. Conf. Evol. Comput., Mach. Learn. Data Mining Bioinformatics*. Springer, 2007, pp. 166–175.
- [50] J. H. Friedman and B. E. Popescu, "Predictive learning via rule ensembles," *Ann. Appl. Stat.*, vol. 2, no. 3, pp. 916–954, 2008.
- [51] R. Bellman, "Dynamic programming," *science*, vol. 153, no. 3731, pp. 34–37, 1966.
- [52] Z. Bozorgasl and H. Chen, "Wav-kan: Wavelet kolmogorov-arnold networks," 2024. [Online]. Available: <https://arxiv.org/abs/2405.12832>
- [53] G. De Franceschi *et al.*, "Ensemble-kan: Leveraging kolmogorov-arnold networks to discriminate individuals with psychiatric disorders from controls," in *Proc. Int. Workshop Appl. Med. AI*, 2024, pp. 186–197.
- [54] S. SS, K. AR, A. KP *et al.*, "Chebyshev polynomial-based kolmogorov-arnold networks: An efficient architecture for nonlinear function approximation," *arXiv preprint arXiv:2405.07200*, 2024.
- [55] R. Genet and H. Inzirillo, "Tkan: Temporal kolmogorov-arnold networks," 2025. [Online]. Available: <https://arxiv.org/abs/2405.07344>
- [56] E. Zeydan, C. J. Vaca-Rubio, L. Blanco, R. Pereira, M. Caus, and A. Aydeger, "F-kans: Federated kolmogorov-arnold networks," in *Proc. 2025 IEEE 22nd Consum. Commun. Netw. Conf.* IEEE, 2025, pp. 1–6.
- [57] K. Hornik, M. Stinchcombe, and H. White, "Multilayer feedforward networks are universal approximators," *Neural networks*, vol. 2, no. 5, pp. 359–366, 1989.
- [58] L.-X. Wang, J. M. Mendel *et al.*, "Fuzzy basis functions, universal approximation, and orthogonal least-squares learning," *IEEE transactions on Neural Networks*, vol. 3, no. 5, pp. 807–814, 1992.
- [59] M. H. Stone, "The generalized weierstrass approximation theorem," *Mathematics Magazine*, vol. 21, no. 5, pp. 237–254, 1948.
- [60] H. Ying, "Sufficient conditions on general fuzzy systems as function approximators," *Automatica*, vol. 30, no. 3, pp. 521–525, 1994.
- [61] B. Kosko, "Fuzzy systems as universal approximators," *IEEE Transactions on Computers*, vol. 43, no. 11, pp. 1329–1333, 2002.
- [62] J. L. Castro, "Fuzzy logic controllers are universal approximators," *IEEE Trans. Syst., Man, Cybern.*, vol. 25, no. 4, pp. 629–635, 2002.
- [63] L.-X. Wang, "Universal approximation by hierarchical fuzzy systems," *Fuzzy sets and systems*, vol. 93, no. 2, pp. 223–230, 1998.
- [64] G. B. Folland, *Real analysis: modern techniques and their applications*. John Wiley & Sons, 1999.
- [65] K. P. Burnham and D. R. Anderson, *Model selection and multimodel inference: a practical information-theoretic approach*. Springer, 2002.
- [66] H. Mühlenbein, M. Schomisch, and J. Born, "The parallel genetic algorithm as function optimizer," *Parallel computing*, vol. 17, no. 6–7, pp. 619–632, 1991.
- [67] M. Jamil and X. S. Yang, "A literature survey of benchmark functions for global optimisation problems," *Int. J. Math. Model. Numer. Optim.*, vol. 4, no. 2, p. 150, 2013.
- [68] A. Stein, S. Menssen, and J. Hähner, "What about interpolation? a radial basis function approach to classifier prediction modeling in XCSF," in *Proc. Genet. Evol. Comput. Conf.*, 2018, pp. 537–544.
- [69] M. Butz, T. Kovacs, P. Lanzi, and S. Wilson, "Toward a theory of generalization and learning in XCS," *IEEE Trans. Evol. Comput.*, vol. 8, no. 1, pp. 28–46, Feb 2004.
- [70] J. R. Koza, "Genetic programming as a means for programming computers by natural selection," *Stat. Comput.*, vol. 4, no. 2, pp. 87–112, 1994.



Hiroki Shiraishi received the B.E. and M.E. degrees in informatics from the University of Electro-Communications, Tokyo, Japan, in 2021 and 2023, respectively, and the Ph.D. degree in information systems from Yokohama National University, Yokohama, Japan, in 2026.

Since 2026, he has been a Researcher with the Digital Healthcare Research Department, Hitachi, Ltd., Tokyo, Japan. His research interests include fuzzy systems, neuroevolution, learning classifier systems, and their clinical applications in pathology.

Dr. Shiraishi received the Best Paper Award at GECCO 2022 and was nominated for the Best Paper Award at GECCO 2023. He served as Chair of the International Workshop on Evolutionary Rule-Based Machine Learning at GECCO from 2024 to 2026.



Hisao Ishibuchi (Fellow, IEEE) received the B.S. and M.S. degrees from Kyoto University in 1985 and 1987, respectively, and the Ph.D. degree from Osaka Prefecture University in 1992.

He was with Osaka Prefecture University from 1987 to 2017. Since 2017, he has been a Chair Professor at Southern University of Science and Technology, China. His research interests include the design, analysis, comparison and application of evolutionary multi-objective optimization algorithms.

Dr. Ishibuchi was the IEEE CIS Vice-President for Technical Activities in 2010–2013, the Editor-in-Chief of the IEEE COMPUTATIONAL INTELLIGENCE MAGAZINE in 2014–2019, and an AdCom member of the IEEE CIS in 2014–2019 and 2021–2026. Currently, he is General Chair of EMO 2027.



Masaya Nakata (Member, IEEE) received the Ph.D. degree in informatics from the University of Electro-Communications, Tokyo, Japan, in 2016.

He is an Associate Professor with the Faculty of Engineering, Yokohama National University, Yokohama, Japan. Since 2019, he has focused his research on surrogate-assisted evolutionary algorithms. His research has also included evolutionary machine learning, data mining, and the theoretical analysis of learning classifier systems.

Dr. Nakata chaired the International Workshop on Learning Classifier Systems in 2015, 2016, and 2018–2020 in GECCO.

Supplementary Material of “Kolmogorov-Arnold Classifier Systems as Universal Approximators”

Hiroki Shiraishi^{id}, Hisao Ishibuchi^{id}, *Fellow, IEEE*, and Masaya Nakata^{id}, *Member, IEEE*

CONTENTS

S1	Inference Complexity Analysis	17
S1-A	XCSF	17
S1-B	KACS	17
S1-C	Comparison of Inference Complexity	17
S1-D	Asymptotic Rule-Count Interpretation	18
S2	Generalization of the KACS Universal Approximation Theorem to Other Consequent Models	18
S3	Comparison with SupRB: A State-of-the-Art Pittsburgh-Style LCS	19
S3-A	Experimental Protocol and Comparability	19
S3-B	Prediction Accuracy	19
S3-C	Rule Complexity	20
S3-D	Interpretability of the Learned Models	20
S4	Formulations of Synthetic Functions	21
S5	A Description of Hyperparameters	22
S6	Detailed Statistical Results	22
S7	Robustness under an Alternative Evaluation Protocol	24
S7-A	Experimental Protocol	24
S7-B	Main Results	24
S7-C	Statistical Results and Interpretation	25
S8	Additional Learning Curves	27
S8-A	Training MAE Learning Curves	27
S8-B	Testing MAE Learning Curves	27
S8-C	Parameter-Count Learning Curves	28
S9	Effects of Rotation, Translation, and Scaling on f_3	29
S9-A	Problem Definition	29
S9-B	Experimental Results	29
S9-C	Discussion	30
S10	Scalability Analysis — Detailed Results	31
S10-A	Sample-Size Scaling	31
S10-B	Dimensional Scaling	34
S11	Covering Dynamics and Cover-Delete Behavior	36
	References	37

Manuscript received 31 March 2026; revised 6 August 2026; accepted 11 September 2026. This work was supported by JSPS KAKENHI (Grant No. JP23KJ0993, JP25K03195), National Natural Science Foundation of China (Grant No. 62376115), and Guangdong Provincial Key Laboratory (Grant No. 2020B121201001). (*Corresponding authors: Hisao Ishibuchi; Masaya Nakata.*)

Hiroki Shiraishi was with the Graduate School of Engineering Science, Yokohama National University, Yokohama 240-8501, Japan, at the time of manuscript submission on 31 March 2026. He is now with the Digital Healthcare Research Department, Hitachi, Ltd., Tokyo 185-8601, Japan (e-mail: hiroki.shiraishi.we@hitachi.com).

Hisao Ishibuchi is with the Department of Computer Science and Engineering, Southern University of Science and Technology, Shenzhen 518055, China (e-mail: hisao@sustech.edu.cn).

Masaya Nakata is with the Faculty of Engineering, Yokohama National University, Yokohama 240-8501, Japan (e-mail: nakata-masaya-tb@ynu.ac.jp).

S1. INFERENCE COMPLEXITY ANALYSIS

This section compares the worst-case inference complexity of XCSF and KACS. The analysis concerns prediction only. It excludes all training operations, including covering, parameter updates, genetic search, subsumption, and deletion.

Let R_X denote the number of macro-rules in the final XCSF population, i.e.,

$$R_X = |\mathcal{P}|. \quad (1)$$

Let R_K denote the total number of macro-rules in all KACS inner and outer submodels:

$$R_K = |\mathcal{P}| = \sum_{q=1}^{2n+1} \sum_{p=1}^n |\mathcal{P}_{q,p}^\psi| + \sum_{q=1}^{2n+1} |\mathcal{P}_q^\Phi|. \quad (2)$$

Here, a macro-rule is counted once regardless of its numerosity.

A. XCSF

For an input $\mathbf{x} \in \mathbb{R}^n$, XCSF forms a match set by testing whether $\mathbf{x}$ satisfies the interval condition of each rule. Since an XCSF rule has an n -dimensional condition, matching one rule requires $O(n)$ comparisons in the worst case. Consequently, constructing the match set requires

$$O(nR_X) \quad (3)$$

operations.

Each matched rule has an $(n+1)$ -parameter linear consequent. Its prediction therefore requires $O(n)$ arithmetic operations. Because the number of matched rules is at most R_X , computing and aggregating the rule predictions also requires

$$O(nR_X) \quad (4)$$

operations in the worst case. Therefore, the total worst-case inference complexity of XCSF is

$$T_{\text{XCSF}} = O(nR_X). \quad (5)$$

B. KACS

KACS evaluates $n(2n+1)$ inner submodels and $2n+1$ outer submodels. Thus, it contains

$$n(2n+1) + (2n+1) = (n+1)(2n+1) = 2n^2 + 3n + 1 \quad (6)$$

submodels.

Each KACS rule has a one-dimensional interval condition and a two-parameter linear consequent. Matching and evaluating an individual rule therefore require $O(1)$ operations. Scanning and evaluating all inner and outer rule populations require

$$O(R_K). \quad (7)$$

KACS additionally computes the intermediate sums

$$\hat{z}_q = \sum_{p=1}^n \hat{\psi}_{q,p}(x_p), \quad q = 1, \dots, 2n+1, \quad (8)$$

which requires $n(2n+1)$ additions. It subsequently aggregates the $2n+1$ outer outputs to obtain $\hat{y}$. The total channel-wise aggregation cost is therefore

$$O(n(2n+1)) = O(n^2). \quad (9)$$

Combining rule evaluation and channel-wise aggregation yields

$$T_{\text{KACS}} = O(R_K + n(2n+1)) = O(R_K + n^2). \quad (10)$$

C. Comparison of Inference Complexity

For the final learned populations, the worst-case inference complexities are

$$T_{\text{XCSF}} = O(nR_X), \quad T_{\text{KACS}} = O(R_K + n^2). \quad (11)$$

Thus, KACS removes the multiplicative factor n from the cost of matching and evaluating an individual rule. However, it evaluates inner and outer submodels across multiple channels and consequently incurs a channel-wise aggregation cost of $O(n^2)$. Hence, this analysis does not imply that KACS is always faster in wall-clock inference time. The practical runtime also depends on R_X , R_K , the allocation of KACS rules among submodels, and implementation-specific factors.

D. Asymptotic Rule-Count Interpretation

The preceding analysis is expressed in terms of the final numbers of macro-rules, R_X and R_K . To relate these quantities to dimensionality, consider an idealized setting in which m effective intervals are required per input dimension for XCSF and, on average, m rules are required per one-dimensional KACS submodel.

Under this assumption, XCSF requires

$$R_X = O(m^n) \quad (12)$$

rules to cover an n -dimensional input space. KACS has $n(2n + 1)$ inner submodels and $2n + 1$ outer submodels. Hence, its total number of rules is

$$R_K = O(m[n(2n + 1) + (2n + 1)]) = O(m(n + 1)(2n + 1)) = O(mn^2). \quad (13)$$

Substituting these estimates into Eqs. (5) and (10) gives

$$T_{\text{XCSF}} = O(nm^n), \quad T_{\text{KACS}} = O(mn^2). \quad (14)$$

These expressions describe asymptotic scaling under the stated idealized rule-allocation assumption. They do not represent the numbers of rules learned in a finite experiment, which depend on the population budget N , the data distribution, and the learning dynamics.

S2. GENERALIZATION OF THE KACS UNIVERSAL APPROXIMATION THEOREM TO OTHER CONSEQUENT MODELS

Although the proof in Section V of the main article is presented with a linear consequent $P_k(z) = w_{k,0} + w_{k,1}z$ as in (3), the same argument extends to a broader class of consequent models. In particular, KACS retains the universal approximation property even when the consequent is chosen as (i) polynomial or B-spline models that can represent linear functions exactly [1], or (ii) universal approximators such as MLP, RBFN [2], and KAN.

This follows because the construction in Lemma 1 (see also (25)) of the main article only requires the consequent of each reference rule cl_j^* , denoted by $P_j^*(z)$, to approximate the target linear function $h_j(z)$ on the corresponding region R_j with error at most $\varepsilon/4$. A linear consequent can represent h_j exactly, and polynomial or B-spline consequents can do so as well because they include linear functions as a special case. If a universal approximator (MLP, RBFN, KAN) is used as the consequent, it can approximate h_j within $\varepsilon/4$, which is sufficient for the same error bound to carry through.

Therefore, the universal approximation capability of KACS is not limited to linear consequents; it generalizes to more flexible consequent models that can represent linear functions either exactly or to arbitrary accuracy.

S3. COMPARISON WITH SUPRB: A STATE-OF-THE-ART PITTSBURGH-STYLE LCS

A. Experimental Protocol and Comparability

We conducted an additional comparison with SupRB, a Pittsburgh-style LCS that separately optimizes rule discovery and final rule-set composition [3], [4]. The comparison includes the four real-world benchmarks used in the main article and two additional benchmarks considered by Heider [4]: the Physicochemical Properties of Protein Tertiary Structure (PPPTS) dataset with $n = 9$ and the Parkinsons Telemonitoring (PT) dataset with $n = 18$. The latter two extend the dimensionality of the real-world evaluation beyond the original maximum of $n = 8$. They should be interpreted as higher-dimensional relative to the original benchmark set, rather than as extremely high-dimensional data.

For our XCSF and KACS experiments, we followed Heider’s evaluation protocol [4]: eight Monte Carlo data splits were combined with eight random seeds per split, yielding 64 runs for each method and dataset; 25% of the samples were held out for testing; and the target was standardized. XCSF and KACS used the same splits and seeds. The input features were scaled to $[0, 1]$ instead of the $[-1, 1]$ range used by Heider because the present KACS formulation assumes inputs in $[0, 1]$. Our XCSF and KACS populations were evaluated without post-training compaction. For PT ($n = 18$) only, we set the population budget to $N = 15984$ for both XCSF and KACS, following the practical guideline in Section VI-C4 of the main article and retaining an equal budget for the controlled comparison. For all other datasets, we used $N = 6400$, as in Section VI-A3 of the main article.

The literature values require several qualifications. Heider’s reported XCSF results for ASN, CCPP, CS, and EEC use dataset-specific hyperparameter tuning, recursive-least-squares consequent updates, and post-training population compaction; XCSF results were not reported for PPPTS or PT. For SupRB, we use the evolution-strategy rule-discovery configuration, denoted SupRB-ES, because this is the reported configuration for which results are available on all six datasets. Its rule count is the number of rules in the final selected solution. The reported XCSF and SupRB-ES values were obtained in separate experimental campaigns and are therefore included as literature reference points, not as paired observations from our runs. Consequently, the tables are used for descriptive comparison only; we do not report cross-study statistical tests or average ranks.

B. Prediction Accuracy

Table S1 compares testing MSE in the standardized target space. Values for all methods are reported as the mean and standard deviation over 64 runs.

On the four benchmarks used in the main article, KACS obtains lower MSE than our uncompacted XCSF in every case: 0.14 vs. 0.32 on ASN, 0.06 vs. 0.07 on CCPP, 0.14 vs. 0.21 on CS, and 0.06 vs. 0.08 on EEC. Its MSE is also close to the literature reference values on ASN, CCPP, and CS, whereas the reported XCSF and SupRB-ES results are lower on EEC. These observations indicate that the favorable KACS–XCSF comparison is retained under the 64-run, standardized-target protocol, but they do not establish superiority over independently reported methods.

The two additional datasets give a more mixed result. On PPPTS, XCSF and KACS both obtain an MSE of 0.74, compared with 0.63 for SupRB-ES. On PT, our XCSF obtains the lowest MSE (0.09), followed by KACS (0.21) and SupRB-ES (0.31). Thus, the higher-dimensional real-world experiments do not support a claim that KACS uniformly provides the best predictive accuracy. Instead, they show that its relative performance depends on the dataset: KACS remains competitive on PT but does not improve upon XCSF on PPPTS.

Descriptively, KACS records lower mean testing MSE than the reported SupRB-ES values on ASN, CCPP, CS, and PT, whereas SupRB-ES records lower values on EEC and PPPTS. These results suggest that KACS can achieve predictive performance competitive with SupRB-ES. However, because the SupRB-ES values were obtained in independent experiments, this comparison should not be interpreted as evidence of statistical superiority.

TABLE S1

TESTING MSE ON THE SIX REAL-WORLD REGRESSION BENCHMARKS. VALUES ARE MEAN $\pm$ STANDARD DEVIATION OVER 64 RUNS. OUR XCSF AND KACS RESULTS WERE OBTAINED WITHOUT COMPACTION. THE LITERATURE VALUES ARE REPORTED BY HEIDER; SUPRB-ES USES EVOLUTION-STRATEGY RULE DISCOVERY. N/A INDICATES THAT NO CORRESPONDING XCSF RESULT WAS REPORTED. THE CROSS-STUDY RESULTS ARE PRESENTED DESCRIPTIVELY, WITHOUT STATISTICAL TESTS OR AVERAGE RANKS

Benchmark	#Samples	n	Ours (no compaction)		Reported by [4]	
			XCSF	KACS	XCSF (after compaction)	SupRB-ES (final solution)
ASN	1503	5	0.32 $\pm$ 0.08	0.14 $\pm$ 0.02	0.12 $\pm$ 0.16	0.15 $\pm$ 0.02
CCPP	9568	4	0.07 $\pm$ 0.00	0.06 $\pm$ 0.01	0.06 $\pm$ 0.00	0.07 $\pm$ 0.00
CS	1030	8	0.21 $\pm$ 0.05	0.14 $\pm$ 0.03	0.17 $\pm$ 0.13	0.15 $\pm$ 0.04
EEC	768	8	0.08 $\pm$ 0.02	0.06 $\pm$ 0.02	0.02 $\pm$ 0.02	0.04 $\pm$ 0.03
PPPTS	45739	9	0.74 $\pm$ 0.01	0.74 $\pm$ 0.04	N/A	0.63 $\pm$ 0.02
PT	5875	18	0.09 $\pm$ 0.02	0.21 $\pm$ 0.07	N/A	0.31 $\pm$ 0.03

TABLE S2
NUMBERS OF RULES ON THE SIX REAL-WORLD REGRESSION BENCHMARKS. NOTATION FOLLOWS TABLE S1

Benchmark	#Samples	n	Ours (no compaction)		Reported by [4]	
			XCSF	KACS	XCSF (after compaction)	SupRB-ES (final solution)
ASN	1503	5	2000 $\pm$ 410.8	1434 $\pm$ 40.38	1617.58 $\pm$ 413.12	43.3 $\pm$ 2.8
CCPP	9568	4	1898 $\pm$ 297.1	1927 $\pm$ 45.26	1922.71 $\pm$ 390.7	5.5 $\pm$ 0.8
CS	1030	8	2837 $\pm$ 434.5	1416 $\pm$ 42.30	481.68 $\pm$ 336.33	42.1 $\pm$ 2.9
EEC	768	8	2985 $\pm$ 391.4	1014 $\pm$ 35.34	707.94 $\pm$ 282.16	20.1 $\pm$ 2.2
PPPTS	45739	9	3001 $\pm$ 578.4	1405 $\pm$ 35.96	N/A	45.7 $\pm$ 3.6
PT	5875	18	4422 $\pm$ 999.9	3564 $\pm$ 89.64	N/A	38.8 $\pm$ 3.3

C. Rule Complexity

Table S2 reports the corresponding numbers of rules.

KACS uses fewer rules than our uncompacted XCSF on five of the six datasets; CCPP is the sole exception, where the counts are similar (1927 vs. 1898). The reduction is particularly pronounced on CS, EEC, and PPPTS. Nevertheless, the results also qualify the compactness claim made from the controlled KACS–XCSF comparison. The compacted XCSF models reported by Heider use fewer rules than KACS on CS and EEC, and SupRB-ES uses substantially fewer rules on every dataset, with only 5.5–45.7 rules on average. KACS should therefore be described as compact relative to the uncompacted XCSF configuration evaluated in our controlled experiments, not as the most compact LCS among the methods considered here.

Raw rule counts also represent different model structures. SupRB-ES selects a small final set of multidimensional rules, whereas KACS distributes one-dimensional rules among $(n + 1)(2n + 1) = 2n^2 + 3n + 1$ inner and outer submodels. This fixed decomposition imposes a structural cost because every submodel must maintain input coverage. Moreover, Heider did not report a directly comparable total parameter count for SupRB-ES. We therefore cannot infer a precise parameter-count ordering from Table S2, although its much smaller final rule sets clearly demonstrate greater rule-set compactness.

D. Interpretability of the Learned Models

A KACS population containing approximately 1000 or more macro-rules should not be regarded as a directly human-readable rule list. Its structure is nevertheless different from that of a flat XCSF population. Across the six datasets, KACS distributes its rules among 45 submodels for CCPP, 66 for ASN, 153 for CS and EEC, 190 for PPPTS, and 703 for PT. The observed totals therefore correspond to approximately 5.1–42.8 one-dimensional rules per submodel. Each submodel can be plotted and inspected as a one-dimensional local function, which provides structured inspectability that is not apparent from the total rule count alone.

This decomposition does not, however, guarantee global interpretability. A complete KACS prediction depends on the composition of all inner and outer submodels across $2n + 1$ channels. Understanding an individual one-dimensional submodel is considerably easier than reading thousands of multidimensional XCSF rules, but understanding the complete mapping still requires tracing many interacting local functions. In this sense, KACS is better characterized as a structured and visualizable model than as a globally transparent model.

SupRB-ES addresses interpretability more directly by selecting a small final set of multidimensional rules. Its 5.5–45.7-rule solutions are far closer to a model that can be inspected rule by rule than either the XCSF or KACS populations reported here. Accordingly, we do not claim that KACS is more globally interpretable than SupRB. The present results support parameter efficiency and structured inspectability relative to uncompacted XCSF, while SupRB-ES provides substantially greater final rule-set compactness. A formal comparison of interpretability—including visualization of learned KACS submodels, fidelity of local explanations, human-subject evaluation, and the effects of pruning or compaction—is left for future work.

S4. FORMULATIONS OF SYNTHETIC FUNCTIONS

This section summarizes the synthetic benchmark functions used in the main article. Fig. S1 illustrates each function for $n = 2$. The four synthetic benchmark functions are:

- **Rastrigin function** (f_1 , cf. Fig. S1a): a highly multimodal landscape with many local minima, defined as:

$$f_1(\mathbf{x}) = 10n + \sum_{i=1}^n \left(x_i^2 - 10 \cos(2\pi x_i) \right). \quad (15)$$

- **Rosenbrock function** (f_2 , cf. Fig. S1b): a narrow curved valley with strong interactions between adjacent variables, defined as:

$$f_2(\mathbf{x}) = \sum_{i=1}^{n-1} \left[100 \left(x_{i+1} - x_i^2 \right)^2 + (x_i - 1)^2 \right]. \quad (16)$$

- **Cross function** (f_3 , cf. Fig. S1c): axis-aligned ridge-like components along each coordinate axis and a central Gaussian peak, with interactions across all dimensions, defined as:

$$a = \frac{1}{\lfloor n/2 \rfloor} \sum_{i=1}^{\lfloor n/2 \rfloor} x_i, \quad b = \frac{1}{\lceil n/2 \rceil} \sum_{i=\lfloor n/2 \rfloor + 1}^n x_i, \quad (17)$$

$$f_3(\mathbf{x}) = \max \left(\exp(-10a^2), \exp(-50b^2), 1.25 \exp(-5(a^2 + b^2)) \right). \quad (18)$$

- **Styblinski-Tang function** (f_4 , cf. Fig. S1d): a separable nonconvex polynomial surface with multiple local minima per dimension, defined as:

$$f_4(\mathbf{x}) = \frac{1}{2} \sum_{i=1}^n \left(x_i^4 - 16x_i^2 + 5x_i \right). \quad (19)$$

These functions collectively cover multimodality (f_1), inter-variable curvature (f_2), anisotropic structure (f_3), and separable nonconvexity (f_4).




Fig. S1. Surface plots of the four synthetic test functions ($n = 2$) shown for visualization (same as Fig. 2 of the main article).

S5. A DESCRIPTION OF HYPERPARAMETERS

The following hyperparameters are commonly used in both XCSF and KACS.

- N : The maximum population size $\mathcal{P}$ (in micro-rules).
- ϵ_0 : The error threshold; rules with prediction error below ϵ_0 are considered accurate. A suitable tolerance can improve robustness to noise-induced error fluctuations and avoid unnecessary specialization, whereas an excessively large value can reduce approximation accuracy [5].
- β : The learning rate for updating prediction error, fitness, and match set size estimates.
- α : The fall-off coefficient in the accuracy calculation; controls the accuracy assigned when the prediction error is at or above ϵ_0 .
- ν : The power parameter for the accuracy calculation; controls the steepness of the accuracy fall-off.
- δ : The fraction of the mean fitness used as the threshold for rule deletion.
- m_0 : The maximum mutation range for interval parameters.
- r_0 : The maximum spread for the covering operator.
- χ : The crossover probability in the GA.
- μ : The mutation probability per allele in the GA.
- τ : The tournament size ratio for parent selection.
- θ_{GA} : The GA application threshold.
- θ_{del} : The experience threshold for rule deletion.
- θ_{sub} : The experience threshold for subsumption.
- $P_{\#}$: The probability of generating a $[0, 1]$ interval during covering.
- *doSubsumption*: A Boolean flag to enable GA subsumption.

S6. DETAILED STATISTICAL RESULTS

This section presents run-level statistics that complement Table II in the main article. For each benchmark and metric, Table S3 reports the mean and standard deviation over the same 30 train-test splits, together with the two-sided Wilcoxon signed-rank p -value and matched-pairs rank-biserial correlation. The effect size is computed from the paired differences XCSF–KACS; positive values favor KACS and negative values favor XCSF because lower values are preferable for every metric.

KACS shows its most consistent advantage in model complexity. Its parameter count and AIC are lower on all eight benchmarks, with an effect size of 1 in every comparison. Its rule count is also lower with an effect size of 1 on seven benchmarks; on CCPP, the rule counts are similar and the effect is small (0.0796). This pattern reflects the KA decomposition, which replaces full n -dimensional local models with one-dimensional submodels.

Accuracy depends more strongly on problem characteristics. For testing MAE, KACS shows positive effects on the four nonlinear synthetic functions (0.7462–1) and ASN (0.9484), supporting its advantage on problems with pronounced nonlinearity or cross-dimensional structure. On f_1 , the effect favors XCSF for training MAE (−0.5226) but KACS for testing MAE (0.7677), which, together with the large parameter-count difference, is consistent with greater overfitting by XCSF. The testing-MAE effects are smaller on CCPP (0.2430) and CS (0.2172), while EEC favors XCSF (−0.3462). For problems that are adequately represented by simpler linear models, the coordination of KACS’s inner and outer submodels can introduce additional approximation overhead, although KACS remains substantially more compact.

The standard deviations show that stability is metric dependent. KACS has lower standard deviations in rule count, parameter count, and AIC on all benchmarks. For testing MAE, however, KACS is less variable on ASN (0.0149 vs. 0.0222) and CS (0.0169 vs. 0.0231), but more variable on the synthetic functions, CCPP, and EEC. In the small-MAE cases, the standard deviations are 0.0029 for XCSF and 0.0073 for KACS on CCPP, and 0.0223 and 0.0314, respectively, on EEC. Thus, KACS provides consistently stable model complexity but does not uniformly reduce variability in prediction accuracy. All MAE statistics use the normalized target scale of the main experiments.

TABLE S3

DETAILED PAIRED COMPARISON OF XCSF AND KACS OVER 30 MATCHED RUNS FOR EACH BENCHMARK AND METRIC. VALUES ARE REPORTED AS THE MEAN $\pm$ STANDARD DEVIATION. GREEN CELLS INDICATE THE LOWER MEAN FOR EACH BENCHMARK AND METRIC. THE WILCOXON COLUMN REPORTS THE TWO-SIDED WILCOXON SIGNED-RANK p -VALUE COMPUTED FROM THE 30 PAIRED RUNS. THE EFFECT SIZE IS THE MATCHED-PAIRS RANK-BISERIAL CORRELATION COMPUTED FROM THE PAIRED DIFFERENCES (XCSF MINUS KACS); POSITIVE VALUES INDICATE THAT KACS TENDED TO PRODUCE LOWER VALUES, WHEREAS NEGATIVE VALUES INDICATE THAT XCSF TENDED TO PRODUCE LOWER VALUES

Benchmark	Metric	XCSF mean $\pm$ SD	KACS mean $\pm$ SD	Wilcoxon p	Effect size
f_1	Training MAE	0.2033 $\pm$ 0.0122	0.2194 $\pm$ 0.0291	0.0113	-0.5226
f_1	Testing MAE	0.2642 $\pm$ 0.0220	0.2351 $\pm$ 0.0250	8.86E-05	0.7677
f_1	#Rules	4162 $\pm$ 57.59	1341 $\pm$ 35.07	1.82E-06	1
f_1	#Parameters	45781 $\pm$ 633.5	2681 $\pm$ 70.13	1.86E-09	1
f_1	AIC	89207 $\pm$ 1266	3024 $\pm$ 262.6	1.86E-09	1
f_2	Training MAE	0.1124 $\pm$ 0.0119	0.1157 $\pm$ 0.0280	0.5838	0.1183
f_2	Testing MAE	0.1564 $\pm$ 0.0195	0.1253 $\pm$ 0.0274	0.0001529	0.7462
f_2	#Rules	4087 $\pm$ 56.88	1462 $\pm$ 37.63	1.82E-06	1
f_2	#Parameters	44960 $\pm$ 625.6	2924 $\pm$ 75.27	1.82E-06	1
f_2	AIC	86579 $\pm$ 1193	2342 $\pm$ 314.1	1.86E-09	1
f_3	Training MAE	0.2510 $\pm$ 0.0167	0.2097 $\pm$ 0.0395	4.42E-06	0.8667
f_3	Testing MAE	0.3246 $\pm$ 0.0250	0.2329 $\pm$ 0.0508	3.73E-09	0.9957
f_3	#Rules	4130 $\pm$ 74.08	1429 $\pm$ 36.94	1.82E-06	1
f_3	#Parameters	45426 $\pm$ 814.9	2857 $\pm$ 73.87	1.86E-09	1
f_3	AIC	88892 $\pm$ 1580	3324 $\pm$ 349.7	1.86E-09	1
f_4	Training MAE	0.1680 $\pm$ 0.0150	0.1334 $\pm$ 0.0301	2.08E-05	0.8194
f_4	Testing MAE	0.2303 $\pm$ 0.0183	0.1430 $\pm$ 0.0299	1.86E-09	1
f_4	#Rules	4170 $\pm$ 61.11	1414 $\pm$ 35.27	1.82E-06	1
f_4	#Parameters	45873 $\pm$ 672.2	2829 $\pm$ 70.54	1.86E-09	1
f_4	AIC	89078 $\pm$ 1300	2412 $\pm$ 425.1	1.86E-09	1
ASN	Training MAE	0.1434 $\pm$ 0.0203	0.1094 $\pm$ 0.0139	2.05E-07	0.9398
ASN	Testing MAE	0.1478 $\pm$ 0.0222	0.1144 $\pm$ 0.0149	1.30E-07	0.9484
ASN	#Rules	2224 $\pm$ 356.7	1417 $\pm$ 46.26	1.86E-09	1
ASN	#Parameters	13345 $\pm$ 2140	2834 $\pm$ 92.51	1.86E-09	1
ASN	AIC	22275 $\pm$ 3953	371.1 $\pm$ 344.2	1.86E-09	1
CCPP	Training MAE	0.0930 $\pm$ 0.0016	0.0918 $\pm$ 0.0062	0.1294	0.3204
CCPP	Testing MAE	0.0929 $\pm$ 0.0029	0.0926 $\pm$ 0.0073	0.2534	0.243
CCPP	#Rules	1953 $\pm$ 292.8	1924 $\pm$ 48.14	0.7112	0.0796
CCPP	#Parameters	9764 $\pm$ 1464	3848 $\pm$ 96.29	1.86E-09	1
CCPP	AIC	-17358 $\pm$ 2823	-29065 $\pm$ 1194	1.86E-09	1
CS	Training MAE	0.1299 $\pm$ 0.0198	0.1213 $\pm$ 0.0137	0.1191	0.329
CS	Testing MAE	0.1350 $\pm$ 0.0231	0.1288 $\pm$ 0.0169	0.3085	0.2172
CS	#Rules	2985 $\pm$ 393.1	1425 $\pm$ 34.58	1.86E-09	1
CS	#Parameters	26868 $\pm$ 3538	2851 $\pm$ 69.16	1.86E-09	1
CS	AIC	50453 $\pm$ 6860	2237 $\pm$ 229.1	1.86E-09	1
EEC	Training MAE	0.0820 $\pm$ 0.0202	0.0967 $\pm$ 0.0320	0.1048	-0.3419
EEC	Testing MAE	0.0847 $\pm$ 0.0223	0.1020 $\pm$ 0.0314	0.1004	-0.3462
EEC	#Rules	2925 $\pm$ 373.6	1012 $\pm$ 31.51	1.82E-06	1
EEC	Parameters	26326 $\pm$ 3363	2023 $\pm$ 63.02	1.86E-09	1
EEC	AIC	49849 $\pm$ 6567	1125 $\pm$ 302.7	1.86E-09	1

S7. ROBUSTNESS UNDER AN ALTERNATIVE EVALUATION PROTOCOL

A. Experimental Protocol

To examine whether the controlled XCSF–KACS comparison depends on the evaluation protocol used in the main article, we repeated the experiments on all eight benchmark problems using a protocol based on Heider’s evaluation design [3], [4]. The main experiments use 30 Monte Carlo splits with 90% of the samples for training, min–max-normalized targets, and MAE. In this alternative protocol, we instead used eight Monte Carlo splits and eight random seeds per split, yielding 64 matched runs for each method and problem. For each split, 75% of the samples were used for training and 25% for testing, the target was standardized, and prediction accuracy was evaluated using MSE.

The target standardization parameters were estimated from the training split and then applied to the corresponding test split. The synthetic inputs retained their prescribed $[0, 1]^n$ domains. For the real-world datasets, input-scaling parameters were estimated from the training split only and used to map the inputs to $[0, 1]^n$; the same transformations were then applied to the test split. This differs from Heider’s input range of $[-1, 1]^n$ because the present KACS formulation assumes inputs in $[0, 1]^n$. Thus, this experiment follows the principal elements of Heider’s evaluation design but is not an exact reproduction of all preprocessing choices.

XCSF and KACS used identical data splits and random seeds. Their hyperparameters, population budget ($N = 6400$), learning duration, and absence of post-training compaction were otherwise unchanged from the main experiments. Learning was disabled when evaluating the held-out test samples.

B. Main Results

Table S4 summarizes prediction accuracy, model complexity, and AIC under the alternative protocol. KACS obtains lower mean training and testing MSE than XCSF on all eight benchmark problems. The advantage is especially pronounced on the four synthetic functions, ASN, and CS, while the difference is smaller but remains statistically significant on CCPP and EEC. The across-problem paired Wilcoxon signed-rank test applied to the 64-run mean for each benchmark also favors KACS for both training and testing MSE ($p = 0.007813$).

KACS also uses fewer macro-rules on seven of the eight problems. CCPP is the only exception: XCSF uses 1898 rules on average and KACS uses 1927, with no significant difference between them. Despite these similar rule counts, KACS uses substantially fewer parameters on CCPP because every KACS rule has only two consequent parameters. Across all eight problems, KACS uses only approximately 5.9%–40.6% as many parameters as XCSF and obtains a lower AIC. The across-problem tests favor KACS for rule count ($p = 0.01563$), parameter count ($p = 0.007813$), and AIC ($p = 0.007813$).

TABLE S4

SUMMARY OF THE XCSF–KACS COMPARISON UNDER THE ALTERNATIVE EVALUATION PROTOCOL. VALUES ARE MEANS OVER 64 MATCHED RUNS CONSISTING OF EIGHT MONTE CARLO SPLITS AND EIGHT RANDOM SEEDS PER SPLIT. TRAINING AND TESTING ERRORS ARE MSE IN THE STANDARDIZED TARGET SPACE. GREEN CELLS INDICATE THE LOWER MEAN. FOR EACH PROBLEM, SYMBOLS +/–/~ DENOTE THAT XCSF IS SIGNIFICANTLY BETTER/WORSE/SIMILAR TO KACS BASED ON A TWO-SIDED PAIRED WILCOXON SIGNED-RANK TEST. RANK IS THE AVERAGE RANK ACROSS THE EIGHT PROBLEMS. THE p -VALUES IN THE FINAL ROW ARE FROM ACROSS-PROBLEM PAIRED WILCOXON SIGNED-RANK TESTS APPLIED TO THE 64-RUN MEAN VALUES. STATISTICAL SIGNIFICANCE IS AT $\alpha = 0.05$ (†)

	MODEL ACCURACY				MODEL COMPLEXITY				TRADE-OFF	
	Training MSE		Testing MSE		#Rules ($ \mathcal{P} $)		#Parameters (k)		AIC	
	XCSF	KACS	XCSF	KACS	XCSF	KACS	XCSF	KACS	XCSF	KACS
f_1	0.6028 –	0.5683	0.8825 –	0.6655	4198 –	1356	46175 –	2712	91970 –	4999
f_2	0.4405 –	0.2622	0.7426 –	0.3226	4178 –	1485	45954 –	2971	91292 –	4919
f_3	0.5968 –	0.2870	0.8707 –	0.3654	4174 –	1444	45919 –	2888	91450 –	4797
f_4	0.4797 –	0.2223	0.7784 –	0.2795	4188 –	1420	46069 –	2839	91583 –	4529
ASN	0.3203 –	0.1285	0.3232 –	0.1456	2000 –	1434	12000 –	2868	22688 –	3416
CCPP	0.0680 –	0.0631	0.0699 –	0.0653	1898 ~	1927	9490 –	3854	-310.4 –	-12171
CS	0.1955 –	0.1223	0.2098 –	0.1491	2837 –	1416	25535 –	2831	49788 –	4034
EEC	0.0770 –	0.0510	0.0842 –	0.0593	2985 –	1014	26867 –	2028	52228 –	2319
Rank	2.00↓†	1.00	2.00↓†	1.00	1.88↓†	1.12	2.00↓†	1.00	2.00↓†	1.00
+/-/~	0/8/0	-	0/8/0	-	0/7/1	-	0/8/0	-	0/8/0	-
p -value	0.007813	-	0.007813	-	0.01563	-	0.007813	-	0.007813	-

C. Statistical Results and Interpretation

Table S5 provides the means, standard deviations, paired Wilcoxon p -values, and matched-pairs rank-biserial correlations for all benchmark–metric combinations. All 16 training- and testing-MSE comparisons favor KACS significantly ($p < 0.001$). The corresponding effect sizes are positive and range from 0.5452 to 1 for training MSE and from 0.7635 to 1 for testing MSE. The parameter-count and AIC comparisons have an effect size of 1 on every benchmark. The rule-count comparisons also have an effect size of 1 except on CCPP, where the difference is nonsignificant ($p = 0.4458$; effect size = -0.1101).

Compared with the MAE-based results in the main article, the alternative protocol produces a more uniform accuracy advantage for KACS. Because KACS also obtains lower training MSE on every benchmark, this pattern cannot be explained solely by improved generalization from a comparable training fit; under this protocol, KACS fits both the training and test data more accurately according to squared error. These results strengthen the evidence that the favorable KACS–XCSF comparison is robust to a different target transformation, error metric, train–test ratio, and repetition design.

Nevertheless, the larger performance difference cannot be attributed to any single protocol component because target standardization, MSE, and the train–test ratio were changed simultaneously. In particular, MSE places greater weight on large residuals than MAE, and the smaller training fraction changes the amount of data available for fitting local models. Moreover, absolute MSE and AIC values should not be compared directly with those in the main experiments because the target scale and training-set size differ. We therefore treat this experiment as a robustness analysis rather than a replacement for the controlled main evaluation.

TABLE S5

DETAILED PAIRED COMPARISON OF XCSF AND KACS UNDER THE ALTERNATIVE EVALUATION PROTOCOL. VALUES ARE REPORTED AS THE MEAN $\pm$ STANDARD DEVIATION OVER 64 MATCHED RUNS. OTHER NOTATION FOLLOWS TABLE S3

Benchmark	Metric	XCSF mean $\pm$ SD	KACS mean $\pm$ SD	Wilcoxon p	Effect size
f_1	Training MSE	0.6028 $\pm$ 0.0533	0.5683 $\pm$ 0.0640	0.0001516	0.5452
f_1	Testing MSE	0.8825 $\pm$ 0.0866	0.6655 $\pm$ 0.0866	5.52E-12	0.9913
f_1	#Rules	4198 $\pm$ 62.85	1356 $\pm$ 41.14	3.60E-12	1
f_1	#Parameters	46175 $\pm$ 691.4	2712 $\pm$ 82.28	3.61E-12	1
f_1	AIC	91970 $\pm$ 1370	4999 $\pm$ 179.8	3.61E-12	1
f_2	Training MSE	0.4405 $\pm$ 0.0440	0.2622 $\pm$ 0.0714	7.17E-11	0.9375
f_2	Testing MSE	0.7426 $\pm$ 0.1222	0.3226 $\pm$ 0.0864	3.61E-12	1
f_2	#Rules	4178 $\pm$ 67.62	1485 $\pm$ 31.24	3.61E-12	1
f_2	#Parameters	45954 $\pm$ 743.9	2971 $\pm$ 62.49	3.61E-12	1
f_2	AIC	91292 $\pm$ 1463	4919 $\pm$ 207.2	3.61E-12	1
f_3	Training MSE	0.5968 $\pm$ 0.0550	0.2870 $\pm$ 0.0984	3.79E-12	0.999
f_3	Testing MSE	0.8707 $\pm$ 0.0765	0.3654 $\pm$ 0.1201	3.61E-12	1
f_3	#Rules	4174 $\pm$ 51.89	1444 $\pm$ 35.87	3.61E-12	1
f_3	#Parameters	45919 $\pm$ 570.8	2888 $\pm$ 71.74	3.61E-12	1
f_3	AIC	91450 $\pm$ 1121	4797 $\pm$ 307.1	3.61E-12	1
f_4	Training MSE	0.4797 $\pm$ 0.0611	0.2223 $\pm$ 0.0649	3.61E-12	1
f_4	Testing MSE	0.7784 $\pm$ 0.0702	0.2795 $\pm$ 0.0783	3.61E-12	1
f_4	#Rules	4188 $\pm$ 61.59	1420 $\pm$ 32.77	3.60E-12	1
f_4	#Parameters	46069 $\pm$ 677.5	2839 $\pm$ 65.54	3.61E-12	1
f_4	AIC	91583 $\pm$ 1336	4529 $\pm$ 217.0	3.61E-12	1
ASN	Training MSE	0.3203 $\pm$ 0.0720	0.1285 $\pm$ 0.0182	3.61E-12	1
ASN	Testing MSE	0.3232 $\pm$ 0.0792	0.1456 $\pm$ 0.0243	3.97E-12	0.9981
ASN	#Rules	2000 $\pm$ 410.8	1434 $\pm$ 40.38	3.61E-12	1
ASN	#Parameters	12000 $\pm$ 2465	2868 $\pm$ 80.77	3.61E-12	1
ASN	AIC	22688 $\pm$ 4671	3416 $\pm$ 191.6	3.61E-12	1
CCPP	Training MSE	0.0680 $\pm$ 0.0016	0.0631 $\pm$ 0.0090	1.24E-08	0.8192
CCPP	Testing MSE	0.0699 $\pm$ 0.0042	0.0653 $\pm$ 0.0086	3.13E-08	0.7962
CCPP	#Rules	1898 $\pm$ 297.1	1927 $\pm$ 45.26	0.4458	-0.1101
CCPP	#Parameters	9490 $\pm$ 1485	3854 $\pm$ 90.51	3.61E-12	1
CCPP	AIC	-310.4 $\pm$ 2911	-12171 $\pm$ 816.7	3.61E-12	1
CS	Training MSE	0.1955 $\pm$ 0.0471	0.1223 $\pm$ 0.0186	7.50E-11	0.9365
CS	Testing MSE	0.2098 $\pm$ 0.0461	0.1491 $\pm$ 0.0271	5.10E-10	0.8942
CS	#Rules	2837 $\pm$ 434.5	1416 $\pm$ 42.30	3.61E-12	1
CS	#Parameters	25535 $\pm$ 3910	2831 $\pm$ 84.60	3.61E-12	1
CS	AIC	49788 $\pm$ 7663	4034 $\pm$ 197.8	3.61E-12	1
EEC	Training MSE	0.0770 $\pm$ 0.0214	0.0510 $\pm$ 0.0155	2.59E-08	0.801
EEC	Testing MSE	0.0842 $\pm$ 0.0236	0.0593 $\pm$ 0.0196	1.12E-07	0.7635
EEC	#Rules	2985 $\pm$ 391.4	1014 $\pm$ 35.34	3.61E-12	1
EEC	#Parameters	26867 $\pm$ 3523	2028 $\pm$ 70.68	3.61E-12	1
EEC	AIC	52228 $\pm$ 6897	2319 $\pm$ 231.5	3.61E-12	1

S8. ADDITIONAL LEARNING CURVES

A. Training MAE Learning Curves

Fig. S2 presents the training MAE curves for all eight benchmark problems.




Fig. S2. Training MAE learning curves for all eight benchmark problems. Curves show the mean over 30 runs, and shaded regions denote 95% confidence intervals.

B. Testing MAE Learning Curves

Fig. S3 presents the testing MAE curves for all eight benchmark problems. Note that Figs. S3a–S3d reproduce Figs. 3a–3d from the main article.




Fig. S3. Testing MAE learning curves for all eight benchmark problems. Curves show the mean over 30 runs, and shaded regions denote 95% confidence intervals.

C. Parameter-Count Learning Curves

Fig. S4 summarizes the parameter-count trajectories during training. Compared with MAE reduction, parameter growth remains controlled, suggesting that KACS improves predictive accuracy without relying on uncontrolled model-size expansion. This compactness trend is observed consistently over all benchmark problems.




Fig. S4. Parameter-count learning curves for all eight benchmark problems. Curves show the mean over 30 runs, and shaded regions denote 95% confidence intervals.

S9. EFFECTS OF ROTATION, TRANSLATION, AND SCALING ON f_3

The original f_3 (cf. Fig. S5a) has ridges aligned with the coordinate axes, which would be a favorable structure for both KACS and XCSF. To test whether the advantage of KACS depends on this alignment, we evaluate both methods on a rotated variant of f_3 in which the ridges are tilted by 45° relative to the coordinate axes. To complement this primary rotation analysis, we also define translated and scaled variants of f_3 below.

A. Problem Definition

Define two aggregate variables

$$a = \frac{1}{\lfloor n/2 \rfloor} \sum_{i=1}^{\lfloor n/2 \rfloor} x_i, \quad b = \frac{1}{\lceil n/2 \rceil} \sum_{i=\lfloor n/2 \rfloor+1}^n x_i. \quad (20)$$

The 45° -rotated coordinates are

$$a_{\text{rot}} = \frac{a+b}{\sqrt{2}}, \quad b_{\text{rot}} = \frac{-a+b}{\sqrt{2}}. \quad (21)$$

The rotated f_3 is then defined as

$$f_3^{\text{rot}}(\mathbf{x}) = \max\left(\exp(-10 a_{\text{rot}}^2), \exp(-50 b_{\text{rot}}^2), 1.25 \exp\left(-5(a^2 + b^2)\right)\right). \quad (22)$$

The third term $1.25 \exp(-5(a^2 + b^2))$ does not change under rotation. Fig. S5b illustrates the rotated f_3 for $n = 2$.

The translated variant shifts every input coordinate by 0.20, i.e.,

$$z_i^{\text{tr}} = x_i - 0.20, \quad i = 1, \dots, n, \quad (23)$$

and

$$a_{\text{tr}} = \frac{1}{\lfloor n/2 \rfloor} \sum_{i=1}^{\lfloor n/2 \rfloor} z_i^{\text{tr}}, \quad b_{\text{tr}} = \frac{1}{\lceil n/2 \rceil} \sum_{i=\lfloor n/2 \rfloor+1}^n z_i^{\text{tr}}. \quad (24)$$

The translated f_3 is

$$f_3^{\text{tr}}(\mathbf{x}) = \max\left(\exp(-10 a_{\text{tr}}^2), \exp(-50 b_{\text{tr}}^2), 1.25 \exp\left[-5\left(a_{\text{tr}}^2 + b_{\text{tr}}^2\right)\right]\right). \quad (25)$$

Fig. S5c illustrates the translated f_3 for $n = 2$.

The scaled variant scales every input coordinate by a factor of 1.25, i.e.,

$$z_i^{\text{sc}} = 1.25 x_i, \quad i = 1, \dots, n, \quad (26)$$

and

$$a_{\text{sc}} = \frac{1}{\lfloor n/2 \rfloor} \sum_{i=1}^{\lfloor n/2 \rfloor} z_i^{\text{sc}}, \quad b_{\text{sc}} = \frac{1}{\lceil n/2 \rceil} \sum_{i=\lfloor n/2 \rfloor+1}^n z_i^{\text{sc}}. \quad (27)$$

The scaled f_3 is

$$f_3^{\text{sc}}(\mathbf{x}) = \max\left(\exp(-10 a_{\text{sc}}^2), \exp(-50 b_{\text{sc}}^2), 1.25 \exp\left[-5\left(a_{\text{sc}}^2 + b_{\text{sc}}^2\right)\right]\right). \quad (28)$$

Fig. S5d illustrates the scaled f_3 for $n = 2$.

All other experimental conditions follow the main article: $n = 10$, $N_S = 1000$, and 30 independent runs.

B. Experimental Results

Figs. S5e and S5f show the testing MAE learning curves for the original and rotated f_3 , respectively. On both problems, KACS achieves significantly lower testing MAE than XCSF at the end of training. After rotation, KACS accuracy improves slightly ($0.2329 \rightarrow 0.2184$) while XCSF accuracy degrades ($0.3246 \rightarrow 0.3430$), widening the gap between the two methods from 0.0917 to 0.1246.

Figs. S5g and S5h show the corresponding results for the translated and scaled variants. On the translated f_3 , the final testing MAE is 0.2901 for XCSF and 0.2478 for KACS, whereas on the scaled f_3 , it is 0.3911 and 0.2488, respectively. KACS therefore retains significantly lower testing MAE under both transformations. Relative to the original f_3 , the accuracy gap narrows from 0.0917 to 0.0423 after translation but widens to 0.1423 after scaling.

C. Discussion

XCSF uses axis-aligned rectangles to cover the input space. These rectangles fit well when the ridges of f_3 run along the coordinate axes, but become less efficient when the ridges are tilted, requiring more rules to cover the diagonal structure. This is why XCSF accuracy degrades after rotation (testing MAE: $0.3246 \rightarrow 0.3430$).

KACS decomposes the target function into sums of one-dimensional components following the KA theorem (cf. (1) in the main article). This additive structure is compatible with both the original and rotated ridges of f_3 , so the rotation does not disadvantage KACS. As a result, the accuracy gap between the two methods widens after rotation ($0.0917 \rightarrow 0.1246$), showing that the advantage of KACS does not depend on axis-aligned function structure.

Translation preserves the orientation and width of the ridges while moving their location by 0.20 and therefore introduces no orientation mismatch. Although the accuracy gap becomes smaller, KACS remains significantly more accurate, indicating that its advantage is not restricted to a function centered at the origin.

Scaling the inputs by 1.25 contracts the ridge widths to 80% of their original values, requiring finer spatial resolution. The larger degradation of XCSF is consistent with the need for finer multidimensional partitions, whereas KACS remains comparatively stable through its one-dimensional submodels.

Together with the rotation results, these findings show that the advantage of KACS persists across changes in the orientation, location, and spatial scale of f_3 .




Fig. S5. Original, rotated, translated, and scaled f_3 settings. (a)–(d): 3D landscapes of the original function and its rotated, translated by 0.20, and scaled by 1.25 variants. (e)–(h): corresponding testing MAE curves.

S10. SCALABILITY ANALYSIS — DETAILED RESULTS

A. Sample-Size Scaling

Table S6 reports detailed results under varying sample sizes $N_S \in \{125, 250, 500, 1000, 2000, 4000, 8000\}$ with $n = 10$ fixed. Table S7 reports the corresponding run-level variability, paired Wilcoxon p -values, and effect sizes for each sample size and metric.

Several patterns are evident. In training MAE, XCSF achieves significantly lower values than KACS at small sample sizes ($N_S \leq 250$), indicating that n -dimensional rules overfit when data are scarce. This gap narrows and reverses as N_S increases: from $N_S = 1000$ onward, KACS achieves significantly lower training MAE, suggesting that one-dimensional submodels become more effective as more data are available per subproblem. In testing MAE, KACS consistently achieves significantly lower values across all sample sizes ($p = 0.0156$), confirming that the generalization advantage of KA-based decomposition holds regardless of data volume.

Fig. S6 provides an anytime view of testing MAE for all sample sizes. XCSF improves rapidly during the early iterations but subsequently changes only gradually, reaching an apparent plateau for most settings and showing increasing testing error at $N_S = 250$. In contrast, KACS requires a longer warm-up but continues to improve and approaches a lower testing-MAE level. For $N_S \geq 500$, the XCSF curves vary little during the latter half of training while a clear accuracy gap remains. At $N_S = 125$, both curves remain relatively variable and KACS is still improving at the final iteration; nevertheless, XCSF has already stabilized at a higher error level.

Model complexity shows a clear structural difference. XCSF rules and parameters grow monotonically with N_S (3164 to 4724 rules; 34800 to 51960 parameters), whereas KACS remains compact throughout (1242–1430 rules; 2484–2860 parameters). The AIC advantage of KACS widens substantially as N_S increases: at $N_S = 8000$, KACS achieves an AIC of -13090 compared with 90170 for XCSF, reflecting both higher accuracy and dramatically fewer parameters at large data scales.

TABLE S6

SUMMARY OF SAMPLE-SIZE SCALABILITY ANALYSIS. GREEN INDICATES THE BEST VALUE. RANK IS THE AVERAGE RANK ACROSS PROBLEMS. SYMBOLS $+/-/\sim$ DENOTE SIGNIFICANTLY BETTER/WORSE/SIMILAR PERFORMANCE COMPARED WITH KACS BY THE WILCOXON SIGNED-RANK TEST. ARROWS $\uparrow/\downarrow$ INDICATE RANK IMPROVEMENT/DECLINE RELATIVE TO KACS. STATISTICAL SIGNIFICANCE IS AT $\alpha = 0.05$ ($\dagger$)

N_S	MODEL ACCURACY				MODEL COMPLEXITY				TRADE-OFF	
	Training MAE		Testing MAE		#Rules ($ \mathcal{P} $)		#Parameters (k)		AIC	
	XCSF	KACS	XCSF	KACS	XCSF	KACS	XCSF	KACS	XCSF	KACS
125	0.0124 +	0.2077	0.4156 ~	0.3798	3164 –	1242	34802 –	2484	68860 –	4652
250	0.0893 +	0.207	0.3964 –	0.3308	3585 –	1333	39436 –	2666	78067 –	4722
500	0.1805 ~	0.1903	0.3484 –	0.2246	3924 –	1353	43166 –	2707	85158 –	4137
1000	0.2510 –	0.2097	0.3246 –	0.2329	4130 –	1429	45426 –	2857	88892 –	3324
2000	0.2824 –	0.2080	0.3095 –	0.2177	4327 –	1441	47597 –	2882	91538 –	886.6
4000	0.3027 –	0.2098	0.3129 –	0.2131	4521 –	1406	49731 –	2812	92463 –	-3964
8000	0.3075 –	0.2146	0.3117 –	0.2159	4724 –	1430	51964 –	2860	90165 –	-13089
Rank	1.57↓	1.43	2.00↓ [†]	1.00	2.00↓ [†]	1.00	2.00↓ [†]	1.00	2.00↓ [†]	1.00
$+/-/\sim$	2/4/1	-	0/6/1	-	0/7/0	-	0/7/0	-	0/7/0	-
p -value	1	-	0.0156	-	0.0156	-	0.0156	-	0.0156	-

TABLE S7
DETAILED PAIRED COMPARISON OF XCSF AND KACS OVER 30 MATCHED RUNS FOR EACH SAMPLE SIZE AND METRIC. NOTATION FOLLOWS
TABLE S3

N_S	Metric	XCSF mean $\pm$ SD	KACS mean $\pm$ SD	Wilcoxon p	Effect size
125	Training MAE	0.0124 $\pm$ 0.0080	0.2077 $\pm$ 0.0775	1.86E-09	-1
125	Testing MAE	0.4156 $\pm$ 0.0814	0.3798 $\pm$ 0.0953	0.1241	0.3247
125	#Rules	3164 $\pm$ 82.06	1242 $\pm$ 45.36	1.82E-06	1
125	#Parameters	34802 $\pm$ 902.7	2484 $\pm$ 90.71	1.86E-09	1
125	AIC	68860 $\pm$ 1857	4652 $\pm$ 176.2	1.86E-09	1
250	Training MAE	0.0893 $\pm$ 0.0297	0.2070 $\pm$ 0.0464	1.86E-09	-1
250	Testing MAE	0.3964 $\pm$ 0.0717	0.3308 $\pm$ 0.0760	0.001232	0.6516
250	#Rules	3585 $\pm$ 69.45	1333 $\pm$ 42.34	1.82E-06	1
250	#Parameters	39436 $\pm$ 763.9	2666 $\pm$ 84.68	1.86E-09	1
250	AIC	78067 $\pm$ 1593	4722 $\pm$ 196.1	1.86E-09	1
500	Training MAE	0.1805 $\pm$ 0.0265	0.1903 $\pm$ 0.0378	0.1772	-0.286
500	Testing MAE	0.3484 $\pm$ 0.0471	0.2246 $\pm$ 0.0515	1.86E-09	1
500	#Rules	3924 $\pm$ 63.14	1353 $\pm$ 39.37	1.82E-06	1
500	#Parameters	43166 $\pm$ 694.5	2707 $\pm$ 78.74	1.86E-09	1
500	AIC	85158 $\pm$ 1387	4137 $\pm$ 213.1	1.86E-09	1
1000	Training MAE	0.2510 $\pm$ 0.0167	0.2097 $\pm$ 0.0395	4.42E-06	0.8667
1000	Testing MAE	0.3246 $\pm$ 0.0250	0.2329 $\pm$ 0.0508	3.73E-09	0.9957
1000	#Rules	4130 $\pm$ 74.08	1429 $\pm$ 36.94	1.82E-06	1
1000	#Parameters	45426 $\pm$ 814.9	2857 $\pm$ 73.87	1.86E-09	1
1000	AIC	88892 $\pm$ 1580	3324 $\pm$ 349.7	1.86E-09	1
2000	Training MAE	0.2824 $\pm$ 0.0086	0.2080 $\pm$ 0.0609	1.22E-05	0.8366
2000	Testing MAE	0.3095 $\pm$ 0.0160	0.2177 $\pm$ 0.0663	3.79E-06	0.871
2000	#Rules	4327 $\pm$ 69.43	1441 $\pm$ 35.93	1.82E-06	1
2000	#Parameters	47597 $\pm$ 763.8	2882 $\pm$ 71.85	1.86E-09	1
2000	AIC	91538 $\pm$ 1521	886.6 $\pm$ 817.7	1.86E-09	1
4000	Training MAE	0.3027 $\pm$ 0.0070	0.2098 $\pm$ 0.0483	1.86E-08	0.9785
4000	Testing MAE	0.3129 $\pm$ 0.0147	0.2131 $\pm$ 0.0469	3.73E-09	0.9957
4000	#Rules	4521 $\pm$ 50.57	1406 $\pm$ 30.42	1.82E-06	1
4000	#Parameters	49731 $\pm$ 556.3	2812 $\pm$ 60.85	1.86E-09	1
4000	AIC	92463 $\pm$ 1033	-3964 $\pm$ 1445	1.86E-09	1
8000	Training MAE	0.3075 $\pm$ 0.0059	0.2146 $\pm$ 0.0468	1.30E-08	0.9828
8000	Testing MAE	0.3117 $\pm$ 0.0099	0.2159 $\pm$ 0.0491	1.86E-08	0.9785
8000	#Rules	4724 $\pm$ 57.72	1430 $\pm$ 32.93	1.82E-06	1
8000	#Parameters	51964 $\pm$ 634.9	2860 $\pm$ 65.86	1.86E-09	1
8000	AIC	90165 $\pm$ 1255	-13089 $\pm$ 2853	1.86E-09	1




Fig. S6. Testing MAE learning curves of XCSF and KACS on f_3 under varying sample sizes, with the input dimension fixed at $n = 10$.

B. Dimensional Scaling

Table S8 reports detailed results as the input dimension n varies from 2 to 20 with $N_S = 1000$ fixed. Table S9 reports the corresponding run-level variability, paired Wilcoxon p -values, and effect sizes for each dimension and metric.

In the practical regime ($n \leq 16$), KACS achieves significantly lower testing MAE than XCSF at all dimensions. The accuracy gap is largest at $n = 2$ (0.0883 vs. 0.1582) and remains consistent through $n = 14$ (0.2021 vs. 0.3066). Notably, XCSF testing MAE does not grow monotonically with n : it peaks around $n = 6$ (0.3292) and slightly decreases at higher dimensions, while KACS testing MAE remains stable between 0.20 and 0.25 up to $n = 14$.

At $n \geq 18$ under the default budget $N = 6400$, KACS degrades sharply: testing MAE rises to 0.3842 at $n = 18$ and 1.2500 at $n = 20$, at which point XCSF achieves significantly better accuracy. As discussed in Section VI-C4 of the main article, this failure is caused by the cover-delete cycle that occurs when N is too small relative to the $(2n^2 + 3n + 1)$ subproblems. Using the scaled budgets $N = 15984$ and $N = 19680$ for $n = 18$ and $n = 20$, respectively, KACS recovers and again achieves significantly lower testing MAE than XCSF (0.2115 vs. 0.2768 at $n = 18$; 0.1970 vs. 0.2833 at $n = 20$), confirming that the degradation is a capacity issue rather than an inherent limitation of KACS.

Model complexity confirms the structural efficiency of KACS throughout. XCSF parameters grow monotonically from 4504 ($n = 2$) to 110,900 ($n = 20$), whereas KACS parameters remain between 2372 and 3909 across all dimensions, including the high-dimensional failure cases. The AIC advantage of KACS holds for $n \leq 16$ (e.g., 2120 vs. 138,200 at $n = 14$) and reverses only partially at $n \geq 18$ under $N = 6400$, where KACS accuracy collapses despite its compact parameter count. At $n = 2$, KACS rule count (1955) slightly exceeds that of XCSF (1501), the only exception across all conditions, reflecting the fixed submodel structure of KACS at low dimensions.

TABLE S8
SUMMARY OF DIMENSIONALITY SCALABILITY ANALYSIS. NOTATION FOLLOWS TABLE S6

n	MODEL ACCURACY				MODEL COMPLEXITY				TRADE-OFF	
	Training MAE		Testing MAE		#Rules ($ \mathcal{P} $)		#Parameters (k)		AIC	
	XCSF	KACS	XCSF	KACS	XCSF	KACS	XCSF	KACS	XCSF	KACS
2	0.1459 –	0.0831	0.1582 –	0.0883	1501 +	1955	4504 –	3909	6251 –	3792
4	0.2210 ~	0.2145	0.2656 –	0.2345	2829 –	1862	14145 –	3725	26047 –	5125
6	0.2632 –	0.2174	0.3292 –	0.2417	3423 –	1723	23960 –	3447	45884 –	4575
8	0.2525 –	0.2076	0.3269 –	0.2208	3837 –	1540	34529 –	3079	67024 –	3765
10	0.2510 –	0.2097	0.3246 –	0.2329	4130 –	1429	45426 –	2857	88892 –	3324
12	0.2355 –	0.2117	0.3224 –	0.2252	4439 –	1311	57703 –	2623	113331 –	2787
14	0.2398 –	0.1870	0.3066 –	0.2021	4674 –	1186	70114 –	2372	138194 –	2120
16	0.2234 ~	0.2359	0.2770 –	0.2513	4890 –	1209	83137 –	2418	164127 –	2713
18	0.2388 +	0.3712	0.2749 +	0.3842	5067 –	1400	96268 –	2801	190490 –	4335
20	0.2395 +	1.2015	0.2706 +	1.2497	5283 –	1862	110941 –	3725	219841 –	8259
Rank	1.70↓	1.30	1.80↓	1.20	1.90↓ [†]	1.10	2.00↓ [†]	1.00	2.00↓ [†]	1.00
+/-/~	2/6/2	-	2/8/0	-	1/9/0	-	0/10/0	-	0/10/0	-
p -value	0.557	-	0.432	-	0.00391	-	0.00195	-	0.00195	-

TABLE S9

DETAILED PAIRED COMPARISON OF XCSF AND KACS OVER 30 MATCHED RUNS FOR EACH DIMENSION AND METRIC. NOTATION FOLLOWS TABLE S3

<i>n</i>	Metric	XCSF mean $\pm$ SD	KACS mean $\pm$ SD	Wilcoxon <i>p</i>	Effect size
2	Training MAE	0.1459 $\pm$ 0.0528	0.0831 $\pm$ 0.0203	8.33E-07	0.9097
2	Testing MAE	0.1582 $\pm$ 0.0637	0.0883 $\pm$ 0.0223	6.92E-06	0.8538
2	#Rules	1501 $\pm$ 220.6	1955 $\pm$ 96.36	1.82E-06	-1
2	#Parameters	4504 $\pm$ 661.9	3909 $\pm$ 192.7	4.41E-05	0.7935
2	AIC	6251 $\pm$ 995.4	3792 $\pm$ 497.9	9.31E-09	0.9871
4	Training MAE	0.2210 $\pm$ 0.0209	0.2145 $\pm$ 0.0226	0.4045	0.1785
4	Testing MAE	0.2656 $\pm$ 0.0310	0.2345 $\pm$ 0.0301	0.0001529	0.7462
4	#Rules	2829 $\pm$ 84.79	1862 $\pm$ 42.24	1.82E-06	1
4	#Parameters	14145 $\pm$ 423.9	3725 $\pm$ 84.48	1.86E-09	1
4	AIC	26047 $\pm$ 767.7	5125 $\pm$ 222.9	1.86E-09	1
6	Training MAE	0.2632 $\pm$ 0.0194	0.2174 $\pm$ 0.0288	1.64E-07	0.9441
6	Testing MAE	0.3292 $\pm$ 0.0228	0.2417 $\pm$ 0.0349	1.86E-09	1
6	#Rules	3423 $\pm$ 78.47	1723 $\pm$ 34.24	1.82E-06	1
6	#Parameters	23960 $\pm$ 549.3	3447 $\pm$ 68.48	1.86E-09	1
6	AIC	45884 $\pm$ 1045	4575 $\pm$ 282.3	1.86E-09	1
8	Training MAE	0.2525 $\pm$ 0.0169	0.2076 $\pm$ 0.0372	9.22E-06	0.8452
8	Testing MAE	0.3269 $\pm$ 0.0242	0.2208 $\pm$ 0.0359	1.86E-09	1
8	#Rules	3837 $\pm$ 73.09	1540 $\pm$ 41.68	1.86E-09	1
8	#Parameters	34529 $\pm$ 657.8	3079 $\pm$ 83.37	1.86E-09	1
8	AIC	67024 $\pm$ 1286	3765 $\pm$ 300.7	1.86E-09	1
10	Training MAE	0.2510 $\pm$ 0.0167	0.2097 $\pm$ 0.0395	4.42E-06	0.8667
10	Testing MAE	0.3246 $\pm$ 0.0250	0.2329 $\pm$ 0.0508	3.73E-09	0.9957
10	#Rules	4130 $\pm$ 74.08	1429 $\pm$ 36.94	1.82E-06	1
10	#Parameters	45426 $\pm$ 814.9	2857 $\pm$ 73.87	1.86E-09	1
10	AIC	88892 $\pm$ 1580	3324 $\pm$ 349.7	1.86E-09	1
12	Training MAE	0.2355 $\pm$ 0.0185	0.2117 $\pm$ 0.0928	0.01454	0.5054
12	Testing MAE	0.3224 $\pm$ 0.0222	0.2252 $\pm$ 0.0927	4.42E-06	0.8667
12	#Rules	4439 $\pm$ 44.61	1311 $\pm$ 37.30	1.86E-09	1
12	#Parameters	57703 $\pm$ 580.0	2623 $\pm$ 74.60	1.86E-09	1
12	AIC	113331 $\pm$ 1156	2787 $\pm$ 593.1	1.86E-09	1
14	Training MAE	0.2398 $\pm$ 0.0175	0.1870 $\pm$ 0.0530	3.24E-06	0.8753
14	Testing MAE	0.3066 $\pm$ 0.0206	0.2021 $\pm$ 0.0595	1.86E-08	0.9785
14	#Rules	4674 $\pm$ 48.48	1186 $\pm$ 33.29	1.86E-09	1
14	#Parameters	70114 $\pm$ 727.2	2372 $\pm$ 66.59	1.86E-09	1
14	AIC	138194 $\pm$ 1437	2120 $\pm$ 551.8	1.86E-09	1
16	Training MAE	0.2234 $\pm$ 0.0149	0.2359 $\pm$ 0.0365	0.0961	-0.3505
16	Testing MAE	0.2770 $\pm$ 0.0256	0.2513 $\pm$ 0.0422	0.01454	0.5054
16	#Rules	4890 $\pm$ 54.43	1209 $\pm$ 31.91	1.86E-09	1
16	#Parameters	83137 $\pm$ 925.3	2418 $\pm$ 63.83	1.86E-09	1
16	AIC	164127 $\pm$ 1828	2713 $\pm$ 277.5	1.86E-09	1
18	Training MAE	0.2388 $\pm$ 0.0124	0.3712 $\pm$ 0.0537	1.86E-09	-1
18	Testing MAE	0.2749 $\pm$ 0.0219	0.3842 $\pm$ 0.0643	3.73E-09	-0.9957
18	#Rules	5067 $\pm$ 51.70	1400 $\pm$ 42.87	1.82E-06	1
18	#Parameters	96268 $\pm$ 982.3	2801 $\pm$ 85.74	1.82E-06	1
18	AIC	190490 $\pm$ 1946	4335 $\pm$ 380.9	1.86E-09	1
20	Training MAE	0.2395 $\pm$ 0.0156	1.2015 $\pm$ 0.1632	1.86E-09	-1
20	Testing MAE	0.2706 $\pm$ 0.0322	1.2497 $\pm$ 0.2080	1.86E-09	-1
20	#Rules	5283 $\pm$ 78.45	1862 $\pm$ 37.57	1.82E-06	1
20	#Parameters	110941 $\pm$ 1647	3725 $\pm$ 75.14	1.86E-09	1
20	AIC	219841 $\pm$ 3369	8259 $\pm$ 322.6	1.86E-09	1

S11. COVERING DYNAMICS AND COVER-DELETE BEHAVIOR

To examine whether XCSF and KACS repeatedly lose input coverage during training, we recorded the number of match sets that invoked covering. For a recording interval of L iterations, let C_X , C_K , C_{in} , and C_{out} denote the numbers of covering events in XCSF, all KACS submodels, the KACS inner submodels, and the KACS outer submodels, respectively. We calculate

$$r_{XCSF} = \frac{C_X}{L}, \quad r_{KACS} = \frac{C_K}{L(2n^2 + 3n + 1)}, \quad (29)$$

$$r_{inner} = \frac{C_{in}}{Ln(2n + 1)}, \quad r_{outer} = \frac{C_{out}}{L(2n + 1)}. \quad (30)$$

Thus, each rate is the fraction of match-set evaluations that require covering, which accounts for the different numbers of match sets evaluated by XCSF and KACS.

Fig. S7 shows that both methods require frequent covering during initialization. Thereafter, the XCSF covering rate rapidly approaches zero and remains negligible on all eight problems. Thus, under the standard experimental settings, XCSF does not regularly exhibit recurring coverage gaps that would indicate a cover-delete cycle. The overall KACS covering rate also decreases sharply, but remains nonzero throughout training. This persistence is most pronounced on the four synthetic problems and CS, while it is smaller on ASN, CCPP, and EEC.

The near-zero XCSF covering rate is consistent with its high rule density within a single population. As reported in Table II of the main article, XCSF retains 1953–4170 macro-rules, all of which are tested when constructing its single match set. In contrast, KACS distributes 1012–1924 macro-rules among $2n^2 + 3n + 1$ submodels. For example, the $n = 10$ synthetic problems have 231 submodels and 1341–1462 KACS macro-rules, corresponding to only about 5.8–6.3 macro-rules per submodel on average. This substantially lower per-submodel rule density makes a KACS match set more likely to become empty. This interpretation concerns antecedent coverage and rule allocation rather than the total number of consequent parameters, because covering is triggered by an empty match set.




Fig. S7. Covering-rate trajectories of XCSF and KACS during training on the eight benchmark problems. Rates are normalized by the number of match-set evaluations. Curves show the mean over 30 runs, and shaded regions denote 95% confidence intervals.

Fig. S8 localizes this behavior within the KACS architecture. The covering rate of the inner submodels approaches zero after initialization on every problem, following a pattern similar to XCSF. In contrast, the outer submodels continue to invoke covering throughout training, although the magnitude is problem dependent. This difference is consistent with the distinct input domains of the two submodel types: inner submodels always receive inputs in $[0, 1]$, whereas the outer inputs $\hat{z}_q$ change as the inner functions are learned and can span a substantially wider range. Consequently, recurrent coverage gaps are concentrated in the outer submodels rather than being a general property of all KACS rulesets.

Persistent late-stage covering indicates that stable outer-submodel coverage is not always maintained and is therefore consistent with recurrent cover-delete behavior. Moreover, this behavior does not cause a general accuracy failure under the standard settings, where KACS remains competitive despite the nonzero outer covering rate. On the other hand, persistent

outer-submodel covering becomes harmful when the population budget is too small to maintain adequate coverage, as observed in the high-dimensional experiments analyzed in Section VI-C4 of the main article. In summary, XCSF and the KACS inner submodels maintain stable coverage after initialization, whereas the dynamically changing outer domains make the KACS outer submodels more susceptible to recurrent covering.




Fig. S8. Covering-rate trajectories of the inner and outer KACS submodels during training on the eight benchmark problems. Each rate is normalized by the number of match-set evaluations for the corresponding submodel type. Curves show the mean over 30 runs, and shaded regions denote 95% confidence intervals.

REFERENCES

- [1] C. De Boor, *A practical guide to splines*. Springer New York, 1978, vol. 27.
- [2] J. Park and I. W. Sandberg, “Universal approximation using radial-basis-function networks,” *Neural Comput.*, vol. 3, no. 2, pp. 246–257, 1991.
- [3] M. Heider, H. Stegherr, R. Sraj, D. Pätz, J. Wurth, and J. Hähner, “SupRB in the context of rule-based machine learning methods: A comparative study,” *Appl. Soft Comput.*, p. 110706, 2023.
- [4] M. Heider, “Disentangling the model selection tasks for improved explainability in a rule-based machine learning system,” Ph.D. dissertation, Universität Augsburg, 2025.
- [5] R. J. Urbanowicz and W. N. Browne, *Introduction to Learning Classifier Systems*, 1st ed. Springer Publishing Company, Incorporated, 2017.