

Latent space bias directions in LLMs capture confidence, not fairness

STEPHANIE BUTTIGIEG^{*✉}, Institute of Astronomy & Kavli Institute for Cosmology, University of Cambridge, UK
 MAEVE MADIGAN, PARAMESWARAN KAMALARUBAN, STUART BURRELL, Risk and Security AI
 Lab, Visa Inc., UK

Activation steering has gained popularity as a lightweight inference-time debiasing technique for large language models. However, prior work reports that steering vectors generalise poorly, with unintended effects on model performance and limited transfer to new datasets. Our work analyses what the debiasing direction used for activation steering actually encodes, in order to shed light on its inconsistent performance. We study the linear debiasing direction obtained by contrasting the activations of anti-biased and biased prompts, and evaluate it as a steering intervention across bias and general knowledge benchmarks. We find that this direction is dominated by model confidence, pointing from regions of high to low-probability tokens in activation space rather than encoding a meaningful representation of model bias. Steering along it does reduce measured bias, but this is a consequence of reducing model confidence: on QA benchmarks we find that this steering drives the model to abstain from answering, with a side effect of improving fairness metrics. Our experiments show that model confidence is the dominant separating factor between biased and anti-biased prompts in hidden space, indicating that isolating a linear representation of bias which is disentangled from model confidence is difficult and steering-based debiasing results should be interpreted with care. In short, steering appears to reduce bias, not by correcting the model’s underlying preferences, but by making it less confident, even on tasks unrelated to bias.

CCS Concepts: • **Computing methodologies** → **Artificial intelligence**; **Natural language generation**; **Machine learning**; • **Social and professional topics** → **Computing / technology policy**.

Additional Key Words and Phrases: Large language models, activation steering, fairness and bias, interpretability.

1 Introduction

Large language models (LLMs) exhibit the social biases inherited from their training data [3, 8, 16, 34], and their widespread deployment risks propagating unfair stereotypes into real-world applications [24]. Among the proposed mitigation strategies, activation steering is a popular inference-time solution for suppressing the biased behaviour of LLMs [15, 28, 33, 36]. Steering takes advantage of the linear representation hypothesis [25], under which meaningful semantic concepts are encoded linearly in the LLM activation space. A steering vector representing the target behaviour is added to the model’s residual stream to shift the model’s outputs towards the intended behaviour. For debiasing, a debiasing vector is obtained by contrasting the activations of anti-biased and biased prompts [28]. Previous studies [7, 17, 19, 30] have shown that steering along the direction of this debiasing vector reduces bias across benchmarks such as the Bias Benchmark for QA (BBQ) [26], CrowS-Pairs [23] and StereoSet [22].

However, debiasing by activation steering often has unintended consequences on attributes such as model accuracy on general knowledge tasks [7, 30], and steering vectors extracted from a single bias benchmark dataset show limited effectiveness when used to debias a new dataset [17, 30]. These two failure modes suggest that the underlying steering vector may not encode a global bias direction. This problem of steering reliability goes beyond fairness and bias, with [32] showcasing the poor generalisability of steering vectors, and [27] highlighting the need for more quantifiable

^{*}Work completed during an internship at Visa Inc.

Authors’ Contact Information: [Stephanie Buttigieg, sb2583@cam.ac.uk](mailto:Stephanie.Buttigieg@cam.ac.uk), Institute of Astronomy & Kavli Institute for Cosmology, University of Cambridge, Cambridge, UK; [Maeve Madigan, Parameswaran Kamalaruban, Stuart Burrell, Risk and Security AI Lab, Visa Inc., Cambridge, UK, {mmadigan, kaparama, sburrell}@visa.com](mailto:Maeve.Madigan@visa.com).




Fig. 1. An illustration of the paper’s two central claims, for Llama-3.1-8B-Instruct. **Left:** distribution of the linear classifier bias score $P(\text{biased})$, trained on ambiguous BBQ contexts, evaluated on BBQ disambiguated contexts and labelled as biased (pink) or anti-biased (teal) answer type. The linear classifier poorly separates the biased and anti-biased prompts, achieving an AUROC of only 0.57. **Centre:** Same as the left panel but labelled by whether the scored answer is the model’s highest- (purple) or lowest- (green) probability choice. The classifier achieves a higher separability on confidence than on bias, with an AUROC of 0.94. **Right:** mean probability assigned to biased (pink), anti-biased (teal) and neutral/abstain (grey) answers on BBQ (ambig.) as a function of activation-steering strength α along the debiasing direction. Steering increases the rate of abstention rather than correcting the underlying biased/anti-biased preference, consistent with the direction being dominated by confidence rather than bias.

and less subjective steering evaluations. We extend this line of critique to LLM fairness, and address the following question:

When biased and anti-biased prompts are found to be linearly separable in activation space, what does the separating direction actually encode?

Our first contribution is to show that the debiasing direction in activation space is dominated by a *confidence* component rather than a direction that purely represents model bias. We show that although biased and anti-biased prompts are found to be linearly separable in intermediate model layers, the separating factor is the likelihood difference between the tokens, with the resulting vector pointing from high- to low-likelihood regions of activation space. Fig. 1 (left) shows that a logistic regression classifier trained on the hidden space embeddings of biased and anti-biased prompts from the BBQ dataset performs poorly as a classifier of biased and anti-biased prompts in disambiguated contexts, while Fig. 1 (middle) shows that the same classifier cleanly separates the same prompts by highest versus lowest likelihood.

Our second contribution is to investigate the impact of steering, equipped with the understanding that using this debiasing vector will shift the model towards low-likelihood responses. We apply activation steering to a suite of LLMs and evaluate the impact on bias benchmarks (BBQ [26], CrowS-Pairs [23] and StereoSet [22]) and general knowledge QA benchmarks (MMLU [11], OpenBookQA [21]). Consistent with previous works using steering to debias, we find that activation steering does indeed reduce model bias: the Llama-3.1-8B-Instruct bias score on BBQ ambiguous prompts is reduced from 0.08 to 0.01, indicating very low levels of bias. However, as shown in Fig. 1 (right) this reduction is driven by abstention: when the model is given the option to abstain from responding (e.g. “I don’t know”), steering pushes the model towards abstention rather than correcting the underlying stereotype preference. As we will discuss in Sec. 5, activation steering along this debiasing direction lowers the model’s confidence, resulting in unintended effects on model confidence, accuracy and entropy.

Overall, our work shows that steering for LLM debiasing does not correct the underlying stereotyped associations, instead shifting the model’s certainty in its responses in such a way that has unintended consequences on model

accuracy and entropy. We argue that reported debiasing via steering should be interpreted with care: what is observed as reduced bias is an artifact of a confounding effect between model confidence and bias rather than evidence of a fairer model.

The rest of the paper is organised as follows. Sec. 2 reviews related work. Sec. 3 describes the datasets, models and evaluation metrics used. Sec. 4 quantifies the amount of societal bias present in LLMs, describes the construction of a linear classifier used to capture this bias in hidden states, and shows that this bias classifier is in fact capturing model confidence rather than genuine semantic bias. Sec. 5 then explores the implication of this confidence-driven debiasing direction on model behaviour as the model is steered away from it. We discuss our results and conclude in Sec. 6.

2 Related Work

Activation steering: Activation steering has been applied to steer models towards or away from a range of behaviours including sycophancy, hallucination, refusal and truthfulness [15, 28]. However, a growing body of work questions the robustness of activation steering [27, 32]. [27] highlights that steering is frequently assessed based on probabilistic outputs which can obscure the true effect of steering on model behaviour, and advocates for more reliable evaluations based on the underlying distribution of token probabilities. [32] analyses the reliability of steering vectors, showing that activation steering is not a universally robust tool for behavioural control.

[19] finds that bias steering vectors are negatively correlated with refusal steering vectors, and that steering towards bias triggers refusal. Our work parallels this by finding that steering in the anti-bias direction triggers a response of low-confidence abstention. [14] uses activation steering to find a causal relationship between model confidence and the likelihood of the model abstention, when given the option to reply with *I don't know*. The authors find that steering towards lower confidence directly impacts the rate at which the model abstains from answering. Our work builds on this connection between confidence and abstention. We find that a vector learned by contrasting biased and anti-biased prompts primarily encodes model confidence, and that steering along this direction increases the probability of model abstention.

Inference-time debiasing: Inference-time debiasing aims to reduce the levels of bias in LLMs [5, 17, 29] and vision-language models [1, 6, 9, 20] at the content-generation stage. Activation steering methods such as FairSteer [17] and the steering-vector approaches of [19, 30] define a debiasing direction by contrasting the activations of biased and unbiased prompts and use the resulting direction to steer the model during inference, reducing the level of bias in the generated tokens. While these methods work well on their target bias benchmarks, they show limited transferability to other datasets [30], and steering interventions can degrade performance on unrelated capabilities [7]. Our work builds an understanding of these behaviours at the level of LLM activations, showing that the learned debiasing direction is in fact a direction that largely encodes model confidence, rather than a linear representation of model bias.

Bias and likelihood: Our work studies the relationship between LLM bias and LLM confidence as measured by model likelihood. Prior work has used the likelihood as a diagnostic for model bias: when a model assigns higher likelihood to one continuation over an equally valid alternative it reveals a preference, and a systematic preference for the biased continuation can be used as a bias metric [22, 23, 26]. [23] measures bias as the model's relative log-likelihood on minimally contrastive stereotyped and anti-stereotyped sentence pairs, and [4] introduces a bias metric based on differences in mean perplexity between statements and their counterfactual variants. These works establish that bias can be detected using the model's likelihood. Our contribution is to connect this phenomenon to the internal geometry

of LLM activation space, showing that the linear direction typically thought to represent model bias in an activation steering context predominantly represents model confidence.

3 Experimental Setup

This section describes the datasets, models and evaluation metrics used throughout the paper with more details being given in Appendix A. Sections 4 and 5 build on this common setup to introduce the linear classifier and steering methodologies respectively.

Datasets. We use three datasets that are constructed to study societal bias in LLMs: BBQ, StereoSet and CrowS-Pairs [22, 23, 26]. Each BBQ question appears under two context conditions: an ambiguous context, which gives insufficient information to determine the correct answer (so the correct response is to abstain), and a disambiguated context, which adds enough information to determine a definite correct answer. Both StereoSet and CrowS-Pairs only consist of ambiguous contexts. We split each of these three datasets into a 70% training set and a 30% test set. We also use two general knowledge datasets, MMLU and OpenBookQA [11, 21], that are designed to probe model performance independently of societal bias. The details of each dataset are given in Appendix A.1, and the specific prompt formatting in Appendix A.2.

Models. We evaluate four open-weight model families, using both the pretrained base model and the instruction-tuned model in each case. We use Llama-3.1-8B [10], Falcon3-7B [2], Ministral-3-8B [18] and Qwen3.5-9B [35]. Across these four families the models range from 7B to 9B parameters. We present results from the Llama-3.1-8B family in the figures of the paper (instruction-tuned in Fig. 1, pre-trained in Figs. 2 and 4, and both variants in Fig. 5). We show results for all models in Tables 1 – 10 and Fig. 3. Greedy decoding is used to generate answers for all QA experiments.

Evaluation metrics. We use four sets of metrics throughout the paper. Area Under the Receiver Operating Characteristic curve (AUROC) assesses how well the linear classifier of Sec. 4 separates biased from anti-biased representations. For the steering experiments of Sec. 5, accuracy (defined only for datasets with a ground-truth answer: BBQ (disambig.), MMLU and OpenBookQA) and answer entropy capture how steering trades off correctness against model confidence.

A bias score, computed differently for BBQ (s_{amb} , s_{dis}) than for StereoSet and CrowS-Pairs, quantifies how often a model favours the biased answer. When using the BBQ dataset, we use the bias score defined in [26]. For disambiguous contexts, this is defined as

$$s_{\text{DIS}} = 2 \left(\frac{n_{\text{biased_ans}}}{n_{\text{biased_ans}} + n_{\text{anti-biased_ans}}} \right) - 1, \quad (1)$$

where $n_{\text{biased_ans}}$ and $n_{\text{anti-biased_ans}}$ are the number of biased and anti-biased answers respectively. For ambiguous contexts, this is defined as

$$s_{\text{AMB}} = (1 - \text{accuracy})s_{\text{DIS}}. \quad (2)$$

Positive values of s_{DIS} or s_{AMB} indicate bias. For StereoSet and CrowS-Pairs, the bias score is defined as the percentage of biased answers given by the model. Because the datasets contain an even split of biased and anti-biased prompts, a bias score of >50% corresponds to a biased model. Full definitions of all four metrics are given in Appendix A.3.

4 A linear classifier for bias

We start by investigating the concept of bias in LLMs and whether it is present as a linear feature in latent space embeddings. This section is structured as follows. Sec. 4.1 confirms that these models exhibit a significant amount of




Fig. 2. Model-assigned probability distributions for each answer option in the test set of BBQ prompts, coloured by answer type: biased (pink), anti-biased (teal), and neutral (grey). Ambiguous and disambiguated contexts are shown in the left and right panels respectively. Vertical dashed lines mark the mean of each distribution. The inset shows the proportion of greedy-decoding responses falling into each answer type.

societal bias, establishing baselines for the remainder of the paper. Sec. 4.2 describes the methodology used to construct a linear classifier that captures bias in the latent space of these models, and investigates the best layer at which this can be done. Sec. 4.3 then shows that the resulting direction captures model confidence rather than semantic bias.

4.1 Background: baseline bias in the tested models

We find that all models introduced in Sec. 3 exhibit measurable societal bias. Full per-model values of bias metrics are reported in Table 4 as baseline values ($\alpha = 0$) before activation steering is performed (Sec. 5). Across all eight models, both BBQ bias scores are positive ($s_{\text{amb}} \in [0.07, 0.18]$, $s_{\text{dis}} \in [0.01, 0.03]$), and CrowS-Pairs/StereoSet stereotype rates exceed the 50% chance baseline in all models, ranging from 69.0–75.8% (CrowS-Pairs) and 62.7–72.3% (StereoSet). These scores are computed using the bias scores defined in Equations (1) and (2) for the BBQ dataset, and the percentage of biased answers given under greedy decoding for StereoSet and CrowS-Pairs.

To further investigate this bias and its connection to model confidence, we examine the probability the model assigns to each answer option. Fig. 2 shows this directly for the BBQ test set in Llama-3.1-8B. Model-assigned answer probabilities are split by context condition (ambiguous, left; disambiguous, right) and coloured by answer type, with vertical lines marking the mean of each distribution. The inset panel then shows the corresponding percentage of greedy-decoded answers given by the model. We find that, in both ambiguous and disambiguated contexts, the mean probability assigned to the biased answer is higher than the mean probability assigned to the anti-biased one. This is then reflected in the number of greedy-decoded answers falling into each answer type with the biased answers being given more than the anti-biased ones. This asymmetry is especially telling in the disambiguated condition: the BBQ dataset balances its templates so that the biased and anti-biased answer are each correct equally often, so an unbiased model should show no net preference between them. In this example, the mean probability of neutral answers is lowest, and this is reflected in the number of neutral answers the model gives.




Fig. 3. AUROC score of a linear classifier trained on ambiguous biased/anti-biased BBQ prompts as a function of layer number for a selection of models. Base models are shown as the solid lines, while the instruction-tuned version of each model is shown in the same colour but in dashed lines. The circular marker indicates the best layer with the highest AUROC value.

4.2 Methodology: constructing a bias classifier

To understand whether bias is linearly encoded in model representations, we train a logistic regression classifier to distinguish biased from anti-biased hidden states. We later show in Sec. 4.3 that this classifier primarily captures confidence rather than bias. To train the classifier we use only the biased and anti-biased answer options as training examples, excluding any neutral/unrelated third option. This is done for two main reasons. Firstly, the neutral option in BBQ, carries a distinct, and trivially learnable signal as it corresponds to the model abstaining from answering rather than making a biased or anti-biased commitment. Secondly, restricting to biased and anti-biased options generalises to all three societal bias datasets; BBQ, StereoSet and CrowS-Pairs.

For each dataset, we train exclusively on ambiguous contexts, i.e. the ambiguous context questions from BBQ, and all examples from StereoSet and CrowS-Pairs. This creates a like-for-like comparison across all three datasets as only BBQ has disambiguated contexts. To construct the prompts, we append the letter corresponding to the biased or anti-biased option and label the prompt correspondingly. We then extract the hidden state at the final token of the full prompt. In this format, this final token is always the answer letter (A, B or C), whose representation is conditioned on the full preceding context (see Figs. 6 - 8). We use the training set discussed in Sec. 3 to train the classifier and the test set to assess its performance.

Linear separability of concepts in transformer representations is known to vary across layers, with intermediate layers often capturing some concepts more distinctly as the model processes inputs prior to committing to a final prediction [12, 17, 31]. Motivated by this, we do not fix a single layer in advance, but instead choose the classification layer for each model empirically. We do this by training a linear classifier on the hidden states at every layer and evaluating the performance using the AUROC on the held-out test set, using this to determine the best layer per model. Fig. 3 shows this AUROC score as a function of layer depth for all models on the BBQ ambiguous dataset.

We observe that, for most models, linear separability of bias peaks at intermediate layers, before declining towards the final layers, with the exception of the Qwen3.5-9B base model which reaches best separability at the final layer. This observation is consistent with similar results found in the fairness literature [17]. Across all models, the instruction-tuned variants achieve a higher AUROC score than their pre-trained counterparts, with the exception of Ministral-3-8B for which both variants reach similar separability at intermediate layers, with the instruction-tuned model performing




Fig. 4. Scatter plots of model-assigned answer probability $P(\text{answer}|\text{prompt})$ against the linear classifier bias score $P(\text{biased})$ indicate a correlation between bias and confidence for the test set of BBQ prompts. The left two panels show ambiguous contexts while the right two panels show disambiguated contexts. The first and third panels (in pink) correspond to the biased prompts while the second and fourth panels (in teal) correspond to the anti-biased prompts. The black line shows a linear fit in each case. The corresponding Spearman rank correlation coefficient between the two quantities is given in Table 1.

only slightly better at the final layers. All models surpass the 50% random-chance baseline, with the highest AUROC value of 0.75 achieved by Llama-3.1-8B-Instruct at layer 15. We use this diagnostic to fix, for each model, the layer with the highest AUROC value, hereafter referred to as the ‘best layer’, and use the classifier at this layer for the rest of this section. The best layer and the corresponding AUROC score for each model is presented in Table 6.

In order to use this trained classifier to assign a bias probability to an unseen prompt, we use the learned weight vector $\mathbf{w}$ and bias term b to compute

$$P(\text{biased}) = \sigma(\mathbf{w} \cdot \mathbf{h} + b). \quad (3)$$

Here $\mathbf{h}$ is the hidden state at the best layer of the final token of the prompt, and σ denotes the sigmoid function. This score serves as a continuous measure of how strongly a given representation is associated with the bias class according to the classifier. We train three separate classifiers, one for each bias dataset (BBQ ambiguous, StereoSet and CrowS-Pairs).

4.3 Results: debiasing direction captures confidence

Fig. 4 plots the model-assigned answer probability $P(\text{answer}|\text{prompt})$ as a function of the linear classifier bias score $P(\text{biased})$, split by context condition (ambiguous, first and second panels; disambiguated, third and fourth) and answer type (biased, first and third panels; anti-biased, second and fourth) for the Llama-3.1-8B model. The linear fit to this data is shown in the solid black line. Spearman rank correlation coefficients r_s corresponding to this fit, together with coefficients for the same linear fit across all models and bias datasets are presented in Table 1.

As shown for Llama-3.1-8B in Fig. 4, a moderate positive correlation is present in the ambiguous condition ($r_s = 0.21$ for biased answers, $r_s = 0.22$ for anti-biased), but the correlation strengthens substantially in the disambiguated condition ($r_s = 0.64$ and $r_s = 0.62$ for biased and anti-biased answer types respectively). This pattern is observed across all models as shown in Table 1.

In ambiguous contexts, the moderate correlation is surprising: there is no reason why the model should assign a higher probability to the answer classified as most biased by the linear classifier. Disambiguated contexts give a better understanding of what the linear classifier is tracking. Here the context makes the correct answer explicit, removing any ambiguity about which answer a model should prefer. If the classifier was tracking semantic bias, its scores should be uncorrelated with answer probability in this condition as the model’s confidence should now be driven by factual context, not by the stereotypical associations the classifier was trained on. Instead, Table 1 shows that the strengthening

Table 1. Correlations are found between the linear classifier bias score $P(\text{biased})$ and the model-assigned answer probability $P(\text{answer}|\text{prompt})$ as measured by Spearman rank correlation coefficients r_s , across models, for BBQ (ambiguous and disambiguated context conditions, as shown in Fig. 4 for the Llama-3.1-8B model) and for StereoSet and CrowS-Pairs (single-context-condition datasets with no ambiguous/disambiguated distinction), evaluated on the held-out test split. Columns correspond to combinations of dataset/context condition and answer type (biased, anti-biased).

Model	BBQ (ambig.)		BBQ (disambig.)		StereoSet		CrowS-Pairs	
	Biased	Anti-biased	Biased	Anti-biased	Biased	Anti-biased	Biased	Anti-biased
Llama-3.1-8B	0.21	0.22	0.64	0.62	0.53	0.52	0.47	0.49
Llama-3.1-8B-Instruct	0.27	0.10	0.77	0.80	0.54	0.64	0.36	0.48
Falcon3-7B-Base	0.10	0.21	0.57	0.59	0.19	0.29	0.28	0.47
Falcon3-7B-Instruct	0.10	0.23	0.73	0.76	0.33	0.38	0.29	0.31
Qwen3.5-9B-Base	0.44	0.45	0.61	0.59	0.41	0.44	0.38	0.46
Qwen3.5-9B	0.22	0.01	0.69	0.71	0.24	0.38	0.30	0.43
Ministral-3-8B-Base	0.15	0.22	0.62	0.64	0.32	0.46	0.41	0.43
Ministral-3-8B-Instruct	0.16	0.15	0.66	0.67	0.41	0.49	0.45	0.52

of the correlation from ambiguous to disambiguated contexts holds across all models with r_s rising from a range of 0.01 – 0.45 in the ambiguous contexts to 0.57 – 0.80 in the disambiguated condition. The effect is strongest for instruction-tuned variants, with consistently higher values of r_s than their pre-trained counterparts. The fact that the correlation is markedly stronger on the disambiguated BBQ dataset for every model tested indicates that the linear classifier is responding to model confidence rather than bias. When the model is more certain about an answer, it assigns it higher probability and a more extreme bias score, irrespective of whether that answer is biased or anti-biased.

StereoSet and CrowS-Pairs, which only have ambiguous contexts, show correlations in the intermediate range ($r_s \in [0.19, 0.64]$ and $r_s \in [0.28, 0.52]$, respectively). This is consistent with the correlation found in the BBQ ambiguous dataset, although slightly stronger.

The interpretation that the debiasing direction is capturing confidence is further supported by the left two panels of Fig. 1 which show the distribution of bias scores for the disambiguated BBQ subset in the Llama-3.1-8B-Instruct model. The left panel shows prompts labelled by type (biased vs. anti-biased). Although some linear separation is achieved, the linear classifier has an AUROC value of 0.57. The central panel instead splits by model preference (higher vs. lower probability answer, comparing only the biased and anti-biased options). The separation now is much more pronounced with an AUROC score of 0.94. The classifier distinguishes the more confident answer from the less confident one, a split that has no relationship to societal bias.

To further test this hypothesis, we evaluate the bias classifier, trained on BBQ (ambig.), StereoSet, or CrowS-Pairs, on three evaluation sets: the disambiguated BBQ subset, and the general-knowledge datasets MMLU and OpenBookQA, labelling answers by model confidence (highest vs. lowest assigned probability). The results are shown in Table 2.

Neither MMLU nor OpenBookQA contains any concept of societal bias. If the direction identified by the linear classifier did correspond to a genuine bias signal, the classifier should perform no better than random chance. Instead we find consistently high AUROC scores: Llama-3.1-8B-Instruct achieves 0.88 on OpenBookQA using a classifier trained on BBQ ambiguous prompts or a classifier trained on CrowS-Pairs. The same experiment performed on the disambiguated BBQ subset yields comparably high separability for BBQ-ambiguous-trained classifiers (AUROC 0.79–0.95 across all eight models), though transfer from StereoSet- and CrowS-Pairs-trained classifiers is less consistent. Overall, these results demonstrate that the bias linear classifier is primarily isolating model confidence, not semantic bias.

Table 2. A linear classifier trained on biased vs. anti-biased prompts achieves a high AUROC when evaluated on the highest vs. lowest probability prompts, even for datasets which do not contain societal bias (MMLU and OpenBookQA). AUROC for highest vs. lowest probability answer embeddings across evaluation datasets (columns), using linear classifiers trained on biased/anti-biased prompts from different training datasets (rows).

Model	Train	BBQ (disambig.)	MMLU	Open BookQA	Model	Train	BBQ (disambig.)	MMLU	Open BookQA
Llama-3.1-8B	BBQ (ambig.)	0.81	0.71	0.79	Qwen3.5-9B-Base	BBQ (ambig.)	0.94	0.80	0.87
	StereoSet	0.33	0.72	0.81		StereoSet	0.62	0.60	0.73
	CrowS-Pairs	0.80	0.88	0.90		CrowS-Pairs	0.70	0.61	0.74
Llama-3.1-8B-Instruct	BBQ (ambig.)	0.94	0.72	0.88	Qwen3.5-9B	BBQ (ambig.)	0.95	0.63	0.72
	StereoSet	0.61	0.78	0.83		StereoSet	0.80	0.63	0.76
	CrowS-Pairs	0.35	0.80	0.88		CrowS-Pairs	0.74	0.81	0.88
Falcon3-7B-Base	BBQ (ambig.)	0.79	0.62	0.67	Ministral-3-8B-Base	BBQ (ambig.)	0.86	0.52	0.62
	StereoSet	0.52	0.56	0.67		StereoSet	0.62	0.73	0.79
	CrowS-Pairs	0.65	0.72	0.69		CrowS-Pairs	0.65	0.89	0.92
Falcon3-7B-Instruct	BBQ (ambig.)	0.93	0.65	0.79	Ministral-3-8B-Instruct	BBQ (ambig.)	0.94	0.54	0.65
	StereoSet	0.82	0.67	0.59		StereoSet	0.51	0.76	0.81
	CrowS-Pairs	0.75	0.57	0.69		CrowS-Pairs	0.69	0.90	0.94

5 Activation steering along the debiasing direction

The results of Sec. 4.3 establish that a linear classifier trained to capture bias in latent space embeddings actually captures confidence. In this section we aim to understand the implications of this bias-confidence confound when this direction is used for debiasing strategies that rely on this direction, by applying activation steering and investigating the resulting change in model behaviour. We find that steering away from the debiasing direction does not correct bias in a targeted way. Instead, it reduces model confidence broadly, causing an increase in abstention where an abstain option is available, and an equilibration of the remaining answer probabilities where it is not, as is illustrated in Fig. 5 for the Llama-3.1-8B model family. The same pattern extends even to general-knowledge datasets that contain no notion of societal bias at all. Sec. 5.1 describes the steering setup, and Sec. 5.2 presents the results.

5.1 Methodology: constructing a debiasing steering vector

For each model, we construct a Contrastive Activation Addition (CAA) [28] direction $\mathbf{v}_b$ by taking the mean difference in hidden states between the biased and anti-biased answer of each question.

$$\mathbf{v}_b = \frac{1}{N} \sum_{i=1}^N (\mathbf{h}_i^{\text{anti-biased}} - \mathbf{h}_i^{\text{biased}}), \quad (4)$$

where $\mathbf{h}_i$ is the hidden state of the final token of the i -th training example, and N is the number of biased/anti-biased pairs in the training set. This direction is independent of the linear classifier of Sec. 4 although it is computed at the same best layer identified via the classifier’s AUROC score.

To test whether the CAA vector aligns with model confidence, we construct a second confidence direction $\mathbf{v}_c$ at the same layer, computed from the MMLU and OpenbookQA datasets that do not share the same data or concept of societal bias. This is done in a similar way to Eq. (4), instead taking the difference of the most preferred to the least preferred answer options (highest and lowest probability, respectively). We compute $\mathbf{v}_c$ separately for MMLU and OpenBookQA, and compare $\mathbf{v}_b$ against $\mathbf{v}_c$ using cosine similarity across all models and training datasets, in Sec. 5.2.

At inference time, we add a scaled, normalised version of the debiasing direction to the hidden state at the best layer, $\mathbf{h}' = \mathbf{h} + \alpha \hat{\mathbf{v}}_b$, where α denotes the scaled magnitude with which steering is applied and $\hat{\mathbf{v}}_b$ is the unit-norm debiasing




Fig. 5. Steering along the debiasing direction does not correct bias in a targeted way: it instead reduces model confidence, causing an increase in abstention where an abstain option is available, and an equilibration of the remaining answer probabilities where it is not. Figure shows the mean probability across prompts split according to answer type; biased (pink), anti-biased (teal), neutral (or abstain; grey) and unrelated (only for StereoSet; olive). The columns show results for the different datasets: BBQ (ambiguous), BBQ (disambiguous), CrowS-Pairs and StereoSet from left to right. The top two rows show the datasets with an option to abstain while the bottom two rows show the same datasets without an option to abstain. Thick borders indicate datasets in their original format. The solid lines in the first and third rows show results for Llama-3.1-8B, while the dashed lines in the second and fourth rows show results for Llama-3.1-8B-Instruct. The star marker shows the natural magnitude of the CAA steering vector.

vector. A negative α , included only for illustrative purposes, indicates steering away from the debiasing direction rather than towards it. The natural (unscaled) magnitude of the direction, $\alpha_{\text{nat}} = \|\mathbf{v}\|$, is marked with a star in each panel of Fig. 5 and is given in Table 7 for all datasets and models.

Table 3. The linear directions in activation space representing model confidence and bias are found to be highly aligned. Cosine similarity between the CAA debiasing direction (Eq. (4), computed from BBQ (ambig.), CrowS-Pairs, or StereoSet at that dataset’s best-AUROC layer) and the confidence direction computed out-of-distribution, from MMLU and OpenBookQA at the same layer. Bold marks the highest value per column.

Model	BBQ		StereoSet		CrowS-Pairs	
	MMLU	OBQA	MMLU	OBQA	MMLU	OBQA
Llama-3.1-8B	0.53	0.56	0.49	0.55	0.38	0.39
Llama-3.1-8B-Instruct	0.78	0.74	0.75	0.74	0.57	0.56
Falcon3-7B-Base	0.58	0.61	0.36	0.51	0.30	0.37
Falcon3-7B-Instruct	0.73	0.76	0.47	0.61	0.29	0.35
Qwen3.5-9B-Base	0.91	0.81	0.68	0.68	0.61	0.74
Qwen3.5-9B	0.82	0.83	0.88	0.89	0.68	0.69
Ministral-3-8B-Base	0.31	0.36	0.73	0.73	0.41	0.44
Ministral-3-8B-Instruct	0.76	0.75	0.80	0.81	0.63	0.63

In Fig. 5, we sweep α from -1 to 2 in increments of 0.5 . When quoting a single steered value elsewhere in the paper (e.g. in Table 4), we use α_{nat} if $\alpha_{\text{nat}} > 1$, and $\alpha = 1$ otherwise, since an unscaled direction smaller than this barely modifies model behaviour (see first two columns in Fig. 5). We label this choice as $\tilde{\alpha}$ for the remainder of this section.

We evaluate each bias dataset in two formats: one with an abstain (neutral) answer option and one without. For BBQ, whose original format includes a neutral option, we obtain the no-abstain format by omitting the neutral option and keeping only the biased and anti-biased answers. For CrowS-Pairs and StereoSet, whose original format does not involve an abstain option and forces the model to give a definite answer, we add a neutral option while keeping the original options unchanged. We do this by using the same phrasing as BBQ’s neutral answers, and insert this option at a random position among the answer choices. For each prompt, we extract the model’s probability on the answer-letter token for every available option and renormalise these so that they sum to one across the options available.

To test whether steering has a similarly non-targeted effect outside the domain of societal bias, we additionally apply each of the three debiasing directions, obtained using BBQ-ambiguous, CrowS-Pairs and StereoSet, to the general-knowledge datasets MMLU and OpenBookQA, at that direction’s own best layer, and measure the resulting change in accuracy and answer entropy relative to $\alpha = 0$. Results are shown in Table 5.

5.2 Results: steering along the debiasing direction increases abstention or entropy

We first compare the debiasing direction $\mathbf{v}_b$ to the confidence direction $\mathbf{v}_c$ before examining the effect of steering along $\mathbf{v}_b$. Table 3 shows cosine similarity values of these two vectors across all models and training datasets. The similarity values found range between 0.29 and 0.91 . Averaged across models and evaluation datasets (MMLU and OpenbookQA), the directions found using the BBQ and StereoSet datasets are the most strongly aligned (mean cosine similarities of 0.68 and 0.67 respectively), while the CrowS-Pairs directions have a mean cosine similarity of 0.50 , indicating a strong alignment in the high-dimensionality activation space.

Having confirmed that the debiasing directions and confidence directions show high levels of alignment as measured by cosine similarity, we now investigate the effects of steering along this debiasing direction. Fig. 5 shows the impact of activation steering on the pretrained and instruction-tuned variants of the Llama-3.1-8B model, as measured by the probability assigned by the model to each answer token conditioned on the prompt, averaged over all the prompts. When the model is allowed to abstain from answering, as shown in the top two rows of Fig. 5, the dominant effect of steering in the debiasing direction is an increase in the probability of the abstain answers. This is seen across all datasets in all models, although the change is always largest in the instruction-tuned model. This is likely a consequence of safety

training which makes the model more likely to abstain even before any steering is applied. As expected, the probability that the model gives a biased answer drops when steering away from bias. More surprisingly, the anti-biased answer probability also drops in most cases when abstaining is allowed, rising only slightly for CrowS-Pairs and StereoSet in the pre-trained model. This indicates that steering reduces model confidence in both substantive answers, concentrating probability mass on the abstain option and causing the model to abstain from answering more frequently. This is a similar effect to that reported in [14], in which steering along a confidence direction is found to directly increase the rates of model abstention, and provides further evidence that the debiasing direction encodes a substantial amount of model confidence. Because this rising abstention concentrates probability mass onto a single option rather than spreading it across several, entropy does not necessarily increase in this regime. This is in contrast with the no-abstain case discussed next, where a rise in entropy is the expected signature of reduced confidence.

This behaviour is in contrast to that shown in the lower two rows of Fig. 5 when the model is not allowed to abstain from answering. In this case, steering equilibrates the average probability assigned to each remaining class. This is driven by the model being pushed to a low-confidence regime in latent space. This equilibration causes entropy to rise, decreasing model confidence and increasing uncertainty. Entropy over a fixed set of answer options is highest when those options are equally likely, so as steering pushes the probability ratios towards unity, entropy increases with it. This is similar to the effect of temperature scaling during decoding, where dividing the output logits by a temperature $T > 1$ before the softmax function flattens the resulting probability distribution over the available options without changing which option the original logits favoured most.

Results from all the other models investigated in this study are qualitatively similar to the representative case shown in Fig. 5. One exception is Qwen3.5-9B-Base for which the layer that achieves the best AUROC score, and so is the most predictive of bias, is its last layer (see Fig. 3). Applying activation steering at this last layer has a negligible impact on the model behaviour as there are no subsequent layers through which the effect of steering can propagate. Results from other models are discussed in Appendix B.2.

Next, we analyse the impact of steering on model accuracy, bias and entropy as shown for all models and datasets in Table 4. The behaviour shown in Figure 5 can easily be misinterpreted as a correct approach to debiasing; for the BBQ ambiguous prompts, the increase in abstention leads to a higher accuracy and lower bias score as can indeed be seen in Table 4. The reduction in the bias score, however, is a direct consequence of how the ambiguous bias score is defined in Equation (2) with a $(1 - \text{accuracy})$ scaling, even though the underlying preference between the biased and anti-biased answers remains largely unchanged. The disambiguous bias score s_{dis} , which does not depend on the abstention rate, stays roughly flat under steering across all models, showing that steering has little to no effect on bias in this context. Table 4 also shows a systematic reduction in accuracy on the disambiguous BBQ dataset across all models, which is a direct consequence of the increased rate of abstention, even though there is enough information for the model to make a substantiated choice. This is a very strong signal indicating that the model is not becoming less biased in its choice between the biased and anti-biased answers; it is becoming less confident overall.

The same caveat applies to CrowS-Pairs and StereoSet. These datasets have no abstain option and so the drop in bias-answer percentage under steering (Table 4) cannot be attributed to increased abstention. Instead, the reduction in bias is accompanied by an increase in entropy, consistent with the equilibration effect described above, rather than a genuine shift in preference towards the anti-biased answer.

Finally, in order to test the impact of steering with the debiasing direction on general model behaviour, we assess the change in accuracy and entropy in the MMLU and OpenBookQA general-knowledge datasets. The results are shown in Table 5. Across all eight models, steering with any of the three directions leaves accuracy either intact or

Table 4. Accuracy / Bias / Entropy, $\alpha = 0$ vs. $\tilde{\alpha}$, native dataset format, where $\tilde{\alpha}$ is the natural CAA magnitude α_{nat} when $\alpha_{\text{nat}} > 1$, and $\alpha = 1$ otherwise. Bias is $s_{\text{amb}}/s_{\text{dis}}$ for BBQ but a bias-answer percentage (0–100) for CrowS-Pairs/StereoSet. Note that the two are not on the same scale. $\uparrow/\downarrow$ on the $\tilde{\alpha}$ column mark a consistent direction of change across (nearly) all eight models; unmarked cells show no consistent trend or are flat.

Model	Dataset	Acc.		Bias		Ent.		Model	Dataset	Acc.		Bias		Ent.	
		0	$\tilde{\alpha}$	0	$\tilde{\alpha}$	0	$\tilde{\alpha}$			0	$\tilde{\alpha}$	0	$\tilde{\alpha}$	0	$\tilde{\alpha}$
Llama-3.1-8B	BBQ (amb.)	0.13	0.25 $\uparrow$	0.12	0.10 $\downarrow$	0.97	1.03	Qwen3.5-9B-Base	BBQ (amb.)	0.56	0.56	0.18	0.18	0.91	0.91
	BBQ (dis.)	0.85	0.82 $\downarrow$	0.03	0.03	0.75	0.91		BBQ (dis.)	0.94	0.94	0.01	0.01	0.37	0.37
	StereoSet	–	–	70.09	62.66 $\downarrow$	0.66	0.77 $\uparrow$		StereoSet	–	–	72.31	72.47	0.57	0.57
	CrowS-Pairs	–	–	75.82	64.71 $\downarrow$	0.52	0.59 $\uparrow$		CrowS-Pairs	–	–	74.51	73.20	0.53	0.53
Llama-3.1-8B-Instruct	BBQ (amb.)	0.76	0.99 $\uparrow$	0.08	0.01 $\downarrow$	0.49	0.29	Qwen3.5-9B	BBQ (amb.)	0.85	0.86 $\uparrow$	0.07	0.06 $\downarrow$	0.53	0.53
	BBQ (dis.)	0.87	0.52 $\downarrow$	0.02	0.04	0.30	0.66		BBQ (dis.)	0.88	0.88	0.01	0.01	0.32	0.36
	StereoSet	–	–	70.25	62.34 $\downarrow$	0.40	0.55 $\uparrow$		StereoSet	–	–	67.09	62.66 $\downarrow$	0.52	0.76 $\uparrow$
	CrowS-Pairs	–	–	69.61	57.84 $\downarrow$	0.31	0.44 $\uparrow$		CrowS-Pairs	–	–	71.57	65.36 $\downarrow$	0.49	0.57 $\uparrow$
Falcon3-7B-Base	BBQ (amb.)	0.39	0.42 $\uparrow$	0.08	0.07 $\downarrow$	0.85	0.86	Ministral-3-8B-Base	BBQ (amb.)	0.44	0.45 $\uparrow$	0.08	0.08	1.02	1.02
	BBQ (dis.)	0.74	0.73 $\downarrow$	0.03	0.03	0.65	0.68		BBQ (dis.)	0.64	0.63 $\downarrow$	0.03	0.03	0.86	0.88
	StereoSet	–	–	67.56	61.87 $\downarrow$	0.61	0.67 $\uparrow$		StereoSet	–	–	69.15	57.12 $\downarrow$	0.69	0.82 $\uparrow$
	CrowS-Pairs	–	–	75.82	58.50 $\downarrow$	0.49	0.56 $\uparrow$		CrowS-Pairs	–	–	68.95	58.17 $\downarrow$	0.57	0.61 $\uparrow$
Falcon3-7B-Instruct	BBQ (amb.)	0.76	0.78 $\uparrow$	0.08	0.07 $\downarrow$	0.26	0.26	Ministral-3-8B-Instruct	BBQ (amb.)	0.82	0.84 $\uparrow$	0.07	0.07	0.34	0.36
	BBQ (dis.)	0.91	0.90 $\downarrow$	0.02	0.02	0.09	0.09		BBQ (dis.)	0.83	0.80 $\downarrow$	0.01	0.01	0.24	0.30
	StereoSet	–	–	70.73	67.72 $\downarrow$	0.18	0.19 $\uparrow$		StereoSet	–	–	62.66	57.91 $\downarrow$	0.34	0.48 $\uparrow$
	CrowS-Pairs	–	–	75.82	70.26 $\downarrow$	0.28	0.33 $\uparrow$		CrowS-Pairs	–	–	70.26	64.71 $\downarrow$	0.31	0.39 $\uparrow$

reduces it, while substantially increasing answer entropy. Steering Qwen3.5-9B with the StereoSet direction at its natural magnitude, for instance, more than doubles OpenBookQA entropy (0.24 to 0.50) and raises MMLU entropy by 80% (0.34 to 0.61). The largest accuracy cost we observe anywhere in Table 5 is in the Llama-3.1-8B-Instruct model, which shows a reduction in accuracy from 0.76 to 0.70 in OpenBookQA under BBQ steering. Overall, accuracy is mostly unaffected because steering pushes the answer probabilities toward a common midpoint without reordering them, leaving the ranking of the candidate answers unchanged. The greedy-decoded answer is usually unaffected as the distribution flattens and entropy rises.

Since neither MMLU nor OpenBookQA contains any specific societal-bias notions, there is no semantic bias for the debiasing direction to correct. Regardless, steering raises answer entropy while slightly lowering task accuracy, mirroring the effect of temperature scaling rather than providing a targeted correction. This highlights the risks associated with debiasing by activation steering. Although Table 4 shows a reduction in overall bias metrics, this is consistently accompanied by an unavoidable increase in model abstention or model entropy depending on the QA dataset format, a result of the debiasing direction encoding model confidence.

6 Discussion and conclusions

Our work uses an interpretability lens to understand how LLMs behave when activation steering is used to debias their outputs. As discussed in Sec. 1, LLMs carry biases inherent to their training data, and inference-time debiasing methods are particularly popular because they are simple to apply and computationally cheaper than alternatives such as fine-tuning. However, this convenience is only valuable if the resulting behaviour can be understood and trusted: without reliability, these methods risk going unused, leaving models biased.

Our analysis finds that the debiasing direction, pointing from biased to anti-biased prompts in LLM activation space, is dominated by model confidence rather than demographic bias. We show that a logistic regression classifier trained to

Table 5. MMLU / OpenBookQA accuracy and entropy: baseline ($\alpha = 0$, direction-independent) vs. $\tilde{\alpha}$ (the natural CAA magnitude α_{nat} when $\alpha_{\text{nat}} > 1$, and $\alpha = 1$ otherwise) for each of the three classifier-trained steering directions. $\downarrow/\uparrow$ on the Acc/Ent headers mark the consistent direction of change from baseline across (nearly) all eight models and all three directions.

Model	Baseline				BBQ (ambig.)				StereoSet				CrowS-Pairs			
	MMLU		OBQA		MMLU		OBQA		MMLU		OBQA		MMLU		OBQA	
	Acc	Ent	Acc	Ent	Acc $\downarrow$	Ent $\uparrow$	Acc $\downarrow$	Ent $\uparrow$	Acc $\downarrow$	Ent $\uparrow$	Acc $\downarrow$	Ent $\uparrow$	Acc $\downarrow$	Ent $\uparrow$	Acc $\downarrow$	Ent $\uparrow$
Llama-3.1-8B	0.64	0.86	0.75	0.78	0.63	0.97	0.74	0.92	0.63	0.95	0.72	0.91	0.62	0.94	0.71	0.91
Llama-3.1-8B-Instruct	0.63	0.55	0.76	0.33	0.59	0.80	0.70	0.57	0.60	0.74	0.72	0.51	0.61	0.73	0.73	0.49
Falcon3-7B-Base	0.67	0.70	0.74	0.69	0.68	0.71	0.74	0.71	0.67	0.75	0.73	0.75	0.65	0.80	0.70	0.79
Falcon3-7B-Instruct	0.69	0.29	0.80	0.19	0.69	0.30	0.80	0.20	0.69	0.31	0.79	0.21	0.68	0.34	0.79	0.23
Qwen3.5-9B-Base	0.78	0.56	0.89	0.53	0.78	0.57	0.88	0.54	0.78	0.56	0.88	0.53	0.78	0.56	0.88	0.53
Qwen3.5-9B	0.79	0.34	0.89	0.24	0.79	0.37	0.89	0.27	0.79	0.61	0.89	0.50	0.79	0.49	0.89	0.39
Ministral-3-8B-Base	0.74	0.73	0.82	0.73	0.74	0.76	0.82	0.76	0.72	0.82	0.79	0.85	0.74	0.79	0.82	0.80
Ministral-3-8B-Instruct	0.72	0.26	0.83	0.19	0.72	0.30	0.83	0.23	0.71	0.37	0.83	0.29	0.71	0.33	0.83	0.26

separate biased and anti-biased prompts achieves an AUROC as high as 0.9 when tested on low versus high-probability prompts from the general knowledge MMLU dataset, despite this dataset encoding no concept of demographic bias. Cosine similarities in the range 0.3-0.9 are found between the debiasing vector and confidence vectors extracted from MMLU and OpenBookQA. The debiasing direction is not just entangled with the confidence direction in activation space: a difference in likelihoods is an inherent feature of biased and anti-biased prompts, arising as a consequence of the over-representation of biased sentences in LLM pretraining data [8].

This has implications for activation steering: steering along the confidence-dominated debiasing direction impacts the model’s confidence in its responses rather than directly reducing model bias. In cases where the model has the option to abstain from responding (e.g. "I don’t know"), the rate of abstention increases with steering while the rates of both biased and anti-biased responses decreases indiscriminately. This builds on the results of [14] which shows that steering in a low-confidence direction directly increases the rate of model abstention in multiple choice QA benchmarks.

When the model has no option to abstain, we observe the rates of anti-biased responses increase and the rates of biased responses decrease. Steering redistributes the model’s probability in each response option, moving from a regime in which most of the probability mass is placed on a single option (the biased response) to a regime where all options have a similar probability. This leads to small reductions in model accuracy, and a large increase in entropy on both bias and general knowledge benchmarks.

Overall, our work demonstrates that when steering does debias QA benchmarks successfully, it does so for the wrong reasons. Steering towards low confidence pushes the model to abstain from answering where possible, and otherwise redistributes model probability among the available multiple choice options regardless of their factual correctness, reducing model accuracy on downstream tasks. A reduction in bias achieved through steering-based debiasing should therefore be interpreted with care and may reflect shifts in model confidence rather than a genuine improvement in model fairness.

Future work will study whether a debiasing direction which is independent of model confidence can be found, and whether this confound impacts inference-time debiasing techniques beyond activation steering. More broadly, it will be important to investigate the prevalence of this effect on other steering vectors based on the linear representation hypothesis, particularly those used in an AI safety context.

Acknowledgments

S. Buttigieg is supported by the Cambridge Centre for Doctoral Training in Data-Intensive Science, funded by the UK Science and Technology Facilities Council (STFC).

Generative AI Usage

The authors used Claude Opus 4.8 to improve fluency, edit grammar and improve table formatting throughout the manuscript. No text generation was performed and the authors take full responsibility for the content of this work.

References

- [1] Dyah Adila, Changho Shin, Linrong Cai, and Frederic Sala. 2024. Zero-Shot Robustification of Zero-Shot Models. In *ICLR*.
- [2] Ebtesam Almazrouei, Hamza Alobeidli, Asma Alshamsi, Alessandro Cappelli, Ruxandra-Aimée Cojocaru, Daniel Hesslow, Julien Launay, Quentin Malartic, Daniele Mazzotta, Badreddine Noune, Baptiste Pannier, and Guilherme Penedo. 2023. The Falcon Series of Open Language Models. *ArXiv abs/2311.16867* (2023). <https://api.semanticscholar.org/CorpusID:265466629>
- [3] Xuechunzi Bai, Angelina Wang, Ilia Sucholutsky, and Thomas L. Griffiths. 2025. Explicitly unbiased large language models still form biased associations. *Proceedings of the National Academy of Sciences* 122, 8 (2025), e2416228122. doi:10.1073/pnas.2416228122
- [4] Soumya Barikeri, Anne Lauscher, Ivan Vulić, and Goran Glavaš. 2021. RedditBias: A Real-World Resource for Bias Evaluation and Debiasing of Conversational Language Models. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (Eds.). Association for Computational Linguistics, Online, 1941–1955. doi:10.18653/v1/2021.acl-long.151
- [5] Xiaoqing Cheng, Ruizhe Chen, Hongying Zan, Yuxiang Jia, and Min Peng. 2025. BiasFilter: An Inference-Time Debiasing Framework for Large Language Models. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (Eds.). Association for Computational Linguistics, Suzhou, China, 15187–15205. doi:10.18653/v1/2025.findings-emnlp.821
- [6] Ching-Yao Chuang, Varun Jampani, Yuanzhen Li, Antonio Torralba, and Stefanie Jegelka. 2023. Debiasing Vision-Language Models via Biased Prompts. *arXiv preprint arXiv:2302.00070* (2023).
- [7] Esin Durmus, Alex Tamkin, Jack Clark, Jerry Wei, Jonathan Marcus, Joshua Batson, Kunal Handa, Liane Lovitt, Meg Tong, Miles McCain, Oliver Rausch, Saffron Huang, Sam Bowman, Stuart Ritchie, Tom Henighan, and Deep Ganguli. 2024. *Evaluating Feature Steering: A Case Study in Mitigating Social Biases*. <https://anthropic.com/research/evaluating-feature-steering>
- [8] Isabel O. Gallegos, Ryan A. Rossi, Joe Barrow, Md Mehrab Tanjim, Sungchul Kim, Franck Dernoncourt, Tong Yu, Ruiyi Zhang, and Nesreen K. Ahmed. 2024. Bias and Fairness in Large Language Models: A Survey. *Computational Linguistics* 50, 3 (Sept. 2024), 1097–1179. doi:10.1162/coli_a_00524
- [9] Walter Gerych, Haoran Zhang, Kimia Hamdih, Eileen Pan, Maanas K Sharma, Tom Hartvigsen, and Marzyeh Ghassemi. 2024. BendVLM: Test-Time Debiasing of Vision-Language Embeddings. In *NeurIPS*.
- [10] Aaron Grattafiori et al. 2024. The Llama 3 Herd of Models. *arXiv preprint arXiv:2407.21783* (2024).
- [11] Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. Measuring Massive Multitask Language Understanding. In *International Conference on Learning Representations*. <https://openreview.net/forum?id=d7KBjmI3GmQ>
- [12] Mingyu Jin, Qinkai Yu, Jingyuan Huang, Qingcheng Zeng, Zhenting Wang, Wenyue Hua, Haiyan Zhao, Kai Mei, Yanda Meng, Kaize Ding, Fan Yang, Mengnan Du, and Yongfeng Zhang. 2025. Exploring Concept Depth: How Large Language Models Acquire Knowledge and Concept at Different Layers?. In *Proceedings of the 31st International Conference on Computational Linguistics*, Owen Rambow, Leo Wanner, Marianna Apidianaki, Hend Al-Khalifa, Barbara Di Eugenio, and Steven Schockaert (Eds.). Association for Computational Linguistics, Abu Dhabi, UAE, 558–573. <https://aclanthology.org/2025.coling-main.37/>
- [13] Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. 2023. Semantic Uncertainty: Linguistic Invariances for Uncertainty Estimation in Natural Language Generation. In *The Eleventh International Conference on Learning Representations*. <https://openreview.net/forum?id=VD-AyTP0dve>
- [14] Dharshan Kumaran, Nathaniel Daw, Simon Osindero, Petar Veličković, and Viorica Patraucean. 2026. Causal evidence that language models use confidence to drive behaviour. *Nature Machine Intelligence* (2026). doi:10.1038/s42256-026-01293-x
- [15] Kenneth Li, Oam Patel, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. 2023. Inference-time intervention: eliciting truthful answers from a language model. In *Proceedings of the 37th International Conference on Neural Information Processing Systems (New Orleans, LA, USA) (NIPS '23)*. Curran Associates Inc., Red Hook, NY, USA, Article 1797, 80 pages.
- [16] Yingji Li, Mengnan Du, Rui Song, Xin Wang, and Y. Wang. 2023. A Survey on Fairness in Large Language Models. *ArXiv abs/2308.10149* (2023). <https://api.semanticscholar.org/CorpusID:261049466>
- [17] Yichen Li, Zhiting Fan, Ruizhe Chen, Xiaotang Gai, Luqi Gong, Yan Zhang, and Zuozhu Liu. 2025. FairSteer: Inference Time Debiasing for LLMs with Dynamic Activation Steering. In *Findings of the Association for Computational Linguistics: ACL 2025*, Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (Eds.). Association for Computational Linguistics, Vienna, Austria, 11293–11312. doi:10.18653/v1/2025.findings-

acl.589

- [18] Alexander Liu et al. 2026. Ministral 3. *ArXiv abs/2601.08584* (2026). <https://api.semanticscholar.org/CorpusID:284704499>
- [19] Dawn Lu and Nina Rimskey. 2024. Investigating Bias Representations in Llama 2 Chat via Activation Steering. *ArXiv abs/2402.00402* (2024). <https://api.semanticscholar.org/CorpusID:267365001>
- [20] Shenyu Lu, Junyi Chai, and Xiaojian Wang. 2024. Mitigating Spurious Correlations in Zero-Shot Multimodal Models. In *ICLR*.
- [21] Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. 2018. Can a Suit of Armor Conduct Electricity? A New Dataset for Open Book Question Answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, Ellen Riloff, David Chiang, Julia Hockenmaier, and Jun'ichi Tsujii (Eds.). Association for Computational Linguistics, Brussels, Belgium, 2381–2391. doi:10.18653/v1/D18-1260
- [22] Moin Nadeem, Anna Bethke, and Siva Reddy. 2021. StereoSet: Measuring stereotypical bias in pretrained language models. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (Eds.). Association for Computational Linguistics, Online, 5356–5371. doi:10.18653/v1/2021.acl-long.416
- [23] Nikita Nangia, Clara Vania, Rasika Bhalerao, and Samuel R. Bowman. 2020. CrowS-Pairs: A Challenge Dataset for Measuring Social Biases in Masked Language Models. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, Bonnie Webber, Trevor Cohn, Yulan He, and Yang Liu (Eds.). Association for Computational Linguistics, Online, 1953–1967. doi:10.18653/v1/2020.emnlp-main.154
- [24] Mahmud Omar, Shelly Soffer, Reem Agbareia, others, and Eyal Klang. 2025. Sociodemographic biases in medical decision making by large language models. *Nature Medicine* 31 (April 2025), 1873–1881. doi:10.1038/s41591-025-03626-6
- [25] Kiho Park, Yo Joong Choe, and Victor Veitch. 2024. The linear representation hypothesis and the geometry of large language models. In *Proceedings of the 41st International Conference on Machine Learning (Vienna, Austria) (ICML '24)*. JMLR.org, Article 1605, 24 pages.
- [26] Alicia Parrish, Angelica Chen, Nikita Nangia, Vishakh Padmakumar, Jason Phang, Jana Thompson, Phu Mon Htut, and Samuel R. Bowman. 2022. BBQ: A hand-built bias benchmark for question answering. In *Findings of the Association for Computational Linguistics: ACL 2022*, Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (Eds.). Association for Computational Linguistics, Dublin, Ireland, 2086–2105. doi:10.18653/v1/2022.findings-acl.165
- [27] Itamar Hagay Pres, Laura Ruis, Ekdeep Singh Lubana, and David Krueger. 2024. Towards Reliable Evaluation of Behavior Steering Interventions in LLMs. *ArXiv abs/2410.17245* (2024). <https://api.semanticscholar.org/CorpusID:273507239>
- [28] Nina Rimskey, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Turner. 2024. Steering Llama 2 via Contrastive Activation Addition. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, Lun-Wei Ku, Andre Martins, and Vivek Srikumar (Eds.). Association for Computational Linguistics, Bangkok, Thailand, 15504–15522. doi:10.18653/v1/2024.acl-long.828
- [29] Timo Schick, Sahana Udupa, and Hinrich Schütze. 2021. Self-Diagnosis and Self-Debiasing: A Proposal for Reducing Corpus-Based Bias in NLP. *Transactions of the Association for Computational Linguistics* 9 (2021), 1408–1424. doi:10.1162/tacl_a_00434
- [30] Zara Siddique, Irtaza Khalid, Liam Turner, and Luis Espinosa-Anke. 2026. Shifting Perspectives: Steering Vectors for Robust Bias Mitigation in LLMs. In *Findings of the Association for Computational Linguistics: EACL 2026*, Vera Demberg, Kentaro Inui, and Lluís Marquez (Eds.). Association for Computational Linguistics, Rabat, Morocco, 809–820. doi:10.18653/v1/2026.findings-eacl.41
- [31] Oscar Skea, Md Rifat Arefin, Dan Zhao, Niket Patel, Jalal Naghiyev, Yann LeCun, and Ravid Shwartz-Ziv. 2025. Layer by layer: uncovering hidden representations in language models. In *Proceedings of the 42nd International Conference on Machine Learning (Vancouver, Canada) (ICML '25)*. JMLR.org, Article 2221, 22 pages.
- [32] Daniel Tan, David Chanin, Aengus Lynch, Brooks Paige, Dimitrios Kanoulas, Adrià Garriga-Alonso, and Robert Kirk. 2024. Analysing the generalisation and reliability of steering vectors. In *Proceedings of the 38th International Conference on Neural Information Processing Systems (Vancouver, BC, Canada) (NIPS '24)*. Curran Associates Inc., Red Hook, NY, USA, Article 4417, 34 pages.
- [33] Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David S. Udell, Juan J. Vazquez, Ulisse Mini, and Monte Stuart MacDiarmid. 2023. Steering Language Models With Activation Engineering. <https://api.semanticscholar.org/CorpusID:261049449>
- [34] UNESCO and IRCAI. 2024. Challenging Systematic Prejudices: An Investigation into Bias Against Women and Girls in Large Language Models. <https://unesdoc.unesco.org/ark:/48223/pf0000388971>
- [35] An Yang et al. 2025. Qwen3 Technical Report. *arXiv e-prints* (2025). arXiv:2505.09388 [cs.CL] doi:10.48550/arXiv.2505.09388
- [36] Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Troy Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, Zico Kolter, and Dan Hendrycks. 2023. Representation Engineering: A Top-Down Approach to AI Transparency. *ArXiv abs/2310.01405* (2023). <https://api.semanticscholar.org/CorpusID:263605618>

A Experimental Setup Details

A.1 Datasets

BBQ. The BBQ dataset is a multiple-choice question set designed to probe societal bias in LLMs across nine demographic characteristics. These are age, disability status, gender identity, nationality, physical appearance, race/ethnicity, religion,

socio-economic status and sexual orientation. It also includes two intersectional biases; gender by race/ethnicity and socio-economic status by race/ethnicity [26]. Each question offers three answer options: a stereotypically biased answer, an anti-biased answer, and a neutral option in which the model declines to answer (e.g. ‘Can’t be determined’ or ‘Unknown’).

Questions appear in one of two context conditions. In disambiguated contexts sufficient information is given for a definitive answer; the biased option is correct for half of these questions, the anti-biased option is correct for the other half, while the neutral option is never correct. In ambiguous contexts, the question can never be answered from the context given. In this case, the neutral option is the only correct answer, and any preference given by the model to the biased answer reflects societal bias acquired during training. Our experiments use a total of 15960 prompts from the BBQ dataset.

StereoSet. StereoSet is a question-answering dataset that is designed to test stereotypical bias [22]. Similarly to BBQ, each question presents three answer options: a stereotypically biased completion, an anti-biased completion, and a semantically unrelated completion. The dataset contains two tasks: intersentence and intrasentence. In the intersentence task, the model is given a context sentence and must select the most appropriate follow-up sentence from the three options. In the intrasentence task, the model is given a sentence with a single missing word and must select the correct completion. We use only the intrasentence subset in this work since this task is more closely aligned with the BBQ format, in which answer options are at most a short phrase rather than a full sentence. As well as this, the single-word structure of the intrasentence answer options provides a cleaner signal for isolating a linear bias direction in activation space. This intrasentence dataset consists of a total of 2106 unique questions.

CrowS-Pairs. The CrowS-Pairs dataset [23] consists of 1508 sentence pairs in which one sentence exhibits a social stereotype, while the other is a minimally different sentence that goes against this stereotype. This dataset was designed to measure the bias present in a pre-trained model by calculating perplexity: a biased model will have a higher perplexity value for the sentence that goes against stereotypes compared to its stereotypical sentence pair.

To ensure minimal variation between paired sentences and avoid confounds such as simultaneous negation changes, we retain only pairs differing by exactly one word, yielding 1,018 examples. To match the format of the other datasets used in this work, we convert CrowS-Pairs to a question-answering format. For each pair, we replace the differing word with a blank and present the biased and anti-biased completions as the two answer options, asking the model “Which word or phrase best completes the sentence?”. We give examples of the prompts and their formatting in Sec. A.2.

As discussed in Sec. 3, each of the three datasets (BBQ, StereoSet and CrowS-Pairs), is split into a 70% training set and a 30% test set. For BBQ, an ambiguous prompt and its corresponding disambiguated prompt are kept within the same split, so that a classifier or steering direction fit on a prompt’s ambiguous form is never evaluated on that same prompt’s disambiguated form. Both splits also preserve a 50-50 balance between disambiguated items for which the biased answer is correct, and those for which the anti-biased answer is correct, so that behavioural metrics computed on either split are not confounded by an accuracy-bias trade-off. The training set is used to train the linear classifier (Sec. 4), and to find the steering direction (Sec. 5), in both cases restricted to ambiguous-context prompts. The test set is then used to assess the performance of the linear classifier, for both in-distribution (ambiguous) and out-of-distribution (disambiguated) examples, and to evaluate the impact of steering on model behaviour.

MMLU. The Massive Multitask Language Understanding (MMLU) benchmark is a multiple-choice evaluation dataset spanning 57 tasks including subjects such as STEM, humanities and social sciences. Each question presents four answer options (A–D) and is designed to probe world knowledge and problem-solving capabilities rather than societal bias. We use a subset of 10,000 prompts drawn from across all categories to investigate how the debiasing direction learned

from the previous three datasets relates to general model behaviour and the impact that activation steering with this debiasing direction has on model performance.

OpenBookQA. We also make use of OpenBookQA [21] as another benchmark dataset that is not related to societal bias. This is a multiple-choice question answering dataset modelled on open-book examinations. It consists of around 6,000 four-choice questions based on a set of 1,329 science facts. Each question requires the LLM to combine one of these core scientific facts with general knowledge, making it a test of reasoning capability instead of just a retrieval test. We use the full dataset as a test set.

In Section 4.3, a linear classifier, trained on the binary task of identifying biased vs anti-biased prompts, is evaluated as a classifier of model confidence on on the BBQ (disambig.), MMLU and OpenBookQA datasets. Since the questions in these datasets offer three to four answer options rather than the two (biased/anti-biased) pairs that the bias linear classifier was trained on, we form this confidence-based test set by keeping, for each question, only the two most extreme answers under the model, the highest and lowest probability options, to mirror the two-way comparison used during training.

A.2 Prompt formatting

Content warning. This appendix includes examples of prompts drawn from the BBQ, CrowS-Pairs, and StereoSet datasets that contain harmful statements about protected demographic groups. These examples are reproduced for scientific purposes. Their inclusion does not reflect the views of the authors and we do not endorse these stereotypes.

Figures 6, 7 and 8 show the prompt format used for each dataset. The same *core prompt* consisting of the context (where applicable), question, and answer options is used for:

- (a) answer generation, used to measure bias score and accuracy before and after steering, and
- (b) extracting the last-token hidden state for each candidate answer, used to train the linear classifier and to compute the CAA direction.

For (b), the model does not complete the prompt itself. Instead, the letter corresponding to each candidate answer is appended to the prompt with a single leading space and the hidden state is read at that final token, using one forward pass per candidate answer. Answer probabilities $P(\text{answer}|\text{prompt})$ are read from the next-token logits of a separate prompt-only forward pass, without any letter appended.

For instruction-tuned models, two changes are applied to every prompt above before the answer token is appended. First, the closing instruction changes from Answer: to Answer with just the letter (A, B, or C), making the expected response format explicit. Second, the core prompt is wrapped in the model’s chat template as a single user turn (apply_chat_template with add_generation_prompt=True) rather than passed as raw text. The content of the prompt, i.e. context, question, and options, is otherwise identical to the base-model format. The same convention of appending the answer token to the prompt with a leading space is used for embedding extraction and next-token scoring as in the base model.

A.3 Evaluation Metric Details

Here we give details of the evaluation metrics used as introduced in Sec. 3.

AUROC. We assess linear classifier performance using the Area Under the Receiver Operating Characteristic Curve (AUROC), which measures the probability that a randomly drawn positive example receives a higher classifier score

BBQ prompt example**Core prompt:**

We couldn't start the board meeting at 9am today because a man and a woman were late. Who was the secretary?

- A. The man
- B. Not enough information
- C. The woman

Answer:

Appended answer token + label:

- C → *biased* ("The woman")
- A → *antibased* ("The man")
- B → *neutral* ("Not enough information")

Fig. 6. Example BBQ prompt (ambiguous context). Options are shuffled per question; A/B/C do not consistently map to a fixed answer type.

StereoSet prompt example**Core prompt:**

The software developer was _____ in high school. Which word or phrase best completes the sentence?

- A. nerdy
- B. popular
- C. glass

Answer:

Appended answer token + label:

- A → *biased* ("nerdy")
- B → *antibased* ("popular")
- C → *neutral* ("glass")

Fig. 7. Example StereoSet prompt (intrasentence). Options are shuffled per question; A/B/C do not consistently map to a fixed answer type. Like CrowS-Pairs, there is a single context condition; unlike CrowS-Pairs, a neutral (unrelated) option is present.

than a randomly drawn negative example. An AUROC of 0.5 indicates no discriminative ability (equivalent to random chance), while a value of 1.0 indicates perfect separation.

BBQ bias score. To assess the amount of bias present in models when using the BBQ dataset, we use the bias score s_{AMB} and s_{DIS} for ambiguous and disambiguous contexts respectively, defined in [26] and shown in Equations (1) and (2).

StereoSet and CrowS-Pairs bias score. We quote bias scores on the StereoSet and CrowS-Pairs datasets as the percentage of biased answers given by the model.




Fig. 8. Example CrowS-Pairs prompt. Options are shuffled per question; A/B do not consistently map to a fixed answer type. CrowS-Pairs has no ambiguous/disambiguated distinction and no neutral option.

Accuracy. Accuracy is the fraction of prompts for which the model assigns its highest probability to the objectively correct answer, and is only defined for datasets with a ground-truth correct answer (BBQ disambiguated, MMLU and OpenBookQA); CrowS-Pairs and StereoSet have no correct answer and are excluded from this metric.

Entropy. Entropy measures how concentrated the model's probability mass is across the available answer options and is often used as a measure of LLM uncertainty [13]. High entropy means the model is unsure among the answer choices, while low entropy means the model is confident about its answer choice. Entropy is defined as

$$H = - \sum_{a \in A} P(a \mid \text{prompt}) \log P(a \mid \text{prompt}), \quad (5)$$

where A is the set of candidate answers.

B Supplementary Results

B.1 Linear classifier

Table 6 extends the per-layer AUROC analysis of Sec. 4 (Fig. 3) to StereoSet and CrowS-Pairs, reporting the best-performing layer and its AUROC for every model on all three bias datasets. Two patterns stand out beyond what Sec. 4.2 already covers for BBQ. First, StereoSet and CrowS-Pairs are consistently easier to linearly separate than BBQ (ambig.): every model's best AUROC is higher on both datasets than on BBQ, typically by 0.15–0.25 (e.g. Ministral-3-8B-Base: 0.73 on BBQ vs. 0.95 on StereoSet), with the exception of Qwen3.5-9B-Base, where the gap is much smaller (0.68 vs. 0.76 on StereoSet, 0.68 vs. 0.82 on CrowS-Pairs). This is due to the fact that CrowS-Pairs and StereoSet datasets contain, on average, shorter prompts than BBQ, in which the longer sentences obscure the bias signal. Second, while the best layer is broadly consistent across datasets within a model, and between the base and instruction-tuned variant of a given model family (differing by at most two or three layers for Llama-3.1-8B, Falcon3-7B, and Ministral-3-8B), Qwen3.5-9B is the clear exception: its base variant reaches peak AUROC only at layer 26–30, ten to thirteen layers later than its own instruction-tuned counterpart (layer 16–17), and with a substantially lower AUROC (0.68/0.76/0.82 vs. 0.74/0.94/0.94). This mirrors the base-model outlier already visible in Fig. 3 for BBQ, and shows the same pattern holds for StereoSet

Table 6. Highest AUROC value and the corresponding layer number for the linear classifier trained to separate biased from anti-biased hidden states, for each model and each of the three bias datasets (BBQ ambiguous, StereoSet and CrowS-Pairs). (Sec. 4); Fig. 3 shows the full per-layer AUROC curve for the BBQ-trained classifiers.

Model	BBQ (ambig.)		StereoSet		CrowS-Pairs	
	Layer	AUROC	Layer	AUROC	Layer	AUROC
Llama-3.1-8B	13	0.70	13	0.92	14	0.94
Llama-3.1-8B-Instruct	14	0.75	14	0.91	14	0.94
Falcon3-7B-Base	17	0.67	15	0.87	16	0.90
Falcon3-7B-Instruct	17	0.70	15	0.90	16	0.92
Qwen3.5-9B-Base	30	0.68	26	0.76	26	0.82
Qwen3.5-9B	17	0.74	16	0.94	16	0.94
Ministral-3-8B-Base	20	0.73	15	0.95	19	0.94
Ministral-3-8B-Instruct	22	0.73	18	0.93	21	0.94

Table 7. Natural alpha (unscaled CAA direction magnitude) per model / dataset.

Model	BBQ (ambig.)	StereoSet	CrowS-Pairs
Llama-3.1-8B	0.10	0.66	1.09
Llama-3.1-8B-Instruct	0.18	0.79	0.90
Falcon3-7B-Base	2.19	11.89	20.27
Falcon3-7B-Instruct	2.87	10.20	12.08
Qwen3.5-9B-Base	3.61	3.14	3.19
Qwen3.5-9B	0.97	4.56	3.49
Ministral-3-8B-Base	0.23	1.32	1.56
Ministral-3-8B-Instruct	0.34	1.25	1.54

and CrowS-Pairs: for every model except Qwen3.5-9B-Base, a linear bias direction emerges at a broadly similar depth and separates the two classes with a comparably high AUROC across all three bias-evaluation datasets.

B.2 Activation steering

CAA produces a steering vector with a natural magnitude which can then be scaled to control the impact extent of steering on model behaviour. Table 7 shows these natural magnitudes before renormalisation for all models and datasets. Metrics showing the impact of steering in Tables 4, 5, 8, 9 and 10 are quoted at this value of α when $\alpha \geq 1$ and at $\alpha = 1$ otherwise.

In Sec. 5.2 we discuss the impact of steering using the debiasing direction on the Llama-3.1-8B models (both pre-trained and instruction tuned). Here we show that the impact of the debiasing-confidence confound can be seen in other models. The trends visualised in Fig. 5 can be seen through the ratio of the average probability of each answer type to that of the anti-biased answers. These are presented for all models in Tables 8, 9 and 10.

The main observed trend is that when abstention is allowed, the ratio of neutral (abstain) to anti-biased answers always increases with increasing α as models tend to abstain more frequently, as shown by Table 8.

At the same time, the ratio of biased to anti-biased probabilities either decreases or remains roughly constant, as shown in Table 9. This ratio remains constant in cases where the model reports low baseline bias scores and, as a result, the biased and anti-biased probabilities are very close to begin with at $\alpha = 0$: this includes all models when evaluated on BBQ (dis.), and all models except for the Llama family when evaluated on BBQ (ambig.) - see Table 4 for baseline bias scores. The reduction of the ratio of biased to anti-biased probabilities shows that the model is steered towards a region of hidden space in which biased and anti-biased responses are treated equally. However, combined with the increase in abstention probability shown in Table 8, this does not signify a debiased model: instead, the model indiscriminately

Table 8. When the model is allowed to abstain, steering increases the probability mass concentrated on the abstain option. Ratio of the mean probability of the neutral (abstain) answer - and, for StereoSet, also the unrelated answer - to that of the anti-biased answer, by dataset and model, in the abstain-option format. $\tilde{\alpha}$ is the natural CAA magnitude α_{nat} when $\alpha_{\text{nat}} > 1$, and $\alpha = 1$ otherwise.

Model	BBQ (amb.)		BBQ (dis.)		StereoSet		StereoSet (unrel.)		CrowS-Pairs	
	0	$\tilde{\alpha}$	0	$\tilde{\alpha}$	0	$\tilde{\alpha}$	0	$\tilde{\alpha}$	0	$\tilde{\alpha}$
Llama-3.1-8B	0.61	0.87	0.30	0.53	1.29	1.40	0.28	0.32	0.86	0.99
Llama-3.1-8B-Instruct	5.51	21.90	0.22	1.82	0.60	2.50	0.19	0.26	0.98	2.24
Falcon3-7B-Base	1.17	1.25	0.39	0.43	0.77	0.92	0.29	0.31	1.02	1.33
Falcon3-7B-Instruct	7.83	8.78	0.18	0.20	1.36	1.78	0.10	0.11	2.49	3.37
Qwen3.5-9B-Base	1.90	1.89	0.21	0.21	1.38	1.37	0.28	0.28	1.35	1.35
Qwen3.5-9B	7.01	7.30	0.28	0.31	1.95	2.68	0.37	0.51	2.57	3.38
Ministral-3-8B-Base-2512	1.18	1.19	0.83	0.86	1.25	1.36	0.43	0.54	1.32	1.19
Ministral-3-8B-Instruct-2512	9.13	9.96	0.42	0.51	2.33	4.57	0.34	0.42	3.08	3.08

Table 9. When the model is allowed to abstain, steering increases the probability mass concentrated on the abstain option and, in most cases, reduces the probability of the biased and anti-biased options. Ratio of the mean probability of the biased answer to that of the anti-biased answer, by dataset and model, in the abstain-option format. $\tilde{\alpha}$ is the natural CAA magnitude α_{nat} when $\alpha_{\text{nat}} > 1$, and $\alpha = 1$ otherwise. The ratio is either left unchanged, as in BBQ (dis.) or is reduced as in BBQ (ambig.), StereoSet and CrowS-Pairs.

Model	BBQ (amb.)		BBQ (dis.)		StereoSet		CrowS-Pairs	
	0	$\tilde{\alpha}$	0	$\tilde{\alpha}$	0	$\tilde{\alpha}$	0	$\tilde{\alpha}$
Llama-3.1-8B	1.13	1.09	1.07	1.05	1.95	1.50	1.73	1.21
Llama-3.1-8B-Instruct	1.58	1.38	1.05	1.07	2.45	2.13	1.94	1.22
Falcon3-7B-Base	1.16	1.15	1.07	1.07	1.82	1.53	1.97	1.32
Falcon3-7B-Instruct	1.85	1.86	1.04	1.04	2.90	2.70	2.94	2.23
Qwen3.5-9B-Base	1.49	1.49	1.04	1.04	2.51	2.51	2.02	2.02
Qwen3.5-9B	1.61	1.60	1.04	1.05	2.97	2.41	2.09	1.71
Ministral-3-8B-Base	1.09	1.08	1.03	1.03	2.28	1.75	1.80	1.47
Ministral-3-8B-Instruct	1.80	1.77	1.03	1.03	2.84	2.78	2.50	2.03

places the probability mass in the abstention option, even when the prompt contains enough context for the model to make a definite answer as in BBQ (dis.).

When there is no abstain option, as shown in Table 10, the ratio of biased to anti-biased mean probability tends towards one, as both answer types become equally likely under steering, a consequence of the model becoming less uncertain about its answer choice. This increase in uncertainty is not just present in the model’s response to bias benchmark prompts: as shown in Table 5, uncertainty and entropy in general knowledge QA benchmarks are also increased under steering.

Table 10. When the model is not allowed to abstain, steering equilibrates the biased and anti-biased probabilities, reducing their ratio towards a value of 1. Ratio of the mean probability of the biased answer - and, for StereoSet, also the unrelated answer - to that of the anti-biased answer, by dataset and model, in the no-abstain format. $\tilde{\alpha}$ is the natural CAA magnitude α_{nat} when $\alpha_{\text{nat}} > 1$, and $\alpha = 1$ otherwise.

Model	BBQ (amb.)		BBQ (dis.)		StereoSet		StereoSet (unrel.)		CrowS-Pairs	
	0	$\tilde{\alpha}$	0	$\tilde{\alpha}$	0	$\tilde{\alpha}$	0	$\tilde{\alpha}$	0	$\tilde{\alpha}$
Llama-3.1-8B	1.14	1.09	1.08	1.05	1.81	1.45	0.29	0.34	1.91	1.43
Llama-3.1-8B-Instruct	1.35	1.22	1.05	1.06	2.30	1.80	0.19	0.31	2.04	1.27
Falcon3-7B-Base	1.17	1.16	1.07	1.07	1.85	1.57	0.25	0.28	2.05	1.31
Falcon3-7B-Instruct	1.49	1.48	1.03	1.03	2.53	2.29	0.12	0.14	2.73	2.11
Qwen3.5-9B-Base	1.40	1.40	1.04	1.04	2.36	2.36	0.31	0.31	1.85	1.86
Qwen3.5-9B	1.37	1.35	1.03	1.03	2.47	1.92	0.48	0.71	1.86	1.47
Ministral-3-8B-Base-2512	1.08	1.07	1.02	1.02	2.24	1.70	0.58	0.73	1.53	1.27
Ministral-3-8B-Instruct-2512	1.40	1.37	1.03	1.02	2.31	2.04	0.46	0.57	2.10	1.72