

Ornstein–Uhlenbeck Is Hard to Beat, Yet Superlinear Drift Ships Lower Transport Costs

Attila Lovas Lóránt Nagy

HUN-REN Alfréd Rényi Institute of Mathematics
Budapest, Hungary

Abstract

Brešar and Mijatović [1] show that Ornstein–Uhlenbeck diffusion is hard to beat in forward convergence under assumptions that exclude superlinear drift. We instead test superlinear Langevin diffusions for score-based image generation, computing their conditional scores numerically from a Fokker–Planck equation. In our experiments, the superlinear models beat the Ornstein–Uhlenbeck baseline on empirical Wasserstein distance across nearly the entire tested grid and show less variation across diffusion horizons. The “hard to beat” verdict of [1] thus fails to be universal.

1 Introduction

Let $\mu_\star$ be a data distribution on $\mathbb{R}^d$. Diffusion-based generative modelling introduces a forward stochastic process that progressively destroys the structure of $\mu_\star$, and then constructs a reverse process that transports a simple terminal law back toward the data distribution. This principle appears in the diffusion model of Sohl-Dickstein et al. [10], the denoising diffusion model of Ho et al. [7], and the continuous-time score-based formulation of Song et al. [11]. The reverse-time diffusion formula itself is classical [2, 6], and score matching provide the learning principle.

Common continuous-time constructions use affine Gaussian corruptions whose conditional transition laws and conditional scores are available analytically. The present experiment replaces the linear mean-reverting drift by a coordinatewise superlinear Langevin drift. The transition score is then computed numerically from the associated Fokker–Planck equation and used as the regression target for the score network.

The construction does not require an analytical expression for either the corrupted-data marginal p_t or the conditional transition density $p_{t|0}$. When the forward diffusion has a sufficiently regular transition density, its conditional score can instead be approximated by solving the associated Fokker–Planck equation. This permits forward processes beyond those with closed-form Gaussian transitions. In the present experiment we restrict attention to coordinatewise Langevin diffusions, for which the conditional score can be computed from a one-dimensional equation and reused across coordinates.

2 Forward diffusion

Fix $\alpha \geq 1$ and $c_\alpha > 0$. Define the scalar potential

$$U_\alpha(y) = \frac{c_\alpha}{\alpha + 1} |y|^{\alpha+1},$$

and the potential on $\mathbb{R}^d$ by

$$\mathcal{U}_\alpha(x) = \sum_{i=1}^d U_\alpha(x^i).$$

The forward process is the gradient Langevin diffusion

$$dX_t = B_\alpha(X_t) dt + dW_t, \quad X_0 \sim \mu_\star, \quad t \in [0, T]. \quad (1)$$

where

$$B_\alpha(x) = -\nabla \mathcal{U}_\alpha(x).$$

Coordinatewise we use the notation,

$$B_\alpha(x) = (b_\alpha(x^1), \dots, b_\alpha(x^d)),$$

where by definition

$$b_\alpha(y) = -U'_\alpha(y) = -c_\alpha |y|^\alpha \operatorname{sgn}(y).$$

Define

$$Z_\alpha = \int_{\mathbb{R}^d} \exp[-2\mathcal{U}_\alpha(x)] dx, \quad V_\alpha(x) = 2\mathcal{U}_\alpha(x) + \log Z_\alpha.$$

The invariant probability measure of (1) is

$$\Pi_\alpha(dx) = e^{-V_\alpha(x)} dx = Z_\alpha^{-1} \exp[-2\mathcal{U}_\alpha(x)] dx. \quad (2)$$

The coordinates evolve independently conditional on the initial image. For $y_0 \in \mathbb{R}$, let $q^{y_0}(t, y)$ denote the transition density of the scalar diffusion

$$dY_t = b_\alpha(Y_t) dt + dB_t, \quad Y_0 = y_0.$$

Then the conditional transition density of (1) factorizes as

$$p_{t|0}(x \mid x_0) = \prod_{i=1}^d q^{x_0^i}(t, x^i). \quad (3)$$

3 Time reversal for the superlinear family

We now justify the reverse-time dynamics of the continuous-time process (1) using the findings in [4]. Assume that

$$H(\mu_\star \mid \Pi_\alpha) < \infty. \quad (4)$$

Let Y follow the same Langevin dynamics as X , with an invariant initial law:

$$dY_t = B_\alpha(Y_t) dt + dW_t, \quad Y_0 \sim \Pi_\alpha.$$

Denote the path laws of X and Y by P and R , respectively. In the notation of [4], the diffusion matrix in the present setup is

$$a = I_d.$$

Since $V_\alpha(x) = 2\mathcal{U}_\alpha(x) + \log Z_\alpha$, we have $\nabla V_\alpha(x) = 2\nabla \mathcal{U}_\alpha(x)$, and therefore $B_\alpha(x) = -\frac{1}{2}a\nabla V_\alpha(x)$. Thus R is the reversible diffusion associated with the invariant measure

$$\Pi_\alpha(dx) = e^{-V_\alpha(x)} dx.$$

Moreover, $V_\alpha \in C^1(\mathbb{R}^d)$, $a = I_d$ is constant, and the growth condition of [4] is satisfied. Indeed,

$$\begin{aligned} x \cdot B_\alpha(x) + \text{tr}(a) &= -c_\alpha \sum_{i=1}^d x^i |x^i|^\alpha \text{sgn}(x^i) + d \\ &= -c_\alpha \sum_{i=1}^d |x^i|^{\alpha+1} + d \\ &\leq d. \end{aligned}$$

The processes X and Y have the same conditional path law given their initial point and differ only in their initial distributions. Consequently,

$$H(P \mid R) = H(\mu_\star \mid \Pi_\alpha) < \infty.$$

Thus the reference diffusion satisfies the required nondegeneracy, reversibility, and growth conditions moreover, P is Markov and, under assumption (4), has finite relative entropy with respect to R . The time-reversal theorem of [4] therefore applies, and hence the stationary process Y is reversible.

Remark. *The finite-entropy assumption (4) can be enforced by an arbitrarily small Gaussian regularization of the data distribution. Indeed, if $\mu_\star$ is supported on a bounded subset of $\mathbb{R}^d$, as is the case for normalized image data, then for any $\varepsilon > 0$ the regularized law*

$$\mu_\star^\varepsilon = \mu_\star * \mathcal{N}(0, \varepsilon^2 I_d)$$

has a smooth strictly positive density and satisfies

$$H(\mu_\star^\varepsilon \mid \Pi_\alpha) < \infty.$$

Thus the assumption (4) may be ensured by adding an arbitrarily small amount of independent Gaussian noise to the data.

4 Reverse diffusion and the score

Let p_t denote the density of X_t , and define reverse time by

$$\tau = T - t, \quad \bar{X}_\tau = X_{T-\tau}.$$

Under the finite-entropy assumption (4), the argument in the preceding section gives

$$d\bar{X}_\tau = [-B_\alpha(\bar{X}_\tau) + \nabla \log p_{T-\tau}(\bar{X}_\tau)] d\tau + d\bar{W}_\tau, \quad \bar{X}_0 \sim \text{Law}(X_T). \quad (5)$$

As usual, the unknown quantity in this equation is the marginal score

$$\nabla \log p_t(x).$$

Although the conditional forward dynamics decouple coordinatewise, the marginal law at time t generally does not, because the initial distribution $\mu_\star$ contains dependencies between image coordinates. Indeed,

$$p_t(x) = \int_{\mathbb{R}^d} p_{t|0}(x \mid x_0) \mu_\star(dx_0).$$

The marginal score at x depends on the posterior distribution of the original image X_0 given $X_t = x$. A neural network $s_\theta(x, t)$ is therefore trained to approximate the full d -dimensional marginal score. The regression target is the conditional score. The denoising score-matching objective is

$$\mathcal{L}(\theta) = \mathbb{E} \left[\left\| s_\theta(X_t, t) - \nabla_x \log p_{t|0}(X_t | X_0) \right\|_2^2 \right]. \quad (6)$$

Under the usual regularity assumptions,

$$\mathbb{E} [\nabla_x \log p_{t|0}(X_t | X_0) | X_t = x] = \nabla_x \log p_t(x), \quad (7)$$

so the population minimizer of (6) is the marginal score required in (5) [12, 11].

5 Score construction and numerical implementation

The time-reversal formula specifies the reverse drift, but its marginal score $\nabla \log p_t$ is not available in closed form. To train the network, we instead construct the conditional score in (6). For fixed y_0 , the scalar transition density $q^{y_0}(t, y)$ defined in Section 2 satisfies the Fokker–Planck equation

$$\partial_t q = -\partial_y (b_\alpha(y)q) + \frac{1}{2} \partial_y^2 q, \quad q(0, \cdot) = \delta_{y_0}. \quad (8)$$

Consequently, the conditional score has components

$$s(y_0, t, y) = \partial_y \log q^{y_0}(t, y), \quad [\nabla_x \log p_{t|0}(x | x_0)]^i = s(x_0^i, t, x^i). \quad (9)$$

For the nonlinear choices of α , we approximate q^{y_0} numerically rather than use a closed-form transition density [9, 3].

We solve (8) on a finite grid for a range of starting values y_0 . A narrow Gaussian approximates the initial point mass. We then take finite differences of the log-density and store the resulting conditional scores in a table indexed by (y_0, t, y) . During training, scores are obtained from this table by trilinear interpolation.

For the experiments, the data consist of 28×28 grayscale images normalized to $[-1, 1]^d$, where $d = 784$. We set $c_\alpha = 0.5$, $c_0 = 0$, and test $\alpha \in \{1, 2, 3\}$, $T \in \{3, \dots, 10\}$, and $N \in \{100, 150, 200\}$. The score table uses 200 starting-value points in $[-1.5, 1.5]$, 700 time points in $[0, T]$, and 200 state points in $[-5.5, 5.5]$. The initial Gaussian has standard deviation 0.03, and densities are floored at 10^{-12} before taking logarithms. For $\alpha = 1$, the forward process is $dX_t = -\frac{1}{2}X_t dt + dW_t$ and its invariant law is $\mathcal{N}(0, I_d)$.

Training samples of the forward process are generated by Euler–Maruyama with step size $h = T/N$:

$$\hat{X}_{k+1} = \hat{X}_k + hB_\alpha(\hat{X}_k) + \sqrt{h}\xi_k, \quad \xi_k \sim \mathcal{N}(0, I_d). \quad (10)$$

For each image, one nonzero time is selected uniformly from its N -step trajectory. A U-Net is trained to predict the tabulated conditional score at that time. It has 64 base channels, channel multipliers (1, 2), two residual blocks per level, dropout 0.1, and a time embedding of dimension 128. We use AdamW for 15 epochs with batch size 64, learning rate 10^{-5} , and zero weight decay.

Reverse sampling also uses Euler–Maruyama with N steps. Its starting law is approximated by the invariant law Π_α ; samples from that law are approximated by evolving standard normal samples under the forward Langevin equation to time $T_{\text{eq}} = 30$. This equilibration uses N steps of size $30/N$. For superlinear drifts, explicit Euler can produce rare, very large excursions [8]; numerical explosions are monitored, and generated images with more than ten percent non-finite coordinates are discarded at evaluation time.

The code used for the numerical experiments is available at <https://github.com/lorant-nagy/genai>.

6 Evaluation and results

We evaluate generated images using the empirical Wasserstein–1 distance with Euclidean ground cost. Real and generated 28×28 images are mapped to $[0, 1]^d$ and flattened, a fixed set of 3000 real images is used. The distance is computed by solving the discrete optimal-transport problem [5].

Across the tested grid, a superlinear choice ($\alpha = 2$ or $\alpha = 3$) gives a lower value than the linear baseline in 23 of the 24 fixed (T, N) comparisons; the exception is $N = 100, T = 8$. The best value in each table is also attained by a superlinear model, and the row summaries show less variation across T . We conjecture that stronger mean reversion contributes to both the improved Wasserstein–1 scores and their reduced sensitivity to the choice of T .

Our findings qualify the “hard to beat” characterization of the Ornstein–Uhlenbeck process in [1]: the results therein concern forward convergence to stationarity under at-most-linear drift, while our superlinear models achieve lower empirical generation error in the experiments reported here.

α	T							
	3	4	5	6	7	8	9	10
3	7.4895	7.1817	7.2128	7.3525	7.5041	7.6127	7.6784	7.7590
2	8.0436	7.1735	7.1995	7.2805	7.4185	7.5190	7.7112	7.6554
1	10.7980	8.1018	9.5526	7.4124	7.4386	7.4421	7.7372	7.7217

Table 1: $\mathcal{W}_1$ for $N = 100$. Lower is better; darker shading indicates a smaller value.

α	T							
	3	4	5	6	7	8	9	10
3	7.6303	7.2553	7.2215	7.4292	7.4934	7.4947	7.5667	7.9462
2	8.3078	7.2908	7.4071	7.4038	7.4565	7.5470	7.5285	8.1154
1	11.1001	11.1918	9.2831	7.5673	10.7467	7.9927	8.3327	9.8957

Table 2: $\mathcal{W}_1$ for $N = 150$. Lower is better; darker shading indicates a smaller value.

α	T							
	3	4	5	6	7	8	9	10
3	8.3180	7.2164	7.3147	7.3457	7.3593	7.5742	7.8070	7.6255
2	9.4270	7.4931	7.5542	7.5268	7.3764	7.5384	8.1468	8.1259
1	11.1501	8.5657	9.3656	11.5609	10.7299	10.1254	9.6737	8.2259

Table 3: $\mathcal{W}_1$ for $N = 200$. Lower is better; darker shading indicates a smaller value.

N	$\alpha = 1$	$\alpha = 2$	$\alpha = 3$
100	7.92 ± 0.76	7.42 ± 0.22	7.47 ± 0.23
150	9.29 ± 1.39	7.54 ± 0.27	7.49 ± 0.24
200	9.75 ± 1.17	7.68 ± 0.32	7.46 ± 0.21

Table 4: Mean and sample standard deviation over $T \in \{4, \dots, 10\}$.

References

- [1] M. Brešar and A. Mijatović. Nonasymptotic bounds for forward processes in denoising diffusions: Ornstein–Uhlenbeck is hard to beat. *Annals of Applied Probability*, 35(6):4439–4463, 2025.
- [2] B. D. O. Anderson. Reverse-time diffusion equation models. *Stochastic Processes and their Applications*, 12(3):313–326, 1982.
- [3] V. I. Bogachev, N. V. Krylov, M. Röckner, and S. V. Shaposhnikov. *Fokker–Planck–Kolmogorov Equations*. American Mathematical Society, 2015.
- [4] P. Cattiaux, G. Conforti, I. Gentil, and C. Léonard. Time reversal of diffusion processes under a finite entropy condition. *Annales de l’Institut Henri Poincaré, Probabilités et Statistiques*, 59(4):1844–1881, 2023.
- [5] R. Flamary, N. Courty, A. Gramfort, et al. POT: Python Optimal Transport. *Journal of Machine Learning Research*, 22(78):1–8, 2021.
- [6] U. G. Haussmann and E. Pardoux. Time reversal of diffusions. *The Annals of Probability*, 14(4):1188–1205, 1986.
- [7] J. Ho, A. Jain, and P. Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.
- [8] M. Hutzenthaler, A. Jentzen, and P. E. Kloeden. Strong and weak divergence in finite time of Euler’s method for stochastic differential equations with non-globally Lipschitz continuous coefficients. *Proceedings of the Royal Society A*, 467(2130):1563–1576, 2011.
- [9] H. Risken. *The Fokker–Planck Equation: Methods of Solution and Applications*. 2nd edition, Springer, 1989.
- [10] J. Sohl-Dickstein, E. Weiss, N. Maheswaranathan, and S. Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. *Proceedings of the 32nd International Conference on Machine Learning*, 2256–2265, 2015.
- [11] Y. Song, J. Sohl-Dickstein, D. P. Kingma, A. Kumar, S. Ermon, and B. Poole. Score-based generative modeling through stochastic differential equations. *International Conference on Learning Representations*, 2021.
- [12] P. Vincent. A connection between score matching and denoising autoencoders. *Neural Computation*, 23(7):1661–1674, 2011.