arXiv:2610.39821v1 [cs.LG] 29 Oct 2026

Possibility-based Inference: A Deterministic Framework for Robust and Reliable Uncertainty Quantification in Decision-Making

S. Musavishavazi[1 [0000−0001−6494−6258]] ✉ and M. Alipour[1 [0000−0001−9966−973X]]

Federal Institute for Occupational Safety and Health
Fabricestraße 8, 01099 Dresden, Germany

Abstract. Decision-making under uncertainty remains a key issue in Machine Learning (ML), particularly in the deployment of safety-critical systems, where reliable quantification of system behavior is essential for evaluating behavioral impacts and strengthening confidence in ML models. This contribution, influenced by fuzzy set theory and grounded in Bayesian statistics, addresses challenges related to data precision and the performance–accuracy trade-off in Bayesian inference (BI). To this end, we introduce a possibility-based contrastive grade of prediction as an alternative quantification method to existing latent posterior-based approaches for parameter estimation (approximation) and model selection. Unlike conventional Bayesian inference, which represents uncertainty within the probabilistic framework, the proposed model adopts a possibility-based representation that allows uncertain and potentially conflicting information to be characterized more flexibly. Rather than focusing on isolated aspects of a problem, the resulting mathematical framework provides a systematic approach to data mining while mitigating overly confident, yet implausible predictions generated by highly specialized deep learning architectures.

Keywords: Possibility-Inference· Baysian ML · UQ · Contrastive-Learning. · Parameter Estimation

1 Introduction

In the context of ML, uncertainty refers to the lack of confidence in the results produced by a model. Looking at the notion of generalization beyond the data seen during the learning step, it is important to recognize that any decision made by an ML model is not provably certain but rather hypothetical [16]. Consequently, accounting for uncertainty is essential in ML models to ensure **robust** inference [42,44], facilitating the transition from real-world data to reliable predicted results. Several factors can influence the decisions made by a model and create uncertainty, such as insufficient or biased data, noise in the data [75], model architecture, and lack of **interpretability** [1,48], to name a few. Taking these factors into account and mitigating them improves uncertainty and increases the **trustworthiness** of model decisions [30].

In statistical terms, uncertainty is encapsulated through standard probabilities and probabilistic predictions. The model's ability to generalize beyond the data it has learned from is a fundamental requirement, achieved through the process of induction, where the model infers patterns and rules based on observed data and applies them to unseen data. To this end, it is assumed that the training and test data are identically and independently distributed (i.i.d.). However, this assumption often does not hold in practice, leading to a deterioration in model predictions due to domain distribution gaps. In addition, collecting all possible data to train the model is expensive and practically impossible. As a consequence, the predictions made by such a model are inherently uncertain [67]. For this reason, the uncertainty in mathematical models stems from the **stochastic** perspective of the model's output, in contrast to a **deterministic** output [50].

There are two main sources of uncertainty: data and lack of knowledge. Data uncertainty, also known as aleatoric uncertainty, is linked to the stochastic nature of the data generation process, making it impossible to eliminate completely [13]. In contrast, knowledge uncertainty, or epistemic uncertainty, arises from information gaps and can potentially be reduced by employing state-of-the-art models or gathering additional data [21]. Epistemic uncertainty encompasses both model uncertainty and approximation uncertainty: model uncertainty pertains to the construction of the model, while approximation uncertainty relates to parameter estimation [30].

Model uncertainty is commonly addressed through the use of over-parameterized neural networks [41,55,62,69,72], particularly within the framework of Bayesian Neural Networks (BNNs) [2,9,32,52,54,56]. BNNs represent model parameters as random variables governed by a posterior probability distribution, thereby enabling principled uncertainty quantification. However, exact posterior inference is generally intractable, which motivates the use of Variational Inference (VI) [34,64], a deterministic approximation approach to Bayesian inference. VI seeks to approximate the true posterior with a tractable distribution by minimizing a divergence measure, most commonly the Kullback–Leibler (KL) divergence [39], between the two distributions. Through this optimization, VI identifies the optimal member of a predefined variational family that best approximates the posterior distribution induced by the observed data.

By providing improved accuracy while analytically reducing computational complexity relative to the original model, this mathematical and statistical framework enables more reliable decision-making and is particularly well suited for data assimilation (DA) [5,20,28,29,51,58], which integrates real-world observations into dynamic models to estimate the true state of complex systems and to generate task-specific neural networks with real-valued outputs.

However, the development of task-specific models for practical deployment, together with the scalability challenges posed by model architectures, has brought computational demands on the one hand and uncertainty in data precision on the other to

the forefront, highlighting the need to balance trade-offs between performance and accuracy [12,63]. Consequently, this motivates the use of a possibilistic approach, rather than a probabilistic one, as a suitable alternative framework for information analysis [70].

To motivate this approach, exploring the concept of possibility, and especially its interconnection with other reasoning frameworks, provides a basis for establishing a robust conceptual platform [43,71]. This platform is particularly advantageous for addressing challenges where imprecision arises from the lack of precisely defined criteria for class membership [47], as opposed to situations involving well-defined random variables [4]. The versatility of possibility theory consequently extends its applicability across a broad spectrum of tasks, ranging from pattern recognition and data science to various other domains [33,61].

Possibility theory, introduced by Zadeh within the framework of fuzzy set theory [71], allows inference in variational inference (VI) to be reformulated using possibility-based mechanisms [6]. Like probability theory, it establishes a formal ordering of preferences, enabling belief representation, prioritization of plausible hypotheses, resolution of inconsistencies, and identification of salient relationships [25]. To unify probability and possibility, the possibility–probability consistency principle [70] provides a basis for calculating and updating possibility distributions, characterizing the coherence or absence of contradiction between information derived from both frameworks [11].

Building on this foundation, [26] introduces a theoretical framework for constructing a joint possibility distribution, paving the way for defining a multivariate possibility distribution in terms of the dimensions of the space where uncertainty is investigated.

To the best of our knowledge, the concept of possibility, described as an imprecise probability distribution [65] and representing a more common occurrence in reality, has received limited attention in this domain. While there have been some possibility-based contributions [6,7,15,27,59] that address the problem by evaluating the plausible values of parameters, our method takes a different approach by using a simultaneous **"one vs. rest" evaluating technique** and building a **contrastive learning** function [23] to achieve the most flexible distribution.

The proposed framework extends variational inference (VI) by incorporating the concept of possibility. To this end, the **posterior** function in the original VI is replaced by another function, namely the **likelihood ratio** function [49]. The advantages of this approach are explained below.

– Firstly, the likelihood ratio, explicitly revised, considers both the positive and negative facets of decision-making, fostering greater confidence in the process and serving as a **leading indicator**. Its significance becomes apparent in a framework grounded in possibility, where the distinction between higher possibility

and greater likelihood becomes crucial, as higher possibility does not necessarily imply a greater likelihood of occurrence.
- Secondly, deploying the likelihood ratio results in a contrastive learning function as an optimization objective, providing a **quantitative metric**. Compared to the original VI model, this function not only quantifies uncertainty with greater precision but also selects a function that more closely aligns with the true distribution within a narrower interval, thereby contributing to more reliable and robust model outcomes.
- Lastly, when deploying the Principle of Insufficient Reason [3], also known as the Principle of Indifference [35], our approach allows the use of the likelihood distribution in the likelihood ratio function instead of the posterior, wherever deemed necessary. It is noteworthy that, unlike the posterior, the choice of the likelihood distribution is within our control, and it extends the **applicability** of the model, specifically in the face of imbalanced data.

The framework clearly holds all the properties of a Robust Design Method (RDM) [17]. These aspects, however, will be examined and discussed in greater detail in sections (2.1.2), (2.1.3), and (2.1.4).

This paper is structured as follows: We begin with a comprehensive model description that explores the relevant background essential to our study. Next, we examine the integration of the likelihood ratio within the framework of BI, emphasizing its role in enhancing analytical rigor. Subsequently, we present a novel possibility-based framework aimed at further refining our methodology. Finally, we conclude by summarizing the proposed framework and outlining potential directions for future research.

2 Model Description

2.1 Probability-based Inference

2.1.1 Background: Inference Challenges and Navigating Towards Variational Optimization

Consider a fully Bayesian model where each parameter is assigned a **prior** distribution, and the model incorporates both parameters and latent variables. The collection of all latent variables and parameters is represented as $\mathrm{Z} = \{\boldsymbol{z}_1, \ldots, \boldsymbol{z}_M\}$. Concurrently, the set of i.i.d observed varaibles(data) is denoted as $\mathrm{X} = \{\boldsymbol{x}_1, \ldots, \boldsymbol{x}_n\}$.

Note: Throughout this contribution, all vectors are represented in bold font, i.e., $\vec{x} := \boldsymbol{x}$.

When establishing the joint distribution $p(\boldsymbol{x}, \boldsymbol{z})$, which includes both observed and latent variables, the distribution of the observed variables is derived through a process called marginalization.

$$p(\boldsymbol{x}) = \sum_{\boldsymbol{z} \in \mathrm{Z}} p(\boldsymbol{x}, \boldsymbol{z}) \tag{1}$$

This technique allows intricate marginal distributions over observed variables to be expressed in terms of more tractable joint distributions across the extended space of both observed and latent variables. It is important to note that $p(\boldsymbol{x})$ is referred to as **evidence**, since a higher marginal value suggests a better model fit. Given our representation of $p(\boldsymbol{x})$, it logically follows that for each observation $\boldsymbol{x}_i = (x_{i1}, \ldots, x_{ir}) \in \mathrm{X}$, there exists a corresponding latent variable $\boldsymbol{z}_i = (z_{i1}, \ldots, z_{is}) \in \mathrm{Z}$. In the following, we will consistently rely on these assumptions.

Considering that the primary objective of any probabilistic model is to assess the **posterior** distribution $p(\boldsymbol{z}_n \mid \boldsymbol{x}_n)$, VI stands as no exception to this fundamental task. Based on Bayes' theorem the posterior is given by;

$$p(\boldsymbol{z}_n \mid \boldsymbol{x}_n) = \frac{p(\boldsymbol{x}_n \mid \boldsymbol{z}_n) \cdot p(\boldsymbol{z}_n)}{p(\boldsymbol{x}_n)} \tag{2}$$

with $p(\boldsymbol{x}_n \mid \boldsymbol{z}_n)$ representing the **likelihood** distribution and $p(\boldsymbol{z}_n)$ denoting the **prior**. The objective is to maximize the likelihood distribution. In the equation (2), the computation of $p(\boldsymbol{x}_n)$ is either infeasible or demands exponential time to achieve a closed form. This highlights the challenge in inference approximation for such models. It is important to note that probabilistic inference, including approximate inference, is a computationally challenging task, classified as NP−hard [31].

To tackle the challenge of the inference problem, VI suggests utilizing a designated family of densities denoted as $\mathcal{Q}$ for the latent variables. The aim is to select the most suitable candidate from this family, representing the best estimate for the true posterior distribution. It's noteworthy that any $q(\mathrm{Z}) \in \mathcal{Q}$ is considered a candidate approximation for the conditional probability $p(\mathrm{Z} \mid \mathrm{X})$. The search for the optimal match, representing the closest approximation to the conditional probability, involves using the KL divergence [10]. Consequently, the challenge of approximating inference is reframed as an optimization problem, where the complexity of the family $\mathcal{Q}$ determines the difficulty of the task.

$$q^*(\mathrm{Z}) = \arg\min_{q \in \mathcal{Q}} \mathrm{KL}(q(\mathrm{Z}) \,||\, p(\mathrm{Z} \mid \mathrm{X})) \tag{3}$$

In equation (3), $\mathrm{KL}(\bullet \,||\, \bullet)$ denotes the KL divergence as follows.

$$\mathrm{KL}(q(\mathrm{Z}) \,||\, p(\mathrm{Z} \mid \mathrm{X})) = -\sum_{i=1}^{N} q(\boldsymbol{z}_i) \cdot \log \frac{p(\boldsymbol{z}_i \mid \boldsymbol{x}_i))}{q(\boldsymbol{z}_i)} \tag{4}$$

Upon closer examination of (4), it becomes apparent that;

$$\mathrm{KL}(q(\mathrm{Z}) \,||\, p(\mathrm{Z} \mid \mathrm{X})) = \mathrm{E}(\log(q(\mathrm{Z})) - \mathrm{E}(\log(p(\mathrm{Z} \mid \mathrm{X}))) \tag{5}$$

with all expectations computed with respect to $q(\mathrm{Z})$. The objective function represented by equation (5) is not computable due to its dependence on $p(\mathrm{X})$, as elucidated in the subsequent equation.

$$\mathrm{KL}(q(\mathrm{Z}) \,||\, p(\mathrm{Z} \mid \mathrm{X})) = \mathrm{E}(\log(q(\mathrm{Z}))) - \mathrm{E}(\log(p(\mathrm{Z},\mathrm{X}))) + \log(p(\mathrm{X}) \tag{6}$$

Given the computational challenges and time-intensive nature associated with equation (6), the optimization process focuses on its equivalent but more manageable alternative as the objective function.

$$\mathrm{ELBO}(q(\mathrm{Z})) = \mathrm{E}(\log(p(\mathrm{Z},\mathrm{X}))) - \mathrm{E}(\log(q(\mathrm{Z}))) \tag{7}$$

The present equation (7) is referred to as the Evidence Lower Bound (ELBO). Closer examination reveals that equation (7) can also be written as the following.

$$\mathrm{ELBO}(q(\mathrm{Z})) = \log(p(\mathrm{X})) - \mathrm{KL}(q(\mathrm{Z}) \,||\, p(\mathrm{Z} \mid \mathrm{X})) \tag{8}$$

As seen in equation (8), $\log(p(\mathrm{X}))$ is independent of $q(\mathrm{Z})$ and therefore remains constant. As a result, maximizing the ELBO leads to minimizing the (4).

In the work by [36], they introduce an estimator for the ELBO known as Stochastic Gradient Variational Bayes (SGVB). This method facilitates more efficient approximate inference and learning in probabilistic models. Notably, SGVB offers the advantage of improved lower bound estimation, which can be optimized using any standard stochastic gradient method.

Given this background, we aim to further enhance the concept of VI by incorporating the notion of possibility. Initially, we confine our discussion to probability-based considerations. After establishing a framework within this context, we gradually relax these conditions and transition towards exploring the concept of possibility.

2.1.2 Exploring Likelihood Ratio as an Alternative to Posterior in BI

In section 2.1.1, the concepts of the posterior distribution (2) and the evidence $p(\boldsymbol{x})$ were discussed. The posterior distribution plays a crucial role in acquiring model parameters based on observed data, facilitating model selection. On the other hand, the evidence proves invaluable within the domain of model comparison, providing a means to evaluate the efficacy of each model in explaining the observed data. Consequently, this prompts a reformulation of the inference problem as an optimization task by leveraging KL Divergence.

Building on the principles of Robust Soft Learning Vector Quantization (RSLVQ) [57], a probabilistic variant of Learning Vector Quantization (LVQ) [37], we introduce the following revised **likelihood ratio** function, denoted by **LR**:

$$\mathrm{LR}(\boldsymbol{x}_n, \boldsymbol{z}_n) = \frac{p(\boldsymbol{z}_n \mid \boldsymbol{x}_n)}{p(\overline{\boldsymbol{z}}_n \mid \boldsymbol{x}_n)} \tag{9}$$

where $p(\boldsymbol{z}_n \mid \boldsymbol{x}_n)$ represents a measure of certainty regarding the latent variable given the observed data. To clarify, when the conditional probability assigns a bigger probability mass to a specific value of the latent variable, it indicates higher confidence or belief in that particular choice given the observed data.

In contrast, $p(\overline{\boldsymbol{z}}_n \mid \boldsymbol{x}_n) = \sum_{i \neq n} p(\boldsymbol{z}_i \mid \boldsymbol{x}_n)$, as the cumulative probability associated with latent variable choices excluding $\boldsymbol{z}_n$, establishes a measure of uncertainty due to its inverse relationship with the likelihood ratio as defined in (9). It's important to emphasize that the likelihood ratio (9) is a monotonically increasing function, reaching its maximum at $p(\boldsymbol{z}^* \mid \boldsymbol{x}) = \max_i \{p(\boldsymbol{z}_i \mid \boldsymbol{x})\}$.

A comparison between the posterior (2) and the likelihood ratio (9) reveals that **our choice of decision function leads to the immediate omission of the evidence** (1), **resulting in hassle-free calculations which is the main advantage.** For clarification, the calculation of $p(\overline{\boldsymbol{z}}_n \mid \boldsymbol{x}_n) = \sum_{i \neq n} p(\boldsymbol{z}_i \mid \boldsymbol{x}_n)$ is limited by the number of latent variables. It is important to note that the subscript of any latent variable refers to its relationship with the corresponding observed data, rather than to the variable's index.

Following the introduction of the likelihood ratio and its crucial advantage, it is time to explore its role in the objective function and the benefit of integrating it into the existing method.

2.1.3 Contrastive Learning as a Model Objective Function

As in the original VI, we aim to identify the most suitable surrogate probability function $q(\bullet)$ to substitute for $p(\bullet \mid \bullet)$. However, $\mathrm{LR}(\bullet, \bullet)$ (9)fails to meet the criteria of a probability function. This limitation prevents us from using divergence directly to quantify the disparity between $q(\bullet)$ and $p(\bullet \mid \bullet)$. Therefore, we must define the subsequent **local loss function**, which is denoted as **loss**, to make further progress.

$$\mathrm{loss}(\boldsymbol{x}_n, \boldsymbol{z}_n) = -q(\boldsymbol{z}_n) \cdot \log\Big(\mathrm{LR}(\boldsymbol{x}_n, \boldsymbol{z}_n)\Big) \tag{10}$$

To advance, we substitute the expanded version of the likelihood ratio (9) into (10).

$$\begin{aligned}
\mathrm{loss}(\boldsymbol{x}_n, \boldsymbol{z}_n) &= -\, q(\boldsymbol{z}_n) \cdot \log\Big(\frac{p(\boldsymbol{z}_n \mid \boldsymbol{x}_n)}{p(\overline{\boldsymbol{z}}_n \mid \boldsymbol{x}_n)}\Big) \\
&= -\, q(\boldsymbol{z}_n) \cdot \log\Big(\frac{p(\boldsymbol{z}_n \mid \boldsymbol{x}_n)}{p(\overline{\boldsymbol{z}}_n \mid \boldsymbol{x}_n)} \cdot \frac{q(\boldsymbol{z}_n)}{q(\boldsymbol{z}_n)}\Big) \\
&= -\, q(\boldsymbol{z}_n) \cdot \log\Big(\frac{p(\boldsymbol{z}_n \mid \boldsymbol{x}_n)}{q(\boldsymbol{z}_n)}\Big) + q(\boldsymbol{z}_n) \cdot \log\Big(\frac{p(\overline{\boldsymbol{z}}_n \mid \boldsymbol{x}_n)}{q(\boldsymbol{z}_n)}\Big)
\end{aligned}$$

By summing up both sides of the aforementioned equation across all potential values of n, we obtain the resulting **global loss function**, referred to as **Loss**.

$$\text{Loss}(\text{X},\text{Z}) = \text{KL}(q(\text{Z}) \mid\mid p(\text{Z} \mid \text{X})) - \text{KL}(q(\text{Z}) \mid\mid p(\overline{\text{Z}} \mid \text{X})) \tag{11}$$

In the preceding equation (11), the first and second terms on the right-hand side are interpreted as positive- and negative-reasoning, respectively. As a result, (11) is a contrastive learning function, substantiating the rationale behind the initial selection of (10). Consequently, we can formulate our objective function as follows.

$$q^*(\text{Z}) = \arg\min_{q \in \mathcal{Q}} \text{Loss}(\text{X},\text{Z}) \tag{12}$$

Unlike the objective function (3) in the original VI, which considers only positive reasoning, $\text{KL}(q(\text{Z}) \mid\mid p(\text{Z} \mid \text{X}))$, **the present objective function (12) not only avoids additional computational complexities, due to the absence of the evidence, but also yields more accurate outcomes by taking into account both positive and negative reasoning.**

In addition to the above advantages, which result in more accurate outcomes and better performance, we should bear in mind that the model is constructed through a transparent process, equipping it with a more tractable representation. As an inference model, it also provides insight into the relationships it has learned. In other words, representation, inference, and learning collectively contribute to **model-based** interpretability, as highlighted in [38] and [45].

The next section will discuss the final advantage of this approach, presenting it as the silver lining.

2.1.4 The Final Edge in Practical Application

We begin this section with the Principle of Indifference (PI) [35]. This principle states that, in the absence of any known reason to prefer one option over its alternatives, all options should be considered equally likely based on the available knowledge. Consequently, in such a special case, applying this principle leads us to assign an equal prior probability to each class of data, i.e., $\frac{1}{n}$, where n is the number of classes.

Understanding the PI and investigating (11) more closely reveals an additional advantage of deploying such an objective function. To elaborate:

$$
\begin{aligned}
&\mathrm{KL}(q(\mathrm{Z}) \,||\, p(\mathrm{Z} \mid \mathrm{X})) - \mathrm{KL}(q(\mathrm{Z}) \,||\, p(\overline{\mathrm{Z}} \mid \mathrm{X})) = \\
&\sum_n -q(\boldsymbol{z}_n) \cdot \log \frac{p(\boldsymbol{z}_n \mid \boldsymbol{x}_n)}{p(\overline{\boldsymbol{z}}_n \mid \boldsymbol{x}_n)} = \\
&\sum_n -q(\boldsymbol{z}_n) \cdot \Big(\log(p(\boldsymbol{z}_n \mid \boldsymbol{x}_n) - \log(p(\overline{\boldsymbol{z}}_n \mid \boldsymbol{x}_n) \Big) = \\
&\sum_n -q(\boldsymbol{z}_n) \cdot \Big(\log(p(\boldsymbol{x}_n, \boldsymbol{z}_n) - \log p(\boldsymbol{x}_n) - \log(p(\boldsymbol{x}_n, \overline{\boldsymbol{z}}_n) + \log p(\boldsymbol{x}_n) \Big) = \\
&\sum_n -q(\boldsymbol{z}_n) \cdot \log \frac{p(\boldsymbol{x}_n, \boldsymbol{z}_n)}{p(\boldsymbol{x}_n, \overline{\boldsymbol{z}}_n)} \\
&\sum_n -q(\boldsymbol{z}_n) \cdot \log \Big(\frac{p(\boldsymbol{x}_n, \boldsymbol{z}_n)}{p(\boldsymbol{x}_n, \overline{\boldsymbol{z}}_n)} \cdot \frac{\frac{1}{n}}{\frac{1}{n}} \Big) = \\
&\sum_n -q(\boldsymbol{z}_n) \cdot \log \frac{p(\boldsymbol{x}_n \mid \boldsymbol{z}_n)}{p(\boldsymbol{x}_n \mid \overline{\boldsymbol{z}}_n)}
\end{aligned}
$$

in other words, the **posterior** density in the initial objective function (9) can be replaced with the **likelihood** density, leading to the reformulation of the subsequent Loss.

$$\mathrm{Loss}(\mathrm{X}, \mathrm{Z}) = \sum_n -q(\boldsymbol{z}_n) \cdot \log \frac{p(\boldsymbol{x}_n \mid \boldsymbol{z}_n)}{p(\boldsymbol{x}_n \mid \overline{\boldsymbol{z}}_n)} \tag{13}$$

Although the PI is dismissed by some as a standard of ideal rationality [18], the current loss function (13) possesses its own independent and unique merits, particularly in addressing the challenges of learning from imbalanced data. To elaborate, standard methods not only introduce bias in favor of the majority class but also struggle to distinguish between minority and noisy data [14].

Along with deploying effective techniques such as resampling [60] and generating synthetic samples [24], [40], [66] to address real-world challenges, the utilization of (13) complements efforts to advance ML methods, highlighting its crucial role in the practical application of imbalanced learning.

The discussion so far has focused on the choice of the likelihood ratio and the corresponding contrastive-learning objective function within the probability-based framework, highlighting its clear advantages over the original VI. Nevertheless, while probability has long been central to decision-making, some contend that much of the information underpinning these decisions is inherently possibilistic [70]. As a result, exploring a possibility-based framework becomes crucial to broadening the applicability of our method across diverse scenarios and achieving greater accuracy and reliability in outcomes.

The subsequent section is entirely dedicated to relaxing some constraints of probability and shifting towards a possibility-based framework.

2.2 Possibility Theory: A Complementary Approach to Probability-based Inference

In statistical inference, population parameters are estimated from sample statistics, as observing the entire population is usually impractical. However, within this inductive framework, the exact values of the parameters cannot be determined with complete certainty due to the inherent limitations of sample-based inference.

BI addresses this issue by providing an order of preference among plausible parameter values, based on both prior information and the likelihood of the observed data. These preferences are represented using probability functions, which allow us to quantify uncertainty.

As has already been argued, probability measures may not always be the best tool for inductive reasoning [53]. In such cases, the possibility measure, an alternative framework that relaxes some of the limitations of probability and has proven to be a viable alternative in statistical inference [6], can be deployed.

2.2.1 Comparing Disparity Based on Generalized Divergences

In the context of probability theory, we encounter a concept known as a σ-algebra (or σ-field) [4], which essentially encompasses the set of all conceivable outcomes X associated with any given event. The fundamental significance of σ-algebra lies in their pivotal role in establishing a measure for each plausible outcome, denoted as $\boldsymbol{x}_i \in \mathrm{X}$, through a density function $p(\boldsymbol{x}_i)$. Importantly, $\sum_i p(\boldsymbol{x}_i) = 1$. However, in practical situations involving incomplete information, the collection of conceivable outcomes does not satisfy the criteria for a σ-algebra. To clarify, unlike probabilities, the degree of membership [71], which represents a possibility distribution within the interval $[0,1]$, is not subject to the same normalization constraint [19]. In other words, $\sum_i p(\boldsymbol{x}_i) \neq 1$.

With particular emphasis on the following assumptions,

- $\forall i;\ p(\boldsymbol{x}_n, \boldsymbol{z}_i) \geq 0$ represents a non-negative possibility measure.
- $\sum_n p(\boldsymbol{x}_n) \neq 1$.

we leverage the equation, $\mathrm{Loss(X,Z)} = \sum_n -q(\boldsymbol{z}_n) \cdot \log \frac{p(\boldsymbol{x}_n, \boldsymbol{z}_n)}{p(\boldsymbol{x}_n, \bar{\boldsymbol{z}}_n)}$. , (2.1.4), as the foundation of the possibility-based scheme. It is important to note that $q(\bullet)$ is also a possibility distribution. Consequently, the KL divergence in equation (11) is unable to effectively measure the dissimilarity between the non-normalized $q(\bullet)$ and $p(\bullet,\bullet)$. Therefore, we deploy extended α-divergence [74], a parameterized form of the Csiszár-Morimoto and Bregman divergences, as detailed below.

$$\mathrm{D}^{\alpha}(q \,||\, p) = -\frac{1}{\alpha \cdot (\alpha - 1)} \cdot \sum_n q_n^{\alpha} \cdot p_n^{1-\alpha} - \alpha \cdot q_n + (\alpha - 1) \cdot p_n \ ;\ \alpha \in \mathbb{R} - \{0,1\} \tag{14}$$

It is important to note that the aforementioned divergence enhances both the flexibility and efficiency of algorithms such as expectation-maximization, thereby improving their robustness [8]. Furthermore, a closer investigation shows as $\alpha \rightarrow 1$, the α-divergence converges to the **generalized** KL divergence [73], $\mathrm{KL}_g(\bullet \,||\, \bullet)$.

$$\lim_{\alpha \rightarrow 1} \mathrm{D}^{\alpha}(q \,||\, p) = -\sum_{n} q_n \cdot \log(\frac{p_n}{q_n}) - q_n + p_n = \mathrm{KL}_g(q \,||\, p) \tag{15}$$

When (15) is restricted to normalized positive measures, we obtain the **standard** KL divergence.

$$\lim_{\alpha \rightarrow 1} \mathrm{D}^{\alpha}(q \,||\, p) = -\sum_{n} q_n \cdot \log(\frac{p_n}{q_n}) = \mathrm{KL}(q \,||\, p) \tag{16}$$

By deploying the α-divergence, the Loss (11) can be expressed as follows.

$$\mathrm{Loss}_g(\mathrm{X}, \mathrm{Z}) = \mathrm{D}^{\alpha}(q(\mathrm{Z}) \,||\, p(\mathrm{Z} \,|\, \mathrm{X})) - \mathrm{D}^{\alpha}(q(\mathrm{Z}) \,||\, p(\overline{\mathrm{Z}} \,|\, \mathrm{X})) \tag{17}$$

Finally the substitution of the **generalized Loss**, denoted by ($\mathbf{Loss_g}$) (17) into the objective function (12) yields a revised objective function, thereby establishing a robust possibility-based inference framework.

3 Discussion

Undoubtedly, significant empirical work is needed to deepen our understanding of this mathematical model. Although the application of the likelihood ratio in the context of BI is novel, its deployment in other studies [46,68] demonstrates the feasibility of the approach and suggests that concerns about the computational aspects and efficiency of the inference process in this model may be unwarranted. Furthermore, these studies provide evidence of the broad applicability of the likelihood ratio.

4 Conclusion

In this paper, we introduce a comprehensive mathematical model for a novel inductive inference framework. Recognizing the crucial role of VI and the computational challenges inherent in Bayesian ML models, we propose a methodical approach that integrates a possibility-based decision function into VI. This results in a robust and reliable platform that enhances decision-making by providing more interpretable support.

On one hand, restricting the model to probability-based measures makes it suitable for predictive inference; on the other hand, incorporating possibility measures facilitates estimation inference [22]. As a consequence, this framework, centered around a contrastive learning function, not only models uncertainty but also enables informed decision-making across various domains, including computer vision, natural language processing, and reinforcement learning.

Specifically, the flexibility of the contrastive learning function, which utilizes likelihood density instead of the standard posterior, contributes to deeper insights into the nature of imbalanced learning at both the data and algorithmic levels.

Although the application of the likelihood ratio in the context of BI is novel, its application in other studies [46,68] provides evidence of its practical feasibility in related settings. However, significant empirical work remains necessary to deepen our understanding of the proposed mathematical model, particularly with respect to the computational aspects and efficiency of the inference process.

In conclusion, this framework opens up new avenues for future research, including empirical investigations of its computational performance, robustness, and applicability across diverse domains and datasets.

Acknowledgments.

This work was conducted at the Federal Institute for Occupational Safety and Health (BAuA Dresden) as part of the junior research group "Artificial Intelligence (AI) in a Safe and Healthy Working Environment", with support from the German Federal Ministry of Labour and Social Affairs. The authors gratefully acknowledge the institute's permission to make this work publicly available.

References

1. Abdar, M., Pourpanah, F., Hussain, S., Rezazadegan, D., Liu, L., Ghavamzadeh, M., Fieguth, P., Cao, X., Khosravi, A., Acharya, U.R., et al.: A review of uncertainty quantification in deep learning: Techniques, applications and challenges. Information fusion **76**, 243–297 (2021)
2. Afkham, B., Chung, J., Chung, M.: Uncertainty quantification for goal-oriented inverse problems via variational encoder-decoder networks. Inverse Problems (2024)
3. Bernoulli, J.: Wahrrscheinlichkeitsrechnung, third and fourth parts. Ostwald, Klassiker der exakten Wissenschaften **108** (1896)
4. Borel, É.: Leçons sur la théorie des fonctions:(éléments et principes de la théorie des ensembles; applications à théorie des fonctions), vol. 1. Gauthier-Villars (1914)
5. Carrassi, A., Bocquet, M., Bertino, L., Evensen, G.: Data assimilation in the geosciences: An overview of methods, issues, and perspectives. Wiley Interdisciplinary Reviews: Climate Change **9**(5), e535 (2018)
6. Chen, Y.Y.: Statistical inference based on the possibility and belief measures. Transactions of the American Mathematical Society **347**(5), 1855–1863 (1995)
7. Chérief-Abdellatif, B.E., Alquier, P.: Mmd-bayes: Robust bayesian estimation via maximum mean discrepancy. In: Symposium on Advances in Approximate Bayesian Inference. pp. 1–21. PMLR (2020)
8. Cichocki, A., Amari, S.i.: Families of alpha-beta-and gamma-divergences: Flexible and robust measures of similarities. Entropy **12**(6), 1532–1568 (2010)
9. Congdon, P.D.: Applied Bayesian hierarchical methods. CRC Press (2010)
10. Csiszár, I.: I-divergence geometry of probability distributions and minimization problems. The annals of probability pp. 146–158 (1975)

11. Delgado, M., Moral, S.: On the concept of possibility-probability consistency. Fuzzy sets and systems **21**(3), 311–318 (1987)
12. Demirkiran, C., Nair, L., Bunandar, D., Joshi, A.: A blueprint for precise and fault-tolerant analog neural networks. Nature Communications **15** (06 2024). https://doi.org/10.1038/s41467-024-49324-8
13. Der Kiureghian, A., Ditlevsen, O.: Aleatory or epistemic? does it matter? Structural safety **31**(2), 105–112 (2009)
14. Douzas, G., Bacao, F.: Effective data generation for imbalanced learning using conditional generative adversarial networks. Expert Systems with applications **91**, 464–471 (2018)
15. Du, L., Choi, K.K., Youn, B.D.: Inverse possibility analysis method for possibility-based design optimization. AIAA journal **44**(11), 2682–2690 (2006)
16. Edwards, W., Lindman, H., Savage, L.J.: Bayesian statistical inference for psychological research. Psychological review **70**(3), 193 (1963)
17. Eifler, T., Christensen, M.E., Howard, T.J.: A classification of the industrial relevance of robust design methods. In: 19th International Conference on Engineering Design. pp. 427–436. Design Society (2013)
18. Eva, B.: Principles of indifference. The Journal of Philosophy **116**(7), 390–411 (2019)
19. Gaines, B.R., Kohout, L.J.: The logic of automata (1976)
20. Gaoming, L., Reynolds, A.C.: An iterative ensemble kalman filter for data assimilation. In: SPE Annual Technical Conference and Exhibition? pp. SPE–109808. SPE (2007)
21. Gustafsson, F.K., Danelljan, M., Schon, T.B.: Evaluating scalable bayesian deep learning methods for robust computer vision. In: Proceedings of the IEEE/CVF conference on computer vision and pattern recognition workshops. pp. 318–319 (2020)
22. Hacking, I.: Logic of statistical inference. Cambridge University Press (2016)
23. Hadsell, R., Chopra, S., LeCun, Y.: Dimensionality reduction by learning an invariant mapping. In: 2006 IEEE computer society conference on computer vision and pattern recognition (CVPR'06). vol. 2, pp. 1735–1742. IEEE (2006)
24. He, H., Bai, Y., Garcia, E.A., Li, S.: Adasyn: Adaptive synthetic sampling approach for imbalanced learning. In: 2008 IEEE international joint conference on neural networks (IEEE world congress on computational intelligence). pp. 1322–1328. Ieee (2008)
25. Van der Helm, R.: Towards a clarification of probability, possibility and plausibility: how semantics could help futures practice to improve. Foresight **8**(3), 17–27 (2006)
26. Hose, D., Mäck, M., Hanss, M.: On probability-possibility consistency in high-dimensional propagation problems. In: Third International Conference on Uncertainty Quantification in Computational Sciences and Engineering (UNCECOMP) (2019)
27. Houssineau, J., Nott, D.J.: Robust bayesian inference in complex models with possibility theory (2022)
28. Houtekamer, P.L., Mitchell, H.L.: Data assimilation using an ensemble kalman filter technique. Monthly weather review **126**(3), 796–811 (1998)
29. Houtekamer, P.L., Mitchell, H.L.: A sequential ensemble kalman filter for atmospheric data assimilation. Monthly weather review **129**(1), 123–137 (2001)
30. Huang, X., Jin, G., Ruan, W.: Machine learning safety. Springer (2023)
31. Jaakkola, T.S.: Tutorial on variational approximation methods. Advanced mean field methods: theory and practice pp. 129–159 (2000)
32. Jeon, Y., Chang, W., Jeong, S., Han, S., Park, J.: A bayesian convolutional neural network-based generalized linear model. Biometrics **80**(2) (2024)
33. Jia, W., Lu, M., Shen, Q., Tian, C., Zheng, X.: Dual generative adversarial networks based on regression and neighbor characteristics. Plos one **19**(1), e0291656 (2024)
34. Jordan, M.I., Ghahramani, Z., Jaakkola, T.S., Saul, L.K.: An introduction to variational methods for graphical models. Machine learning **37**, 183–233 (1999)

35. Keynes, J.M.: The principle of indifference. A treatise on probability **4**, 41–64 (1921)
36. Kingma, D.P., Welling, M.: Auto-encoding variational bayes. arXiv preprint arXiv:1312.6114 (2013)
37. Kohonen, T., Kohonen, T.: Learning vector quantization. Self-organizing maps pp. 175–189 (1995)
38. Koller, D.: Probabilistic Graphical Models: Principles and Techniques. The MIT Press (2009)
39. Kullback, S., Leibler, R.A.: On information and sufficiency. The annals of mathematical statistics **22**(1), 79–86 (1951)
40. Li, D.C., Hu, S.C., Lin, L.S., Yeh, C.W.: Detecting representative data and generating synthetic samples to improve learning accuracy with imbalanced data sets. PloS one **12**(8), e0181853 (2017)
41. Li, Y., Liang, Y.: Learning overparameterized neural networks via stochastic gradient descent on structured data. Advances in neural information processing systems **31** (2018)
42. Ma, X., Wang, J.: Robust inference using inverse probability weighting. Journal of the American Statistical Association **115**(532), 1851–1860 (2020)
43. McDermott, D., Doyle, J.: Non-monotonic logic i. Artificial Intelligence **13**(1), 41–72 (1980), special Issue on Non-Monotonic Logic
44. Miller, J.W., Dunson, D.B.: Robust bayesian inference via coarsening. Journal of the American Statistical Association (2019)
45. Murdoch, W.J., Singh, C., Kumbier, K., Abbasi-Asl, R., Yu, B.: Definitions, methods, and applications in interpretable machine learning. Proceedings of the National Academy of Sciences **116**(44), 22071–22080 (2019)
46. Musavishavazi, S., Alipour, M.: Possibilistic reject-classification based on contrastive learning in vector quantization networks. In: International Conference on Data Mining and Big Data. pp. 353–366. Springer (2022)
47. Musavishavazi, S., Kaden, M., Villmann, T.: Possibilistic classification learning based on contrastive loss in learning vector quantizer networks. In: Artificial Intelligence and Soft Computing: 20th International Conference, ICAISC 2021, Virtual Event, June 21–23, 2021, Proceedings, Part I 20. pp. 156–167. Springer (2021)
48. Musavishavazi, S., Mohannazadeh Bakhtiari, M., Villmann, T.: A mathematical model for optimum error-reject trade-off for learning of secure classification models in the presence of label noise during training. In: Artificial Intelligence and Soft Computing: 19th International Conference, ICAISC 2020, Zakopane, Poland, October 12-14, 2020, Proceedings, Part I 19. pp. 547–554. Springer (2020)
49. Neyman, J., Pearson, E.S.: On the use and interpretation of certain test criteria for purposes of statistical inference: Part i. Biometrika pp. 175–240 (1928)
50. Nilsen, T., Aven, T.: Models and model uncertainty in the context of risk analysis. Reliability Engineering & System Safety **79**(3), 309–317 (2003)
51. Ott, E., Hunt, B.R., Szunyogh, I., Zimin, A.V., Kostelich, E.J., Corazza, M., Kalnay, E., Patil, D., Yorke, J.A.: A local ensemble kalman filter for atmospheric data assimilation. Tellus A: Dynamic Meteorology and Oceanography **56**(5), 415–428 (2004)
52. Peng, R., Han, B., Hu, X., Li, J., Liu, Y.: 2-d probabilistic inversion of mt data and uncertainty quantification using the hamiltonian monte carlo method. Geophysical Journal International **237**(3), 1826–1841 (2024)
53. Popper, K.R., Miller, D.W.: Why probabilistic support is not inductive. Philosophical Transactions of the Royal Society of London. Series A, Mathematical and Physical Sciences **321**(1562), 569–591 (1987)
54. Ray, J., Lefantzi, S., Arunajatesan, S., Dechant, L.: Bayesian parameter estimation of ak-ε model for accurate jet-in-crossflow simulations. AIAA Journal **54**(8), 2432–2448 (2016)

55. Ribeiro, A.H., Schön, T.B.: Overparameterized linear regression under adversarial attacks. IEEE Transactions on Signal Processing **71**, 601–614 (2023)
56. Sedehi, O., Papadimitriou, C., Katafygiotis, L.S.: Data-driven uncertainty quantification and propagation in structural dynamics through a hierarchical bayesian framework. Probabilistic Engineering Mechanics **60**, 103047 (2020)
57. Seo, S., Obermayer, K.: Soft learning vector quantization. Neural computation **15**(7), 1589–1604 (2003)
58. Slater, A.G., Clark, M.P.: Snow data assimilation via an ensemble kalman filter. Journal of Hydrometeorology **7**(3), 478–493 (2006)
59. Tang, J., Li, X., Fu, C., Liu, H., Cao, L., Mi, C., Yu, J., Yao, Q.: A possibility-based solution framework for interval uncertainty-based design optimization. Applied Mathematical Modelling **125**, 649–667 (2024)
60. Thanathamathee, P., Lursinsap, C.: Handling imbalanced data sets with synthetic boundary data generation using bootstrap re-sampling and adaboost techniques. Pattern Recognition Letters **34**(12), 1339–1347 (2013)
61. Ulhe, P.P., Dhepe, A.D., Shevale, V.D., Warghane, Y.S., Jadhav, P.S., Babhare, S.L.: Flexibility management and decision making in cyber-physical systems utilizing digital lean principles with brain-inspired computing pattern recognition in industry 4.0. International Journal of Computer Integrated Manufacturing **37**(6), 708–725 (2024)
62. Vaswani, S., Bach, F., Schmidt, M.: Fast and faster convergence of sgd for over-parameterized models and an accelerated perceptron. In: The 22nd international conference on artificial intelligence and statistics. pp. 1195–1204. PMLR (2019)
63. Vetra-Carvalho, S., Van Leeuwen, P.J., Nerger, L., Barth, A., Altaf, M.U., Brasseur, P., Kirchgessner, P., Beckers, J.M.: State-of-the-art stochastic data assimilation methods for high-dimensional non-Gaussian problems. Tellus Series A **70**, 1445364 (Jan 2018). `https://doi.org/10.1080/16000870.2018.1445364`
64. Wainwright, M.J., Jordan, M.I., et al.: Graphical models, exponential families, and variational inference. Foundations and Trends® in Machine Learning **1**(1–2), 1–305 (2008)
65. Walley, P.: Statistical reasoning with imprecise probabilities (1991)
66. Wan, Z., Zhang, Y., He, H.: Variational autoencoder based synthetic data generation for imbalanced learning. In: 2017 IEEE symposium series on computational intelligence (SSCI). pp. 1–7. IEEE (2017)
67. Wang, J., Lan, C., Liu, C., Ouyang, Y., Qin, T., Lu, W., Chen, Y., Zeng, W., Philip, S.Y.: Generalizing to unseen domains: A survey on domain generalization. IEEE transactions on knowledge and data engineering **35**(8), 8052–8072 (2022)
68. Xiao, L., Peng, Y., Hong, L.J., Ke, Z., Yang, S.: Training artificial neural networks by generalized likelihood ratio method: An effective way to improve robustness. In: 2020 IEEE 16th International Conference on Automation Science and Engineering (CASE). pp. 1343–1348. IEEE (2020). `https://doi.org/10.1109/CASE48305.2020.9216839`
69. Yang, A., Li, D., Li, G.: A fast adaptive online gradient descent algorithm in over-parameterized neural networks. Neural Processing Letters **55**(4), 4641–4659 (2023)
70. Zadeh, L.: Fuzzy sets as a basis for a theory of possibility. Fuzzy sets and systems **100**, 9–34 (1999)
71. Zadeh, L.A.: Fuzzy sets. Information and control **8**(3), 338–353 (1965)
72. Zhang, C., Bengio, S., Hardt, M., Recht, B., Vinyals, O.: Understanding deep learning (still) requires rethinking generalization. Communications of the ACM **64**(3), 107–115 (2021)
73. Zhu, H., Rohwer, R.: Bayesian invariant measurements of generalization. Neural Processing Letters **2**, 28–31 (1995)
74. Zhu, H., Rohwer, R.: Measurements of generalisation based on information geometry. In: Mathematics of neural networks: models, algorithms and applications, pp. 394–398. Springer (1997)

75. Zhu, X., Wu, X.: Class noise vs. attribute noise: A quantitative study. Artificial intelligence review **22**, 177–210 (2004)