

NATURAL STATE-PREDICTION ACCURACY CAN HIDE WEAK CONTROLLED RESPONSIVENESS IN VLA READOUTS

Hyungjoon Kim^{1*} Wonbin Son¹ Mi Young Lee²
Jun Young Lee² Seungmin Rho^{2†}

¹ Changwon National University ² Chung-Ang University

hyungjoon@changwon.ac.kr diwjidghk78@gmail.com
miylee@cau.ac.kr tfg0074@cau.ac.kr smrho@cau.ac.kr

ABSTRACT

Accurately decoding object states from the internal representations of vision-language-action (VLA) models does not establish that the predictions respond faithfully to changes in the target physical state. In natural observations, object state, robot configuration, occlusion, and task progress vary together, allowing contextual cues to contribute to prediction. In this paper, we introduce an evaluation framework that separates prediction accuracy, target-state responsiveness, and context stability using physically validated observations that cross target coordinates with robot contexts. We demonstrate that high natural-trajectory accuracy can coexist with weak controlled target-state responsiveness in fixed representation–readout pairs. Comparisons and interventions involving representations, readouts, and training data show that the three properties provide distinct diagnostic information. Furthermore, adding responsiveness and context sensitivity to a failure predictor based on initial state error and physical variables reduces policy-failure prediction error on new initializations relative to the specified baseline while same-observation controlled MAE is also informative. These findings motivate evaluating target-state responsiveness and context stability alongside natural prediction accuracy, and examining their relationship to actual policy behavior and task outcomes.

1 INTRODUCTION

Recent studies examine whether object states, robot states, and task progress can be decoded from vision-language-action (VLA) representations. They recover object and action states, state transitions, and robot-related variables from hidden features, and use these estimates for behavioral intervention or failure recovery (Lu et al., 2025; Molinari et al., 2025; Buurmeijer et al., 2026; Zhang et al., 2026a). Such analyses provide a way to investigate the state information available in a model and its potential use.

However, low prediction error on natural trajectories alone does not establish that a fixed representation–readout pair responds faithfully to the target physical variable. Along successful trajectories, object state changes together with robot configuration, contact, occlusion, and task progress. Natural accuracy therefore leaves unresolved whether predictions respond appropriately

*First author.

†Corresponding author: smrho@cau.ac.kr.




Figure 1: Evaluation framework. (a) Target state and robot context co-vary in natural observations. (b) Crossed comparisons vary state at fixed context (orange row) and context at fixed state (blue column). (c) The same fixed representation–readout pair is evaluated for accuracy, responsiveness, and stability. A separate fixed policy receives observations, and its outcomes are related to the diagnostics (dashed connection). Readout predictions are not policy inputs. Scenes, grids, and small plots are schematic illustrations.

when object state changes at fixed robot configuration, or remain stable when robot configuration changes at fixed object state.

We distinguish three properties. **Prediction accuracy** measures how accurately a readout estimates the target coordinate in natural observations. **Target-state responsiveness** measures how its predictions change with the actual coordinate at fixed robot context. **Context stability** measures how consistently it predicts the same target state across robot contexts. Responsiveness and stability must be considered jointly: an almost constant readout can appear stable while failing to respond to state changes, whereas a responsive readout can remain sensitive to context. Together with natural accuracy, these properties assess how faithfully the readout responds to the target physical coordinate.

We fit state readouts to frozen VLA features and evaluate each pair on natural observations and observations that cross target coordinates with robot contexts. We also examine the relationship between these diagnostics and policy outcomes. Decoding a state, responding to a physical change, producing an action, and completing a task are distinct evaluation targets.

Figure 1 summarizes the framework and its behavioral connection. First, we construct physically and visually validated crossed comparisons that separate accuracy, responsiveness, and context stability. Second, a fixed confirmatory protocol and comparisons across representations and readouts establish the separation between natural accuracy and controlled responsiveness; training interventions and candidate comparisons reveal how the diagnostics change under different choices. Third, we evaluate failure predictors on separate initializations to determine whether controlled diagnostics provide outcome information beyond initial state error and specified physical variables. A comparison with simple error summaries from the same controlled observations further characterizes this contribution.

2 RELATED WORK

Decoding state and task signals from VLA representations. Lu et al. (2025) analyze symbolic object and action states in OpenVLA, while Molinari et al. (2025) probe future changes in visual state embeddings. Buurmeijer et al. (2026) study linearly observable robot-related features and representation interventions for behavioral control. ProbeAct uses object-position estimates from hidden features for failure recovery (Zhang et al., 2026a). Bhardwaj et al. (2026) analyze task progress and language counterfactuals, distinguishing decodability from steerability. Zhang et al. (2026c) evaluate success-related signals in frozen representations through task- and timestep-matched comparisons and action selection.

State representations and control performance. Dong et al. (2026) relate the quality of environment-state decoding from pretrained visual encoders to downstream control performance. This supports using state information when selecting representations. We address a different question from correlations across models: whether a given readout’s natural accuracy establishes its responsiveness to controlled physical changes.

Interpreting and intervening on VLA computations. Häon et al. (2025) steer behavior through semantic activation directions, and Mitra et al. (2025) identify task-relevant attention heads for selective finetuning. Swann et al. (2026) study interpretable sparse-autoencoder features and their behavioral effects. Grant et al. (2026) examine modality and computational pathways through activation injection and probing. VLA-Trace connects representation changes, attention interventions, and behavioral tests (Shi et al., 2026), while Zhang et al. (2026b) study how masking visual regions affects actions and relates to generalization.

Diagnosing robot-policy failures. DART (Laskey et al., 2017) and HYDRA (Belkhale et al., 2023) address execution errors and distribution shift in imitation learning. Sentinel monitors generative policies using consistency and progress (Agia et al., 2025). Complementing these studies, we measure the responsiveness and stability of the same state readout through crossed physical-coordinate and robot-context comparisons, and test whether these summaries provide outcome information beyond initial state error and physical variables.

3 METHOD

The proposed evaluation separates natural state-prediction accuracy from responses to controlled target-coordinate changes. Let $z = f(o)$ be a frozen representation and $\hat{q} = h(z)$ a fitted state readout. We apply the same $h \circ f$ to natural and crossed target-state-by-context observations. Responsiveness is measured at the prediction output of this pair.

3.1 TARGET STATES, ROBOT CONTEXTS, AND CONTROLLED COMPARISONS

The target state q is a single continuous physical coordinate, such as a joint displacement, rotation angle, or object-position component. A scene s is an independent evaluation unit, corresponding to one simulator initialization. Let P and K denote the numbers of robot contexts and target-coordinate values, with indices $p \in \{1, \dots, P\}$ and $k \in \{1, \dots, K\}$. They count evaluation conditions, not coordinate dimensions. We denote an observation and its measured coordinate by o_{spk} and q_{spk} .

Robot context specifies the robot’s pose and configuration at observation time; associated changes in robot appearance and object occlusion can also affect the image. Natural trajectories couple coordinate and context changes. Crossing P contexts with K coordinates provides two comparisons: varying k at fixed p evaluates responsiveness, whereas varying p at fixed k evaluates stability at the same state.

The fixed quantities must agree within task-specific tolerances at the final observation time. Metrics are computed on valid crossed grids specified by each analysis. A metric is not estimated if the required endpoints, coordinate separation, or context set cannot be obtained. Cells are not excluded based on prediction results.

3.2 ACCURACY, RESPONSIVENESS, AND CONTEXT SENSITIVITY

Prediction accuracy. We use mean absolute error (MAE). Natural MAE first averages observation errors within each rollout, then weights multiple rollouts from the same scene equally. Controlled MAE weights the crossed observations within a scene equally. Each measures accuracy under its respective observation condition.

Target-state responsiveness. For the two endpoints $k = 1, K$ of the tested coordinate range, define the signed endpoint gain and its scene mean as

$$g_{sp} = \frac{\hat{q}_{spK} - \hat{q}_{sp1}}{q_{spK} - q_{sp1}}, \quad G_s = \frac{1}{P} \sum_{p=1}^P g_{sp}. \quad (1)$$

Both differences retain their signs. Thus, $g_{sp} = 1$ indicates a prediction change with the correct direction and magnitude, zero indicates equal endpoint predictions, and a negative gain indicates the opposite direction. Gain is a dimensionless response ratio, not a distance. To detect cancellation between under- and over-response across contexts, we also measure

$$E_{G,s} = \frac{1}{P} \sum_{p=1}^P |g_{sp} - 1|. \quad (2)$$

An error of zero means unit endpoint gain in every tested context. Endpoint gain does not determine intermediate linearity, monotonicity, or absolute prediction error; we therefore examine MAE and coordinate-wise prediction curves alongside it.

Context sensitivity. We average the prediction range across contexts at each target coordinate:

$$R_s = \frac{1}{K} \sum_{k=1}^K \left(\max_p \hat{q}_{spk} - \min_p \hat{q}_{spk} \right). \quad (3)$$

A small R_s indicates less variation across the tested contexts. A constant predictor also has $R_s = G_s = 0$, so stability is interpreted jointly with responsiveness and accuracy. This diagnostic concerns the state readout; it does not require identical policy actions at different robot configurations. All metrics are computed per scene and summarized with equal scene weights. MAE and R_s retain the coordinate’s physical units; g_{sp} , G_s , and $E_{G,s}$ are dimensionless.

3.3 READOUT FITTING AND BEHAVIORAL EVALUATION

We freeze the feature extractor and fit readouts using training features, with normalization determined on training data. We compare full-natural training with natural and controlled training matched in sample count and actual target coordinates. Joint training specifies the contribution of each data source to the loss. Each fitted representation–readout pair remains fixed during evaluation.

Behavioral relevance is evaluated separately. Under the same observation conditions, we record readout predictions, policy actions, subsequent object states, and task success. Diagnostic outputs are not fed back to the policy. We add controlled diagnostics to failure predictors using initial state error and physical variables, then compare losses on separate evaluation initializations. A baseline using MAE from the same controlled observations distinguishes the value of additional observations from that of their diagnostic summaries.

3.4 CONTROLLED OBSERVATION CONSTRUCTION AND VALIDATION

Task-specific state-setting and restoration procedures establish target coordinates and robot configurations. After the specified settling or state-maintenance checks, we validate the physical state and image actually used for evaluation, including coordinate, robot configuration, object stability, velocity, and contact. Matched-training observations reproduce the measured coordinates of selected natural observations, and labels are checked after generation.

Visual checks assess target visibility, image differences induced by coordinate changes, and repeated-rendering agreement. Segmentation and physical metadata are used for validation, not as primary readout inputs. Natural observations retain their original occlusion and image distribution.

Physical validity and training support are assessed separately. Robot proximity, coordinate range and density, and joint distances over physical variables are distinct checks. Passing a limited check does not establish equality of the full state–context distribution. Support-conditioned analyses are reported as non-estimable if valid comparisons fall below their fixed minimum. Appendices A, E, and F specify the procedures and thresholds.

3.5 EVALUATION PROTOCOL AND STATISTICAL ANALYSIS

Training, development, confirmation, and separate follow-up evaluations have distinct roles. Confirmation data are excluded from fitting and model or hypothesis selection; primary comparisons and statistical procedures are internally fixed before accessing these data. Additional analyses of previously examined data are identified as post hoc.

Independent initializations are the statistical units. Coordinates, contexts, frames, training seeds, and action-noise repetitions within an initialization do not increase the independent sample count. We average scene metrics across MLP seeds and preserve initialization pairing in comparisons and bootstrap resampling. Individual intervals describe evaluation-initialization variability conditional on fixed training data and fitted models.

The primary confirmation uses exact sign tests for directional consistency and paired bootstrap intervals for mean effects and differences. Test families, adjustments, tie rules, and resampling procedures are specified for each experiment. Development and follow-up results are not pooled into the primary confirmatory sample or test family.

4 EXPERIMENTS

The primary confirmation evaluates drawer displacement and faucet rotation in Meta-World (Yu et al., 2020), using ridge readouts fitted to frozen SmolVLA (Shukor et al., 2025) and OpenVLA (Kim et al., 2024) features. Table 1 distinguishes the datasets and roles of the evaluations.

4.1 NATURAL ACCURACY AND CONTROLLED RESPONSIVENESS

We first test whether an accurate natural-trajectory readout responds faithfully to controlled physical changes. **Low natural MAE and small endpoint gain coexist in all four task–representation combinations.** Table 2 reports all three diagnostic axes, and Figure 2 shows every confirmatory scene’s predictions and gains.

All 12 scenes in each combination have $G_s < 1$. The four responsiveness sign tests each yield Holm-adjusted $p = 0.001953125$ across the eight primary hypotheses. These tests establish directional consistency; the curves and effect sizes show the response magnitude. Slopes fitted to all six coordinates are also small, showing that the low global linear response is not specific to the two-endpoint summary (Appendix B.7). Natural prediction accuracy and faithful response to controlled coordinate changes are therefore distinct properties.

Table 1: Evaluation design. Behavioral experiments use a task-adapted, frozen SmolVLA policy in LIBERO (Liu et al., 2023), separately from the Meta-World representation analysis. Appearance interventions, stove evaluations, and development controls use the distinct sample counts reported with their results.

Evaluation	Data and independent units	Purpose
Primary confirmation	24 train / 8 development / 12 confirmation initializations per task; 4 contexts $\times$ 6 coordinates per scene	Natural accuracy, controlled response, matched training
Representation/model extension	32 new evaluation initializations per task; radial/lateral context axes	Fixed-candidate replication and comparison
Free object	32 mug-position initializations; 64 support follow-up initializations	Physical scope and estimability
Failure prediction	96 development / 128 evaluation initializations; 2 normal action-noise rollouts each	Additional pre-rollout outcome information

Table 2: Primary confirmation with full-natural readouts. Values are equal-weight means over 12 scenes per task. MAE and R use mm for Drawer and rad for Faucet; G and E_G are dimensionless. Brackets are individual 95% scene-bootstrap intervals. Unit mean gain does not imply accuracy at every intermediate state. Appendix A.7 reports intervals for all metrics.

Task	Model	Nat. MAE	Ctrl. MAE	G [95% CI]	E_G	R
Drawer	SmolVLA	5.554	74.184	0.1806 [0.1653, 0.1978]	0.8194	16.499
	OpenVLA	3.892	75.884	0.1525 [0.1387, 0.1662]	0.8475	9.797
Faucet	SmolVLA	0.0763	0.6698	0.0211 [0.0035, 0.0388]	0.9789	0.1285
	OpenVLA	0.0570	0.6475	0.0512 [0.0292, 0.0717]	0.9488	0.1008

4.2 ROBUSTNESS TO EVALUATION, READOUT, REPRESENTATION, AND MODEL CHOICES

The separation persists in actual-coordinate-matched evaluations and with RBF and MLP readouts. Some nonlinear settings improve controlled error or response, but improvements in natural accuracy do not consistently improve responsiveness and stability.

We evaluate fixed representation-location, pooling, and readout candidates on new initializations, and extend the comparison to π_0 base (Black et al., 2024) and GR00T N1.6 (NVIDIA GEAR Team, 2025). Table 3 summarizes representative gains. Frozen SigLIP 2, VC-1, R3M, and DINOv3 features exhibit the same type of separation (Tschannen et al., 2025; Majumdar et al., 2023; Nair et al., 2023; Siméoni et al., 2025); the separation is therefore not specific to VLA architectures.

Table 3: Mean endpoint gain of fixed final-mean-ridge candidates on 32 new initializations per task. Radial and lateral axes share initializations and use local ± 10 mm hand-position changes relative to the robot. Model-native input paths differ, so this is not a controlled ranking of model quality. Appendix B provides MAE and candidate details.

Model	Drawer G : radial / lateral	Faucet G : radial / lateral
SmolVLA	0.2058 / 0.2060	0.0097 / 0.0122
OpenVLA	0.1692 / 0.1661	0.0429 / 0.0394
π_0 base	0.1094 / 0.1086	−0.0106 / −0.0011
GR00T N1.6	0.2413 / 0.2426	0.0428 / 0.0435




Figure 2: Confirmatory predictions and responses. Left: all 12 scenes $\times$ 4 context curves per combination (faint), mean predictions (bold), and identity lines (dashed). Right: scene-level endpoint gains and post-hoc all-coordinate slopes; large markers and bars show means and individual 95% intervals. Both summaries are below unit response. Mean gain does not characterize intermediate non-monotonicity.

Table 4: Free-object results and estimability. The first evaluation passes its physical and visual criteria. The support follow-up is non-estimable, not a zero-gain or model-response failure. The target is one position component, not full 6-DoF state.

Evaluation	Initializations	Result
6 cm position variation	32	Natural MAE 128.314 mm; controlled MAE 39.765 mm; $G = 0.140$. Natural error is already large.
Support-conditioned follow-up	64	43 physically valid; 5 support-valid; intersection 0. Below the minimum of 32 for estimation.

Actual-coordinate matching within natural observations also reveals prediction variation, although it does not directly measure low endpoint responsiveness on the natural distribution. Coordinate matching and readout comparisons weaken simple coordinate-range and single-probe explanations. Section 5 discusses the remaining joint-distribution shift.

4.3 SCOPE ACROSS PHYSICAL STATE DEFINITIONS AND TASK SETTINGS

We evaluate a mug’s world- x position to examine the pattern beyond articulated coordinates. As Table 4 shows, the combination of low natural error and weak controlled response does not reproduce in this free-object setting. The physical structure and support of natural training coordinates affect which crossed comparisons can be constructed. Appendices E and F report book and other task-construction results.




Figure 3: Matched controlled minus matched natural training. Points and bars show means and individual 95% paired scene-bootstrap intervals over 12 confirmation scenes. Negative values indicate lower error or sensitivity. For display only, MAE and R are divided by $S = 0.16$ m for Drawer and $S = 1.4$ rad for Faucet; metric definitions are unchanged.

4.4 TRAINING INTERVENTIONS AND DIAGNOSTIC SELECTION

We first replace 36 natural observations with 36 controlled observations matched in training scene, sample count, and actual coordinate. Figure 3 shows lower controlled MAE and gain error but higher natural MAE and mean context sensitivity. This is the tradeoff observed in this matched replacement comparison.

In development analyses, changing coordinate–context pairing changes error and responsiveness even with fixed sample count and coordinate/context marginals. Joint natural–controlled training can reduce both MAEs without reducing context sensitivity. A 50:50 MLP mixture improves both MAEs relative to matched-natural training in all four combinations under the original evaluation, but only one combination under actual-coordinate matching. The evidence supports diagnostic changes that depend on training composition and evaluation conditions, rather than an unavoidable tradeoff.

Candidate comparisons likewise identify Pareto alternatives with advantages in gain error or context sensitivity. Candidates fixed on development data do not retain all relative advantages on new initializations. The minimum-natural-MAE candidate belongs to every development group’s Pareto set, so the two criteria do not establish different unique winners. Appendix C reports the training and candidate comparisons.

4.5 READOUT DIAGNOSTICS AND POLICY BEHAVIOR

Natural whole-trajectory MAE is associated with success, but intervention-condition accuracy rankings do not always preserve success rankings. At the same initial target coordinate, changing robot context reduces MAE from 38.766 to 30.684 mm while successes decrease from 106 to 52 out of 128. This is a descriptive comparison of errors measured after rollout; context also changes geometry and the required actions.

To evaluate pre-rollout information, we fit failure predictors on 96 development initializations and evaluate two normal-noise rollouts from each of 128 separate initializations. M_0 uses initial state error and physical variables; the original M_{GR} adds E_G and R . Post-hoc controls add MAE from the same six controlled snapshots (M_C), or MAE together with E_G, R (M_{CGR}). Existing models are not refitted; both new models are fitted only on development data.

Controlled diagnostics provide additional policy-failure information beyond initial error and physical variables. Both M_{GR} and M_C reduce Brier score and log loss relative to M_0 (Table 5,

Table 5: Failure-prediction losses on the same 128 evaluation initializations; lower is better. Two normal-noise rollouts are grouped within each equally weighted initialization. M_0/M_{GR} form the original fixed comparison; M_C/M_{CGR} are post-hoc additions. This evaluates failure prediction, not an improvement to policy success.

Model	Information added to M_0	Brier	Log loss
M_0	None	0.181515	0.543533
M_C	Controlled MAE	0.175654	0.528602
M_{GR}	E_G, R	0.171381	0.519075
M_{CGR}	Controlled MAE, E_G, R	0.169677	0.514777




Figure 4: Mean loss differences and individual 95% intervals from 20,000 paired initialization-bootstrap draws. Negative differences favor the first model. Original and post-hoc comparisons are distinguished. Intervals describe evaluation uncertainty conditional on the development fits.

Figure 4). For comparisons between summaries of the same controlled observations, the individual 95% intervals for $M_{GR} - M_C$ and $M_{CGR} - M_C$ include zero for both losses.

Additional evaluations distinguish readout, action, and outcome. Changing robot appearance at the same physical state changes the readout and initial action, but paired initial object-progression differences are zero and success-difference intervals include zero. On Stove, small readout responses coexist with high policy success. Understanding the behavioral meaning of a diagnostic therefore requires examining predictions, actions, physical progression, and success together. Appendix F provides the task-specific results.

5 DISCUSSION AND CONCLUSION

5.1 DISCUSSION

Natural state-prediction accuracy establishes that a state can be decoded under natural observations. Our results show that this evidence does not substitute for faithful response to controlled state changes or stability across contexts at the same state. The different diagnostic changes under representation, readout, and training choices indicate that selecting candidates by natural MAE alone can overlook meaningful distinctions.

Time and robot configuration alone predict target coordinates accurately on natural trajectories (Appendix G.4). This establishes contextual predictability, not that the VLA uses the same pathway. Coordinate matching, visual validation, and model comparisons also leave generalization to new

state–context combinations unresolved. The empirical finding is that natural accuracy and controlled responsiveness can separate in the tested fixed representation–readout pairs.

Adding controlled diagnostics improves failure prediction beyond initial error and physical variables, and controlled MAE is also informative. Controlled diagnostics, including controlled MAE, provide additional policy-failure information beyond initial state-prediction error and the specified physical variables. Responsiveness and context sensitivity additionally describe the direction and magnitude of prediction changes and their variation across contexts. Using these diagnostics to improve policy success remains a future research direction.

5.2 LIMITATIONS AND SCOPE

Application to real robots requires further validation. State–context comparisons and outcome-prediction relationships established in simulation may change under real sensor errors, contact, friction, and scene variation. How to use these diagnostics to improve actual task success remains open.

The evaluations cover single physical coordinates in a limited set of tasks and contexts. The free-object setting does not reproduce the same central pattern, and some comparisons cannot jointly satisfy physical and support criteria. Controlled observations may lie outside the natural joint distribution; the present results do not separate representation content, readout feature selection, and distribution-shift effects. Endpoint gain and R also depend on the chosen coordinate range and context set.

Behavioral prediction results concern the evaluated fixed policy, task, and specified baselines. Controlled-MAE comparisons and all-coordinate slopes are post-hoc analyses, with individual intervals conditional on fixed training data and fitted models. We do not establish that the diagnostic readout is the policy’s internal state estimator or a causal mediator of failure.

5.3 CONCLUSION

High state-prediction accuracy on natural images alone does not establish faithful response to controlled target-state changes or downstream task success. We demonstrate distinct accuracy, responsiveness, and context-stability properties in fixed representation–readout pairs, and show that controlled diagnostics provide additional policy-failure information beyond initial error and physical variables. VLA evaluation and design should consider these properties together and examine their relationship to policy behavior and task outcomes.

AI USE STATEMENT

We used ChatGPT and Codex to assist with drafting selected sections of the manuscript, translation and grammatical editing, preparing and editing draft figures and tables, searching for relevant literature, and executing selected experimental code and organizing its results. AI-generated outputs and interpretations were used to support the preparation and refinement of the study, including the design of follow-up analyses and experiments.

Vision-language models were also used to assist with visual inspection of selected rendered observations and figures. These assessments were used as supporting information and were reviewed by the authors.

All AI-assisted outputs, experimental results, analyses, figures, references, and manuscript text were reviewed and verified by the authors. The authors made all final scientific and editorial decisions and take full responsibility for the manuscript and its conclusions.

REPRODUCIBILITY STATEMENT

Section 3 defines the evaluation and metrics. Appendix A specifies data splits, feature extraction, normalization, fitting, validation tolerances, and statistical procedures. Appendices B–G describe the additional evaluations, training interventions, visual checks, physical-setting extensions, behavioral experiments, and support analyses. Model revisions, seeds, independent evaluation units, and the distinction between confirmatory and post-hoc analyses are provided with the corresponding procedures. Appendix H provides examples of controlled observations.

REFERENCES

- Christopher Agia, Rohan Sinha, Jingyun Yang, Ziang Cao, Rika Antonova, Marco Pavone, and Jeannette Bohg. Unpacking Failure Modes of Generative Policies: Runtime Monitoring of Consistency and Progress. In *Conference on Robot Learning*, volume 270 of *Proceedings of Machine Learning Research*, pp. 689–723. PMLR, 2025. URL <https://proceedings.mlr.press/v270/agia25a.html>.
- Suneel Belkhale, Yuchen Cui, and Dorsa Sadigh. HYDRA: Hybrid Robot Actions for Imitation Learning. In *Conference on Robot Learning*, volume 229 of *Proceedings of Machine Learning Research*, pp. 2113–2133. PMLR, 2023. URL <https://proceedings.mlr.press/v229/belkhale23a.html>.
- Atiksh Bhardwaj, Edward Weiyi Duan, Prithwish Dan, Wei-Chiu Ma, and Preston Culbertson. Decoding Task Progress from VLA Representations. arXiv preprint arXiv:2608.13474, 2026. URL <https://arxiv.org/abs/2608.13474>.
- Kevin Black, Noah Brown, Danny Driess, Adnan Esmail, Michael Equi, Chelsea Finn, Niccolo Fusai, Lachy Groom, Karol Hausman, Brian Ichter, Szymon Jakubczak, Tim Jones, Liyiming Ke, Sergey Levine, Adrian Li-Bell, Mohith Mothukuri, Suraj Nair, Karl Pertsch, Lucy Xiaoyang Shi, James Tanner, Quan Vuong, Anna Walling, Haohuan Wang, and Ury Zhilinsky. π_0 : A Vision-Language-Action Flow Model for General Robot Control. arXiv preprint arXiv:2410.24164, 2024. URL <https://arxiv.org/abs/2410.24164>.
- Hugo Buurmeijer, Carmen Amo Alonso, Aiden Swann, and Marco Pavone. Observing and Controlling Features in Vision-Language-Action Models. arXiv preprint arXiv:2603.05487, 2026. URL <https://arxiv.org/abs/2603.05487>.
- Jiahua Dong, Yunze Man, Pavel Tokmakov, and Yu-Xiong Wang. Capturing Visual Environment Structure Correlates with Control Performance. In *International Conference on Learning Representations*, 2026. URL https://proceedings.iclr.cc/paper_files/paper/20

- 26/hash/3bca7054c944d9d254adaa953307bdd8-Abstract-Conference.html.
- Bryce Grant, Xijia Zhao, and Peng Wang. Not All Features Are Created Equal: A Mechanistic Study of Vision-Language-Action Models. arXiv preprint arXiv:2603.19233, 2026. URL <https://arxiv.org/abs/2603.19233>.
- Bear Häon, Kaylene Caswell Stocking, Ian Chuang, and Claire Tomlin. Mechanistic Interpretability for Steering Vision-Language-Action Models. In *Conference on Robot Learning*, volume 305 of *Proceedings of Machine Learning Research*, pp. 2743–2762. PMLR, 2025. URL <https://proceedings.mlr.press/v305/haon25a.html>.
- Moo Jin Kim, Karl Pertsch, Siddharth Karamcheti, Ted Xiao, Ashwin Balakrishna, Suraj Nair, Rafael Rafailov, Ethan Foster, Grace Lam, Pannag Sanketi, Quan Vuong, Thomas Kollar, Benjamin Burchfiel, Russ Tedrake, Dorsa Sadigh, Sergey Levine, Percy Liang, and Chelsea Finn. OpenVLA: An Open-Source Vision-Language-Action Model. arXiv preprint arXiv:2406.09246, 2024. URL <https://arxiv.org/abs/2406.09246>.
- Michael Laskey, Jonathan Lee, Roy Fox, Anca Dragan, and Ken Goldberg. DART: Noise Injection for Robust Imitation Learning. In *Conference on Robot Learning*, volume 78 of *Proceedings of Machine Learning Research*, pp. 143–156. PMLR, 2017. URL <https://proceedings.mlr.press/v78/laskey17a.html>.
- Bo Liu, Yifeng Zhu, Chongkai Gao, Yihao Feng, Qiang Liu, Yuke Zhu, and Peter Stone. LIBERO: Benchmarking Knowledge Transfer for Lifelong Robot Learning. In *Advances in Neural Information Processing Systems*, volume 36, 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/8c3c666820ea055a77726d66fc7d447f-Abstract-Datasets_and_Benchmarks.html.
- Hong Lu, Hengxu Li, Prithviraj Singh Shahani, Stephanie Herbers, and Matthias Scheutz. Probing a Vision-Language-Action Model for Symbolic States and Integration into a Cognitive Architecture. arXiv preprint arXiv:2502.04558, 2025. URL <https://arxiv.org/abs/2502.04558>.
- Arjun Majumdar, Karmesh Yadav, Sergio Arnaud, Yecheng Jason Ma, Claire Chen, Sneha Silwal, Aryan Jain, Vincent-Pierre Berges, Pieter Abbeel, Jitendra Malik, Dhruv Batra, Yixin Lin, Oleksandr Maksymets, Aravind Rajeswaran, and Franziska Meier. Where are we in the search for an Artificial Visual Cortex for Embodied Intelligence? arXiv preprint arXiv:2303.18240, 2023. URL <https://arxiv.org/abs/2303.18240>.
- Chancharik Mitra, Yusen Luo, Raj Saravanan, Dantong Niu, Anirudh Pai, Jesse Thomason, Trevor Darrell, Abrar Anwar, Deva Ramanan, and Roei Herzig. Mechanistic Finetuning of Vision-Language-Action Models via Few-Shot Demonstrations. arXiv preprint arXiv:2511.22697, 2025. URL <https://arxiv.org/abs/2511.22697>.
- Marco Molinari, Leonardo Nevali, Saharsha Navani, and Omar G. Younis. Emergent World Representations in OpenVLA. arXiv preprint arXiv:2509.24559, 2025. URL <https://arxiv.org/abs/2509.24559>.
- Suraj Nair, Aravind Rajeswaran, Vikash Kumar, Chelsea Finn, and Abhinav Gupta. R3M: A Universal Visual Representation for Robot Manipulation. In *Conference on Robot Learning*, volume 205 of *Proceedings of Machine Learning Research*, pp. 892–909. PMLR, 2023. URL <https://proceedings.mlr.press/v205/nair23a.html>.
- NVIDIA GEAR Team. GR00T-N1.6-3B. NVIDIA official model card, 2025. URL <https://huggingface.co/nvidia/GR00T-N1.6-3B>.

- Haoyuan Shi, Xiancong Ren, Yingji Zhang, Qinfan Zhang, Jiayu Hu, Haozhe Shan, Han Dong, Jinpeng Lu, Yinda Chen, Yi Zhang, Yong Dai, and Xiaozhu Ju. VLA-Trace: Diagnosing Vision-Language-Action Models through Representation and Behavior Tracing. arXiv preprint arXiv:2605.30117, 2026. URL <https://arxiv.org/abs/2605.30117>.
- Mustafa Shukor, Dana Aubakirova, Francesco Capuano, Pepijn Kooijmans, Steven Palma, Adil Zouitine, Michel Aractingi, Caroline Pascal, Martino Russi, Andres Marafioti, Simon Alibert, Matthieu Cord, Thomas Wolf, and Remi Cadene. SmolVLA: A Vision-Language-Action Model for Affordable and Efficient Robotics. arXiv preprint arXiv:2506.01844, 2025. URL <https://arxiv.org/abs/2506.01844>.
- Oriane Siméoni, Huy V. Vo, Maximilian Seitzer, Federico Baldassarre, Maxime Oquab, Cijo Jose, Vasil Khalidov, Marc Szafraniec, Seungeun Yi, Michaël Ramamonjisoa, Francisco Massa, Daniel Haziza, Luca Wehrstedt, Jianyuan Wang, Timothée Darcet, Théo Moutakanni, Leonel Sentana, Claire Roberts, Andrea Vedaldi, Jamie Tolan, John Brandt, Camille Couprie, Julien Mairal, Hervé Jégou, Patrick Labatut, and Piotr Bojanowski. DINOv3. arXiv preprint arXiv:2508.10104, 2025. URL <https://arxiv.org/abs/2508.10104>.
- Aiden Swann, Lachlain McGranahan, Hugo Buurmeijer, Monroe Kennedy III, and Mac Schwager. Sparse Autoencoders Reveal Interpretable and Steerable Features in VLA Models. arXiv preprint arXiv:2603.19183, 2026. URL <https://arxiv.org/abs/2603.19183>.
- Emanuel Todorov, Tom Erez, and Yuval Tassa. MuJoCo: A Physics Engine for Model-Based Control. In *IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 5026–5033, 2012. doi: 10.1109/IROS.2012.6386109. URL <https://www.roboti.us/lab/papers/TodorovIROS12.pdf>.
- Michael Tschannen, Alexey Gritsenko, Xiao Wang, Muhammad Ferjad Naeem, Ibrahim Alabdulmohsin, Nikhil Parthasarathy, Talfan Evans, Lucas Beyer, Ye Xia, Basil Mustafa, Olivier Hénaff, Jeremiah Harmsen, Andreas Steiner, and Xiaohua Zhai. SigLIP 2: Multilingual Vision-Language Encoders with Improved Semantic Understanding, Localization, and Dense Features. arXiv preprint arXiv:2502.14786, 2025. URL <https://arxiv.org/abs/2502.14786>.
- Tianhe Yu, Deirdre Quillen, Zhanpeng He, Ryan Julian, Karol Hausman, Chelsea Finn, and Sergey Levine. Meta-World: A Benchmark and Evaluation for Multi-Task and Meta Reinforcement Learning. In *Conference on Robot Learning*, volume 100 of *Proceedings of Machine Learning Research*, pp. 1094–1100. PMLR, 2020. URL <https://proceedings.mlr.press/v100/yu20a.html>.
- Fan Zhang, Seongbin Park, Baharan Mirzasoleiman, Shariar Talebi, and Nader Sehatbakhsh. Probe-Act: Probe-Guided Training-Free Failure Recovery in Vision-Language-Action Models. arXiv preprint arXiv:2606.09740, 2026a. URL <https://arxiv.org/abs/2606.09740>.
- Hanxin Zhang, Mingshuo Xu, Abdulqader Dhafer, Shigang Yue, Hongbiao Dong, and Zhou Daniel Hao. Embodied Interpretability: Linking Causal Understanding to Generalization in Vision-Language-Action Models. arXiv preprint arXiv:2605.00321, 2026b. URL <https://arxiv.org/abs/2605.00321>.
- Jiachen Zhang, Junnan Nie, Junyi Lao, Wei Cheng, Chenghao Liu, Jiaxin Jiang, and Songfang Huang. What Frozen VLAs Already Know About Success: A Probing Study of Value-Like Structure in Foundation Robot Policies. arXiv preprint arXiv:2605.28527, 2026c. URL <https://arxiv.org/abs/2605.28527>.

A PRIMARY CONSTRUCTION AND STATISTICAL PROTOCOL

This appendix specifies the primary Meta-World evaluation. Appendices B–G provide robustness analyses, training comparisons, visual controls, physical scope, behavioral evaluation, and additional controls, respectively.

A.1 TASKS, SPLITS, AND OBSERVATION SAMPLING

We use `drawer-open-v3` and `faucet-open-v3` in Meta-World 3.1.1 with MuJoCo 3.3.0 (Todorov et al., 2012), retaining the native tasks and dynamics. Each task has 24 training, eight development, and 12 confirmation initializations. Natural training contains 652 drawer and 479 faucet observations; development contains 220 and 156, respectively. Across both tasks, confirmation contains 563 natural and 576 controlled observations.

Confirmation initializations are excluded from fitting, selection, and evaluation-design development. Models, feature paths, normalization, fitting, rendering, admission criteria, hypotheses, and analyses were fixed internally before accessing the confirmation data. This was an internally fixed protocol, not external preregistration. Natural trajectories are sampled every four frames, additionally including the first successful and terminal frames without duplication. Natural occlusion is retained; the controlled-visibility filter is not applied to natural observations.

Each controlled scene crosses four robot contexts with six coordinates. Context anchors are frames 6, 12, 24, and 36 for Drawer, and 12, 16, 20, and 24 for Faucet. These indices do not imply identical poses across scenes. Drawer coordinates are $[0, -0.04, -0.08, -0.12, -0.145, -0.16]$ m; faucet coordinates are $[0, 0.28, 0.56, 0.84, 1.12, 1.40]$ rad.

A.2 FROZEN FEATURES, NORMALIZATION, AND READOUT FITTING

Encoders remain frozen, and diagnostic predictions are not fed to a policy. The primary SmolVLA feature concatenates four spatial means of final prefix image tokens (3,840 dimensions). The primary OpenVLA feature averages 256 final-layer image hidden states (4,096 dimensions). We retain model-native preprocessing, fixed task instructions, and input paths. OpenVLA’s causal image tokens cannot attend to subsequent language tokens; the models therefore do not provide identically language-conditioned features.

The diagnostic readout receives no ground-truth coordinate, numerical proprioception, scene/frame identifier, task progress, object/goal vector, or segmentation mask. Such metadata are reserved for validation and explicitly privileged controls. For full-natural training, each trajectory has equal total weight, distributed equally among its sampled observations. For features z_i and weights summing to one, normalization is

$$\mu = \sum_i w_i z_i, \quad a = \sqrt{\sum_i w_i \|z_i - \mu\|^2}, \quad x_i = (z_i - \mu)/a. \quad (4)$$

Training conditions sharing a representation use the same full-natural normalization. Ridge regression minimizes weighted squared error plus $\lambda \|\beta\|^2$, with $\lambda = 0.001$ and an unpenalized intercept.

Table S1: Primary training conditions. Implementation names are included solely to map stored artifacts to scientific conditions.

Condition	Artifact name	Training observations
Full natural	<code>natural_full</code>	All 24 natural training trajectories
Matched natural	<code>natural36</code>	Six scenes, six observations each; 36 total
Matched controlled	<code>exact_control36</code>	The same six scenes and 36 actual coordinates

Matching sample count and coordinate values does not match the joint distribution of robot configuration, contact, velocity, and appearance.

A.3 STATE RESTORATION, SETTLING, AND VISUAL ADMISSION

For each context, we restore the simulator state, set the native object joint coordinate and zero object velocity, and apply 60 fixed neutral actions under the original dynamics. A fixed quantity means agreement of the final measured state within tolerance, rather than agreement of nominal commands. Matched training observations reproduce the natural observation’s actual coordinate; they are not relabeled grid observations.

We use `corner4` for Drawer and `corner3` for Faucet, with 256×256 RGB, MSAA disabled, and fixed geometry, lighting, shadows, and hidden sites. Five repeated renders are generated for each observation. Confirmation repeats are bit-identical. Target visible area must be at least 64 pixels, and endpoint centroid displacement at least four pixels. All 24 confirmation scenes and 96 scene–context groups pass without replacement. These criteria establish the intended comparison, not membership in the natural joint distribution.

A.4 INDEPENDENT UNITS AND FIXED INFERENCE

A scene is an independent simulator initialization. Frames, contexts, readouts, training seeds, and bootstrap draws do not increase the number of scenes. Scene metrics have equal weight; multiple natural rollouts are averaged equally within scene.

The eight primary hypotheses cross two tasks and two representations with (i) $1 - G_s > 0$ for full-natural readouts and (ii) positive controlled-MAE differences between matched-natural and matched-controlled training. One-sided exact sign tests use fixed ties and Holm correction across all eight hypotheses. They test directional consistency, not the mean effect magnitude.

We use 20,000 paired scene-bootstrap draws for individual percentile 95% intervals of mean effects. All compared conditions retain scene pairing. Intervals condition on fixed training data and fitted pairs. Coordinate–context assignment analyses instead use 5,000 paired draws over eight development scenes; these are post-hoc, descriptive, unadjusted intervals. The two populations and inferential roles are not pooled.

A.5 VALIDATION AND NUMERICAL REPRODUCIBILITY

Physical checks cover object drift, final speed, unintended contact, repeated-state agreement, and final robot consistency across target coordinates. They do not require every state during settling to be stationary. The robot-support check requires a single natural training state to satisfy the position, arm, gripper, and orientation bounds jointly; it does not certify full joint support. Natural–controlled MAE differences consequently remain descriptive rather than estimates of a context-specific causal effect.

Independent numerical replay checks features, predictions, and metrics separately from rendering reproducibility. An early MSAA-on drawer render differed by one intensity level. That discrepancy was retained, and the final MSAA-off pipeline was fixed for training feature extraction, normalization, and evaluation before confirmation. Checkpoint revisions, initialization identifiers, and checksums specify reproducibility; internal workflow names are not scientific conditions.

A.6 IMPLEMENTATION DETAILS AND NUMERICAL THRESHOLDS

Coordinate matching uses one-to-one assignment minimizing squared coordinate differences, implemented with `scipy.optimize.linear_sum_assignment` and a fixed index order for ties. Controlled matches target the final measured natural coordinate.

Table S2: Primary simulator initialization identifiers.

Task	Training	Development	Confirmation
Drawer	108200–108223	108300–108307	108400–108411
Faucet	110200–110223	110300–110307	110400–110411

Neutral actions are $[0, 0, 0, -1]$ for Drawer and $[0, 0, 0, +1]$ for Faucet, applied through the native action interface for 60 steps. Object drift and final speed are each at most 10^{-3} (m and m/s for Drawer; rad and rad/s for Faucet). Repeated-state component differences are at most 10^{-8} , and final robot-state spread across target coordinates is at most 10^{-7} . One common natural training state must match end-effector position within 0.02 m, arm-joint RMSE within 0.15 rad, gripper RMSE within 0.005 m, and orientation within 10° . These thresholds were not adjusted after confirmation.

The robot consistency vector contains seven arm joints (rad), two gripper joints (m), three hand-position components (m), and four quaternion components. Drawer uses each component’s maximum minus minimum across coordinate conditions; Faucet uses the maximum absolute difference from the first coordinate condition. Tolerances apply componentwise in native units, not to an aggregate physical distance mixing units.

The primary sign-test tie tolerance is 10^{-8} . Confirmation uses 20,000 bootstrap draws and seed 113200; coordinate–context assignment uses 5,000 draws. Stored task-specific indices are shared across paired conditions. Repeated observations within a scene/root are never resampled independently.

Table S3: Frozen feature paths. Model-native token grids and preprocessing are retained.

Model	Feature	Dimension/pooling
SmolVLA	Final prefix image tokens	Four spatial means concatenated; 3,840 primary
OpenVLA	Final-layer 256 causal image states	Mean; 4,096 primary
π_0 base	Final native image/prefix features	Mean or adaptive 2×2 ; no numerical robot state in this feature path
GR00T N1.6	Final native visual tokens	Native 9×9 grid; mean or adaptive 2×2
SigLIP2	Vision pooler output	768; revision-pinned processor
VC-1	Normalized CLS	768; official resize/crop and ImageNet normalization
R3M	ResNet-50 pre-FC average pool	2,048; official preprocessing
DINOv3	Post-normalization CLS	384; official 224×224 preprocessing

The SmolVLA checkpoint SHA is 7cd549ac2351fb069c0ddb3c34ad2d09cfc92b56a15dcdcf2e41467aaca01eb; OpenVLA revision is 47a0ec7fc4ec123775a391911046cf33cf9ed83f. VC-1 and R3M source revisions are 76fe35e87b1937168f1ec4b236e863451883eaf3 and b2334e726887fa0206962d7984c69c5fb09cceaab. DINOv3 uses facebook/dinov3-vits16-pretrain-lvd1689m, checkpoint revision 114c1379950215c8b35dfcd4e90a5c251dde0d32, and source revision 6876159a11b4df116f30f667f8c9888617df0751. Its inference is FP32 with TF32 disabled.

DINOv3 uses the common inventory of 9,955 images and two task-specific ridge heads. The accepted run produces 8,064 predictions, 384 root–condition metrics, and 16 development-root metrics; independent numerical replay has maximum absolute difference 1.221×10^{-15} . All four non-VLA controls use natural-only task-specific ridge heads ($\lambda = 0.001$), with equal total weight per natural training root, and no encoder updates or policy rollouts.

The SmolVLA/OpenVLA extension contains 64 logical candidates and 96 fitted heads, combining intermediate/final features, mean/spatial pooling, ridge/RBF/MLP, and PCA-ridge. The π_0 /GR00T extension contains 24 candidates and 40 fitted heads. GR00T’s adaptive-pooling bins differ from those of SmolVLA/OpenVLA. Dimension and input-path differences preclude interpreting these comparisons as a controlled ranking of representation quality.

A.7 COMPLETE PRIMARY METRICS AND UNCERTAINTY

Table S4 provides all primary intervals using the original scene metrics and resampling indices. Recomputed predictions used for the figures agree with the stored metrics.

Table S4: Complete primary metrics: mean [individual 95% scene-bootstrap interval], $n = 12$ per task. MAE/ R are mm for Drawer and rad for Faucet; G , E_G are dimensionless.

Task	Metric	SmolVLA	OpenVLA
Drawer	Natural MAE	5.554 [4.921, 6.328]	3.892 [3.357, 4.477]
	Controlled MAE	74.184 [72.277, 75.993]	75.884 [74.810, 76.974]
	G	0.1806 [0.1653, 0.1978]	0.1525 [0.1387, 0.1662]
	E_G	0.8194 [0.8022, 0.8347]	0.8475 [0.8338, 0.8613]
	R	16.499 [13.189, 20.415]	9.797 [7.576, 12.035]
Faucet	Natural MAE	0.0763 [0.0596, 0.0940]	0.0570 [0.0446, 0.0707]
	Controlled MAE	0.6698 [0.6560, 0.6841]	0.6475 [0.6326, 0.6614]
	G	0.0211 [0.0035, 0.0388]	0.0512 [0.0292, 0.0717]
	E_G	0.9789 [0.9612, 0.9965]	0.9488 [0.9283, 0.9708]
	R	0.1285 [0.1115, 0.1459]	0.1008 [0.0861, 0.1171]




Figure S1: All primary scene-level context sensitivities R , with means and individual 95% intervals. Each point is one initialization; contexts and observations are not independent sample units.

B ROBUSTNESS ACROSS EVALUATION, READOUTS, REPRESENTATIONS, AND MODELS

B.1 COORDINATE-MATCHED EVALUATION

The primary controlled grid and natural trajectories need not share coordinate marginals. We therefore select natural development observations by measured q and reconstruct the same coordinates

at each controlled context. This post-hoc evaluation reuses eight development scenes per task and no confirmation scenes. Table S5 uses full-natural MLPs, averaging scene metrics over three fixed training seeds rather than ensembling predictions or selecting the best seed.

Table S5: Actual-coordinate-matched development evaluation.

Task	Model	Matched natural MAE	Matched controlled MAE	G
Drawer	SmolVLA	4.155 mm	49.369 mm	0.1217
	OpenVLA	3.242 mm	49.317 mm	0.1451
Faucet	SmolVLA	0.1025 rad	0.5976 rad	0.0193
	OpenVLA	0.0755 rad	0.5873 rad	0.0442

Mean errors remain separated after matching actual-coordinate marginals, with local counterexamples retained. Across the nonlinear matched analysis, controlled error is no greater than natural error in 315 of 2,304 coordinate-level rows and 1,454 of 9,216 coordinate-context rows. These repeated observations do not constitute additional independent confirmations.

B.2 NONLINEAR READOUTS AND READOUT CAPACITY

For RBF regression, we compute the off-diagonal median $\tilde{d}$ of normalized training-feature distances and evaluate all nine combinations of $\sigma \in \{0.5\tilde{d}, \tilde{d}, 2\tilde{d}\}$ and $\lambda \in \{10^{-4}, 10^{-3}, 10^{-2}\}$. The kernel is $K_{ij} = \exp(-\|x_i - x_j\|^2 / (2\sigma^2))$, with an unpenalized intercept.

The MLP is `Linear(d, 128) - GELU - Linear(128, 1)` without dropout. Targets use training-only weighted mean/standard deviation. AdamW uses learning rate and weight decay 10^{-3} , $\beta = (0.9, 0.999)$, and $\epsilon = 10^{-8}$. We run 1,000 full-batch updates without early stopping or development-based checkpoint selection, using seeds 42001, 42002, and 42003. Representative MLP values average metrics across these seeds.

Table S6: Representative full-natural development results. MAE/ R are mm for Drawer and rad for Faucet. RBF uses fixed $\sigma = \tilde{d}$, $\lambda = 0.001$; MLP averages three seed-specific metrics.

Task	Model	Readout	Nat. MAE	Ctrl. MAE	G	E_G	R
Drawer	SmolVLA	Linear	4.846	76.295	0.1785	0.8215	15.514
		RBF	6.068	75.934	0.1696	0.8304	15.316
		MLP	3.650	78.502	0.1506	0.8494	13.176
	OpenVLA	Linear	3.606	76.217	0.1487	0.8513	10.534
		RBF	4.590	77.307	0.1262	0.8738	9.752
		MLP	2.408	78.310	0.1337	0.8663	8.822
Faucet	SmolVLA	Linear	0.0846	0.6625	0.0128	0.9872	0.1317
		RBF	0.0892	0.6524	0.0130	0.9870	0.1207
		MLP	0.0634	0.6542	0.0181	0.9819	0.1292
	OpenVLA	Linear	0.0623	0.6501	0.0351	0.9649	0.1159
		RBF	0.0643	0.6477	0.0378	0.9622	0.0983
		MLP	0.0510	0.6413	0.0405	0.9595	0.1241

The full-natural nonlinear grid contains 48 fitted conditions: nine RBF settings and three MLP seeds for each of four task-representation combinations. Every condition has mean controlled MAE greater than natural MAE and $G < 1$ over the eight development scenes. These are decoder comparisons on shared scenes, not 48 independent datasets.

RBF/MLP gain ranges are respectively 0.108–0.175/0.147–0.153 for Drawer–SmolVLA, 0.083–0.144/0.133–0.135 for Drawer–OpenVLA, 0.013–0.022/0.017–0.019 for Faucet–SmolVLA, and

0.019–0.072/0.037–0.043 for Faucet–OpenVLA. Some nonlinear readouts improve controlled error; increasing capacity does not make natural accuracy and responsiveness interchangeable. Independent prediction replay has maximum differences 8.89×10^{-16} for linear, 3.27×10^{-14} for RBF, and 4.12×10^{-7} standardized-target units for MLP.

B.3 REPRESENTATION LOCATION, POOLING, AND DIMENSIONALITY CONTROLS

We cross intermediate/final features with mean/ 2×2 spatial pooling and add 16-dimensional PCA-ridge for SmolVLA and OpenVLA. All 64 logical candidates have development mean controlled MAE greater than natural MAE and $G < 1$. Pooling/readout changes can improve natural MAE while worsening E_G , or vice versa.

On the new evaluation bank, spatial pooling improves natural MAE in all 32 comparisons with mean pooling, and MLP improves it in all 16 comparisons with ridge. Corresponding E_G changes comprise 20 decreases/44 increases for pooling and 12 decreases/20 increases for MLP. Natural MAE uses common natural observations, whereas E_G is measured on two context axes, doubling the comparison count. PCA uses training-only weighted covariance and 16 principal components as a capacity control.

B.4 INDEPENDENT EVALUATION BANKS AND ADDITIONAL MODEL FAMILIES

We use 32 new initializations per task, with radial and lateral hand-position variations of ± 10 mm about a reference configuration. Representative feature–pooling–ridge settings and statistical rules were fixed after development and technical checks, before inspecting new evaluation predictions.

During technical checks, an additional post-settling nominal joint-limit gate failed in 3,340 rows and was removed. Initial inverse-kinematics joint limits and the existing physical/visual checks were retained, as were the original failures and 230 physically invalid matched-observation rows. The modified contract was fixed before inspecting predictions. This bank should not be described as passing every original confirmation gate unchanged.

Table S7: Fixed final-mean-ridge results on 32 new initializations per task. MAEs are mm for Drawer and rad for Faucet. Paired entries denote radial/lateral axes.

Task	Model	Natural MAE	Controlled MAE	G
Drawer	SmolVLA	7.303	72.420 / 74.559	0.2058 / 0.2060
	OpenVLA	4.317	76.258 / 76.555	0.1692 / 0.1661
	π_0 base	6.689	81.547 / 82.161	0.1094 / 0.1086
	GR00T N1.6	3.711	69.011 / 68.812	0.2413 / 0.2426
Faucet	SmolVLA	0.0698	0.6867 / 0.6792	0.0097 / 0.0122
	OpenVLA	0.0484	0.6789 / 0.6778	0.0429 / 0.0394
	π_0 base	0.0703	0.6897 / 0.6881	−0.0106 / −0.0011
	GR00T N1.6	0.0468	0.6375 / 0.6392	0.0428 / 0.0435

All 176 candidate–axis summaries (88 fixed candidates, two axes) have $G < 1$ and controlled MAE greater than natural MAE. They share 64 roots. For the eight prespecified representative task–model comparisons, all 32/32 roots have $G < 1$, with Holm-adjusted $p = 1.86265 \times 10^{-9}$ within this separate follow-up family. These tests are not merged with the primary eight-test family.

B.5 LOCAL RESPONSES AND CONTEXT-AXIS EFFECTS

Across 130,560 adjacent-coordinate rows, 38,603 responses are negative and 458 exceed unit response. Repeated rows are not independent units. Context-axis effects are not uniformly monotone and do not support a universal model ranking. Natural-coordinate matching and training-support

restriction are analyzed separately: faucet results remain directionally consistent, whereas drawer support is insufficient (Appendix G.1).

B.6 OUTPUT CALIBRATION AND LOCAL-RESPONSE INTERPRETATION

An additive output correction can improve MAE while leaving G and R unchanged because prediction differences are unchanged. An affine rescaling can move gain toward one while also changing natural MAE and R . These post-hoc corrections do not retrain representations or policies and cannot establish joint improvement. Local gains retain negative and greater-than-one values without clipping.

B.7 ALL-COORDINATE RESPONSE SLOPES

As a post-hoc check of the endpoint summary, we fit an intercept and slope to all six coordinates for every original confirmation scene/context:

$$b_{sp} = \frac{\sum_k (q_{spk} - \bar{q}_{sp})(\hat{q}_{spk} - \bar{\hat{q}}_{sp})}{\sum_k (q_{spk} - \bar{q}_{sp})^2}, \quad B_s = \frac{1}{P} \sum_p b_{sp}. \quad (5)$$

Bars denote means across the six coordinate levels. We equally weight the same 12 scenes and reuse the 20,000 bootstrap draws without changing the primary hypotheses.

Table S8: Endpoint gains and all-coordinate slopes: means [individual 95% intervals].

Task	Model	Endpoint G	All-coordinate B
Drawer	SmolVLA	0.1806 [0.1653, 0.1978]	0.1618 [0.1477, 0.1762]
	OpenVLA	0.1525 [0.1387, 0.1662]	0.1561 [0.1427, 0.1691]
Faucet	SmolVLA	0.0211 [0.0035, 0.0388]	0.0262 [0.0141, 0.0373]
	OpenVLA	0.0512 [0.0292, 0.0717]	0.0550 [0.0394, 0.0702]

Low global linear response is therefore not confined to endpoint gain. Either summary can conceal local non-monotonicity; Figure 2 also reports the coordinate-level curves. No additional bank or independent sample is introduced.

C TRAINING INTERVENTIONS AND CANDIDATE SELECTION

C.1 MATCHED REPLACEMENT OF NATURAL OBSERVATIONS

Matched training uses six scenes and 36 actual target coordinates. Replacing natural with controlled observations reduces mean controlled MAE and E_G , while increasing natural MAE, in all four task–representation combinations. For Drawer–SmolVLA, controlled MAE changes from 52.645 to 26.450 mm and natural MAE from 37.376 to 53.098 mm. Mean R increases in all four combinations, with the scene-level directions shown below.

Training composition changes diagnostic behavior without necessarily improving all properties together.

C.2 COORDINATE–CONTEXT ASSIGNMENT AND COUPLING STRENGTH

We vary which coordinate is paired with which robot context while holding sample count and both marginals fixed. For 36 faucet samples, we compare correlated, reversed, and two balanced assignments, preserving normalization, regularization, counts, and marginal frequencies. All eight

Table S9: Scene-level context-sensitivity changes under matched controlled replacement ($n = 12$ per task).

Task	Model	R increases	R decreases
Drawer	SmolVLA	12	0
	OpenVLA	10	2
Faucet	SmolVLA	11	1
	OpenVLA	9	3

representation–baseline/balanced comparisons improve mean development natural MAE, controlled MAE, and gain error. In one SmolVLA comparison, balanced instead of correlated assignment changes natural MAE from 0.5629 to 0.4693 rad and controlled MAE from 0.3954 to 0.2648 rad.

Individual context-pair stability is not uniformly improved. In the same comparison, the prediction range between context anchors 16 and 20 increases from 0.2118 to 0.2242 rad. Extending coupling to 17 assignments and applying the principle to Drawer produces non-monotone changes. Assignment effects also appear in 24 leave-one-training-scene-out configurations. No tested coupling is consistently best across all diagnostics.

C.3 JOINT NATURAL–CONTROLLED TRAINING

Table S10: Joint-training designs. All fit a single readout to both observation types.

Design	Composition	Purpose
Joint-A	36 matched natural + 36 matched controlled = 72	Combine observations of the same scenes/coordinates
Joint-B	Full natural + 36 controlled; 688 Drawer / 515 Faucet	Retain all original natural training data
Fixed budget	36 total; controlled fractions 1/3, 1/2, 2/3, each with two complementary assignments	Compare mixtures at fixed sample count

Joint-A/B use controlled loss weights 0.25, 0.50, and 0.75, with 0.50 as the central comparison. These are loss weights, not sample fractions. The Joint-B count condition weights every combined row equally, also changing the full-natural trajectory weighting. Representations, training-only normalization, and readout families remain fixed. Verification covers 184 head/conditions including baselines and fixed-budget conditions, with 28 new linear and 84 new MLP heads.

Relative to matched-natural MLP training, the 50:50 Joint-A MLP reduces both MAEs in all four combinations under the original development evaluation. For Drawer–SmolVLA, natural MAE changes from 62.048 to 55.274 mm and controlled MAE from 46.203 to 32.520 mm, while R increases from 26.715 to 49.512 mm. Under coordinate-matched evaluation, only Drawer–SmolVLA retains improvement in both MAEs.

Relative to full-natural training, 50:50 Joint-B generally reduces controlled MAE and E_G while increasing natural MAE and R across linear/MLP and both evaluations. For Drawer–SmolVLA MLP, natural MAE changes from 3.650 to 5.259 mm, controlled MAE from 78.502 to 39.359 mm, and R from 13.176 to 39.217 mm. Other mixture weights and uniform-row training include exceptions where both MAEs improve, such as coordinate-matched Faucet–SmolVLA. Hence the tradeoff is not inevitable. No tested A/B condition improves all four mean metrics simultaneously, within this finite mixture/readout study.

C.4 CANDIDATE SELECTION BY ACCURACY AND JOINT DIAGNOSTICS

Selection rules are fixed on development data and evaluated on new initializations. Natural-accuracy selection retains every candidate within 10^{-8} of the minimum normalized natural MAE. Joint selection retains the Pareto non-dominated set for $(MAE_{nat}/S, E_G, R/S)$, where $S = 0.16$ m for Drawer and 1.4 rad for Faucet.

Development Pareto-set sizes are 9 for each Drawer–SmolVLA/OpenVLA group, 7 for Faucet–OpenVLA, and 4 for Faucet–SmolVLA. They are 3 and 4 for Drawer–GR00T/ π_0 , and 3 for each Faucet–GR00T/ π_0 group. Many candidates remain non-dominated on new initializations, but not every relative advantage persists.

All eight development groups include a minimum-natural-MAE candidate in their Pareto set. Different sets therefore do not establish different unique winners. We examine alternative candidates’ E_G, R advantages and their persistence. Evaluation Pareto sets are descriptive, not used to reselect a winner. Policy success improvement is not evaluated here.

D VISUAL DISCRIMINABILITY AND SUPPLEMENTARY VISUAL CONTROLS

D.1 DIFFERENCES AFTER IMAGE PREPROCESSING

We separately check whether target-state differences survive each model’s actual image preprocessing. Endpoint pairs admitted in raw RGB are processed through the native resizing, cropping, and normalization path, after which target-region spatial differences and endpoint ordering are inspected. Features or predictions are not used to retain observations with a desired response. This audit is distinct from physical validity and readout responsiveness: visual distinguishability does not establish how a representation responds.

D.2 CONTROLLED OBSERVATION EXAMPLES

Figure S2 in Appendix H shows six target-coordinate settings at one fixed robot context for each task. The observations are ordered by their measured simulator coordinate, with coordinate values and units displayed. A fixed 180-degree orientation correction presents the rendered images upright. These examples illustrate the controlled comparison; quantitative physical and visual checks remain those specified in Appendix A and Sections D.1 and D.3.

D.3 TARGET-PIXEL PRESERVATION AND RENDERING CONTROLS

Primary visual admission requires at least 64 visible target pixels and at least four pixels of endpoint centroid displacement. Five renders of each state test reproducibility; all 5,695 repeated RGB comparisons in confirmation are bit-identical. An early MSAA-on one-intensity-level mismatch is retained separately. The final primary pipeline uses MSAA-off consistently for training features and evaluation.

Appearance interventions preserve the target label and physical state while changing robot or background pixels inside specified masks. Pixel-level audits check target preservation and record unintended changes outside masks. These interventions isolate specified appearance factors; they do not hold every aspect of visual context fixed.

D.4 PRIVILEGED REGION POOLING AND VISUAL-FEATURE CONTROLS

Segmentation-based object-region pooling is a privileged control, not the primary method. We compare object ROIs, equal-area control ROIs, and training-fixed ROIs on the same frozen token grid.

Table S11: Representative natural-full region-pooling controls. MAE units are mm for Drawer and rad for Faucet. Blank task/model cells inherit the preceding entry.

Task	Model	Pooling	Natural MAE	Controlled MAE	G
Drawer	SmolVLA	Full mean	7.501	72.656	0.200
		Object ROI	10.038	42.553	0.521
		Equal-area control	6.736	85.426	0.108
	OpenVLA	Full mean	3.606	76.217	0.149
		Object ROI	5.708	41.143	0.514
		Equal-area control	3.586	70.235	0.243
Faucet	SmolVLA	Full mean	0.0964	0.6976	-0.001
		Object ROI	0.1150	0.5291	0.125
		Equal-area control	0.0965	0.6829	-0.005
	OpenVLA	Full mean	0.0623	0.6501	0.035
		Object ROI	0.0568	0.5957	0.057
		Equal-area control	0.0814	0.4900	0.249

Object ROIs substantially improve controlled error and response in some settings, but are not uniformly best across metrics. A separate bounding-box-only privileged coordinate diagnostic has natural-full gain approximately 1.071 for Drawer and 0.921 for Faucet. Explicit geometric location can therefore predict q ; this does not imply that VLA tokens use that information in the same way.

E PHYSICAL-SETTING SCOPE AND FREE-OBJECT ANALYSES

E.1 FREE-OBJECT CONSTRUCTION AND VALIDATION

We use a mug’s world- x position as the scalar target beyond articulated joints. This is a diagnostic of one position component, not the full six-degree-of-freedom pose. An initial 2 cm translation setting supports behavioral rollouts but yields too few roots passing the fixed visual gate. We separately construct a 6 cm setting to obtain measurable visual state changes, retaining the earlier failures. Final world- x , post-translation stability, unintended contact, visibility, and repeated rendering are checked. Joint-specific articulated settling rules are not transferred unchanged.

E.2 MUG STATE-READOUT EVALUATION

Table S12: Free-object results with 6 cm state variation. Both evaluations pass their physical and visual criteria. Natural error is already large.

Evaluation	Roots	Natural MAE (mm)	Controlled MAE (mm)	G
Development	16	121.767	42.293	0.167
New roots	32	128.314	39.765	0.140

Initial natural error in the 16-root evaluation is 32.826 mm. Of 32 new-root natural rollouts, six achieve native success and 26 time out. Natural error exceeds controlled error in 27 roots; five show the reverse. Although endpoint response is small, the central low-natural-error/weak-response pattern does not reproduce because natural error is large. We therefore do not count these results as additional articulated-pattern replications.

E.3 SUPPORT-AWARE FREE-OBJECT AND ADDITIONAL-TASK ANALYSES

Before inspecting predictions, a free-object follow-up defines eligibility by both natural-training support and physical validity. Of 64 new candidate roots, support intervals can be calculated for 53; 159 physical state levels are checked.

Table S13: Free-object follow-up eligibility. No root satisfies both required gates.

Gate	Roots
Physically valid	43
Prespecified support-valid	5
Physical and support-valid	0
Required minimum for response estimation	32

With an empty intersection, no readout forward pass, G , E_G , or bootstrap interval is computed. Support thresholds, translation span, and target coordinate are not relaxed to acquire a sample.

Separate storage/shelf tasks evaluate book orientation and the right book’s relative- y coordinate. Each bank contains 32 initializations with 3×3 crossed observations; all 288 controlled observations lie outside that bank’s prespecified support. Cached predictions permit some descriptive checks, but not a common comparison across every model, so they are not main quantitative results.

A separate book world- x preparation check uses 16 initializations and ten conditions. In one initialization, every condition drifts approximately 1.20–2.15 m after 20 zero-control steps. Passing static construction checks therefore does not guarantee state maintenance. These ten conditions count as one initialization failure. The planned 320 book policy rollouts from this construction were not run. Appendix F.8 reports other natural-rollout explorations.

E.4 BOUNDARY CASES AND NON-ESTIMABLE SUPPORT

A separate 64-root support-screened OOD bank contains 192 groups and 576 observations, all outside the q99 support bound. No root is eligible for primary estimation; no new model forward pass, readout fit, prediction, or gain is produced. The support vector comprises target q , nine robot joints, hand position, and quaternion. We use nearest-neighbor RMS distance after natural-training standardization, with leave-one-training-initialization-out q95 primary and q99 secondary thresholds. Coordinates are the original q and ± 0.05 training IQR, with minimum spacing 0.001. Being outside even q99 also makes the q95 analysis non-estimable.

We distinguish physically invalid observations, physically valid observations outside the prespecified empirical support, and estimable observations satisfying physical, support, and minimum-sample criteria. Non-estimability is not encoded as $G = 0$, a policy failure, or a measured negative response. Appendix G.1 applies the same distinction to articulated tasks.

F POLICY EVALUATION AND SUPPLEMENTARY BEHAVIORAL RESULTS

F.1 POLICY, INPUTS, AND PAIRED EXECUTION

Behavioral experiments use a task-adapted, frozen SmolVLA policy in LIBERO, separately from the Meta-World representation study. The policy receives RGB, robot state, and a language instruction. A diagnostic readout predicts the target coordinate from saved policy representations; its output is not fed back to the policy. We distinguish the diagnostic prediction $\hat{q}$, the policy action command, subsequent physical coordinate q , and native outcome. Simultaneous prediction/action changes do not establish that the policy uses the diagnostic readout internally.

Appearance comparisons share initial physical state and action noise. Physical-context interventions change specified robot joints and are a different design. Comparisons retain root/noise pairing; conditions and action steps are not independent samples.

The drawer task is LIBERO-90’s KITCHEN_SCENE2_open_the_top_drawer_of_the_cabinet_demo, with instruction “open the top drawer of the cabinet.” We freeze a 40,000-step task-adapted SmolVLA checkpoint, SHA256 e67afd358fb364d8fe9255e11beb935531c07f1cd81f175ff09c5c26f6e206ed. It uses 128×128 agentview/wrist RGB, robot state, and language, at 20 Hz with replanning every four actions. The horizon is 300 actions and chunk length 16. Native success requires drawer $q < -0.14$ m. The natural-prefix ridge diagnostic aggregates 32×960 features into 7,680 dimensions.

Controlled snapshots cross $q_0 = 0$, $q_1 = -0.06$ m with first-arm-joint offsets $c_0 = -0.12$, $c_1 = 0$, $c_2 = +0.12$ rad. Velocities are zeroed and controller targets reset. A four-zero-action check requires drawer drift at most 1 mm, after which the intervention state is restored before snapshot acquisition and policy execution. Coordinate error, matched robot state, and restoration error use tolerance 10^{-8} ; other qpos components use 10^{-10} . Initial negative-distance robot–target contacts are absent, and repeated RGB agreement is checked.

F.2 READOUT–ACTION CORRESPONDENCE AND PHYSICAL PROGRESSION

The drawer appearance follow-up has 32 roots, two action-noise realizations, and six conditions (384 branches; 16,090 decisions).

Table S14: Initial changes relative to sham under identical physical state. Translation shifts are normalized command L_2 differences, not distances in physical coordinate units.

Condition	Mean $ \Delta\hat{q} $ (mm)	First translation-command shift
Robot-low	4.482	0.03613
Robot-high	15.506	0.04550

Sham exactly matches original initial predictions/actions and paired successes. Both background conditions have zero initial prediction/action shift; this is not a claim of trajectory-wide invariance. Paired coordinate-progression differences after four and 16 actions are zero for every root. Initial command changes therefore do not establish immediate object-state changes. Commands and physical coordinates have different units and are not directly subtracted.

F.3 ADDITIONAL PREDICTIVE VALUE FOR TASK OUTCOMES

We fit pre-rollout failure predictors on 96 development initializations, freeze coefficients, and evaluate 128 separate initializations. Two normal-noise rollouts per evaluation root yield 175 successes and 81 failures among 256 rollouts. Development has 58 failures among 192 rollouts. The target is failure = 1.

M_0 uses E_0 and the three physical variables; the original augmented model, denoted M_{GR} , adds E_G, R . Columns use population mean/standard deviation over 96 development roots; columns with standard deviation at most 10^{-12} are removed. In practice $D_q = 1$ throughout development and is dropped. Whole-trajectory MAE, contact, termination, and outcome information are not predictor inputs.

We average the two noise losses within root, equally weight roots, and add 0.1/2 times the squared slope norm to logistic loss, leaving the intercept unpenalized. Fitting uses float64, zero initialization, and L-BFGS-B with maxiter 10000, gtol 10^{-10} , ftol 0, and maxls 50. Final gradient infinity norm is at most 10^{-8} .

Table S15: Failure-predictor inputs, all measured before rollout.

Input	Definition	Scaling
E_0	Absolute prediction error at the normal initial observation	Divide by 0.14 m
D_q	Initial coordinate distance to success boundary −0.14 m	Divide by 0.14 m
D_{eef}	Euclidean distance from end effector to cabinet origin	m
D_{robot}	Standardized RMS difference of seven arm joints from policy-training state mean	Policy-training standard deviation; dimensionless
E_G	Mean context-wise endpoint gain error from six controlled snapshots	Dimensionless
R	Prediction range over three contexts, averaged over two coordinates	Divide by 0.14 m

Table S16: Original fixed failure-prediction comparison. Intervals condition on development fitting.

Loss	M_0	M_{GR}	Difference	Individual 95% interval
Brier	0.181515	0.171381	−0.010134	[−0.017898, −0.002478]
Log loss	0.543533	0.519075	−0.024458	[−0.043453, −0.005586]

Evaluation likewise groups both noises within root. We use 20,000 paired bootstrap draws, PCG64 seed 943122, and linear-percentile individual 95% intervals. Brier uses raw probabilities; log loss clips at 10^{-12} and $1 - 10^{-12}$. Intervals reflect new-root sampling variation conditional on the development fits, not separate causal contributions of each diagnostic. Artifact variables named G and C correspond to E_G and $R/(0.14 \text{ m})$, respectively, not signed gain. Appendix F.7 compares controlled MAE from the same snapshots.

F.4 BEHAVIORAL EVALUATION ACROSS MANIPULATION TASKS

Table S17: Post-hoc relationship between whole-trajectory error and success, grouping two normal rollouts per evaluation root.

Successes among two rollouts	Roots	Mean whole-trajectory MAE (mm)
0/2	28	55.075
1/2	25	35.295
2/2	75	6.701

Natural accuracy is associated with success. The post-hoc Pearson correlation between root-level MAE and success fraction is $r = -0.8075$; it is descriptive, not confirmatory. Rankings need not agree: at fixed q_1 , changing c_1 to c_2 reduces whole-trajectory MAE from 38.766 to 30.684 mm but changes success from 106/128 to 52/128. Context also changes interaction geometry and required actions, preventing a causal interpretation in terms of prediction error.

Robot-high minus sham success is −7.8125 percentage points for Drawer, with 95% root-bootstrap interval [−20.3125, 4.6875], and zero for Stove, with interval [−4.6875, 4.6875]. Individual 98.75% intervals for the prespecified four-comparison family are [−23.4375, 7.8125] and [−6.25, 6.25], respectively. Intervals including zero do not establish equivalence or absence of an effect. Stove background interventions are rendered-pixel no-ops and provide no evidence of background robustness.

Table S18: Appearance-intervention successes out of 64 rollouts per task/condition (32 roots, two noises).

Task	Original	Sham	Robot-low	Robot-high	BG-low	BG-high
Drawer	41	41	41	36	42	41
Stove	60	60	61	60	60	60

F.5 STOVE DEVELOPMENT AND SENSITIVITY ANALYSES

Table S19: Initial development-pilot successes out of eight under different robot contexts.

Task	Central	−0.12 rad	+0.12 rad
Drawer	8	3	1
Stove	8	8	8

Matched-natural readouts have mean gains 0.1221 for Drawer and 0.0110 for Stove. Small stove diagnostic response coexists with high policy success. A separate stove extension has 1,216 branches from 16 development roots, with 1,128 successes and 88 timeouts. The same fixed readout has gains −0.012517 over the original 0–0.25 rad interval and −0.002556 over 0.25–0.45 rad. These settings share 16 roots and are not different readouts or 1,216 independent initializations.

F.6 INTERVENTION FOLLOW-UP AND PATH SEPARATION

An early behavioral follow-up uses ten roots and two noises (20 unique normal trials), recording both normal and planned release-intervention branches. Forty branches are produced, but neither release triggers nor actual overrides occur. No paired treatment effect can be estimated; identical normal/release branches do not establish a zero intervention effect.

Normal trials yield 13 successes and seven failures. At the final prediction (step 296), all seven failures have actual opening 0 mm but predicted opening 96.541–125.320 mm. Mean whole-trajectory MAE is 71.968 mm for failures and 6.391 mm for successes. A single pre-action observation at $t = 40$ reverses this ordering: errors are 2.996 and 5.924 mm. The temporal summary therefore matters. Canonical finger contact occurs in 13/20 trials, all successful; restricting analysis to contact-reaching trials structurally excludes all failures.

Across these experiments, readouts diagnose observations and do not modify policy actions. The study evaluates relations among readouts, actions, physical states, and outcomes, rather than the performance of a diagnostic-guided controller.

F.7 SAME-OBSERVATION CONTROLLED-MAE BASELINE

This additional analysis was specified after observing the original evaluation results and does not inherit the original M_0 – M_{GR} comparison’s fixed-protocol status. Controlled MAE averages absolute errors equally over the same six pre-rollout snapshots used for E_G , R , then divides by 0.14 m. M_C adds this value to M_0 ; M_{CGR} additionally includes E_G , R .

Existing M_0 / M_{GR} coefficients are retained. Only M_C / M_{CGR} are fitted on the original 96 development roots, using the same procedure. New coefficients, normalization, code, and development-input hashes are saved before reading the evaluation inputs, without evaluation-based tuning. The overall comparison nevertheless remains post-hoc.

Table S20: All failure-prediction models on 128 evaluation roots.

Model	Added to M_0	Brier	Log loss
M_0	None	0.181515	0.543533
M_C	Controlled MAE	0.175654	0.528602
M_{GR}	E_G, R	0.171381	0.519075
M_{CGR}	Controlled MAE, E_G, R	0.169677	0.514777

Table S21: Paired loss differences [individual 95% intervals], sharing 20,000 root-resampling indices.

Comparison	Brier difference	Log-loss difference
$M_{CGR} - M_C$	-0.005977 [-0.012421, 0.000381]	-0.013824 [-0.030022, 0.002338]
$M_{GR} - M_C$	-0.004273 [-0.010564, 0.001869]	-0.009527 [-0.025286, 0.006211]
$M_C - M_0$	-0.005861 [-0.009132, -0.002744]	-0.014932 [-0.022798, -0.007270]
$M_{GR} - M_0$	-0.010134 [-0.017898, -0.002478]	-0.024458 [-0.043453, -0.005586]

Original scores and intervals are reproduced. We reconstruct E_G, R and MAE from the six snapshots, check new-fit scalar gradients and probabilities, and verify intervals using a resampling-frequency matrix. No simulator rollouts or VLA fitting/inference are added.

Both loss-difference intervals for $M_C - M_0$ lie below zero. The $M_{CGR} - M_C$ and $M_{GR} - M_C$ point estimates are negative, but their intervals include zero for both losses. Controlled summaries thus add information beyond the specified initial baseline; superiority of E_G, R over controlled MAE is not established. Uncertainty about differences is not equivalence. No new p -values or evaluation-based selection are used.

F.8 OTHER TASK AND CONSTRUCTION OUTCOMES

Table S22: Exploratory natural rollouts of fixed pick-and-place policies. Numerical errors with unknown outcomes are not imputed as failures.

Task	Roots	Planned	Success	Timeout	Unknown
Mug to plate	32	64	13	51	0
Book to compartment	32	64	2	57	5
Middle book to shelf	32	64	1	48	15
Right book to shelf	32	64	11	44	9
Descriptive total	128	256	27	200	29

Separate mug behavioral data contain 320 rollouts from 16 roots: 30 successes, 290 timeouts, and no numerical failures. They differ from the 32 new-root state-readout evaluation in Appendix E. Book state-maintenance failures are reported there. These exploratory/construction samples are not pooled with the 128-root failure evaluation or primary confirmation.

G ADDITIONAL SUPPORT, INTERVENTION, AND BASELINE ANALYSES

G.1 COORDINATE SUPPORT AND ESTIMABILITY

Physical validity and empirical support are recorded separately on the new initialization bank. The main six-coordinate/context grid is constructible for all 32 roots per task; matched-coordinate and support-restricted subsets differ.

Table S23: Eligible roots for each analysis, per context axis.

Subset	Drawer	Faucet
Main controlled grid	32/32	32/32
Natural- q -matched grid	0/32	18/32
Target- q -support-restricted main grid	0/32	32/32
Support-restricted natural-matched grid	0/32	0/32

Mean $G < 1$ and positive controlled-minus-natural MAE persist across fixed candidates in the separate 18-root matched and 32-root support-restricted faucet analyses. Support restriction leaves no eligible natural-matched grids.

This support check concerns the training range/density of target q , not the joint image-robot distribution. Training coordinates are divided into 20 bins, requiring at least eight observations from three training initializations. Drawer has only two supported grid coordinates, below the prespecified minimum of three distinct values. Non-estimable gains are not recorded as zero.

G.2 STATE-CONTEXT APPEARANCE INTERVENTIONS

Robot/background pixels are changed inside fixed masks while target pixels are preserved. The resulting endpoint gains are shown below.

Table S24: Appearance effects on endpoint gain under a common mask.

Task	Model	Sham G	Robot-high G
Drawer	SmolVLA	0.2124	0.1730
	OpenVLA	0.1608	0.1126
	π_0	0.0992	-0.1009
	GR00T	0.2388	0.2326
Faucet	SmolVLA	0.0135	0.0042
	OpenVLA	0.0345	-0.0084
	π_0	-0.0010	-0.0837
	GR00T	0.0474	0.0612

Robot appearance often reduces response, with exceptions such as GR00T-Faucet. For Drawer robot-high, mean absolute natural-prediction shifts are 11.257 mm for SmolVLA, 14.694 mm for OpenVLA, 13.878 mm for π_0 , and 16.555 mm for GR00T. These quantify sensitivity to specified appearance interventions, not a causal decomposition of every visual-context effect.

G.3 NATURAL-ONLY MATCHED-COORDINATE ANALYSIS

We post-hoc match frames within natural trajectories at nearly equal actual coordinates and measure prediction differences. No new rendering intervention is introduced. Pairs share eight development roots per task and do not increase independent sample size.

Each non-VLA model uses 9,649 drawer pairs and 2,886 faucet pairs. For DINOv3, pair-weighted mean actual-coordinate differences are 0.105 mm and 2.91×10^{-5} rad, whereas equally root-weighted mean prediction differences are 6.390 mm and 0.0757 rad. Their aggregation units differ; these means are not paired effect estimates. In the VLA analysis, SmolVLA scene-mean absolute prediction differences are approximately 5.05 mm and 0.0769 rad. Prediction variation is therefore not confined to artificially constructed images. These observational matches do not jointly hold contact, occlusion, progress, and robot configuration fixed, and do not estimate a specific context factor’s causal effect.

G.4 NON-TARGET CONTEXTUAL BASELINES

Simple time/robot-state baselines test the predictive structure of non-target variables in natural trajectories. Each task uses 24 training, eight development, and 32 evaluation roots; 12 heads produce 10,563 predictions. Combined time/configuration baselines obtain whole-trajectory MAE 1.494 mm for Drawer and 0.0488 rad for Faucet. Thus, progress and robot variables can strongly predict the coordinate in natural data. This does not establish that VLA features use those exact scalar variables.

G.5 NON-VLA FROZEN-VISION CONTROLS

SigLIP2, VC-1, R3M, and DINOv3 use frozen visual encoders with natural-only task-specific ridge readouts. No encoder update or policy rollout is performed. The common bank has 32 roots per task. Here natural MAE uses three selected snapshots per root, rather than whole trajectories.

Table S25: Native-context gains for non-VLA controls on the common evaluation bank.

Encoder	Drawer G	Faucet G
SigLIP2	0.3357	0.0794
VC-1	0.1979	0.0503
R3M	0.3445	0.1391
DINOv3	0.1837	0.1611

Table S26: DINOv3 native-context metrics. MAE/ R are mm for Drawer and rad for Faucet.

Task	Natural MAE	Controlled MAE	G	E_G	R
Drawer	3.947	77.460	0.1837	0.8163	7.158
Faucet	0.0414	0.5532	0.1611	0.8389	0.0937

DINOv3 uses the same image inventory and training-only protocol as the other encoders. Native and appearance predictions from the accepted run are stored and independently replayed.

Table S27: DINOv3 appearance-condition metrics, with mm for Drawer MAE/ R and rad for Faucet MAE/ R .

Task	Appearance	Natural MAE	Controlled MAE	G	R
Drawer	Original/sham	3.947	77.460	0.1837	7.158
	Robot-low	12.127	69.297	0.2036	10.336
	Robot-high	17.906	55.802	0.2587	14.443
	Background-low	6.396	79.937	0.1957	8.143
	Background-high	8.431	80.598	0.2106	6.352
Faucet	Original/sham	0.0414	0.5532	0.1611	0.0937
	Robot-low	0.0720	0.4730	0.1595	0.0909
	Robot-high	0.0868	0.5203	0.1764	0.0994
	Background-low	0.0582	0.5747	0.1393	0.0831
	Background-high	0.1352	0.6319	0.1325	0.0756

Appearance changes can improve controlled MAE or gain while worsening natural MAE or R . The evidence does not identify a common causal mechanism across all models. The natural-accuracy/controlled-response separation is not uniquely specific to VLA policy architectures. These controls compare diagnostic behavior, not policy performance or a model-quality ranking.

G.6 CROSS-MODEL AND CROSS-TASK COVERAGE

Representation/readout factorials, additional VLAs, non-VLA encoders, and appearance interventions share or partially overlap roots and image banks. Candidate, fitted-head, and prediction counts are not counts of independent replications. The 64-root VLA bank contains 88 fixed candidates, 136 fitted heads, and 250,172 checked predictions. The first three non-VLA families each use 9,955 image-feature rows and two natural-only task heads; DINOv3 uses the same inventory and split. These counts indicate numerical coverage without increasing independent roots.

Tokenization, visual grids, language access, feature dimension, and preprocessing differ across models. Their metric differences cannot isolate a single architectural component. Model extensions test dependence on one model/path rather than rank architectures.

G.7 READOUT-POLICY PATH SEPARATION

In Figure 1 and Appendix F, diagnostic predictions do not return to the policy. Readout/action changes and diagnosis/success associations are analyzed together without assuming the policy internally uses the fitted readout. The additional outcome comparison retains this separation.

G.8 ALTERNATIVE EXPLANATIONS AND OOD SCOPE

Table S28: Alternative explanations and the scope of the available controls.

Explanation	Available evidence	Remaining question
Physical/rendering errors	Actual coordinate, robot, visibility, repeated-render and target-pixel checks	Does not establish natural joint-distribution membership
Different target-coordinate ranges	Actual-coordinate matching and separate faucet state-value matching	Does not match the entire context distribution
Variation confined to artificial images	Prediction differences in natural-only near-equal- q pairs	Observational matching does not isolate a causal context factor
One VLA or readout fails	Multiple VLAs, feature paths, pooling, nonlinear readouts, non-VLA controls	Models may share sensitivity to distribution shift
Novel state-context combinations are jointly OOD	Limited support-aware follow-ups	Joint-distribution OOD remains possible

A separate faucet state-value-matched follow-up uses a post-hoc restricted set of four initializations. After matching actual q , four VLA models have mean gains approximately 0.016–0.070 and controlled-minus-matched-natural MAE approximately 0.470–0.514 rad. This weakens a coordinate-mismatch-only explanation but is not in-distribution confirmation of the full joint state-context distribution.

The controls make target-coordinate range, simple image-construction errors, a single readout, or a single VLA insufficient as complete explanations. Generalization failure on state-context combinations outside the natural joint distribution remains possible. We therefore interpret the findings as a diagnostic separation between natural accuracy and responsiveness under validated interventions, rather than as identification of an OOD-independent mechanism.

H CONTROLLED OBSERVATION EXAMPLES

Figure S2 shows target-coordinate variation at a fixed robot context in one development scene per task. The selected groups are the first available scene and robot-context frame in numeric order for each task. Columns are ordered by the measured native joint coordinate. The supplementary package provides the 12 source images, full-precision coordinates, and their image hashes.




Figure S2: Controlled observations at fixed robot contexts. Each row contains six coordinate settings from one development scene: Drawer seed 108300, robot-context frame 6; Faucet seed 110300, robot-context frame 12. Coordinates increase from left to right, follow the simulator’s native sign convention, and are rounded for display. A fixed 180° orientation correction presents the rendered images upright. These are illustrative examples; quantitative validation is reported in Appendices A and D.