

Poster: A Preliminary Study of LLM Distillation Inference

Edward Chen
edward200907@gmail.com
Carmel High School
Carmel, Indiana, USA

Yuntao Du*
ytdu@purdue.edu
Purdue University
West Lafayette, Indiana, USA

Abstract

Unauthorized model distillation, in which a model is trained on the outputs of a proprietary large language model (LLM), is a growing threat to model providers. We study *distillation inference*: determining whether a suspect model was distilled from another model or trained independently. We formulate this problem as a hypothesis test and estimate the behavior expected under each hypothesis by training *shadow models*: distilled shadow models learn from the teacher's reasoning traces, whereas independent shadow models learn only from reference answers. The auditor measures how closely each model predicts the teacher's reasoning outputs and then uses the shadow models to convert the suspect's score into a calibrated p -value. In a preliminary study using Qwen2.5-7B as the teacher and Llama-3.2-3B for the suspects, our test achieves a true positive rate of 1.0 at a significance level of 0.02. These results demonstrate the feasibility of using distillation inference to detect distillation attacks.

CCS Concepts

• Security and privacy;

Keywords

distillation inference; knowledge distillation; large language models

ACM Reference Format:

Edward Chen and Yuntao Du. 2026. Poster: A Preliminary Study of LLM Distillation Inference. In *Proceedings of the 2026 ACM SIGSAC Conference on Computer and Communications Security (CCS '26)*, November 15–19, 2026, The Hague, Netherlands. ACM, New York, NY, USA, 3 pages. <https://doi.org/10.1145/3830454.3846416>

1 Introduction

As large language models (LLMs) grow in capability and commercial value, their providers face a growing threat from *unauthorized distillation attacks*, in which an adversary trains its own model on a proprietary model's outputs to copy its capabilities. In February 2026, Google [3] and Anthropic [1] both reported a sharp rise in such attacks, which raise legal, intellectual property, and national security concerns [8]. These reports highlight the urgent need to determine whether a suspect model was distilled from a specific teacher, a task we call *distillation inference*.

*Corresponding author.



This work is licensed under a Creative Commons Attribution 4.0 International License. CCS '26, The Hague, Netherlands

© 2026 Copyright held by the owner/author(s).

ACM ISBN 979-8-4007-2871-6/2026/11
<https://doi.org/10.1145/3830454.3846416>

Research on distillation inference has grown rapidly over the past year [6, 9, 11]. Existing methods measure the suspect's behavioral similarity to the teacher and report a score or ranking over a candidate pool. They cannot provide what enforcement requires: a statistical guarantee for a specific teacher–suspect pair, *i.e.*, a decision with a p -value and a bounded false positive rate (FPR).

To address this, we frame distillation inference as a hypothesis test: is the suspect's behavior closer to a model distilled from the teacher, or to a model trained independently? Since these two behavioral distributions cannot be observed directly, we approximate them with *shadow models* [2, 10]: *distilled shadow models* fine-tuned on the teacher's chain-of-thought (CoT) and *independent shadow models* fine-tuned on reference answers. We then score every model with three signals of how well it predicts the teacher's CoT token by token. We found that per-instance signals are too weak for reliable distillation auditing; we instead *aggregate* the evidence across the entire audit set into a single per-model likelihood-ratio statistic that yields a calibrated p -value and a controlled FPR.

We evaluate our method with Qwen2.5-7B-Instruct as the teacher and Llama-3.2-3B as the base model for the suspects and shadows. At a significance level of $\alpha = 0.02$, the test detects every distilled suspect and never flags an independently trained model.

2 Problem Setup

The *teacher* T is a known, typically proprietary model. The *suspect* f_{sus} is a published model whose provenance is in question: it was produced either by *distilling* from T or by *independent* training without access to T . The *auditor* distinguishes between these possibilities using an *audit set* $D_{\text{audit}} = \{(x_i, y_i)\}_{i=1}^N$ of N questions x_i with answers y_i . Querying T with x_i yields the teacher's CoT t_i .

Distillation Inference Protocol. The audit proceeds as follows:

- (1) The teacher's owner trains T and deploys it with query access.
- (2) The suspect's owner curates D_{train} , produces f_{sus} by distilling from T on this dataset or by training it independently.
- (3) The teacher's owner submits D_{audit} to the auditor.
- (4) The auditor runs its algorithm on D_{audit} using access to T and f_{sus} , outputting a decision $\hat{y} \in \{0, 1\}$ ($\hat{y} = 1$ means evidence of distillation) with a calibrated p -value.

Audit Setting. We consider a setting in which the teacher's owner holds logs of queries submitted by the suspect's owner and uses them as the audit set, *i.e.*, $D_{\text{audit}} \subseteq D_{\text{train}}$. This arises when the API logs containing the distillation queries can be identified [1, 3].

Access Levels. The auditor has query access to the teacher to collect t_i . For the suspect, we assume either *grey-box* access (*i.e.*, next-token probabilities, available for any open-weight release or log-probability API) or *black-box* access (*i.e.*, generated text only).

3 Methods

Overview. Our method instantiates the audit as a binary hypothesis test: is f_{sus} 's behavior on D_{audit} more consistent with a model distilled from T (the alternative hypothesis H_1) or with one trained independently (the null hypothesis H_0)? Since the two distributions are unknown, we estimate them in three stages: fine-tune distilled shadows and independent shadows models (Stage 1); score every model with three signals of how closely it tracks the teacher's CoT (Stage 2); aggregate the per-instance signal into a likelihood-ratio test calibrated by the shadows, returning a p -value and a verdict at a controlled FPR (Stage 3).

Stage 1: Training Shadow Models. The auditor fine-tunes M shadow models from each class [2]. These models share the same base model, audit set, and training procedure and differ *only* in their supervision targets. A distilled shadow f_m^{dist} is fine-tuned with Low-Rank Adaptation (LoRA) [4] to reproduce the teacher's CoT t_i for each x_i . In contrast, an independent shadow f_m^{ind} is fine-tuned on the reference answer y_i without access to T , representing a model trained without distillation. Each model is trained using the randomly sampled half of the D_{audit} . Thus, every pair of distilled and independent shadows differs only in its training target (*i.e.*, t_i or y_i). This design controls for confounding factors because knowledge shared by both classes cancels out in shadow models.

Stage 2: Extracting Distillation Signals. Every shadow model f is scored in a *single teacher forward pass* over the teacher's CoT: for instance i with CoT tokens $t_{i,1:L_i}$, the pass yields the next-token distribution $p_{i,\ell}^f = f(\cdot \mid x_i, t_{i,1:L_i})$ at every position ℓ . Averaging over the L_i positions, we extract three signals presenting how closely f tracks the teacher.

- **Log-probability (grey-box).** It measures the mean log-likelihood of the teacher's tokens under f : $g_{\text{lp}}(f, i) = \frac{1}{L_i} \sum_{\ell} \log p_{i,\ell}^f(t_{i,\ell})$. A distilled model was trained to reproduce this text, so it scores the text higher than an independent model that learned a different but equally valid solution.
- **Predictive entropy (grey-box).** We compute the mean entropy as $g_{\text{ent}}(f, i) = \frac{1}{L_i} \sum_{\ell} \mathbb{H}(p_{i,\ell}^f)$ to measure the certainty of model about the outputs.
- **Token agreement (black-box).** We compute the fraction of positions at which f 's greedy token $\hat{t}_{i,\ell}^f = \arg \max_v p_{i,\ell}^f(v)$ matches the teacher's token as $g_{\text{ta}}(f, i) = \frac{1}{L_i} \sum_{\ell} \mathbb{1}[\hat{t}_{i,\ell}^f = t_{i,\ell}]$. This signal directly measures whether f would emit the teacher's tokens when decoding on its own.

Stage 3: Performing Distillation Inference. Our test adapts the per-example construction of the Likelihood Ratio Attack (LiRA) [2]. It has two levels: a *per-instance* score and a *model-level* statistic, both calibrated using the shadows.

Per-instance distributions and the calibrated score. For instance i , the values from the distilled shadows, $\{g(f_m^{\text{dist}}, i)\}_m$, and the independent shadows, $\{g(f_m^{\text{ind}}, i)\}_m$, characterize how the signal behaves under the two hypotheses. We summarize the two distributions with Gaussians $\mathcal{N}(\mu_{\text{dist},i}, \sigma_{\text{dist},i}^2)$ and $\mathcal{N}(\mu_{\text{ind},i}, \sigma_{\text{ind},i}^2)$, whose parameters are the means and unbiased variances over the M shadows. The evidence provided by model f for instance i is the log-likelihood




Figure 1: Per instance (left), the log-probability signal overlaps across the two classes, so membership inference cannot separate them (AUC 0.67). Aggregated to one statistic Λ per model (right), the distilled (H_1) and independent (H_0) populations are fully separated, so our methods can faithfully detect distillation.

ratio (LLR) of its value under the two distributions:

$$\lambda_i(f) = \log \frac{p(g(f, i) \mid \mathcal{N}(\mu_{\text{dist},i}, \sigma_{\text{dist},i}^2))}{p(g(f, i) \mid \mathcal{N}(\mu_{\text{ind},i}, \sigma_{\text{ind},i}^2))}. \quad (1)$$

The *calibration* matters because $g(f, i)$ alone conflates specificity to the teacher with per-instance difficulty (every model scores high on an easy instance), whereas λ_i measures f *relative* to both classes on that instance.

Model-level statistic and its null/alternative. Summing over the audit set gives the statistic $\Lambda(f) = \sum_{i=1}^N \lambda_i(f)$, the most powerful test at any fixed FPR under this Gaussian model [7]. Its distribution under each hypothesis is estimated from the shadows using a leave-one-out procedure. Each shadow is scored against Gaussians fitted to the *other* shadows in its class, yielding one draw from H_1 (distilled) or H_0 (independent). Thus, no model is evaluated against a distribution that it helped define. The suspect, which is trained separately from the shadows, is scored against Gaussians fitted to all shadows.

Audit Decision. The p -value ranks $\Lambda(f_{\text{sus}})$ against the scores of the independent shadows,

$$p = \frac{1 + \#\{m : \Lambda(f_m^{\text{ind}}) \geq \Lambda(f_{\text{sus}})\}}{M + 1}, \quad (2)$$

i.e., the estimated frequency with which an independent model matches the teacher at least as closely as the suspect does. The decision is $\hat{y}(f_{\text{sus}}) = \mathbb{1}[p < \alpha]$. We estimate the FPR by testing each independent shadow against a threshold fitted without that shadow, so the estimate changes in increments of $1/M$. Both quantities become more precise as M increases.

4 Preliminary Evaluation

Experimental Setup. The teacher T is Qwen2.5-7B-Instruct, and the base model for the suspect and all shadows is Llama-3.2-3B. The audit set D_{audit} contains $N = 500$ instances from CoT-Collection [5], and we train $M = 50$ shadows per class. All models are fine-tuned with LoRA (rank 8, scaling factor 16, and dropout 0.05 on the attention projections) for three epochs. We retain the checkpoint with the lowest loss on the held-out half and build all prompts with a shared formatter to rule out formatting confounds. Suspects are

Table 1: Membership inference on individual instances barely separates distilled from independent models, whereas aggregating the same signal across the audit set (dataset inference, our method) separates the model populations perfectly. bal-acc = balanced accuracy.

Signal		AUC	bal-acc	TPR@5%FPR	TPR@0%FPR
log-prob	per-instance (MIA)	0.672	0.518	0.086	0.000
	per-model (ours)	1.000	1.000	1.000	1.000
entropy	per-instance (MIA)	0.672	0.524	0.098	0.000
	per-model (ours)	1.000	1.000	1.000	1.000
token agreement	per-instance (MIA)	0.635	0.512	0.073	0.003
	per-model (ours)	1.000	1.000	1.000	1.000

trained separately from the shadows using the same procedure: distilled suspects learn from the teacher’s CoT, whereas independent suspects learn from reference answers. We train these models to achieve similar utility as their base model by evaluating them on a separate held-out dataset.

Baselines and Evaluation. We contrast two ways of turning the per-instance signals of Section 3 into a verdict. The *membership-inference* baseline [10] treats each instance in isolation: it thresholds a single instance’s signal to decide whether that model is distilled. We report audit performance with AUC, balanced accuracy, and TPR at 0% and 5% FPR.

Results. (i) *Membership inference does not detect distillation.* On individual instances the signals barely separate the classes (AUC 0.64–0.67), and they are useless in the low-FPR regime that enforcement requires: TPR at 0% FPR is essentially zero (≤ 0.003) and stays below 0.10 even at 5% FPR (Table 1, “per-instance”; Figure 1, left). (ii) *Our method separates the model populations perfectly.* Aggregating the same signals across D_{audit} lifts every metric to 1.000 (Table 1, “per-model”; Figure 1, right): the $M = 50$ distilled and independent populations do not overlap, so the audit flags every distilled suspect (TPR 1.0) and clears every independent one. (iii) *Shadow calibration certifies the decision.* A raw aggregate score separates the populations but cannot bound the false-positive rate. Calibrating Λ against the shadow populations turns it into a hypothesis test with a certified operating point: at $M = 50$ the p -value reaches its floor $1/(M+1) = 0.020$ and the leave-one-out FPR is $\approx 1/M = 0.020$, both shrinking monotonically with M while detection stays perfect (Table 2).

Impact of Model Architecture. The main experiment uses a Qwen teacher and a Llama suspect. We find that a same-family pair (Qwen→Qwen), which shares a tokenizer and output format, produces *larger* separation between the two distributions. This result rules out model-formatting differences between families (e.g., whitespace patterns in generation) as confounding factors.

Mitigation. We also evaluate an evasion strategy in which the suspect’s owner trains the suspect on a *paraphrased* teacher CoT. We find the inference statistic decreases from original CoT to teacher-generated paraphrase, and decreases again for Mistral-generated paraphrase. All suspects remain flagged at $\alpha = 0.05$ (these ablation pools use $M = 20$, where the p -floor is $1/(M+1) \approx 0.05$), although

Table 2: More shadow models tighten the certified operating point: the p -value floor $1/(M+1)$ and the FPR ($\approx 1/M$) both shrink with M , while per-model detection stays perfect (AUC = 1.000 throughout).

M	p -floor	FPR
5	0.167	0.200
10	0.091	0.100
20	0.048	0.050
40	0.024	0.025
50	0.020	0.020

the paraphrase-trained suspects enter the gap between the populations. Replacing the distilled shadows with a matching population trained on paraphrased text restores a clean audit, as expected.

5 Conclusion and Limitations

In this paper, we frame distillation inference as a hypothesis test and propose a likelihood-ratio test calibrated with shadow models. In a preliminary study, our method detects every distilled suspect model without any false positives, providing a statistical bound on FPR for enforcement. Our study has three limitations. First, it requires fine-tuning a pool of shadow models, which may be expensive in practice given the size of frontier LLMs. Second, it assumes that the audit set is a subset of the suspect’s training data, which may be hard to establish in practice. Third, it assumes that the suspect is trained with the same procedure as the shadow models. Relaxing the last two assumptions is an important direction for future work.

References

- [1] Anthropic. 2026. Detecting and Preventing Distillation Attacks. Anthropic News.
- [2] Nicholas Carlini, Steve Chien, Milad Nasr, Shuang Song, Andreas Terzis, and Florian Tramèr. 2022. Membership Inference Attacks From First Principles. In *IEEE Symposium on Security and Privacy (S&P)*. 1897–1914.
- [3] Google Threat Intelligence Group. 2026. GTIG AI Threat Tracker: Distillation, Experimentation, and (Continued) Integration of AI for Adversarial Use. Google Cloud Blog.
- [4] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-Rank Adaptation of Large Language Models. In *International Conference on Learning Representations (ICLR)*.
- [5] Seungone Kim, Se June Joo, Doyoung Kim, Joel Jang, Seonghyeon Ye, Jamin Shin, and Minjoon Seo. 2023. The CoT Collection: Improving Zero-shot and Few-shot Learning of Language Models via Chain-of-Thought Fine-Tuning. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*. Association for Computational Linguistics, 12685–12708.
- [6] Sunbowen Lee, Juntong Zhou, Chang Ao, Kaige Li, Xeron Du, Sirui He, Haihong Wu, Tianci Liu, Jiaheng Liu, Hamid Alinejad-Rokny, Min Yang, Yitao Liang, Zhoufutu Wen, and Shiwen Ni. 2025. Quantification of Large Language Model Distillation. In *Annual Meeting of the Association for Computational Linguistics (ACL)*. 4985–5004.
- [7] Jerzy Neyman and Egon Sharpe Pearson. 1933. On the Problem of the Most Efficient Tests of Statistical Hypotheses. *Philosophical Transactions of the Royal Society of London. Series A* 231 (1933), 289–337.
- [8] Shristi Sharma. 2025. Intellectual Property Rights in the Era of AI Model Distillation. *Journal of Legal Research and Juridical Sciences* 4, 4 (2025), 899–912.
- [9] Qin Shi, Amber Yijia Zheng, Qifan Song, and Raymond A. Yeh. 2025. Knowledge Distillation Detection for Open-weights Models. In *Advances in Neural Information Processing Systems (NeurIPS)*.
- [10] Reza Shokri, Marco Stronati, Congzheng Song, and Vitaly Shmatikov. 2017. Membership Inference Attacks Against Machine Learning Models. In *IEEE Symposium on Security and Privacy (S&P)*. 3–18.
- [11] Somn Wadhwa, Chantal Shaib, Silvio Amir, and Byron C. Wallace. 2025. Who Taught You That? Tracing Teachers in Model Distillation. In *Findings of the Association for Computational Linguistics (ACL Findings)*. 3307–3315.