

QC-Stark: A Multi-Task Benchmark Revealing Capability Dissociations in LLMs Evaluated on Quantum Computing Tasks

Pranav Gupta¹[0000-0002-1412-0885]

Cisco, 2901 3rd Ave, Suite 600, Seattle, WA 98121, USA
pranavpg@cisco.com

Abstract. We introduce QC-Stark, a benchmark for evaluating large language models (LLMs) on 11 quantum computing (QC) tasks, spanning circuit construction, debugging, compilation, error correction, and simulation. Across 2,750 evaluations (10 models $\times$ 11 tasks $\times$ 5 difficulty levels $\times$ 5 seeds), we find that overall rankings mask substantial per-task variation. The Spearman correlation ρ between overall and per-task rankings is statistically insignificant for 4 out of the 11 tasks included in this benchmark. A 2-parameter Item Response Theory (IRT) model validates measurement quality, and prompt sensitivity analysis confirms ranking robustness across prompt conditions. All tasks are auto-verifiable via execution, thus not requiring any manual evaluation. We make the code and data publicly available on Huggingface.

Keywords: Large Language Models (LLMs) · Quantum Computing · Item Response Theory.

1 Introduction

While large language models (LLMs) are being increasingly applied to quantum computing (QC) tasks [1], existing evaluations still focus on specific aspects, such as algorithm implementation [2], challenge-style programming [3], or conceptual question-answering [4]. There is a lack of benchmarks that span the complete spectrum of a quantum computing practitioner’s day-to-day operations, ranging from circuit construction through compilation, debugging, error correction, and simulation.

This gap is important because LLM capabilities cannot be expected to generalize across tasks, given the diversity in their architecture, algorithms and training/evaluation data. A model that excels at oracle synthesis might score close to zero on hardware routing. In some cases, a model ranked first overall may score 0% on a challenging task. An ideal benchmark should ideally also include features such as run-time procedural generation, in order to avoid dataset contamination or leakage.

QC-Stark addresses these concerns by providing (1) 11 tasks covering the full QC workflow, (2) 5 difficulty levels per task, (3) seed-based procedural generation to resist against data contamination, and (4) automatic verification via code execution.

2 Related Work

QC-Stark complements existing quantum computing benchmarks. Quantum-Audit [4] evaluates conceptual knowledge via multiple-choice questions (best performance: 84%), Qiskit QuantumKatas [2] tests 350 educational exercises (best performance: 83%), QCoder [3] evaluates on contest problems with simulator feedback (best performance: 78%), whereas QCircuitBench [5] provides large-scale algorithm design data. QC-Stark spans the full operational spectrum with systematic difficulty scaling in terms of 5 separate levels.

Outside quantum computing, scientific coding benchmarks like SciCode [6] (best performance: 4.6%) and CMT-Benchmark [7] (best performance: 30%) find frontier models far from research-level capability, thus implying the need for continuously developing new benchmarks which are fundamentally distinct from existing ones.

3 Benchmark Design

Tasks. QC-Stark consists of 11 tasks organized by stages in a QC practitioner’s workflow: Circuit Construction (State Preparation, Trotter Decomposition, Oracle Synthesis), Code Understanding (Debugging, Noise Discrimination, Reverse Engineering), Verification (Equivalence Checking), Compilation (Hardware Routing), Simulation (Noise Fidelity Estimation, Variational Quantum Eigensolver (VQE)), and Error Correction (Syndrome Decoding). Appendix D provides full descriptions for each task.

Difficulty scaling. Each task has 5 levels: L1 (TEXTBOOK), L2 (HOMEWORK), L3 (EXAM), L4 (RESEARCH), L5 (OPEN), controlled via problem size, constraint complexity, and domain-specific parameters. Appendix B provides example prompt templates.

Evaluation. Each instance is deterministically generated from a (`task`, `level`, `seed`) tuple. Models receive a system prompt with Qiskit 2.x [10] API guidance and are asked to output a `solve()` function, which is run by a verifier to check for correctness. The output is matched against ground truth, in terms of aspects such as state fidelity, functional equivalence and correct identification. By principle, we do not require any human judgment.

Models. We evaluated 10 models: o4-mini, Claude Sonnet 5, GPT-5.4, Gemma-4 31B, Claude Opus 4.1, GPT-4.1-mini, Gemini Flash Lite (Gemini FL), Gemini 3.5 Flash, Mistral Large 3, and LLaMA-3.3 70B. These models were chosen based on our availability constraints and a goal of encompassing various model parameter sizes in our study. Note that we used Claude Code (Opus 4.6 and higher) for designing the benchmark, hence there could be some bias towards Claude models. In the future, this can be remediated by the use of a council of LLMs collectively designing the benchmark or by excluding those model families from the evaluation. We chose to keep Anthropic/Claude models for the sake of completion.

Table 1. Mean accuracy per model and task (all models at maximum supported token budgets). **Bold:** best per task. Gray: worst. Last column: overall mean score $\pm$ standard deviation across seeds. Task codes: T1=State Preparation, T2=Trotter Decomposition, T3=Oracle Synthesis, T4=Debugging, T5=Noise Discrimination, T6=Reverse Engineering, T7=Equivalence, T8=Routing, T9=Noise Fidelity, T10=VQE, T11=Quantum Error Correction

Model	T1	T2	T3	T4	T5	T6	T7	T8	T9	T10	T11	Overall
Sonnet 5	.68	.24	1.00	.60	.64	.64	1.00	.20	1.00	.60	.68	.662$\pm$.047
Gemini 3.5F	.92	.00	.96	.48	.60	.76	.84	.20	1.00	.80	.60	.651 $\pm$.059
o4-mini	.52	.64	.84	.00	.56	.68	.88	.32	1.00	.40	.68	.593 $\pm$.060
GPT-5.4	.40	.36	.44	.20	.60	.68	.84	.04	.80	.88	.64	.535 $\pm$.083
Gemma-4	.40	.52	.52	.00	.52	.48	.76	.28	.72	.56	.64	.491 $\pm$.088
GPT-4.1 mini	.40	.20	.24	.00	.16	.48	.80	.20	.84	.40	.60	.393 $\pm$.034
Opus 4.1	.40	.24	.48	.00	.00	.32	.88	.16	.76	.56	.40	.382 $\pm$.041
Gemini FL	.44	.04	.36	.00	.32	.40	1.00	.44	.48	.48	.08	.367 $\pm$.067
Mistral L3	.40	.00	.16	.00	.00	.56	.80	.12	.04	.40	.40	.262 $\pm$.015
LLaMA-70B	.40	.00	.00	.04	.00	.04	.00	.12	.00	.36	.36	.120 $\pm$.009
Task mean	.50	.22	.50	.13	.34	.50	.78	.21	.66	.54	.51	.445

4 Results

4.1 Overall Performance and Rank Inversions

Table 1 presents the scores from 2,750 evaluations (10 models $\times$ 11 tasks $\times$ 5 seeds $\times$ 5 difficulty levels). The best model (Claude Sonnet 5) achieves 0.662 overall, but its performance drops 59% as we increase the difficulty level from L1 to L5. Task difficulty varies $5.9\times$ (Equivalence: 0.78 vs. Debugging: 0.13).

The overall ranking is *not predictive* of per-task performance on 4 out of 11 tasks, where Spearman ρ between the overall and individual task rankings is statistically non-significant. These 4 tasks were Routing ($\rho = +0.27$, $p = 0.45$), Trotterization ($\rho = +0.49$, $p = 0.15$), Debugging ($\rho = +0.54$, $p = 0.11$), and Equivalence ($\rho = +0.45$, $p = 0.19$). These inversions demonstrate that a single aggregate score is insufficient in guiding model selection for quantum computing tasks, and there is still progress to made for creating LLMs that outperform their predecessors on all kinds of benchmarks.

4.2 The “Debugging” Conundrum

Despite all models being run at their maximum supported token budgets, 6 of 10 models score 0.00 on debugging. Claude Sonnet 5 leads at 60% (15/25), followed by Gemini 3.5 Flash at 48% (12/25 correct), GPT-5.4 at 20% (5/25 correct), and LLaMA-70B at 4% (1/25 correct). Dedicated reasoning models (o4-mini) score 0% even at token budgets of 65,536 tokens.

4.3 Routing: A Universal Bottleneck

Hardware routing (T8) has a mean accuracy of 0.21 across all models, with Gemini Flash Lite leading at a mean accuracy of 0.44 (driven by strong L1/L2 performance but weaker performance in more difficult problems in L3 and beyond). The Spearman correlation between overall and routing rankings is non-significant ($\rho = +0.27$, $p = 0.45$): the 8th-ranked model leads, while 4th-ranked GPT-5.4 scores merely 0.04 (1 is the maximum score in all these evaluations). Many evaluations produce circuits not functionally equivalent to input. This shows that models find it difficult to maintain circuit semantics while inserting SWAP gates for hardware connectivity.

4.4 Measurement Validation

IRT analysis. Our Item Response Theory (IRT) analysis follows ATLAS [8]. Equally weighted averages over all tasks to determine the final rankings can thus be misleading. A 2-parameter logistic (2PL) IRT model [12] fitted via Joint Maximum Likelihood Estimation (JMLE) yields marginal reliability = 0.985, with ability estimates spanning 3.6 standard units (Table 2). Of 275 items (11 tasks $\times$ 5 seeds $\times$ 5 difficulty levels), 216 (78.5%) achieve discrimination $a > 1.0$, which provides evidence that our benchmark problems are appropriate in terms of difficulty. As expected, difficulty progresses monotonically from L1 ($b = -0.88$) to L5 ($b = +0.89$) (see Appendix C for a per-level breakdown). The IRT ability ranking is nearly identical to the raw accuracy ordering ($\rho = 0.976$, $p < 0.001$). Claude Sonnet 5 leads in terms of both IRT ability ($\theta = 1.418$) and mean accuracy. The equation for the IRT model is given below.

$$\Pr(Y_{mjs} = 1) = p_{mj} = \frac{1}{1 + e^{-a_j(\theta_m - b_j)}} \quad (1)$$

$$\log a_j \sim \mathcal{N}(0, \sigma^2), \quad \sigma = 0.5, \quad \lambda = 1/\sigma^2 = 4 \quad (2)$$

$$\ell(\theta, a, b) = \sum_{m=1}^{10} \sum_{j=1}^{55} \left[k_{mj} \log p_{mj} + (n_{mj} - k_{mj}) \log(1 - p_{mj}) \right] \quad (3)$$

$$(\hat{\theta}, \hat{a}, \hat{b}) = \arg \max \left\{ \ell(\theta, a, b) - \frac{\lambda}{2} \sum_{j=1}^{55} (\log a_j)^2 \right\} \quad (4)$$

Here $m = 1, \dots, 10$ indexes models, $j = 1, \dots, 55$ indexes items (one per task-level cell), and $s = 1, \dots, 5$ indexes seeds. $Y_{mjs} \in \{0, 1\}$ is whether model m solved seed s of item j ; p_{mj} is the probability of a correct response, shared by all five seeds of a cell. θ_m is the ability of model m , standardised so that θ has mean 0 and unit standard deviation; b_j is the difficulty of item j on that same scale, and $a_j > 0$ its discrimination, the slope of the response curve in θ . $k_{mj} = \sum_s Y_{mjs}$ is the number of seeds solved and $n_{mj} = 5$ the number attempted. ℓ is the binomial log-likelihood, σ the prior standard deviation of $\log a_j$, and $\lambda = 1/\sigma^2$ the equivalent penalty weight; hats denote estimates.

Prompt sensitivity. When we compared the canonical structured prompt against a second, minimal prompt across all 11 tasks and all 10 models (2,745 paired evaluations per condition), we found that model rankings are largely preserved ($\rho = 0.915$, Kendall $\tau = 0.778$). The top-4 ranked models stay in the top 4 across conditions, whereas the bottom-4 do not (GPT-4.1-mini falls from 6th to 8th under the minimal prompt, displacing Opus 4.1). Further details can be found in Appendix A.

Error taxonomy and limitations. All 2,750 evaluations were successful with 0 API errors after retries. Each model was run at its maximum supported token budget: 65,536 for o4-mini, GPT-5.4, Sonnet 5, Gemini 3.5 Flash, and Mistral L3, 32,768 for GPT-4.1 mini, 32,000 for Opus 4.1, 8,192 for LLaMA-70B, and 4,096 for Gemma-4 and Gemini FL. 11 records remained truncated at hard API caps that cannot be increased. 46 evaluations timed out during verification (we used a limit of 300 seconds), which were concentrated in VQE and Trotterization tasks that produce computationally expensive circuits. The benchmark requires Qiskit 2.x Python output, running the risk of conflating quantum domain knowledge with framework-specific API proficiency. A framework-agnostic format such as OpenQASM could potentially isolate reasoning but it changes task difficulty (e.g., state decomposition into elementary gates is substantially harder without high-level primitives). While the structured prompt’s Qiskit 2.x guidance functions as lightweight context injection, retrieval augmented generation (RAG) with official documentation could further isolate reasoning ability from API memorization.

5 Conclusion

QC-Stark demonstrates that QC competence is not unidimensional: dedicated reasoning models o4-mini and o3-mini score 0% on debugging even at 64K-token budgets (o3 scores 13%). Surprisingly, Gemini Flash Lite (8th overall) leads routing at 44%. The best accuracies per task display a huge range, from 13.2% in Debugging to 78.0% in Equivalence. Performance drops 59% as we increase the difficulty level from L1 to L5.

Prompt sensitivity analysis confirms ranking robustness ($\rho = 0.915$). IRT analysis validates the benchmark as a reliable instrument ($r = 0.985$) with monotonic difficulty progression, establishing that the observed dissociations reflect genuine structure in capability rather than just noise. Future work includes RLVR-based fine-tuning [14], framework-agnostic representations, and retrieval-augmented generation (RAG).

Acknowledgements

Claude [15] provided assistance for portions of benchmark infrastructure. All scientific claims and experimental design are solely the author’s responsibility. The data for this benchmark is available at <https://huggingface.co/datasets/pranavgupta/qc-stark>.

References

1. Cao, S., Zhang, Z., Alghadeer, M., Fasciati, S.D., Piscitelli, M., Bakr, M., Leek, P., Aspuru-Guzik, A.: Automating quantum computing laboratory experiments with an agent-based AI framework. *Patterns* 6(10), 101372 (2025)
2. Cruz-Benito, J., Faro, I.: Qiskit QuantumKatas: Adapting Microsoft’s quantum computing exercises for LLM evaluation. *arXiv:2605.27210* (2026)
3. Mikuriya, T., et al.: QCoder Benchmark: Bridging language generation and quantum hardware through simulator-based feedback. *INLG* (2025)
4. Afane, M., et al.: Quantum-Audit: Evaluating the reasoning limits of LLMs on quantum computing. *arXiv:2602.10092* (2026)
5. Yang, R., et al.: QCircuitBench: A large-scale dataset for benchmarking quantum algorithm design. *arXiv:2410.07961* (2024)
6. Tian, M., et al.: SciCode: A research coding benchmark curated by scientists. *arXiv:2407.13168* (2024)
7. Pan, H., et al.: CMT-Benchmark: A benchmark for condensed matter theory built by expert researchers. In: *ICLR 2026*. *arXiv:2510.05228* (2025)
8. Liang, P., et al.: Holistic evaluation of language models. *TMLR* (2023). *arXiv:2211.09110*
9. Vishwakarma, S., et al.: Qiskit HumanEval: An evaluation benchmark for quantum code generative models. *arXiv:2406.14712* (2024)
10. Treinish, M., Lishman, J., Bello, L., Gambetta, J., et al.: Qiskit/qiskit: Qiskit 2.4.1. *Zenodo* (2026). <https://doi.org/10.5281/zenodo.19742751>
11. Huang, D., Wang, Z.: Task complexity matters: An empirical study of reasoning in LLMs for sentiment analysis. In: Wong, R.C.W., et al. (eds.) *Advances in Knowledge Discovery and Data Mining (PAKDD 2026)*. *Lecture Notes in Computer Science*, vol. 16600. Springer, Singapore (2026). https://doi.org/10.1007/978-981-92-1468-6_18
12. Baker, F.B., Kim, S.-H.: *Item Response Theory: Parameter Estimation Techniques*. Marcel Dekker, New York (2004)
13. Schaeffer, R., Miranda, B., Koyejo, S.: Are emergent abilities of large language models a mirage? In: *NeurIPS 2023*. *arXiv:2304.15004* (2023)
14. Lambert, N., Morrison, J., Pyatkin, V., et al.: Tulu 3: Pushing frontiers in open language model post-training. *arXiv:2411.15124* (2024)
15. Anthropic: Claude. <https://www.anthropic.com/claude> (2025)

A Prompt Sensitivity Details

Spearman $\rho = 0.915$ (Kendall $\tau = 0.778$) between model rankings under the two conditions; overall accuracy rises $0.403 \rightarrow 0.446$ with the structured prompt. The top-4 grouping did not change across prompt types, but the bottom-4 ranks changed.

B Prompt Templates

B.1 System Prompts

Structured prompt:

You are a quantum computing expert writing Python code.

Environment: Python 3.13, Qiskit 2.x, numpy, scipy.

Key Qiskit 2.x notes:

- `QuantumCircuit.qasm()` removed -> use `qiskit.qasm2.dumps(circuit) / loads(qasm_str)`
- `execute()` removed -> use `Statevector` or `StatevectorSimulator`
- `qiskit.opflow` removed -> use `qiskit.quantum_info (Operator, Statevector)`

Output requirements:

- Respond with ONLY executable Python code. No markdown fences, no explanations.
- Define a function called `solve()` that returns the answer.

Note: The canonical string uses a Unicode right-arrow (U+2192) where -> is shown above, and does not wrap the two long lines.

Minimal prompt:

You are a quantum computing expert. Respond with ONLY executable Python code using Qiskit (version 2.x). No explanations, no markdown fences, just the raw code. The code must define a function called `solve()` that returns the answer. Do NOT use deprecated APIs like `.qasm()` -- use `qiskit.qasm2.dumps()` if needed.

B.2 Task Prompt Examples

T1 — State Preparation (L1, seed=1):

Write a Qiskit function `solve()` that returns a `QuantumCircuit` on 2 qubits which prepares the following quantum state from $|00\rangle$:

$|00\rangle$: $0.707106781186548 + 0.0i$

```

|01>: 0.0 + 0.0i
|10>: 0.0 + 0.0i
|11>: 0.707106781186548 + 0.0i

```

Requirements:

- You may use `QuantumCircuit.initialize(statevector, qubits)` or any standard gates.
- Ensure the statevector is normalized before passing to `initialize()`.
- The circuit should achieve fidelity > 0.999 with the target state.
- Return ONLY the `QuantumCircuit` object from `solve()`.

T4 — Debugging (L2, seed=3):

The following 3-qubit quantum circuit has exactly ONE bug (a wrong gate, swapped qubits, or missing gate).

Buggy circuit (OpenQASM 2.0):

```

OPENQASM 2.0; include "qelib1.inc";
qreg q[3]; h q[0]; cx q[0],q[1]; cx q[0],q[2]; ...

```

The INTENDED unitary transformation maps basis states as follows:

```

|000> -> (0.7071+0.0000i)|000> + (0.7071+0.0000i)|111>
|001> -> ...

```

Identify the bug and write a Qiskit function `solve()` that returns the CORRECTED `QuantumCircuit`.

C Difficulty-Level Breakdown

Performance degrades monotonically with difficulty (59% drop from L1 to L5). The steepest L1→L5 drops occur on State Preparation ($1.00 \rightarrow 0.14$), VQE ($0.96 \rightarrow 0.12$), and Oracle Synthesis ($0.88 \rightarrow 0.24$). Debugging falls least in absolute terms ($0.16 \rightarrow 0.02$). Noise Fidelity is the only task that holds roughly flat across difficulty levels ($0.70 \rightarrow 0.66$).

D Task Descriptions

Table 2. 2PL IRT fit. Items are the 55 (task, level) cells, each administered to every model under 5 seeds; abilities are standardised to mean 0 and unit SD. 120 parameters (10 abilities, 55 difficulties, 55 discriminations) over 2750 responses. Discrimination carries a log-normal(0, 0.5) prior, without which the 55 slopes are not identifiable from 10 models. In (b), n is the number of identified items entering each mean: State Preparation L1 and L2 were passed by every model under every seed, leaving their difficulty unidentified, so they are excluded.

(a) Model ability

Rank	Model	θ	SE	95% CI
1	Gemini 3.5	1.122	0.088	[0.949, 1.295]
2	Sonnet 5	1.090	0.088	[0.919, 1.262]
3	o4-mini	0.669	0.085	[0.502, 0.837]
4	GPT-5.4	0.432	0.087	[0.262, 0.603]
5	Gemma-4	0.251	0.089	[0.077, 0.425]
6	Opus 4.1	-0.021	0.093	[-0.203, 0.161]
7	GPT-4.1m	-0.087	0.094	[-0.272, 0.098]
8	Gemini FL	-0.141	0.096	[-0.328, 0.046]
9	Mistral L3	-0.843	0.124	[-1.086, -0.600]
10	LLaMA-70B	-2.473	0.223	[-2.909, -2.037]

(b) Task difficulty and discrimination

Task	Mean difficulty $\bar{b}$	Mean discrimination $\bar{a}$	n
Routing	1.897	0.862	5
Debugging	1.711	2.267	5
Trotter Decomposition	1.581	0.987	5
State Preparation	1.116	2.841	3
Noise Discrimination	0.662	1.560	5
Reverse Engineering	0.107	1.349	5
Oracle	0.015	2.824	5
QEC Decoding	-0.069	0.794	5
Noise Fidelity	-0.325	2.526	5
VQE	-0.917	1.243	5
Equivalence	-1.272	1.597	5

Table 3. Prompt sensitivity: mean binarized-accuracy difference (structured – minimal) by model and task, over all 11 tasks and all 10 models (2,745 paired evaluations per condition). The structured condition is the canonical system prompt used in the paper. 5 of the Gemma-4-31B State-Preparation L5 calls had to be excluded from this analysis: they could not be obtained in the minimal condition even after 6 retry rounds (persistent upstream 502/503 API errors).

Model	Δ	Task	Δ
o4-mini	+0.113	T11 (QEC Decoding)	+0.244
Gemma-4	+0.107	T9 (Noise Fidelity)	+0.072
GPT-4.1 mini	+0.095	T7 (Equivalence)	+0.052
Mistral L3	+0.062	T6 (Reverse Engineering)	+0.048
LLaMA-70B	+0.058	T8 (Routing)	+0.044
GPT-5.4	+0.029	T10 (VQE)	+0.036
Gemini FL	+0.007	T2 (Trotter Decomposition)	+0.028
Sonnet 5	+0.000	T3 (Oracle Synthesis)	+0.004
Opus 4.1	−0.011	T4 (Debugging)	−0.016
Gemini 3.5F	−0.025	T5 (Noise Discrimination)	−0.016
		T1 (State Preparation)	−0.020

Table 4. Mean accuracy by difficulty level across all models and tasks.

	L1	L2	L3	L4	L5
Mean score	0.655	0.553	0.416	0.336	0.267

Table 5. QC-Stark task descriptions with scoring criteria and difficulty scaling parameters.

Task	Description	Scoring	Difficulty Scaling
T1: State Preparation	Synthesize gate sequence producing target quantum state from $ 0\rangle^n$	State fidelity > 0.999	L1-2: initialize() allowed; L3+: elementary gates only; number of qubits: 2-6
T2: Trotter Decomposition	Decompose e^{-iHt} into Trotter product formula	Operator fidelity to exact evolution	Terms: 2-8; order: 1-4; time steps: 1-20
T3: Oracle Synthesis	Construct unitary oracle from Boolean specification	Functional equivalence to target	Input bits: 2-5; function complexity: linear to non-linear
T4: Debugging	Locate and fix single injected fault in quantum circuit	Binary: correct circuit or not	Qubits: 3-7; fault types: gate substitution, qubit swap, gate deletion
T5: Noise Discrimination	Distinguish noise-corrupted circuits from structurally-buggy ones	Correct identification	Channel types: depolarizing, amplitude damping; similarity level
T6: Reverse Engineering	Identify algorithm from obfuscated circuit	Correct algorithm name	Algorithms: Bell, GHZ, QFT, Grover, VQE; obfuscation: transpiled to basis gates
T7: Equivalence	Determine if two circuits implement same unitary	Binary correctness	Number of qubits: 2-5; circuit pairs: identical, permuted, distinct
T8: Routing	Insert SWAPs for hardware connectivity	Functional equivalence on topology	Number of qubits: 5-20; topologies: linear, T, heavy-hex
T9: Noise Fidelity	Construct noise channel matching error profile	Channel fidelity to target	Error types: depolarizing, amplitude damping, combined; number of qubits: 1-3
T10: VQE	Implement variational quantum eigensolver for ground-state energy estimation	Energy accuracy	Qubit count, ansatz depth, Hamiltonian complexity
T11: QEC Decoding	Decode stabilizer syndrome to identify error	Correct error identification	Codes: repetition, Steane, surface; code distance: 3-7