

The Golden Path Hypothesis: Reusable Schedules in Diffusion Caching

Dong Wang¹ Wenwu Tang¹ Francesco Corti¹ Yun Cheng² Lothar Thiele³ Olga Saukh^{1,4}

¹Graz University of Technology, Austria

²Swiss Data Science Center, Switzerland ³ETH Zurich, Switzerland

⁴Complexity Science Hub, Austria

{dong.wang, wenwu.tang, francesco.corti, saukh}@tugraz.at
yun.cheng@sdsc.ethz.ch thiele@tik.ee.ethz.ch

Abstract

Diffusion caching accelerates generation by replacing transformer computation with cached or predicted features at selected denoising steps. We introduce the *Golden Path Hypothesis* (GPH): under fixed inference conditions, prompt-independent cache schedules can achieve final-output quality comparable to the best prompt-specific schedules across prompts. We investigate the GPH across ten caching methods, four image and video models, and three cache ratios. Prompt-adaptive methods repeatedly select a small number of schedules, and reusing their most frequent schedules on new prompts closely matches the quality of prompt-specific choices. Exhaustive evaluation of 1.4 million schedules on four examples further identifies prompt-independent schedules that remain competitive on unseen prompts. To explain this transfer, we analyze denoising trajectories and the accumulation of caching errors. Latent-state trajectories exhibit similar structures across datasets and seeds, while an exact error decomposition shows that accumulated effects of earlier errors predict final latent-state error better than local approximation errors. This motivates searching for end-to-end schedules using final-output quality. With only a small set of examples, the resulting golden paths transfer across prompts and datasets, and can be tuned to the desired quality objective, including reconstruction fidelity or perceptual similarity.

1 Introduction

Diffusion and flow-matching models generate images and videos through repeated model evaluations (Ho et al., 2020; Lipman et al., 2022). Diffusion caching reduces this cost by reusing intermediate features (Ma et al., 2024) or predicting them from earlier evaluations (Liu et al., 2025b). A cache schedule specifies which denoising steps use full computation or an approximation. Because intermediate features depend on the prompt and noise seed, many caching methods choose these steps adaptively during generation. This suggests that high-quality schedules depend on the input. Yet offline methods search for a schedule before generation and reuse it across prompts, achieving high output quality in our image and video evaluations (Lei et al., 2026; Gao et al., 2026a). Our large-scale analysis shows that the search objectives used by existing offline methods can be improved. The approximation policy also affects a shared schedule’s quality. Existing work lacks a systematic analysis of these choices. More fundamentally, it remains unclear why schedules found offline work across prompts. We therefore ask a basic question: *how much does a high-quality cache schedule actually need to change across prompts?* See Section 7 for a detailed discussion of related work.

We propose the *Golden Path Hypothesis* (GPH): under fixed inference conditions, prompt-independent




Figure 1: Shared schedules retain quality across prompts. Both panels use FLUX.1-dev on PartiPrompts, with full-compute outputs for the same prompts and seeds as references. (a) Each method’s five most frequent schedules are shown at a 74% target cache ratio. Black or dark-red cells mark full steps, and white cells mark cached steps. Percentages give schedule frequencies across 4,896 prompt–seed runs. The searched schedule is reused in every run. PSNR and Learned Perceptual Image Patch Similarity (LPIPS) (Zhang et al., 2018) are averaged over all runs for each method or searched schedule. Higher PSNR and lower LPIPS are better. Adaptive methods retain their approximation policies, while search uses SeaCache’s feature reuse. (b) We reuse each method’s most frequent schedule on 1,088 prompts excluded from selection, keeping its approximation policy unchanged. Small points show up to 300 runs per method and ratio where schedules differ. Large markers show mean PSNR over all such runs. Colors denote target cache ratios and large-marker shapes denote methods. The diagonal marks equal PSNR.

schedules can achieve final-output quality comparable to the best prompt-specific schedules across prompts. Our experiments provide several forms of evidence for this hypothesis. First, prompt-adaptive methods repeatedly select a small number of schedules. For example, SeaCache selects only 14 different schedules across 4,896 prompt–seed runs on FLUX.1-dev at a 74% cache ratio (Figure 1(a)). More generally, reusing an adaptive method’s most frequent schedule on unseen prompts closely matches the quality of its prompt-specific choices (Figure 1(b)). For each tested model and cache ratio, a shared schedule stays within 1.0 dB of each prompt’s best evaluated PSNR on a majority of prompts, as reported in Section 3. Finally, we exhaustively evaluate 1.4 million schedules on four examples and identify a single schedule that remains competitive on thousands of unseen prompt–seed runs, as shown in Section 3.2 and Figure 2.

Why can the same schedule work for different inputs? We first examine full-compute denoising trajectories obtained without caching. Within each model, relative displacement, state norm, and changes in direction evolve similarly across datasets and seeds. Direction changes are smaller in the middle of denoising than near its ends. Step displacements normalized by the distance between each trajectory’s initial and final states also vary little across prompts over much of denoising. These patterns persist even though the trajectories have different spatial directions. These common changes support the use of shared cache schedules. To evaluate such a schedule, we also need to understand how caching changes the generation process. We derive an exact decomposition of the error in the model output used to update the latent state at each step. It separates the error introduced by the approximation at that step from the effect of state changes caused

by earlier cached steps. The accumulated effects of these state changes correlate much more strongly with final latent-state error than the errors introduced by the individual approximations. These findings motivate scoring schedules by final-output quality rather than accumulating prediction-error costs as done in DPCache and MeanCache (Cui et al., 2026; Gao et al., 2026a).

We then search for *golden paths* on a small number of examples, scoring candidates by final-output quality. The resulting schedules retain their quality on unseen prompts across four image datasets. Optimizing perceptual similarity instead of pixel fidelity selects different schedules and improves perceptual similarity to full-compute outputs on new prompts.

Our main contributions are:

- We formulate and test the *Golden Path Hypothesis*. Large-scale comparisons and exhaustive evaluation show that shared schedules can approach each prompt’s best evaluated output quality.
- We identify common patterns of relative step displacement and direction change in full-compute trajectories across prompts, datasets, and seeds within each model. These patterns provide empirical support for the GPH even when the trajectories have different spatial directions.
- We derive an exact decomposition of the error in the model output at each step and analyze how caching errors propagate to the final output. This analysis guides the scoring of candidate golden paths by final-output quality. We also show that changing the approximation policy can improve quality on a fixed schedule, and that this effect depends on the schedule.
- Motivated by the GPH, we search on a small set of examples using different output-quality objectives and find golden paths that retain high output quality on unseen prompts and datasets.

2 The Golden Path Hypothesis

A *full step* computes the model’s output without caching. The schedule specifies the full steps and *cached steps*. At a cached step, an *approximation policy* specifies how features or model outputs are obtained in place of full model computation. For example, it may reuse a stored feature or predict a feature from earlier computations. The *cache ratio* is K/N for K cached steps out of N total steps. The *inference conditions* comprise the model, sampler, sequence of noise levels, cache ratio, approximation policy, and quality metric. The quality metric used to rank schedules is the *objective*.

Golden Path Hypothesis. *Under fixed inference conditions, prompt-independent schedules can achieve final-output quality comparable to the best prompt-specific schedule across prompts.*

We call such a prompt-independent schedule a *golden path*. The comparison is with each prompt’s best schedule among all schedules that satisfy these inference conditions. On new prompts, we compare shared schedules’ output quality with each prompt’s best evaluated quality.

Evaluation protocol. All experiments use 50 denoising steps. The main schedule comparisons target cache ratios 0.58, 0.74, and 0.82, corresponding to $K = 29, 37$, and 41 . The baseline comparisons retain each method’s original approximation policy. Schedule reuse retains the same approximation policy. Our search experiments and tests against each prompt’s best evaluated schedule use *residual reuse*. The residual is the change in hidden features across the transformer blocks. A cached step adds the residual from the most recent full step to its current input features. We calibrate each adaptive method to achieve a *target cache ratio* on average across prompt–seed runs. The *realized cache ratio* is the ratio achieved in an individual run.

We evaluate FLUX.1-dev (Black Forest Labs, 2024) and Qwen-Image (Wu et al., 2025) on DrawBench (Saharia et al., 2022), GenEval-style (Ghosh et al., 2023), PartiPrompts (Yu et al., 2022), and DiffusionDB-clean10k (Wang et al., 2022). We evaluate the video models HunyuanVideo (Kong et al., 2024) and

Wan2.1 (Team Wan, 2025) on Penguin599 (Tencent Hunyuan, 2025) and VBench944 (Huang et al., 2024). The image and video baseline comparisons use three seeds per prompt. PSNR and SSIM (Wang et al., 2004) increase as the cached output approaches its full-compute reference. LPIPS (Zhang et al., 2018) decreases. Appendix A describes the datasets, model configurations, calibration procedures, and other experimental details.

A *quality margin* is an allowed loss relative to a prompt’s best evaluated schedule, measured in the units of the quality metric. We measure *coverage* as the fraction of prompts on which a schedule stays within that margin. For each test, the *candidate set* contains the schedules included in that comparison under the same model, cache ratio, and approximation policy. We report PSNR coverage at margins 0.25, 0.5, and 1.0 dB. Appendix B.4.3 relates these margins to the quality change from one additional cached step and gives the SSIM and LPIPS margins.

3 Shared Schedules Recur and Transfer

We test the GPH through two comparisons of output quality. We compare shared schedules with schedules chosen adaptively for each prompt and with each prompt’s best evaluated schedule. We study SeaCache (Chung et al., 2026), TeaCache (Liu et al., 2025a), SenCache (Haghighi and Alahi, 2026), and DiCache (Bu et al., 2025), which choose cached steps during generation. Their choices concentrate on a small number of schedules, as illustrated in Figure 1(a). Our image study contains 891,720 prompt–seed runs across 96 combinations of method, model, dataset, and cache ratio. The four datasets include prompts about object counts, attributes, spatial relations, and visual styles, as well as user-written prompts from DiffusionDB. Across these 96 combinations, the fraction of runs using one of the three most frequent schedules has a median of 89.8% and a range of 40.7–100%. The decisions repeat across prompts despite being made separately for each run.

3.1 Shared schedules retain quality on new prompts

We first test how output quality changes when the same schedule replaces prompt-specific adaptive decisions. For each image model, method, and cache ratio, we select the most frequent schedule with the target cache count on 544 prompts from PartiPrompts and reuse it on the remaining 1,088 prompts. We keep the approximation policy unchanged to compare the two ways of choosing cached steps. We compare outputs for the same prompt and seed, using runs where the shared and adaptive schedules differ. The large markers in Figure 1(b) lie close to the diagonal for FLUX.1-dev: the two ways of choosing schedules produce similar mean PSNR. The absolute difference between their mean PSNR values has a median of 0.10 dB across the 24 model–method–ratio combinations. Mean PSNR with the shared schedule ranges from 0.81 dB lower to 1.56 dB higher than with the adaptive method. Table 1 summarizes the corresponding changes in PSNR, SSIM, and LPIPS on the prompts excluded from schedule selection.

We repeat the comparison on HunyuanVideo and Wan2.1 using 150 prompts from each of Penguin599 and VBench944, with one seed per prompt. The most frequent schedules remain unchanged when selected using only prompts outside this evaluation set. We retain only runs where the schedules differ and the shared schedule has the target cache count, leaving 19 model–method–ratio combinations. In 17 of these 19 combinations, the shared schedule’s mean PSNR is at most 0.25 dB below the adaptive method’s mean. Shared schedules can therefore retain the mean quality of adaptive methods on new image and video prompts.

Table 1: The most frequent schedules retain quality on new prompts. The evaluation uses the 1,088 prompts excluded from schedule selection. For each metric, we subtract the value obtained with the adaptive method from the value obtained with the fixed schedule on the same prompt and seed. We average these differences within each model–ratio combination, using only runs where the two schedules differ, with 34 to 2,901 runs per combination. Each entry gives the median [minimum, maximum] of the six means from two image models and three target cache ratios. Arrows show which direction favors the fixed schedule. Bold marks the largest median Δ PSNR and Δ SSIM and the smallest median Δ LPIPS. Table 20 in Appendix B.2 gives each combination.

Method	Fixed – adaptive		
	Δ PSNR, dB $\uparrow$	Δ SSIM $\uparrow$	Δ LPIPS $\downarrow$
SeaCache	−0.03 [−0.07, +0.02]	−0.0011 [−0.0025, +0.0034]	+0.0009 [−0.0019, +0.0049]
TeaCache	+0.11 [−0.81, +1.56]	+0.0011 [−0.0333, +0.0268]	−0.0026 [−0.0390, +0.0333]
SenCache	−0.02 [−0.26, +0.30]	+0.0008 [−0.0182, +0.0122]	−0.0014 [−0.0153, +0.0203]
DiCache	−0.06 [−0.16, +0.18]	0.0000 [−0.0062, +0.0047]	−0.0005 [−0.0075, +0.0133]

3.2 A shared schedule approaches each prompt’s best evaluated quality

How closely can one shared schedule approach each prompt’s best evaluated output quality? For FLUX.1-dev at cache ratio 0.82, we exhaustively evaluate 1,370,754 schedules on four prompts from PartiPrompts, using one seed per prompt. We select the schedule with the highest mean PSNR across these four runs. Table 2 compares this shared schedule with each selection run’s best schedule in the fully enumerated space. Its PSNR gap is at most 0.269 dB in three selection runs and 1.249 dB in the fourth.

Table 2: The shared schedule is within 0.269 dB of the best schedule for three of the four selection runs. Each run uses FLUX.1-dev at cache ratio 0.82 with residual reuse. The best PSNR is the maximum over all 1,370,754 schedules with steps 0, 1, 2, and 49 fixed as full computations. The shared schedule maximizes mean PSNR across the four selection runs. The gap is the best PSNR minus the shared schedule’s PSNR, computed before rounding. All quality values are in dB.

Prompt index	Seed	Best PSNR	Shared-schedule PSNR	Gap
5	47	22.334	21.086	1.249
8	50	28.621	28.590	0.030
9	51	20.915	20.813	0.102
15	57	20.765	20.496	0.269

We then evaluate this shared schedule on 2,381 new prompts from DrawBench, GenEval-style, and PartiPrompts. We combine high-scoring schedules from the exhaustive search, uniformly sampled schedules, and control schedules such as those from MeanCache and BudCache. Removing duplicates yields 337 candidate schedules. For each prompt, we compare the shared schedule’s output PSNR with the highest PSNR among these candidates. Appendix B.5 details the candidate construction. Figure 2 shows that the selected schedule stays within 0.5 dB of the best evaluated PSNR on 57% of the new prompts and within 1.0 dB on 79%. A schedule selected on a few prompts can therefore approach the best evaluated prompt-specific schedules on new prompts.

Appendices B.1–B.3 report recurrence across seeds and datasets, additional quality metrics, and random schedule controls. In the coverage tests of Appendix B.4, a schedule selected for each of four models and three cache ratios achieves majority coverage at 1.0 dB. All 12 lower confidence bounds exceed 50%. Appendix B.5 gives the four-prompt selection rule and search-space constraints.

Transferability of a shared schedule




Figure 2: A shared schedule transfers to new prompts. For FLUX.1-dev at cache ratio 0.82, curves show the percentage of 2,381 prompts within each gap. We average each schedule’s PSNR over three seeds for each prompt. The gap is the highest mean PSNR among 337 candidates minus the mean PSNR of the schedule shown. All three schedules use residual reuse. Circles mark 1 dB.

4 Common Patterns in Full-Compute Denoising

To understand why the shared schedules in Section 3 transfer across prompts, we examine whether full-compute denoising trajectories share step-by-step patterns. We compare how latent states change and how trajectories turn, then examine the shapes and directions of individual trajectories. The measurements cover 74,310 image trajectories and 4,629 trajectories from each video model. Each dataset uses three noise seeds per prompt. Appendix A.1 gives the sampling configurations.

4.1 Step-by-step changes across prompts

We first compare the relative distances that latent states move at the same denoising step across prompts. We measure how far each latent state lies from the line joining the initial and final states, how far it moves at each step, and the state norm. Let z_n be the latent state after n denoising steps. There are 51 states, from initial noise z_0 to final state z_{50} . The vector $\ell = z_{50} - z_0$ joins the endpoints. Its length $L = \|\ell\|$ is the *chord length*, and $\hat{\ell} = \ell/L$ is its direction. The part of $z_n - z_0$ perpendicular to this line is the *off-chord vector*

$$\beta_n = (z_n - z_0) - ((z_n - z_0)^\top \hat{\ell}) \hat{\ell}. \quad (1)$$

The normalized distance from the line is $\|\beta_n\|/L$. At step n , the normalized displacement is $\|z_{n+1} - z_n\|/L$. Both distances are expressed relative to the trajectory’s chord length. We measure the state norm as $\|z_n\|/\sqrt{d}$, where d is the number of latent coordinates. For each model and dataset, we also measure how much these quantities vary across prompt–seed runs at each state or step. We use the *coefficient of variation*, abbreviated CV: the population standard deviation divided by the mean across runs at that index. We report CV as a percentage.

Within each model, the upper curves in Figure 3 show similar trends across datasets, although their magnitudes differ. Figure 10 shows the corresponding measurements for Qwen-Image and Wan2.1. The distance from the line rises gradually and falls rapidly near the end. Step displacements generally increase, while the state norm first decreases and then increases. The profiles reflect both the model and its sampler.




Figure 3: Full-compute trajectories follow similar patterns across datasets within FLUX.1-dev and HunyuanVideo. Rows show FLUX.1-dev and HunyuanVideo from top to bottom. Colors and line styles identify datasets within each model. Distance is measured from the line through each trajectory’s endpoints. Distance and displacement are divided by each trajectory’s chord length L . State norm is divided by $\sqrt{d}$, where d is the latent dimension. Upper curves show medians across prompt–seed runs for each dataset, with bands spanning the middle 50% at each index. Lower curves show the coefficient of variation across these runs at each index on a shared logarithmic percentage scale. Distance CV omits states 0 and 50, where it is undefined. GenEval and DiffusionDB denote GenEval-style and DiffusionDB-clean10k. FLUX.1-dev uses 37,155 prompt–seed runs from four datasets, and HunyuanVideo uses 4,629 runs from two datasets. Each dataset uses three seeds per prompt. Step n updates state n to $n + 1$.

The lower curves in Figure 3 show similar cross-prompt variation across these datasets. Normalized step displacement has low variation over much of the trajectory. The median CV over the 50 steps ranges from 1.94% to 2.35% across the four FLUX.1-dev datasets and from 0.59% to 0.63% across the two HunyuanVideo datasets. Normalized step displacement varies more across prompts at the start. State norms also vary little across prompts at the early and middle states, with more variation near the final output. Distances from the endpoint line vary more across prompts. We conclude that normalized step displacements are similar across prompts at most steps within each model. This consistency supports the GPH.

4.2 Changes in direction

We next compare how much trajectories change direction at the same denoising steps across datasets and seeds. The turning angle measures the change in direction around state n . We compute it from the state changes over w steps before and after n :

$$\theta_n^{(w)} = \arccos \frac{(z_n - z_{n-w})^\top (z_{n+w} - z_n)}{\|z_n - z_{n-w}\| \|z_{n+w} - z_n\|}. \quad (2)$$

We use $w = 5$ and call the sequence of angles over denoising steps a *turning profile*. Figure 4 shows smaller direction changes in the middle than at the ends. The FLUX.1-dev profiles also share a local peak near step 18. Appendix C.3 gives the sampling details and compares window widths. The common step-by-step patterns therefore include both direction changes and relative displacement.




Figure 4: Direction changes follow similar patterns across datasets within each model. Curves show median turning angles across prompts for each dataset and seed. Colors identify datasets.

4.3 The shape and direction of individual trajectories

We next ask whether the common patterns in normalized displacement and turning angle also correspond to shared directions in latent space. We use principal-component analysis, abbreviated PCA, to describe the off-chord vectors of each trajectory. For each trajectory, we subtract the mean of its 51 off-chord vectors and fit the first two principal components, PC1 and PC2. These components span a plane for the trajectory’s off-chord vectors. Across model–dataset combinations, the median fraction of centered off-chord variance explained by these two components ranges from 89.9% to 96.3%, as shown in Figure 5(b). Adding the chord direction gives a three-dimensional approximation of the complete trajectory. Figure 5(a) shows three measured off-chord curves whose projected endpoints coincide because the off-chord vector is zero at both the initial and final states.

We then compare the directions of the fitted planes in the original latent space. Their *first principal angle* is the smallest angle between a unit direction in one plane and a unit direction in the other. An angle near zero means that the planes share a direction. An angle near 90° means that they are nearly orthogonal. When both the prompt and initial noise differ, the median first principal angle is about 88° in both image models. In both image models, pairs that share initial noise have smaller median first principal angles than pairs that share a prompt, as shown in Figure 5(c). To summarize, trajectories within each model share patterns in normalized displacement and turning angle, even when their off-chord planes have different orientations. Together with the transfer results in Section 3, these common patterns provide empirical support for the GPH.

5 Evaluating Schedules by Final-Output Quality

The common patterns in Section 4 describe denoising without caching. To compare candidate golden paths, we now examine how reusing or predicting features changes later computations and the final output. We ask what a quality score needs to capture when evaluating a complete schedule. We define the *output error* as the difference between the cached and full-compute final latent states for the same prompt and seed, and measure its magnitude using the L2 norm.




Figure 5: Off-chord variation is low-dimensional, but its directions differ across inputs. (a) Each FLUX.1-dev curve shows off-chord vectors in its own PC1–PC2 coordinates, normalized by the full-compute trajectory’s chord length. Solid lines show states 0–40, and pale dashed lines show states 40–50. Dots mark all 51 states. Open circles mark states 0 and 50. Planes are rotated and separated in display coordinates. (b) For each model, ranges give the minimum and maximum dataset medians of the percentage of centered off-chord variance explained by PC1 and by PC1 + PC2. (c) Bars show median first principal angles in the original latent space. Pairs share only initial noise, only the prompt, or neither. Colors identify models. The Random group shows random-plane references. The dotted line marks 90°. FLUX, Qwen, HYV, and Wan denote FLUX.1-dev, Qwen-Image, HunyuanVideo, and Wan2.1. Appendix C.4 gives the sample construction and pair counts.

5.1 Current approximations and earlier errors

How do current approximation errors and the effects of earlier cached steps relate to output error? Figure 6 compares the full-compute state z_n^F and cached state $\tilde{z}_n$ at denoising step $n = 0, \dots, 49$, before the update, for the same prompt and seed. Earlier approximations affect the cached state. The full model predicts velocity v_n^F at z_n^F . At $\tilde{z}_n$, a full step would produce v_n^{CF} , with all earlier cached steps unchanged. The cached run uses $\bar{v}_n$ to update $\tilde{z}_n$ to $\tilde{z}_{n+1}$. At a cached step, the approximation policy produces $\bar{v}_n$, and we compute v_n^{CF} separately for comparison. At a full step, $\bar{v}_n = v_n^{CF}$.

The *velocity error*, $\bar{v}_n - v_n^F$, has the exact decomposition:

$$\bar{v}_n - v_n^F = \underbrace{\bar{v}_n - v_n^{CF}}_{a_n: \text{current contribution}} + \underbrace{v_n^{CF} - v_n^F}_{g_n: \text{state contribution}}. \quad (3)$$

The current contribution a_n compares approximate and full-model predictions at the same cached state. The state contribution g_n compares full-model predictions at the cached and full-compute states. At a full step, $a_n = 0$.

We measure both contributions on 100 PartiPrompts with FLUX.1-dev, SeaCache, and TeaCache at cache ratios near 0.58 and 0.82. For each prompt, we sum the magnitude of each contribution over denoising steps. Across the four method–ratio combinations, the Spearman correlation of the summed state contribution, $\sum_n \|g_n\|$, with output-error magnitude ranges from 0.988 to 0.996. For the summed current contribution, $\sum_n \|a_n\|$, it ranges from 0.579 to 0.748. The summed state contribution is more strongly associated with output error than the summed current contribution. Earlier cached steps can affect the model’s prediction even at later full steps. Appendix D.1 gives the state recursion.

5.2 Propagation from one cached step

We next isolate one cached step to trace how its feature error reaches the final output. This explains which effects a local feature-error score omits. We replace a feature only at step k of a full-compute trajectory.




Figure 6: The velocity error has current and state contributions. Schematic illustration. Dots mark states. The dotted line joins the pair at cached step n . Arrows show velocity predictions.

Let d_k^F be that feature and $\hat{d}_k$ its cached approximation. Write their difference as $r_k = \hat{d}_k - d_k^F$. Let B_k map feature error to velocity error. Let H_k map velocity error to the error in the next latent state through the sampler update. For a one-step sampler, let J_j be the Jacobian of a later full-compute transition. Let $e_{50}^{(k)}$ be the output error with only step k cached. To first order,

$$e_{50}^{(k)} \approx \underbrace{J_{49} \cdots J_{k+1}}_{\Phi_{50,k+1}} H_k B_k r_k. \quad (4)$$

Thus, output error depends on both the feature error and its propagation through the model, sampler, and remaining steps.

The experiment uses 100 DrawBench prompts and three approximation policies on FLUX.1-dev: residual reuse, first-order Taylor prediction, and second-order Hermite prediction. We measure two gains: the velocity-error norm divided by the feature-error norm, and the output-error norm divided by the next-state error norm. At each step, we average each gain over the other 99 prompts with the same approximation policy, then multiply the two means by the Euler step-size magnitude to obtain the propagation gain h_k^{LOO} . LOO denotes leave-one-prompt-out estimation. Appendix D.3 gives the derivation and measurement procedure.

Table 3: Scores that include propagation rank output errors more accurately than local feature error alone.

Entries give Spearman correlations between each score and the L2 distance between the final latent states with and without caching, over 4,800 isolated cached steps per approximation policy. $\|r_k\|$ is the feature-error norm, and h_k^{LOO} is the propagation gain estimated from the other 99 prompts at the same step and with the same approximation policy. The step-only score is the negative cached-step index $-k$. Bold marks the highest correlation in each row.

Approximation policy	Feature error $\ r_k\ $	Propagation gain h_k^{LOO}	Feature error $\times$ gain $\ r_k\ h_k^{\text{LOO}}$	Step only $-k$
Residual reuse	0.528	0.803	0.886	0.867
Hermite order 2	0.586	0.800	0.896	0.880
Taylor order 1	0.676	0.788	0.899	0.880

Table 3 shows that scores including propagation factors estimated from other prompts rank the measured output errors more accurately than local feature error alone. The step-only score is $-k$, so earlier cached steps rank higher.

The single-step experiment starts from a full-compute state. In a complete cached trajectory, earlier approximations change the states at which later approximations are made. Adding scores measured independently

on the full-compute trajectory would omit this dependence on earlier choices. Scoring final outputs includes these effects when comparing candidate golden paths.

5.3 The approximation policy changes schedule quality

We test whether changing the approximation policy can improve output quality on a fixed schedule, and whether the effect differs across schedules. We compare four schedules under five approximation policies on FLUX.1-dev and Qwen-Image, using 1,632 prompts from PartiPrompts and three seeds. For FLUX.1-dev at cache ratio 0.58, keeping the BudCache schedule fixed and replacing residual reuse with second-order Hermite prediction raises mean PSNR by 0.48 dB. At cache ratio 0.82 on FLUX.1-dev, replacing residual reuse with second-order Hermite prediction lowers mean PSNR by 0.38 dB on the BudCache schedule and by 6.68 dB on DiCache’s most frequent schedule. Figure 7 shows these comparisons at cache ratio 0.82 for both models.




Figure 7: The effect of changing the approximation policy depends on the schedule. Both panels use cache ratio 0.82. Each curve holds one schedule fixed while changing the approximation policy. Points show mean PSNR over 1,632 PartiPrompts and three seeds. Circles denote BudCache schedules, squares DPCache schedules, triangles uniform schedules, and diamonds DiCache’s most frequent schedules. The policies are residual reuse, first-order Taylor prediction, second-order Hermite prediction, interval-average velocity prediction, and two-anchor prediction. Nonparallel curves show that the same change in approximation policy produces different PSNR changes across schedules.

We use an additive model to measure this dependence on the schedule. In this model, replacing one approximation policy with another changes predicted PSNR by the same amount for every schedule. We fit the model to the 20 mean PSNR values for each image model and cache ratio. The differences between measured and fitted means quantify the interaction between schedule and approximation policy. At cache ratios 0.74 and 0.82, these differences account for 13–27% of the variation among the 20 means. A schedule found by offline search can achieve higher mean PSNR with a different approximation policy. The gain or loss from changing the policy depends on the schedule. We therefore evaluate a candidate golden path with the approximation policy intended for generation. Table 32 reports the interaction results for each model and cache ratio.

6 Searching for Golden Paths

Motivated by the GPH, we test whether standard search can find transferable schedules without exhaustive enumeration. We score complete schedules on a few examples by final-output quality, following Section 5. We also compare schedules and output quality under different objectives.

Finding schedules that transfer. On FLUX.1-dev and Qwen-Image, we search under residual reuse using hill climbing, simulated annealing, and greedy coordinate ascent, with random search as a control. For each model and cache ratio, we score candidates by mean PSNR on eight prompt–seed runs. Among candidates from all four procedures, we select the schedule with the highest mean PSNR on 50 separate COCO validation prompts (Lin et al., 2014). The scoring and validation prompts are separate from the evaluation datasets. We evaluate each selected schedule on the four image datasets with three seeds per prompt. See Appendix E for search and selection details.

Table 4: Searched schedules achieve higher or comparable mean PSNR relative to all three reference schedules.

For each prompt and seed, we subtract the reference schedule’s output PSNR from the searched schedule’s output PSNR. Entries give the mean differences, with positive values favoring the searched schedule. All schedules use residual reuse. The random-search schedule is selected from random search alone. FLUX denotes FLUX.1-dev and Qwen denotes Qwen-Image. DB, GE, PP, and DDB denote DrawBench, GenEval-style, PartiPrompts, and DiffusionDB-clean10k, respectively. We average over 600, 1,659, 4,896, and 30,000 prompt–seed runs, respectively. Confidence intervals and four additional metrics appear in Table 38.

Model	Cache ratio	Mean Δ PSNR: searched – comparison schedule, dB											
		MeanCache				BudCache				Random search			
		DB	GE	PP	DDB	DB	GE	PP	DDB	DB	GE	PP	DDB
FLUX	0.58	+0.70	+0.66	+0.28	+0.37	+5.49	+6.21	+4.35	+3.26	+2.83	+2.94	+2.36	+1.99
FLUX	0.74	+0.49	+0.50	+0.36	+0.32	+1.14	+1.17	+0.91	+0.74	+0.57	+0.58	+0.57	+0.40
FLUX	0.82	+0.41	+0.58	+0.42	+0.44	+0.47	+0.70	+0.31	+0.12	+0.60	+0.83	+0.61	+0.46
Qwen	0.58	-0.02	-0.05	+0.04	+0.09	+1.19	+0.84	+1.08	+1.15	+3.95	+3.71	+3.93	+3.88
Qwen	0.74	+0.07	-0.09	-0.02	-0.03	+0.41	+0.28	+0.35	+0.30	+0.87	+0.70	+0.68	+0.49
Qwen	0.82	+0.70	+0.96	+0.79	+0.71	+1.57	+1.99	+1.51	+1.06	+1.36	+1.52	+1.62	+1.57

The searched schedules have higher mean PSNR than BudCache and random search in every comparison in Table 4. They also improve on MeanCache in 19 of the 24 comparisons. In the remaining five, mean PSNR is only 0.02–0.09 dB lower than MeanCache’s. Thus, a small set of scoring examples can identify schedules that remain useful across a much larger set of prompts.

Choosing the quality objective. Existing offline methods use different objectives. DPCache (Cui et al., 2026) accumulates feature prediction errors, while MeanCache (Gao et al., 2026a) uses errors in predicting the average velocity over a denoising interval. Both measure these errors on full-compute trajectories, which omit the state changes caused by earlier cache approximations. BudCache (Lei et al., 2026) instead scores complete cached generations using final latent MSE. Latent MSE measures a different quantity from pixel fidelity or perceptual similarity.

We repeat hill climbing and simulated annealing using LPIPS instead of PSNR, while keeping the approximation policy fixed. For each procedure, we compare its LPIPS-selected schedule with its PSNR-selected schedule. This gives 48 comparisons across two procedures, two models, three cache ratios, and four datasets. Table 5 shows that the LPIPS-selected schedules achieve lower mean LPIPS and higher mean SSIM than the PSNR-selected schedules in all 48 comparisons. Their mean PSNR is higher in 15 comparisons and lower in the remaining 33. Golden-path search can therefore improve perceptual similarity on new prompts by changing the output-quality objective.

Table 5: Optimizing LPIPS selects different schedules and improves the targeted metric. Each entry gives the range across eight comparisons, using hill climbing and annealing on four datasets. For each procedure and dataset, we subtract the mean PSNR, SSIM, or LPIPS of the PSNR-selected schedule’s outputs from the corresponding mean for the LPIPS-selected schedule’s outputs. Positive PSNR and SSIM differences and negative LPIPS differences favor the LPIPS-selected schedule. Both means use the same 600 DrawBench, 1,659 GenEval-style, 4,896 PartiPrompts, or 30,000 DiffusionDB-clean10k prompt-seed runs, with three seeds per prompt.

Model	Cache ratio	LPIPS-selected – PSNR-selected		
		PSNR range (dB)	SSIM range	LPIPS range
FLUX.1-dev	0.58	−0.002 to +0.269	+0.0023 to +0.0144	−0.0224 to −0.0043
FLUX.1-dev	0.74	−0.451 to +0.080	+0.0009 to +0.0241	−0.0493 to −0.0025
FLUX.1-dev	0.82	−0.630 to −0.004	+0.0010 to +0.0410	−0.0992 to −0.0044
Qwen-Image	0.58	−0.883 to +0.329	+0.0007 to +0.0210	−0.0261 to −0.0074
Qwen-Image	0.74	−1.262 to −0.365	+0.0059 to +0.0206	−0.0454 to −0.0124
Qwen-Image	0.82	−0.365 to +0.055	+0.0068 to +0.0115	−0.0199 to −0.0036

7 Related Work

Feature reuse and prediction. DeepCache reuses U-Net features (Ma et al., 2024). FORA (Selvaraju et al., 2024) and Δ -DiT (Chen et al., 2024b) extend feature or residual reuse to diffusion transformers. ToCa selects cacheable tokens within layers (Zou et al., 2025). For feature prediction, TaylorSeer uses finite differences (Liu et al., 2025b), while HiCache uses Hermite interpolation (Feng et al., 2026). L2P instead learns the predictor (Shen et al., 2026). FoCa uses multistep prediction and correction (Zheng et al., 2026c). HyCa assigns solvers to feature dimensions (Zheng et al., 2026b). SVD-Cache separates principal and residual subspaces (Chen et al., 2026). RFC estimates output changes from module inputs (Son et al., 2026). DiCache extrapolates from the two most recent full-step residuals, using the first transformer block’s output to guide the extrapolation (Bu et al., 2025). We extend this line of work by studying how approximation policies and schedules jointly affect output quality. Controlled comparisons show that changing the policy can improve output quality without changing the schedule, and that the effect depends on the schedule. This identifies policy choice as another way to improve the output quality of candidate golden paths.

Schedule selection. TeaCache (Liu et al., 2025a), SeaCache (Chung et al., 2026), SenCache (Haghighi and Alahi, 2026), and DiCache (Bu et al., 2025) select cached steps during generation. DPCache (Cui et al., 2026) selects fixed schedules using accumulated feature prediction errors. MeanCache (Gao et al., 2026a) uses errors in predicted interval-average velocity. Both measure these errors on full-compute trajectories and omit the state changes caused by earlier cache approximations. BudCache (Lei et al., 2026) selects its cache schedule using final latent MSE. OTCache interpolates schedules across computation limits after searching with an LPIPS objective (Gao et al., 2026b). ReCache uses reinforcement learning to select schedules under compute constraints (Aliev et al., 2026). We extend the study of reusable schedules by testing the GPH through large-scale comparisons of the quality obtained with shared and prompt-specific schedules. Shared schedules can approach each prompt’s best evaluated quality. Our error analysis explains why candidate schedules should be evaluated by final-output quality. Controlled comparisons then show how the choice of output-quality objective affects the schedules selected and their quality on new prompts.

Trajectory geometry. Chen et al. (2024a) use diffusion trajectory geometry to choose sampling times. OmniCache studies cache-specific curvature (Chu et al., 2025). Fresco instead reduces spatial resolution at early steps (Zheng et al., 2026a). Our large-scale study of full-compute trajectories covers image and video models across prompts, datasets, and seeds. Within each model, relative step displacements and direction

changes follow similar patterns even when spatial directions differ. These shared patterns provide empirical support for the GPH across different inputs.

8 Discussion and Conclusion

Discussion and conclusion. Our experiments support the GPH: shared schedules can achieve quality comparable to the best evaluated prompt-specific schedules. Common step-by-step denoising patterns within each model provide empirical support for this reuse, even when trajectories differ in spatial direction. Our error analysis motivates scoring complete schedules by final-output quality, since local approximation errors omit the effects of earlier state changes. The effect of an approximation policy also depends on the schedule, so evaluation should use the policy intended for generation. Searches on a few examples demonstrate a practical use of the GPH. They find schedules that transfer to new prompts, and changing the objective can improve the chosen quality metric on those prompts. Future work will study whether the distribution of golden paths in the schedule space can guide searches that require fewer candidate evaluations. We will consider evolutionary search and ant colony optimization.

Limitations. Our experiments cover transformer-based image and video models. We have not tested the GPH on non-transformer diffusion models or other data modalities. We have not systematically studied how the number and diversity of scoring examples affect output quality on new prompts. We have not systematically characterized the distribution of golden paths or the distances between them. Whether small schedule changes can connect them at a fixed cache ratio while preserving high output quality across prompts remains an open question.

AI Disclosure

We used Claude Code and Codex with Fable 5.1 and GPT-5.6 to implement baseline methods and experimental code, write Slurm scripts, clean and reformat data, and produce figures. For English drafting and editing, we used Fable 5, Fable 5.1, GPT-5.6, and GPT-6.

We initially used AI agents to write all experimental code. The authors independently made the original observations, formulated the GPH, designed the methodology, developed the mathematical claims, and interpreted the results. AI tools assisted with subsequent discussion and review. The authors made the final scientific decisions and specified the experimental conditions and scope. We recorded our exploratory experiments in hundreds of Markdown files. The authors specified each experiment’s design and procedure in these files, and AI agents implemented the experiments and submitted jobs to the compute clusters. The agents updated the corresponding files with results under the authors’ authorization. The authors substantially rewrote the initial AI-edited English drafts. We take responsibility for the final paper, code, and reported results.

Reproducibility Statement

Code and instructions for reproducing the experiments are available at <https://github.com/nanguoyu/Golden-Path-Hypothesis>. The repository includes model-specific implementations, generation and evaluation scripts, and the search and analysis code used in this paper. It also provides environment setup and data preparation instructions.

References

- Mishan Aliev, Eva Neudachina, Ilya Bykov, Aleksandr Oganov, Kirill Struminsky, Aibek Alanov, and Denis Rakitin. ReCache: Learning budget-aware caching schedules for diffusion models via REINFORCE. *arXiv preprint arXiv:2606.06060*, 2026.
- Black Forest Labs. FLUX. <https://github.com/black-forest-labs/flux>, 2024.
- Jiazi Bu, Pengyang Ling, Yujie Zhou, Yibin Wang, Yuhang Zang, Dahua Lin, and Jiaqi Wang. DiCache: Let diffusion model determine its own cache. *arXiv preprint arXiv:2508.17356*, 2025.
- Defang Chen, Zhenyu Zhou, Can Wang, Chunhua Shen, and Siwei Lyu. On the trajectory regularity of ODE-based diffusion sampling. In *International Conference on Machine Learning*, 2024a. arXiv:2405.11326.
- Guantao Chen, Shikang Zheng, Yuqi Lin, and Linfeng Zhang. Forecast the principal, stabilize the residual: Subspace-aware feature caching for efficient diffusion transformers. *arXiv preprint arXiv:2601.07396*, 2026.
- Pengtao Chen, Mingzhu Shen, Peng Ye, Jianjian Cao, Chongjun Tu, Christos-Savvas Bouganis, Yiren Zhao, and Tao Chen. Δ -DiT: A training-free acceleration method tailored for diffusion transformers. *arXiv preprint arXiv:2406.01125*, 2024b.
- Huanpeng Chu, Wei Wu, Guanyu Feng, and Yutao Zhang. OmniCache: A trajectory-oriented global perspective on training-free cache reuse for diffusion transformer models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 16302–16312, 2025. arXiv:2508.16212.
- Jiwoo Chung, Sangeek Hyun, MinKyu Lee, Byeongju Han, Geonho Cha, Dongyoon Wee, Youngjun Hong, and Jae-Pil Heo. SeaCache: Spectral-evolution-aware cache for accelerating diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14283–14294, 2026. arXiv:2602.18993.
- Bowen Cui, Yuanbin Wang, Huajiang Xu, Biaolong Chen, Aixi Zhang, Hao Jiang, Zhengzheng Jin, Xu Liu, and Pipei Huang. Denoising as path planning: Training-free acceleration of diffusion models with DPCache. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 43632–43642, 2026. arXiv:2602.22654.
- Liang Feng, Shikang Zheng, Jiacheng Liu, Yuqi Lin, Qinming Zhou, Peiliang Cai, Xinyu Wang, Junjie Chen, Chang Zou, Yue Ma, and Linfeng Zhang. HiCache: A plug-in scaled-hermite upgrade for taylor-style cache-then-forecast diffusion acceleration. In *International Conference on Learning Representations*, 2026. arXiv:2508.16984.
- Huanlin Gao, Ping Chen, Fuyuan Shi, Ruijia Wu, Yantao Li, Qiang Hui, et al. MeanCache: From instantaneous to average velocity for accelerating flow matching inference. In *International Conference on Learning Representations*, 2026a. arXiv:2601.19961.
- Huanlin Gao, Fang Zhao, Qiang Hui, Fuyuan Shi, Shaoan Zhao, Yantao Li, Chao Tan, Ting Lu, Yuren You, Kai Wang, and Shiguo Lian. OTCache: Optimal transport for geometry-aware caching in diffusion models. *arXiv preprint arXiv:2606.31026*, 2026b.
- Dhruba Ghosh, Hannaneh Hajishirzi, and Ludwig Schmidt. GenEval: An object-focused framework for evaluating text-to-image alignment. In *Advances in Neural Information Processing Systems*, 2023.
- Yasaman Haghighi and Alexandre Alahi. SenCache: Accelerating diffusion model inference via sensitivity-aware caching. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14295–14304, 2026. arXiv:2602.24208.
- Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. In *Advances in Neural Information Processing Systems*, 2020.
- Ziqi Huang, Yinan He, Jiashuo Yu, Fan Zhang, Chenyang Si, Yuming Jiang, Yuanhan Zhang, Tianxing Wu, Qingyang Jin, Nattapol Chanpaisit, et al. VBench: Comprehensive benchmark suite for video generative models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024.

- Weijie Kong, Qi Tian, Zijian Zhang, Rox Min, Zuozhuo Dai, Jin Zhou, Jiangfeng Xiong, Xin Li, Bo Wu, Jianwei Zhang, et al. HunyuanVideo: A systematic framework for large video generative models. *arXiv preprint arXiv:2412.03603*, 2024.
- Mingkun Lei, Tong Zhao, Liangyu Yuan, and Chi Zhang. Budget-constrained step-level diffusion caching. In *International Conference on Machine Learning*, 2026. arXiv:2606.13496.
- Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C. Lawrence Zitnick. Microsoft coco: Common objects in context. In *European Conference on Computer Vision*, pages 740–755, 2014.
- Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nickel, and Matt Le. Flow matching for generative modeling. *arXiv preprint arXiv:2210.02747*, 2022.
- Feng Liu, Shiwei Zhang, Xiaofeng Wang, Yujie Wei, Haonan Qiu, Yuzhong Zhao, Yingya Zhang, Qixiang Ye, and Fang Wan. Timestep embedding tells: It’s time to cache for video diffusion model. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2025a. arXiv:2411.19108.
- Jiacheng Liu, Chang Zou, Yuanhuiyi Lyu, Junjie Chen, and Linfeng Zhang. From reusing to forecasting: Accelerating diffusion models with TaylorSeers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2025b. arXiv:2503.06923.
- Xinyin Ma, Gongfan Fang, and Xinchao Wang. DeepCache: Accelerating diffusion models for free. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, 2021.
- Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily Denton, Seyed Kamyar Seyed Ghasemipour, Burcu Karagol Ayan, S. Sara Mahdavi, Raphael Gontijo-Lopes, et al. Photorealistic text-to-image diffusion models with deep language understanding. In *Advances in Neural Information Processing Systems*, 2022.
- Pratheba Selvaraju, Tianyu Ding, Tianyi Chen, Ilya Zharkov, and Luming Liang. FORA: Fast-forward caching in diffusion transformer acceleration. *arXiv preprint arXiv:2407.01425*, 2024.
- Zhirong Shen, Rui Huang, Jiacheng Liu, Chang Zou, Peiliang Cai, Shikang Zheng, Zhengyi Shi, Liang Feng, and Linfeng Zhang. Beyond fixed formulas: Data-driven linear predictor for efficient diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 30792–30801, 2026.
- Byungwan Son, Jeimin Jeon, Jeongwoo Choi, and Bumsub Ham. Relational feature caching for accelerating diffusion transformers. *arXiv preprint arXiv:2602.19506*, 2026.
- Team Wan. Wan: Open and advanced large-scale video generative models. *arXiv preprint arXiv:2503.20314*, 2025.
- Tencent Hunyuan. Penguin video benchmark. <https://github.com/Tencent-Hunyuan/HunyuanVideo/blob/main/assets/PenguinVideoBenchmark.csv>, 2025.
- Zhou Wang, Alan C. Bovik, Hamid R. Sheikh, and Eero P. Simoncelli. Image quality assessment: From error visibility to structural similarity. *IEEE Transactions on Image Processing*, 13(4):600–612, 2004.
- Zijie J. Wang, Evan Montoya, David Munechika, Haoyang Yang, Benjamin Hoover, and Duen Horng Chau. DiffusionDB: A large-scale prompt gallery dataset for text-to-image generative models. *arXiv preprint arXiv:2210.14896*, 2022.
- Chenfei Wu, Jiahao Li, Jingren Zhou, Junyang Lin, Kaiyuan Gao, Kun Yan, Sheng-ming Yin, Shuai Bai, Xiao Xu, Yilei Chen, et al. Qwen-Image technical report, 2025. arXiv:2508.02324.

- Jiazheng Xu, Xiao Liu, Yuchen Wu, Yuxuan Tong, Qinkai Li, Ming Ding, Jie Tang, and Yuxiao Dong. ImageReward: Learning and evaluating human preferences for text-to-image generation. In *Advances in Neural Information Processing Systems*, 2023.
- Jiahui Yu, Yuanzhong Xu, Jing Yu Koh, Thang Luong, Gunjan Baid, Zirui Wang, Vijay Vasudevan, Alexander Ku, Yinfei Yang, Burcu Karagol Ayan, et al. Scaling autoregressive models for content-rich text-to-image generation. *arXiv preprint arXiv:2206.10789*, 2022.
- Richard Zhang, Phillip Isola, Alexei A. Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2018.
- Shikang Zheng, Guantao Chen, Lixuan He, Jiacheng Liu, Yuqi Lin, Chang Zou, and Linfeng Zhang. From sketch to fresco: Efficient diffusion transformer with progressive resolution. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2026a. arXiv:2601.07462.
- Shikang Zheng, Guantao Chen, Qinming Zhou, Yuqi Lin, Lixuan He, Chang Zou, Peiliang Cai, Jiacheng Liu, and Linfeng Zhang. Let features decide their own solvers: Hybrid feature caching for diffusion transformers. In *International Conference on Learning Representations*, 2026b. arXiv:2510.04188.
- Shikang Zheng, Liang Feng, Xinyu Wang, Qinming Zhou, Peiliang Cai, Chang Zou, Jiacheng Liu, Yuqi Lin, Junjie Chen, Yue Ma, and Linfeng Zhang. Forecast then calibrate: Feature caching as ODE for efficient diffusion transformers. In *AAAI Conference on Artificial Intelligence*, 2026c. arXiv:2508.16211.
- Chang Zou, Xuyang Liu, Ting Liu, Siteng Huang, and Linfeng Zhang. Accelerating diffusion transformers with token-wise feature caching. In *International Conference on Learning Representations*, 2025. arXiv:2410.05317.

Appendix

Appendix	Contents	Page
A	Experimental setup and baseline results	17
B	Schedule frequencies, reuse, coverage, and exhaustive search	25
C	Additional full-compute trajectory results	37
D	Cache-error analysis and approximation policy comparisons	39
E	Schedule search, quality objectives, and additional results	43

A Experimental Setup and Baseline Results

A.1 Sampling conditions

The FLUX.1-dev trajectories use 50 FlowMatchEuler steps, BF16 inference, 1024×1024 images, and guidance scale 3.5. Their three base seeds are 41, 42, and 43. The Qwen-Image trajectories use 50 FlowMatchEuler steps with the checkpoint’s dynamic noise-level shift, BF16 inference, the model’s native 1328×1328 image grid, classifier-free guidance 4.0, and base seeds 42, 100042, and 200042. The seed for prompt index i is the base seed plus i . Each prompt is therefore evaluated with three different seeds.

The four datasets contain 200 DrawBench prompts, 553 GenEval-style prompts, 1,632 PartiPrompts, and 10,000 DiffusionDB prompts. GenEval-style prompts are built from GenEval templates (Ghosh et al., 2023). DiffusionDB-clean10k is a 10,000-prompt subset of DiffusionDB (Wang et al., 2022). Distances from the line joining trajectory endpoints and principal-component variance summaries use all prompts. Turning profiles and comparisons of plane orientations use the first 120 prompts from each dataset and seed, giving 1,440 trajectories per image model.

Both video models generate 65 frames with 50 denoising steps in BF16. HunyuanVideo uses the HYVideo-T/2-cfgdistill checkpoint at 640×480 , Euler sampling with flow shift 7, embedded guidance 6, and CFG scale 1. Wan2.1 uses T2V-1.3B at 832×480 , UniPC sampling with shift 5 and guidance 5. Each video model uses all 599 Penguin599 and 944 VBench944 prompts under three base seeds, giving 4,629 full-compute trajectories. The base seeds are 54, 55, and 56 for Penguin599 and 42, 43, and 44 for VBench944. Both models use the base seed plus the prompt index as the generation seed.

A.2 Methods

Table 6 compares how the methods choose cached steps and how they approximate the skipped computation. Adaptive methods choose a schedule during each prompt–seed run. Offline searches select a fixed schedule before generation.

Table 6: The methods differ in both schedule selection and approximation policy. The last row describes the search experiments in Section 6.

Method	Schedule choice	Selection rule or objective	Approximation policy
SeaCache (Chung et al., 2026)	Adaptive	Spectral feature change	Residual reuse
TeaCache (Liu et al., 2025a)	Adaptive	Calibrated feature change	Residual reuse
SenCache (Haghighi and Alahi, 2026)	Adaptive	Latent and timestep sensitivity	Residual reuse
DiCache (Bu et al., 2025)	Adaptive	First-block output change	Two-anchor prediction
TaylorSeer (Liu et al., 2025b)	Fixed	Uniform spacing	First-order Taylor prediction
HiCache (Feng et al., 2026)	Fixed	Uniform spacing	Second-order Hermite prediction
L2P (Shen et al., 2026)	Fixed	Uniform spacing	Learned causal linear prediction
DPCache (Cui et al., 2026)	Offline dynamic programming	Feature prediction error	Second-order feature prediction
BudCache (Lei et al., 2026)	Offline annealing	Final latent MSE	Residual reuse
MeanCache (Gao et al., 2026a)	Offline graph search	Interval-average velocity error	Interval-average velocity prediction
Our search experiments	Offline search	Final-output PSNR or LPIPS	Residual reuse

A.3 Aggregation and evaluation measures

For every model, method, cache ratio, dataset, and base seed, the accelerated output is compared with a full-compute output generated from the same prompt and seed. PSNR measures pixel error on a logarithmic scale. Higher values mean closer reconstruction. SSIM compares local luminance, contrast, and structure. Higher is better (Wang et al., 2004). LPIPS compares deep visual features. Lower is better (Zhang et al., 2018). For video, Δ_t compares the two videos’ changes between consecutive frames. For each video, we average LPIPS over all 64 adjacent frame pairs in its 65-frame sequence. We subtract the full-compute video’s average from the accelerated video’s average. A value closer to zero is better. CLIP Score measures text–image alignment and ImageReward is a learned preference score (Xu et al., 2023). CLIP Score uses image and text representations from CLIP (Radford et al., 2021). VBench evaluates semantic and temporal video quality.

Tables 7–10 report each dataset separately. Every result is first averaged over prompts within a base seed and then over the three base seeds. Bold marks the best unrounded mean within each dataset, cache ratio, and metric. For image experiments that reuse an adaptive method’s most frequent schedule, we compute confidence intervals for the mean PSNR difference by resampling prompts. We subtract the adaptive output’s PSNR from the PSNR of the output generated with the shared schedule on each run where the schedules differ, then average these differences over the retained seeds for each prompt.

A.4 Calibration, schedule search, and evaluation separation

Preparing predictors and fixed schedules. Image methods use a separate set of 50 prompts whose normalized texts do not overlap with the four image evaluation datasets. Video methods use 50 motion prompts that are separate from Penguin599 and VBench944. Each fitted predictor or calibration table is shared across datasets for the same model and method. DPCache and MeanCache construct one schedule per model and cache ratio on the preparation set and reuse it across evaluation datasets. BudCache follows the same model-level protocol, using two preparation prompts for FLUX and each video model and three for Qwen-Image. Each BudCache search runs one restart, 200 simulated-annealing proposals, and at most 20 local hill-climbing rounds. BudCache ranks candidate schedules by final latent MSE.

Calibrating the cache ratio. Adaptive image methods initially use the same 50 preparation prompts. For DiffusionDB, we calibrate the cache ratio using a separate set of 512 prompts whose normalized texts do not appear in the evaluation datasets. If the realized cache ratio drifts, we adjust the threshold once using cache counts from the evaluation data. For video, we use 48 prompts from each evaluation corpus. These prompts remain in the full 599-prompt and 944-prompt evaluations. Ratio calibration uses cache decisions and realized cache counts. The resulting threshold is fixed for each model, method, target ratio, and prompt distribution across its prompt–seed runs.

Selecting shared schedules. For SeaCache, TeaCache, SenCache, and DiCache, we shuffle the 1,632 PartiPrompts indices with seed 42 and split them into three equal subsets. We use the first subset of 544 prompts to select the most frequent schedule with exactly K cached steps for each model, method, and target ratio. We combine the schedules from all three base seeds, counting each prompt–seed run once. We evaluate its reuse on the other 1,088 prompts. The full 1,632-prompt result includes both selection and evaluation prompts. These schedules also enter the comparisons of schedules and approximation policies and provide initial candidates for the search in Section 6.

A.5 Complete per-model results

The following tables present each model separately, with results by method, dataset, target cache ratio, and quality metric. Dataset abbreviations are DB for DrawBench, PP for PartiPrompts, GE for GenEval-style, DDB for DiffusionDB-clean10k, P599 for Penguin599, and VB944 for VBench944. Method labels shorten SeaCache, TeaCache, SenCache, DiCache, TaylorSeer, HiCache, DPCache, BudCache, and MeanCache to Sea, Tea, Sen, Di, Tay, Hi, DP, Bud, and Mean. O1 and O2 are prediction orders. P, S, L, C, and IR denote PSNR, SSIM, LPIPS, CLIP, and ImageReward. The video tables add temporal-LPIPS change Δ_t and VBench score VB.

Table 7: Complete FLUX.1-dev results, averaged over three base seeds. P is PSNR in dB, S is SSIM, and L is LPIPS. C is CLIP score and IR is ImageReward. $\rho = K/50$ is the target cache ratio. Bold marks the best unrounded mean within each dataset, ratio, and metric.

Data	Method	$\rho = .58 (K = 29)$					$\rho = .74 (K = 37)$					$\rho = .82 (K = 41)$				
		P↑	S↑	L↓	C↑	IR↑	P↑	S↑	L↓	C↑	IR↑	P↑	S↑	L↓	C↑	IR↑
DB	Sea	27.208	.9066	.0845	27.619	.9983	21.435	.8006	.2114	27.627	.9897	19.407	.7365	.3078	27.621	.9537
DB	Tea	18.497	.7463	.2759	27.604	1.0032	16.868	.6880	.3628	27.657	.9765	15.458	.6307	.4590	27.531	.8569
DB	Sen	27.769	.9083	.0834	27.568	.9943	22.437	.7711	.2740	27.723	.8880	19.826	.6927	.3876	27.700	.8271
DB	Di	28.200	.9172	.0721	27.590	.9964	21.397	.7157	.3861	27.652	.7174	19.070	.6981	.4010	27.579	.7091
DB	Tay O1	21.442	.8250	.1713	27.521	.9812	17.571	.7194	.3017	27.516	.9893	14.275	.5709	.5221	27.204	.7305
DB	Hi O2	21.981	.8322	.1622	27.636	.9981	18.071	.7301	.2885	27.449	.9925	14.275	.5689	.5116	27.348	.7608
DB	L2P	22.742	.8460	.1481	27.662	1.0093	16.467	.6055	.4284	27.339	.7865	16.888	.5415	.5230	27.448	.6667
DB	DP	24.396	.8797	.1120	27.555	.9959	20.593	.7922	.2067	27.574	1.0199	17.025	.6815	.3500	27.755	.9887
DB	Bud	23.655	.8551	.1390	27.681	1.0027	22.553	.8165	.1934	27.657	.9879	20.099	.7352	.3153	27.607	.9082
DB	Mean	29.576	.9307	.0590	27.631	1.0034	23.930	.8449	.1507	27.653	.9968	19.939	.7058	.3364	27.947	.9198

Table 7: Continued.

Data	Method	$\rho = .58 (K = 29)$					$\rho = .74 (K = 37)$					$\rho = .82 (K = 41)$				
		P↑	S↑	L↓	C↑	IR↑	P↑	S↑	L↓	C↑	IR↑	P↑	S↑	L↓	C↑	IR↑
PP	Sea	27.608	.9091	.0836	27.459	1.1947	22.191	.8127	.2042	27.545	1.1816	20.065	.7444	.3047	27.681	1.1629
PP	Tea	19.206	.7632	.2610	27.439	1.2017	17.345	.7026	.3502	27.534	1.1822	15.745	.6411	.4522	27.533	1.1225
PP	Sen	27.878	.9092	.0849	27.459	1.1942	22.576	.7680	.2863	27.738	1.0673	20.201	.6927	.3926	27.600	1.0222
PP	Di	28.502	.9212	.0695	27.396	1.1986	21.480	.7105	.3978	27.542	.8851	19.461	.7048	.3998	27.754	.9303
PP	Tay O1	22.395	.8422	.1556	27.402	1.2018	18.098	.7325	.2916	27.424	1.1939	14.382	.5688	.5258	27.616	1.0275
PP	Hi O2	23.088	.8515	.1433	27.459	1.1995	18.705	.7473	.2724	27.487	1.1906	14.405	.5732	.5069	27.437	1.0118
PP	L2P	23.970	.8655	.1281	27.408	1.2022	17.225	.6260	.4123	27.488	1.0070	17.417	.5520	.5155	27.784	.9394
PP	DP	25.312	.8915	.1002	27.407	1.1963	21.370	.8091	.1916	27.428	1.2032	17.442	.6946	.3401	27.585	1.1889
PP	Bud	24.557	.8687	.1271	27.453	1.1928	23.132	.8238	.1913	27.558	1.1797	20.747	.7433	.3139	27.712	1.1079
PP	Mean	29.760	.9330	.0572	27.421	1.1990	24.482	.8507	.1475	27.470	1.1928	20.482	.7125	.3335	27.991	1.1287
GE	Sea	29.312	.9357	.0598	28.172	1.0007	22.606	.8424	.1749	28.204	.9935	20.275	.7843	.2617	28.306	.9843
GE	Tea	18.988	.7777	.2633	28.070	.9993	16.990	.7254	.3490	28.133	.9628	15.545	.6817	.4363	28.060	.8710
GE	Sen	29.885	.9410	.0549	28.177	1.0019	24.173	.8372	.1954	28.457	.9503	21.256	.7551	.3221	28.291	.9048
GE	Di	30.404	.9469	.0476	28.092	1.0031	23.006	.7765	.3251	28.540	.8533	20.296	.7663	.3143	28.489	.7990
GE	Tay O1	22.190	.8499	.1575	28.072	1.0075	17.892	.7538	.2831	27.978	.9919	14.208	.6031	.5080	27.841	.7577
GE	Hi O2	22.969	.8606	.1434	28.177	1.0163	18.507	.7658	.2671	28.126	1.0019	14.370	.6056	.5004	27.687	.7890
GE	L2P	23.906	.8738	.1289	28.139	1.0168	17.337	.6491	.4217	28.572	.8499	17.630	.5527	.5426	28.495	.7881
GE	DP	25.133	.8949	.1050	28.077	1.0023	21.392	.8234	.1893	28.043	1.0136	17.642	.7217	.3312	27.976	.9866
GE	Bud	25.109	.8895	.1109	28.161	1.0051	24.122	.8628	.1480	28.227	.9952	21.381	.7965	.2472	28.360	.9598
GE	Mean	31.808	.9559	.0382	28.135	1.0039	25.620	.8853	.1156	28.129	.9995	21.318	.7629	.2985	28.664	.9558
DDB	Sea	25.926	.8729	.1203	27.798	.9382	21.814	.7737	.2540	27.890	.9182	20.061	.7024	.3687	28.003	.8760
DDB	Tea	19.549	.7378	.2865	27.878	.9589	17.575	.6685	.3867	27.918	.9276	15.904	.6016	.4958	27.892	.8562
DDB	Sen	25.938	.8673	.1286	27.795	.9371	21.472	.7067	.3903	27.638	.6980	19.679	.6539	.4744	27.575	.6636
DDB	Di	26.351	.8813	.1092	27.784	.9520	20.452	.6541	.5161	26.548	.2812	18.948	.6550	.4928	27.534	.5655
DDB	Tay O1	22.372	.8180	.1805	27.797	.9644	18.385	.7056	.3215	27.895	.9743	14.985	.5656	.5262	27.687	.8925
DDB	Hi O2	22.851	.8243	.1719	27.839	.9589	19.007	.7202	.3032	27.927	.9611	15.051	.5782	.4997	27.789	.8787
DDB	L2P	23.611	.8396	.1551	27.822	.9607	17.253	.6039	.4143	27.074	.7824	17.501	.5650	.4964	27.373	.7281
DDB	DP	25.057	.8716	.1190	27.757	.9578	21.334	.7798	.2214	27.848	.9711	17.491	.6618	.3742	27.961	.9577
DDB	Bud	23.780	.8337	.1652	27.799	.9370	22.246	.7767	.2538	27.883	.9074	20.415	.6939	.3986	27.862	.7943
DDB	Mean	27.595	.8994	.0894	27.776	.9502	23.331	.8055	.1991	27.846	.9427	19.894	.6630	.3901	27.897	.8678

Table 8: Complete Qwen-Image results, averaged over three base seeds. P is PSNR in dB, S is SSIM, and L is LPIPS. C is CLIP score and IR is ImageReward. $\rho = K/50$ is the target cache ratio. Bold marks the best unrounded mean within each dataset, ratio, and metric.

Data	Method	$\rho = .58 (K = 29)$					$\rho = .74 (K = 37)$					$\rho = .82 (K = 41)$				
		P↑	S↑	L↓	C↑	IR↑	P↑	S↑	L↓	C↑	IR↑	P↑	S↑	L↓	C↑	IR↑
DB	Sea	27.437	.9192	.0765	29.226	1.2162	21.385	.8267	.1873	29.113	1.1725	16.778	.7007	.3526	29.002	1.1046
DB	Tea	20.363	.8218	.1796	29.217	1.2135	17.022	.7146	.3163	29.073	1.1344	14.457	.6162	.4615	28.793	.9185
DB	Sen	28.182	.9252	.0707	29.181	1.2186	21.825	.7634	.2641	28.768	1.0396	18.904	.7092	.3339	28.883	.9792
DB	Di	30.210	.9463	.0458	29.242	1.2233	20.468	.7283	.3225	28.722	.8573	17.205	.6562	.4084	28.381	.6534
DB	Tay O1	20.834	.8368	.1613	29.142	1.2188	13.984	.6163	.4399	28.220	.9413	9.680	.4308	.6760	26.485	.1029
DB	Hi O2	21.715	.8492	.1452	29.217	1.2171	13.804	.6039	.4531	28.229	.9149	8.099	.3894	.7636	23.437	-1.0827
DB	L2P	22.670	.8663	.1280	29.231	1.2178	18.737	.7491	.2724	29.049	1.1697	14.421	.5387	.5467	27.859	.6882
DB	DP	21.573	.8478	.1501	29.157	1.2300	17.533	.7366	.2776	29.043	1.1830	10.693	.4795	.6413	26.605	.3402
DB	Bud	29.627	.9343	.0651	29.211	1.2218	24.417	.8464	.1719	29.196	1.1759	19.320	.7564	.2829	29.129	1.1238
DB	Mean	32.051	.9530	.0438	29.206	1.2206	24.911	.8608	.1295	29.067	1.1967	19.869	.7234	.2873	29.292	1.1085
PP	Sea	28.278	.9304	.0667	28.546	1.3633	22.109	.8431	.1715	28.641	1.3441	17.284	.7148	.3315	28.669	1.2760
PP	Tea	21.210	.8419	.1600	28.563	1.3607	17.555	.7273	.2968	28.597	1.3015	14.632	.6177	.4547	28.453	1.0761
PP	Sen	28.569	.9320	.0657	28.537	1.3600	21.894	.7631	.2717	28.538	1.2045	19.140	.7147	.3370	28.511	1.1438
PP	Di	30.705	.9527	.0399	28.510	1.3694	20.452	.7211	.3415	28.322	.9587	17.249	.6566	.4181	28.148	.7717
PP	Tay O1	21.804	.8576	.1404	28.525	1.3736	14.300	.6318	.4267	27.982	1.1453	9.614	.4303	.6730	26.636	.3364
PP	Hi O2	22.787	.8697	.1247	28.572	1.3718	14.161	.6168	.4358	28.019	1.0993	8.312	.3945	.7520	23.397	-1.0213
PP	L2P	23.639	.8839	.1105	28.503	1.3745	19.386	.7685	.2568	28.605	1.3477	14.588	.5532	.5376	28.123	.8367
PP	DP	22.210	.8625	.1358	28.483	1.3733	17.837	.7478	.2673	28.403	1.3610	10.685	.4830	.6348	26.687	.5402
PP	Bud	30.127	.9407	.0603	28.560	1.3596	24.852	.8529	.1709	28.598	1.3197	19.966	.7693	.2721	28.635	1.2860
PP	Mean	32.522	.9573	.0408	28.537	1.3650	25.552	.8694	.1255	28.502	1.3497	20.330	.7317	.2824	28.959	1.2983
GE	Sea	30.394	.9426	.0454	30.661	1.3485	23.880	.8663	.1273	30.716	1.3440	19.674	.7783	.2360	30.703	1.3316

Table 8: Continued.

Data	Method	$\rho = .58 (K = 29)$					$\rho = .74 (K = 37)$					$\rho = .82 (K = 41)$				
		P $\uparrow$	S $\uparrow$	L $\downarrow$	C $\uparrow$	IR $\uparrow$	P $\uparrow$	S $\uparrow$	L $\downarrow$	C $\uparrow$	IR $\uparrow$	P $\uparrow$	S $\uparrow$	L $\downarrow$	C $\uparrow$	IR $\uparrow$
GE	Tea	22.771	.8645	.1231	30.673	1.3530	19.159	.7685	.2219	30.654	1.3425	16.106	.6762	.3635	30.318	1.2631
GE	Sen	30.704	.9454	.0430	30.679	1.3481	23.889	.8014	.1878	30.593	1.2997	20.832	.7569	.2421	30.582	1.2861
GE	Di	32.853	.9643	.0238	30.626	1.3521	22.341	.7669	.2347	30.517	1.2335	18.473	.7086	.3183	30.256	1.1117
GE	Tay O1	23.087	.8772	.1127	30.564	1.3569	14.594	.6565	.4135	29.430	1.0941	9.477	.4527	.6678	27.930	.3777
GE	Hi O2	24.198	.8881	.0963	30.675	1.3568	14.876	.6642	.4027	29.622	1.0983	8.615	.4372	.7350	25.432	-.7869
GE	L2P	25.272	.9040	.0805	30.602	1.3558	20.597	.7904	.2241	30.270	1.3399	14.596	.5441	.5693	29.439	.8622
GE	DP	24.324	.8913	.0954	30.520	1.3590	19.895	.7951	.1994	30.269	1.3605	11.678	.5500	.5842	28.647	.8084
GE	Bud	32.154	.9501	.0400	30.664	1.3449	26.887	.8724	.1177	30.711	1.3334	21.265	.7930	.2034	30.724	1.3289
GE	Mean	34.465	.9635	.0267	30.624	1.3481	27.713	.8888	.0854	30.504	1.3437	21.920	.7589	.2414	30.828	1.2910
DDB	Sea	26.216	.9127	.0945	29.805	1.3186	21.109	.8197	.2183	29.782	1.2883	16.290	.6615	.4168	29.463	1.1681
DDB	Tea	20.502	.8193	.1988	29.806	1.3158	16.873	.6920	.3553	29.592	1.2228	12.790	.5344	.5877	28.185	.6855
DDB	Sen	26.272	.9118	.0979	29.792	1.3128	20.280	.7299	.3582	29.117	1.0921	17.777	.6747	.4391	28.982	.9865
DDB	Di	27.706	.9315	.0688	29.782	1.3252	18.663	.6685	.4783	28.074	.6158	15.893	.5974	.5480	27.717	.4255
DDB	Tay O1	20.865	.8301	.1806	29.816	1.3310	13.746	.5959	.4563	29.231	1.1502	9.174	.3992	.7005	26.439	.2964
DDB	Hi O2	21.745	.8465	.1615	29.846	1.3281	13.127	.5651	.4882	29.025	1.0891	7.455	.3496	.8208	20.746	-1.2761
DDB	L2P	21.738	.8402	.1690	29.770	1.3264	18.522	.7354	.2989	29.438	1.2569	13.777	.5099	.5481	27.087	.5743
DDB	DP	20.985	.8309	.1809	29.810	1.3302	16.886	.6965	.3332	29.688	1.2888	9.942	.4216	.6860	26.219	.2505
DDB	Bud	27.898	.9265	.0850	29.809	1.3140	23.236	.8303	.2279	29.729	1.2566	19.197	.7456	.3406	29.680	1.2146
DDB	Mean	29.900	.9456	.0603	29.786	1.3191	23.606	.8443	.1724	29.605	1.2913	18.776	.6865	.3482	29.165	1.1818

Table 9: Complete HunyuanVideo results, averaged over three base seeds. P is PSNR in dB, S is SSIM, and L is LPIPS. Δ_t is temporal LPIPS for the cached video minus that for the full-compute video. Values closer to zero are better. VB is the VBench score, reported only on VB944. $\rho = K/50$ is the target cache ratio. Bold marks the best unrounded mean within each dataset, ratio, and metric.

Data	Method	$\rho = .58 (K = 29)$					$\rho = .74 (K = 37)$					$\rho = .82 (K = 41)$				
		P $\uparrow$	S $\uparrow$	L $\downarrow$	Δ_t	VB $\uparrow$	P $\uparrow$	S $\uparrow$	L $\downarrow$	Δ_t	VB $\uparrow$	P $\uparrow$	S $\uparrow$	L $\downarrow$	Δ_t	VB $\uparrow$
P599	Sea	29.36	.8954	.0725	-.00141	-	-23.26	.7756	.1891	-.00101	-	-19.40	.6771	.3171	-.00495	-
P599	Tea	23.18	.7800	.1726	+.00190	-	-19.18	.6713	.2952	+.00531	-	-17.80	.6217	.3760	+.00732	-
P599	Sen	30.60	.9093	.0630	-.00208	-	-24.91	.7908	.1919	-.00335	-	-21.65	.7058	.2877	+.00027	-
P599	Di	31.82	.9241	.0471	-.00042	-	-22.24	.6910	.3632	-.00650	-	-20.19	.6631	.3947	-.00340	-
P599	Bud	30.92	.9123	.0658	-.00281	-	-25.07	.7837	.2133	-.00396	-	-22.13	.7052	.3253	-.00386	-
P599	Mean	33.47	.9382	.0401	-.00225	-	-27.58	.8544	.1421	-.00574	-	-23.12	.7600	.2569	-.00666	-
P599	Tay O1	23.24	.7880	.1641	-.00019	-	-18.40	.6611	.2943	-.00099	-	-15.11	.5508	.4458	-.00336	-
P599	Hi O2	23.81	.7947	.1571	+.00084	-	-20.05	.6974	.2566	+.00227	-	-17.43	.6129	.3627	+.00396	-
P599	L2P	23.95	.7983	.1567	+.00107	-	-20.91	.7220	.2380	+.00247	-	-19.33	.6711	.3081	+.00455	-
VB944	Sea	29.74	.9012	.0718	-.00100	.8077	23.17	.7790	.1926	-.00066	.8051	19.52	.6833	.3178	-.00264	.7929
VB944	Tea	22.84	.7754	.1874	+.00131	.8106	19.10	.6689	.3097	+.00419	.8064	17.82	.6250	.3884	+.00583	.7885
VB944	Sen	31.25	.9187	.0585	-.00139	.8071	25.37	.8093	.1790	-.00197	.7929	21.64	.7166	.2889	+.00041	.7830
VB944	Di	32.54	.9318	.0445	-.00034	.8084	22.63	.7104	.3581	-.00318	.7254	20.36	.6780	.4013	-.00235	.7158
VB944	Bud	31.79	.9238	.0584	-.00192	.8078	25.55	.8029	.2011	-.00228	.7872	22.31	.7216	.3243	-.00221	.7542
VB944	Mean	34.34	.9457	.0365	-.00151	.8069	28.09	.8669	.1336	-.00364	.7975	23.16	.7699	.2584	-.00439	.7803
VB944	Tay O1	23.09	.7872	.1741	-.00050	.8100	18.74	.6704	.2955	-.00189	.8018	16.02	.5759	.4192	-.00402	.7820
VB944	Hi O2	23.55	.7927	.1688	+.00043	.8108	20.07	.7017	.2653	+.00099	.8032	17.91	.6301	.3594	+.00108	.7908
VB944	L2P	23.59	.7934	.1710	+.00085	.8105	20.56	.7163	.2569	+.00213	.8069	19.17	.6701	.3236	+.00373	.7991

Table 10: Complete Wan2.1 results, averaged over three base seeds. P is PSNR in dB, S is SSIM, and L is LPIPS. Δ_t is temporal LPIPS for the cached video minus that for the full-compute video. Values closer to zero are better. VB is the VBench score, reported only on VB944. $\rho = K/50$ is the target cache ratio. Bold marks the best unrounded mean within each dataset, ratio, and metric.

Data	Method	$\rho = .58 (K = 29)$					$\rho = .74 (K = 37)$					$\rho = .82 (K = 41)$				
		P $\uparrow$	S $\uparrow$	L $\downarrow$	Δ_t	VB $\uparrow$	P $\uparrow$	S $\uparrow$	L $\downarrow$	Δ_t	VB $\uparrow$	P $\uparrow$	S $\uparrow$	L $\downarrow$	Δ_t	VB $\uparrow$
P599	Sea	26.96	.8732	.0885	-.00245	-	-21.72	.7452	.2041	-.00094	-	-18.31	.6408	.3235	+.00401	-
P599	Tea	23.32	.8080	.1376	-.00082	-	-21.35	.7480	.2046	-.00191	-	-18.76	.6414	.3516	+.00318	-
P599	Sen	26.57	.8733	.0889	-.00156	-	-22.42	.7302	.2262	+.00173	-	-19.61	.6382	.3332	+.01492	-
P599	Di	26.83	.8824	.0744	-.00078	-	-20.43	.7319	.2129	-.00057	-	-18.44	.6381	.3612	+.00029	-
P599	Bud	24.23	.8282	.1216	-.00182	-	-22.86	.7673	.1897	-.00202	-	-20.36	.6742	.2956	+.00479	-

Table 10: Continued.

Data	Method	$\rho = .58 (K = 29)$					$\rho = .74 (K = 37)$					$\rho = .82 (K = 41)$				
		P $\uparrow$	S $\uparrow$	L $\downarrow$	Δ_t	VB $\uparrow$	P $\uparrow$	S $\uparrow$	L $\downarrow$	Δ_t	VB $\uparrow$	P $\uparrow$	S $\uparrow$	L $\downarrow$	Δ_t	VB $\uparrow$
P599	Mean	30.68	.9275	.0464	-.00234	-22.77	.7887	.1601	+.00293	-18.13	.6391	.3218	+.01160	-	-	-
P599	Tay O1	17.92	.6571	.2821	+.00092	-13.27	.4916	.4962	+.00120	-10.75	.4038	.6442	+.00608	-	-	-
P599	Hi O2	19.57	.7039	.2332	-.00038	-16.14	.5835	.3808	-.00112	-13.43	.4898	.5353	-.00306	-	-	-
P599	L2P	20.10	.7213	.2151	+.00061	-17.81	.6377	.3024	+.00927	-14.00	.4642	.5015	+.06617	-	-	-
VB944	Sea	27.19	.8872	.0745	-.00085	.7996	21.18	.7511	.1927	+.00099	.7952	17.53	.6383	.3221	+.00595	.7816
VB944	Tea	22.95	.8201	.1268	-.00015	.8042	20.94	.7599	.1906	-.00038	.7976	18.35	.6508	.3340	+.00597	.7533
VB944	Sen	26.97	.8922	.0720	-.00063	.8007	22.42	.7455	.1981	+.00432	.7826	19.32	.6506	.3064	+.01514	.7484
VB944	Di	27.24	.9013	.0592	-.00042	.8040	20.09	.7483	.1962	-.00001	.7986	18.07	.6511	.3370	+.00297	.7345
VB944	Bud	23.90	.8390	.1112	-.00066	.8025	22.63	.7796	.1703	+.00055	.7949	19.97	.6836	.2736	+.00751	.7699
VB944	Mean	31.33	.9399	.0362	-.00136	.8052	22.87	.8100	.1389	+.00294	.7869	17.82	.6545	.3033	+.01056	.7374
VB944	Tay O1	17.46	.6708	.2729	+.00059	.8051	13.41	.5192	.4744	+.00309	.7784	11.07	.4300	.6208	+.01202	.6899
VB944	Hi O2	18.84	.7089	.2311	-.00002	.8083	15.90	.6020	.3673	+.00009	.7976	13.57	.5149	.5135	+.00121	.7474
VB944	L2P	19.28	.7218	.2173	+.00079	.8068	17.25	.6461	.3002	+.00741	.7848	13.89	.4849	.4862	+.05478	.6661

A.6 Cache-ratio alignment

The six fixed-schedule image methods execute exactly K cached steps. The four adaptive methods choose full and cached steps for each prompt–seed run and are calibrated toward the same target mean. Tables 11 and 12 report their realized mean cache counts separately for every dataset represented in the complete quality tables.

Table 11: FLUX.1-dev mean realized cache counts for the four adaptive methods.

Dataset	Method	$K_{\text{tgt}} = 29$	$K_{\text{tgt}} = 37$	$K_{\text{tgt}} = 41$
DrawBench	SeaCache	28.998	37.000	41.000
DrawBench	TeaCache	29.013	36.917	40.993
DrawBench	SenCache	28.718	37.000	40.793
DrawBench	DiCache	28.668	37.000	41.000
Parti	SeaCache	28.991	37.000	41.000
Parti	TeaCache	29.021	36.864	40.989
Parti	SenCache	28.757	36.999	40.825
Parti	DiCache	28.716	37.000	41.000
GenEval	SeaCache	28.997	37.000	41.000
GenEval	TeaCache	29.010	36.903	40.987
GenEval	SenCache	28.457	37.000	40.731
GenEval	DiCache	28.558	36.999	41.000
DiffusionDB	SeaCache	28.991	37.000	41.000
DiffusionDB	TeaCache	29.023	36.854	40.994
DiffusionDB	SenCache	29.093	37.000	40.912
DiffusionDB	DiCache	28.823	37.000	41.000

The realized means remain close to their targets, but adaptive methods do not always execute exactly the target cache ratio. The largest image deviation is 0.543 cached steps for FLUX SenCache on GenEval-style at target 29. Tables 11–14 give the realized cache counts for each quality comparison.

A.7 Online Runtime and Offline Preparation Cost

The online and offline costs answer different questions. Online latency is paid for every generated sample. Calibration, predictor fitting, and schedule search are one-time costs that can be amortized over later generations. We therefore report them separately.

Table 12: Qwen-Image mean realized cache counts for the four adaptive methods.

Dataset	Method	$K_{\text{tgt}} = 29$	$K_{\text{tgt}} = 37$	$K_{\text{tgt}} = 41$
DrawBench	SeaCache	29.003	37.003	41.000
DrawBench	TeaCache	29.000	37.195	40.875
DrawBench	SenCache	28.915	37.000	41.000
DrawBench	DiCache	28.932	37.000	41.000
Parti	SeaCache	29.002	37.002	41.000
Parti	TeaCache	28.999	37.175	40.894
Parti	SenCache	28.925	37.000	41.000
Parti	DiCache	28.944	37.000	41.000
GenEval	SeaCache	29.000	36.998	41.000
GenEval	TeaCache	29.000	37.051	40.827
GenEval	SenCache	28.993	37.000	41.000
GenEval	DiCache	28.879	37.000	41.000
DiffusionDB	SeaCache	29.001	37.001	41.000
DiffusionDB	TeaCache	29.000	37.238	41.000
DiffusionDB	SenCache	28.964	37.000	41.000
DiffusionDB	DiCache	28.995	37.000	41.000

Table 13: HunyuanVideo mean realized cache counts for the four adaptive methods.

Dataset	Method	$K_{\text{target}} = 29$	$K_{\text{target}} = 37$	$K_{\text{target}} = 41$
Penguin599	SeaCache	29.042	37.000	41.000
Penguin599	TeaCache	28.053	36.534	41.019
Penguin599	SenCache	28.959	36.000	40.853
Penguin599	DiCache	28.710	37.000	41.000
VBench944	SeaCache	29.019	37.000	41.000
VBench944	TeaCache	28.055	36.687	41.019
VBench944	SenCache	28.965	36.000	40.884
VBench944	DiCache	28.659	37.000	41.000

Table 14: Wan2.1 mean realized cache counts for the four adaptive methods.

Dataset	Method	$K_{\text{target}} = 29$	$K_{\text{target}} = 37$	$K_{\text{target}} = 41$
Penguin599	SeaCache	29.973	37.018	40.000
Penguin599	TeaCache	29.000	36.000	41.000
Penguin599	SenCache	28.975	37.000	41.010
Penguin599	DiCache	28.954	36.900	41.000
VBench944	SeaCache	29.956	37.007	40.000
VBench944	TeaCache	29.000	36.000	41.000
VBench944	SenCache	28.871	36.999	41.004
VBench944	DiCache	28.925	36.867	41.000

The image benchmark uses one H100 per image and a batch size of one. Each model–method–ratio configuration uses the same 16 prompts at base seed 314159. The first four prompt indices are excluded as warm-up, and latency is the arithmetic mean over the other 12 prompt–seed runs. These are 12 different prompts. Timing includes prompt encoding, denoising, VAE decoding, and conversion to an image. It excludes model loading and image-file saving. GPU work is synchronized before and after the timed

computation. Speedup divides the full-compute mean latency by the accelerated mean.

Video latency is measured during generation on H100 GPUs at batch size one. Each configuration generates one video for each prompt–seed run, giving 599 videos per Penguin599 base seed and 944 per VBench944 base seed. Timing includes prompt encoding, denoising, decoding, and output-file saving. It excludes model loading. The first video of each generation worker is excluded as warm-up. We average the retained per-video times within each dataset and base seed, then give the six dataset–seed means equal weight. The image and video timings therefore use different sample populations and timing boundaries. Tables 15–18 give the four online latency tables.

Table 15: Generation is faster with caching on FLUX.1-dev. Columns specify the target cache count K . Each entry gives the mean time in seconds per image, followed by the speedup relative to full-compute generation. Full-compute generation takes 10.19 s per image. We average 12 H100 measurements after excluding four initial samples.

Method	$K = 29$	$K = 37$	$K = 41$
SeaCache	4.81 / 2.12×	3.26 / 3.13×	2.51 / 4.06×
TeaCache	4.73 / 2.15×	3.16 / 3.22×	2.45 / 4.17×
SenCache	4.74 / 2.15×	3.19 / 3.20×	2.45 / 4.15×
DiCache	4.89 / 2.08×	3.34 / 3.05×	2.61 / 3.91×
TaylorSeer O1	5.42 / 1.88×	4.00 / 2.55×	3.31 / 3.08×
HiCache O2	5.86 / 1.74×	4.55 / 2.24×	3.88 / 2.63×
L2P	4.68 / 2.18×	3.17 / 3.21×	2.40 / 4.24×
DPCache	4.71 / 2.16×	3.16 / 3.22×	2.41 / 4.23×
BudCache	4.69 / 2.17×	3.15 / 3.23×	2.37 / 4.29×
MeanCache	4.69 / 2.17×	3.15 / 3.23×	2.40 / 4.25×

Table 16: Generation is faster with caching on Qwen-Image. Columns specify the target cache count K . Each entry gives the mean time in seconds per image, followed by the speedup relative to full-compute generation. Full-compute generation takes 33.45 s per image. We average 12 H100 measurements after excluding four initial samples.

Method	$K = 29$	$K = 37$	$K = 41$
SeaCache	14.79 / 2.26×	9.48 / 3.53×	6.84 / 4.89×
TeaCache	14.67 / 2.28×	9.30 / 3.60×	6.68 / 5.00×
SenCache	14.58 / 2.29×	9.36 / 3.57×	6.66 / 5.02×
DiCache	14.85 / 2.25×	9.73 / 3.44×	7.11 / 4.71×
TaylorSeer O1	17.62 / 1.90×	12.95 / 2.58×	10.59 / 3.16×
HiCache O2	19.76 / 1.69×	15.40 / 2.17×	13.13 / 2.55×
L2P	14.48 / 2.31×	9.20 / 3.64×	6.61 / 5.06×
DPCache	14.46 / 2.31×	9.21 / 3.63×	6.59 / 5.08×
BudCache	14.59 / 2.29×	9.33 / 3.58×	6.69 / 5.00×
MeanCache	14.52 / 2.30×	9.23 / 3.63×	6.63 / 5.05×

Offline preparation is paid once per model. SeaCache, DiCache, TaylorSeer, and HiCache do not fit model-specific predictors. TeaCache uses published coefficients on FLUX.1-dev and requires no additional coefficient fitting there. BudCache runs the largest search. It evaluates 179 to 727 candidate schedules per cache count on the image models, which takes 0.19 to 1.65 H100 hours on FLUX.1-dev and 0.91 to 5.82 hours on Qwen-Image. On the video models it evaluates 162 to 446 schedules, which takes 4.8 to 18.3 RTX 6000 Pro GPU hours on HunyuanVideo and 1.4 to 8.2 H100 hours on Wan2.1. The other fitted methods are cheaper. SenCache, L2P, and MeanCache take 2.5 to 7.2 RTX 6000 Pro GPU hours on HunyuanVideo and 1.8 to 2.9 H100 hours on Wan2.1. Image calibration for these methods and DPCache uses 50 prompts. Comparable preparation times were recorded only for the video implementations. Calibrating adaptive

Table 17: Generation is faster with caching on HunyuanVideo. Columns specify the target cache count K . Each entry gives the mean time in seconds per video, followed by the speedup relative to full-compute generation. Full-compute generation takes 103.49 s per video. H100 measurements include writing the video file. We exclude each worker’s first video.

Method	$K = 29$	$K = 37$	$K = 41$
SeaCache	47.64 / 2.17×	32.24 / 3.21×	24.50 / 4.22×
TeaCache	49.26 / 2.10×	32.99 / 3.14×	24.20 / 4.28×
SenCache	47.36 / 2.19×	33.78 / 3.06×	24.32 / 4.25×
DiCache	48.97 / 2.11×	33.17 / 3.12×	25.72 / 4.02×
TaylorSeer O1	49.68 / 2.08×	34.53 / 3.00×	26.98 / 3.84×
HiCache O2	50.83 / 2.04×	35.72 / 2.90×	28.14 / 3.68×
L2P	47.25 / 2.19×	31.78 / 3.26×	24.31 / 4.26×
BudCache	47.26 / 2.19×	31.86 / 3.25×	24.09 / 4.30×
MeanCache	47.25 / 2.19×	31.75 / 3.26×	24.02 / 4.31×

Table 18: Generation is faster with caching on Wan2.1. Columns specify the target cache count K . Each entry gives the mean time in seconds per video, followed by the speedup relative to full-compute generation. Full-compute generation takes 74.98 s per video. H100 measurements include writing the video file. We exclude each worker’s first video.

Method	$K = 29$	$K = 37$	$K = 41$
SeaCache	32.66 / 2.30×	22.64 / 3.31×	18.42 / 4.07×
TeaCache	33.74 / 2.22×	23.77 / 3.15×	16.75 / 4.48×
SenCache	33.76 / 2.22×	22.34 / 3.36×	16.66 / 4.50×
DiCache	35.38 / 2.12×	24.48 / 3.06×	18.91 / 3.96×
TaylorSeer O1	37.21 / 2.02×	26.29 / 2.85×	20.91 / 3.58×
HiCache O2	38.81 / 1.93×	27.93 / 2.68×	22.44 / 3.34×
L2P	33.69 / 2.23×	22.31 / 3.36×	16.69 / 4.49×
BudCache	33.71 / 2.22×	22.42 / 3.34×	16.75 / 4.48×
MeanCache	33.67 / 2.23×	22.28 / 3.37×	16.66 / 4.50×

methods to the target cache ratios is the largest offline cost for the evaluated video methods: 67.5 H100 hours for HunyuanVideo and 68.0 hours for Wan2.1. RTX 6000 Pro hours are not converted to H100 hours.

The exhaustive schedule search of Appendix B.5 is far larger than any of these. It generated 5,483,016 cached images. At the 2.37 seconds per image measured for a fixed schedule with residual reuse at $K = 41$ on FLUX.1-dev in Table 15, that is about 3,600 H100 hours.

B Additional Evidence for Shared Schedules

B.1 Schedule-distribution statistics

The image study comprises 891,720 prompt–seed runs across 96 combinations of method, model, dataset, and cache ratio. The number of unique schedules ranges from 2 to 62 per combination, with a median of 11 across the 96 combinations. Across these 96 combinations, the fraction of runs using one of the three most frequent schedules has a median of 89.8% and a range of 40.7–100%. The same schedule is most frequent under all three seeds in 85 of the 96 image combinations.

We compute schedule frequencies from the exact sequences of 50 full or cached decisions, combining the three base seeds within each model, dataset, cache ratio, and method. If schedule u occurs on a fraction $p(u)$ of runs, the effective schedule count is $\exp[-\sum_u p(u) \log p(u)]$. It is the number of equally frequent schedules with the same entropy. For example, if all observed schedules are equally frequent, their effective count equals their unique count.

Table 19: Schedules chosen by the four adaptive image methods. Within each model, dataset, and target cache ratio, we combine the three seeds and compute schedule frequencies. Top- r is the fraction of runs using one of the r most frequent schedules within that combination. The table averages these fractions equally over 24 combinations, each with 600 to 30,000 prompt-seed runs. Unique and effective counts are averaged over the same combinations, with their minimum and maximum in brackets. Runs gives the total across combinations.

Method	Runs	Unique	Effective	Top-1	Top-3	Top-10
SeaCache	222,930	8.75 [2,18]	2.23 [1.04,3.77]	0.746	0.960	0.9996
TeaCache	222,930	18.25 [3,62]	5.56 [1.60,13.75]	0.456	0.778	0.9752
SenCache	222,930	10.46 [3,25]	3.99 [1.23,8.64]	0.561	0.857	0.9918
DiCache	222,930	16.46 [5,51]	5.55 [2.28,12.89]	0.426	0.777	0.9811

The most frequent schedule of an image method is identical across all four image datasets in five of six model-ratio combinations for SeaCache. The counts are four of six for SenCache, two of six for TeaCache, and one of six for DiCache. On video, the same schedule is most frequent under all three base seeds in 46 of 48 model-method-dataset-ratio combinations. The two disagreements are TeaCache on HunyuanVideo VBench944 at cache ratio 0.58 and SenCache on Wan2.1 Penguin599 at cache ratio 0.74. Across the two video models, the most frequent schedules differ at 4 to 23 step positions. The two video datasets share the most frequent schedule in 18 of the 24 model-method-ratio combinations.

The four datasets have different sample sizes, which affects their unique schedule counts in Table 19. Top- r frequencies and effective-count summaries are more directly comparable across datasets.

Each method contributes 222,930 prompt-seed runs across 24 combinations. Each model-dataset-ratio combination contains 600 runs for DrawBench, 1,659 for GenEval, 4,896 for PartiPrompts, or 30,000 for DiffusionDB. These combinations receive equal weight in the summary, regardless of their size.

Schedule concentration varies across methods. SeaCache has the smallest mean effective count, 2.23, followed by SenCache at 3.99. TeaCache and DiCache average 5.56 and 5.55 effective schedules, respectively. The broadest observed combination has 13.75 effective schedules. The schedule-reuse experiment in Section 3.1 evaluates each method’s most frequent schedule on new prompts.

Fixed schedules can also differ between models. Replacing HunyuanVideo with Wan2.1 changes the BudCache schedule by 22, 12, and 6 steps at cache ratios 0.58, 0.74, and 0.82. The corresponding MeanCache changes are 18, 8, and 0 steps. MeanCache therefore uses the same schedule on both models at cache ratio 0.82.

B.2 Reusing adaptive schedules on images

We compare SeaCache, TeaCache, SenCache, and DiCache with fixed reuse of their most frequent schedules. Each model-method-ratio combination uses 1,632 prompts under three seeds, giving 4,896 prompt-seed runs. We select the most frequent schedule on 544 prompts and evaluate its reuse on the remaining 1,088 prompts. For each run, we subtract the adaptive output’s PSNR from the PSNR of the output generated with the fixed schedule and the same approximation policy. Runs with identical schedules have zero difference, so the results below use only runs where the two schedules differ.

We first report mean quality changes across the 24 model-method-ratio combinations. Using all prompts gives 54 to 4,313 retained runs per combination. The mean PSNR differences range from -0.79 to $+1.60$ dB, where positive values favor the fixed schedule. The median absolute difference in mean PSNR is 0.09 dB. Restricting evaluation to the 1,088 prompts excluded from selection gives 34 to 2,901 retained runs per combination. On these prompts, the mean PSNR differences range from -0.81 to $+1.56$ dB, with a median absolute difference in mean PSNR of 0.10 dB.

We separately measure the size of the change within individual runs. For each combination, we take the

absolute PSNR difference on each retained run from the 1,088 evaluation prompts and report the median. These 24 medians range from 0.00 to 1.53 dB, with a median of 0.08 dB. Tables 20 and 21 report the combined-seed and per-seed results.

Table 20 gives 95% confidence intervals for the mean PSNR differences on prompts excluded from selection. We first average each prompt’s PSNR differences over the seeds where its adaptive and fixed schedules differ, then resample prompts 20,000 times. Each resampled mean weights a prompt by its number of retained runs, matching the reported mean paired difference. The interval spans the 2.5th to 97.5th percentiles of these resampled means. Twenty-two of the 24 intervals exclude zero. The two that do not are Qwen-Image DiCache at $K = 29$ and Qwen-Image SeaCache at $K = 37$, the latter containing 34 runs.

The lower block of Table 20 replaces the fixed schedule with a random schedule of the same K , on the same held-out runs where the fixed and adaptive schedules differ. We draw each random schedule’s K cached steps uniformly without replacement from steps 3–48, leaving steps 0, 1, 2, and 49 full. Each random schedule uses the approximation policy of the method it is compared against: residual reuse for SeaCache, SenCache, and TeaCache, and the two-anchor extrapolation for DiCache. There are five draws per model at $K = 29$ and $K = 37$ and two at $K = 41$. The first two draws at each cache count use three seeds. The remaining draws at $K = 29$ and $K = 37$ use only base seed 42. For each paired run, we subtract the adaptive output’s PSNR from the random schedule output’s PSNR. We report the median of these differences across draws, models, cache counts, available seeds, and evaluation prompts where the adaptive and fixed schedules differ. A prompt can contribute to several draws and seeds. The median paired PSNR difference is negative for SeaCache, SenCache, and DiCache. For TeaCache, the random schedules have higher PSNR but lower SSIM and higher LPIPS than the adaptive schedules.

B.3 Reusing adaptive schedules on videos

The video comparison covers the same four methods. Each comparison contains 150 prompts from each of Penguin599 and VBench944, with one seed per prompt. Both models use the first 150 prompts in each dataset’s evaluation list, ordered by the SHA-256 hash of the prompt text. For Penguin599, we apply Unicode NFKC normalization, lowercase the text, remove leading and trailing whitespace, and replace internal runs of whitespace with a single space before hashing. For VBench944, we hash the original text. Both use UTF-8 encoding. Generation uses the original prompt text.

For each model, method, and target cache ratio, we combine schedule counts from both datasets and all three base seeds, counting each prompt–seed run once. We choose the most frequent schedule with exactly K cached steps. If no schedule has that cache count, we choose the most frequent schedule across all cache counts. Restricting selection to prompts outside the 300 evaluation prompts, excluding those prompts under all three seeds, gives the same schedule in all 24 model–method–ratio combinations. Of the 24 model–method–ratio combinations, three have a fixed schedule whose cache count differs from the target. In two other combinations, the adaptive method already follows the fixed schedule on every evaluation prompt. Table 22 separates these groups. We compare mean PSNR on prompts with different schedules in the remaining 19 combinations. The fixed schedule’s mean PSNR is at most 0.25 dB lower than the adaptive method’s in 17 of them. The two exceptions are SenCache on HunyuanVideo at ratio 0.58 and SenCache on HunyuanVideo at ratio 0.82. Table 23 gives the Penguin599 and VBench944 results separately.

The video random control uses uniformly sampled schedules with the same cache ratio and residual-reuse approximation policy. For each model and cache ratio, we draw two schedules by sampling the K cached steps uniformly without replacement from steps 3–48. Steps 0, 1, 2, and 49 remain full. We compare them with SeaCache, TeaCache, and SenCache on both video models. For each paired run, we subtract the adaptive output’s PSNR from the random-schedule output’s PSNR. For each model and method, we take the median of these differences across random draws, cache ratios, dataset-specific base seeds, and prompts. A prompt can contribute to several draws and cache ratios. The six medians range from -5.9 to -0.3 dB, favoring

Table 20: Replacing adaptive schedules with one fixed schedule changes mean PSNR by -0.81 to $+1.56$ dB on new prompts where the schedules differ. We select the fixed schedule on 544 prompts and reuse it with the adaptive method’s approximation policy. m is the fraction of prompt–seed runs on which the adaptive method already used the fixed schedule. n_{off} counts runs on which the adaptive method follows another schedule. For each run, we obtain ΔP by subtracting the adaptive method’s output PSNR from the fixed schedule’s output PSNR on the same prompt and seed. $\overline{\Delta P}$ is the mean of these differences over the n_{off} runs. Each model–method–ratio combination uses 1,632 prompts under three base seeds, or 4,896 runs. The held-out columns use the 1,088 prompts not used for schedule selection. All PSNR differences are in dB. Positive differences favor the fixed schedule. The 95% interval belongs to $\overline{\Delta P}^{\text{held}}$ and is given to three decimals. It comes from resampling prompts and keeping each prompt’s runs together, using only runs where the schedules differ. Prompt means are weighted by these run counts. The final column is the median $|\Delta P|$ over the $n_{\text{off}}^{\text{held}}$ runs. Table 19 in Appendix B.1 reports a larger fraction for the same methods because it averages over four image datasets and counts the most frequent schedule whatever its cache count, while m counts one schedule that caches exactly K steps on PartiPrompts. The lower block replaces the fixed schedule with random schedules of the same K . For each random schedule, we retain its available held-out runs where the adaptive method’s schedule differs from the selected fixed schedule. Each retained run contributes one paired evaluation for that random schedule. We subtract the adaptive method’s output PSNR from each random schedule’s output PSNR. The median and minimum-to-maximum range summarize these differences across random schedules, models, and cache ratios.

Method	K	m (%)	n_{off}	$\overline{\Delta P}$	$n_{\text{off}}^{\text{held}}$	$\overline{\Delta P}^{\text{held}}$	95% interval	Med. $ \Delta P ^{\text{held}}$
FLUX.1-dev								
SeaCache	29	85.7	699	-0.07	461	-0.07	$[-0.104, -0.046]$	0.06
TeaCache	29	38.5	3,009	+0.26	1,992	+0.23	$[0.142, 0.329]$	0.02
SenCache	29	11.9	4,313	+0.05	2,901	+0.05	$[0.031, 0.067]$	0.13
DiCache	29	18.7	3,979	-0.12	2,639	-0.12	$[-0.146, -0.088]$	0.13
SeaCache	37	68.7	1,534	+0.01	1,057	+0.01	$[0.009, 0.019]$	0.03
TeaCache	37	18.9	3,973	+0.96	2,644	+0.92	$[0.825, 1.028]$	0.07
SenCache	37	21.9	3,823	-0.09	2,551	-0.09	$[-0.108, -0.080]$	0.09
DiCache	37	40.6	2,907	-0.15	1,958	-0.16	$[-0.168, -0.144]$	0.13
SeaCache	41	40.0	2,938	-0.03	1,915	-0.03	$[-0.031, -0.027]$	0.03
TeaCache	41	46.8	2,605	+1.60	1,743	+1.56	$[1.446, 1.682]$	1.53
SenCache	41	30.9	3,383	-0.13	2,291	-0.13	$[-0.153, -0.108]$	0.06
DiCache	41	25.8	3,631	-0.10	2,440	-0.10	$[-0.111, -0.091]$	0.08
Qwen-Image								
SeaCache	29	75.2	1,213	-0.06	779	-0.06	$[-0.073, -0.051]$	0.05
TeaCache	29	80.5	954	0.00	651	-0.01	$[-0.007, -0.003]$	0.00
SenCache	29	83.8	795	+0.08	543	+0.08	$[0.039, 0.125]$	0.12
DiCache	29	41.2	2,877	-0.01	1,937	-0.02	$[-0.038, 0.002]$	0.09
SeaCache	37	98.9	54	-0.03	34	-0.03	$[-0.105, 0.025]$	0.03
TeaCache	37	28.6	3,497	-0.79	2,320	-0.81	$[-0.858, -0.763]$	0.55
SenCache	37	85.5	711	-0.26	460	-0.26	$[-0.287, -0.231]$	0.18
DiCache	37	47.4	2,573	+0.11	1,737	+0.11	$[0.087, 0.127]$	0.22
SeaCache	41	77.0	1,127	+0.02	739	+0.02	$[0.013, 0.021]$	0.02
TeaCache	41	57.8	2,064	-0.07	1,365	-0.08	$[-0.106, -0.049]$	0.01
SenCache	41	66.2	1,657	+0.29	1,096	+0.30	$[0.276, 0.323]$	0.28
DiCache	41	64.7	1,726	+0.18	1,173	+0.18	$[0.164, 0.195]$	0.19
Random exact-K control on the same evaluation subset								
Method	Paired evaluations		Median ΔP , dB		Min–max ΔP , dB			
SeaCache	12,319		-2.605		-26.675 to +16.731			
SenCache	26,194		-4.232		-28.694 to +9.086			
TeaCache	29,032		+0.632		-14.963 to +24.957			
DiCache	32,036		-4.411		-32.094 to +13.442			

Table 21: Replacing adaptive schedules with one fixed schedule changes mean PSNR by -0.83 to $+1.60$ dB across base seeds on new prompts. We use only runs where the adaptive method chooses a different schedule. For each run, we subtract the adaptive method’s output PSNR from the fixed schedule’s output PSNR. Each entry gives the number of these runs, the mean PSNR difference, and the median absolute PSNR difference, in that order. Both differences are in dB. Each base-seed assignment uses 1,088 PartiPrompts. Base seeds A, B, and C are 41, 42, and 43 for FLUX.1-dev and 42, 100042, and 200042 for Qwen-Image.

Model	Method	K	Base seed A	Base seed B	Base seed C
FLUX	SeaCache	29	157/ $-0.08/0.06$	157/ $-0.10/0.06$	147/ $-0.04/0.06$
FLUX	TeaCache	29	675/ $+0.26/0.02$	654/ $+0.19/0.02$	663/ $+0.25/0.02$
FLUX	SenCache	29	967/ $+0.05/0.13$	975/ $+0.04/0.13$	959/ $+0.06/0.13$
FLUX	DiCache	29	868/ $-0.11/0.12$	886/ $-0.13/0.14$	885/ $-0.11/0.13$
FLUX	SeaCache	37	353/ $+0.01/0.03$	356/ $+0.02/0.03$	348/ $+0.01/0.03$
FLUX	TeaCache	37	873/ $+0.91/0.07$	884/ $+0.93/0.08$	887/ $+0.93/0.06$
FLUX	SenCache	37	845/ $-0.10/0.10$	856/ $-0.09/0.09$	850/ $-0.09/0.09$
FLUX	DiCache	37	642/ $-0.16/0.13$	661/ $-0.15/0.13$	655/ $-0.16/0.13$
FLUX	SeaCache	41	647/ $-0.03/0.03$	622/ $-0.03/0.03$	646/ $-0.03/0.03$
FLUX	TeaCache	41	581/ $+1.60/1.56$	579/ $+1.56/1.51$	583/ $+1.53/1.53$
FLUX	SenCache	41	754/ $-0.13/0.06$	765/ $-0.13/0.06$	772/ $-0.13/0.06$
FLUX	DiCache	41	802/ $-0.10/0.08$	810/ $-0.10/0.08$	828/ $-0.10/0.08$
Qwen	SeaCache	29	260/ $-0.05/0.05$	259/ $-0.07/0.04$	260/ $-0.07/0.05$
Qwen	TeaCache	29	216/ $-0.01/0.00$	219/ $0.00/0.00$	216/ $0.00/0.00$
Qwen	SenCache	29	183/ $+0.07/0.13$	183/ $+0.04/0.09$	177/ $+0.13/0.14$
Qwen	DiCache	29	631/ $-0.02/0.09$	655/ $0.00/0.09$	651/ $-0.03/0.08$
Qwen	SeaCache	37	10/ $-0.03/0.04$	15/ $-0.04/0.03$	9/ $-0.03/0.01$
Qwen	TeaCache	37	780/ $-0.83/0.56$	769/ $-0.77/0.49$	771/ $-0.83/0.59$
Qwen	SenCache	37	156/ $-0.26/0.18$	157/ $-0.29/0.20$	147/ $-0.23/0.17$
Qwen	DiCache	37	578/ $+0.11/0.22$	568/ $+0.10/0.22$	591/ $+0.11/0.21$
Qwen	SeaCache	41	251/ $+0.02/0.02$	246/ $+0.02/0.02$	242/ $+0.02/0.02$
Qwen	TeaCache	41	457/ $-0.07/0.01$	446/ $-0.08/0.01$	462/ $-0.08/0.01$
Qwen	SenCache	41	363/ $+0.29/0.26$	369/ $+0.30/0.28$	364/ $+0.31/0.29$
Qwen	DiCache	41	383/ $+0.18/0.19$	376/ $+0.17/0.19$	414/ $+0.19/0.20$

the adaptive methods. DiCache is excluded because its adaptive run uses two-anchor prediction rather than residual reuse.

B.4 The coverage test

B.4.1 Candidate sets and schedule selection

A prompt’s best evaluated result depends on the schedules in its candidate set. We compare two candidate sets to examine how this choice affects coverage. The smaller sets contain 9–17 schedules from offline search methods, uniform spacing, frequent adaptive choices, and variants of the MeanCache schedule. The enlarged sets contain every available distinct schedule at the same cache ratio under residual reuse, including further MeanCache variants and random schedules. They contain 13–32 schedules. Section 3 summarizes the coverage results for these enlarged sets. Within each set, we compare a fixed schedule’s quality with the highest quality reached by any candidate on the same prompt.

For the image coverage tests, we construct variants of the MeanCache schedule by exchanging one, two, or four cached steps with full steps while preserving the cache count. For each available swap count, the first variant restricts every exchanged position to steps after the first cached step and is evaluated under three seeds. Further variants at cache ratios 0.58 and 0.74 use base seed 42, with swaps either restricted in this way or allowed throughout steps 3–48. The coverage tests include the variants with available quality measurements.

Formally, let $q(u; x)$ be the seed-averaged quality of schedule u on prompt x . The comparison value is

Table 22: Reusing a fixed schedule loses at most 0.25 dB in mean PSNR relative to adaptive scheduling in 17 of 19 comparisons. In these comparisons, the fixed schedule has the requested cache count and differs from the adaptive schedule on at least one prompt. Each row uses 300 prompts, split evenly between Penguin599 and VBench944. m is the fraction of prompts on which the adaptive method already used the fixed schedule. n_{off} counts prompts where it chooses a different schedule. For each such prompt, we subtract the adaptive method’s output PSNR from the fixed schedule’s output PSNR, using the same seed. $\overline{\Delta P}_{\text{off}}$ is the mean of these differences in dB. Positive values favor the fixed schedule. Target K is the requested cached-step count. Actual K is the count in the fixed schedule. The lower block contains schedules whose counts differ from the target. Mean differences are not applicable when $n_{\text{off}} = 0$.

Model	Method	Target K	Actual K	m (%)	n_{off}	$\overline{\Delta P}_{\text{off}}$	Mean loss ≤ 0.25 dB
HunyuanVideo	SeaCache	29	29	55	134	+0.03	yes
HunyuanVideo	TeaCache	29	29	2	294	+0.03	yes
HunyuanVideo	SenCache	29	29	26	223	-0.54	no
HunyuanVideo	DiCache	29	29	36	192	+0.05	yes
HunyuanVideo	SeaCache	37	37	76	71	+0.02	yes
HunyuanVideo	TeaCache	37	37	51	146	-0.03	yes
HunyuanVideo	DiCache	37	37	58	125	+0.21	yes
HunyuanVideo	SeaCache	41	41	30	211	+0.01	yes
HunyuanVideo	TeaCache	41	41	66	101	+0.15	yes
HunyuanVideo	SenCache	41	41	85	46	-0.70	no
HunyuanVideo	DiCache	41	41	31	206	-0.07	yes
Wan2.1	SeaCache	29	29	4	288	+0.37	yes
Wan2.1	TeaCache	29	29	100	0	n/a	n/a
Wan2.1	SenCache	29	29	35	196	-0.20	yes
Wan2.1	DiCache	29	29	79	63	-0.22	yes
Wan2.1	SeaCache	37	37	67	98	+0.08	yes
Wan2.1	SenCache	37	37	36	192	-0.01	yes
Wan2.1	DiCache	37	37	30	209	-0.23	yes
Wan2.1	TeaCache	41	41	100	0	n/a	n/a
Wan2.1	SenCache	41	41	51	146	+0.08	yes
Wan2.1	DiCache	41	41	37	189	-0.03	yes
HunyuanVideo	SenCache	37	36	64	107	+0.10	yes
Wan2.1	TeaCache	37	36	100	0	n/a	n/a
Wan2.1	SeaCache	41	40	80	61	+0.04	yes

$b(x) = \max_{u \in \mathcal{U}} q(u; x)$ for candidate set $\mathcal{U}$. A binary schedule has $u_n = 1$ at a cached step. The fixed-budget space is $\mathcal{S}_K = \{u \in \{0, 1\}^N : \|u\|_0 = K\}$. Each experiment specifies any required full steps within this space.

For each image prompt and schedule, we average scores over the available base seeds. Most configurations use three base seeds. Additional MeanCache variants and random draws use only base seed 42, as described above and in Appendix B.2. We also evaluate all image schedules at their common base seed 42 below. Video scores use one seed per prompt throughout each candidate set.

For each candidate set, we select the schedule with the highest coverage at 0.25 dB and report that same schedule at all three margins. We repeat this selection for the enlarged set. To account for selecting among m schedules, we compute a one-sided binomial lower confidence bound at the Bonferroni level $0.05/m$. At each margin, we count the model–ratio combinations whose corrected lower bound on coverage exceeds 0.5.

B.4.2 PSNR coverage

For the smaller candidate sets, Table 25 reports 12 model–ratio combinations, six image and six video. All twelve corrected bounds exceed 0.5 at the 0.5 dB margin, the lowest being 0.529. Eight of the twelve pass at the 0.25 dB margin under the same correction. Random schedules of the same K reach at most 6% of prompts at 0.25 dB.

The enlarged candidate sets provide a stronger per-prompt reference. Under the same correction, the lower bound exceeds 0.5 in 7 of 12 combinations at 0.25 dB, 9 of 12 at 0.5 dB, and all 12 at 1.0 dB. These are the enlarged-set results summarized in Section 3. The separate 337-schedule comparison in Appendix B.5

Table 23: Replacing adaptive schedules with a fixed schedule causes the largest mean PSNR losses for SenCache on HunyuanVideo in both video datasets. We use only prompts where the schedules differ. For each such prompt, we subtract the adaptive method’s output PSNR from the fixed schedule’s output PSNR, using the same seed. Each entry gives the number of these prompts, the mean PSNR difference, and the median absolute PSNR difference, in that order. Both differences are in dB. Each dataset uses 150 prompts. Penguin599 uses base seed 54 and VBench944 uses base seed 42. Target K is the requested cached-step count. Actual K is the count in the fixed schedule. The lower block contains schedules whose counts differ from the target. A zero count means that the adaptive method uses the fixed schedule on every prompt, so the mean and median are not applicable.

Model	Method	Target K	Actual K	Penguin599	VBench944
HunyuanVideo	SeaCache	29	29	64/+0.02/0.04	70/+0.04/0.03
HunyuanVideo	TeaCache	29	29	146/0.00/0.01	148/+0.06/0.01
HunyuanVideo	SenCache	29	29	113/−0.53/0.51	110/−0.55/0.49
HunyuanVideo	DiCache	29	29	89/+0.05/0.20	103/+0.05/0.16
HunyuanVideo	SeaCache	37	37	37/+0.02/0.02	34/+0.02/0.02
HunyuanVideo	TeaCache	37	37	83/−0.03/0.02	63/−0.03/0.02
HunyuanVideo	DiCache	37	37	52/+0.22/0.20	73/+0.20/0.19
HunyuanVideo	SeaCache	41	41	103/+0.01/0.02	108/+0.01/0.02
HunyuanVideo	TeaCache	41	41	48/+0.18/0.15	53/+0.12/0.08
HunyuanVideo	SenCache	41	41	27/−0.75/0.71	19/−0.64/0.50
HunyuanVideo	DiCache	41	41	112/−0.05/0.08	94/−0.08/0.07
Wan2.1	SeaCache	29	29	144/+0.37/0.25	144/+0.37/0.24
Wan2.1	TeaCache	29	29	0 / n/a / n/a	0 / n/a / n/a
Wan2.1	SenCache	29	29	100/−0.22/0.14	96/−0.19/0.20
Wan2.1	DiCache	29	29	33/−0.20/0.08	30/−0.24/0.14
Wan2.1	SeaCache	37	37	46/+0.16/0.01	52/+0.01/0.01
Wan2.1	SenCache	37	37	100/−0.01/0.07	92/−0.00/0.07
Wan2.1	DiCache	37	37	100/−0.24/0.20	109/−0.23/0.20
Wan2.1	TeaCache	41	41	0 / n/a / n/a	0 / n/a / n/a
Wan2.1	SenCache	41	41	76/+0.08/0.18	70/+0.07/0.15
Wan2.1	DiCache	41	41	92/−0.03/0.05	97/−0.03/0.05
HunyuanVideo	SenCache	37	36	47/+0.08/0.15	60/+0.12/0.14
Wan2.1	TeaCache	37	36	0 / n/a / n/a	0 / n/a / n/a
Wan2.1	SeaCache	41	40	32/+0.05/0.03	29/+0.03/0.01

examines FLUX.1-dev at cache ratio 0.82 on 2,381 new prompts. One schedule stays within 0.5 dB of each prompt’s best candidate on 62% of these prompts. The schedule selected from four scoring runs reaches 57%.

To compare all image schedules under the same seed, we repeat the enlarged-set analysis at base seed 42 in Table 24. We again select one schedule at the 0.25 dB margin before reporting all three margins. Each of the six reported schedules stays within 0.5 dB of its candidate set’s per-prompt best on a majority of prompts, including after correcting the lower bounds for candidate set size.

Table 24: One fixed schedule stays within 0.5 dB of the per-prompt best on most prompts in every enlarged image candidate set. Each candidate set uses the same 1,088 prompts at base seed 42 and residual reuse for every schedule. “Schedules” gives the number of candidates. Within each candidate set, we select the schedule with the highest coverage at 0.25 dB under this common seed and report it at all three margins. Entries give the fraction of prompts within each PSNR margin of the per-prompt best. Brackets give the Bonferroni-adjusted one-sided 95% lower bound.

Model	Cache ratio	Schedules	Fixed schedule	0.25 dB	0.5 dB	1.0 dB
FLUX.1-dev	0.58	32	MeanCache	.616 [.571]	.737 [.696]	.865 [.832]
FLUX.1-dev	0.74	31	MeanCache	.500 [.455]	.670 [.627]	.817 [.780]
FLUX.1-dev	0.82	15	BudCache	.556 [.515]	.671 [.631]	.806 [.772]
Qwen-Image	0.58	29	MeanCache	.449 [.405]	.559 [.514]	.703 [.661]
Qwen-Image	0.74	30	MeanCache	.438 [.393]	.549 [.504]	.727 [.686]
Qwen-Image	0.82	13	MeanCache	.589 [.549]	.667 [.628]	.800 [.765]

Table 25: One shared schedule in each smaller candidate set stays within 0.5 dB of the per-prompt best on most prompts. These sets contain 9–17 schedules. For every model and cache ratio, the per-prompt best is the highest seed-averaged PSNR reached by any schedule in the candidate set, all of which use residual reuse. Each entry gives the share of prompts inside the margin, with the unadjusted one-sided 95% binomial lower bound in brackets. The reported counts of combinations whose lower bounds exceed 0.5 use Bonferroni-adjusted bounds. We report the candidate set member with the largest share at 0.25 dB. The reported MeanCache variant exchanges one cached step with one full step. Image rows use the 1,088 PartiPrompts prompts excluded from the 544-prompt recurring-schedule selection split. Video rows use 300 prompts split between Penguin599 and VBench944.

Model	K	Candidates	Fixed schedule	0.25 dB	0.5 dB	1.0 dB
FLUX.1-dev	29	17	MeanCache	0.694 [0.670]	0.776 [0.754]	0.869 [0.851]
FLUX.1-dev	37	17	MeanCache variant	0.443 [0.418]	0.571 [0.546]	0.715 [0.692]
FLUX.1-dev	41	10	BudCache	0.653 [0.629]	0.752 [0.729]	0.882 [0.865]
Qwen-Image	29	17	MeanCache	0.482 [0.456]	0.583 [0.558]	0.767 [0.744]
Qwen-Image	37	17	MeanCache	0.530 [0.505]	0.617 [0.592]	0.763 [0.741]
Qwen-Image	41	10	MeanCache	0.756 [0.734]	0.849 [0.830]	0.949 [0.937]
HunyuanVideo	29	11	MeanCache	0.530 [0.481]	0.637 [0.588]	0.817 [0.776]
HunyuanVideo	37	10	MeanCache	0.620 [0.571]	0.703 [0.657]	0.807 [0.765]
HunyuanVideo	41	10	BudCache	0.630 [0.582]	0.713 [0.667]	0.860 [0.823]
Wan2.1	29	11	MeanCache	0.697 [0.650]	0.760 [0.716]	0.840 [0.801]
Wan2.1	37	10	MeanCache	0.637 [0.588]	0.740 [0.695]	0.907 [0.874]
Wan2.1	41	9	BudCache	0.673 [0.626]	0.827 [0.787]	0.943 [0.916]

B.4.3 Quality margins and coverage under SSIM and LPIPS

To interpret the PSNR margins in Table 25, we compare them with the quality change across cache ratios for the schedules from BudCache, DPCache, MeanCache, and uniform spacing. For each schedule, image model, and ratio, we average PSNR over the available seeds within each prompt and take the median across the 1,088 held-out PartiPrompts prompts. We subtract the higher-ratio median from the lower-ratio median. Adjacent ratios differ by 8 and by 4 cached steps, so we divide each drop by the number of additional cached steps. This gives the average quality change per additional cached step between the tested ratios. There are 16 values, four schedules by two ratio pairs by two models. They run from 0.171 to 1.166 dB, with a median of 0.592 dB. The margins are 0.25, 0.5, and 1.0 dB. These are 0.42, 0.84, and 1.69 times that median.

The coverage test in Table 25 uses PSNR to measure quality. We repeat the test with SSIM and LPIPS, using the same candidate sets and prompts. Each measure needs its own margins. On the same four schedules, we take the median of seed-averaged prompt quality over the same 1,088 held-out prompts at each cache ratio. We divide the SSIM decrease or LPIPS increase between adjacent tested ratios by the number of additional cached steps. There are again 16 values. For SSIM they run from 0.0054 to 0.0367, with a median of 0.0138. For LPIPS they run from 0.0080 to 0.0495, with a median of 0.0202. For each metric, the three margins are about one half, one, and two times its median change per additional cached step. LPIPS is smaller when quality is better, so we negate it before the test and state its margins as positive LPIPS differences. Table 26 gives the result.

After the same candidate-count correction, all 12 SSIM bounds exceed 0.5 at the middle margin, the lowest being 0.521, and seven of the twelve do so at the tightest margin. Under LPIPS, 10 of the 12 corrected bounds exceed 0.5 at the middle margin, and eight do so at the tightest margin. At the middle margin, HunyuanVideo has corrected bounds of 0.477 at $K = 37$ and 0.481 at $K = 41$. At the tightest margins, the best random schedules have higher coverage under SSIM and LPIPS than under PSNR. The best random schedule under SSIM covers 0.118 of the image prompts and 0.117 of the video prompts. Under LPIPS the two shares are 0.132 and 0.087. Under PSNR they are 0.057 and 0.020.

Table 26: Shared schedules also approach prompt-specific choices under SSIM and LPIPS. Candidate sets and evaluation prompts are those of Table 25. For each metric, we select the schedule with the highest coverage at the tightest margin and report it at all three margins. Cells show coverage and the unadjusted one-sided 95% lower bound in brackets. Each prompt’s reference is its best seed-averaged score among the candidates. All schedules use residual reuse. The MeanCache variant exchanges one cached step with one full step. LPIPS is negated for the test, while margins are reported as positive LPIPS differences.

Model	K	Candidates	Fixed schedule	Tight	Middle	Wide
SSIM, margins 0.0075, 0.015, and 0.03						
FLUX.1-dev	29	17	MeanCache	0.825 [0.805]	0.917 [0.902]	0.968 [0.958]
FLUX.1-dev	37	17	MeanCache variant	0.484 [0.459]	0.602 [0.577]	0.773 [0.751]
FLUX.1-dev	41	10	SeaCache most frequent	0.608 [0.583]	0.723 [0.700]	0.866 [0.848]
Qwen-Image	29	17	MeanCache	0.619 [0.595]	0.835 [0.816]	0.964 [0.953]
Qwen-Image	37	17	MeanCache	0.481 [0.455]	0.626 [0.601]	0.821 [0.801]
Qwen-Image	41	10	BudCache	0.551 [0.526]	0.689 [0.665]	0.866 [0.848]
HunyuanVideo	29	11	MeanCache	0.730 [0.685]	0.847 [0.808]	0.940 [0.912]
HunyuanVideo	37	10	MeanCache	0.523 [0.474]	0.633 [0.585]	0.750 [0.705]
HunyuanVideo	41	10	BudCache	0.503 [0.454]	0.597 [0.548]	0.723 [0.678]
Wan2.1	29	11	MeanCache	0.567 [0.518]	0.680 [0.633]	0.823 [0.783]
Wan2.1	37	10	BudCache	0.613 [0.565]	0.690 [0.643]	0.827 [0.787]
Wan2.1	41	9	BudCache	0.760 [0.716]	0.863 [0.826]	0.950 [0.924]
LPIPS, margins 0.01, 0.02, and 0.04						
FLUX.1-dev	29	17	MeanCache	0.851 [0.832]	0.936 [0.922]	0.983 [0.976]
FLUX.1-dev	37	17	MeanCache variant	0.480 [0.454]	0.623 [0.598]	0.791 [0.770]
FLUX.1-dev	41	10	SeaCache most frequent	0.660 [0.636]	0.761 [0.739]	0.870 [0.852]
Qwen-Image	29	17	BudCache	0.649 [0.624]	0.846 [0.826]	0.955 [0.943]
Qwen-Image	37	17	MeanCache	0.463 [0.438]	0.592 [0.567]	0.798 [0.777]
Qwen-Image	41	10	BudCache	0.545 [0.520]	0.675 [0.650]	0.853 [0.834]
HunyuanVideo	29	11	MeanCache	0.727 [0.681]	0.880 [0.845]	0.967 [0.944]
HunyuanVideo	37	10	SeaCache most frequent	0.493 [0.444]	0.553 [0.504]	0.647 [0.599]
HunyuanVideo	41	10	SenCache most frequent	0.487 [0.438]	0.557 [0.508]	0.690 [0.643]
Wan2.1	29	11	MeanCache	0.690 [0.643]	0.840 [0.801]	0.960 [0.936]
Wan2.1	37	10	MeanCache	0.617 [0.568]	0.790 [0.748]	0.947 [0.920]
Wan2.1	41	9	MeanCache	0.690 [0.643]	0.857 [0.819]	0.970 [0.948]

B.5 Exhaustive high-ratio schedule search

B.5.1 Search space and schedule selection

This experiment uses FLUX.1-dev with 50 FlowMatchEuler steps, BF16 inference, 1024×1024 resolution, guidance scale 3.5, and residual reuse at every cached step. Steps 0, 1, 2, and 49 always run the full transformer. Five additional full steps are chosen from steps 3 through 48, giving $\binom{46}{5} = 1,370,754$ schedules with 41 cached steps.

Every schedule is evaluated on four PartiPrompts calibration examples, each containing one prompt and one seed. We sort the indices of the 544-prompt selection subset described in Appendix A.4 in ascending order and take its first four prompts. The generation seed for prompt index i is $42 + i$. The four inputs are:

- Index 5, seed 47: “an illustration of a baby daikon radish in a tutu walking a dog”.
- Index 8, seed 50: “an avocado”.
- Index 9, seed 51: “a young badger delicately sniffing a yellow rose, richly textured oil painting”.
- Index 15, seed 57: “a store front that has the word ‘openai’ written on it.”

This search produces 5,483,016 cached images. Two schedules are selected from these four PSNR values

before the larger evaluation. One maximizes their mean. The other maximizes their minimum. Table 27 gives both schedules and two existing fixed-schedule controls.

Figure 8 shows how many schedules approach the highest mean PSNR on the four selection examples.




Figure 8: On the four selection examples, 76 schedules are within 0.1 dB of the highest mean PSNR. The curve shows the cumulative number of schedules within each PSNR gap after evaluating all 1,370,754 schedules for FLUX.1-dev at cache ratio 0.82. The vertical axis is logarithmic. Circles mark the counts at gaps of 0.1 and 0.5 dB.

Table 27: Schedules selected from four calibration examples. The four boundary steps are required for every schedule. PSNR values are in dB.

Selection rule	Full-compute steps	Mean PSNR	Minimum PSNR
Highest mean	0, 1, 2, 4, 6, 11, 24, 41, 49	22.746	20.496
Highest minimum	0, 1, 2, 4, 6, 13, 23, 40, 49	22.672	20.739
MeanCache schedule	0, 1, 2, 3, 4, 9, 19, 34, 49	21.619	18.041
BudCache schedule	0, 1, 2, 4, 7, 13, 20, 39, 49	22.235	19.190

The schedule selected by four-run mean PSNR is on average 0.412 dB below the four runs’ individual best schedules. Table 2 compares its PSNR with the highest PSNR found for each run across all 1,370,754 schedules in the space defined above.

We also count schedules that are close to all four individual maxima. For each schedule, we subtract its PSNR from the best PSNR for each run and retain it only if all four gaps are at most 1.0 dB. Exactly 42 schedules satisfy this condition in the same fully enumerated space.

B.5.2 Evaluation data and fixed-schedule results

For the larger evaluation, we select the top 64 schedules by four-run mean PSNR, the top 64 by minimum PSNR, and the top 16 by mean PSNR for every subset of one, two, or three scoring runs. We also sample 128 distinct schedules uniformly from the full search space using seed 20270826 and include 11 existing or constructed controls. Combining these candidates and removing duplicates yields 337 distinct schedules. The 11 controls include the BudCache, MeanCache, and DPCache schedules, DiCache’s most frequent schedule with 41 cached steps, and a schedule with additional full steps at 3, 14, 25, 37, and 48. The other six are two MeanCache variants formed by exchanging one or two cached steps with full steps, two previously sampled random schedules, and two schedules constructed from full-compute trajectory measurements. The last two have full steps at 0, 1, 2, 4, 17, 31, 41, 46, 49 and at 0, 1, 2, 17, 28, 36, 42, 46, 49, respectively.

The two selected schedules, the MeanCache and BudCache schedules, and the adaptive methods are evaluated on the data in Table 28. The quality and ranking summaries omit the four prompt–seed runs used for selection, leaving 7,151 runs across the first three datasets. All 337 candidate schedules are evaluated on

these runs. The two selected schedules and the method comparisons are also run on 30,000 DiffusionDB runs. The coverage analysis in Figure 2 instead excludes the four selection prompts under all three seeds. It averages each remaining prompt’s scores over the three seeds and uses 2,381 new prompts across the first three datasets.

Table 28: Evaluation data for the high-ratio search. Each dataset uses three base seeds.

Dataset	Prompts	Runs	Schedules evaluated
DrawBench	200	600	337 candidates and method comparisons
GenEval-style	553	1,659	337 candidates and method comparisons
PartiPrompts	1,632	4,892	337 candidates and method comparisons
DiffusionDB-clean10k	10,000	30,000	selected schedules and methods
Total		37,151	

Table 29 compares the selected schedules with MeanCache and BudCache schedules and the adaptive SeaCache method, all using residual reuse. For DrawBench, GenEval-style, and PartiPrompts, we average each metric over prompts within each dataset and seed, then give the nine means equal weight. The schedule selected by mean PSNR has the highest mean PSNR and SSIM and the lowest mean LPIPS among the results reported for these three datasets. On DiffusionDB, it has higher PSNR than SeaCache, while SeaCache has higher SSIM and lower LPIPS.

Table 29: The schedule selected by mean PSNR transfers beyond its four scoring examples. All fixed schedules use residual reuse. SeaCache uses its original adaptive schedule and residual-reuse rule. The three-dataset results exclude the four selection runs. MeanCache’s SSIM and LPIPS are reported on the full 7,155-run scope in Appendix B.5.4. Its DiffusionDB row uses all 30,000 runs. PSNR is in dB. Bold marks the best value within each scope.

Scope	Method or schedule	PSNR $\uparrow$	SSIM $\uparrow$	LPIPS $\downarrow$
Three datasets	selected by four-run mean	20.944	0.7638	0.2880
Three datasets	selected by four-run minimum	20.782	0.7608	0.2890
Three datasets	MeanCache schedule	20.766		
Three datasets	BudCache schedule	20.742	0.7583	0.2922
Three datasets	SeaCache	19.916	0.7551	0.2914
DiffusionDB	selected by four-run mean	20.485	0.6981	0.3963
DiffusionDB	selected by four-run minimum	20.370	0.6961	0.3952
DiffusionDB	MeanCache schedule	20.091	0.6732	0.4144
DiffusionDB	BudCache schedule	20.415	0.6939	0.3986
DiffusionDB	SeaCache	20.061	0.7024	0.3687

Under residual reuse, the schedule selected by mean PSNR also exceeds the MeanCache schedule by 0.178 dB in mean PSNR, giving the first three datasets equal weight. Within each dataset–seed combination, we compute the fraction of prompts for which the schedule selected by mean PSNR outperforms SeaCache. Averaging these fractions equally across combinations gives 72.3% for PSNR, 56.2% for SSIM, and 45.9% for LPIPS. The corresponding DiffusionDB fractions are 61.2%, 37.6%, and 21.8%.

B.5.3 Schedule rankings across datasets

Across the nine dataset–seed combinations, Spearman correlation between the ranking by four-run mean PSNR and the larger evaluation ranking ranges from 0.896 to 0.946. In each dataset–seed combination, 34 to 42 of the schedules ranked in the top 64 by the four-run mean remain in the top 64 of the larger evaluation. The schedule selected by four-run mean PSNR ranks between 30th and 42nd in the individual combinations.

It ranks 36th when schedules are ranked by their mean PSNR, with equal weight for the nine dataset–seed combinations.

Figure 9 plots both scores against each other for the whole set.




Figure 9: Calibration and evaluation scores give similar schedule rankings. Each point is one of the 337 schedules in the set. Its horizontal position is its mean PSNR on the four prompt–seed runs used for selection. Its vertical position is its mean PSNR on the 7,151 held-out prompt–seed runs, with the nine dataset–seed combinations weighted equally. We obtain a Spearman rank correlation of 0.926 across the set. Indigo circles show search-derived schedules, dark olive triangles show existing or synthetic controls, and open gray squares show the 128 uniformly sampled schedules. The dashed lines mark the best 64 schedules on each axis. 39 schedules are in the best 64 on both. The diamond is the schedule selected by four-run mean PSNR. It ranks 36th of 337 by mean PSNR on the held-out runs. Its mean PSNR is 0.18 dB above the MeanCache schedule’s and 0.20 dB above the BudCache schedule’s. The best held-out schedule in the set is one of the uniform draws.

B.5.4 Five approximation policies

We evaluate each of four schedules with each of five approximation policies. The schedules are those selected by the mean and minimum PSNR of the four scoring runs, the schedule with the highest mean PSNR on the 337-candidate evaluation, and the MeanCache schedule. The approximation policies are residual reuse, first-order Taylor prediction, second-order Hermite prediction, interval-average velocity, and two-anchor prediction guided by the first transformer block. Each of the 20 combinations is evaluated on 37,155 prompt–seed runs. This count includes the four runs used to select the first two schedules. The 37,151-run transfer evaluation in Table 29 leaves those four out. Table 30 contrasts residual reuse with the two-anchor rule on the schedule selected by four-run mean. Its residual-reuse PSNR is 20.945 dB rather than the 20.944 dB of Table 29 for that reason.

Under residual reuse, MeanCache has mean SSIM 0.7459 and mean LPIPS 0.3010 on the full 7,155-run three-dataset evaluation, with equal weight for each dataset–seed mean.

Two-anchor prediction evaluates the first transformer block at each cached step. Its quality gains therefore come with more computation than residual reuse. For the schedule selected by four-run mean PSNR, the difference between the highest and lowest mean PSNR across the five approximation policies is 1.262 dB on the three smaller datasets and 0.899 dB on DiffusionDB. The schedule with the highest residual-reuse

Table 30: Two-anchor prediction improves all three quality metrics on the schedule selected by four-run mean. Three-dataset values equally weight the nine dataset–seed means. DiffusionDB values average its three base-seed means. The four selection runs are included. PSNR is in dB. Bold marks the better approximation policy within each scope.

Scope	Approximation policy	PSNR $\uparrow$	SSIM $\uparrow$	LPIPS $\downarrow$
Three datasets	residual reuse	20.945	0.7638	0.2880
Three datasets	two-anchor	21.193	0.7865	0.2392
DiffusionDB	residual reuse	20.485	0.6981	0.3963
DiffusionDB	two-anchor	20.929	0.7316	0.3192

PSNR in the 337-schedule evaluation set uses full computation at steps 0, 1, 2, 3, 5, 7, 13, 20, and 49. The corresponding differences across approximation policies are 3.963 dB on the three smaller datasets and 3.508 dB on DiffusionDB. With no full step between steps 20 and 49, its Taylor and Hermite predictions deteriorate over the long extrapolation interval. The schedule selected by four-run mean PSNR has later full steps at 24 and 41.

C Additional Full-Trajectory Results

Appendix A.1 gives the sampling configurations.

C.1 Step-by-step profiles for the other models

Figure 10 extends the measurements in Figure 3 to Qwen-Image and Wan2.1. Each model group compares all evaluated datasets within that model.

Qwen-Image has a distinct last-step drop in displacement. Its sampler uses a smaller noise-level change at the final step.

Across datasets, the median CV of normalized step displacement over the 50 steps ranges from 0.67% to 1.17% for Qwen-Image and 1.25% to 1.28% for Wan2.1. The CV of normalized step displacement is larger at the start, reaching 19.27% in Wan2.1.

C.2 Distance from the line joining the endpoints

We use the normalized off-chord distance defined in Section 4.1.

The normalized off-chord distance rises slowly and returns rapidly. It begins at zero, reaches its maximum late in denoising, and returns to zero at the final latent. We first take the median normalized distance across all prompt–seed runs at each state within each dataset. The peak is the maximum of this dataset median profile. Across the four datasets, its height is 0.0925–0.1079 of the chord length for FLUX and 0.0358–0.0529 for Qwen-Image. The peak state indices are 40–41 and 37–39, respectively.

C.3 Numerical precision of turning angles

The image turning profiles use the first 120 prompts from each dataset and seed, giving 2,880 trajectories across the two image models. The video profiles use all trajectories described in Appendix A.1.

The stored image trajectory states use BF16. To estimate the rounding floor, we replace each three-state window’s middle state by the exact midpoint of its endpoints in FP64, round it to BF16, and measure the resulting angle. The signal-to-floor ratio divides the median measured angle by this median rounding-induced angle at the same step. A one-step angle is too small to separate reliably from rounding, so Equation 2 uses a multi-step window. For FLUX, $w = 5$ produces a signal-to-rounding-floor ratio of 3.42–25.5 over the complete trajectory. Qwen-Image is straighter in the middle. Its minimum ratio at $w = 5$ is 2.61. On a




Figure 10: Full-compute trajectories show similar patterns across datasets in Qwen-Image and Wan2.1. Model groups show Qwen-Image and Wan2.1 from top to bottom. Colors and line styles identify datasets. Columns show distance from the line joining the initial and final states, step displacement, and state norm. The first two quantities are divided by each trajectory’s chord length. State norm is divided by the square root of the latent dimension. For each model, upper curves show medians across prompt–seed runs. Shaded bands span the middle 50% of values at each index. Lower curves show the coefficient of variation: standard deviation divided by the mean across runs at the same index. Upper axes use different vertical ranges. Lower axes share a logarithmic percentage scale. Distance CV omits states 0 and 50, where it is undefined. Qwen-Image uses 37,155 runs from four datasets, and Wan2.1 uses 4,629 runs from two datasets. Every dataset uses three seeds per prompt. GenEval and DiffusionDB denote GenEval-style and DiffusionDB-clean10k. State n follows n updates, while step n updates state n to $n + 1$.

subset of 30 Qwen-Image trajectories, increasing the window gives minimum ratios 3.76, 5.13, and 6.54 for $w = 7, 9, 11$. The profiles across datasets use $w = 5$. The measurements at $w \geq 7$ assess numerical precision on the 30-trajectory subset.

C.4 Samples for the spatial-direction measurements

Figure 5(a) uses the first three DrawBench prompts from the stored FLUX.1-dev full-compute trajectories. Their zero-based prompt indices are 0, 1, and 2. The base seed is 41, giving actual seeds 41, 42, and 43. Each example contains all 51 latent states and uses its own chord length and fitted principal components. The PCA fit uses the complete sequence. The curve through states 0–40 is emphasized, and the segment from state 40 through state 50 remains visible as a pale dashed line. The display applies a rotation and translation to each plane and one common scale to both coordinates of all three curves. The endpoint states have identical off-chord coordinates. The first two components explain 95.02%, 95.17%, and 94.56% of centered off-chord variance in these three examples.

The plane-angle measurements in Figure 5(c) use the first 120 prompts from each of four datasets and

three seeds, giving 1,440 trajectories per image model. Pairs with identical initial noise contain different prompts. Pairs with the same prompt use different initial noise. For FLUX.1-dev, these groups contain 7,856 and 1,440 pairs. For Qwen-Image, they contain 2,160 and 1,440 pairs. Each model also uses 20,000 pairs sharing neither prompt nor noise and 500 random-plane comparisons at the same latent dimension. The same-noise pairs come from 122 distinct initial-noise tensors for FLUX and 360 for Qwen-Image.

D Additional Cache-Error Analysis

D.1 State and current contributions

Let z_n^F and $\tilde{z}_n$ be the full-compute and cached latent states at step n . The full model’s velocity prediction is $v_\theta(z, \tau_n, c)$, where z is the latent state, τ_n is the noise level, and c is the prompt conditioning. Write the sampler update as $z_{n+1} = \Psi_n(z_n, v_n)$.

Equation 3 follows by adding and subtracting the full model’s velocity prediction at the cached state:

$$\bar{v}_n - v_n^F = \bar{v}_n - v_\theta(\tilde{z}_n, \tau_n, c) + v_\theta(\tilde{z}_n, \tau_n, c) - v_\theta(z_n^F, \tau_n, c) \quad (5)$$

$$= a_n + g_n. \quad (6)$$

For a one-step sampler, the latent-state error $e_n = \tilde{z}_n - z_n^F$ evolves as

$$e_{n+1} = \Psi_n(\tilde{z}_n, \bar{v}_n) - \Psi_n(z_n^F, v_n^F). \quad (7)$$

For an Euler sampler with step matrix H_n ,

$$e_{n+1} = e_n + H_n(a_n + g_n). \quad (8)$$

At a full step, $a_n = 0$ and the update becomes $e_{n+1} = e_n + H_n g_n$. The incoming state error remains part of the update. Its direction relative to $H_n g_n$ determines whether the next step reduces or enlarges the gap.

We measure a_n and g_n on FLUX.1-dev with SeaCache and TeaCache for 100 PartiPrompts, using seed $42 + i$ for prompt index i and 50 Euler steps. SeaCache thresholds 0.29 and 1.0 yield mean cache ratios 0.580 and 0.820. TeaCache thresholds 0.38 and 1.2 yield 0.581 and 0.820. At cached steps, the full model is evaluated at the cached state for measurement, without feeding that output back into generation. Define

$$E_{\text{current}} = \sum_n \|a_n\|_2, \quad E_{\text{state}} = \sum_n \|g_n\|_2. \quad (9)$$

The output error magnitude is $\|e_{50}\|_2 = \|\tilde{z}_{50} - z_{50}^F\|_2$. For SeaCache at mean cache ratios 0.580 and 0.820, the Spearman correlations between output-error magnitude and E_{state} are 0.988 and 0.991, compared with 0.748 and 0.742 for E_{current} . For TeaCache at mean cache ratios 0.581 and 0.820, the correlations are 0.994 and 0.996 for E_{state} , compared with 0.681 and 0.579 for E_{current} . The accumulated state contribution is more strongly correlated with output error magnitude than the accumulated current contribution.

D.2 Complete cached trajectories

We compare differences between cached and full-compute latent states with final image quality across schedules and approximation policies. The image analysis uses 256 combinations of model, cache ratio, schedule, and approximation policy. Each combination uses 49 PartiPrompts with one seed per prompt, $42 + i$ for prompt index i , and the matching full-compute output. Retaining all 51 latent states gives 12,544 paired trajectories. For state n , the normalized latent-state gap is

$$D_n = \frac{\|\tilde{z}_n - z_n^F\|_2}{\|z_{50}^F - z_0^F\|_2}. \quad (10)$$

The states agree before the first cached step. The gap then grows along the cached trajectory. For each combination, we take the median D_{50} over the 49 prompts with stored trajectories and mean PSNR over all 1,632 PartiPrompts at base seed 42. We compare these two summaries across combinations within each model and cache ratio. The Spearman correlations range from -0.98 to -0.95 across the six model–ratio combinations.

We next compare early state differences with the position of the first cached step as predictors of final quality. For each combination, we use median D_{10} over the 49 prompts with stored trajectories and the same 1,632-prompt mean PSNR. We retain the 218 combinations whose first cached step occurs before state 10, so that caching has begun when the early gap is measured. Within each model and cache count K , we standardize the first cached step, median D_{10} , and mean PSNR to zero mean and unit variance, then pool the standardized values. Ordinary least-squares regression with an intercept gives $R^2 = 0.268$ for the first cached step alone and $R^2 = 0.715$ for median D_{10} alone. Using both predictors also gives $R^2 = 0.715$. The early gap accounts for more of the variation in PSNR than the first cached-step position alone.

To measure this association using prompts outside schedule selection, we recompute median D_{10} over the 32 prompts with stored trajectories outside the 544-prompt selection split. The other 17 prompts with stored trajectories belong to that split. We compare the recomputed median with the same 1,632-prompt mean PSNR. This rank-correlation analysis standardizes values within each model and K over all combinations before retaining the 218 combinations that begin caching before state 10. Their pooled Spearman correlation is -0.82 .

Figure 11 groups schedules by their source. Method-derived schedules are the fixed schedules and most frequent adaptive schedules used in the experiment varying schedules and approximation policies. Schedule perturbations swap cached and full steps while preserving K . Other fixed controls use trajectory geometry or less frequent adaptive schedules. Random schedules are sampled at the same K .

The geometry-based controls use derivatives of the mean normalized off-chord distance and speed along full-compute trajectories. Speed is normalized step displacement per unit change in noise level. These derivatives define costs for cached intervals, with larger costs for longer noise-level gaps since the last full step. Dynamic programming selects a schedule with the lowest total cost for each model and cache ratio. The FLUX.1-dev controls also include six schedules selected using preliminary output quality. These variants change the derivative order and how strongly the interval cost increases with the gap.

The video analysis retains 50 paired trajectories for each of 27 method and cache-ratio combinations in each model. The cached and full-compute trajectories again agree before the first cached step and separate afterwards.

D.3 Derivation and measurement of the four factors

Let d_k^F denote the full-compute feature at step k and let $\hat{d}_k = d_k^F + r_k$ be its approximation when only step k is cached. Let G_k map this feature to the velocity prediction used by the sampler. A first-order expansion at d_k^F gives

$$G_k(d_k^F + r_k) - G_k(d_k^F) = B_k r_k + \mathcal{O}(\|r_k\|^2), \quad B_k = \left. \frac{\partial G_k}{\partial d} \right|_{d_k^F}. \quad (11)$$

When only step k is cached, it begins at the full-compute state. The error in the next state is therefore

$$e_{k+1} = H_k B_k r_k + \mathcal{O}(\|r_k\|^2), \quad H_k = \left. \frac{\partial \Psi_k}{\partial v} \right|_{(z_k^F, v_k^F)}. \quad (12)$$

For each later full-compute step j , define $T_j(z) = \Psi_j(z, v_\theta(z, \tau_j, c))$ and $J_j = \partial T_j / \partial z|_{z_j^F}$. Propagating the perturbation through the remaining transitions yields

$$e_{50}^{(k)} \approx J_{49} \cdots J_{k+1} H_k B_k r_k = \Phi_{50,k+1} H_k B_k r_k. \quad (13)$$




Figure 11: Larger latent-state gaps at state 10 are associated with lower final-image PSNR. Each point represents a fixed schedule and approximation policy. D_{10} is the L2 distance between the cached and full-compute states at state 10, divided by the full-compute trajectory’s chord length. The horizontal axis gives median D_{10} over 49 prompts. The vertical axis gives mean PSNR in dB over 1,632 PartiPrompts. Colors and marker shapes distinguish schedules from caching methods, modified schedules, other fixed controls, and random schedules. Open markers indicate schedules whose first cached step is at or after step 10, so $D_{10} = 0$. Each panel reports the Spearman correlation ρ_s and number of combinations n for filled markers.

Taking the Euclidean norm of the error and operator norms of the linear maps gives the scalar bound

$$\|e_{50}^{(k)}\| \lesssim \|\Phi_{50,k+1}\| \|H_k\| \|B_k\| \|r_k\|. \quad (14)$$

The experiment uses FLUX.1-dev, 100 DrawBench prompts, 50 Euler steps, and seed $42 + i$ for prompt index i . We test steps 1–49 separately, caching only the tested step under residual reuse, first-order Taylor prediction, or second-order Hermite prediction. At early steps, predictions use the highest order supported by the available feature history. For the Euler update, write $\Delta\tau_k = \tau_{k+1} - \tau_k$, using the sampler’s actual noise levels. We measure the velocity error and the resulting next-state error:

$$\delta v_k = G_k(d_k^F + r_k) - G_k(d_k^F), \quad (15)$$

$$\eta_k = \Delta\tau_k \delta v_k. \quad (16)$$

We resume full computation from $z_{k+1}^F + \eta_k$ and denote its final state by z_{50}' . The measured output error is $e_{50}^{(k)} = z_{50}' - z_{50}^F$. The ratios $\|\delta v_k\|_2 / \|r_k\|_2$ and $\|e_{50}^{(k)}\|_2 / \|\eta_k\|_2$ measure the model’s response to the feature error and the remaining trajectory’s response to the next-state error. These are measured gains along the finite perturbations used in the experiment. For an evaluation prompt i , let mean_{-i} denote the arithmetic mean over the other 99 prompts at the same step and with the same approximation policy. We estimate the

propagation gain by averaging the two ratios separately:

$$h_k^{\text{LOO}} = \text{mean}_{-i} \left[\frac{\|\delta v_k\|_2}{\|r_k\|_2 + \epsilon} \right] |\Delta\tau_k| \text{mean}_{-i} \left[\frac{\|e_{50}^{(k)}\|_2}{\|\eta_k\|_2 + \epsilon} \right], \quad \epsilon = 10^{-12}. \quad (17)$$

The score for prompt i is its feature-error norm multiplied by h_k^{LOO} . Step 0 has no stored residual and step 49 has no later transition for the amplification measurement. The common comparison therefore uses steps 1–48, giving 4,800 prompt–step observations per approximation policy.

We pool all 4,800 prompt–step observations within each approximation policy and compute Spearman correlations with output-error magnitude. For residual reuse, the complete product has a correlation of 0.886, compared with 0.528 for local feature error $\|r_k\|$ and 0.867 for the negated step index $-k$. For second-order Hermite prediction, the correlation is 0.896 for the complete product, 0.586 for $\|r_k\|$, and 0.880 for $-k$. For first-order Taylor prediction, it is 0.899 for the complete product, 0.676 for $\|r_k\|$, and 0.880 for $-k$. The sampler step size $|\Delta\tau_k|$ and the measured future gain change in opposite directions over denoising steps. The feature-error norm multiplied by the step size, and the next-state error estimate defined in Table 31, are negatively correlated with output-error magnitude. Including the future gain in $\|r_k\| h_k^{\text{LOO}}$ gives a positive correlation.

Table 31: Combining feature error with propagation gain gives the highest correlation with output error magnitude. We compute Spearman correlations over 100 prompts and steps 1–48, giving 4,800 isolated cached steps per approximation policy. The step-only score is the negative cached-step index $-k$. The propagation gain h_k^{LOO} uses the other 99 prompts at the same step and with the same approximation policy. The next-state error estimate is $\|r_k\| |\Delta\tau_k|$ multiplied by the first mean ratio in Equation 17.

Approximation policy	Step only $-k$	Feature error $\ r_k\ $	Feature error $\times$ step size $\ r_k\ \Delta\tau_k $	Next-state error estimate	Propagation gain h_k^{LOO}	Feature error $\times$ gain $\ r_k\ h_k^{\text{LOO}}$
Residual reuse	0.867	0.528	-0.382	-0.215	0.803	0.886
Hermite order 2	0.880	0.586	-0.391	-0.180	0.800	0.896
Taylor order 1	0.880	0.676	-0.350	-0.115	0.788	0.899

We also split the 100 prompts into 50 even-indexed and 50 odd-indexed prompts. For each approximation policy, we average the two gain ratios on one half, form the propagation gain, and evaluate its product with $\|r_k\|$ on the other half’s 2,400 prompt–step observations. We test both transfer directions. Using the profile estimated from the other half changes the correlation between this product and output-error magnitude by less than 0.003, relative to using a profile estimated from the evaluation half. Across approximation policies, the Spearman correlation between the two halves’ propagation profiles ranges from 0.9955 to 0.9981. Thus, the propagation profile transfers across these prompt subsets. The norm $\|r_k\|$ captures differences in feature error between prompts at the same step.

D.4 Schedule and approximation policy comparisons

We distinguish the effects of schedule selection and feature approximation through controlled comparisons.

Joint effects of schedule and approximation policy. The image experiment uses four schedules: Bud-Cache, DPCache, the uniform schedule shared by the fixed predictors, and DiCache’s most frequent schedule selected on the 544-prompt selection split. Each is evaluated with residual reuse, first-order Taylor prediction, second-order Hermite prediction, MeanCache’s interval-average velocity prediction, and two-anchor prediction in every model–ratio combination, using 1,632 PartiPrompts under three base seeds. For each of the

20 combinations, we average PSNR over prompts within each seed, then average the three seed means. An additive least-squares fit with equal weight for all 20 means separates the schedule and approximation policy effects, with each set of effects constrained to sum to zero. The interaction is the residual from this fit. Its variance share is the sum of squared residuals divided by the total sum of squared deviations of the 20 means from their grand mean. Schedule and approximation policy shares use the corresponding fitted effects and the same denominator. Table 32 reports the separate and joint effects.

Holding one choice fixed. The fixed-schedule comparisons in Figure 12 evaluate the five approximation policies on BudCache schedules. FLUX.1-dev uses 1,632 PartiPrompts under three seeds. HunyuanVideo uses 300 prompts, split evenly between Penguin599 and VBench944, with one seed per prompt. The comparisons with a fixed approximation policy instead use the three-seed baseline results of Appendix A.5. They compare fixed BudCache schedules with adaptive SeaCache schedules under residual reuse, averaging equally over four image datasets or two video datasets. Figure 13 gives this comparison for Qwen-Image and Wan2.1. The two methods’ mean PSNR differs by up to 3.2 dB on images and 3.0 dB on videos. Table 33 also compares TaylorSeer, HiCache, and L2P, which share a schedule but use different approximation policies. Its PSNR range across approximation policies is the difference between their highest and lowest mean PSNR.

Table 32: Interactions between schedules and approximation policies account for 13–27% of the variation in mean PSNR at cache ratios 0.74 and 0.82. For each model and cache ratio, we fit an additive model to the 20 mean PSNR values from four schedules and five approximation policies, with equal weight for every combination. The schedule and approximation policy columns give the fractions of the total sum of squares explained by their separate effects. The interaction column gives the remaining fraction. The last column is the average of the 20 mean PSNR values, in dB.

Model	K	Schedule	Approximation policy	Interaction	Mean PSNR (dB)
FLUX.1-dev	29	.950	.037	.013	25.20
FLUX.1-dev	37	.613	.117	.270	20.95
FLUX.1-dev	41	.493	.269	.238	18.53
Qwen-Image	29	.983	.012	.005	26.78
Qwen-Image	37	.657	.181	.162	20.26
Qwen-Image	41	.368	.499	.133	15.79

E Schedule Search

E.1 Search space, scoring examples, and evaluation

The search of Section 6 runs on FLUX.1-dev and Qwen-Image at $K = 29, 37$, and 41 , with 50 Flow-MatchEuler steps and residual reuse at every cached step. Steps 0, 1, 2, and 49 always run the full model. The remaining full steps are chosen among steps 3 to 48. The spaces contain 1,749,695,026,860 schedules at $K = 29$, 1,101,716,330 at $K = 37$, and 1,370,754 at $K = 41$.

To evaluate a schedule, we generate images from the eight prompt–seed examples in Table 34. We compare each image with the full-compute output from the same prompt and seed, then average the eight PSNR values. The eight examples were fixed before any search ran. None of the eight prompts appears in DrawBench, GenEval-style, PartiPrompts, or DiffusionDB-clean10k. Repeat visits to an already scored schedule reuse its stored score and consume no additional evaluations. Initial schedules include recurring schedules selected using 544 PartiPrompts. The final PartiPrompts results include that selection set. DrawBench, GenEval-style, and DiffusionDB evaluation prompts are separate from both initialization data and candidate-scoring examples.

Table 33: BudCache and SeaCache differ by up to 3.24 dB on images and 3.01 dB on video under residual reuse. “PSNR range across approximation policies” is the difference between the highest and lowest mean PSNR of TaylorSeer, HiCache, and L2P, which share a schedule. “Schedule difference” subtracts adaptive SeaCache’s mean PSNR from the mean PSNR obtained with the fixed BudCache schedule. Both use residual reuse at the same target ratio, as in Figures 12 and 13. We give equal weight to the mean PSNR of each dataset, using four image datasets or two video datasets. Positive schedule differences favor BudCache.

Model	K	PSNR range across	
		approximation policies (dB)	Schedule difference (dB)
FLUX.1-dev	29	1.457	-3.238
FLUX.1-dev	37	1.502	+1.002
FLUX.1-dev	41	2.897	+0.708
Qwen-Image	29	1.683	+1.870
Qwen-Image	37	5.319	+2.727
Qwen-Image	41	6.225	+2.431
HunyuanVideo	29	0.606	+1.806
HunyuanVideo	37	2.166	+2.096
HunyuanVideo	41	3.683	+2.758
Wan2.1	29	1.995	-3.007
Wan2.1	37	4.189	+1.295
Wan2.1	41	3.030	+2.240




Figure 12: Both the schedule and the approximation policy affect quality. (a, c) The BudCache schedule is fixed at each cache ratio. For each approximation policy, we subtract the mean PSNR obtained with residual reuse from the mean PSNR obtained with that policy on the same prompts and seeds. Bars show these differences. Zero denotes residual reuse. Means use 1,632 PartiPrompts under three seeds for FLUX and 150 videos from each of Penguin599 and VBench944 for HunyuanVideo, with one seed per video prompt. (b, d) Fixed residual-reuse approximation policy. Circles show BudCache and squares show SeaCache. Means give equal weight to four image datasets or two video datasets. These axes use target ratios because SeaCache’s cache counts vary. Vertical scales differ.

E.2 Search parameters

A swap exchanges one cached step with one full step whose position is not required by the search-space constraints. It preserves the cache count and the required full steps. Hill climbing examines the one-swap neighbors in random order and accepts the first improvement. Greedy coordinate ascent optimizes the movable full-step positions one at a time.

Each procedure receives the same evaluation budget within a model and cache ratio: 1,400 at $K = 29$, 700 at $K = 37$, and 400 at $K = 41$. Before search, we evaluate 25 pairs, each containing a uniformly sampled




Figure 13: Schedule choice also affects quality on Qwen-Image and Wan2.1. Both methods use residual reuse. Circles show fixed BudCache schedules and squares show adaptive SeaCache. PSNR means give equal weight to four image datasets or two video datasets. The horizontal axes show target cache ratios because SeaCache’s realized cache counts vary. Tables 11–14 in Appendix A.6 report these counts. Table 33 gives the PSNR differences.

Table 34: The eight scoring examples. Base seeds 50042 and 60042 differ from every evaluation base seed.

Prompt category	Source	Base seed
person	COCO 2014 val	50042
animal	COCO 2014 val	50042
indoor object	COCO 2014 val	50042
outdoor scene	COCO 2014 val	50042
stylized A	DiffusionDB calibration prompt set	60042
stylized B	DiffusionDB calibration prompt set	60042
counting	COCO 2014 val	60042
rendered text	fixed template	60042

schedule and a one-swap neighbor. These 50 evaluations measure the scale of PSNR changes and count toward the budget. For annealing, we set $t_{\max}$ to ten times the median absolute change across these pairs and $t_{\min}$ to that median divided by 100. The temperatures are rounded to two significant figures. Table 35 gives the measured changes and temperatures.

The schedules used to start optimization are separate from these 50 schedules. Hill climbing and annealing start from a shuffled list of six to eight schedules from BudCache, MeanCache, DPCache, uniform spacing, and the most frequent adaptive schedules that satisfy the search-space constraints. Each procedure optimizes from these schedules in turn, then uses random restarts if its budget remains. Greedy coordinate ascent starts from a random schedule.

An annealing proposal first selects a cached step uniformly. With probability 0.7, it exchanges that step with a movable full step at most three positions away, if one exists. Otherwise, it selects the full step uniformly from all movable full steps. Each annealing chain uses 680, 360, or 200 proposals at $K = 29, 37, 41$, followed by up to 20 rounds of steepest improvement using swaps within three step positions. All stages are subject to the evaluation budget.

Hill climbing also stops after two consecutive completed climbs that each improve the best mean score by less than twice its standard error. Annealing applies this rule to completed chains followed by local improvement. Greedy coordinate ascent applies it to completed coordinate sweeps. This standard error is computed from the current best schedule’s eight scores. Random search uses only the evaluation limit. All PSNR searches exhausted their evaluation budgets.

Table 35: Initial score differences determine the annealing temperatures. The PSNR range and standard deviation are over the 50 initial schedules. The swap delta is the absolute change in mean PSNR on the eight scoring runs between schedules that differ by one swap. Median SE is the median standard error across the 50 schedules, with each standard error computed from that schedule’s eight scores. All values are in dB.

Model	K	PSNR range	PSNR sd	Median swap delta	Median SE	$t_{\max}$	$t_{\min}$
FLUX.1-dev	29	15.45–22.37	1.430	0.0236	0.625	0.24	0.00024
FLUX.1-dev	37	14.79–18.92	1.103	0.0433	0.589	0.43	0.00043
FLUX.1-dev	41	14.64–18.38	0.921	0.0536	0.537	0.54	0.00054
Qwen-Image	29	14.07–21.30	1.603	0.0174	0.693	0.17	0.00017
Qwen-Image	37	12.93–19.48	1.552	0.0347	0.542	0.35	0.00035
Qwen-Image	41	11.73–17.23	1.427	0.0766	0.585	0.77	0.00077

E.3 Candidate validation and selection

Random sampling, hill climbing, simulated annealing, and greedy coordinate ascent each retain their best three candidates that differ from one another at four or more step positions. At each such position, one schedule uses a full step and the other uses a cached step. All candidates for a model–ratio combination are re-scored on 50 separate validation prompts from COCO 2014 captions at seed 50042. To select these prompts, we order the COCO 2014 captions by annotation ID and take the first 50 after the largest ID used by the scoring examples. Each procedure selects the candidate with the highest validation mean. Identical schedules are merged across procedures. For each model–ratio combination, Section 6 reports the candidate with the highest validation mean across all four procedures. Table 36 lists the six selected schedules. Table 37 shows the eight procedure–model–ratio combinations where validation changes the candidate selected by the eight-example mean.

Table 36: The selected schedule for each model–ratio combination. Full steps are the positions that run the full model. Every other step of the 50 is cached. Validation PSNR is the mean over the 50 validation prompts.

Model	K	Validation PSNR (dB)	Full steps
FLUX.1-dev	29	30.705	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 13, 15, 17, 19, 24, 30, 38, 46, 49
FLUX.1-dev	37	24.832	0, 1, 2, 3, 4, 6, 8, 10, 14, 19, 30, 43, 49
FLUX.1-dev	41	21.552	0, 1, 2, 3, 5, 8, 13, 27, 49
Qwen-Image	29	30.381	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 14, 16, 19, 22, 26, 33, 40, 46, 49
Qwen-Image	37	24.499	0, 1, 2, 3, 4, 5, 6, 8, 11, 14, 22, 35, 49
Qwen-Image	41	20.766	0, 1, 2, 3, 5, 9, 17, 31, 49

Table 37: Validation changes the selected candidate in eight search runs. The replaced candidate has the highest mean PSNR on the eight scoring runs. The selected candidate has the highest mean PSNR on 50 validation prompts. The first two numeric columns give the candidates’ mean validation PSNR. For each metric, we subtract the value for the replaced candidate’s output from the value for the selected candidate’s output on the same prompt and seed. The last three columns report the means of these differences over 4,896 PartiPrompts prompt–seed runs. Positive PSNR and SSIM differences and negative LPIPS differences favor the selected candidate. All PSNR values are in dB. Brackets give a 95% bootstrap interval for the PSNR difference. Hill, anneal, and greedy denote hill climbing, annealing, and greedy coordinate ascent.

Model, cache ratio	Procedure	Selected PSNR	Replaced PSNR	Δ PSNR (dB)	Δ SSIM	Δ LPIPS
FLUX.1-dev, ratio 0.58	hill	30.705	30.418	+0.072 [+0.052, +0.091]	+0.0010	-0.0005
FLUX.1-dev, ratio 0.74	anneal	24.663	24.654	-0.002 [-0.011, +0.006]	+0.0022	-0.0008
FLUX.1-dev, ratio 0.74	greedy	24.499	24.476	+0.221 [+0.182, +0.255]	+0.0011	+0.0019
FLUX.1-dev, ratio 0.74	hill	24.832	24.825	-0.012 [-0.020, -0.006]	+0.0006	-0.0008
Qwen-Image, ratio 0.58	anneal	30.381	30.201	+0.149 [+0.128, +0.170]	+0.0011	-0.0015
Qwen-Image, ratio 0.82	anneal	20.739	20.662	+0.001 [-0.014, +0.019]	-0.0002	+0.0005
Qwen-Image, ratio 0.82	greedy	20.481	20.423	-0.015 [-0.024, -0.006]	+0.0044	-0.0029
Qwen-Image, ratio 0.82	hill	20.766	20.712	+0.050 [+0.042, +0.058]	-0.0042	+0.0045

E.4 Results on five quality measures

Table 38: **Searched schedules improve PSNR over BudCache in every reported model, cache ratio, and dataset combination.** Each row compares the selected schedule with one reference schedule under residual reuse. For each metric, we subtract the value for the reference schedule’s output from the value for the searched schedule’s output, using the same prompt and seed. Entries are means of these differences over the listed prompt–seed runs. Positive PSNR, SSIM, ImageReward, and CLIP differences and negative LPIPS differences favor the searched schedule. IR denotes ImageReward. PSNR differences are in dB. Brackets give 95% bootstrap intervals obtained by resampling prompt–seed runs individually.

Model, cache ratio	Dataset	Reference	Runs	Δ PSNR (dB)	Δ SSIM	Δ LPIPS	Δ IR	Δ CLIP
FLUX.1-dev, ratio 0.58	DrawBench	MeanCache	600	+0.697 [0.55, 0.85]	-0.0062	+0.0114	-0.012	-0.013
		BudCache	600	+5.489 [5.18, 5.80]	+0.0558	-0.0539	-0.017	-0.058
FLUX.1-dev, ratio 0.58	GenEval-style	MeanCache	1,659	+0.661 [0.56, 0.77]	-0.0049	+0.0084	-0.011	+0.108
		BudCache	1,659	+6.214 [6.03, 6.40]	+0.0517	-0.0535	-0.014	+0.121
FLUX.1-dev, ratio 0.58	PartiPrompts	MeanCache	4,896	+0.277 [0.22, 0.33]	-0.0124	+0.0191	-0.016	+0.062
		BudCache	4,896	+4.351 [4.25, 4.45]	+0.0375	-0.0339	-0.015	+0.075
FLUX.1-dev, ratio 0.58	DiffusionDB	MeanCache	30,000	+0.370 [0.35, 0.39]	-0.0136	+0.0229	-0.026	-0.037
		BudCache	30,000	+3.259 [3.22, 3.29]	+0.0340	-0.0312	-0.025	-0.038
FLUX.1-dev, ratio 0.74	DrawBench	MeanCache	600	+0.492 [0.42, 0.56]	+0.0027	+0.0029	-0.003	+0.044
		BudCache	600	+1.139 [1.03, 1.25]	+0.0083	-0.0044	-0.013	+0.048
FLUX.1-dev, ratio 0.74	GenEval-style	MeanCache	1,659	+0.503 [0.46, 0.55]	+0.0031	-0.0000	-0.013	+0.050
		BudCache	1,659	+1.168 [1.10, 1.23]	+0.0080	-0.0059	-0.012	+0.080
FLUX.1-dev, ratio 0.74	PartiPrompts	MeanCache	4,896	+0.357 [0.33, 0.38]	-0.0016	+0.0086	-0.017	+0.036
		BudCache	4,896	+0.906 [0.87, 0.94]	+0.0007	+0.0043	-0.020	+0.052
FLUX.1-dev, ratio 0.74	DiffusionDB	MeanCache	30,000	+0.318 [0.31, 0.33]	-0.0030	+0.0153	-0.027	-0.028
		BudCache	30,000	+0.741 [0.73, 0.75]	-0.0021	+0.0101	-0.029	-0.016
FLUX.1-dev, ratio 0.82	DrawBench	MeanCache	600	+0.408 [0.31, 0.50]	-0.0044	+0.0110	-0.047	+0.111
		BudCache	600	+0.474 [0.35, 0.60]	-0.0165	+0.0192	-0.046	+0.106
FLUX.1-dev, ratio 0.82	GenEval-style	MeanCache	1,659	+0.576 [0.51, 0.64]	+0.0008	-0.0021	-0.026	+0.130
		BudCache	1,659	+0.695 [0.60, 0.78]	-0.0077	+0.0036	-0.026	+0.130
FLUX.1-dev, ratio 0.82	PartiPrompts	MeanCache	4,896	+0.425 [0.40, 0.46]	-0.0068	+0.0110	-0.070	+0.017
		BudCache	4,896	+0.311 [0.27, 0.35]	-0.0233	+0.0236	-0.073	-0.007
FLUX.1-dev, ratio 0.82	DiffusionDB	MeanCache	30,000	+0.441 [0.43, 0.45]	-0.0040	+0.0183	-0.130	-0.405
		BudCache	30,000	+0.117 [0.11, 0.13]	-0.0247	+0.0341	-0.137	-0.373
Qwen-Image, ratio 0.58	DrawBench	MeanCache	600	-0.021 [-0.09, 0.05]	-0.0012	+0.0019	+0.002	+0.045
		BudCache	600	+1.188 [0.98, 1.41]	+0.0032	+0.0011	-0.005	+0.011
Qwen-Image, ratio 0.58	GenEval-style	MeanCache	1,659	-0.048 [-0.09, -0.00]	-0.0014	+0.0019	-0.000	+0.019
		BudCache	1,659	+0.844 [0.71, 0.97]	-0.0026	+0.0041	-0.002	+0.024
Qwen-Image, ratio 0.58	PartiPrompts	MeanCache	4,896	+0.040 [0.02, 0.06]	-0.0011	+0.0020	+0.000	+0.012
		BudCache	4,896	+1.075 [1.01, 1.15]	+0.0008	+0.0044	-0.004	+0.013
Qwen-Image, ratio 0.58	DiffusionDB	MeanCache	30,000	+0.094 [0.09, 0.10]	-0.0008	+0.0018	-0.001	+0.013
		BudCache	30,000	+1.154 [1.13, 1.18]	+0.0041	+0.0028	-0.006	+0.002
Qwen-Image, ratio 0.74	DrawBench	MeanCache	600	+0.073 [-0.09, 0.25]	-0.0099	+0.0173	-0.006	+0.040
		BudCache	600	+0.413 [0.27, 0.57]	-0.0024	+0.0053	+0.003	+0.022
Qwen-Image, ratio 0.74	GenEval-style	MeanCache	1,659	-0.086 [-0.17, 0.00]	-0.0115	+0.0140	-0.005	-0.006
		BudCache	1,659	+0.279 [0.20, 0.36]	-0.0055	+0.0038	-0.002	-0.026
Qwen-Image, ratio 0.74	PartiPrompts	MeanCache	4,896	-0.022 [-0.07, 0.03]	-0.0132	+0.0209	-0.019	+0.034
		BudCache	4,896	+0.350 [0.31, 0.39]	-0.0058	+0.0090	-0.010	+0.021
Qwen-Image, ratio 0.74	DiffusionDB	MeanCache	30,000	-0.031 [-0.05, -0.02]	-0.0143	+0.0291	-0.027	-0.037
		BudCache	30,000	+0.298 [0.28, 0.31]	-0.0071	+0.0163	-0.016	-0.019
Qwen-Image, ratio 0.82	DrawBench	MeanCache	600	+0.700 [0.57, 0.83]	+0.0091	-0.0123	+0.009	+0.085
		BudCache	600	+1.574 [1.44, 1.73]	+0.0120	-0.0159	-0.028	-0.010
Qwen-Image, ratio 0.82	GenEval-style	MeanCache	1,659	+0.957 [0.87, 1.04]	+0.0087	-0.0132	+0.003	+0.005
		BudCache	1,659	+1.985 [1.89, 2.08]	+0.0123	-0.0178	-0.010	-0.013
Qwen-Image, ratio 0.82	PartiPrompts	MeanCache	4,896	+0.790 [0.75, 0.83]	+0.0085	-0.0108	+0.007	+0.019
		BudCache	4,896	+1.514 [1.46, 1.56]	+0.0076	-0.0079	-0.019	+0.030

Continued on next page

Table 38 continued

Model, cache ratio	Dataset	Reference	Runs	Δ PSNR (dB)	Δ SSIM	Δ LPIPS	Δ IR	Δ CLIP
Qwen-Image, ratio 0.82	DiffusionDB	MeanCache	30,000	+0.710 [0.70, 0.72]	+0.0084	-0.0080	-0.001	-0.010
	DiffusionDB	BudCache	30,000	+1.065 [1.05, 1.08]	+0.0030	+0.0067	-0.041	-0.130

E.5 Schedules selected by different objectives

Section 6 compares schedules selected using PSNR and LPIPS. We also repeat hill climbing and annealing over the same eight scoring examples with the sum of standardized mean PSNR and standardized negative mean LPIPS. Standardization uses the mean and standard deviation of each metric’s eight-example average across the 50 initial schedules in that model–ratio combination. Thus the joint objective is $(\text{PSNR} - \mu_P)/\sigma_P - (\text{LPIPS} - \mu_L)/\sigma_L$. Each objective uses the same 50 validation prompts and four evaluation datasets, including the full PartiPrompts set described above.

Compared with PSNR-selected schedules, schedules selected by the standardized PSNR–LPIPS objective also have higher SSIM and lower LPIPS in all 48 tests and higher PSNR in 26 of them. Changing the objective therefore changes the quality tradeoff among schedules in the same search space.

E.6 Changing the approximation policy

We also hold each of the six PSNR-selected schedules fixed and replace residual reuse with first-order Taylor prediction, second-order Hermite prediction, interval-average velocity, or two-anchor extrapolation. Each combination is evaluated on the same four datasets and three base seeds. Interval-average velocity uses MeanCache’s average-velocity predictor with its trajectory-based correction. Two-anchor prediction uses the first transformer block to estimate an extrapolation coefficient from the two most recent full-step residuals. Two-anchor extrapolation gives the highest equal-weight mean PSNR in all six model–ratio combinations. Its gain over residual reuse is 1.672, 0.989, and 0.071 dB for FLUX.1-dev, and 1.433, 0.454, and 0.157 dB for Qwen-Image, at cache ratios 0.58, 0.74, and 0.82.

Table 39: Two-anchor prediction gives the highest mean PSNR on all six searched schedules. Each row holds the PSNR-selected schedule fixed. Mean PSNR is in dB and gives equal weight to the four evaluation datasets, totaling 37,155 prompt–seed runs per row and approximation policy. Bold marks the highest mean in each row. Interval-average denotes MeanCache’s interval-average velocity prediction. Two-anchor uses the first transformer block to extrapolate from two full-step residuals.

Model	Cache ratio	Reuse	Taylor O1	Hermite O2	Interval-average	Two-anchor
FLUX.1-dev	0.58	29.104	29.931	30.257	30.342	30.775
FLUX.1-dev	0.74	24.001	24.013	24.513	24.542	24.990
FLUX.1-dev	0.82	21.060	19.459	20.334	20.325	21.131
Qwen-Image	0.58	31.017	31.812	31.981	32.205	32.450
Qwen-Image	0.74	25.183	24.612	25.294	24.549	25.637
Qwen-Image	0.82	21.471	20.473	21.414	20.346	21.628

E.7 Comparing search procedures using exhaustive scores

We compare ten search algorithms using the scores from the exhaustive FLUX.1-dev experiment at $K = 41$. Looking up a schedule’s stored score counts as one evaluation. We use these comparisons to choose the four search procedures and their hyperparameters for Section 6. At each evaluation count, we subtract the best score found so far from the highest exhaustive score of 22.746 dB and average this gap over 50 searches. Table 40 reports the results. Unseeded methods use independent random starts. Seeded variants first evaluate the fixed schedules specified by their method and then use random restarts.

Table 40: Ten search algorithms evaluated using the stored scores of all 1,370,754 FLUX.1-dev schedules that cache 41 of 50 steps. The columns 50 to 5,000 give the number of candidate evaluations. Gaps are PSNR differences in dB below the best exhaustive score. Each gap is averaged over 50 searches. 0.000 means the algorithm found that score exactly. “Exact by 1,000” counts how many of the 50 searches found the best exhaustive score within 1,000 candidate evaluations. The last column is the median evaluation count among repetitions that reached a gap of 0.05 dB. A dash indicates that fewer than 25 of the 50 repetitions reached this gap within 5,000 evaluations. The annealing implementation follows BudCache (Lei et al., 2026), with temperatures scaled to the observed score differences.

Search algorithm	50	200	1,000	5,000	Exact by 1,000	To 0.05 dB
Random sampling	1.19	0.74	0.38	0.18	0/50	–
Hill climb, first improvement	0.75	0.18	0.010	0.000	21/50	324
Hill climb, steepest ascent	1.82	1.49	0.055	0.0003	9/50	802
Hill climb, seeded	0.57	0.16	0.005	0.000	25/50	308
Annealing	1.02	0.08	0.000	0.000	50/50	171
Annealing, seeded	0.65	0.05	0.000	0.000	50/50	172
Greedy coordinate ascent	1.81	0.26	0.003	0.000	32/50	550
Learned additive cost	1.06	0.58	0.19	0.14	3/50	–
Learned pairwise cost	1.08	0.27	0.14	0.083	9/50	723
Bayesian optimization	1.18	0.34	0.035	0.0014	18/50	642

The exhaustive scores also show how many schedules approach the highest mean PSNR. Three schedules are within 0.01 dB of that score, 12 within 0.05 dB, 76 within 0.10 dB, and 247 within 0.20 dB. Steepest ascent from 2,000 random starts under the one-swap neighborhood converges to one of three schedules: the exhaustive best in 54.6% of climbs, a second optimum 0.0057 dB below it in 39.0%, and a third 0.26 dB below it in 6.3%.

We also measure how reducing the number of scoring runs affects schedule selection. For every subset of n of the four scoring runs, we select the schedule with the highest n -run mean PSNR over the whole space. We then evaluate that schedule by its four-run mean PSNR. The mean loss relative to the best four-run mean is 0.315 dB over the four single-run subsets, 0.284 dB over the six two-run subsets, and 0.219 dB over the four three-run subsets. The individual subset losses run from 0.000 to 1.017 dB, showing that the choice of scoring examples affects which schedule is selected.