

RETHINKING CIRCUIT EVALUATION: DO CIRCUITS EXPLAIN MODEL ERRORS?

Li Zhang*

University of Toronto
zli@cs.toronto.edu

Chuqin Geng*

University of Toronto
McGill University
chuqin.geng@mail.mcgill.ca

Mark Zhang

University of Toronto

Chen Yang

Tsinghua University

Luke Zhang

University of Toronto

Haolin Ye

McGill University

Xujie Si

University of Toronto
six@cs.toronto.edu

ABSTRACT

Mechanistic interpretability (MI) aims to explain a model’s behaviour through analyzing its internal computations; circuit-based explanations aim to isolate these computations with compact subnetworks validated by ablating the rest of the model. We show that circuits validated this way may fail to recover the underlying mechanism of the model’s behaviour by closely reproducing its successful decisions while failing to account for most of its errors. Such explanations should account for the model’s particular errors as well as its successes. We evaluate this requirement by measuring exact answer agreement separately on model successes and failures, across circuit sizes and ablation settings, on IOI, DOCSTRING, and six model–task settings from the Mechanistic Interpretability Benchmark. We discover that many tested circuits closely replicate correct behaviour while missing most of the model’s errors. On indirect object identification (IOI) for GPT-2 small, under mean ablation, the manual circuit and tested automated circuits, including one trained against the model’s full output distribution, agree with the model on 97.3–99.5% of prompts it answers correctly but only 11.4–41.7% of errors. An IOI case study shows that lost errors are recoverable by restoring omitted attention-heads which raise error reproduction from 14.2% to 75.1% on a separate held-out set with 0.41 percentage point decrease on correct agreement, exceeding matched random extensions and scalar-biased control. Intervention traces show how omitted computations produce specific wrong answers for a reproducible subset of errors. In all, these findings show circuits can preserve task success without adequately explaining model’s failures, and support exact error reproduction as a necessary, but not sufficient, test of circuit-based explanations of model behaviour.

1 INTRODUCTION

Mechanistic interpretability (MI) is a post-hoc interpretability method that aims to understand the underlying mechanisms of neural networks by reverse engineering them into human-understandable algorithms and circuits (Olah et al., 2020). By connecting computation units of the network and forming subgraphs, circuits attempt to explain the behaviour of the full model on specific tasks. These tasks formalize specific language-model behaviours as problems expressed as next-token prediction, such as identifying the recipient of an action or completing an arithmetic expression. Manual analysis (Wang et al., 2023; Hanna et al., 2023) and automated-circuit extraction methods (Conmy et al., 2023; Syed et al., 2024) identify the components and connections responsible for these behaviours.

Prior work evaluates these circuits through faithfulness: how closely a circuit preserves the full model’s behaviour under a metric and specific intervention (Wang et al., 2023; Hanna et al., 2024).

*Equal contribution.

Common evaluations compare task scores, like average logit difference, or measure divergence between the model and circuit output distributions (Conmy et al., 2023). These evaluations are popular for the identification of compact circuits and improvements in automated extraction.

MI seeks to explain the computations underlying a model’s behaviour, including the computations that produce mistakes. A circuit is a proposed account of that behaviour, therefore, it should be evaluated on inputs where the model is wrong as well as those where it is correct (Jacovi & Goldberg, 2020). We ask: *to what extent do existing circuit-analysis methods account for naturally occurring model errors?*

Explaining the model’s errors matters because an explanation of how the model succeeds on a task does not necessarily explain why it fails. A circuit that produces the correct answer when the model is wrong may capture useful task computation while ignoring influences that determine the model’s real choice. Such failures limit its use as diagnostic tools: an explanation that removes the exact failure cannot, by itself, identify why the failure happened. Therefore, error reproduction tests a distinct scope of a circuit’s explanatory ability, beyond its ability to perform the task correctly.

We find that evaluated manual circuits and most tested automated extraction methods inadequately support model errors, often only preserving most of the correct behaviour. We characterize these failure modes and settings in which error reproduction succeeds, and use circuit completion and causal interventions on IOI to investigate the mechanisms involved. Our contribution covers the systematic evidence about the ability of existing circuit-analysis methods to account for the full mechanism of models.

2 PRELIMINARIES

2.1 TASKS AND CIRCUITS

Tasks. A *task* is fixed by MI researchers as an observable behaviour under the model. It contains three parts: a distribution over prompts x ; a *labeling rule* $y(x)$ that fixes the correct answer for every prompt; and a measure of success. Because circuits are evaluated by patching in activations from another input, each prompt is replaced according to the specific ablation rule.

Circuits. A circuit $\mathcal{C} \subseteq \mathcal{M}$ is a subgraph of the computation graph (Wang et al., 2023). We evaluate it together with a patching setting specifying which activations or edge contributions outside the circuit are replaced and how their replacement values are obtained. Resample ablation uses activation from a counterfactual example, mean ablation uses averages over specified examples, and optimal ablation uses learned replacement constants. Retained computation is run forward on x . We define $\mathcal{C}(k | x)$ for the logit on candidate k under the stated patching setting.

2.2 FAITHFULNESS METRIC

Following Heimersheim & Janiak (2023), who evaluate circuits by the proportion of prompts in which it predicts the correct argument, which Miller et al. (2024) classifies as a faithfulness metric, we similarly score predictions by first defining success as a computation over a *candidate set* $\mathcal{K}(x)$ of single-token answers with $y(x) \in \mathcal{K}(x)$. Rather than free generation, every token is a ranked choice among candidates. These definitions apply to both the full model $\mathcal{M}$ and any circuit $\mathcal{C}$. The model’s *choice* on x is

$$\hat{y}_{\mathcal{M}}(x) = \arg \max_{k \in \mathcal{K}(x)} \mathcal{M}(k | x), \quad (1)$$

The *margin* of the label against its strongest candidate is

$$m_{\mathcal{M}}(x) = \mathcal{M}(y(x) | x) - \max_{k \in \mathcal{K}(x) \setminus \{y(x)\}} \mathcal{M}(k | x). \quad (2)$$

Error. For disagreements between the label $y(x)$ and the model’s choice $\hat{y}_{\mathcal{M}}(x)$, we call this instance an *error* of $\mathcal{M}$. We define:

$$\mathcal{E}(\mathcal{M}) = \{x : \hat{y}_{\mathcal{M}}(x) \neq y(x)\}, \quad \varepsilon(\mathcal{M}) = \Pr_{x \sim \mathcal{D}}[x \in \mathcal{E}(\mathcal{M})]. \quad (3)$$

for the error set and the error rate respectively. A negative answer margin implies an error and a positive margin implies a correct prediction. At zero, we use a deterministic tie rule (i.e. lowest token ID for IOI and docstring, refer to Appendix B, D.1 for MIB and IOI case study).

Agreement. We score the circuit against the model’s choice $\hat{y}_{\mathcal{M}}(x)$ rather than the ground truth $y(x)$. This allows us to focus on whether $\mathcal{C}$ reproduces $\mathcal{M}$, not whether $\mathcal{C}$ matches the task’s correct $y(x)$. Let $a(x) = \mathbb{1}[\hat{y}_{\mathcal{C}}(x) = \hat{y}_{\mathcal{M}}(x)]$, and split it by the stratum x falls in:

$$A_{\text{ok}} = \mathbb{E}[a(x) \mid x \notin \mathcal{E}(\mathcal{M})], \quad A_{\text{err}} = \mathbb{E}[a(x) \mid x \in \mathcal{E}(\mathcal{M})], \quad \Delta = A_{\text{ok}} - A_{\text{err}}. \quad (4)$$

We call agreement on model-correct prompts correct agreement, A_{ok} , and agreement on model-error prompts error agreement, A_{err} .

2.3 BENCHMARKS

We use three major task families: IOI (Wang et al., 2023), DOCSTRING (Heimersheim & Janiak, 2023), and MIB (Mueller et al., 2025).

IOI. We generate prompts following the standard IOI protocol, using 15 template families in both ABBA and BABA order. We sample distinct names and fill place and object slots from the library vocabularies, restricting to single-token entries. Each prompt contains two names and repeats one as the subject (S) where the correct continuation is the other name, the indirect object (IO). We remove the final answer from the generated sentence and evaluate GPT-2 Small over $\mathcal{K}(x) = \{\text{IO}, \text{S}\}$, with $y(x) = \text{IO}$. For counterfactual ablations, we use same-template ABC reference prompts containing three distinct names. We evaluate both resample ablation and mean ablation.

Docstring. From the public ACDC docstring benchmark, we generate synthetic Python function signatures and partially completed docstrings. The argument names and description words are randomly sampled from fixed vocabularies. The task is defined as predicting the next argument name in the docstring in the order established in the function signature. We evaluate a four-layer attention-only transformer over the benchmark’s 14 single-token candidates: the correct argument and 13 distractors. We generate counterfactual prompts from the generator’s `random_random` corruption, which replaces argument names in both the signature and docstring to break their correspondence.

MIB. We use the published prompts and dataset splits from MIB, specifically ARC-Easy, ARC-Challenge, and arithmetic subtraction in our main evaluations. ARC consists of multiple-choice science questions where the answer letter option labels as candidates (Clark et al., 2018). For subtraction, candidates are single-token integers from 0 to 99. We use the supplied symbol counterfactuals for ARC and random-operand counterfactuals for subtraction. We omit Addition and synthetic MCQA from the experiments because they contain only seven and five full-model errors on the public test splits, respectively, yielding loose error-agreement estimates.

We do not include GREATER-THAN year-span benchmark as Hanna et al. (2023) report 100% correct top-1 performance; similarly, for well-posedness, we restrict each task to models whose answers is contained in a single token i.e subtraction is ran on Llama-3.1 8B only (as Gemma-2 and Qwen-2.5 tokenize numbers by digit so answers fall out of candidate sets 1). Full details are reported in Appendix B.

3 AGREEMENT ANALYSIS

Table 1 compares A_{ok} and A_{err} (Eq. 4) under mean and paired resample ablation for IOI and DOCSTRING. Figure 1 reports the MIB evaluations under counterfactual activation replacement values. We also evaluate optimal ablation (Li & Janson, 2024), whose replacement values are learned to minimize KL divergence from the full model’s output distribution. For both IOI and DOCSTRING, ACDC (Conmy et al., 2023) and our EAP-IG configuration (Hanna et al., 2024) use KL divergence from the full model’s output distribution as their discovery objective. Edge Pruning, evaluated on IOI, also uses this model-matching KL loss alongside its sparsity objective. These objectives target the model’s output distribution, including on examples where it is wrong, without explicitly rewarding the ground-truth answer.

High task faithfulness can conceal poor error reproduction. Prior work has shown that average circuit evaluations can miss substantial disagreements on individual inputs (uit de Bos & Garriga-Alonso, 2024), and has distinguished task performance from reproducing model behaviour (Miller

Table 1: Normalized task faithfulness and exact agreement with $\mathcal{M}$ under argmax over the benchmark candidate set $\mathcal{K}(x)$. EAP-IG and Edge Pruning use validation-selected recovery circuits; manual and ACDC circuits are reference checkpoints.

Circuit / model	Size	Ablation	F	Agreement (%)		100 Δ (pp)
				A_{ok}	A_{err}	[95% CI]
<i>IOI</i>						
Manual reference	26 heads	Mean	0.956	99.5	15.2	84.3 [82.0, 86.6]
		Resample (ABC)	0.644	91.2	40.6	50.5 [47.1, 54.0]
		OA (KL)	0.906	99.9	10.0	90.0 [87.9, 91.9]
ACDC ($\tau = 0.003$)	402 edges	Mean	1.167	97.3	11.8	85.5 [83.3, 87.6]
		Resample (ABC)	0.887	91.5	24.8	66.8 [63.8, 69.7]
		OA (KL)	0.869	99.7	8.1	91.6 [89.8, 93.3]
EAP-IG-KL	6,498 edges	Mean	0.987	99.1	41.7	57.4 [54.2, 60.6]
		Resample (ABC)	0.905	97.8	51.4	46.4 [43.1, 49.7]
		OA (KL)	0.985	99.8	44.0	55.8 [52.5, 59.1]
Edge Pruning	256/268/268 edges	Mean	1.486	98.3	11.4	86.9 [85.2, 88.5]
		Resample (ABC)	1.002	93.7	17.6	76.0 [73.7, 78.3]
		OA (KL)	0.971	99.2	15.2	84.0 [82.1, 85.8]
<i>Docstring</i>						
Manual reference	8 heads	Mean	1.017	77.1	35.8	41.3 [39.4, 43.1]
		Resample	0.765	47.2	38.9	8.2 [6.2, 10.2]
		OA (KL)	0.998	81.6	42.5	39.1 [37.3, 41.0]
ACDC ($\tau = 0.005$)	129 edges	Mean	0.729	67.8	53.3	14.4 [12.4, 16.4]
		Resample	0.918	71.7	56.3	15.4 [13.4, 17.3]
		OA (KL)	1.006	83.3	41.5	41.9 [40.0, 43.7]
ACDC ($\tau = 0.02$)	52 edges	Mean	0.990	74.8	37.2	37.6 [35.7, 39.5]
		Resample	0.866	59.0	42.0	17.1 [15.1, 19.1]
		OA (KL)	0.898	78.9	39.1	39.8 [37.9, 41.7]
EAP-IG-KL	500 edges	Mean	0.651	65.6	69.4	−3.8 [−5.7, −1.9]
		Resample	0.842	66.3	66.3	0.0 [−2.0, 2.0]
		OA (KL)	1.043	89.9	60.0	29.9 [28.2, 31.7]

EAP-IG and Edge Pruning use the smallest evaluated non-full circuit with normalized validation-resample faithfulness $F_{\text{val}} \geq 0.85$, where $F = (\bar{m}_C - \bar{m}_0) / (\bar{m}_{\mathcal{M}} - \bar{m}_0)$ with graph- and ablation-specific empty controls. Edge Pruning lists three fitted-seed sizes and averages their agreement. Intervals use 10,000 paired stratified bootstrap resamples, retain sampling weights, and condition on fitted masks.

et al., 2024). Similarly, our results support a systematic deficit on the model’s own errors. On IOI under mean ablation, the manual circuit, ACDC, EAP-IG-KL, and Edge Pruning (Bhaskar et al., 2024) preserve 97.3%–99.5% of the correct choices but reproduce only 11.4%–41.7% of errors. The manual circuit has normalized mean logit-difference faithfulness of $F = 0.956$, yet reproduces only 15.2% of the model’s errors. This gap also happens in circuits discovered with model-matching KL objectives. However, error reproduction still varies with the evaluation setting; EAP-IG reaches 51.4% under resampling at 6,498 edges.

Smaller gaps can reflect either better error reproduction or lost correct behaviour. For the DOCSTRING manual circuit, resampling reduces the gap from 41.3% to 8.2%, mainly due to the correct agreement falling from 77.1% to 47.2%. In contrast, DOCSTRING EAP-IG instead reproduces 69.4% of errors under mean ablation which exceeds its 65.6% correct agreement, suggesting that an extracted circuit can preserve substantial performance on both behaviours.

Discovery error exposure and weighting provide only partial recovery. In the six MIB settings, 187–849 model errors appear in the public-training splits, representing 4.9–41.1% of the discovery examples. On Gemma ARC-Challenge, 430 of the 1,119 discovery examples (38.4%) are errors, yet across most edge budget sizes, there’s a sustained gap. For instance, at 1% edge budget, the




Figure 1: Preservation of correct and incorrect model prediction across circuit sizes. Circuits are extracted on the full public-training split and evaluated on the public-test split. Shading indicate the point-wise 95% bootstrap confidence intervals. Specific models are: Llama-3.1 (8B), Gemma-2 (2b), Qwen-2.5 (0.5B).

circuit preserves 80.3% of correct choices and only reproduces 54.4% of the model’s wrong answers. Thus, the disparity cannot be solely attributed simply to errors being rare during discovery as it still persists with roughly 60:40 correct to error split. Nevertheless, we test whether increasing the weight assigned to errors during discovery improves their reproduction in a separate ACDC follow up on IOI: while assigning existing errors 50% of the total discovery KL weight raises average exact-error agreement under mean ablation from 9.3% to 37.0%, it causes correct agreement to fall from 98.7% to 91.0%. Reweighting therefore improves error reproduction, but still leaves a significant agreement gap while incurring a non-trivial correct-case cost.

Matching margins diminishes some disparities. Model errors may be concentrated at small margins (Hendrycks & Gimpel, 2017), increasing the probability that smaller margins make their predictions more sensitive to differences between the circuit and model logits. Therefore, we match correct and error test examples on the absolute model margin between the highest and second highest candidate logits computed from the full model over the candidate set $\mathcal{K}(x)$, within each setting for IOI, DOCSTRING, and MIB. Margin matching does decrease several MIB ARC agreement gaps. For Llama ARC-Challenge at 2% edge budget, correct agreement is 80.0% across all correct examples, but 46.7% among the matched correct examples, while exact-error agreement remains at 54.9%. The narrowed gap shows lower preservation of correct examples within comparable margins. Some disparities do exist like Gemma ARC-Easy retaining gaps of 15.3–21.2 % at the 5%, 10%, and 20% budgets. Therefore, several agreement gaps are smaller on margin-matched examples, with the remaining gaps depending on the setting and circuit size. Positive gaps also persist after margin matching in all IOI and most DOCSTRING configurations reported in Table 1. Full results for IOI, Docstring, and MIB are provided in the Appendix C.

Additional recovery attempts have mixed effects. We also test discovery sets with increased distinct model errors, error-conditioned activation replacements, and post-hoc calibration of circuit logits and decision thresholds. In the ACDC IOI follow-up, using a discovery split of 500 error and 500 correct examples results in a A_{err} of 44.2% and A_{ok} of 91.4%. Error-conditioned mean and resample replacements also improve IOI A_{err} , but simply shifting the output logits toward the subject name reproduces at least as many errors. Matching the model’s overall error rate does not consistently recover its particular wrong answers, while more aggressive threshold calibration can narrow the gap by sacrificing correct performance.




Figure 2: **Two omitted computations recover model errors:** A) Restored contextual computation changes S-Inhibition and Name Mover queries, producing Courtney instead of Sara. B) Restored-name source computations changes keys, reducing the retrieval of Katie by a Positive Name Mover and increasing it by a Negative Name Mover, both favouring Vanessa over Katie.

4 CASE STUDY: WHY THE MANUAL REFERENCE CIRCUIT MISSES MODEL ERRORS

We next show in an IOI case study that restoring selected omitted components can substantially improve exact-error agreement while largely preserving correct behaviour, and trace the computations underlying these recoveries.

4.1 UNDERSTANDING MISSING ERRORS

We organize our case-study around three primary questions:

Q1: Which omitted components contribute to missing errors, and how? We test whether restoring selected components reproduces the model’s exact wrong answers, and whether they act through separate mechanisms or modify existing circuit computations.

Q2: Can error recovery improve while largely preserving correct agreement? We analyze whether restricted extensions improve error agreement with limited losses on correct examples, reporting both changes relative to the reference circuit and the number of added components.

Q3: How concentrated and stable are the missing contributions? We examine whether errors share omitted contributions and whether their effects persist across ablation settings and held-out tests.

Experimental setup. We use GPT-2 small and Wang et al. (2023)’s published IOI reference circuit C_0 and, similarly, search for attention heads h at specific positions. We search over following positional token rules: END (the last input position), IO (the recipient’s name), S1 and S2 (the subject’s first and second occurrences), S1 + 1 (the position after the subject’s first occurrence), BOS (the beginning of sequence position). The error-recovery experiment in Section 4.2 uses an expanded search space, described below. To further match the IOI study(Wang et al., 2023), we scope our investigation on the attention heads while ablating with mean knockouts, and we do not intervene on any other components. We provide definitions of IOI-specific terminology and additional details of the reference circuit in Appendix D.1.

The reference circuit contains several functional head groups (Wang et al., 2023). Positive Name Movers attend to earlier name tokens and increase those names’ output logits; Negative Name Movers decreases them. Backup Name Movers perform a similar name-copying function when

primary Name Movers are ablated. S-Inhibition heads use information about the repeated subject to influence the Name Mover queries, helping them avoid copying the subject.

We search for a compact extension of C_0 that more faithfully reproduces the full model’s ($\mathcal{M}$) predictions on examples where $\mathcal{M}$ is incorrect, while preserving the agreement on examples it answers correctly.

Starting from C_0 , we greedily expand the circuit using a gradient-based screening to identify head-position candidates, followed by exact binary-intervention evaluation. We guide our search with the following objective:

$$J(\mathcal{C}) = A_{err}(\mathcal{C}) - \alpha [A_{ok}(\mathcal{C}_0) - A_{ok}(\mathcal{C}) - \epsilon]_+ - \lambda_P P_{added}(\mathcal{C}), \quad (5)$$

where $[z]_+ = \max(z, 0)$, ϵ is the tolerated decline in correct agreement, and $P_{added}(\mathcal{C})$ counts added head-position nodes beyond $\mathcal{C}_0$,

Our objective reflects two standard principles in circuit extraction: faithfulness and minimality (Wang et al., 2023; Conmy et al., 2023). The recovery term pushes towards recovering $\mathcal{M}$ on $\mathcal{E}(\mathcal{M})$, while the agreement penalty penalizes the recovery from degrading the initial correct performance for $\mathcal{C}_0$. The sparsity terms favour compact extensions, with separate costs for introduce new heads. We provide the full algorithm and hyperparameters in the Appendix D.1.

4.2 ERROR RECOVERY ON FRESH DATA

For this experiment, we expand the search space to 25 positional rules across all 144 attention heads, yielding 3,574 supported head–position additions beyond the reference circuit $\mathcal{C}_0$. The selected extension, $\mathcal{C}_*$, adds 63 position–head nodes, with approximately 61.54 additional outputs per prompt on average. The final selected extension adds 63 rules. On a frozen 26,000-example test set containing 225 $\mathcal{M}$ errors, the reference circuit reproduces only 14.22% errors, whereas the selected extension reproduces 75.11%. This is with only a correct agreement drop of 0.41 percentage points from 99.34% for the reference to 98.93% for the extension. Despite the strong class imbalance towards correct examples, the extension still gains more agreements in absolute terms than it loses, recovering 137 additional model errors while losing 106 correct examples. $\mathcal{C}_*$ also exceeds all structurally matched random extensions (error agreement 17.33–41.33%, median 29.33%). A scalar subject-bias applied to $\mathcal{C}_0$, fitted on validation correct cases to match $\mathcal{C}_*$ ’s correct agreement, reached only 20.44% exact error agreement on this test set at nearly identical correct agreement (98.93%).

This answers Q2 affirmatively on this evaluation: a restricted position-specific extension is able to recover a significant gain of model failures that are not reproduced by the published reference circuit, while largely preserving its behaviour on examples the model answers correctly.

4.3 HOW OMITTED COMPUTATIONS CHANGE WHICH NAME WINS

To address Q1, given the existing subject-inhibition (S-inhibition heads) and name-writing (Name Mover heads) components, our analysis identifies two ways in which omitted inputs alter its behaviour: **contextual information changes the queries used to select names, while early name-dependent writes change the keys through which the correct name is retrieved.** Retained heads and MLPs can amplify or oppose both of these effects.

Mechanistic analysis. We study all 137 new reproduced errors, denoted as G . Like (Wang et al., 2023), we use activation patching and path patching to test whether selected activation changes from the expansion make $\mathcal{C}_0$ reproduce the model’s wrong answer. Conversely, we also patch reference-circuit activations into $\mathcal{C}_*$ and $\mathcal{M}$ to test whether these replacements restore the correct answer. To find the context that is responsible, we patch activations from counterfactual prompts with altered object words, name identities, or name positions, while keeping the receiving prompt unchanged. We compare the logits of the indirect object (IO) and subject (S). *Recovery* refers to reproducing the model’s preference for the incorrect subject name; *repair* means restoring the preference for the correct IO name.

Contextual inputs effect subject inhibition. Existing S-inhibition heads read information about the repeated subject at S2 and influence which names the Name Mover heads select. Restored

object-related inputs change how the inhibition heads read this information. In the traced computation, the resulting query changes increase downstream attention to the subject, causing the retained Name Movers to copy the wrong name, illustrated by Figure 2. To test this mechanism, we isolate the difference between C_* and C_0 at the part of the inhibition output obtained by attending to S2. Patch patching this changed inhibition contribution into the Name Mover queries of C_0 , with reference keys and values fixed causes it to select the wrong subject on 120 of the 137 error prompts. Thus, retained heads can produce the wrong answer when supplied with altered inhibition signals.

Testing the influence of the object content. We construct corresponding prompts in which the object word is replaced with "snack." For instance, "gave a bone to" becomes "gave a snack to", while keeping the remaining text untouched. These altered prompts supply the replacement content for the information retrieved from the object position by the added attention heads in C_* . The circuit still operates on the original prompt, and the attention weights at the substituted outputs remain unchanged. This isolates the influence of object-derived information inside the circuit. The substitution of this object restores the correct IO answer on 107 of the 137 prompts. Then, we repeat it while holding the S-Inhibition outputs at the same values from C_* before the substitution. Under this constraint, 68 of those corrections disappear. This suggests an object-dependent influence on subject inhibition, however, this does not disclose which exact semantic feature of the object causes it.

Early name processing affects retrieval. A second omitted computation changes the representation of the correct name before later heads retrieve it. The extension restores the outputs of five first-layer heads: 0.1, 0.3, 0.5, 0.6, and 0.10, at the IO position; $\ell.h$ denotes the attention head h in layer ℓ , with both indices starting at zero. Their outputs combine with downstream MLP transformations to change the IO representation used to compute the Name Movers' keys, shown in 2B. After activation patching the Name Movers' keys at the IO position with their values from C_* on the same prompt, the intervention reproduces the model's wrong subject answer on 35/137 examples. Restoring the keys only at either subject occurrence, or only at the remaining positions, reproduces none. In the measured route, the changed keys reduce IO retrieval by Positive Name Movers and increase it by Negative Name Movers, whose IO-source values oppose the correct name in the IO minus subject margin.

Concentration and interactions (Q3) Path patching the S-Inhibition heads' S2 contribution into C_0 's Positive, Negative, and Backup Name Mover queries reproduces 120/137 newly recovered errors, showing a recurring contribution across examples. Additionally, the extension's performance persists under resample ablation: error agreement increases from 40.89% to 60.89%, and the correct agreement from 91.41% to 97.67%. Therefore, recovery involves re-recurring interactions with retained computation and is observed under both replacement settings.

5 RECOMMENDATIONS

From our findings in Section 3 and 4, we recommend the following checks to test whether a circuit reproduces the model's choices on both model-correct and model-incorrect prompts, based on the stated circuit execution and ablation rule. However, this alone does not establish whether the circuit recovers the model's underlying mechanism (Wang et al., 2023).

Build Stratum. For each data split, partition the prompts based on whether the full model correctly answers the task. The strata is then fixed across all evaluated circuits, sizes and ablation methods.

5.1 RAW METRICS FOR EXTRACTED CIRCUIT

Report A_{ok}, A_{err} together with their difference Δ as defined in Eqn 4. If there are no model errors, A_{err}, Δ is undefined. Note that specifically for $x \in \mathcal{E}(\mathcal{M})$ where $\hat{y}_{\mathcal{M}}(x) \neq y(x)$: $a(x) = 1$ requires the circuit to return the *same incorrect* answer the model returns. A circuit returning the correct answer for the task when the full model was wrong or a different incorrect answer from the full model counts as a disagreement. As an additional diagnostic for future circuit evaluations, to distinguish these two types of disagreement, we define $B_{err}(\mathcal{C})$, the fraction of model-error prompts

on which the circuit is also incorrect:

$$B_{\text{err}}(\mathcal{C}) = \mathbb{E}[\mathbb{1}[\hat{y}_{\mathcal{C}}(x) \neq y(x)] \mid x \in \mathcal{E}(\mathcal{M})] \quad (6)$$

The shares on which the circuit selects the correct answer and a different incorrect answer are $1 - B_{\text{err}}(\mathcal{C})$ and $B_{\text{err}}(\mathcal{C}) - A_{\text{err}}$, respectively. For binary tasks, $B_{\text{err}}(\mathcal{C}) = A_{\text{err}}$.

5.2 EVALUATION ACROSS CIRCUIT SIZES

Evaluation at a single circuit size may not be sufficient in accounting for how these numbers change as circuit size changes. Following Mueller et al. (2025)’s use of a set containing proportions of components, we recommend evaluating agreement across a specified sequence of circuit sizes. Crucially, we track agreement on each stratum separately across sizes, because a high average logit-difference score does not necessarily imply circuit matches the model’s individual predictions (Miller et al., 2024).

Size sequence. When a discovery method provides a ranking or budget sequence, specify the evaluated sizes before final evaluation and report the retained component counts and their units. For our MIB experiments, we evaluate circuits at retained-edge fractions, $s \in \{.001, .002, .005, .01, .02, .05, .1, .2, .5, 1\}$ and report empty circuit ($s = 0$) control. A circuit with no defined sequence can be reported as individual points.

Stratified curves. Plot $A_{\text{ok}}(s)$ and $A_{\text{err}}(s)$ evaluated on $\mathcal{C}_s$ against s . Their difference, $\Delta(s)$, shows whether A_{err} is lower at every non-full model size or only at the size we happened to pick. A smaller gap can reflect improved error agreement, but could also mean reduced correct agreement.

Reporting. In short, our main recommendation is to separately report agreement on model-correct and model-error prompts, requiring the same incorrect answer on the error stratum in particular. To make these results interpretable, report the evaluated split, the number of prompts in each stratum, circuit size and ablation rule, since circuit evaluations depend on these methodological choices (Miller et al., 2024).

6 RELATED WORK

Manual circuit analyses aim to discover compact explanations of model behaviour (Wang et al., 2023), while automated methods like ACDC and EAP-IG automate the identification of relevant components (Conmy et al., 2023; Hanna et al., 2024). Evaluating these explanations still remains as a challenge. Miller et al. (2024) show that circuit faithfulness depends greatly on ablation methodology, and Shi et al. (2024) develop statistical tests of behavioural preservation, localization, and minimality. Mueller et al. (2025) separates components that improve task performance from those with any measurable influence, including negative effects, and evaluates circuit discovery across sizes. Nikankin et al. (2025) analyze arithmetic heuristics and link their failures with reduced support for correct-answer logits, while Bertolazzi et al. (2025) show that models often accept incorrect arithmetic solutions because they check whether the stated numbers agree with each other rather than if the calculation is correct. These works provide mechanistic accounts of specific model failures. Our work systematically tests whether existing circuit explanations reproduce their models’ wrong answers, revealing frequent shortfalls relative to the correct-case preservation and tracing omitted computations that recover a subset of those errors.

7 LIMITATIONS AND CONCLUSION

Limitations. Our findings spans IOI, DOCSTRING, and MIB across multiple models, extraction methods, circuit sizes, and ablation settings, but our conclusions are scoped to these tested settings and their benchmarks. Our detailed case study concerns one IOI reference circuit and its found extension; it illustrates specific recovered errors without establishing that the same mechanisms generalize to other circuits or tasks. Although several recovery strategies were tested and demonstrations indicate that significant recovery is possible, we neither exhaust all possible remedies nor establish a generalized solution for recovering omitted computations across all circuit settings while consistently preserving correct behaviour.

Conclusion. Explaining a model’s behaviour requires accounting for its failures as well as its successes. The tested manual circuits and most automated extraction methods we evaluate often fail this requirement, reproducing correct predictions substantially better than the model’s particular wrong answers. Our IOI case study demonstrates that missing errors can be recovered and traces how specific missed computations produce these specific wrong answers. Therefore, we recommend evaluating exact wrong-answer reproduction alongside correct-answer preservation as a necessary test of circuits intending to explain model behaviour.

REFERENCES

- Leonardo Bertolazzi, Philipp Mondorf, Barbara Plank, and Raffaella Bernardi. The validation gap: A mechanistic analysis of how language models compute arithmetic but fail to validate it. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 29387–29424, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-332-6. doi: 10.18653/v1/2025.emnlp-main.1495. URL <https://aclanthology.org/2025.emnlp-main.1495/>.
- Adithya Bhaskar, Alexander Wettig, Dan Friedman, and Danqi Chen. Finding transformer circuits with edge pruning. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang (eds.), *Advances in Neural Information Processing Systems*, volume 37, pp. 18506–18534. Curran Associates, Inc., 2024. doi: 10.52202/079017-0587. URL https://proceedings.neurips.cc/paper_files/paper/2024/file/20fdaf67581e6d7157376dled584040a-Paper-Conference.pdf.
- Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge, 2018. URL <https://arxiv.org/abs/1803.05457>.
- Arthur Conmy, Augustine N. Mavor-Parker, Aengus Lynch, Stefan Heimersheim, and Adrià Garriga-Alonso. Towards automated circuit discovery for mechanistic interpretability. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL <https://openreview.net/forum?id=89ia77nZ8u>.
- Michael Hanna, Ollie Liu, and Alexandre Variengien. How does GPT-2 compute greater-than?: Interpreting mathematical abilities in a pre-trained language model. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL <https://openreview.net/forum?id=p4PckNQR8k>.
- Michael Hanna, Sandro Pezzelle, and Yonatan Belinkov. Have faith in faithfulness: Going beyond circuit overlap when finding model mechanisms. In *First Conference on Language Modeling*, 2024. URL <https://openreview.net/forum?id=TZ0CCGDcuT>.
- Stefan Heimersheim and Jett Janiak. A circuit for python docstrings in a 4-layer attention-only transformer. AI Alignment Forum, February 2023. URL <https://www.alignmentforum.org/posts/u6KXXmKFbXfWzoAXn/a-circuit-for-python-docstrings-in-a-4-layer-attention-only>.
- Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In *International Conference on Learning Representations*, 2017. URL <https://openreview.net/forum?id=Hkg4TI9xl>.
- Alon Jacovi and Yoav Goldberg. Towards faithfully interpretable NLP systems: How should we define and evaluate faithfulness? In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel Tetreault (eds.), *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 4198–4205, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.386. URL <https://aclanthology.org/2020.acl-main.386/>.
- Maximilian Li and Lucas Janson. Optimal ablation for interpretability. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL <https://openreview.net/forum?id=opt72TYzwZ>.
- Joseph Miller, Bilal Chughtai, and William Saunders. Transformer circuit evaluation metrics are not robust. In *First Conference on Language Modeling*, 2024. URL <https://openreview.net/forum?id=zSf8PJyQb2>.
- Aaron Mueller, Atticus Geiger, Sarah Wiegreffe, Dana Arad, Iván Arcuschin, Adam Belfki, Yik Siu Chan, Jaden Fried Fiotto-Kaufman, Tal Haklay, Michael Hanna, Jing Huang, Rohan Gupta, Yaniv Nikankin, Hadas Orgad, Nikhil Prakash, Anja Reusch, Aruna Sankaranarayanan, Shun Shao, Alessandro Stolfo, Martin Tutek, Amir Zur, David Bau, and Yonatan Belinkov. MIB: A mechanistic interpretability benchmark. In *Forty-second International Conference on Machine Learning*, 2025. URL <https://openreview.net/forum?id=sSrOwve6vb>.

-
- Yaniv Nikankin, Anja Reusch, Aaron Mueller, and Yonatan Belinkov. Arithmetic without algorithms: Language models solve math with a bag of heuristics. In Y. Yue, A. Garg, N. Peng, F. Sha, and R. Yu (eds.), *International Conference on Learning Representations*, volume 2025, pp. 55939–55965, 2025. URL https://proceedings.iclr.cc/paper_files/paper/2025/file/8c5f30296296d2ae402ebbd09aaa9c12-Paper-Conference.pdf.
- Chris Olah, Nick Cammarata, Ludwig Schubert, Gabriel Goh, Michael Petrov, and Shan Carter. Zoom in: An introduction to circuits. *Distill*, 2020. doi: 10.23915/distill.00024.001. <https://distill.pub/2020/circuits/zoom-in>.
- Claudia Shi, Nicolas Beltran-Velez, Achille Nazaret, Carolina Zheng, Adrià Garriga-Alonso, Andrew Jesson, Maggie Makar, and David Blei. Hypothesis testing the circuit hypothesis in LLMs. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL <https://openreview.net/forum?id=5ai2YFAXV7>.
- Aaquib Syed, Can Rager, and Arthur Conmy. Attribution patching outperforms automated circuit discovery. In Yonatan Belinkov, Najoung Kim, Jaap Jumelet, Hosein Mohebbi, Aaron Mueller, and Hanjie Chen (eds.), *Proceedings of the 7th BlackboxNLP Workshop: Analyzing and Interpreting Neural Networks for NLP*, pp. 407–416, Miami, Florida, US, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.blackboxnlp-1.25. URL <https://aclanthology.org/2024.blackboxnlp-1.25/>.
- Niels uit de Bos and Adrià Garriga-Alonso. Adversarial circuit evaluation. In *ICML 2024 Workshop on Mechanistic Interpretability*, 2024. URL <https://openreview.net/forum?id=I5E9ZZNBjT>.
- Kevin Ro Wang, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt. Interpretability in the wild: a circuit for indirect object identification in GPT-2 small. In *The Eleventh International Conference on Learning Representations*, 2023. URL <https://openreview.net/forum?id=NpsVSN6o4ul>.

Table 2: IOI/Docstring data coverage. Discovery pools are used in full for current EAP-IG, Edge Pruning where supported, and OA fitting.

Task	Split	Rows evaluated	Candidate errors	Candidate correct
IOI	Discovery pool	13,000	135	12,865
IOI	Validation	10,000	95	9,905
IOI	Test census	100,000	884	99,116
IOI	Circuit-scored test sample	10,884	884	10,000
Docstring	Discovery pool	3,000	1,027	1,973
Docstring	Validation	2,000	676	1,324
Docstring	Test	10,000	3,536	6,464

A EXPERIMENT DETAILS: IOI AND DOCSTRING

A.1 MODELS, PROMPTS, AND EVALUATION POPULATIONS

All IOI experiments use the frozen GPT-2 small checkpoint (12 layers, 12 attention heads per layer). DOCSTRING uses NEELNANDA/ATTN_ONLY_4L512W_C4_CODE, a four-layer, eight head per layer, attention only model. In these computations, we use float32 with TF32 disabled; model weights are fixed throughout extraction and replacement fitting.

IOI Construction. The generator uses 15 template families with ABBA and BABA name order, resulting in 30 template/order cells. We filter names, places, and objects to single tokens. Two distinct names fill each clean prompt, with the repeated name representing the subject (S) and the other name as the indirect object (IO). For ablation, we sample a corresponding prompt from the same template using three distinct names, producing an ABC prompt in which the repetition structure is removed. The lengths of x' and x token lengths must match. Therefore, x' may change object and place words as well as names, instead of a names-only counterfactual.

Docstring construction. We use the public ACDC generator in its reST-style format. Each prompt contains a function definition with two prefix arguments, followed by three matching arguments and a suffix argument. The docstring documents the first two matching arguments, and the task is to predict the third as the next entry. We use no docstring-prefix arguments, a three-word method description, two-word argument descriptions, and function arguments without default values. The next argument is scored against a fixed set of 14 benchmark candidate argument tokens (the correct argument and 13 alternatives). For ablations, x' is from `random_random` corrupted dataset used by ACDC, which independently randomizes the variable names in both the function definition and the docstring.

Coverage and seperation. Our discovery pools contain 13,000 IOI examples and 3,000 DOCSTRING examples which includes both correct and incorrect model predictions, with equal weight per example. Discovery, validation, and test sets are disjoint, including the prompts used for ablation.

For IOI, we evaluate the circuits on 10,884 prompts sampled from the 100,000 prompt test pool while retaining all model wrong answers and weighting results to account for the sampling. For DOCSTRING, we evaluate circuits on all 10,000 test prompts.

Prediction and uncertainty. Candidates are sorted by token ID before argmax, so on ties, the lowest token ID is selected. Correct/error classification is defined by this prediction. Exact error agreement counts the identical wrong candidate on every model error. The reported gap intervals use 10,000 percentile bootstrap draws, resampling within the three IOI sampling cells. For Edge Pruning, we average the three seed agreement indicators for each prompt before bootstrapping shared prompts.

Table 3: OA training for current recovery/reference rows. Selection uses minimum validation KL

Task	Circuit	Epochs	Updates	Selected epoch
IOI	Manual / ACDC / EAP-IG	13	10,725	12
IOI	Edge Pruning seed 0	12	9,900	9
IOI	Edge Pruning seeds 1, 2	13	10,725	12
Docstring	Manual	26	4,888	23
Docstring	ACDC $\tau = .005$	26	4,888	23
Docstring	ACDC $\tau = .02$	29	5,452	26
Docstring	EAP-IG	30	5,640	27

A.2 DISCOVERY IMPLEMENTATIONS

Manual references. The IOI reference contains 26 attention heads at specific positions: previous-token heads at S1+1, induction and duplicate-token heads at S2, and the remaining heads at END. All other attention-head outputs are ablated with MLPs remaining active. We provide Appendix D.1 which lists the retained heads details and positions. For DOCSTRING, the retained reference heads are: 0.2, 0.4, 0.5, 1.2, 1.4, 2.0, 3.0, 3.6.

ACDC. ACDC checks a candidate edge removal against the current circuits and commits to the removal when the increase in mean $D_{KL}(p_{\mathcal{M}}||p_C)$ is below its selected threshold (Conmy et al., 2023). For both tasks, the loss compares full-vocabulary distributions at the answer position without using ground-truth labels. For IOI, we use an implementation built on AutoCircuit¹. For DOCSTRING, we use the authors’ ACDC implementation² with redundant-edge removal and absolute-value thresholding disabled. These fixed circuits are evaluated on the held-out test sets.

EAP-IG. EAP uses activation difference and local gradients to approximate edge interventions (Syed et al., 2024). We use the input-integrated-gradient variant and circuit search of Hanna et al. (2024).³ Attribution scores are computed over the complete discovery split using five interpolation steps from the corrupt to clean input embeddings. The objective is the full-vocabulary $D_{KL}(p_{\mathcal{M}}||p_C)$ at the answer position. Circuits are constructed backward from the output using absolute attribution scores, allowing for both positive and negative attributions to be picked up, followed by the removal of disconnected components.

Edge Pruning. We use the authors’ IOI implementation of Edge Pruning (Bhaskar et al., 2024).⁴ This method learns a sparse circuit by using learnable gates on edges between the transformer components and optimizing these gates to preserve the model’s behaviour while encouraging sparsity. We fit a range of sparsity targets using three random seeds and over the complete 13,000 example discovery set. Each fit runs for 3,000 updates with batch size of 32, learning rate of 0.8, and 2,500 step sparsity warmup. The separate node-loss term is disabled. Dropout is disabled and gradients are clipped at norm 1. The three random seeds are 0, 1, and 2. The sparsity-target grid is

$$\{0.2, 0.4, 0.6, 0.8, 0.9, 0.94, 0.945, 0.95, 0.955, 0.96, 0.965, 0.97, 0.975, 0.98, 0.985, 0.99, 0.995, 1, 1.01, 1.02, 1.05, 1.1\}.$$

Targets above one are optimization targets, not realized sparsity fractions. We discretize the final training checkpoint using the implementation’s thresholding procedure and report actual retained edge counts.

We don’t evaluate Edge Pruning on DOCSTRING as the official implementation does not support its attention-only architecture.

A.3 REPLACEMENT ACTIVATIONS AND NORMALIZED FAITHFULNESS

Mean IOI replacements are per-template, per-position averages of the source activations on 128 independent ABC donors. For DOCSTRING, we generate a separate set of 1,024 prompt pairs using the same ACDC docstring generator and corruption procedure as the task dataset. We exclude duplicate prompts across this set and the discovery and evaluation sets. Mean replacements are position-specific averages of source activations over the corrupted prompts in this reference set.

Optimal ablation. Following optimal ablation (Li & Janson, 2024), we replace each component outside the fixed circuit with a learned, input-independent constant. For each circuit, all constants are jointly learned to minimize the full-vocab $D_{\text{KL}}(p_{\mathcal{M}}||p_C)$ between the full model and the circuit. Each constant is shared across all token positions and all downstream components that read from it. Attention-head constants are fitted in the head’s output space before W_O . We use Adam $\alpha = 0.002$ with batch of 16, each batch containing a single template and sequence length. We train for at least three epochs and stop when validation KL has not strictly decreased for three consecutive epochs. We report the test performance of the checkpoint with the lowest validation KL.

Table 4: Summary of attempts to improve exact reproduction of model errors, with their correct-case effects and limitations.

Approach	Observed result	Tradeoff or limitation
Full-training discovery	Correct–error agreement gaps persist on Gemma ARC-Challenge despite errors comprising 38.4% of discovery examples.	Greater discovery coverage has mixed effects across settings; exposure to errors does not ensure their reproduction.
Error reweighting	IOI ACDC: assigning errors 50% of discovery KL weight raises A_{err} from 9.3% to 37.0%.	A_{ok} falls from 98.7% to 91.0%.
Distinct-error enrichment	IOI ACDC: A_{err} rises from 9.3% to 44.2% with 500 error and 500 correct discovery examples.	A_{ok} falls from 98.7% to 91.4%; enrichment changes discovery composition as well as error prevalence.
Optimal ablation	Improves both agreement measures for some Docstring circuits; large IOI agreement gaps remain.	Benefits depend on the circuit and task; minimizing KL does not ensure high exact-error agreement.
Error-conditioned replacements	Mean and resample replacements increase IOI exact-error agreement.	Scalar subject-logit shifts match or exceed recovery at approximately matched correct-case cost. These controls are calibrated on evaluation correct cases.
Scalar and threshold calibration	Can substantially increase IOI exact-error agreement; matching overall error rates does not consistently recover particular errors.	Aggressive thresholds can narrow the agreement gap by reducing correct preservation.
Candidate-specific logit calibration	Qwen ARC-Challenge: a fitted candidate bias raises A_{err} from 38.5% to 62.8% and A_{ok} from 59.3% to 70.3% on 169 reserved validation questions.	A successful partial recovery at the nominal 2% edge budget; an added output correction does not establish the original circuit’s causal fidelity.
Targeted circuit expansion	Adding 63 IOI head–position rules raises A_{err} from 14.2% to 75.1% on the original held-out evaluation.	A_{ok} falls by 0.41 percentage points there and 0.85 points on a fresh 5,200-prompt check, exceeding the original 0.5-point tolerance on the fresh sample.

¹<https://github.com/UFO-101/auto-circuit>

²<https://github.com/ArthurConmy/Automatic-Circuit-Discovery>

³<https://github.com/hannamw/eap-ig>

⁴<https://github.com/princeton-nlp/Edge-Pruning>

Attempts to recover model errors. Table 4 summarizes interventions targeting discovery data, ablation values, output predictions, and circuit membership. We test whether exposing extraction to more errors, increasing their discovery weight, changing replacement activations, calibrating circuit outputs, or restoring omitted components improves reproduction of the model’s errors. Several interventions do produce substantial gains, but their correct agreement effects vary.

B MIB DATA, EXTRACTION, AND METRIC IMPLEMENTATION

Table 5: Complete discovery coverage and candidate-scored public-test strata.

Setting	Train N	Train correct	Train errors	Test N	Test correct	Test errors
Llama ARC-Challenge	1119	908	211	586	464	122
Gemma ARC-Challenge	1119	689	430	586	349	237
Qwen ARC-Challenge	1119	659	460	586	315	271
Llama ARC-Easy	2251	2064	187	1188	1097	91
Gemma ARC-Easy	2251	1763	488	1188	927	261
Llama subtraction	17424	16575	849	1000	944	56

Dataset. We use MIB’s public prompts, splits and counterfactual fields (Mueller et al., 2025). The evaluated curves come from the full public-training set. We report the full correct / error statistics in Table 5.

Answer candidate and tie breaking. ARC predictions select based on the highest logit among the prompt’s answer-label tokens. Llama subtraction uses the single-token integer canddiates from 0 to 99. The original candidate order is the tie breaker: choice order for ARC and ascending numerical order for arithmetic. **This differs from the lowest token ID rule in the other tasks.**

Counterfactuals and circuit extraction. We extract MIB circuits using EAP-IG (Hanna et al., 2024) , with five input-interpolation steps and attribution scores computed over the entire public training split. For ARC counterfactual prompts replace the letter labels with numbers while preserving the question and answer choices. For subtraction, they replace the operands with randomly sampled values. We use these paired prompts for circuit scoring and evaluation, replacing excluded edge contributions with activations from the corresponding counterfactual run.

Circuit budgets and MIB metrics. Following MIB, we evaluate circuits at edge budgets

$$s \in \{0.001, 0.002, 0.005, 0.01, 0.02, 0.05, 0.1, 0.2, 0.5, 1\}$$

. Let F_j denote normalized task-score faithfulness at budget s_j . We compute

$$\text{CPR} = \sum_{j=1}^9 (s_{j+1} - s_j) \frac{F_j + F_{j+1}}{2}, \quad \text{CMD} = \sum_{j=1}^9 (s_{j+1} - s_j) \frac{|1 - F_j| + |1 - F_{j+1}|}{2}.$$

Table 6 reports CPR (higher is better) and CMD (lower is better).

C MARGIN-MATCHED AGREEMENT

We examine whether differences in intact-model prediction margins account for the gap between correct-case preservation and error reproduction. This analysis reuses the same evaluated circuits and their predictions. For all evaluations, predictions are selected through argmax over the benchmark candidate set $\mathcal{K}(x)$.

Matching procedure. For IOI and Docstring, we match on the highest-versus-second-highest candidate logits. Within each seetting, we pair model-error examples with model correct examples without replacement, within a 0.1 logit slack.

Table 6: Public-test MIB aggregate task-score metrics

Model	Task	CPR $\uparrow$	CMD $\downarrow$
Llama-3.1 8B	ARC-Challenge	0.8388	0.1602
Gemma-2 2B	ARC-Challenge	1.0017	0.0547
Qwen-2.5 0.5B	ARC-Challenge	0.9364	0.0646
Llama-3.1 8B	ARC-Easy	0.8458	0.1639
Gemma-2 2B	ARC-Easy	0.9943	0.0392
Llama-3.1 8B	Subtraction	0.9954	0.0036

Table 7: Agreement with $\mathcal{M}$ after matching correct and errors model predictions on absolute answer margin. Predictions are selected by argmax over the benchmark candidate set $\mathcal{K}(x)$; Circuits and selection procedures are the same to Table 1.

Circuit	Ablation	Matched agreement (%)		100 Δ_{match} (pp)
		A_{ok}	A_{err}	[95% CI]
<i>IOI</i>				
Manual reference	Mean	94.9	14.8	80.1 [77.3, 83.0]
	Resample (ABC)	71.3	40.0	31.3 [26.7, 36.0]
	OA (KL) [†]	98.4	10.2	88.2 [86.0, 90.4]
ACDC ($\tau = 0.003$)	Mean	91.1	11.3	79.8 [76.8, 82.7]
	Resample (ABC)	80.9	24.1	56.8 [52.7, 60.7]
	OA (KL) [†]	96.3	8.3	88.0 [85.7, 90.2]
EAP-IG-KL	Mean	81.9	42.4	39.5 [35.2, 43.9]
	Resample (ABC)	73.4	51.8	21.6 [17.0, 26.1]
	OA (KL) [†]	92.3	45.8	46.5 [42.7, 50.2]
Edge Pruning	Mean	93.0	11.1	81.9 [79.7, 83.9]
	Resample (ABC)	84.3	17.3	67.0 [63.8, 70.1]
	OA (KL) [†]	92.7	15.4	77.3 [75.0, 79.6]
<i>Docstring</i>				
Manual reference	Mean	72.9	35.8	37.1 [35.0, 39.2]
	Resample	43.4	38.9	4.4 [2.1, 6.7]
	OA (KL)	77.3	42.4	34.8 [32.8, 36.9]
ACDC ($\tau = 0.005$)	Mean	61.6	53.3	8.3 [6.0, 10.5]
	Resample	65.4	56.3	9.1 [6.9, 11.3]
	OA (KL)	79.6	41.5	38.2 [36.1, 40.2]
ACDC ($\tau = 0.02$)	Mean	71.1	37.2	33.9 [31.7, 36.1]
	Resample	54.3	41.9	12.4 [10.1, 14.7]
	OA (KL)	73.9	39.0	34.9 [32.7, 37.0]
EAP-IG-KL	Mean	56.7	69.4	−12.6 [−14.8, −10.5]
	Resample	57.3	66.3	−9.0 [−11.1, −6.8]
	OA (KL)	85.9	60.0	25.9 [24.1, 27.7]

IOI and Docstring. We use the absolute difference between the highest and second-highest full model logits over $K(x)$. Matching still retains 805/884 IOI errors and 3,534/3,536 Docstring errors. All twelve IOI configurations still have positive matched gaps. Docstring EAP-IG-KL is an exception under mean and resample ablation, with negative percentage points.

MIB. Figure 3 uses the top1 minus top2 candidate margin, with fixed pairs across size. Matching reduces several ARC gaps, but results still depend on setting and size. Subtraction margin matching retains only 20/56 errors.




Figure 3: Correct minus error agreement gaps on MIB before and after margin matching. Circuits are extracted using EAP-IG on the full public-training split and evaluated on the public-test split. Correct and error examples are bucketed within each model–task setting within a 0.1 logit range without replacement; Shading denotes pointwise 95% bootstrap intervals.

Table 8: IOI Manual Reference Circuit Heads

Reference group	Heads	Retained position
Name Movers	9.9, 10.0, 9.6	END
Backup Name Movers	10.10, 10.6, 10.2, 10.1, 11.2, 9.7, 9.0, 11.9	END
Negative Name Movers	10.7, 11.10	END
S-Inhibition	7.3, 7.9, 8.6, 8.10	END
Induction	5.5, 5.8, 5.9, 6.9	S2
Duplicate Token	0.1, 0.10, 3.0	S2
Previous Token	2.2, 4.11	S1+1

D IOI CASE-STUDY DETAILS

D.1 TASK, PREDICTION RULE, AND REFERENCE CIRCUIT

Task and terminology. Indirect object identification (IOI) models the task of predicting the recipient of an action. For instance, in "Then, Sara and Courtney went to the hospital. Courtney gave a bone to", in this case, the correct indirect object (IO) is Sara, and the subject (S) is Courtney. We define the subject’s first and second occurrences by S1 and S2, the position right after its first occurrence by S1+1, the final input position by END. For ABBA prompts, the first mentioned name is IO and the second mentioned name is S. For BABA prompts, the first two roles are reversed. The repeated name is S in both cases.

Exact answers and conditional agreement. For every prediction in this case study, it is selected by argmax over the fixed, prompt-specific candidates [IO, S], with ties assigned to IO. Define

$$m_C(x) = z_C(\text{IO} \mid x) - z_C(\text{S} \mid x), \quad \hat{y}_C(x) = \begin{cases} \text{IO}, & m_C(x) \geq 0, \\ \text{S}, & m_C(x) < 0. \end{cases} \quad (7)$$

So, on model errors, a negative margin reproduces that particular wrong subject name.

Reference implementation. We use GPT-2 small in float32 and the published IOI head groups from Wang et al. (2023), instantiated as the 26 nodes in Table 8.

Data and search space. We use a 60,000 prompt base, split by unordered name pair into 42,584 training prompts (463 model errors) and 17,416 validation prompts (177 errors). The candidate

space contains 3,574 supported additions across all 144 heads and 25 position rules: END, IO, S1, S2, S1+1, BOS, and offsets from END excluding the officially listed positions. Our term P_{added} is the mean number of instantiated additional head outputs per prompt.

Screening candidate nodes. Evaluating every possible addition at every search step is expensive. Therefore, we use gradients to approximate promising additions, then we evaluate the candidates exactly. We represent the circuit with gates $\mathbf{g}$, one for each head-position:

$$\tilde{\mathbf{o}}_i(x; \mathbf{g}) = \mu_{i,t(x)} + g_i(\mathbf{o}_i(x; \mathbf{g}) - \mu_{i,t(x)}), \quad (8)$$

where $\mathbf{o}_i$ is the output of the intervened circuit and $\mu_{i,t(x)}$ is its template-matched ablation mean.

At each search step, we temporarily relax the candidate gates to $[0, 1]$ and differentiate the full-training loss

$$\mathcal{L}(\mathbf{g}) = \text{mean softplus}_{x \in \mathcal{E}_{tr}}(m_C(\mathbf{g})(x)) + w \text{mean softplus}_{x \in \mathcal{O}_{tr}}(-m_C(\mathbf{g})(x)), \quad (9)$$

where $\mathcal{E}_{tr}$ and $\mathcal{O}_{tr}$ are the original model errors and correct examples, respectively. We set $w = 8$ when correct agreement falls more than 0.005 below the reference circuit, and $w = 1$ otherwise.

We rank omitted outputs by

$$s_i = - \left. \frac{\partial \mathcal{L}(\mathbf{g})}{\partial g_i} \right|_{\mathbf{g}=\mathbf{g}_{current}}, \quad (10)$$

These proposals are then evaluated on the complete training prompt set with binary gates.

Evaluating and selection additions. At each search step, we test each of the four highest-scoring additions individually, every pair among those four, and three larger proposals containing the top 4, 8, or 16 additions. We remove duplicate proposals and evaluate each remaining circuit on the entire training set, with every gate set to either zero or one. We select the proposal by maximizing:

$$J(C) = A_{err}(C) - 8[A_{ok}(C_0) - A_{ok}(C) - 0.005]_+ - \lambda_P P_{added}(C). \quad (11)$$

This score rewards exact error reproduction while penalizing correct agreement drops, and penalizes big extension sizes. We run two searches from C_0 , using $\lambda_P \in \{0.0005, 0.002\}$, each with at most 32 addition rounds and 128 added rules.

During each search, we also test removing previous added nodes, either individually or together with other additions part of the same head. We accept a removal only if it maintains or improves $J(C)$, while keeping the original reference circuit intact.

Choosing the final extension. On validation, we keep candidates whose correct agreement is at most 0.005 below C_0 . Among these candidates, let G^* be the largest improvement in exact error agreement over C_0 . We select candidates that minimize P_{added} subject to retaining at least 90% of G^* and breaking ties by higher error agreement.

Then, we evaluate every added component and every joint delete of a head’s added rules. After adding the candidates, we recompute G^* , and reapply the same selection process until no tested deletion yields a smaller circuit satisfying both agreement thresholds. Convergence happened after three sweeps to 63 added rules.

Finally, we freeze this extension and evaluate it on a 26,000 hold out set with 225 model errors and 25,775 model correct examples.