

```
1 using GSL
```

```
1 using MultipleScattering
```

```
1 using Plots
```

```
1 using PyPlot
```

```
PyPlotBackend()
```

```
1 pyplot()
```

```
1 using LinearAlgebra
```

```
1 using DelimitedFiles
```

```
1 using Base.Threads
```

```
1 hk(n::Integer,x::Float64)=sf_bessel_jl(n,x)+im*sf_bessel_yl(n,x);
```

ymn (generic function with 1 method)

```
1 function ymn(n::Integer,m::Integer,θ::Float64,φ::Float64)    #spherical harmonics
2 if m>=0
3     return sf_legendre_sphPlm(n,m,cos(θ))*exp(im*m*φ);
4 elseif isodd(-m)
5     return -sf_legendre_sphPlm(n,-m,cos(θ))*exp(im*m*φ);
6 else
7     return sf_legendre_sphPlm(n,-m,cos(θ))*exp(im*m*φ);
8 end
9 end
```

Selection deleted

buildModelProto (generic function with 1 method)

```

1 #####build simulation model#####
2 function buildModelProto(dimensionTmp::Integer, pbTmp::Float64, cbTmp::Float64,
  ppTmp::Float64, cpTmp::Float64, wbTmp::Float64, pNoTmp::Integer, RsTmp::Float64,
  parPos::Matrix{Float64})
3 parPosTmp=deepcopy(parPos);
4 #####set incident waves#####
5 incAmpTmp = 3000.0; #amplitude of incident beam
6 incDirTmp1 = [0.0, 0.0, 1.0]; #set incident direction 1
7 incDirTmp2 = [0.0, 0.0, -1.0]; #set incident direction 2
8 incPosTmp1 = [0.0, 0.0, -1]; #original position of incident wave 1
9 incPosTmp2 = [0.0, 0.0, 1]; #original position of incident wave 2
10 bgMediumTmp = Acoustic(dimensionTmp; ρ = pbTmp, c = cbTmp); #build background
    acoustic model
11 waveTmp = plane_source(bgMediumTmp; amplitude = incAmpTmp, direction = incDirTmp1,
    position = incPosTmp1)+plane_source(bgMediumTmp; amplitude = -incAmpTmp, direction =
    incDirTmp2, position = incPosTmp2); #build incident plane wave
12 #####incident wave done#####
13 #####set particles#####
14 parMediumTmp = Acoustic(dimensionTmp; ρ = ppTmp, c = cpTmp); #build the acoustic
    model in particles
15 particlesTmp=Array{Particle{dimensionTmp, Acoustic{Float64, dimensionTmp},
    Sphere{Float64, dimensionTmp}}}(undef, 0); #define a null array to store particles
    model
16 #build particle set
17 for iTmp in 1:pNoTmp
18     parShapeTmp=Sphere(parPosTmp[iTmp,:],RsTmp);
19     particlesTmp=push!(particlesTmp,Particle(parMediumTmp,parShapeTmp));
20 end
21 #####particles done#####
22 simModelTmp=FrequencySimulation(particlesTmp,waveTmp);#build simulation model
23 return simModelTmp
24 end

```

getCoefProto (generic function with 1 method)

```

1 #####get expansion coefficients#####
2 function getCoefProto(wbTmp::Float64, modelTmp::FrequencySimulation,
  coefOrderTmp::Integer)
3 simModelTmp=modelTmp;
4 coefDataTmp=basis_coefficients(simModelTmp,wbTmp,basis_order=coefOrderTmp);#store the
    expansion coefficients
5 return coefDataTmp
6 end

```

Selection deleted

pProto (generic function with 1 method)

```

1 #####define function to calculate pressure in position [x,y,z]#####
2 function pProto(x::Float64, y::Float64, z::Float64, ωbTmp::Float64,
   modelTmp::FrequencySimulation, coefData::Matrix{ComplexF64})
3   coefDataTmp=deepcopy(coefData);
4   simModelTmp=modelTmp;
5   pNoTmp=length(simModelTmp.particles);
6   dimensionTmp=typeof(simModelTmp.source.medium).parameters[2];
7   cbTmp=Float64(simModelTmp.source.medium.c);      #make soundspeed a real number
8   coefOrderTmp=Int(sqrt(length(coefDataTmp[:,1])))-1;
9   parPosTmp=Matrix{Float64}(undef,pNoTmp,dimensionTmp);
10  k=ωbTmp/cbTmp;
11  for iTmp in 1:pNoTmp
12    for jTmp in 1:dimensionTmp
13      parPosTmp[iTmp,jTmp]=simModelTmp.particles[iTmp].shape.origin[jTmp];
14    end
15  end
16  pField=0.0+0.0*im;
17  r=Array{Float64}(undef,pNoTmp);
18  θ=Array{Float64}(undef,pNoTmp);
19  φ=Array{Float64}(undef,pNoTmp);
20  for iTmp in 1:pNoTmp
21    parPosTmp2=deepcopy(parPosTmp[iTmp,:]);
22    xx=x-parPosTmp2[1];
23    yy=y-parPosTmp2[2];
24    zz=z-parPosTmp2[3];
25    r[iTmp]=sqrt(xx*xx+yy*yy+zz*zz);
26    θ[iTmp]=acos(zz/max(r[iTmp],0.000000001));
27    if yy==0&&xx>0
28      φ[iTmp]=0.0;
29    elseif yy==0&&xx<0
30      φ[iTmp]=π;
31    else
32      φ[iTmp]=(1-sign(yy))*π+sign(yy)*acos(xx/max(sqrt(xx*xx+yy*yy),0.000000001));
33    end
34    for nTmp in 0:coefOrderTmp
35      for mTmp in -nTmp:nTmp
36        pField+=coefDataTmp[nTmp*nTmp+nTmp+mTmp+1,iTmp]*hk(nTmp,k*r[iTmp])*ymn(nT
          mp,mTmp,θ[iTmp],φ[iTmp]);
37      end
38    end
39  end
40  return pField+simModelTmp.source.field([x,y,z],ωbTmp);
41  end

```

Selection deleted

vProto (generic function with 1 method)

```

1 #####Calculate velocity field by using five-point stencil#####
2 function vProto(x::Float64, y::Float64, z::Float64, ωbTmp::Float64,
   coefDataTmp::FrequencySimulation, coefData::Matrix{ComplexF64})
3   coefDataTmp=deepcopy(coefData);
4   simModelTmp=modelTmp;
5   dimensionTmp=typeof(simModelTmp.source.medium).parameters[2];
6   δh=0.00005;
7   pbTmp=simModelTmp.source.medium.ρ;
8   vField=Array{ComplexF64}(undef,dimensionTmp);
9   pX2=pProto(x+2*δh,y,z,ωbTmp,simModelTmp,coefDataTmp);
10  pX1=pProto(x+δh,y,z,ωbTmp,simModelTmp,coefDataTmp);
11  pXN2=pProto(x-2*δh,y,z,ωbTmp,simModelTmp,coefDataTmp); #N denotes negative
12  pXN1=pProto(x-δh,y,z,ωbTmp,simModelTmp,coefDataTmp);
13  pY2=pProto(x,y+2*δh,z,ωbTmp,simModelTmp,coefDataTmp);
14  pY1=pProto(x,y+δh,z,ωbTmp,simModelTmp,coefDataTmp);
15  pYN2=pProto(x,y-2*δh,z,ωbTmp,simModelTmp,coefDataTmp);
16  pYN1=pProto(x,y-δh,z,ωbTmp,simModelTmp,coefDataTmp);
17  pZ2=pProto(x,y,z+2*δh,ωbTmp,simModelTmp,coefDataTmp);
18  pZ1=pProto(x,y,z+δh,ωbTmp,simModelTmp,coefDataTmp);
19  pZN2=pProto(x,y,z-2*δh,ωbTmp,simModelTmp,coefDataTmp);
20  pZN1=pProto(x,y,z-δh,ωbTmp,simModelTmp,coefDataTmp);
21  vField[1]=-im/pbTmp/ωbTmp*(-pX2+8*pX1-8*pXN1+pXN2)/12/δh;
22  vField[2]=-im/pbTmp/ωbTmp*(-pY2+8*pY1-8*pYN1+pYN2)/12/δh;
23  vField[3]=-im/pbTmp/ωbTmp*(-pZ2+8*pZ1-8*pZN1+pZN2)/12/δh;
24  return vField
25 end

```

Selection deleted

T (generic function with 1 method)

```

1 #####calculate time average of stress tensor#####
2 function T(x::Float64, y::Float64, z::Float64, ωbTmp::Float64,
   modelTmp::FrequencySimulation, coefData::Matrix{ComplexF64})
3   coefDataTmp=deepcopy(coefData);
4   simModelTmp=modelTmp;
5   dimensionTmp=typeof(simModelTmp.source.medium).parameters[2];
6   TDataTmp=Matrix{Float64}(undef,dimensionTmp,dimensionTmp); #matrix to store stress
   tensor in the form:
7   #####
8   ##### Txx Txy Txz #####
9   ##### Tyx Tyy Tyz #####
10  ##### Tzx Tzy Tzz #####
11  #####
12  pbTmp=simModelTmp.source.medium.ρ;
13  cbTmp=simModelTmp.source.medium.c;
14  vTmp=vProto(x,y,z,ωbTmp,simModelTmp,coefDataTmp)
15  vxTmp=vTmp[1];
16  vyTmp=vTmp[2];
17  vzTmp=vTmp[3];
18  cjvxTmp=conj(vxTmp);
19  cjvyTmp=conj(vyTmp);
20  cjvzTmp=conj(vzTmp);
21  pTmp=pProto(x,y,z,ωbTmp,simModelTmp,coefDataTmp);
22  cjpTmp=conj(pTmp);
23  vSqu=real(vxTmp*cjvxTmp+vyTmp*cjvyTmp+vzTmp*cjvzTmp);
24  pSquCoeff=real(pTmp*cjpTmp/2/pbTmp/cbTmp/cbTmp);
25  TDataTmp[1,1]=0.5*(pbTmp*(real(vxTmp*cjvxTmp)-0.5*vSqu)+pSquCoeff);
26  TDataTmp[1,2]=0.5*pbTmp*real(vxTmp*cjvyTmp);
27  TDataTmp[1,3]=0.5*pbTmp*real(vxTmp*cjvzTmp);
28  TDataTmp[2,1]=0.5*pbTmp*real(vyTmp*cjvxTmp);
29  TDataTmp[2,2]=0.5*(pbTmp*(real(vyTmp*cjvyTmp)-0.5*vSqu)+pSquCoeff);
30  TDataTmp[2,3]=0.5*pbTmp*real(vyTmp*cjvzTmp);
31  TDataTmp[3,1]=0.5*pbTmp*real(vzTmp*cjvxTmp);
32  TDataTmp[3,2]=0.5*pbTmp*real(vzTmp*cjvyTmp);
33  TDataTmp[3,3]=0.5*(pbTmp*(real(vzTmp*cjvzTmp)-0.5*vSqu)+pSquCoeff);
34  return TDataTmp
35  end

```

Selection deleted

fDens (generic function with 1 method)

```

1 #####calculate force density#####
2 function fDens(θ::Float64,φ::Float64,parID::Integer,wbTmp::Float64,
   modelTmp::FrequencySimulation, coefData::Matrix{ComplexF64})
3   coefDataTmp=deepcopy(coefData);
4   simModelTmp=modelTmp;
5   dimensionTmp=typeof(simModelTmp.source.medium).parameters[2];
6   fDensDataTmp=Array{Float64}(undef,dimensionTmp);    #[fDensx,fDensy,fDensz]
7   R=simModelTmp.particles[parID].shape.radius+0.00015;
8   x0=simModelTmp.particles[parID].shape.origin[1];#x0,y0,z0 denote particle's position
9   y0=simModelTmp.particles[parID].shape.origin[2];
10  z0=simModelTmp.particles[parID].shape.origin[3];
11  sθ=sin(θ);cθ=cos(θ);sφ=sin(φ);cφ=cos(φ);
12  xTmp=x0+R*sθ*cφ;
13  yTmp=y0+R*sθ*sφ;
14  zTmp=z0+R*cθ;
15  TData=T(xTmp,yTmp,zTmp,wbTmp,simModelTmp,coefDataTmp);
16  fDensDataTmp[1]=(TData[1,1]*sθ*cφ+TData[1,2]*sθ*sφ+TData[1,3]*cθ)*R*R*sθ;
17  fDensDataTmp[2]=(TData[2,1]*sθ*cφ+TData[2,2]*sθ*sφ+TData[2,3]*cθ)*R*R*sθ;
18  fDensDataTmp[3]=(TData[3,1]*sθ*cφ+TData[3,2]*sθ*sφ+TData[3,3]*cθ)*R*R*sθ;
19  return fDensDataTmp
20 end

```

forcePart1 (generic function with 1 method)

```

1 #####function to execute part of the parallel computation#####
2 function
   forcePart1(parID::Integer,n1::Integer,n2::Integer,lowLim1::Float64,upLim1::Float64,lowLim2::Float64,upLim2::Float64,wbTmp::Float64, modelTmp::FrequencySimulation,
   coefData::Matrix{ComplexF64})
3   coefDataTmp=deepcopy(coefData);
4   fDataTmp=[0.0,0.0,0.0]#####[fx,fy,fz]#####
5   xDataStoreTmp=zeros(n1,n2);
6   yDataStoreTmp=zeros(n1,n2);
7   zDataStoreTmp=zeros(n1,n2);
8   step1=(upLim1-lowLim1)/n1;
9   step2=(upLim2-lowLim2)/n2;
10  for i in 1:n1
11    θTmp=lowLim1+(i-1)*step1;
12    for j in 1:n2
13      φTmp=lowLim2+(j-1)*step2;
14      fDensData=fDens(θTmp,φTmp,parID,wbTmp,modelTmp,coefDataTmp);
15      xDataStoreTmp[i,j]=fDensData[1];
16      yDataStoreTmp[i,j]=fDensData[2];
17      zDataStoreTmp[i,j]=fDensData[3];
18    end
19  end
20  fDataTmp[1]=-sum(xDataStoreTmp)*step1*step2;
21  fDataTmp[2]=-sum(yDataStoreTmp)*step1*step2;
22  fDataTmp[3]=-sum(zDataStoreTmp)*step1*step2;
23  return fDataTmp
24 end

```

Selection deleted

forcePart2 (generic function with 1 method)

```
1 #####function to execute part of the parallel computation#####
2 function
  forcePart2(parID::Integer,n1::Integer,n2::Integer,lowLim1::Float64,upLim1::Float64,lowLim2::Float64,upLim2::Float64,wbTmp::Float64, modelTmp::FrequencySimulation,
  coefData::Matrix{ComplexF64})
3 coefDataTmp=deepcopy(coefData);
4 fDataTmp=[0.0,0.0,0.0]#####[fx,fy,fz]#####
5 xDataStoreTmp=zeros(n1,n2);
6 yDataStoreTmp=zeros(n1,n2);
7 zDataStoreTmp=zeros(n1,n2);
8 step1=(upLim1-lowLim1)/n1;
9 step2=(upLim2-lowLim2)/n2;
10 for i in 1:n1
11     θTmp=lowLim1+(i-1)*step1;
12     for j in 1:n2
13         φTmp=lowLim2+(j-1)*step2;
14         fDensData=fDens(θTmp,φTmp,parID,wbTmp,modelTmp,coefDataTmp);
15         xDataStoreTmp[i,j]=fDensData[1];
16         yDataStoreTmp[i,j]=fDensData[2];
17         zDataStoreTmp[i,j]=fDensData[3];
18     end
19 end
20 fDataTmp[1]=-sum(xDataStoreTmp)*step1*step2;
21 fDataTmp[2]=-sum(yDataStoreTmp)*step1*step2;
22 fDataTmp[3]=-sum(zDataStoreTmp)*step1*step2;
23 return fDataTmp
24 end
```

Selection deleted

forcePart3 (generic function with 1 method)

```
1 #####function to execute part of the parallel computation#####
2 function
  forcePart3(parID::Integer,n1::Integer,n2::Integer,lowLim1::Float64,upLim1::Float64,lowLim2::Float64,upLim2::Float64,wbTmp::Float64, modelTmp::FrequencySimulation,
  coefData::Matrix{ComplexF64})
3 coefDataTmp=deepcopy(coefData);
4 fDataTmp=[0.0,0.0,0.0]#####[fx,fy,fz]#####
5 xDataStoreTmp=zeros(n1,n2);
6 yDataStoreTmp=zeros(n1,n2);
7 zDataStoreTmp=zeros(n1,n2);
8 step1=(upLim1-lowLim1)/n1;
9 step2=(upLim2-lowLim2)/n2;
10 for i in 1:n1
11     θTmp=lowLim1+(i-1)*step1;
12     for j in 1:n2
13         φTmp=lowLim2+(j-1)*step2;
14         fDensData=fDens(θTmp,φTmp,parID,wbTmp,modelTmp,coefDataTmp);
15         xDataStoreTmp[i,j]=fDensData[1];
16         yDataStoreTmp[i,j]=fDensData[2];
17         zDataStoreTmp[i,j]=fDensData[3];
18     end
19 end
20 fDataTmp[1]=-sum(xDataStoreTmp)*step1*step2;
21 fDataTmp[2]=-sum(yDataStoreTmp)*step1*step2;
22 fDataTmp[3]=-sum(zDataStoreTmp)*step1*step2;
23 return fDataTmp
24 end
```

Selection deleted

forcePart4 (generic function with 1 method)

```
1 #####function to execute part of the parallel computation#####
2 function
  forcePart4(parID::Integer,n1::Integer,n2::Integer,lowLim1::Float64,upLim1::Float64,lowLim2::Float64,upLim2::Float64,wbTmp::Float64, modelTmp::FrequencySimulation,
  coefData::Matrix{ComplexF64})
3 coefDataTmp=deepcopy(coefData);
4 fDataTmp=[0.0,0.0,0.0]#####[fx,fy,fz]#####
5 xDataStoreTmp=zeros(n1,n2);
6 yDataStoreTmp=zeros(n1,n2);
7 zDataStoreTmp=zeros(n1,n2);
8 step1=(upLim1-lowLim1)/n1;
9 step2=(upLim2-lowLim2)/n2;
10 for i in 1:n1
11     θTmp=lowLim1+(i-1)*step1;
12     for j in 1:n2
13         φTmp=lowLim2+(j-1)*step2;
14         fDensData=fDens(θTmp,φTmp,parID,wbTmp,modelTmp,coefDataTmp);
15         xDataStoreTmp[i,j]=fDensData[1];
16         yDataStoreTmp[i,j]=fDensData[2];
17         zDataStoreTmp[i,j]=fDensData[3];
18     end
19 end
20 fDataTmp[1]=-sum(xDataStoreTmp)*step1*step2;
21 fDataTmp[2]=-sum(yDataStoreTmp)*step1*step2;
22 fDataTmp[3]=-sum(zDataStoreTmp)*step1*step2;
23 return fDataTmp
24 end
```

Selection deleted

forcePart5 (generic function with 1 method)

```
1 #####function to execute part of the parallel computation#####
2 function
  forcePart5(parID::Integer,n1::Integer,n2::Integer,lowLim1::Float64,upLim1::Float64,lowLim2::Float64,upLim2::Float64,wbTmp::Float64, modelTmp::FrequencySimulation,
  coefData::Matrix{ComplexF64})
3 coefDataTmp=deepcopy(coefData);
4 fDataTmp=[0.0,0.0,0.0]#####[fx,fy,fz]#####
5 xDataStoreTmp=zeros(n1,n2);
6 yDataStoreTmp=zeros(n1,n2);
7 zDataStoreTmp=zeros(n1,n2);
8 step1=(upLim1-lowLim1)/n1;
9 step2=(upLim2-lowLim2)/n2;
10 for i in 1:n1
11     θTmp=lowLim1+(i-1)*step1;
12     for j in 1:n2
13         φTmp=lowLim2+(j-1)*step2;
14         fDensData=fDens(θTmp,φTmp,parID,wbTmp,modelTmp,coefDataTmp);
15         xDataStoreTmp[i,j]=fDensData[1];
16         yDataStoreTmp[i,j]=fDensData[2];
17         zDataStoreTmp[i,j]=fDensData[3];
18     end
19 end
20 fDataTmp[1]=-sum(xDataStoreTmp)*step1*step2;
21 fDataTmp[2]=-sum(yDataStoreTmp)*step1*step2;
22 fDataTmp[3]=-sum(zDataStoreTmp)*step1*step2;
23 return fDataTmp
24 end
```

Selection deleted

forcePart6 (generic function with 1 method)

```
1 #####function to execute part of the parallel computation#####
2 function
  forcePart6(parID::Integer,n1::Integer,n2::Integer,lowLim1::Float64,upLim1::Float64,lowLim2::Float64,upLim2::Float64,wbTmp::Float64, modelTmp::FrequencySimulation,
  coefData::Matrix{ComplexF64})
3 coefDataTmp=deepcopy(coefData);
4 fDataTmp=[0.0,0.0,0.0]#####[fx,fy,fz]#####
5 xDataStoreTmp=zeros(n1,n2);
6 yDataStoreTmp=zeros(n1,n2);
7 zDataStoreTmp=zeros(n1,n2);
8 step1=(upLim1-lowLim1)/n1;
9 step2=(upLim2-lowLim2)/n2;
10 for i in 1:n1
11     θTmp=lowLim1+(i-1)*step1;
12     for j in 1:n2
13         φTmp=lowLim2+(j-1)*step2;
14         fDensData=fDens(θTmp,φTmp,parID,wbTmp,modelTmp,coefDataTmp);
15         xDataStoreTmp[i,j]=fDensData[1];
16         yDataStoreTmp[i,j]=fDensData[2];
17         zDataStoreTmp[i,j]=fDensData[3];
18     end
19 end
20 fDataTmp[1]=-sum(xDataStoreTmp)*step1*step2;
21 fDataTmp[2]=-sum(yDataStoreTmp)*step1*step2;
22 fDataTmp[3]=-sum(zDataStoreTmp)*step1*step2;
23 return fDataTmp
24 end
```

forcePart7 (generic function with 1 method)

```
1 #####function to execute part of the parallel computation#####
2 function
  forcePart7(parID::Integer,n1::Integer,n2::Integer,lowLim1::Float64,upLim1::Float64,lowLim2::Float64,upLim2::Float64,wbTmp::Float64, modelTmp::FrequencySimulation,
  coefData::Matrix{ComplexF64})
3 coefDataTmp=deepcopy(coefData);
4 fDataTmp=[0.0,0.0,0.0]#####[fx,fy,fz]#####
5 xDataStoreTmp=zeros(n1,n2);
6 yDataStoreTmp=zeros(n1,n2);
7 zDataStoreTmp=zeros(n1,n2);
8 step1=(upLim1-lowLim1)/n1;
9 step2=(upLim2-lowLim2)/n2;
10 for i in 1:n1
11     θTmp=lowLim1+(i-1)*step1;
12     for j in 1:n2
13         φTmp=lowLim2+(j-1)*step2;
14         fDensData=fDens(θTmp,φTmp,parID,wbTmp,modelTmp,coefDataTmp);
15         xDataStoreTmp[i,j]=fDensData[1];
16         yDataStoreTmp[i,j]=fDensData[2];
17         zDataStoreTmp[i,j]=fDensData[3];
18     end
19 end
20 fDataTmp[1]=-sum(xDataStoreTmp)*step1*step2;
21 fDataTmp[2]=-sum(yDataStoreTmp)*step1*step2;
22 fDataTmp[3]=-sum(zDataStoreTmp)*step1*step2;
23 return fDataTmp
24 end
```

forcePart8 (generic function with 1 method)

```
1 #####function to execute part of the parallel computation#####
2 function
  forcePart8(parID::Integer,n1::Integer,n2::Integer,lowLim1::Float64,upLim1::Float64,lowLim2::Float64,upLim2::Float64,wbTmp::Float64, modelTmp::FrequencySimulation,
  coefData::Matrix{ComplexF64})
3 coefDataTmp=deepcopy(coefData);
4 fDataTmp=[0.0,0.0,0.0]#####[fx,fy,fz]#####
5 xDataStoreTmp=zeros(n1,n2);
6 yDataStoreTmp=zeros(n1,n2);
7 zDataStoreTmp=zeros(n1,n2);
8 step1=(upLim1-lowLim1)/n1;
9 step2=(upLim2-lowLim2)/n2;
10 for i in 1:n1
11     θTmp=lowLim1+(i-1)*step1;
12     for j in 1:n2
13         φTmp=lowLim2+(j-1)*step2;
14         fDensData=fDens(θTmp,φTmp,parID,wbTmp,modelTmp,coefDataTmp);
15         xDataStoreTmp[i,j]=fDensData[1];
16         yDataStoreTmp[i,j]=fDensData[2];
17         zDataStoreTmp[i,j]=fDensData[3];
18     end
19 end
20 fDataTmp[1]=-sum(xDataStoreTmp)*step1*step2;
21 fDataTmp[2]=-sum(yDataStoreTmp)*step1*step2;
22 fDataTmp[3]=-sum(zDataStoreTmp)*step1*step2;
23 return fDataTmp
24 end
```

forceT1 (generic function with 1 method)

```
1 #####single-threaded routine#####
2 #####numerical quadrature for acoustic force#####
3 #####n1,n2 denote sample numbers in polar angle  $\theta$  and azimuthal angle  $\phi$ 
  coordinate respectively#####
4 function forceT1(parID::Integer,n1::Integer,n2::Integer,wbTmp::Float64,
  modelTmp::FrequencySimulation, coefData::Matrix{ComplexF64})
5 coefDataTmp=deepcopy(coefData);
6 fDataTmp=[0.0,0.0,0.0]#####[fx,fy,fz]#####
7 xDataStoreTmp=zeros(n1,n2);
8 yDataStoreTmp=zeros(n1,n2);
9 zDataStoreTmp=zeros(n1,n2);
10 step1= $\pi/n1$ ;
11 step2= $2*\pi/n2$ ;
12 for i in 1:n1
13      $\theta$ Tmp=(i-1)*step1;
14     for j in 1:n2
15          $\phi$ Tmp=(j-1)*step2;
16         fDensData=fDens( $\theta$ Tmp, $\phi$ Tmp,parID,wbTmp,modelTmp,coefDataTmp);
17         xDataStoreTmp[i,j]=fDensData[1];
18         yDataStoreTmp[i,j]=fDensData[2];
19         zDataStoreTmp[i,j]=fDensData[3];
20     end
21 end
22 fDataTmp[1]=-sum(xDataStoreTmp)*step1*step2;
23 fDataTmp[2]=-sum(yDataStoreTmp)*step1*step2;
24 fDataTmp[3]=-sum(zDataStoreTmp)*step1*step2;
25 return fDataTmp
26 end
```

forceT2 (generic function with 1 method)

```
1 #####2-threaded routine#####
2 #####numerical quadrature for acoustic force#####
3 #####n1,n2 denote sample numbers in polar angle  $\theta$  and azimuthal angle  $\phi$ 
  coordinate respectively#####
4 function forceT2(parID::Integer,n1::Integer,n2::Integer,wbTmp::Float64,
  modelTmp::FrequencySimulation, coefData::Matrix{ComplexF64})
5   threadNo=2;
6   threadNo1=1;
7   threadNo2=2;
8   n1Tmp=Int(n1/threadNo1);
9   n2Tmp=Int(n2/threadNo2);
10  lowLim1=Array{Float64}(undef,threadNo1);
11  upLim1=Array{Float64}(undef,threadNo1);
12  lowLim2=Array{Float64}(undef,threadNo2);
13  upLim2=Array{Float64}(undef,threadNo2);
14  for i in 1:threadNo1
15      lowLim1[i]=(i-1)* $\pi$ /threadNo1;
16      upLim1[i]=lowLim1[i]+ $\pi$ /threadNo1;
17  end
18  for i in 1:threadNo2
19      lowLim2[i]=(i-1)*2 $\pi$ /threadNo2;
20      upLim2[i]=lowLim2[i]+2 $\pi$ /threadNo2;
21  end
22  result1=Threads.@spawn
    forcePart1(parID,n1Tmp,n2Tmp,lowLim1[1],upLim1[1],lowLim2[1],upLim2[1],wbTmp,
    modelTmp, coefData);
23  result2=Threads.@spawn
    forcePart2(parID,n1Tmp,n2Tmp,lowLim1[1],upLim1[1],lowLim2[2],upLim2[2],wbTmp,
    modelTmp, coefData);
24  return fetch(result1) + fetch(result2)
25  end
```

forceT4 (generic function with 1 method)

```

1 #####4-threaded routine#####
2 #####numerical quadrature for acoustic force#####
3 #####n1,n2 denote sample numbers in polar angle  $\theta$  and azimuthal angle  $\phi$ 
  coordinate respectively#####
4 function forceT4(parID::Integer,n1::Integer,n2::Integer,wbTmp::Float64,
  modelTmp::FrequencySimulation, coefData::Matrix{ComplexF64})
5 threadNo=4;
6 threadNo1=2;
7 threadNo2=2;
8 n1Tmp=Int(n1/threadNo1);
9 n2Tmp=Int(n2/threadNo2);
10 lowLim1=Array{Float64}(undef,threadNo1);
11 upLim1=Array{Float64}(undef,threadNo1);
12 lowLim2=Array{Float64}(undef,threadNo2);
13 upLim2=Array{Float64}(undef,threadNo2);
14 for i in 1:threadNo1
15     lowLim1[i]=(i-1)* $\pi$ /threadNo1;
16     upLim1[i]=lowLim1[i]+ $\pi$ /threadNo1;
17 end
18 for i in 1:threadNo2
19     lowLim2[i]=(i-1)*2 $\pi$ /threadNo2;
20     upLim2[i]=lowLim2[i]+2 $\pi$ /threadNo2;
21 end
22 result1=Threads.@spawn
  forcePart1(parID,n1Tmp,n2Tmp,lowLim1[1],upLim1[1],lowLim2[1],upLim2[1],wbTmp,
  modelTmp, coefData);
23 result2=Threads.@spawn
  forcePart2(parID,n1Tmp,n2Tmp,lowLim1[1],upLim1[1],lowLim2[2],upLim2[2],wbTmp,
  modelTmp, coefData);
24 result3=Threads.@spawn
  forcePart3(parID,n1Tmp,n2Tmp,lowLim1[2],upLim1[2],lowLim2[1],upLim2[1],wbTmp,
  modelTmp, coefData);
25 result4=Threads.@spawn
  forcePart4(parID,n1Tmp,n2Tmp,lowLim1[2],upLim1[2],lowLim2[2],upLim2[2],wbTmp,
  modelTmp, coefData);
26 return fetch(result1) + fetch(result2) + fetch(result3) + fetch(result4)
27 end

```


forceT6 (generic function with 1 method)

```

1 #####6-threaded routine#####
2 #####numerical quadrature for acoustic force#####
3 #####n1,n2 denote sample numbers in polar angle  $\theta$  and azimuthal angle  $\phi$ 
  coordinate respectively#####
4 function forceT6(parID::Integer,n1::Integer,n2::Integer,wbTmp::Float64,
  modelTmp::FrequencySimulation, coefData::Matrix{ComplexF64})
5 threadNo=4;
6 threadNo1=2;
7 threadNo2=3;
8 n1Tmp=Int(n1/threadNo1);
9 n2Tmp=Int(n2/threadNo2);
10 lowLim1=Array{Float64}(undef,threadNo1);
11 upLim1=Array{Float64}(undef,threadNo1);
12 lowLim2=Array{Float64}(undef,threadNo2);
13 upLim2=Array{Float64}(undef,threadNo2);
14 for i in 1:threadNo1
15     lowLim1[i]=(i-1)* $\pi$ /threadNo1;
16     upLim1[i]=lowLim1[i]+ $\pi$ /threadNo1;
17 end
18 for i in 1:threadNo2
19     lowLim2[i]=(i-1)*2 $\pi$ /threadNo2;
20     upLim2[i]=lowLim2[i]+2 $\pi$ /threadNo2;
21 end
22 result1=Threads.@spawn
  forcePart1(parID,n1Tmp,n2Tmp,lowLim1[1],upLim1[1],lowLim2[1],upLim2[1],wbTmp,
  modelTmp, coefData);
23 result2=Threads.@spawn
  forcePart2(parID,n1Tmp,n2Tmp,lowLim1[1],upLim1[1],lowLim2[2],upLim2[2],wbTmp,
  modelTmp, coefData);
24 result3=Threads.@spawn
  forcePart3(parID,n1Tmp,n2Tmp,lowLim1[1],upLim1[1],lowLim2[3],upLim2[3],wbTmp,
  modelTmp, coefData);
25 result4=Threads.@spawn
  forcePart4(parID,n1Tmp,n2Tmp,lowLim1[2],upLim1[2],lowLim2[1],upLim2[1],wbTmp,
  modelTmp, coefData);
26 result5=Threads.@spawn
  forcePart5(parID,n1Tmp,n2Tmp,lowLim1[2],upLim1[2],lowLim2[2],upLim2[2],wbTmp,
  modelTmp, coefData);
27 result6=Threads.@spawn
  forcePart6(parID,n1Tmp,n2Tmp,lowLim1[2],upLim1[2],lowLim2[3],upLim2[3],wbTmp,
  modelTmp, coefData);
28 return fetch(result1) + fetch(result2) + fetch(result3) + fetch(result4)+
  fetch(result5) + fetch(result6)
29 end

```

forceT8 (generic function with 1 method)

```

1 #####8-threaded routine#####
2 #####numerical quadrature for acoustic force#####
3 #####n1,n2 denote sample numbers in polar angle  $\theta$  and azimuthal angle  $\phi$ 
  coordinate respectively#####
4 function forceT8(parID::Integer,n1::Integer,n2::Integer,wbTmp::Float64,
  modelTmp::FrequencySimulation, coefData::Matrix{ComplexF64})
5 threadNo=4;
6 threadNo1=2;
7 threadNo2=4;
8 n1Tmp=Int(n1/threadNo1);
9 n2Tmp=Int(n2/threadNo2);
10 lowLim1=Array{Float64}(undef,threadNo1);
11 upLim1=Array{Float64}(undef,threadNo1);
12 lowLim2=Array{Float64}(undef,threadNo2);
13 upLim2=Array{Float64}(undef,threadNo2);
14 for i in 1:threadNo1
15     lowLim1[i]=(i-1)* $\pi$ /threadNo1;
16     upLim1[i]=lowLim1[i]+ $\pi$ /threadNo1;
17 end
18 for i in 1:threadNo2
19     lowLim2[i]=(i-1)*2 $\pi$ /threadNo2;
20     upLim2[i]=lowLim2[i]+2 $\pi$ /threadNo2;
21 end
22 result1=Threads.@spawn
  forcePart1(parID,n1Tmp,n2Tmp,lowLim1[1],upLim1[1],lowLim2[1],upLim2[1],wbTmp,
  modelTmp, coefData);
23 result2=Threads.@spawn
  forcePart2(parID,n1Tmp,n2Tmp,lowLim1[1],upLim1[1],lowLim2[2],upLim2[2],wbTmp,
  modelTmp, coefData);
24 result3=Threads.@spawn
  forcePart3(parID,n1Tmp,n2Tmp,lowLim1[1],upLim1[1],lowLim2[3],upLim2[3],wbTmp,
  modelTmp, coefData);
25 result4=Threads.@spawn
  forcePart4(parID,n1Tmp,n2Tmp,lowLim1[1],upLim1[1],lowLim2[4],upLim2[4],wbTmp,
  modelTmp, coefData);
26 result5=Threads.@spawn
  forcePart5(parID,n1Tmp,n2Tmp,lowLim1[2],upLim1[2],lowLim2[1],upLim2[1],wbTmp,
  modelTmp, coefData);
27 result6=Threads.@spawn
  forcePart6(parID,n1Tmp,n2Tmp,lowLim1[2],upLim1[2],lowLim2[2],upLim2[2],wbTmp,
  modelTmp, coefData);
28 result7=Threads.@spawn
  forcePart7(parID,n1Tmp,n2Tmp,lowLim1[2],upLim1[2],lowLim2[3],upLim2[3],wbTmp,
  modelTmp, coefData);
29 result8=Threads.@spawn
  forcePart8(parID,n1Tmp,n2Tmp,lowLim1[2],upLim1[2],lowLim2[4],upLim2[4],wbTmp,
  modelTmp, coefData);
30 return fetch(result1) + fetch(result2) + fetch(result3) + fetch(result4)+
  fetch(result5) + fetch(result6)+ fetch(result7) + fetch(result8)
31 end

```

force (generic function with 1 method)

```
1 function force(parID::Integer,n1::Integer,n2::Integer,wbTmp::Float64,  
  modelTmp::FrequencySimulation, coefData::Matrix{ComplexF64})  
2   coefDataTmp=deepcopy(coefData);  
3   num_threads = Threads.nthreads();  
4   if num_threads==1  
5       println("Single-threaded computation")  
6       return forceT1(parID,n1,n2,wbTmp, modelTmp, coefDataTmp)  
7   elseif 2<=num_threads&&num_threads<4  
8       println("2-threaded parallel computation")  
9       return forceT2(parID,n1,n2,wbTmp, modelTmp, coefDataTmp)  
10  elseif 4<=num_threads&&num_threads<6  
11      println("4-threaded parallel computation")  
12      return forceT4(parID,n1,n2,wbTmp, modelTmp, coefDataTmp)  
13  elseif 6<=num_threads&&num_threads<8  
14      println("6-threaded parallel computation")  
15      return forceT6(parID,n1,n2,wbTmp, modelTmp, coefDataTmp)  
16  else  
17      println("8-threaded parallel computation")  
18      return forceT8(parID,n1,n2,wbTmp, modelTmp, coefDataTmp)  
19  end  
20 end  
21
```

allForce (generic function with 1 method)

```
1 #####calculate all particles forces#####  
2 function allForce(n1::Integer,n2::Integer,wbTmp::Float64,  
  modelTmp::FrequencySimulation, coefData::Matrix{ComplexF64})  
3   coefDataTmp=deepcopy(coefData);  
4   simModelTmp=modelTmp;  
5   pNoTmp=length(simModelTmp.particles);  
6   dimensionTmp=typeof(simModelTmp.source.medium).parameters[2];  
7   allForceTmp=Array{Float64}(undef,0)  
8   for iTmp in 1:pNoTmp  
9       forceTmp=force(iTmp,n1,n2,wbTmp, modelTmp, coefDataTmp);  
10      allForceTmp=push!(allForceTmp,forceTmp[1],forceTmp[2],forceTmp[3]);  
11  end  
12  return allForceTmp  
13 end
```

forcePackLow (generic function with 1 method)

```
1 function forcePackLow(RsTmp::Float64,parPos::Matrix{Float64})
2   parPosTmp=deepcopy(parPos);
3   freqIn=40000;
4   ω=2.0*π*freqIn;
5   dimension=3;
6   pb=1.225;
7   pp=29.0;
8   cb=343.0;
9   cp=900.0;
10  pNo=length(parPosTmp[:,1]);
11  coefOrder=6;
12  modelTmp=buildModelProto(dimension, pb, cb, pp, cp, ω, pNo, RsTmp, parPosTmp)
13  coefData=getCoefProto(ω, modelTmp, coefOrder);
14  forceTmp=allForce(24,48,ω, modelTmp, coefData);
15  return forceTmp
16 end
```

forcePackMiddle (generic function with 1 method)

```
1 function forcePackMiddle(RsTmp::Float64,parPos::Matrix{Float64})
2   parPosTmp=deepcopy(parPos);
3   freqIn=40000;
4   ω=2.0*π*freqIn;
5   dimension=3;
6   pb=1.225;
7   pp=29.0;
8   cb=343.0;
9   cp=900.0;
10  pNo=length(parPosTmp[:,1]);
11  coefOrder=8;
12  modelTmp=buildModelProto(dimension, pb, cb, pp, cp, ω, pNo, RsTmp, parPosTmp)
13  coefData=getCoefProto(ω, modelTmp, coefOrder);
14  forceTmp=allForce(30,60,ω, modelTmp, coefData);
15  return forceTmp
16 end
```

forcePackHigh (generic function with 1 method)

```
1 function forcePackHigh(RsTmp::Float64,parPos::Matrix{Float64})
2   parPosTmp=deepcopy(parPos);
3   freqIn=40000;
4   ω=2.0*π*freqIn;
5   dimension=3;
6   pb=1.225;
7   pp=29.0;
8   cb=343.0;
9   cp=900.0;
10  pNo=length(parPosTmp[:,1]);
11  coefOrder=10;
12  modelTmp=buildModelProto(dimension, pb, cb, pp, cp, ω, pNo, RsTmp, parPosTmp)
13  coefData=getCoefProto(ω, modelTmp, coefOrder);
14  forceTmp=allForce(36,72,ω, modelTmp, coefData);
15  return forceTmp
16 end
```

