

# VAYU-BSP-01.01.04.14 ReleaseNotes

---

## BSP Version 01.01.04.14

### Release Notes

7th May, 2014

### Important Note

This release is for TDA2xx (Vayu) and TI814x (Centaurus for serial drivers only) platforms

### Document License

This work is licensed under the Creative Commons Attribution-Share Alike 3.0 United States License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/us/> or send a letter to Creative Commons, 171 Second Street, Suite 300, San Francisco, California, 94105, USA.

### Introduction

This release notes provides important information that will assist you in using the BSP software package. This document provides the product information and know issues that are specific to the BSP software package.

### New in this Release

- DSS Display: Added support to get underflow status per pipeline
- VIP Capture: Callback function for getting timestamp from application
- McSPI: Interrupt mode support
- McSPI: Polled mode tested
- UART: Interrupt mode support
- UART: Multi-instance tested
- Bug Fixes

### Installation and Usage

Installation and Usage of the BSP package could be found at BSP\_UserGuide

### Upgrade and Compatibility Information

- **Common**
  - None
- **VIP Capture**
  - Added IOCTL `IOCTL_VPS_REGISTER_TIMESTAMP_FXN` for registering application function for getting the time stamp value used to update the timestamp member of FVID2 frame
- **VPE M2M**
  - None
- **DSS Display**
  - Added `underflowCount` to structure `Vps_DispStatus`. IOCTL `IOCTL_VPS_DISP_GET_STATUS` now returns the underflow status per pipeline

- **UART**
  - Added IOCTL IOCTL\_UART\_GET\_FIFO\_STATUS to get the FIFO status.
- **McSPI**
  - None
- **I2C**
  - None
- **McASP**
  - None
- **Audio**
  - None

## Dependencies

This release requires following tools/packages to be installed.

- Starterware Package: 01.01.02.19
- Code Composer Studio Version: 5.4
- XDC Tools Version: 3.25.05.94
- BIOS Version: 6.37.01.24
- CG Tool (TMS470) Version: 5.0.7
- CG Tool (C6000) Version: 7.4.2
- EDMA LLD: 02.11.11.13

## Devices Supported

- TDA2xx ES1.0,ES1.1
- TI814x (for Serial Drivers only)

## Application Boards Supported

- TDA2xx Base board + LCD board
- TDA2xx Vision application board
- TDA2xx Vision application board with Multi-deserializer board
- TDA2xx JAMR3 application board

## What is Supported

### Common

- Supports TDA2xx EVM/VIRTIO/Zebu
  - Supports FVID2 interfaces for all the supported drivers
  - Package includes BSP driver sources, sample applications that demonstrate use of drivers and sample applications executables
  - SYS BIOS mode is tested
  - Benelli M4 (IPU1) Core 0 for TDA2xx
  - Virtual to physical address translation for VPDMA descriptor memory is supported
-

## **VIP Capture Driver**

- Supports VIP capture driver (12 instance on TDA2xx)
- Support for OV10635 sensor present in TDA2xx vision daughter card
- Support for Aptina A0132 sensor present in TDA2xx vision daughter card
- Support for HDMI sil9127 receiver present in TDA2xx vision daughter card
- Support for 6-channel LVDS capture from multi-deserializer board
- Support for LI sensor present in base board
- Support for TVP5158 decoder present in JAMR3board

## **VPE M2M Driver**

- Supports VPE1 path
- Supportted Input Formats: YUV422I, YUV420SP and YUV422SP
- Supportted Output Formats: YUV422I, YUV420SP, YUV422SP, RGB888 and YUV444
- Supports SC and DEI
- Supports sliced based scaling

## **DSS Display Driver**

- Supports DSS display driver with all pipelines going to any LCD, blended or without blending
- Supports display controller driver to set the display paths and VENC resolution
- Supports LCD and On-Chip HDMI display

## **UART Driver**

- Device Driver for UART on ARM M3,M4
- Sample Application that demonstrate the use of driver for UART - Echo Test.

## **McSPI Driver**

- Device Driver for McSPI on ARM Cortex M3,M4
- Sample Applications that demonstrate the usage of Driver:
  - Writes to On Board Serial Flash in case of TI814X
  - EVM to EVM Communication for both TI814X and TDA2XX
  - Loopback Testing for TDA2xx
  - Writes to McSPI Slave Adaptor with McSPI as Master for TDA2XX

## **I2C Driver**

- Device Driver for I2C on M4 Core
- GIO and IOM Model APIs are supported for Application
- Sample Application that demonstrate the usage of Driver:

## **McASP Driver**

- Device Driver for McASP on DSP Core
  - Sample Application that demonstrate the usage of Driver:
  - Driver expects the data (samples) to be in a specific format when requesting for an IO transfer based on below configurations
    - Single Serializer
    - Multiple Serializer
-

- BurstMode
- Multislot TDM/I2S
- DIT

## Audio Driver

- Device Driver for Audio on DSP Core
- Every Instance can support multiple codecs
- Sample Applications that demonstrate the usage of Driver
  - Sine Tone Generation
  - Loopback Application

## Aic31 Driver

- Device Driver for AIC31 on DSP Core
- Appropriate interfaces to configure the initial values of gain, sample rate
- Interfaces to control the codec specific features like sample rate etc

## Features

### VIP Capture Driver Features

Feature	Supported	Tested on EVM
12 instances (3 VIP x 2 Slice x 2 Port)	YES	YES, Only VIP1 Slice 0 Port A
8-bit Embedded Sync (BT.656)	YES	YES
16-bit Embedded Sync (BT.1120)	YES	NO
24-bit Embedded Sync	YES	NO
8-bit Discrete Sync	YES	YES (only VSYNC/HSYNC mode)
16-bit Discrete Sync	YES	YES
24-bit Discrete Sync	YES	NO
8-bit YUV422 Input	YES	YES
16-bit YUV422 Input	YES	NO
24-bit YUV444 Input	YES	NO
16-bit RGB656 Input	YES	NO
24-bit RGB888 Input	YES	YES
12-bit RAW Input	YES	YES
16/24-bit RAW Input	YES	NO
YUV422I, YUV420SP, YUV422SP, RGB888, YUV444 and RAW output formats	YES	YES
Embedded Sync Multiplexed Modes	NO	NO
Ancillary (VBI) data capture	NO	NO
Bypass mode (RAW to RAW - no processing)	YES	NO
Inline SC Support (cropping, down scaling)	YES	YES
Inline CSC	YES	YES
Configurable VPDMA Line Limit Feature	YES	YES

Tiled (2D) output	NO	NO
Dual stream output (scaled/non-scaled)	NO	NO
Sub-frame based capture	YES	YES
Sub-frame based OTF use case	YES	NO
Re-packer	YES	YES (only on TDA2xx Zebu)
VIP Parser Crop	YES	YES
Buffer Capture Modes - drop frame, last frame repeat, circular frame repeat	YES	YES
Frame Drop IOCTL	YES	YES
Instance and channel status	YES	YES

### VPE M2M Driver Features

Feature	Supported	Tested on EVM
VPE1 instance	YES	YES
YUV422I, YUV420SP, YUV422SP input formats	YES	YES
YUV422I, YUV420SP, YUV422SP, RGB888, YUV444 output formats	YES	YES
Tiler (2D) input/output	YES	YES
Tiler Rotation/Mirroring	YES	YES
SC (cropping, scaling)	YES	YES
DEI (bypass and in deinterlacing mode)	YES	YES
VC1 range mapping and reduction	NO	NO
DEI FMD mode	NO	NO
Multi-Handle	YES	YES
Multi-Channel	YES	YES
Lazy loading of SC coefficient	YES	YES
Slice based scaling (only horizontal slices)	YES	YES
Runtime parameter change	YES	YES

### DSS Display Driver Features

Feature	Supported	Tested on EVM
Video pipeline (Video 1,2,3)	YES	YES
Graphics pipeline (GRPX1)	YES	YES
Writeback pipeline	NO	NO
All LCD/DPI outputs	YES	YES (only DPI1 tested on EVM)
On-Chip HDMI 1.4 Support	YES	YES
HDMI 3D	NO	NO
HDMI 36-bit RGB Color	NO	NO
HDMI HDCP 1.4	NO	NO
HDMI Deep color mode	NO	NO

8-bit Embedded Sync (BT.656)	YES	NO
16-bit Embedded Sync (BT.1120)	YES	NO
24-bit Discrete Sync	YES	YES
8/16 bit Discrete Sync	NO	NO
HDMI PLL	YES	YES
VIDEO 1/2 PLL	YES	YES
YUV422I (YUYV),YUV422I (UYVY),YUV420SP, RGB888 input formats	YES	YES
YUV444 input formats	NO	NO
Tiler Memory (2D)	NO	NO
Tiler Rotation/Mirroring	NO	NO
VC1 Range Mapping (for Video Pipes)	NO	NO
Bypass mode	NO	NO
Inline SC	YES	YES
Inline CSC	YES	YES
Blending	YES	YES
Low-latency display (ability to queue frame to driver/hardware just before VSYNC)	YES	YES
Interlaced scan format	YES	NO
Fields merged and separated interlaced buffers	YES	NO

### UART Driver Features

Feature	Supported	Tested
Single instance	YES	YES
Multi instance and Re-Entrant	YES	YES
Each Instance as Transmitter and / or receiver	YES	YES
DMA Mode Of Operation	YES	YES
POLLED Mode Of Operation	YES	YES
INTERRUPT Mode Of Operation	YES	YES

### I2C Driver Features

Feature	Supported	Tested
Single instance	YES	YES
Multi instance and Re-Entrant	YES	YES
Slave Device Probe IOCTL	YES	YES
Each Instance as Master Transmitter	YES	YES
DMA Mode Of Operation	NO	NO
POLLED Mode Of Operation	YES	YES
INTERRUPT Mode Of Operation	YES	YES

### McSPI Driver Features

Feature	Supported	Tested on Tda2xx	Tested on TI814x
Single instance	YES	YES	YES
Multi instance and Re-Entrant	YES	YES	YES
Each Instance as Transmitter and / or receiver	YES	YES	YES
DMA Mode Of Operation	YES	YES	YES
POLLED Mode Of Operation	YES	YES	NO
INTERRUPT Mode Of Operation	YES	YES	NO

### Audio Driver Features

Feature	Supported	Tested on Tda2xx	Tested on TI814x
Multi instance and Re-Entrant	YES	YES	YES
Each Instance as Transmitter and / or receiver of an audio device	YES	YES	YES
DMA Mode Of Operation	YES	YES	YES
POLLED Mode Of Operation	NO	NO	NO
INTERRUPT Mode Of Operation	NO	NO	NO

### McASP Driver Features

Feature	Supported	Tested on Tda2xx	Tested on TI814x
Single instance	YES	YES	YES
Multi instance and Re-Entrant	YES	YES	YES
Each Instance as Transmitter and / or receiver	YES	YES	YES
Multiple Data Formats	YES	NO	NO
Configurations to operate: multi-slot TDM, I2S, DSP	YES	YES	YES
Configurations to operate: DIT (S/PDIF)	YES	NO	NO
Desired data (such as NULL tone), when idle Transmission Mechanism.	YES	YES	YES
Explicit control of PIN directions for High Clock, Bit Clock and Frame Sync PINS.	YES	YES	YES
DMA Mode Of Operation	YES	YES	YES
POLLED Mode Of Operation	NO	NO	NO
INTERRUPT Mode Of Operation	NO	NO	NO

## AIC31 Codec Driver Features

Feature	Supported	Tested
Multi instance and Re-Entrant	YES	YES
Independent Configuration of Transmitter and receive of an audio device with and multiple audio codecs	YES	YES
Interfaces to control the codec specific features like sample rate etc	YES	YES
Appropriate interfaces to configure the initial values of gain, sample rate etc	YES	YES

## Driver Maturity

### Driver Maturity

Driver	TDA2xx	TI814x
VIP Capture	Beta 1.0	NA
VPE M2M	Beta 1.0	NA
DSS Display	Beta 1.0	NA
UART	Beta 1.0	Beta 1.0
McSPI	Beta 1.0	Beta 1.0
I2C	Beta 1.0	Beta 1.0
McASP	Beta 1.0	Beta 1.0

## Supported/Validated Examples on TDA2XX-EVM

### Supported/Validated Examples

Examples	Supported	Validated
VIP Capture	YES	YES
VIP Sub-frame	YES	YES
VPE M2M	YES	YES
DSS Display	YES	YES
Loopback	YES	YES
UART ECHO	YES	YES
MCSPI LOOPBACK	YES	YES
MCSPI MASTER SLAVE BOARD TO BOARD	YES	NO
MCSPI PERFORMANCE APP	YES	YES
I2C ON Board LED Blink	YES	YES
Audio SINE TONE GENERATION using AIC31Codec	YES	YES
Audio Loopback Application	YES	YES



- Examples could be found at \$BSP\_Install\_Dir\examples\

## What is Not Supported

- Checking for most of the input parameters for out of range and invalid values is not done
- Scaler lazy loading and user coefficient loading are not supported in VIP capture driver
- Mux-mode VIP capture is not supported
- Multiple stream outputs from same video source is not supported
- McASP does not support Interrupt/Polled mode
- I2C is not supported in DMA mode

## Fixed in this Release

### Fixed in this Release

ID	Headline	Module	Remarks
OMAPS00307065	[OSAL] - task_delete is unconditional for BIOS in bsp_osal	OSAL	NA
OMAPS00308262	Use ID Code to Identify ES1.1 Silicon	Platform	NA
OMAPS00303975	[Display] - Error Interrupts are not logged in driver	Display	NA
OMAPS00305906	FVID2Stop On one of the video pipe halts all video Pipe,	Display Controller	NA
OMAPS00306622	EDID Prog Fails on LVDS setup	Capture	NA
OMAPS00302354	[EDMA LLD] Spurious EDMA CC Interrupts on Enabling McSPI DMA Mode	McSPI	NA
OMAPS00308348	Loopback McSPI example not working on EVM	McSPI	NA
OMAPS00308550	McSPI dma mode doesnot work with FIFO Enabled	McSPI	NA
OMAPS00308553	McSPI DMA mode doesnot work for word length other than 8	McSPI	NA
OMAPS00304966	UART DMA Mode does not work for Tx Threshold other than 56	UART	NA
OMAPS00305590	Infinite blocking of the UART Read if there is no data available.	UART	NA
OMAPS00306882	Random Junk Characters on console with UART write in Interrupt Mode	UART	NA
OMAPS00306977	[UART UT] UART DMA Mode IOCTL Tests are Failing	UART	NA
OMAPS00307780	UART doesnt work in interrupt mode.	UART	NA
OMAPS00307823	[UART] SDK Demo hangs when UART cable is disconnected in interrupt mode	UART	NA
OMAPS00308273	[UART] Disconnecting UART cable in DMA mode results in assertion	UART	NA
OMAPS00308277	[UART] TCC used in EDMA param should be the one returned by EDMA request channel	UART	NA
OMAPS00308304	[UART] IPU Interrupt for the UART instance 4 to 10 in SOC define are reserved and can't be mapped using XBAR	UART	NA
OMAPS00308349	[UART] TX FIFO is not fully utilized in interrupt/pollled modes even when user enables FIFO mode	UART	NA
OMAPS00308406	[UART] Polled mode timeout value doesnt work for certain large timeouts becasue of 32-bit expression truncation	UART	NA
OMAPS00308414	[UART] Timeout need not be used for the semaphore used to protect polled mode read and write	UART	NA
OMAPS00308417	[UART] GIO submit doesn't return proper error code and actual bytes read in case of polled mode timeout	UART	NA
OMAPS00308425	[UART] TX/RX hangs in DMA mode when FIFO is disabled	UART	NA

OMAPS00308504	[UART] Delete channel API should wait for FIFO to empty in case TX	UART	NA
OMAPS00308621	[UART] Cancel current IO IOCTL asserts	UART	NA
OMAPS00308622	[UART] TX after set trigger Level IOCTL hangs in DMA mode	UART	NA
OMAPS00308625	[UART] TX/RX after reset TX/RX FIFO IOCTL hangs in DMA mode	UART	NA
OMAPS00308647	[UART] RX in DMA mode hangs randomly and gives random EDMA CC error	UART	NA
OMAPS00308662	[UART] Simultaneous RX and TX in DMA mode leads to corrupted received data	UART	NA

## Known Issues / Limitations

### Known Issues

ID	Headline	Module	Workaround in this release
OMAPS00291957	Display :- Low latency display is not supported for Overlays other than LCD1.	Display Driver	This is DSS IP Limitation
OMAPS00296239	Display : VID3 pipeline output results in black output when zorderEnable is disabled	Display Driver	Enable Z-order and assign proper order
OMAPS00297821	[Display] - BT656 display mode not working	Display Driver	This is DSS IP Bug
OMAPS00308281	[DSS] - Different scaling coeff for diff scaling ratios	Display Driver	Currently only one coefficient set is used for all scaling ratios
OMAPS00306536	No Signal warning in the HDMI display with some TV	HDMI Driver	NA
OMAPS00307811	HDMI PLL lock and starting PHY failed	HDMI Driver	NA
OMAPS00308882	[HDMI] - Fields are swapped for 1080I display	HDMI Driver	NA
OMAPS00301476	[LVDS] Re-run of the any LVDS option results in I2C issues	Capture Driver	Disable I2C probe all at the start of device init by setting isI2cProbingReq of Bsp_DeviceInitParams init parameter to FALSE
OMAPS00301599	Random FVID2_TIMEOUT error during sensor configuration in LVDS use case	Capture Driver	After debugging, this is root caused because of Deserializer watchdog time out of 500ms for the control channel to the serializer. This needs to be debugged further with the EVM team
OMAPS00294864	[Vayu ] McASP Slave Mode Testing for audio codec application is not supported	McASP Driver	This is Vayu EVM Limitation
OMAPS00305846	Vayu: McASP driver create causing ROV HeapMem corruption	McASP Driver	NA
OMAPS00306980	[Audio UT] Audio Noise on McASP UT Tests	McASP Driver	NA
OMAPS00308764	Not set ASYNC bit for ACLKXCTL register via the McASP_HwSetup	McASP Driver	NA
OMAPS00308563	McSPI Master-Slave example not working	McSPI Driver	NA
OMAPS00303494	SIL9127 errata needs to be implemented fully before CES	SIL Driver	NA

OMAPS00305622	[I2C] I2C read to a known slave fails after I2C write to absent slave timeout	I2C Driver	NA
OMAPS00307156	For DMAxBARConnect vision_sdk make files changes to link sys_config. This is not preferred option.	Makerules	NA
OMAPS00307881	[Platform] "1.17 DPLL Controller Sticks When Left Clock Requests Are Removed" Errata workaround needs to be implemented	Platform	NA

## Common

- While validating the sample application on Zebu, it is observed that when very short frames is given as input to VIP or very small size sub-frame is configured in VIP or when the display resolution is small, the M4 is not getting time to run the task context. This is because of back-to-back interrupts from the VIP/DSS. Because of this the application task never gets time to execute and hence the application never ends even though the outputs are captured/displayed properly. Hence it is recommended to use bigger frame size for VIP/DSS. This issue is also due to the fact that the M4 in Zebu is currently configured to run in bypass mode (equivalent to 20 MHz) and also cache is disabled.

## VIP Capture Driver

- 24-bit RAW capture - No support in EVM
- RGB888 input to VIP - No support in EVM/Simulator
- Various discrete sync modes except HSYNC/VSNC mode - No support in EVM

## VPE M2M Driver

- YUV444 output is not modeled in Virtio and the test results in hang. This feature is validated/supported only on Zebu/Silicon.

## DSS Display Driver

- Blended output (say 1 Video + GRPX) on Virtio is not proper as it is not modeled properly on Virtio

## Serial Drivers

- UART Baud rates greater than 115200 are not supported due to high error percentage observed for baud rates greater than 115200.
- UART single byte transfer is supported in Polled Mode and not in DMA Mode.
- A15 needs to be running while loading and running applications on DSP Core

## Validation Information

- This release is validated on TDA2xx (Silicon Revisions ES1.0, ES1.1) EVM for the above mentioned components

## Technical Support and Product Updates

For further information or to report any problems, contact <http://e2e.ti.com> or <http://community.ti.com> or <http://support.ti.com>.

# Article Sources and Contributors

**VAYU-BSP-01.01.04.14 ReleaseNotes** *Source:* <http://ap-fpdsp-swapps.dal.design.ti.com/index.php?oldid=188577> *Contributors:* A0131716, SivarajR, X0153534