

VISION SDK LINUX (v02.08.00)

Data Sheet

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
RF/IF and ZigBee® Solutions	www.ti.com/lprf

Applications

Audio	www.ti.com/audio
Automotive	www.ti.com/automotive
Broadband	www.ti.com/broadband
Digital Control	www.ti.com/digitalcontrol
Medical	www.ti.com/medical
Military	www.ti.com/military
Optical Networking	www.ti.com/opticalnetwork
Security	www.ti.com/security
Telephony	www.ti.com/telephony
Video & Imaging	www.ti.com/video
Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2014, Texas Instruments Incorporated

Table of Contents

1	Supported Features.....	5
1.1	Use-cases	5
1.2	Framework features.....	5
1.3	Supported Links on A15 + Linux	5
1.4	Features Not Supported and/or not Tested	5
2	1CH VIP capture + SGX DISPLAY (A15) usecase.....	6
2.1	Overview.....	6
2.2	Dataflow	6
2.3	System Parameters	7
2.4	CPU loading and Task Info.....	7
2.4.1	<i>Total CPU load</i>	<i>7</i>
2.4.2	<i>Task Level Information and Task Level CPU load</i>	<i>7</i>
2.4.3	<i>Heap Memory Usage.....</i>	<i>8</i>
2.5	System Performance.....	8
2.6	Processing Latency	8
3	Multi-channel 3D Surround view using SGX on Linux Use case TDA2xx.....	9
3.1	Overview.....	9
3.2	Data Flow.....	9
3.2.1	<i>4CH LVDS capture, 3D Surround View demonstration</i>	<i>9</i>
3.3	System Parameters	11
3.4	CPU loading and Task Info.....	11
3.4.1	<i>Total CPU load</i>	<i>11</i>
3.4.2	<i>Task Level Information and Task Level CPU load</i>	<i>11</i>
3.4.3	<i>Heap Memory Usage.....</i>	<i>12</i>
3.5	System Performance.....	12
3.6	Processing Latency	12
3.7	DDR BW usage	13
4	Multi-channel LVDS capture and display usecase on Linux for TDA2Ex	14
4.1	Overview.....	14
4.2	Data Flow.....	14
4.2.1	<i>4CH LVDS capture.....</i>	<i>14</i>
4.3	System Parameters	15
4.4	CPU loading and Task Info.....	15
4.4.1	<i>Total CPU load</i>	<i>15</i>
4.4.2	<i>Task Level Information and Task Level CPU load</i>	<i>15</i>
4.4.3	<i>Heap Memory Usage.....</i>	<i>15</i>
4.5	System Performance.....	16
4.6	Processing Latency	16
4.7	DDR BW usage	16
5	System Memory Usage for Tda2xx	17
5.1	Code / Data Memory Usage	17
6	System Memory Usage for TDA2Ex.....	17
6.1	Code / Data Memory Usage	17

7	IPC latency measurements.....	17
7.1	A15->IPU1_0 IPC latencies	17
7.2	IPU1_0->A15 IPC latencies	17
8	Common System Parameters	18
9	Revision History	18

1 Supported Features

1.1 Use-cases

The Linux + Vision SDK supports the following use-cases as examples

- 1CH VIP capture + SGX DISPLAY(A15)
- 1CH VIP capture + Encode + Decode + SGX DISPLAY(A15)
- 1CH VIP capture + Pedestrian Detect (EVE1 + DSP1) + SGX DISPLAY(A15)
- 4CH LVDS capture + SGX DISPLAY(A15)
- 4CH LVDS capture + 3D SRV (SGX-A15) + DRM DISPLAY(A15)
- 4CH AVB capture + Decode + SGX DISPLAY(A15)

From the list above, two usecases are picked for system-parameter measurements in this document. For others data can be interpreted from BIOS usecases results - please refer Vision SDK BIOS datasheet at `$INSTALL_DIR\vision_sdk\docs\VisionSDK_DataSheet.pdf`.

1.2 Framework features

- Refer `$INSTALL_DIR\vision_sdk\docs\VisionSDK_DataSheet.pdf`

1.3 Supported Links on A15 + Linux

Links for the following modules with the features listed below

- SGXDISPLAY
- IPC_IN
- IPC_OUT
- NULL
- SGX 3D Surround View (TDA2xx only)

1.4 Features Not Supported and/or not Tested


- Buffers captured on IPU cannot be accessed / processed by A15 as caching is not taken care in A15. (temporary limitation)
- Alg links on A15 not support, mainly because caching operations on A15 are not tested. (temporary limitation)

2 1CH VIP capture + SGX DISPLAY (A15) usecase

2.1 Overview

This usecase consists of continuous capture on IPU1_0 and display on A15 with SGX. Capture can be done at 720p@30fps (OV Sensor) via the VIP1 Slice1 Port A. Display can be on LCD via DPI1 output port or on HDMI display via HDMI output port.

2.2 Dataflow



2.3 System Parameters

Refer Section 13.1 in \$INSTALL_DIR/vision_sdk/docs/VisionSDK_DataSheet.pdf

The only difference when Linux is in picture is, A15 runs at 1000MHz instead of 750 MHz.

2.4 CPU loading and Task Info

2.4.1 Total CPU load

CPU	CPU LOAD (%)	
SOC	TDA2xx	TDA2EX
IPU1_0	3.6	1.4
A15	0.8	1

2.4.2 Task Level Information and Task Level CPU load

CPU	TASK NAME	TASK DESCRIPTION	CPU LOAD (%)	
SOC			TDA2xx	TDA2EX
IPU1_0	Capture	Capture frames via VIP port	0.1	0.1
	IPC OUT	To send frame to another processor	0.4	0.4
	SYSTEM_IPU1_127	System thread for generic control command like print heap stats, CPU load etc	0.1	0.3
	Stat Coll	Stat collector	1.8	NA
	App Ctrl	Sensor init and board level contro	0.1	0.1
	Misc	Miscellaneous	0.4	0.3
A15	IPC IN	To receive frames from another processor	NA	NA
	SGXDISPLAY	To submit received buffer to SGX and then display via DRM	NA	NA

2.4.3 Heap Memory Usage

CPU	MEMORY SECTION	MEMORY SIZE RESERVED		MEMORY SIZE USED	
		TDA2xx	TDA2EX	TDA2XX	TDA2EX
SOC					
IPU1_0	Local heap	256 KB	256 KB	22 KB	22 KB
	HDVPSS Descriptor Mem	2MB	2MB	1 MB	1 MB
Shared Memory	SR0 DDR	10 MB	10 MB	3 MB	0 MB
	SR1 (Frame Buffers)	253 MB	253 MB	9 MB	9 MB
	SR2 (OCMC)	1023 KB	511 KB	0 KB	0 KB
	Remote Log Buffer	1 MB	1 MB	145 KB	145 KB

2.5 System Performance

COMPONENT	PARAMETER	VALUE	
SOC		TDA2xx	TDA2EX
Capture	Out FPS	30	30
SGXDISPLAY	Input FPS	30	30

NOTE: FPS numbers are rounded off to nearest integer

2.6 Processing Latency

		LATENCY	
SOC		TDA2xx	TDA2Ex
Capture to Display Latency	Avg	15.6 ms	15 ms
	Min	7.2 ms	7 ms
	Max	23 ms	25 ms

Note: Latency is from VIP output to the display. Additional capture latency needs to be added for end to end latency

3 Multi-channel 3D Surround view using SGX on Linux Use case TDA2xx

3.1 Overview


This use case demonstrates 3D surround view using SGX with Linux running on A15.

3.2 Data Flow

3.2.1 4CH LVDS capture, 3D Surround View demonstration

In this configuration we capture 4 Channel video from 4 OV1063x sensors @ 720p 30fps. Captured frames are then passed on to Sync link, where these captured frames are synced based on time stamps. This "group of sync'ed frames" is passed on to algorithm links of Geometric alignment and synthesis link. Geometric Analysis link running on DSP core is invoked once in K frames. This link generates the geometric alignment LUTs to be used during synthesis stage. Photometric Analysis link runs on DSP core. Certain image statistics needed for calculating photometric LUTs are provided by the synthesis stage. Photometric Analysis link generates LUTs for pixel value transformations during Synthesis. Synthesis link on DSP encapsulates the algorithm for generating the photometric statistics & Blend Lookup tables, based on geometric and photometric LUTs. SGX link encapsulates the algorithm for stitching, based on geometric, Blend and photometric LUTs. This Link runs on A15 (Linux) and SGX (3D GRPX Engine) is used to create the 360 degree of the car using Open GL API/Algos. Output of Synthesis link is the stitched frame which is passed onto display link, which shall display the surround view image using display drivers via LCD or HDMI output.

Please note in dataflow diagram below IPC IN/OUT blocks are left-out to improve readability. Please assume these whenever CPU changes in the flow.



**IPC IN/OUT blocks are left-out to improve readability.

3.3 System Parameters

Refer Section 13.1 in \$INSTALL_DIR/vision_sdk/docs/VisionSDK_DataSheet.pdf

The only difference when Linux is in picture is, A15 runs at 1000MHz instead of 750 MHz.

3.4 CPU loading and Task Info

3.4.1 Total CPU load

CPU	CPU LOAD (%)
IPU1_0	8.2
A15_0	3.0
DSP1	42
DSP2	0.2
SGX	60

3.4.2 Task Level Information and Task Level CPU load

CPU	TASK NAME	TASK DESCRIPTION	CPU LOAD (%)
SOC			TDA2xx
IPU1_0	Capture	Capture frames via VIP port	0.5
	IPC OUT	To send frame to another processor	0.9
	SYNC Link	Sync Link to synchronize the frames from different channels	0.8
	Stat Coll	Stat collector	2.3
	GrpxSrc0	Graphic source link	0.8
	App Ctrl	Sensor init and board level contro	0.1
	Misc	Miscellaneous	0.5
A15	IPC IN	To receive frames from another processor	3.0
	SGXDISPLAY	To submit received buffer to SGX and then display via DRM	

3.4.3 Heap Memory Usage

CPU	MEMORY SECTION	MEMORY RESERVED	MEMORY SIZE USED
IPU1_0	Local heap	256 KB	22 KB
	HDVPSS Descriptor Mem	2MB	2 MB
DSP 1	L2	224 KB	128 KB
	Local Heap	32 KB	14 KB
DSP 2	L2	224 KB	0 KB
	Local Heap	32 KB	14 KB
Shared Memory	SR0	10 MB	3 MB
	SR1 (Frame Buffers)	253 MB	130 MB
	SR2 (OCMC)	1023KB	0KB
	Remote Log Buffer	1 MB	145 KB

3.5 System Performance

COMPONENT	PARAMETER	VALUE
Capture	Out FPS	30fps
ALG Synthesis (DSP1)	Output fps	30fps
ALG – Photometric Align (DSP1)	Output fps	30fps
SGXDISPLAY	Input FPS	30fps

NOTE: FPS numbers are rounded off to nearest integer. The performance bottleneck here is the Linux SGX/DRM driver, the current driver architecture do not allow the SGX to load more than 60%. This will be fixed by Q4-2015.

3.6 Processing Latency

		LATENCY
Capture to Display Latency	Avg	34 ms
	Min	5 ms
	Max	96 ms

NOTE:

- This latency is as measured inside the system by software.

- There will an additional $1/(\text{capture rate})$ added on top of this from sensor/receiver itself.
- There will an additional $1/(\text{display rate})$ added on top of this for the frame to actually get displayed on the screen.
- Thus e.g. in a scenario of display at 60fps and capture at 30fps - 16.67ms + 33.33ms needs to be added to latency figures in above table to get true capture to display latency

3.7 DDR BW usage

PARAMETER	BANDWIDTH	
EMIF1 Read + Write	Avg	1179 MB/s
	Peak	1673 MB/s
EMIF2 Read + Write	Avg	1176 MB/s
	Peak	1693 MB/s
Total	Avg	2356 MB/s
	Peak	3367 MB/s

4 Multi-channel LVDS capture and display usecase on Linux for TDA2Ex

4.1 Overview


This use case demonstrates 4CH LVDS using SGX with Linux running on A15.

4.2 Data Flow

4.2.1 4CH LVDS capture

In this configuration we capture 4 Channel video from 4 OV1063x sensors @ 720p 30fps. Captured frames are then passed on to Sync link, where these captured frames are synced based on time stamps. Output of Synthesis link is the stitched frame which is passed onto display link, which shall display the images using display drivers via LCD or HDMI output.

Please note in dataflow diagram below IPC IN/OUT blocks are left-out to improve readability. Please assume these whenever CPU changes in the flow.



**IPC IN/OUT blocks are left-out to improve readability.

4.3 System Parameters

Refer Section 13.1 in \$INSTALL_DIR/vision_sdk/docs/VisionSDK_DataSheet.pdf

The only difference when Linux is in picture is, A15 runs at 1000MHz instead of 750 MHz.

4.4 CPU loading and Task Info

4.4.1 Total CPU load

CPU	CPU LOAD (%)
IPU1_0	4.3
DSP1	0.2
A15	2.0

4.4.2 Task Level Information and Task Level CPU load

CPU	TASK NAME	TASK DESCRIPTION	CPU LOAD (%)
IPU1_0	Capture	Capture frames via VIP port	0.4
	IPC_OUT	To send frame to another processor	0.4
	SYNC	Sync across frames from multiple channels	0.8
	STAT COLL	DDR BW stats collector	1.3
	MISC	Miscellaneous	0.4

4.4.3 Heap Memory Usage

CPU	MEMORY SECTION	MEMORY RESERVED	MEMORY SIZE USED
IPU1_0	Local heap	256 KB	22 KB
	HDVPSS Descriptor Mem	2MB	1 MB
DSP 1	L2	224 KB	0 KB
	Local Heap	512 KB	14 KB
Shared	SR0	10 MB	0 MB

Memory	SR1 (Frame Buffers)	253 MB	25 MB
	SR2 (OCMC)	511 KB	0 KB
	Remote Log Buffer	1 MB	145 KB

4.5 System Performance

COMPONENT	PARAMETER	VALUE
Capture	Out FPS	30fps
SGXDISPLAY	Input FPS	30fps

NOTE: FPS numbers are rounded off to nearest integer

4.6 Processing Latency

LATENCY		
Capture to Display Latency	Avg	29.23
	Min	19.85
	Max	37.30

Note: Latency is from VIP output to the display. Additional capture latency needs to be added for end to end latency

4.7 DDR BW usage

PARAMETER	BANDWIDTH	
EMIF Read only	Avg	676 MB/s
	Peak	1436 MB/s
EMIF Write only	Avg	409 MB/s
	Peak	1336 MB/s
Total	Avg	1085 MB/s
	Peak	2772 MB/s

5 System Memory Usage for Tda2xx

5.1 Code / Data Memory Usage

Overall Linux on A15 has full 1.5 GB on the EVM except following two holes in the memory

From 0x85800000 size 0xFC00000 bytes

From 0xA0000000 size 0x4000000 bytes

From 0xA2000000 size 0x2000000 bytes

Refer Section 16.2 in \$INSTALL_DIR/vision_sdk/docs/VisionSDK_DataSheet.pdf of code and data memory usage of IPU1_0

6 System Memory Usage for TDA2Ex

6.1 Code / Data Memory Usage

Overall Linux on A15 has full 1.5 GB on the EVM except following one holes in the memory

From 0xA0000000 0x2000000 bytes

Refer Section 16.2 in \$INSTALL_DIR/vision_sdk/docs/VisionSDK_DataSheet.pdf of code and data memory usage of IPU1_0

7 IPC latency measurements

This section focuses on IPC latency measurements between Linux (A15) <-> Bios (IPU1_0). A15 <-> DSP IPC latencies are not measured.

For Bios <-> Bios ipc measurements refer Section 12.2 in \$INSTALL_DIR/vision_sdk/docs/VisionSDK_DataSheet.pdf

7.1 A15->IPU1_0 IPC latencies

These are average case latencies.

This involves send from A15 + ISR on IPU1_0 and receipt of notification / message on IPU1_0

SOC	IPC One-way Notify Interrupt Latency (usecs)	IPC Buffer One-way Passing Latency (usecs)
TDA2xx	80	105
TDA2EX	Not Tested	Not Tested

7.2 IPU1_0->A15 IPC latencies

These are average case latencies.

This involves time for command msg sent using System_rpmsgSendNotify()/System_rpmsgMsgQSendMsg() on IPU1_0 till it is received on A15.

It means, it is send on IPU1_0 + ISR on A15 + scheduling / context switching overheads on Linux.

SOC	IPC One-way Notify Interrupt Latency (usecs)	IPC Buffer Latency (usecs)	One-way Passing
TDA2xx	112	136	
TDA2EX	115	137	

8 Common System Parameters

Refer Section 13.1 in \$INSTALL_DIR/vision_sdk/docs/VisionSDK_DataSheet.pdf

The only difference when Linux is in picture is, A15 runs at 1000MHz instead of 750 MHz.

9 Revision History

Version	Date	Revision History
1.00	25th July 2014	Created for Vision SDK release v2.03
2.00	17 th Nov 2014	Updated for Vision SDK release v2.05
3.00	4 th Mar 2015	Updated for Vision SDK release v2.06
4.00	7 th July 2015	Updated for Vision SDK release v2.07
5.00	15 th Oct 2015	Updated for Vision SDK release v2.08