

# The Algorithmic Phase Transition for Correlated Spiked Models

Zhangsong Li

School of Mathematical Sciences, Peking University

December 5, 2025

Sino-Russian Student Seminar

# Motivation

- A common theme in high-dimensional statistics & machine learning: recovering a **low-dimensional structure** from **high-dimensional noise**.
  - Recognize certain features in an image;
  - Determine which combination of genes cause a certain disease;
  - Find “communities” in a social network;
  - Predict which users will click which ads;
  - etc.

# An idealized model: Spiked random matrix

- Spiked Wigner model:

$$\mathbf{Y} = \mathbf{W} + \frac{\lambda}{\sqrt{n}} \mathbf{x}\mathbf{x}^T \in \mathbb{R}^{n \times n}.$$

# An idealized model: Spiked random matrix

- Spiked Wigner model:

$$\mathbf{Y} = \mathbf{W} + \frac{\lambda}{\sqrt{n}} \mathbf{x}\mathbf{x}^T \in \mathbb{R}^{n \times n}.$$

Noise  $\mathbf{W}$ : an  $n \times n$  Wigner matrix (i.e.,  $\mathbf{W}$  is symmetric and  $\mathbf{W}_{i,j} \sim \mathcal{N}(0, 1 + \mathbf{1}_{i=j})$  independently for  $i \leq j$ ).

# An idealized model: Spiked random matrix

- Spiked Wigner model:

$$\mathbf{Y} = \mathbf{W} + \frac{\lambda}{\sqrt{n}} \mathbf{x}\mathbf{x}^T \in \mathbb{R}^{n \times n}.$$

Noise  $\mathbf{W}$ : an  $n \times n$  Wigner matrix (i.e.,  $\mathbf{W}$  is symmetric and  $\mathbf{W}_{i,j} \sim \mathcal{N}(0, 1 + \mathbf{1}_{i=j})$  independently for  $i \leq j$ ).

$\lambda$ : signal-to-noise ratio.

# An idealized model: Spiked random matrix

- **Spiked Wigner model:**

$$\mathbf{Y} = \mathbf{W} + \frac{\lambda}{\sqrt{n}} \mathbf{x} \mathbf{x}^T \in \mathbb{R}^{n \times n}.$$

Noise  $\mathbf{W}$ : an  $n \times n$  Wigner matrix (i.e.,  $\mathbf{W}$  is symmetric and  $\mathbf{W}_{i,j} \sim \mathcal{N}(0, 1 + \mathbf{1}_{i=j})$  independently for  $i \leq j$ ).

$\lambda$ : signal-to-noise ratio.

Signal vector (“spike”)  $\mathbf{x}$ : sampled from  $\pi$  such that  $\|\mathbf{x}\| \approx \sqrt{n}$ , e.g.,

# An idealized model: Spiked random matrix

- **Spiked Wigner model:**

$$\mathbf{Y} = \mathbf{W} + \frac{\lambda}{\sqrt{n}} \mathbf{x} \mathbf{x}^T \in \mathbb{R}^{n \times n}.$$

Noise  $\mathbf{W}$ : an  $n \times n$  Wigner matrix (i.e.,  $\mathbf{W}$  is symmetric and  $\mathbf{W}_{i,j} \sim \mathcal{N}(0, 1 + \mathbf{1}_{i=j})$  independently for  $i \leq j$ ).

$\lambda$ : signal-to-noise ratio.

Signal vector (“spike”)  $\mathbf{x}$ : sampled from  $\pi$  such that  $\|\mathbf{x}\| \approx \sqrt{n}$ , e.g.,

- ① uniform  $\{-1, +1\}^n$  hypercube (Rademacher);

# An idealized model: Spiked random matrix

- **Spiked Wigner model:**

$$\mathbf{Y} = \mathbf{W} + \frac{\lambda}{\sqrt{n}} \mathbf{x}\mathbf{x}^T \in \mathbb{R}^{n \times n}.$$

Noise  $\mathbf{W}$ : an  $n \times n$  Wigner matrix (i.e.,  $\mathbf{W}$  is symmetric and  $\mathbf{W}_{i,j} \sim \mathcal{N}(0, 1 + \mathbf{1}_{i=j})$  independently for  $i \leq j$ ).

$\lambda$ : signal-to-noise ratio.

**Signal vector (“spike”)  $\mathbf{x}$ :** sampled from  $\pi$  such that  $\|\mathbf{x}\| \approx \sqrt{n}$ , e.g.,

- ① uniform  $\{-1, +1\}^n$  hypercube (Rademacher);
- ② Gaussian distribution  $\mathcal{N}(0, \mathbb{I}_n)$ .



# An idealized model: Spiked random matrix

- **Spiked Wigner model:**

$$\mathbf{Y} = \mathbf{W} + \frac{\lambda}{\sqrt{n}} \mathbf{x}\mathbf{x}^T \in \mathbb{R}^{n \times n}.$$

Noise  $\mathbf{W}$ : an  $n \times n$  Wigner matrix (i.e.,  $\mathbf{W}$  is symmetric and  $\mathbf{W}_{i,j} \sim \mathcal{N}(0, 1 + \mathbf{1}_{i=j})$  independently for  $i \leq j$ ).

$\lambda$ : signal-to-noise ratio.

**Signal vector (“spike”)  $\mathbf{x}$ :** sampled from  $\pi$  such that  $\|\mathbf{x}\| \approx \sqrt{n}$ , e.g.,

- ① uniform  $\{-1, +1\}^n$  hypercube (Rademacher);
- ② Gaussian distribution  $\mathcal{N}(0, \mathbb{I}_n)$ .
- ③ normalized “sparse” Rademacher.

# An idealized model: Spiked random matrix

- **Spiked Wishart (covariance) model:**

$$\mathbf{Y} = \mathbf{W} + \frac{\sqrt{\lambda}}{\sqrt{n}} \mathbf{x} \mathbf{u}^\top \in \mathbb{R}^{n \times N}.$$

$$\iff \mathbf{Y} = (\mathbf{Y}_1, \dots, \mathbf{Y}_N), \mathbf{Y}_i \sim \mathcal{N}(0, \mathbb{I}_n + \frac{\lambda}{n} \mathbf{x} \mathbf{x}^\top).$$

# An idealized model: Spiked random matrix

- **Spiked Wishart (covariance) model:**

$$\mathbf{Y} = \mathbf{W} + \frac{\sqrt{\lambda}}{\sqrt{n}} \mathbf{x} \mathbf{u}^\top \in \mathbb{R}^{n \times N}.$$

$$\iff \mathbf{Y} = (\mathbf{Y}_1, \dots, \mathbf{Y}_N), \mathbf{Y}_i \sim \mathcal{N}(0, \mathbb{I}_n + \frac{\lambda}{n} \mathbf{x} \mathbf{x}^\top).$$

Noise  $\mathbf{W}$ : i.i.d.  $\mathcal{N}(0, 1)$  entries.

# An idealized model: Spiked random matrix

- **Spiked Wishart (covariance) model:**

$$\mathbf{Y} = \mathbf{W} + \frac{\sqrt{\lambda}}{\sqrt{n}} \mathbf{x} \mathbf{u}^\top \in \mathbb{R}^{n \times N}.$$

$$\iff \mathbf{Y} = (\mathbf{Y}_1, \dots, \mathbf{Y}_N), \mathbf{Y}_i \sim \mathcal{N}(0, \mathbb{I}_n + \frac{\lambda}{n} \mathbf{x} \mathbf{x}^\top).$$

Noise  $\mathbf{W}$ : i.i.d.  $\mathcal{N}(0, 1)$  entries.

$\lambda$ : signal-to-noise ratio.

# An idealized model: Spiked random matrix

- **Spiked Wishart (covariance) model:**

$$\mathbf{Y} = \mathbf{W} + \frac{\sqrt{\lambda}}{\sqrt{n}} \mathbf{x} \mathbf{u}^\top \in \mathbb{R}^{n \times N}.$$

$$\iff \mathbf{Y} = (\mathbf{Y}_1, \dots, \mathbf{Y}_N), \mathbf{Y}_i \sim \mathcal{N}(0, \mathbb{I}_n + \frac{\lambda}{n} \mathbf{x} \mathbf{x}^\top).$$

Noise  $\mathbf{W}$ : i.i.d.  $\mathcal{N}(0, 1)$  entries.

$\lambda$ : signal-to-noise ratio.

**Signal vector (“spike”)  $\mathbf{x}$** : sampled from  $\pi$  such that  $\|\mathbf{x}\| \approx \sqrt{n}$ ;  **$\mathbf{u}$** : sampled from  $\mathcal{N}(0, \mathbb{I}_N)$ .

# An idealized model: Spiked random matrix

- **Spiked Wishart (covariance) model:**

$$\mathbf{Y} = \mathbf{W} + \frac{\sqrt{\lambda}}{\sqrt{n}} \mathbf{x} \mathbf{u}^\top \in \mathbb{R}^{n \times N}.$$

$$\iff \mathbf{Y} = (\mathbf{Y}_1, \dots, \mathbf{Y}_N), \mathbf{Y}_i \sim \mathcal{N}(0, \mathbb{I}_n + \frac{\lambda}{n} \mathbf{x} \mathbf{x}^\top).$$

Noise  $\mathbf{W}$ : i.i.d.  $\mathcal{N}(0, 1)$  entries.

$\lambda$ : signal-to-noise ratio.

**Signal vector (“spike”)  $\mathbf{x}$** : sampled from  $\pi$  such that  $\|\mathbf{x}\| \approx \sqrt{n}$ ;  **$\mathbf{u}$** : sampled from  $\mathcal{N}(0, \mathbb{I}_N)$ .

We will focus on the “critical” regime where  $N = \Theta(n)$  and  $\lambda = \Theta(1)$ .

# Spectral approach

**Two** inference tasks: **detection**, **recovery**.

- **Detection**: distinguish **reliably** (error prob  $\rightarrow 0$ ) the spiked matrix and the pure noise matrix.
- **Recovery**: **non-trivial correlation** with the truth:  $\frac{|\langle \hat{x}, x \rangle|}{\|\hat{x}\| \|x\|} = \Omega(1)$ .

# Spectral approach

**Two** inference tasks: **detection**, **recovery**.

- **Detection**: distinguish **reliably** (error prob  $\rightarrow 0$ ) the spiked matrix and the pure noise matrix.
- **Recovery**: **non-trivial correlation** with the truth:  $\frac{|\langle \hat{x}, x \rangle|}{\|\hat{x}\| \|x\|} = \Omega(1)$ .

A canonical spectral approach: principle component analysis (PCA).



# Spectral approach

**Two** inference tasks: **detection**, **recovery**.

- **Detection**: distinguish **reliably** (error prob  $\rightarrow 0$ ) the spiked matrix and the pure noise matrix.
- **Recovery**: **non-trivial correlation** with the truth:  $\frac{|\langle \hat{x}, x \rangle|}{\|\hat{x}\| \|x\|} = \Omega(1)$ .

A canonical spectral approach: principle component analysis (PCA).

- Idea: use the top eigenpair  $\varsigma_1(\mathbf{Y}\mathbf{Y}^\top)$ ,  $v_1(\mathbf{Y}\mathbf{Y}^\top)$  for detection and recovery, i.e.,

# Spectral approach

**Two** inference tasks: **detection**, **recovery**.

- **Detection**: distinguish **reliably** (error prob  $\rightarrow 0$ ) the spiked matrix and the pure noise matrix.
- **Recovery**: **non-trivial correlation** with the truth:  $\frac{|\langle \hat{x}, x \rangle|}{\|\hat{x}\| \|x\|} = \Omega(1)$ .

A canonical spectral approach: principle component analysis (PCA).

- Idea: use the top eigenpair  $\varsigma_1(\mathbf{Y}\mathbf{Y}^\top)$ ,  $v_1(\mathbf{Y}\mathbf{Y}^\top)$  for detection and recovery, i.e.,
  - Detection:  $\varsigma_1(\mathbf{Y}\mathbf{Y}^\top)$  is large  $\implies$  spiked.

# Spectral approach

**Two** inference tasks: **detection**, **recovery**.

- **Detection**: distinguish **reliably** (error prob  $\rightarrow 0$ ) the spiked matrix and the pure noise matrix.
- **Recovery**: **non-trivial correlation** with the truth:  $\frac{|\langle \hat{x}, x \rangle|}{\|\hat{x}\| \|x\|} = \Omega(1)$ .

A canonical spectral approach: principle component analysis (PCA).

- Idea: use the top eigenpair  $\varsigma_1(\mathbf{Y}\mathbf{Y}^\top)$ ,  $v_1(\mathbf{Y}\mathbf{Y}^\top)$  for detection and recovery, i.e.,
  - Detection:  $\varsigma_1(\mathbf{Y}\mathbf{Y}^\top)$  is large  $\implies$  spiked.
  - Recovery: estimate  $x$  by  $v_1(\mathbf{Y}\mathbf{Y}^\top)$ .

# Spectral approach

**Two** inference tasks: **detection**, **recovery**.

- **Detection**: distinguish **reliably** (error prob  $\rightarrow 0$ ) the spiked matrix and the pure noise matrix.
- **Recovery**: **non-trivial correlation** with the truth:  $\frac{|\langle \hat{x}, x \rangle|}{\|\hat{x}\| \|x\|} = \Omega(1)$ .

A canonical spectral approach: principle component analysis (PCA).

- Idea: use the top eigenpair  $\varsigma_1(\mathbf{Y}\mathbf{Y}^\top)$ ,  $v_1(\mathbf{Y}\mathbf{Y}^\top)$  for detection and recovery, i.e.,
  - Detection:  $\varsigma_1(\mathbf{Y}\mathbf{Y}^\top)$  is large  $\implies$  spiked.
  - Recovery: estimate  $x$  by  $v_1(\mathbf{Y}\mathbf{Y}^\top)$ .
- Intuition: for large  $\lambda$  one expects the rank-one deformation to create an outlier eigenvalue.

# Spectral (BBP) transition

Spiked Wishart model:  $\mathbf{Y} = \mathbf{W} + \frac{\sqrt{\lambda}}{\sqrt{n}} \mathbf{x} \mathbf{u}^\top \in \mathbb{R}^{n \times N}$  with  $n = \gamma N$ .

# Spectral (BBP) transition

Spiked Wishart model:  $\mathbf{Y} = \mathbf{W} + \frac{\sqrt{\lambda}}{\sqrt{n}} \mathbf{x} \mathbf{u}^\top \in \mathbb{R}^{n \times N}$  with  $n = \gamma N$ .

- $\lambda = 0$  (pure Wishart matrix) [Marčenko-Pastur 1967]:  
 $\varsigma_1(\frac{1}{N} \mathbf{W} \mathbf{W}^\top) \rightarrow (1 + \sqrt{\gamma})^2$ .

# Spectral (BBP) transition

Spiked Wishart model:  $\mathbf{Y} = \mathbf{W} + \frac{\sqrt{\lambda}}{\sqrt{n}} \mathbf{x} \mathbf{u}^\top \in \mathbb{R}^{n \times N}$  with  $n = \gamma N$ .

- $\lambda = 0$  (pure Wishart matrix) [Marčenko-Pastur 1967]:  
 $\varsigma_1(\frac{1}{N} \mathbf{W} \mathbf{W}^\top) \rightarrow (1 + \sqrt{\gamma})^2$ .
- $\lambda > 0$  (spiked Wishart matrix) [Baik-Ben Arous-Péché 2005]:

# Spectral (BBP) transition

Spiked Wishart model:  $\mathbf{Y} = \mathbf{W} + \frac{\sqrt{\lambda}}{\sqrt{n}} \mathbf{x} \mathbf{u}^\top \in \mathbb{R}^{n \times N}$  with  $n = \gamma N$ .

- $\lambda = 0$  (pure Wishart matrix) [Marčenko-Pastur 1967]:  
 $\varsigma_1(\frac{1}{N} \mathbf{W} \mathbf{W}^\top) \rightarrow (1 + \sqrt{\gamma})^2$ .
- $\lambda > 0$  (spiked Wishart matrix) [Baik-Ben Arous-Péché 2005]:
  - $\lambda^2 \leq \gamma$  (subcritical):  $\varsigma_1(\frac{1}{N} \mathbf{Y} \mathbf{Y}^\top) \rightarrow (1 + \sqrt{\gamma})^2$  and  $\langle \nu_1(\frac{1}{N} \mathbf{Y} \mathbf{Y}^\top), \mathbf{x} \rangle \rightarrow 0$ .



# Spectral (BBP) transition

Spiked Wishart model:  $\mathbf{Y} = \mathbf{W} + \frac{\sqrt{\lambda}}{\sqrt{n}} \mathbf{x} \mathbf{u}^\top \in \mathbb{R}^{n \times N}$  with  $n = \gamma N$ .

- $\lambda = 0$  (pure Wishart matrix) [Marčenko-Pastur 1967]:  
 $\varsigma_1(\frac{1}{N} \mathbf{W} \mathbf{W}^\top) \rightarrow (1 + \sqrt{\gamma})^2$ .
- $\lambda > 0$  (spiked Wishart matrix) [Baik-Ben Arous-Péché 2005]:
  - $\lambda^2 \leq \gamma$  (subcritical):  $\varsigma_1(\frac{1}{N} \mathbf{Y} \mathbf{Y}^\top) \rightarrow (1 + \sqrt{\gamma})^2$  and  $\langle \mathbf{v}_1(\frac{1}{N} \mathbf{Y} \mathbf{Y}^\top), \mathbf{x} \rangle \rightarrow 0$ .
  - $\lambda^2 > \gamma$  (supercritical):  $\varsigma_1(\frac{1}{N} \mathbf{Y} \mathbf{Y}^\top) \rightarrow (1 + \lambda)(1 + \frac{\gamma}{\lambda}) > (1 + \sqrt{\gamma})^2$  and  $\langle \mathbf{v}_1(\frac{1}{N} \mathbf{Y} \mathbf{Y}^\top), \mathbf{x} \rangle = \Omega(1)$ .

# Spectral (BBP) transition

Spiked Wishart model:  $\mathbf{Y} = \mathbf{W} + \frac{\sqrt{\lambda}}{\sqrt{n}} \mathbf{x} \mathbf{u}^\top \in \mathbb{R}^{n \times N}$  with  $n = \gamma N$ .

- $\lambda = 0$  (pure Wishart matrix) [Marčenko-Pastur 1967]:  
 $s_1(\frac{1}{N} \mathbf{W} \mathbf{W}^\top) \rightarrow (1 + \sqrt{\gamma})^2$ .
- $\lambda > 0$  (spiked Wishart matrix) [Baik-Ben Arous-Péché 2005]:
  - $\lambda^2 \leq \gamma$  (subcritical):  $s_1(\frac{1}{N} \mathbf{Y} \mathbf{Y}^\top) \rightarrow (1 + \sqrt{\gamma})^2$  and  $\langle v_1(\frac{1}{N} \mathbf{Y} \mathbf{Y}^\top), \mathbf{x} \rangle \rightarrow 0$ .
  - $\lambda^2 > \gamma$  (supercritical):  $s_1(\frac{1}{N} \mathbf{Y} \mathbf{Y}^\top) \rightarrow (1 + \lambda)(1 + \frac{\gamma}{\lambda}) > (1 + \sqrt{\gamma})^2$  and  $\langle v_1(\frac{1}{N} \mathbf{Y} \mathbf{Y}^\top), \mathbf{x} \rangle = \Omega(1)$ .




Figure:  $\gamma = 0.5, \lambda = 0$




Figure:  $\gamma = 0.5, \lambda = 0.5$




Figure:  $\gamma = 0.5, \lambda = 1.5$

# Spectral (BBP) transition

Spiked Wigner model:  $\mathbf{Y} = \mathbf{W} + \frac{\lambda}{\sqrt{n}} \mathbf{x}\mathbf{x}^T \in \mathbb{R}^{n \times n}$ .

# Spectral (BBP) transition

Spiked Wigner model:  $\mathbf{Y} = \mathbf{W} + \frac{\lambda}{\sqrt{n}} \mathbf{x}\mathbf{x}^\top \in \mathbb{R}^{n \times n}$ .

- $\lambda = 0$  (pure Wigner matrix) [Wigner 1958]:  $\varsigma_1(\frac{1}{\sqrt{n}} \mathbf{Y}) \rightarrow 2$ .

# Spectral (BBP) transition

Spiked Wigner model:  $\mathbf{Y} = \mathbf{W} + \frac{\lambda}{\sqrt{n}} \mathbf{x}\mathbf{x}^\top \in \mathbb{R}^{n \times n}$ .

- $\lambda = 0$  (pure Wigner matrix) [Wigner 1958]:  $\varsigma_1(\frac{1}{\sqrt{n}} \mathbf{Y}) \rightarrow 2$ .
- $\lambda > 0$  (spiked Wigner matrix) [Féral-Péché 2007]:

# Spectral (BBP) transition

Spiked Wigner model:  $\mathbf{Y} = \mathbf{W} + \frac{\lambda}{\sqrt{n}} \mathbf{x}\mathbf{x}^\top \in \mathbb{R}^{n \times n}$ .

- $\lambda = 0$  (pure Wigner matrix) [Wigner 1958]:  $\varsigma_1(\frac{1}{\sqrt{n}} \mathbf{Y}) \rightarrow 2$ .
- $\lambda > 0$  (spiked Wigner matrix) [Féral-Péché 2007]:
  - $\lambda \leq 1$  (subcritical):  $\varsigma_1(\frac{1}{\sqrt{n}} \mathbf{Y}) \rightarrow 2$  and  $\langle v_1(\frac{1}{\sqrt{n}} \mathbf{Y}), \mathbf{x} \rangle \rightarrow 0$ .

# Spectral (BBP) transition

Spiked Wigner model:  $\mathbf{Y} = \mathbf{W} + \frac{\lambda}{\sqrt{n}} \mathbf{x}\mathbf{x}^\top \in \mathbb{R}^{n \times n}$ .

- $\lambda = 0$  (pure Wigner matrix) [Wigner 1958]:  $\varsigma_1(\frac{1}{\sqrt{n}} \mathbf{Y}) \rightarrow 2$ .
- $\lambda > 0$  (spiked Wigner matrix) [Féral-Péché 2007]:
  - $\lambda \leq 1$  (subcritical):  $\varsigma_1(\frac{1}{\sqrt{n}} \mathbf{Y}) \rightarrow 2$  and  $\langle \mathbf{v}_1(\frac{1}{\sqrt{n}} \mathbf{Y}), \mathbf{x} \rangle \rightarrow 0$ .
  - $\lambda > 1$  (supercritical):  $\varsigma_1(\frac{1}{\sqrt{n}} \mathbf{Y}) \rightarrow \lambda + \frac{1}{\lambda} > 2$  and  $\langle \mathbf{v}_1(\frac{1}{\sqrt{n}} \mathbf{Y}), \mathbf{x} \rangle = \Omega(1)$ .

# Spectral (BBP) transition

Spiked Wigner model:  $\mathbf{Y} = \mathbf{W} + \frac{\lambda}{\sqrt{n}} \mathbf{x}\mathbf{x}^\top \in \mathbb{R}^{n \times n}$ .

- $\lambda = 0$  (pure Wigner matrix) [Wigner 1958]:  $\varsigma_1(\frac{1}{\sqrt{n}} \mathbf{Y}) \rightarrow 2$ .
- $\lambda > 0$  (spiked Wigner matrix) [Féral-Péché 2007]:
  - $\lambda \leq 1$  (subcritical):  $\varsigma_1(\frac{1}{\sqrt{n}} \mathbf{Y}) \rightarrow 2$  and  $\langle \mathbf{v}_1(\frac{1}{\sqrt{n}} \mathbf{Y}), \mathbf{x} \rangle \rightarrow 0$ .
  - $\lambda > 1$  (supercritical):  $\varsigma_1(\frac{1}{\sqrt{n}} \mathbf{Y}) \rightarrow \lambda + \frac{1}{\lambda} > 2$  and  $\langle \mathbf{v}_1(\frac{1}{\sqrt{n}} \mathbf{Y}), \mathbf{x} \rangle = \Omega(1)$ .




Figure:  $\lambda = 0$




Figure:  $\lambda = 0.5$




Figure:  $\lambda = 1.5$



# Optimality of PCA

**Question:** is this spectral approach optimal

- Statistically (i.e., among all possible statistics)?
- Computationally (i.e., if we restrict to **polynomial-time** computable statistics)?

# Optimality of PCA

**Question:** is this spectral approach optimal

- Statistically (i.e., among all possible statistics)?
- Computationally (i.e., if we restrict to **polynomial-time** computable statistics)?

Statistically: the answer depends on the prior  $\pi$  of  $x$ .

- [Perry-Wein-Bandeira-Moitra 2018]: for “simple” and “dense” priors (e.g.,  $\pi = \text{unif}(\{-1, +1\}^n)$  or  $\pi = \mathcal{N}(0, \mathbb{I}_n)$ ), PCA is optimal.
- [Lesieur-Krzakala-Zdeborová 2015], [Lelarge-Miolane 2019], [El Alaoui-Krzakala-Jordan 2020], etc.: for “sufficiently sparse” prior  $\pi$ , PCA is not optimal.

# Optimality of PCA

**Question:** is this spectral approach optimal

- Statistically (i.e., among all possible statistics)?
- Computationally (i.e., if we restrict to polynomial-time computable statistics)?

Statistically: the answer depends on the prior  $\pi$  of  $x$ .

- [Perry-Wein-Bandeira-Moitra 2018]: for “simple” and “dense” priors (e.g.,  $\pi = \text{unif}(\{-1, +1\}^n)$  or  $\pi = \mathcal{N}(0, \mathbb{I}_n)$ ), PCA is optimal.
- [Lesieur-Krzakala-Zdeborová 2015], [Lelarge-Miolane 2019], [El Alaoui-Krzakala-Jordan 2020], etc.: for “sufficiently sparse” prior  $\pi$ , PCA is not optimal.

Computationally: [Kunisky-Wein-Bandeira 2022]: evidence suggests that PCA is always optimal.

# Why correlated spiked models?

# Why correlated spiked models?

- Modern data analysis increasingly involves multiple, related datasets.

# Why correlated spiked models?

- Modern data analysis increasingly involves multiple, related datasets.
- **Belief** in multi-modal learning: jointly analyzing related datasets can yield more powerful inferences than processing each one in isolation.




Figure: Multiple related datasets

# Correlated spiked models

[Krzakala-Zdeborová 2025]: a natural toy model for multi-modal inference:

$$\mathbf{X} = \sum_{k=1}^r \frac{\lambda_k}{\sqrt{n}} \mathbf{x}_k \mathbf{u}_k^\top + \mathbf{W} \in \mathbb{R}^{n \times N}, \quad \mathbf{Y} = \sum_{k=1}^r \frac{\mu_k}{\sqrt{n}} \mathbf{y}_k \mathbf{v}_k^\top + \mathbf{Z} \in \mathbb{R}^{n \times N}.$$

Here  $(\mathbf{x}_k, \mathbf{y}_k)$  are correlated spikes such that  $\|\mathbf{x}_k\|, \|\mathbf{y}_k\| \approx \sqrt{n}$  and  $\langle \mathbf{x}_k, \mathbf{y}_k \rangle \approx \rho_k \|\mathbf{x}_k\| \|\mathbf{y}_k\|$ .

# Correlated spiked models

[Krzakala-Zdeborová 2025]: a natural toy model for multi-modal inference:

$$\mathbf{X} = \sum_{k=1}^r \frac{\lambda_k}{\sqrt{n}} \mathbf{x}_k \mathbf{u}_k^\top + \mathbf{W} \in \mathbb{R}^{n \times N}, \quad \mathbf{Y} = \sum_{k=1}^r \frac{\mu_k}{\sqrt{n}} \mathbf{y}_k \mathbf{v}_k^\top + \mathbf{Z} \in \mathbb{R}^{n \times N}.$$

Here  $(\mathbf{x}_k, \mathbf{y}_k)$  are correlated spikes such that  $\|\mathbf{x}_k\|, \|\mathbf{y}_k\| \approx \sqrt{n}$  and  $\langle \mathbf{x}_k, \mathbf{y}_k \rangle \approx \rho_k \|\mathbf{x}_k\| \|\mathbf{y}_k\|$ . Two special cases:

Correlated spiked Wigner model:

$$\mathbf{X} = \frac{\lambda}{\sqrt{n}} \mathbf{x} \mathbf{x}^\top + \mathbf{W} \in \mathbb{R}^{n \times n},$$
$$\mathbf{Y} = \frac{\mu}{\sqrt{n}} \mathbf{y} \mathbf{y}^\top + \mathbf{Z} \in \mathbb{R}^{n \times n}.$$

Correlated spiked Wishart model:

$$\mathbf{X} = \frac{\sqrt{\lambda}}{\sqrt{n}} \mathbf{x} \mathbf{u}^\top + \mathbf{W} \in \mathbb{R}^{n \times N},$$
$$\mathbf{Y} = \frac{\sqrt{\mu}}{\sqrt{n}} \mathbf{y} \mathbf{v}^\top + \mathbf{Z} \in \mathbb{R}^{n \times N}.$$



# Special case 1

## Correlated spiked Wigner model:

$$\mathbf{X} = \frac{\lambda}{\sqrt{n}} \mathbf{x} \mathbf{x}^\top + \mathbf{W} \in \mathbb{R}^{n \times n}, \quad \mathbf{Y} = \frac{\mu}{\sqrt{n}} \mathbf{y} \mathbf{y}^\top + \mathbf{Z} \in \mathbb{R}^{n \times n}.$$

Here  $(x, y) \sim \pi$  such that  $\|x\|, \|y\| \approx \sqrt{n}$  and  $\langle x, y \rangle \approx \rho \|x\| \|y\|$ , e.g.,

## Correlated spiked Wigner model:

$$\mathbf{X} = \frac{\lambda}{\sqrt{n}} \mathbf{x} \mathbf{x}^\top + \mathbf{W} \in \mathbb{R}^{n \times n}, \quad \mathbf{Y} = \frac{\mu}{\sqrt{n}} \mathbf{y} \mathbf{y}^\top + \mathbf{Z} \in \mathbb{R}^{n \times n}.$$

Here  $(x, y) \sim \pi$  such that  $\|x\|, \|y\| \approx \sqrt{n}$  and  $\langle x, y \rangle \approx \rho \|x\| \|y\|$ , e.g.,

- ① correlated Gaussian:  $(x_i, y_i) \stackrel{iid}{\sim} \mathcal{N}(0, \begin{pmatrix} 1 & \rho \\ \rho & 1 \end{pmatrix})$ ;

## Correlated spiked Wigner model:

$$\mathbf{X} = \frac{\lambda}{\sqrt{n}} \mathbf{x} \mathbf{x}^\top + \mathbf{W} \in \mathbb{R}^{n \times n}, \quad \mathbf{Y} = \frac{\mu}{\sqrt{n}} \mathbf{y} \mathbf{y}^\top + \mathbf{Z} \in \mathbb{R}^{n \times n}.$$

Here  $(\mathbf{x}, \mathbf{y}) \sim \pi$  such that  $\|\mathbf{x}\|, \|\mathbf{y}\| \approx \sqrt{n}$  and  $\langle \mathbf{x}, \mathbf{y} \rangle \approx \rho \|\mathbf{x}\| \|\mathbf{y}\|$ , e.g.,

- ① correlated Gaussian:  $(x_i, y_i) \stackrel{iid}{\sim} \mathcal{N}(0, \begin{pmatrix} 1 & \rho \\ \rho & 1 \end{pmatrix})$ ;
- ② correlated Rademacher:  $(x_i, y_i) \stackrel{iid}{\sim}$  such that  $x_i, y_i \sim \text{unif}(\{-1, +1\})$  and  $\mathbb{E}[x_i y_i] = \rho$ ;

## Correlated spiked Wigner model:

$$\mathbf{X} = \frac{\lambda}{\sqrt{n}} \mathbf{x}\mathbf{x}^\top + \mathbf{W} \in \mathbb{R}^{n \times n}, \quad \mathbf{Y} = \frac{\mu}{\sqrt{n}} \mathbf{y}\mathbf{y}^\top + \mathbf{Z} \in \mathbb{R}^{n \times n}.$$

Here  $(x, y) \sim \pi$  such that  $\|x\|, \|y\| \approx \sqrt{n}$  and  $\langle x, y \rangle \approx \rho \|x\| \|y\|$ , e.g.,

- ① correlated Gaussian:  $(x_i, y_i) \stackrel{iid}{\sim} \mathcal{N}(0, \begin{pmatrix} 1 & \rho \\ \rho & 1 \end{pmatrix})$ ;
- ② correlated Rademacher:  $(x_i, y_i) \stackrel{iid}{\sim}$  such that  $x_i, y_i \sim \text{unif}(\{-1, +1\})$  and  $\mathbb{E}[x_i y_i] = \rho$ ;
- ③ correlated sparse Rademacher:  $(x_i, y_i) \stackrel{iid}{\sim} (\frac{BX}{\sqrt{p}}, \frac{BY}{\sqrt{p}})$  such that  $B \sim \text{Ber}(p)$  and  $X, Y$  are correlated Rademacher.

## Correlated spiked Wishart model:

$$\mathbf{X} = \frac{\sqrt{\lambda}}{\sqrt{n}} \mathbf{x} \mathbf{u}^\top + \mathbf{W} \in \mathbb{R}^{n \times N}, \quad \mathbf{Y} = \frac{\sqrt{\mu}}{\sqrt{n}} \mathbf{y} \mathbf{v}^\top + \mathbf{Z} \in \mathbb{R}^{n \times N}.$$

Here  $(\mathbf{x}, \mathbf{y}) \sim \pi$  such that  $\|\mathbf{x}\|, \|\mathbf{y}\| \approx \sqrt{n}$  and  $\langle \mathbf{x}, \mathbf{y} \rangle \approx \rho \|\mathbf{x}\| \|\mathbf{y}\|$ , and  $\mathbf{u}, \mathbf{v} \sim \mathcal{N}(0, \mathbb{I}_N)$ . Equivalently,

$$(\mathbf{X}, \mathbf{Y}) = (\mathbf{X}_1, \dots, \mathbf{X}_N; \mathbf{Y}_1, \dots, \mathbf{Y}_N)$$

such that given  $\mathbf{x}, \mathbf{y}$

$$(\mathbf{X}_i, \mathbf{Y}_i) \stackrel{iid}{\sim} \mathcal{N}(0, \mathbb{I}_n + \frac{\lambda}{n} \mathbf{x} \mathbf{x}^\top) \otimes \mathcal{N}(0, \mathbb{I}_n + \frac{\mu}{n} \mathbf{y} \mathbf{y}^\top)$$

# Approach 1: Canonical correlation analysis

- A widely-used spectral approach [Thompson 2000], [Guo-Wu 2019]: canonical correlation analysis (CCA).

# Approach 1: Canonical correlation analysis

- A widely-used spectral approach [Thompson 2000], [Guo-Wu 2019]: canonical correlation analysis (CCA).
- Idea: extract information of the spike from the MANOVA matrix

$$(\mathbf{X}\mathbf{X}^\top)^{-\frac{1}{2}}(\mathbf{X}\mathbf{Y}^\top)(\mathbf{Y}\mathbf{Y}^\top)^{-\frac{1}{2}}.$$

# Approach 1: Canonical correlation analysis

- A widely-used spectral approach [Thompson 2000], [Guo-Wu 2019]: canonical correlation analysis (CCA).
- Idea: extract information of the spike from the MANOVA matrix

$$(\mathbf{X}\mathbf{X}^\top)^{-\frac{1}{2}}(\mathbf{X}\mathbf{Y}^\top)(\mathbf{Y}\mathbf{Y}^\top)^{-\frac{1}{2}}.$$

- **Advantages:** widely-used for general inference of hidden directions; seems to be robust in practice.



# Approach 1: Canonical correlation analysis

- A widely-used spectral approach [Thompson 2000], [Guo-Wu 2019]: canonical correlation analysis (CCA).
- Idea: extract information of the spike from the MANOVA matrix

$$(\mathbf{X}\mathbf{X}^\top)^{-\frac{1}{2}}(\mathbf{X}\mathbf{Y}^\top)(\mathbf{Y}\mathbf{Y}^\top)^{-\frac{1}{2}}.$$

- **Advantages**: widely-used for general inference of hidden directions; seems to be robust in practice.
- **Limitations I**: requires  $(\mathbf{X}\mathbf{X}^\top)$  to be invertible  $\implies$  restricts to the case  $N \geq n$  (for Wishart model).

# Approach 1: Canonical correlation analysis

- A widely-used spectral approach [Thompson 2000], [Guo-Wu 2019]: canonical correlation analysis (CCA).
- Idea: extract information of the spike from the MANOVA matrix

$$(\mathbf{X}\mathbf{X}^\top)^{-\frac{1}{2}}(\mathbf{X}\mathbf{Y}^\top)(\mathbf{Y}\mathbf{Y}^\top)^{-\frac{1}{2}}.$$

- **Advantages:** widely-used for general inference of hidden directions; seems to be robust in practice.
- **Limitations I:** requires  $(\mathbf{X}\mathbf{X}^\top)$  to be invertible  $\implies$  restricts to the case  $N \geq n$  (for Wishart model).
- **Limitations II:** has unsatisfactory performance for the correlated spiked model [Bao-Hu-Pan-Zhou 2019], [Ma-Yang 2023], [Bykhovskaya-Gorin 2023].

## Approach 2: Partial least squares

- Another widely-used spectral approach [Wold-Sjöström-Eriksson 2001]: partial least squares (PLS).

## Approach 2: Partial least squares

- Another widely-used spectral approach [Wold-Sjöström-Eriksson 2001]: partial least squares (PLS).
- Idea: extract information of the spike from the sample-cross-covariance matrix

$$\mathbf{XY}^T.$$

## Approach 2: Partial least squares

- Another widely-used spectral approach [Wold-Sjöström-Eriksson 2001]: partial least squares (PLS).
- Idea: extract information of the spike from the sample-cross-covariance matrix

$$\mathbf{XY}^\top.$$

- [Mergny-Zdeborová 2025]: outperforms the CCA approach (especially when  $\rho$  is close to 1).

## Approach 2: Partial least squares

- Another widely-used spectral approach [Wold-Sjöström-Eriksson 2001]: partial least squares (PLS).
- Idea: extract information of the spike from the sample-cross-covariance matrix

$$\mathbf{XY}^\top.$$

- [Mergny-Zdeborová 2025]: outperforms the CCA approach (especially when  $\rho$  is close to 1).

**Question 1:** better algorithms?

## Approach 2: Partial least squares

- Another widely-used spectral approach [Wold-Sjöström-Eriksson 2001]: partial least squares (PLS).
- Idea: extract information of the spike from the sample-cross-covariance matrix

$$\mathbf{X}\mathbf{Y}^\top.$$

- [Mergny-Zdeborová 2025]: outperforms the CCA approach (especially when  $\rho$  is close to 1).

**Question 1:** better algorithms?

**Question 2:** computational threshold for this model?

# Our algorithmic results

Define

$$F(\lambda, \mu, \rho, \gamma) = \max \left\{ \frac{\lambda^2}{\gamma}, \frac{\mu^2}{\gamma}, \frac{\lambda^2 \rho^2}{\gamma - \lambda^2 + \lambda^2 \rho^2} + \frac{\mu^2 \rho^2}{\gamma - \mu^2 + \mu^2 \rho^2} \right\}.$$

## Theorem (L.25+)

- (1) For the correlated spiked Wigner model, suppose that  $F(\lambda, \mu, \rho, 1) > 1$ . Then (under some mild assumptions on the prior  $\pi$ ) we can solve the detection/recovery problem efficiently.
- (2) For the correlated spiked Wishart model, suppose that  $\frac{n}{N} = \gamma$  for some  $\gamma = \Theta(1)$  and  $F(\lambda, \mu, \rho, \gamma) > 1$ . Then (under some mild assumptions on the prior  $\pi$ ) we can solve the detection/recovery problem efficiently.





# Discussions

- Shows that an algorithm can leverage the correlation between the spikes to detect and estimate the signals even in regimes where efficiently recovering either  $x$  from  $\mathbf{X}$  alone or  $y$  from  $\mathbf{Y}$  alone is believed to be computationally infeasible.

# Discussions

- Shows that an algorithm can leverage the correlation between the spikes to detect and estimate the signals even in regimes where efficiently recovering either  $x$  from  $\mathbf{X}$  alone or  $y$  from  $\mathbf{Y}$  alone is believed to be computationally infeasible.
- Outperforms the PLS/CCA method (see the figure below for a comparison when  $\gamma = 0.25$  and  $\rho = 0.99$ ).




Figure: Phase diagram in the  $(\lambda, \mu)$  plane.

# Algorithmic heuristics

Let us focus on the spiked Wigner model  $\mathbf{X} = \frac{\lambda}{\sqrt{n}} \mathbf{x} \mathbf{x}^\top + \mathbf{W}$ .

# Algorithmic heuristics

Let us focus on the spiked Wigner model  $\mathbf{X} = \frac{\lambda}{\sqrt{n}} \mathbf{x} \mathbf{x}^\top + \mathbf{W}$ .

PCA: determine spiked/non-spiked by  $\|\mathbf{X}\|_{\text{op}}$ . Trace method:

# Algorithmic heuristics

Let us focus on the spiked Wigner model  $\mathbf{X} = \frac{\lambda}{\sqrt{n}} \mathbf{x} \mathbf{x}^\top + \mathbf{W}$ .

PCA: determine spiked/non-spiked by  $\|\mathbf{X}\|_{\text{op}}$ . Trace method:

$$\begin{aligned} \|\mathbf{X}\|_{\text{op}}^{2k} - \|\mathbf{W}\|_{\text{op}}^{2k} &\stackrel{k \gg (\log n)}{\approx} \text{tr}(\mathbf{X}^{2k}) - \text{tr}(\mathbf{W}^{2k}) \\ &= \sum_{i_1, \dots, i_{2k}} \mathbf{x}_{i_1, i_2} \cdots \mathbf{x}_{i_{2k}, i_1} - \mathbf{w}_{i_1, i_2} \cdots \mathbf{w}_{i_{2k}, i_1} \quad (*) \end{aligned}$$

# Algorithmic heuristics


Let us focus on the spiked Wigner model  $\mathbf{X} = \frac{\lambda}{\sqrt{n}} \mathbf{x} \mathbf{x}^\top + \mathbf{W}$ .

PCA: determine spiked/non-spiked by  $\|\mathbf{X}\|_{\text{op}}$ . Trace method:

$$\begin{aligned} \|\mathbf{X}\|_{\text{op}}^{2k} - \|\mathbf{W}\|_{\text{op}}^{2k} &\stackrel{k \gg (\log n)}{\approx} \text{tr}(\mathbf{X}^{2k}) - \text{tr}(\mathbf{W}^{2k}) \\ &= \sum_{i_1, \dots, i_{2k}} \mathbf{x}_{i_1, i_2} \cdots \mathbf{x}_{i_{2k}, i_1} - \mathbf{w}_{i_1, i_2} \cdots \mathbf{w}_{i_{2k}, i_1} \quad (*) \end{aligned}$$

Observation:  $\gamma = (i_1, \dots, i_{2k}, i_1)$  forming a “self-avoided” cycle is the main contribution of  $(*)$ .

$$\begin{aligned} (*) &\approx \sum_{\gamma \text{ self-avoided}} \mathbf{x}_\gamma - \mathbf{w}_\gamma \\ \|\mathbf{X}\|_{\text{op}}^{2k} &\approx \sum_{\gamma \text{ self-avoided}} \mathbf{x}_\gamma \end{aligned}$$



# Algorithmic heuristics


Now we are given two matrices  $\mathbf{X} = \frac{\lambda}{\sqrt{n}}\mathbf{x}\mathbf{x}^\top + \mathbf{W}$ ,  $\mathbf{Y} = \frac{\mu}{\sqrt{n}}\mathbf{y}\mathbf{y}^\top + \mathbf{Z}$ .



# Algorithmic heuristics

Now we are given two matrices  $\mathbf{X} = \frac{\lambda}{\sqrt{n}} \mathbf{x} \mathbf{x}^\top + \mathbf{W}$ ,  $\mathbf{Y} = \frac{\mu}{\sqrt{n}} \mathbf{y} \mathbf{y}^\top + \mathbf{Z}$ .

Natural idea: cycles  $\implies$  decorated (edge-colored) cycles




$$(\mathbf{X}, \mathbf{Y})_{\gamma'} :=$$

$$\mathbf{X}_{i_1, i_2} \mathbf{X}_{i_2, i_3} \mathbf{Y}_{i_3, i_4} \cdots \mathbf{X}_{i_{2k-1}, i_{2k}} \mathbf{Y}_{i_{2k}, i_1}$$

# Algorithmic heuristics

Now we are given two matrices  $\mathbf{X} = \frac{\lambda}{\sqrt{n}} \mathbf{x} \mathbf{x}^\top + \mathbf{W}$ ,  $\mathbf{Y} = \frac{\mu}{\sqrt{n}} \mathbf{y} \mathbf{y}^\top + \mathbf{Z}$ .

Natural idea: cycles  $\implies$  decorated (edge-colored) cycles



$$(\mathbf{X}, \mathbf{Y})_{\gamma'} := \mathbf{X}_{i_1, i_2} \mathbf{X}_{i_2, i_3} \mathbf{Y}_{i_3, i_4} \cdots \mathbf{X}_{i_{2k-1}, i_{2k}} \mathbf{Y}_{i_{2k}, i_1}$$

Approach: consider a suitable **(weighted)** linear combination

$$\sum_{\gamma': \text{decorated cycle}} \Lambda(\gamma') \cdot (\mathbf{X}, \mathbf{Y})_{\gamma'}.$$

# Algorithmic heuristics

# Algorithmic heuristics

- Why  $(\star) = \sum_{\gamma': \text{decorated cycle}} \Lambda(\gamma') \cdot (\mathbf{X}, \mathbf{Y})_{\gamma'}$  outperforms the PLS method/  
BBP-threshold?

# Algorithmic heuristics

- Why  $(\star) = \sum_{\gamma': \text{decorated cycle}} \Lambda(\gamma') \cdot (\mathbf{X}, \mathbf{Y})_{\gamma'}$  outperforms the PLS method/BBP-threshold?

High-level answer: PLS method (studying  $\mathbf{X}\mathbf{Y}^\top$ )/BBP-threshold (studying  $\mathbf{X}$ ) correspond to two **sub-classes**

$$\left\{ \mathbf{X}_{i_1, i_2} \mathbf{Y}_{i_2, i_3} \mathbf{X}_{i_3, i_4} \cdots \mathbf{Y}_{i_{2k}, i_1} \right\}, \quad \left\{ \mathbf{X}_{i_1, i_2} \mathbf{X}_{i_2, i_3} \cdots \mathbf{X}_{i_{2k}, i_1} \right\}.$$

# Algorithmic heuristics

- Why  $(\star) = \sum_{\gamma': \text{decorated cycle}} \Lambda(\gamma') \cdot (\mathbf{X}, \mathbf{Y})_{\gamma'}$  outperforms the PLS method/BBP-threshold?

High-level answer: PLS method (studying  $\mathbf{XY}^\top$ )/BBP-threshold (studying  $\mathbf{X}$ ) correspond to two **sub-classes**

$$\left\{ \mathbf{X}_{i_1, i_2} \mathbf{Y}_{i_2, i_3} \mathbf{X}_{i_3, i_4} \cdots \mathbf{Y}_{i_{2k}, i_1} \right\}, \quad \left\{ \mathbf{X}_{i_1, i_2} \mathbf{X}_{i_2, i_3} \cdots \mathbf{X}_{i_{2k}, i_1} \right\}.$$

- Can this statistic be efficiently calculated?

# Algorithmic heuristics

- Why  $(\star) = \sum_{\gamma': \text{decorated cycle}} \Lambda(\gamma') \cdot (\mathbf{X}, \mathbf{Y})_{\gamma'}$  outperforms the PLS method/BBP-threshold?

High-level answer: PLS method (studying  $\mathbf{XY}^\top$ )/BBP-threshold (studying  $\mathbf{X}$ ) correspond to two **sub-classes**

$$\left\{ \mathbf{X}_{i_1, i_2} \mathbf{Y}_{i_2, i_3} \mathbf{X}_{i_3, i_4} \cdots \mathbf{Y}_{i_{2k}, i_1} \right\}, \quad \left\{ \mathbf{X}_{i_1, i_2} \mathbf{X}_{i_2, i_3} \cdots \mathbf{X}_{i_{2k}, i_1} \right\}.$$

- Can this statistic be efficiently calculated?
  - $\gamma'$  has length  $\Theta(\log n)$ : brutal-force enumeration takes time  $n^{\Theta(\log n)}$  (pseudo-polynomial).

# Algorithmic heuristics

- Why  $(\star) = \sum_{\gamma': \text{decorated cycle}} \Lambda(\gamma') \cdot (\mathbf{X}, \mathbf{Y})_{\gamma'}$  outperforms the PLS method/BBP-threshold?

High-level answer: PLS method (studying  $\mathbf{XY}^\top$ )/BBP-threshold (studying  $\mathbf{X}$ ) correspond to two **sub-classes**

$$\left\{ \mathbf{X}_{i_1, i_2} \mathbf{Y}_{i_2, i_3} \mathbf{X}_{i_3, i_4} \cdots \mathbf{Y}_{i_{2k}, i_1} \right\}, \quad \left\{ \mathbf{X}_{i_1, i_2} \mathbf{X}_{i_2, i_3} \cdots \mathbf{X}_{i_{2k}, i_1} \right\}.$$

- Can this statistic be efficiently calculated?
  - $\gamma'$  has length  $\Theta(\log n)$ : brutal-force enumeration takes time  $n^{\Theta(\log n)}$  (pseudo-polynomial).
  - Use the idea of color-coding [Alon-Yuster-Zwick 1995], [Hopkins-Steurer 2017],  $(\star)$  can be approximately computed efficiently.



# Algorithmic heuristics

- Why  $(\star) = \sum_{\gamma': \text{decorated cycle}} \Lambda(\gamma') \cdot (\mathbf{X}, \mathbf{Y})_{\gamma'}$  outperforms the PLS method/BBP-threshold?

High-level answer: PLS method (studying  $\mathbf{XY}^\top$ )/BBP-threshold (studying  $\mathbf{X}$ ) correspond to two **sub-classes**

$$\left\{ \mathbf{X}_{i_1, i_2} \mathbf{Y}_{i_2, i_3} \mathbf{X}_{i_3, i_4} \cdots \mathbf{Y}_{i_{2k}, i_1} \right\}, \quad \left\{ \mathbf{X}_{i_1, i_2} \mathbf{X}_{i_2, i_3} \cdots \mathbf{X}_{i_{2k}, i_1} \right\}.$$

- Can this statistic be efficiently calculated?
  - $\gamma'$  has length  $\Theta(\log n)$ : brutal-force enumeration takes time  $n^{\Theta(\log n)}$  (pseudo-polynomial).
  - Use the idea of color-coding [Alon-Yuster-Zwick 1995], [Hopkins-Steurer 2017],  $(\star)$  can be approximately computed efficiently.
- Detection  $\implies$  recovery?

# Algorithmic heuristics

- Why  $(\star) = \sum_{\gamma': \text{decorated cycle}} \Lambda(\gamma') \cdot (\mathbf{X}, \mathbf{Y})_{\gamma'}$  outperforms the PLS method/BBP-threshold?

High-level answer: PLS method (studying  $\mathbf{XY}^\top$ )/BBP-threshold (studying  $\mathbf{X}$ ) correspond to two **sub-classes**

$$\left\{ \mathbf{X}_{i_1, i_2} \mathbf{Y}_{i_2, i_3} \mathbf{X}_{i_3, i_4} \cdots \mathbf{Y}_{i_{2k}, i_1} \right\}, \quad \left\{ \mathbf{X}_{i_1, i_2} \mathbf{X}_{i_2, i_3} \cdots \mathbf{X}_{i_{2k}, i_1} \right\}.$$

- Can this statistic be efficiently calculated?
  - $\gamma'$  has length  $\Theta(\log n)$ : brutal-force enumeration takes time  $n^{\Theta(\log n)}$  (pseudo-polynomial).
  - Use the idea of color-coding [Alon-Yuster-Zwick 1995], [Hopkins-Steurer 2017],  $(\star)$  can be approximately computed efficiently.
- Detection  $\implies$  recovery?

High-level answer: decorated cycles  $\implies$  decorated paths.

**Question:** is our algorithm optimal?

**Question:** is our algorithm optimal?

- We cannot deduce the optimality from statistical lower bounds even when the correlation  $\rho = 0$ :
  - $F < 1 \iff$  BBP threshold;
  - For certain choice of (sparse) priors  $\pi$  detection/recovery is possible below BBP threshold.

**Question:** is our algorithm optimal?

- We cannot deduce the optimality from statistical lower bounds even when the correlation  $\rho = 0$ :
  - $F < 1 \iff$  BBP threshold;
  - For certain choice of (sparse) priors  $\pi$  detection/recovery is possible below BBP threshold.

**Statistical-computational gap:** a major challenge in high-dimensional statistics.

# Computational lower bounds

**Question:** is our algorithm optimal?

- We cannot deduce the optimality from statistical lower bounds even when the correlation  $\rho = 0$ :
  - $F < 1 \iff$  BBP threshold;
  - For certain choice of (sparse) priors  $\pi$  detection/recovery is possible below BBP threshold.

**Statistical-computational gap:** a major challenge in high-dimensional statistics.

- Instead, can we show all **poly-time algorithms** fail when  $F < 1$ ?

# Computational lower bounds

# Computational lower bounds

- Traditionally, complexity theory studies hardness of computational problems for **worst-case** instance.



# Computational lower bounds

- Traditionally, complexity theory studies hardness of computational problems for **worst-case** instance.
- Usually certify hardness by **reduction**: solving this problem  $\implies$  solving some well-known hard problems.

# Computational lower bounds

- Traditionally, complexity theory studies hardness of computational problems for **worst-case** instance.
- Usually certify hardness by **reduction**: solving this problem  $\implies$  solving some well-known hard problems.
- For problems with **random** instance, we care about the hardness for a **typical** instance  $\implies$  reduction is much more difficult than in worst-case instance.

# Computational lower bounds

- Traditionally, complexity theory studies hardness of computational problems for **worst-case** instance.
- Usually certify hardness by **reduction**: solving this problem  $\implies$  solving some well-known hard problems.
- For problems with **random** instance, we care about the hardness for a **typical** instance  $\implies$  reduction is much more difficult than in worst-case instance.
- Another popular **evidence** of average-case hardness: show that a wide class of algorithms fail to solve the problem, e.g.,

# Computational lower bounds

- Traditionally, complexity theory studies hardness of computational problems for **worst-case** instance.
- Usually certify hardness by **reduction**: solving this problem  $\implies$  solving some well-known hard problems.
- For problems with **random** instance, we care about the hardness for a **typical** instance  $\implies$  reduction is much more difficult than in worst-case instance.
- Another popular **evidence** of average-case hardness: show that a wide class of algorithms fail to solve the problem, e.g.,
  - local algorithms/MCMC;

# Computational lower bounds

- Traditionally, complexity theory studies hardness of computational problems for **worst-case** instance.
- Usually certify hardness by **reduction**: solving this problem  $\implies$  solving some well-known hard problems.
- For problems with **random** instance, we care about the hardness for a **typical** instance  $\implies$  reduction is much more difficult than in worst-case instance.
- Another popular **evidence** of average-case hardness: show that a wide class of algorithms fail to solve the problem, e.g.,
  - local algorithms/MCMC;
  - smooth algorithms;

# Computational lower bounds

- Traditionally, complexity theory studies hardness of computational problems for **worst-case** instance.
- Usually certify hardness by **reduction**: solving this problem  $\implies$  solving some well-known hard problems.
- For problems with **random** instance, we care about the hardness for a **typical** instance  $\implies$  reduction is much more difficult than in worst-case instance.
- Another popular **evidence** of average-case hardness: show that a wide class of algorithms fail to solve the problem, e.g.,
  - local algorithms/MCMC;
  - smooth algorithms;
  - sum-of-squares method;

# Computational lower bounds

- Traditionally, complexity theory studies hardness of computational problems for **worst-case** instance.
- Usually certify hardness by **reduction**: solving this problem  $\implies$  solving some well-known hard problems.
- For problems with **random** instance, we care about the hardness for a **typical** instance  $\implies$  reduction is much more difficult than in worst-case instance.
- Another popular **evidence** of average-case hardness: show that a wide class of algorithms fail to solve the problem, e.g.,
  - local algorithms/MCMC;
  - smooth algorithms;
  - sum-of-squares method;
  - statistical physics method/belief propagation;

# Computational lower bounds

- Traditionally, complexity theory studies hardness of computational problems for **worst-case** instance.
- Usually certify hardness by **reduction**: solving this problem  $\implies$  solving some well-known hard problems.
- For problems with **random** instance, we care about the hardness for a **typical** instance  $\implies$  reduction is much more difficult than in worst-case instance.
- Another popular **evidence** of average-case hardness: show that a wide class of algorithms fail to solve the problem, e.g.,
  - local algorithms/MCMC;
  - smooth algorithms;
  - sum-of-squares method;
  - statistical physics method/belief propagation;
  - this talk: **low-degree polynomials**; ...



# The low-degree method

# The low-degree method

Goal: hypothesis testing with error probability  $o(1)$  between

- Null distribution  $\mathbb{Q}$  (i.e., two independent noise matrices).
- Planted distribution  $\mathbb{P}$  (i.e., two matrices with correlated spikes);

# The low-degree method

Goal: hypothesis testing with error probability  $o(1)$  between

- Null distribution  $\mathbb{Q}$  (i.e., two independent noise matrices).
- Planted distribution  $\mathbb{P}$  (i.e., two matrices with correlated spikes);

**Degree- $D$  test:** multivariate polynomials  $f : (\mathbf{X}, \mathbf{Y}) \rightarrow \mathbb{R}$  of degree  $D = D_n$

# The low-degree method

Goal: hypothesis testing with error probability  $o(1)$  between

- Null distribution  $\mathbb{Q}$  (i.e., two independent noise matrices).
- Planted distribution  $\mathbb{P}$  (i.e., two matrices with correlated spikes);

**Degree- $D$  test:** multivariate polynomials  $f : (\mathbf{X}, \mathbf{Y}) \rightarrow \mathbb{R}$  of degree  $D = D_n$

“Success”:  $f = f_n$  separates  $\mathbb{P}$  and  $\mathbb{Q}$  if

$$\sqrt{\max\{\mathrm{Var}_{\mathbb{P}}(f), \mathrm{Var}_{\mathbb{Q}}(f)\}} = o(1) \cdot |\mathbb{E}_{\mathbb{P}}[f] - \mathbb{E}_{\mathbb{Q}}[f]|.$$

# The low-degree method

Goal: hypothesis testing with error probability  $o(1)$  between

- Null distribution  $\mathbb{Q}$  (i.e., two independent noise matrices).
- Planted distribution  $\mathbb{P}$  (i.e., two matrices with correlated spikes);

**Degree- $D$  test:** multivariate polynomials  $f : (\mathbf{X}, \mathbf{Y}) \rightarrow \mathbb{R}$  of degree  $D = D_n$

“Success”:  $f = f_n$  separates  $\mathbb{P}$  and  $\mathbb{Q}$  if

$$\sqrt{\max\{\mathrm{Var}_{\mathbb{P}}(f), \mathrm{Var}_{\mathbb{Q}}(f)\}} = o(1) \cdot |\mathbb{E}_{\mathbb{P}}[f] - \mathbb{E}_{\mathbb{Q}}[f]|.$$

Heuristics: failure of degree- $D$  polynomials  $\xRightarrow{\text{evidence}}$  failure of algorithms with running time  $n^{D/\text{polylog}(n)}$ .

# The low-degree method

Goal: hypothesis testing with error probability  $o(1)$  between

- Null distribution  $\mathbb{Q}$  (i.e., two independent noise matrices).
- Planted distribution  $\mathbb{P}$  (i.e., two matrices with correlated spikes);

**Degree- $D$  test:** multivariate polynomials  $f : (\mathbf{X}, \mathbf{Y}) \rightarrow \mathbb{R}$  of degree  $D = D_n$

“Success”:  $f = f_n$  separates  $\mathbb{P}$  and  $\mathbb{Q}$  if

$$\sqrt{\max\{\mathrm{Var}_{\mathbb{P}}(f), \mathrm{Var}_{\mathbb{Q}}(f)\}} = o(1) \cdot |\mathbb{E}_{\mathbb{P}}[f] - \mathbb{E}_{\mathbb{Q}}[f]|.$$

Heuristics: failure of degree- $D$  polynomials  $\xRightarrow{\text{evidence}}$  failure of algorithms with running time  $n^{D/\text{polylog}(n)}$ .

Usually prove the “failure” of degree- $D$  polynomials by showing the following bound on the **low-degree advantage**:

$$\mathrm{Adv}_{\leq D}(\mathbb{P}, \mathbb{Q}) := \max_{\deg(f) \leq D} \frac{\mathbb{E}_{\mathbb{P}}[f]}{\sqrt{\mathbb{E}_{\mathbb{Q}}[f^2]}} = O(1).$$

# The low-degree method

$$\text{Adv}_{\leq D}(\mathbb{P}, \mathbb{Q}) := \max_{\deg(f) \leq D} \frac{\mathbb{E}_{\mathbb{P}}[f]}{\sqrt{\mathbb{E}_{\mathbb{Q}}[f^2]}}$$

likelihood ratio:  $L = \frac{d\mathbb{P}}{d\mathbb{Q}}$

# The low-degree method

$$\text{Adv}_{\leq D}(\mathbb{P}, \mathbb{Q}) := \max_{\deg(f) \leq D} \frac{\mathbb{E}_{\mathbb{P}}[f]}{\sqrt{\mathbb{E}_{\mathbb{Q}}[f^2]}}$$

likelihood ratio:  $L = \frac{d\mathbb{P}}{d\mathbb{Q}}$

$$= \max_{\deg(f) \leq D} \frac{\mathbb{E}_{\mathbb{Q}}[L \cdot f]}{\sqrt{\mathbb{E}_{\mathbb{Q}}[f^2]}}$$

$$\langle f, g \rangle := \mathbb{E}_{\mathbb{Q}}[f \cdot g]$$



# The low-degree method

$$\text{Adv}_{\leq D}(\mathbb{P}, \mathbb{Q}) := \max_{\deg(f) \leq D} \frac{\mathbb{E}_{\mathbb{P}}[f]}{\sqrt{\mathbb{E}_{\mathbb{Q}}[f^2]}}$$

likelihood ratio:  $L = \frac{d\mathbb{P}}{d\mathbb{Q}}$

$$= \max_{\deg(f) \leq D} \frac{\mathbb{E}_{\mathbb{Q}}[L \cdot f]}{\sqrt{\mathbb{E}_{\mathbb{Q}}[f^2]}}$$

$$\langle f, g \rangle := \mathbb{E}_{\mathbb{Q}}[f \cdot g]$$

$$= \max_{\deg(f) \leq D} \frac{\langle L, f \rangle}{\|f\|}$$

$$\|f\| = \sqrt{\langle f, f \rangle}$$

# The low-degree method

$$\text{Adv}_{\leq D}(\mathbb{P}, \mathbb{Q}) := \max_{\deg(f) \leq D} \frac{\mathbb{E}_{\mathbb{P}}[f]}{\sqrt{\mathbb{E}_{\mathbb{Q}}[f^2]}}$$

likelihood ratio:  $L = \frac{d\mathbb{P}}{d\mathbb{Q}}$

$$= \max_{\deg(f) \leq D} \frac{\mathbb{E}_{\mathbb{Q}}[L \cdot f]}{\sqrt{\mathbb{E}_{\mathbb{Q}}[f^2]}}$$

$$\langle f, g \rangle := \mathbb{E}_{\mathbb{Q}}[f \cdot g]$$

$$= \max_{\deg(f) \leq D} \frac{\langle L, f \rangle}{\|f\|}$$

$$\|f\| = \sqrt{\langle f, f \rangle}$$

$$= \|L_{\leq D}\|.$$

# The low-degree method

$$\begin{aligned}\text{Adv}_{\leq D}(\mathbb{P}, \mathbb{Q}) &:= \max_{\deg(f) \leq D} \frac{\mathbb{E}_{\mathbb{P}}[f]}{\sqrt{\mathbb{E}_{\mathbb{Q}}[f^2]}} && \text{likelihood ratio: } L = \frac{d\mathbb{P}}{d\mathbb{Q}} \\&= \max_{\deg(f) \leq D} \frac{\mathbb{E}_{\mathbb{Q}}[L \cdot f]}{\sqrt{\mathbb{E}_{\mathbb{Q}}[f^2]}} && \langle f, g \rangle := \mathbb{E}_{\mathbb{Q}}[f \cdot g] \\&= \max_{\deg(f) \leq D} \frac{\langle L, f \rangle}{\|f\|} && \|f\| = \sqrt{\langle f, f \rangle} \\&= \|L_{\leq D}\|.\end{aligned}$$

- Maximizer:  $f = L_{\leq D} :=$  projection of  $L$  onto degree- $D$  subspace.

# The low-degree method

$$\begin{aligned}\text{Adv}_{\leq D}(\mathbb{P}, \mathbb{Q}) &:= \max_{\deg(f) \leq D} \frac{\mathbb{E}_{\mathbb{P}}[f]}{\sqrt{\mathbb{E}_{\mathbb{Q}}[f^2]}} && \text{likelihood ratio: } L = \frac{d\mathbb{P}}{d\mathbb{Q}} \\&= \max_{\deg(f) \leq D} \frac{\mathbb{E}_{\mathbb{Q}}[L \cdot f]}{\sqrt{\mathbb{E}_{\mathbb{Q}}[f^2]}} && \langle f, g \rangle := \mathbb{E}_{\mathbb{Q}}[f \cdot g] \\&= \max_{\deg(f) \leq D} \frac{\langle L, f \rangle}{\|f\|} && \|f\| = \sqrt{\langle f, f \rangle} \\&= \|L_{\leq D}\|.\end{aligned}$$

- Maximizer:  $f = L_{\leq D} :=$  projection of  $L$  onto degree- $D$  subspace.
- Since  $\mathbb{Q}$  is a product measure, we can directly calculate the projection using orthogonal polynomials w.r.t.  $\mathbb{Q}$ .

# Advantages of low-degree method

# Advantages of low-degree method

- Possible to calculate  $\|L_{\leq D}\|$  in many problems.

# Advantages of low-degree method

- Possible to calculate  $\|L_{\leq D}\|$  in many problems.
- Predictions seem “correct”! e.g., for planted clique, sparse/tensor PCA, community detection, etc. It is the case that
  - The best known poly-time algorithms are captured by low-degree polynomials (spectral/AMP/...);
  - Low-degree polynomials fail in the conjectured “hard” regime.

# Advantages of low-degree method

- Possible to calculate  $\|L_{\leq D}\|$  in many problems.
- Predictions seem “correct”! e.g., for planted clique, sparse/tensor PCA, community detection, etc. It is the case that
  - The best known poly-time algorithms are captured by low-degree polynomials (spectral/AMP/...);
  - Low-degree polynomials fail in the conjectured “hard” regime.
- (Relatively) simple:
  - Much simpler than sum-of-squares lower bound;
  - Rules out detection rather than certification.



# Advantages of low-degree method

- Possible to calculate  $\|L_{\leq D}\|$  in many problems.
- Predictions seem “correct”! e.g., for planted clique, sparse/tensor PCA, community detection, etc. It is the case that
  - The best known poly-time algorithms are captured by low-degree polynomials (spectral/AMP/...);
  - Low-degree polynomials fail in the conjectured “hard” regime.
- (Relatively) simple:
  - Much simpler than sum-of-squares lower bound;
  - Rules out detection rather than certification.
- General: not much assumptions on  $\mathbb{P}, \mathbb{Q}$ .

# Advantages of low-degree method

- Possible to calculate  $\|L_{\leq D}\|$  in many problems.
- Predictions seem “correct”! e.g., for planted clique, sparse/tensor PCA, community detection, etc. It is the case that
  - The best known poly-time algorithms are captured by low-degree polynomials (spectral/AMP/...);
  - Low-degree polynomials fail in the conjectured “hard” regime.
- (Relatively) simple:
  - Much simpler than sum-of-squares lower bound;
  - Rules out detection rather than certification.
- General: not much assumptions on  $\mathbb{P}, \mathbb{Q}$ .
- By varying  $D$ , can explore running times other than polynomial.

# Advantages of low-degree method

- Possible to calculate  $\|L_{\leq D}\|$  in many problems.
- Predictions seem “correct”! e.g., for planted clique, sparse/tensor PCA, community detection, etc. It is the case that
  - The best known poly-time algorithms are captured by low-degree polynomials (spectral/AMP/...);
  - Low-degree polynomials fail in the conjectured “hard” regime.
- (Relatively) simple:
  - Much simpler than sum-of-squares lower bound;
  - Rules out detection rather than certification.
- General: not much assumptions on  $\mathbb{P}, \mathbb{Q}$ .
- By varying  $D$ , can explore running times other than polynomial.
- No ingenuity required.

# Advantages of low-degree method

- Possible to calculate  $\|L_{\leq D}\|$  in many problems.
- Predictions seem “correct”! e.g., for planted clique, sparse/tensor PCA, community detection, etc. It is the case that
  - The best known poly-time algorithms are captured by low-degree polynomials (spectral/AMP/...);
  - Low-degree polynomials fail in the conjectured “hard” regime.
- (Relatively) simple:
  - Much simpler than sum-of-squares lower bound;
  - Rules out detection rather than certification.
- General: not much assumptions on  $\mathbb{P}, \mathbb{Q}$ .
- By varying  $D$ , can explore running times other than polynomial.
- No ingenuity required.
- Interpretable.

## Theorem (L.25)

- (1) For the correlated spiked Wigner model, suppose that  $F(\lambda, \mu, \rho, 1) < 1$ . Then all degree  $D = n^{o(1)}$  polynomials fails to strongly separate  $\mathbb{P}$  and  $\mathbb{Q}$ .
- (2) For the correlated spiked Wishart model, suppose that  $\frac{n}{N} = \gamma$  for some  $\gamma = \Theta(1)$  and  $F(\lambda, \mu, \rho, \gamma) < 1$ . Then all degree  $D = n^{o(1)}$  polynomials fails to strongly separate  $\mathbb{P}$  and  $\mathbb{Q}$ .

## Theorem (L.25)

- (1) For the correlated spiked Wigner model, suppose that  $F(\lambda, \mu, \rho, 1) < 1$ . Then all degree  $D = n^{o(1)}$  polynomials fails to strongly separate  $\mathbb{P}$  and  $\mathbb{Q}$ .
- (2) For the correlated spiked Wishart model, suppose that  $\frac{n}{N} = \gamma$  for some  $\gamma = \Theta(1)$  and  $F(\lambda, \mu, \rho, \gamma) < 1$ . Then all degree  $D = n^{o(1)}$  polynomials fails to strongly separate  $\mathbb{P}$  and  $\mathbb{Q}$ .

Suggests that detection requires **stretched-exponential time** below the threshold  $F = 1$ .

## Theorem (L.25)

- (1) For the correlated spiked Wigner model, suppose that  $F(\lambda, \mu, \rho, 1) < 1$ . Then all degree  $D = n^{o(1)}$  polynomials fails to strongly separate  $\mathbb{P}$  and  $\mathbb{Q}$ .
- (2) For the correlated spiked Wishart model, suppose that  $\frac{n}{N} = \gamma$  for some  $\gamma = \Theta(1)$  and  $F(\lambda, \mu, \rho, \gamma) < 1$ . Then all degree  $D = n^{o(1)}$  polynomials fails to strongly separate  $\mathbb{P}$  and  $\mathbb{Q}$ .

Suggests that detection requires **stretched-exponential time** below the threshold  $F = 1$ .

Recovery should be harder than detection  $\implies$  recovery also requires stretched-exponential time.

## Theorem (L.25)

- (1) For the correlated spiked Wigner model, suppose that  $F(\lambda, \mu, \rho, 1) < 1$ . Then all degree  $D = n^{o(1)}$  polynomials fails to strongly separate  $\mathbb{P}$  and  $\mathbb{Q}$ .
- (2) For the correlated spiked Wishart model, suppose that  $\frac{n}{N} = \gamma$  for some  $\gamma = \Theta(1)$  and  $F(\lambda, \mu, \rho, \gamma) < 1$ . Then all degree  $D = n^{o(1)}$  polynomials fails to strongly separate  $\mathbb{P}$  and  $\mathbb{Q}$ .

Suggests that detection requires **stretched-exponential time** below the threshold  $F = 1$ .

Recovery should be harder than detection  $\implies$  recovery also requires stretched-exponential time.

In conclusion, suggests that  $F = 1$  is the exact computational threshold (and thus our algorithm is optimal).



# Proof sketch

Standard calculation yields that

$$\begin{aligned}\text{Adv}_{\leq D}(\mathbb{P}, \mathbb{Q}) &= \|L_{\leq D}\| \\ &= \mathbb{E}_{(x,y),(x',y') \sim \pi} \left[ \exp_{\leq D} \left( \frac{\lambda^2}{2} \left( \frac{\langle x, x' \rangle}{\sqrt{n}} \right)^2 + \frac{\mu^2}{2} \left( \frac{\langle y, y' \rangle}{\sqrt{n}} \right)^2 \right) \right].\end{aligned}$$

# Proof sketch

Standard calculation yields that

$$\begin{aligned}\text{Adv}_{\leq D}(\mathbb{P}, \mathbb{Q}) &= \|L_{\leq D}\| \\ &= \mathbb{E}_{(x,y),(x',y') \sim \pi} \left[ \exp_{\leq D} \left( \frac{\lambda^2}{2} \left( \frac{\langle x, x' \rangle}{\sqrt{n}} \right)^2 + \frac{\mu^2}{2} \left( \frac{\langle y, y' \rangle}{\sqrt{n}} \right)^2 \right) \right].\end{aligned}$$

Our intuition in bounding  $(\star)$ : by CLT

$$\left( \frac{\langle x, x' \rangle}{\sqrt{n}}, \frac{\langle y, y' \rangle}{\sqrt{n}} \right) \approx (U, V) \sim \mathcal{N}(0, \begin{pmatrix} 1 & \rho^2 \\ \rho^2 & 1 \end{pmatrix}).$$

So  $(\star) \approx \mathbb{E}[\exp_{\leq D}(\frac{\lambda^2 U^2 + \mu^2 V^2}{2})]$ , which is  $O(1)$  if and only if  $F(\lambda, \mu, \rho) \leq 1$ .

# Proof sketch

Standard calculation yields that

$$\begin{aligned}\text{Adv}_{\leq D}(\mathbb{P}, \mathbb{Q}) &= \|L_{\leq D}\| \\ &= \mathbb{E}_{(x,y),(x',y') \sim \pi} \left[ \exp_{\leq D} \left( \frac{\lambda^2}{2} \left( \frac{\langle x, x' \rangle}{\sqrt{n}} \right)^2 + \frac{\mu^2}{2} \left( \frac{\langle y, y' \rangle}{\sqrt{n}} \right)^2 \right) \right].\end{aligned}$$

Our intuition in bounding  $(\star)$ : by CLT

$$\left( \frac{\langle x, x' \rangle}{\sqrt{n}}, \frac{\langle y, y' \rangle}{\sqrt{n}} \right) \approx (U, V) \sim \mathcal{N}(0, \begin{pmatrix} 1 & \rho^2 \\ \rho^2 & 1 \end{pmatrix}).$$

So  $(\star) \approx \mathbb{E}[\exp_{\leq D}(\frac{\lambda^2 U^2 + \mu^2 V^2}{2})]$ , which is  $O(1)$  if and only if  $F(\lambda, \mu, \rho) \leq 1$ .

Approach: verify such Gaussian approximation using a careful Lindeberg's argument.

# Summary and future perspectives

Take-home message:

# Summary and future perspectives

## Take-home message:

- For the correlated spiked model, we determine the precise algorithmic phase transition (in the low-degree polynomial framework).

# Summary and future perspectives

## Take-home message:

- For the correlated spiked model, we determine the precise algorithmic phase transition (in the low-degree polynomial framework).
- Our algorithmic approach exploits the power of counting decorated cycles/paths.

# Summary and future perspectives

## Take-home message:

- For the correlated spiked model, we determine the precise algorithmic phase transition (in the low-degree polynomial framework).
- Our algorithmic approach exploits the power of counting decorated cycles/paths.
- Our computational lower bound use a interpolation argument in the low-degree analysis.

# Summary and future perspectives

## Take-home message:

- For the correlated spiked model, we determine the precise algorithmic phase transition (in the low-degree polynomial framework).
- Our algorithmic approach exploits the power of counting decorated cycles/paths.
- Our computational lower bound use a interpolation argument in the low-degree analysis.

## Open problems:



# Summary and future perspectives

## Take-home message:

- For the correlated spiked model, we determine the precise algorithmic phase transition (in the low-degree polynomial framework).
- Our algorithmic approach exploits the power of counting decorated cycles/paths.
- Our computational lower bound use a interpolation argument in the low-degree analysis.

## Open problems:

- Practical algorithms;

# Summary and future perspectives

## Take-home message:

- For the correlated spiked model, we determine the precise algorithmic phase transition (in the low-degree polynomial framework).
- Our algorithmic approach exploits the power of counting decorated cycles/paths.
- Our computational lower bound use a interpolation argument in the low-degree analysis.

## Open problems:

- Practical algorithms;
- General-rank model and other multi-modal inference problems.

# Summary and future perspectives

## Take-home message:

- For the correlated spiked model, we determine the precise algorithmic phase transition (in the low-degree polynomial framework).
- Our algorithmic approach exploits the power of counting decorated cycles/paths.
- Our computational lower bound use a interpolation argument in the low-degree analysis.

## Open problems:

- Practical algorithms;
- General-rank model and other multi-modal inference problems.

## Reference:

Zhangsong Li. The Algorithmic Phase Transition for Correlated Spiked Models. arXiv:2511.06040.