Literature Benchmark Values for This Glioblastoma Radiotherapy Project

Study	Dataset / setting	Model	Pearson	Pearson Delta	Pearson Delta DE	Interpretation
This Glioblastoma Radiotherapy Project	Glioblastoma, ctrl vs IR-24h / IR-1week	scGPT	0.991	0.944	0.981	Computed average values are high across Pearson-family metrics; condition-only baselines remain competitive on mean-correlation metrics.
This Glioblastoma Radiotherapy Project	Same	Seen-condition mean	0.996	0.975	0.997	Computed values suggest this condition-average baseline is highly competitive on mean-profile metrics.
This Glioblastoma Radiotherapy Project	Same	Bilinear Ridge delta	0.992	0.946	0.988	Low-rank ridge structure appears competitive on Pearson-family metrics in this computed summary.
This Glioblastoma Radiotherapy Project	Same	Pseudobulk RF-PCA	0.995	0.965	0.995	The saved-split values suggest competitive delta reconstruction, while the pseudobulk design provides a more informative RF comparator than condition-only encoding.
Ahlmann-Eltze et al., 2025	Adamson, Replogle K562/RPE1; unseen single-gene perturbations	scGPT	0.975	0.486	Not reported	scGPT appears lower than simple baselines on the reported single-gene task.
Ahlmann-Eltze et al., 2025	Same	Mean baseline	0.978	0.575	Not reported	Mean baseline shows higher Pearson Delta than scGPT in this summary.
Ahlmann-Eltze et al., 2025	Same	Self-trained linear/PCA model	0.979	0.586	Not reported	Values point toward the self-trained linear/PCA model as most favorable among these rows.
Csendes et al., 2025	Adamson, Norman, Replogle K562/RPE1; CRISPR Perturb-seq	scGPT	0.985	0.529	0.666	The reported values do not suggest consistent scGPT advantage over baselines on delta metrics.
Csendes et al., 2025	Same	Train mean	0.986	0.567	0.618	Mean baseline shows higher Pearson Delta than scGPT in this summary.
Csendes et al., 2025	Same	RF-GO	0.987	0.613	0.669	Values point toward GO-informed RF as the most favorable listed Csendes baseline.
Csendes et al., 2025	Same	RF-scGPT embeddings	0.987	0.591	0.637	scGPT embeddings may be useful for RF, though not clearly best overall.

Note: Values are compared across non-identical datasets and settings; interpretation is therefore directional rather than inferential.