



Introduction

Course Overview

Welcome

Course objectives:

- Learn how crypto primitives work
- Learn how to use them correctly and reason about security

My recommendations:

- Take notes
- Pause video frequently to think about the material
- Answer the in-video questions

Cryptography is everywhere

Secure communication:

- web traffic: HTTPS
- wireless traffic: 802.11i WPA2 (and WEP), GSM, Bluetooth



Encrypting files on disk: EFS, TrueCrypt

Content protection (e.g. DVD, Blu-ray): CSS, AACS

User authentication

... and much much more

Secure communication




Secure Sockets Layer / TLS

Two main parts

1. Handshake Protocol: **Establish shared secret key using public-key cryptography** (2nd part of course)
2. Record Layer: **Transmit data using shared secret key**
Ensure confidentiality and integrity (1st part of course)


Protected files on disk



Analogous to secure communication:

Alice today sends a message to Alice tomorrow

Building block: sym. encryption



E, D : cipher k : secret key (e.g. 128 bits)

m, c : plaintext, ciphertext

Encryption algorithm is **publicly known**

- Never use a proprietary cipher

Use Cases

Single use key: (one time key)

- Key is only used to encrypt one message
 - encrypted email: new key generated for every email

Multi use key: (many time key)

- Key used to encrypt multiple messages
 - encrypted files: same key used to encrypt many files
- Need more machinery than for one-time key

Things to remember

Cryptography is:

- A tremendous tool
- The basis for many security mechanisms

Cryptography is not:

- The solution to all security problems
- Reliable unless implemented and used properly
- Something you should try to invent yourself
 - many many examples of broken ad-hoc designs

End of Segment




Introduction


What is cryptography?

Crypto core

Secret key establishment:




Secure communication:




But crypto can do much more

- Digital signatures
- Anonymous communication




But crypto can do much more

- Digital signatures
- Anonymous communication
- Anonymous **digital** cash
 - Can I spend a “digital coin” without anyone knowing who I am?
 - How to prevent double spending?



Protocols

- Elections
- Private auctions




winner = MAJ [votes]

auction
winner = [highest bidder,
pays 2nd highest bid]

Protocols

- Elections
- Private auctions




Goal: compute $f(x_1, x_2, x_3, x_4)$

“Thm:” anything that can be done with trusted auth. can also be done without


- Secure multi-party computation

Crypto magic

- Privately outsourcing computation




- Zero knowledge (proof of knowledge)



A rigorous science

The three steps in cryptography:

- 
- Precisely specify threat model
 - Propose a construction
 - Prove that breaking construction under threat mode will solve an underlying hard problem

End of Segment




Introduction


History

History

David Kahn, “The code breakers” (1996)



Symmetric Ciphers



Few Historic Examples

(all badly broken)

1. Substitution cipher

$$c := E(k, "bcza") = "wnac"$$
$$D(k, c) = "bcza"$$

$k :=$

$a \rightarrow c$

$b \rightarrow w$

$c \rightarrow n$

\vdots

$z \rightarrow a$

Caesar Cipher (no key)

shift by 3:

a	→	d
b	→	e
c	→	f
⋮		
y	→	b
z	→	c

What is the size of key space in the substitution cipher assuming 26 letters?

$$|\mathcal{K}| = 26$$

$$|\mathcal{K}| = 26! \quad (26 \text{ factorial})$$

$$|\mathcal{K}| = 2^{26}$$

$$|\mathcal{K}| = 26^2$$



$$26! \approx 2^{88}$$

How to break a substitution cipher?

What is the most common letter in English text?

“X”

“L”

“E”

“H”



How to break a substitution cipher?

(1) Use frequency of English letters

"e": 12.7% , "t": 9.1% , "a": 8.1%

(2) Use frequency of pairs of letters (digrams)

"he", "an", "in", "th"

⇒ CT only attack!!

An Example

UKBYBIPOUZBCUFEEBORUKBYBHOBBERFESPVKBWFOFERNBCVBZPRUBOFERNBCVBPCYYFVUFO
FEIKNWFRFIKJNUPWRFIPOUNVNIPUBRNCUKBEFWWFDNCHXCYBOHOPYXPUBNCUBOYNRVNIWN
CPOJIOFHOPZRVFZIXUBORJRUBZRBCHNCBBONCHRJZSFWNVRJRUBZRPCYZPUKBZPUNVPWPCYVF
ZIXUPUNFCPWVRVNBCVBRPYYNUNFCPWJUKBYBIPOUZBCUIPOUNVNIPUBRNCHOPYXPUBNCUB
OYNRVNIWNCPOJIOFHOPZRNCRVNBCUNENVVFZIXUNCHPCYVFZIXUPUNFCPWZPUKBZPUNVR

B	36	→ E
N	34	
U	33	→ T
P	32	→ A
C	26	

NC	11	→ IN
PU	10	→ AT
UB	10	
UN	9	

digrams

UKB	6	→ THE
RVN	6	
FZI	4	

trigrams

2. Vigenere cipher (16'th century, Rome)

k = **C R Y P T O C R Y P T O C R Y P T** (+ mod 26)
m = **W H A T A N I C E D A Y T O D A Y**



c = **Z Z Z J U C | L U D T U N | W G C Q S**

Red arrows point to the first letter of each word in the ciphertext: Z, L, and W.

suppose most common = "H" \Rightarrow first letter of key = "H" - "E" = "C"


3. Rotor Machines (1870-1943)

Early example: the Hebern machine (single rotor)



Rotor Machines (cont.)

Most famous: the Enigma (3-5 rotors)



keys = $26^4 = 2^{18}$ (actually 2^{36} due to plugboard)

4. Data Encryption Standard (1974)

DES: # keys = 2^{56} , block size = 64 bits

Today: AES (2001), Salsa20 (2008) (and many others)

End of Segment



Introduction

Discrete Probability (crash course)

U : finite set (e.g. $U = \{0,1\}^n$)

Def: **Probability distribution** P over U is a function $P: U \rightarrow [0,1]$

such that
$$\sum_{x \in U} P(x) = 1$$

Examples:

1. Uniform distribution: $\forall x \in U: P(x) = 1/|U|$
2. Point distribution at x_0 : $P(x_0) = 1, \quad \forall x \neq x_0: P(x) = 0$

Distribution vector: $(P(000), P(001), P(010), \dots, P(111))$


Notation

- For a set $A \subseteq U$: $\Pr[A] = \sum_{x \in A} P(x) \in [0,1]$
- The set A is called an **event**

Example:

- $A = \{ \text{all } x \text{ in } \{0,1\}^n \text{ such that } \text{lsb}_2(x)=11 \}$

for the uniform distribution on $\{0,1\}^n$: $\Pr[A] =$




The union bound

- For events A_1 and A_2

$$\Pr[A_1 \cup A_2] \leq \Pr[A_1] + \Pr[A_2]$$

$$A_1 \cap A_2 = \emptyset \Rightarrow \Pr[A_1 \cup A_2] = \Pr[A_1] + \Pr[A_2]$$



Example:

$$A_1 = \{ \text{all } x \text{ in } \{0,1\}^n \text{ s.t. } \text{lsb}_2(x)=11 \} \quad ; \quad A_2 = \{ \text{all } x \text{ in } \{0,1\}^n \text{ s.t. } \text{msb}_2(x)=11 \}$$

$$\Pr[\text{lsb}_2(x)=11 \text{ or } \text{msb}_2(x)=11] = \Pr[A_1 \cup A_2] \leq \frac{1}{4} + \frac{1}{4} = \frac{1}{2}$$


Random Variables

Def: a random variable X is a function $X:U \rightarrow V$

Example: $X: \{0,1\}^n \rightarrow \{0,1,\dots,n\}$; $X(y) = \#1's(y)$

Random variable X induces a distribution on V :

$$\Pr[X=v] := \Pr[X^{-1}(v)]$$



In the example, for $v \in \{0,1,\dots,n\}$: $\Pr[X = v] =$




Randomized algorithms

- Deterministic algorithm: $y \leftarrow A(x)$
- Randomized algorithm $y \leftarrow A(x; r)$
output is a random variable

$$y \xleftarrow{R} A(x)$$

Example: $A(x; k) = E(k, x)$, $y \xleftarrow{R} A(x)$

$r \xleftarrow{R} \Omega$ denotes **uniform** rand. var. over Ω



Independence

Def: events A and B are **independent** if $\Pr[A \text{ and } B] = \Pr[A] \cdot \Pr[B]$
 random variables $X, Y : U \rightarrow V$ are independent if
 $\forall a, b \in V: \Pr[X=a \text{ and } Y=b] = \Pr[X=a] \cdot \Pr[Y=b]$

Thm: A a rand. var. over $\{0,1\}^n$, X an indep. uniform var. on $\{0,1\}^n$
 Then $Y := A \oplus X$ is uniform var. on $\{0,1\}^n$

Proof: (for $n=1$)

$$\Pr[Y=0] = \frac{p_0}{2} + \frac{p_1}{2} = \frac{1}{2} (p_0 + p_1) = \frac{1}{2}$$

A	p_r	X	p_r	A	X	Pr
0	p_0	0	$1/2$	0	0	$p_0/2$
0		1		0	1	$p_0/2$
1	p_1	1	$1/2$	1	0	$p_1/2$
1				1	1	$p_1/2$

End of Segment