

《数据库系统原理》实验报告（3）

题目：数据库安全性

学号	2154312	姓名	郑博远	日期	2023.10.31
----	---------	----	-----	----	------------

实验环境：Docker MariaDB

实验步骤及结果截图：

1. 进入名为 sys 的数据库：

```
MariaDB [(none)]> use sys;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
MariaDB [sys]>
```

2. 在 sys 数据库中，创建表 studentA：

```
MariaDB [sys]> create table studentA(
  -> `Sno` varchar(9) primary key,
  -> `Sname` varchar(20) unique,
  -> `Ssex` varchar(2),
  -> `Sage` smallint,
  -> `Sdept` varchar(20)
  -> );
Query OK, 0 rows affected (0.011 sec)

MariaDB [sys]> desc studentA;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Sno   | varchar(9)    | NO   | PRI | NULL    |       |
| Sname | varchar(20)   | YES  | UNI | NULL    |       |
| Ssex  | varchar(2)    | YES  |     | NULL    |       |
| Sage  | smallint(6)   | YES  |     | NULL    |       |
| Sdept | varchar(20)   | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.001 sec)
```

3. 向 table studentA 插入两个元组('200215121','Tom','m',20,'CS')、('200215122','Lily','f',19,'CS')。并查询：

```
MariaDB [sys]> insert into studentA values('200215121','Tom','m',20,'CS');
Query OK, 1 row affected (0.008 sec)

MariaDB [sys]> insert into studentA values('200215122','Lily','f',19,'CS')
  -> ;
Query OK, 1 row affected (0.001 sec)

MariaDB [sys]> select * from studentA;
+-----+-----+-----+-----+-----+
| Sno   | Sname | Ssex | Sage | Sdept |
+-----+-----+-----+-----+-----+
| 200215121 | Tom   | m    | 20   | CS    |
| 200215122 | Lily  | f    | 19   | CS    |
+-----+-----+-----+-----+-----+
2 rows in set (0.000 sec)
```

4. 建立用户 masterA，授予用户 masterA 以系统特权，包括 create session、create table、create user、alter user 和 drop user 等，并赋予其再授权的能力。

MariaDB 中，所对应的系统特权与任务要求略有不同。可以通过“show privileges”命令查看：

```
MariaDB [(none)]> show privileges;
```

Privilege	Context	Comment
Alter	Tables	To alter the table
Alter routine	Functions,Procedures	To alter or drop stored functions/procedures
Create	Databases,Tables,Indexes	To create new databases and tables
Create routine	Databases	To use CREATE FUNCTION/PROCEDURE
Create temporary tables	Databases	To use CREATE TEMPORARY TABLE
Create view	Tables	To create new views
Create user	Server Admin	To create new users
Delete	Tables	To delete existing rows
Delete history	Tables	To delete versioning table historical rows
Drop	Databases,Tables	To drop databases, tables, and views
Event	Server Admin	To create, alter, drop and execute events
Execute	Functions,Procedures	To execute stored routines
File	File access on server	To read and write files on the server
Grant option	Databases,Tables,Functions,Procedures	To give to other users those privileges you possess
Index	Tables	To create or drop indexes
Insert	Tables	To insert data into tables
Lock tables	Databases	To use LOCK TABLES (together with SELECT privilege)
Process	Server Admin	To view the plain text of currently executing queries
Proxy	Server Admin	To make proxy user possible
References	Databases,Tables	To have references on tables
Reload	Server Admin	To reload or refresh tables, logs and privileges
Binlog admin	Server	To purge binary logs
Binlog monitor	Server	To use SHOW BINLOG STATUS and SHOW BINARY LOG
Binlog replay	Server	To use BINLOG (generated by mariadb-binlog)
Replication master admin	Server	To monitor connected slaves
Replication slave admin	Server	To start/stop slave and apply binlog events
Slave monitor	Server	To use SHOW SLAVE STATUS and SHOW RELAYLOG EVENTS
Replication slave	Server Admin	To read binary log events from the master

可以观察到不存在“create session”、“create table”指令，此处用“create”指令替代。“create user”指令即涵盖了 alter、drop 的权限，此处为方便后一个实验任务中进行删除，对“masterA”用户赋予“alter”、“drop”权限（权限内容不同，只是为了后一个任务中左删除）：

```
MariaDB [sys]> grant create, create user, alter, drop on *.* to 'masterA'@'localhost' identified by 'masterA_password' with grant option;
Query OK, 0 rows affected (0.001 sec)

MariaDB [sys]> show grants for 'masterA'@'localhost';
+-----+
| Grants for masterA@localhost |
+-----+
| GRANT CREATE, DROP, ALTER, CREATE USER ON *.* TO 'masterA'@'localhost' IDENTIFIED BY PASSWORD '*D586982ACFA7C9454374059971D1CDA80F004138' WITH GRANT OPTION |
+-----+
1 row in set (0.000 sec)
```

5. 删除 masterA 的 create user、alter user 和 drop user 的系统特权：

```
MariaDB [sys]> revoke create user, drop, alter on *.* from 'masterA'@'localhost';
Query OK, 0 rows affected (0.007 sec)

MariaDB [sys]> show grants for 'masterA'@'localhost';
+-----+
| Grants for masterA@localhost |
+-----+
| GRANT CREATE ON *.* TO 'masterA'@'localhost' IDENTIFIED BY PASSWORD '*D586982ACFA7C9454374059971D1CDA80F004138' WITH GRANT OPTION |
+-----+
1 row in set (0.000 sec)
```

6. 在 masterA 用户下尝试查询 table studentA(注意使用 sys.studentA)：

```
MariaDB [sys]> quit;
Bye
# mariadb -u masterA -p
Enter password:
Welcome to the MariaDB monitor. Commands end with ; or \g.
Your MariaDB connection id is 5
Server version: 11.1.2-MariaDB-1:11.1.2+mariadb-ubu2204 mariadb.org binary distribution

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> desc sys.studentA;
ERROR 1142 (42000): SELECT command denied to user 'masterA'@'localhost' for table 'sys`.`studentA`
```

观察到由于“masterA”用户没有 select 权限，无法查询 table studentA。

7. 授予用户 masterA 对表 studentA 的查询、插入、修改等对象特权，并赋予其再授权的能力：

```
MariaDB [(none)]> quit;
Bye
# mariadb -u root -p
Enter password:
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 6
Server version: 11.1.2-MariaDB-1:11.1.2+maria-ubu2204 mariadb.org binary distribution

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> grant select, insert, update on sys.studentA to 'masterA'@'localhost' with grant option;
Query OK, 0 rows affected (0.007 sec)
```

8. 在 masterA 用户下查询 sys.studentA(注意使用 sys.studentA):

```
MariaDB [(none)]> quit;
Bye
# mariadb -u masterA -p
Enter password:
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 7
Server version: 11.1.2-MariaDB-1:11.1.2+maria-ubu2204 mariadb.org binary distribution

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> desc sys.studentA;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Sno   | varchar(9)    | NO   | PRI | NULL    |       |
| Sname | varchar(20)   | YES  | UNI | NULL    |       |
| Ssex  | varchar(2)    | YES  |     | NULL    |       |
| Sage  | smallint(6)   | YES  |     | NULL    |       |
| Sdept | varchar(20)   | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.001 sec)
```

9. 在 masterA 用户下再插入一个元组的数据('200215123','Bob','m',21,'IS')，并在 masterA 用户下查询(注意使用 sys.studentA):

```
MariaDB [(none)]> insert into sys.studentA values ('200215123','Bob','m',21,'IS');
Query OK, 1 row affected (0.007 sec)

MariaDB [(none)]> select * from sys.studentA;
+-----+-----+-----+-----+-----+-----+
| Sno      | Sname | Ssex | Sage | Sdept |
+-----+-----+-----+-----+-----+-----+
| 200215121 | Tom   | m    | 20   | CS    |
| 200215122 | Lily  | f    | 19   | CS    |
| 200215123 | Bob   | m    | 21   | IS    |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.000 sec)
```

10.删除今天创建的 masterA 用户：

```
MariaDB [(none)]> quit;
Bye
# mariadb -u root -p
Enter password:
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 8
Server version: 11.1.2-MariaDB-1:11.1.2+maria-ubu2204 mariadb.org binary distribution

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> drop user 'masterA'@'localhost';
Query OK, 0 rows affected (0.001 sec)
```

出现的问题:

1. 对“masterA”用户赋予实验中要求的权限会报错:

```
MariaDB [(none)]> grant create session, create table, create user, alter user, drop user on sys.studentA to 'masterA'@'localhost' identified by 'masterA_password' with grant option;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MariaDB server version for the right syntax to use near 'session, create table, create user, alter user, drop user on sys.studentA to ...' at line 1
```

解决方案:

1. MariaDB 中，所对应的系统特权与任务要求略有不同。可以通过“show privileges”命令查看:

```
MariaDB [(none)]> show privileges;
```

Privilege	Context	Comment
Alter	Tables	To alter the table
Alter routine	Functions,Procedures	To alter or drop stored functions/procedures
Create	Databases,Tables,Indexes	To create new databases and tables
Create routine	Databases	To use CREATE FUNCTION/PROCEDURE
Create temporary tables	Databases	To use CREATE TEMPORARY TABLE
Create view	Tables	To create new views
Create user	Server Admin	To create new users
Delete	Tables	To delete existing rows
Delete history	Tables	To delete versioning table historical rows
Drop	Databases,Tables	To drop databases, tables, and views
Event	Server Admin	To create, alter, drop and execute events
Execute	Functions,Procedures	To execute stored routines
File	File access on server	To read and write files on the server
Grant option	Databases,Tables,Functions,Procedures	To give to other users those privileges you possess
Index	Tables	To create or drop indexes
Insert	Tables	To insert data into tables
Lock tables	Databases	To use LOCK TABLES (together with SELECT privilege)
Process	Server Admin	To view the plain text of currently executing queries
Proxy	Server Admin	To make proxy user possible
References	Databases,Tables	To have references on tables
Reload	Server Admin	To reload or refresh tables, logs and privileges
Binlog admin	Server	To purge binary logs
Binlog monitor	Server	To use SHOW BINLOG STATUS and SHOW BINARY LOG
Binlog replay	Server	To use BINLOG (generated by mariadb-binlog)
Replication master admin	Server	To monitor connected slaves
Replication slave admin	Server	To start/stop slave and apply binlog events
Slave monitor	Server	To use SHOW SLAVE STATUS and SHOW RELAYLOG EVENTS
Replication slave	Server Admin	To read binary log events from the master
Select	Tables	To retrieve rows from tables

可以观察到不存在“create session”、“create table”指令，“create”指令即可涵盖对 databases、indexes 以及 tables 的创建权限。此外，也不存在“alter user”、“drop user”的系统特权，“create user”指令即涵盖了“alter user”、“drop user”的权限。在实验时，选用其他的特权进行替代。