

Probability and Stochastic Process II: Random Matrix Theory and Applications

Lecture 1: Introduction

Zhenyu Liao, Tiebin Mi, Caiming Qiu

School of Electronic Information and Communications (EIC)
Huazhong University of Science and Technology (HUST)

March 1, 2023


Outline

Sample Covariance


RMT for Telecom

RMT for SP


RMT for ML




- » **Big Data era:** exploit large n, p, N
- » counterintuitive phenomena different from classical asymptotics statistics
- » complete change of understanding of many methods in statistics, machine learning, signal processing, and wireless communications
- » Random Matrix Theory (RMT) provides the tools!



- » **Big Data era:** exploit large n, p, N
- » **counterintuitive** phenomena **different** from classical asymptotics statistics
- » complete **change** of understanding of many methods in statistics, machine learning, signal processing, and wireless communications
- » Random Matrix Theory (RMT) provides the tools!



- » **Big Data era:** exploit large n, p, N
- » **counterintuitive** phenomena **different** from classical asymptotics statistics
- » complete **change** of understanding of many methods in statistics, machine learning, signal processing, and wireless communications
- » Random Matrix Theory (RMT) provides the tools!



- » **Big Data era:** exploit large n, p, N
- » **counterintuitive** phenomena **different** from classical asymptotics statistics
- » complete **change** of understanding of many methods in statistics, machine learning, signal processing, and wireless communications
- » **Random Matrix Theory (RMT)** provides the tools!

Outline

Sample Covariance

RMT for Telecom

RMT for SP

RMT for ML

» **Problem:** estimate **covariance** $\mathbf{C} \in \mathbb{R}^{p \times p}$ from n data samples $\mathbf{x}_1, \dots, \mathbf{x}_n$ with $\mathbf{x}_i \sim \mathcal{N}(\mathbf{0}, \mathbf{C})$,

» Maximum likelihood sample covariance matrix with entry-wise convergence

$$\hat{\mathbf{C}} = \frac{1}{n} \sum_{i=1}^n \mathbf{x}_i \mathbf{x}_i^T \in \mathbb{R}^{p \times p}, \quad [\hat{\mathbf{C}}]_{ij} \rightarrow [\mathbf{C}]_{ij}$$

almost surely as $n \rightarrow \infty$: optimal for $n \gg p$ (or, for p “small”).

» In the regime $n \sim p$, conventional wisdom breaks down: for $\mathbf{C} = \mathbf{I}_p$ with $n < p$, $\hat{\mathbf{C}}$ has at least $p - n$ **zero eigenvalues**:

$$\boxed{\|\hat{\mathbf{C}} - \mathbf{C}\| \not\rightarrow 0, \quad n, p \rightarrow \infty} \Rightarrow \text{eigenvalue mismatch and not consistent!}$$

» due to $\|\mathbf{A}\|_\infty \leq \|\mathbf{A}\| \leq p\|\mathbf{A}\|_\infty$ for $\mathbf{A} \in \mathbb{R}^{p \times p}$ and $\|\mathbf{A}\|_\infty \equiv \max_{ij} |\mathbf{A}_{ij}|$.

- » **Problem:** estimate **covariance** $\mathbf{C} \in \mathbb{R}^{p \times p}$ from n data samples $\mathbf{x}_1, \dots, \mathbf{x}_n$ with $\mathbf{x}_i \sim \mathcal{N}(\mathbf{0}, \mathbf{C})$,
- » Maximum likelihood sample covariance matrix with **entry-wise** convergence

$$\hat{\mathbf{C}} = \frac{1}{n} \sum_{i=1}^n \mathbf{x}_i \mathbf{x}_i^T \in \mathbb{R}^{p \times p}, \quad [\hat{\mathbf{C}}]_{ij} \rightarrow [\mathbf{C}]_{ij}$$

almost surely as $n \rightarrow \infty$: optimal for $n \gg p$ (or, for p “small”).

- » In the regime $n \sim p$, conventional wisdom breaks down: for $\mathbf{C} = \mathbf{I}_p$ with $n < p$, $\hat{\mathbf{C}}$ has at least $p - n$ **zero eigenvalues**:

$$\boxed{\|\hat{\mathbf{C}} - \mathbf{C}\| \not\rightarrow 0, \quad n, p \rightarrow \infty} \Rightarrow \text{eigenvalue mismatch and not consistent!}$$

- » due to $\|\mathbf{A}\|_\infty \leq \|\mathbf{A}\| \leq p\|\mathbf{A}\|_\infty$ for $\mathbf{A} \in \mathbb{R}^{p \times p}$ and $\|\mathbf{A}\|_\infty \equiv \max_{ij} |\mathbf{A}_{ij}|$.

- » **Problem:** estimate **covariance** $\mathbf{C} \in \mathbb{R}^{p \times p}$ from n data samples $\mathbf{x}_1, \dots, \mathbf{x}_n$ with $\mathbf{x}_i \sim \mathcal{N}(\mathbf{0}, \mathbf{C})$,
- » Maximum likelihood sample covariance matrix with **entry-wise** convergence

$$\hat{\mathbf{C}} = \frac{1}{n} \sum_{i=1}^n \mathbf{x}_i \mathbf{x}_i^T \in \mathbb{R}^{p \times p}, \quad [\hat{\mathbf{C}}]_{ij} \rightarrow [\mathbf{C}]_{ij}$$

almost surely as $n \rightarrow \infty$: optimal for $n \gg p$ (or, for p “small”).

- » In the regime $n \sim p$, conventional wisdom breaks down: for $\mathbf{C} = \mathbf{I}_p$ with $n < p$, $\hat{\mathbf{C}}$ has at least $p - n$ **zero eigenvalues**:

$$\boxed{\|\hat{\mathbf{C}} - \mathbf{C}\| \not\rightarrow 0, \quad n, p \rightarrow \infty} \Rightarrow \text{eigenvalue mismatch and not consistent!}$$

- » due to $\|\mathbf{A}\|_\infty \leq \|\mathbf{A}\| \leq p\|\mathbf{A}\|_\infty$ for $\mathbf{A} \in \mathbb{R}^{p \times p}$ and $\|\mathbf{A}\|_\infty \equiv \max_{ij} |\mathbf{A}_{ij}|$.

- » **Problem:** estimate **covariance** $\mathbf{C} \in \mathbb{R}^{p \times p}$ from n data samples $\mathbf{x}_1, \dots, \mathbf{x}_n$ with $\mathbf{x}_i \sim \mathcal{N}(\mathbf{0}, \mathbf{C})$,
- » Maximum likelihood sample covariance matrix with **entry-wise** convergence

$$\hat{\mathbf{C}} = \frac{1}{n} \sum_{i=1}^n \mathbf{x}_i \mathbf{x}_i^T \in \mathbb{R}^{p \times p}, \quad [\hat{\mathbf{C}}]_{ij} \rightarrow [\mathbf{C}]_{ij}$$

almost surely as $n \rightarrow \infty$: optimal for $n \gg p$ (or, for p “small”).

- » In the regime $n \sim p$, conventional wisdom breaks down: for $\mathbf{C} = \mathbf{I}_p$ with $n < p$, $\hat{\mathbf{C}}$ has at least $p - n$ **zero eigenvalues**:

$$\boxed{\|\hat{\mathbf{C}} - \mathbf{C}\| \not\rightarrow 0, \quad n, p \rightarrow \infty} \Rightarrow \text{eigenvalue mismatch and not consistent!}$$

- » due to $\|\mathbf{A}\|_\infty \leq \|\mathbf{A}\| \leq p\|\mathbf{A}\|_\infty$ for $\mathbf{A} \in \mathbb{R}^{p \times p}$ and $\|\mathbf{A}\|_\infty \equiv \max_{ij} |\mathbf{A}_{ij}|$.

- » **Problem:** estimate **covariance** $\mathbf{C} \in \mathbb{R}^{p \times p}$ from n data samples $\mathbf{x}_1, \dots, \mathbf{x}_n$ with $\mathbf{x}_i \sim \mathcal{N}(\mathbf{0}, \mathbf{C})$,
- » Maximum likelihood sample covariance matrix with **entry-wise** convergence

$$\hat{\mathbf{C}} = \frac{1}{n} \sum_{i=1}^n \mathbf{x}_i \mathbf{x}_i^T \in \mathbb{R}^{p \times p}, \quad [\hat{\mathbf{C}}]_{ij} \rightarrow [\mathbf{C}]_{ij}$$

almost surely as $n \rightarrow \infty$: optimal for $n \gg p$ (or, for p “small”).

- » In the regime $n \sim p$, conventional wisdom breaks down: for $\mathbf{C} = \mathbf{I}_p$ with $n < p$, $\hat{\mathbf{C}}$ has at least $p - n$ **zero eigenvalues**:

$$\boxed{\|\hat{\mathbf{C}} - \mathbf{C}\| \not\rightarrow 0, \quad n, p \rightarrow \infty} \Rightarrow \text{eigenvalue mismatch and not consistent!}$$

- » due to $\|\mathbf{A}\|_\infty \leq \|\mathbf{A}\| \leq p\|\mathbf{A}\|_\infty$ for $\mathbf{A} \in \mathbb{R}^{p \times p}$ and $\|\mathbf{A}\|_\infty \equiv \max_{ij} |\mathbf{A}_{ij}|$.

- » **Problem:** estimate **covariance** $\mathbf{C} \in \mathbb{R}^{p \times p}$ from n data samples $\mathbf{x}_1, \dots, \mathbf{x}_n$ with $\mathbf{x}_i \sim \mathcal{N}(\mathbf{0}, \mathbf{C})$,
- » Maximum likelihood sample covariance matrix with **entry-wise** convergence

$$\hat{\mathbf{C}} = \frac{1}{n} \sum_{i=1}^n \mathbf{x}_i \mathbf{x}_i^T \in \mathbb{R}^{p \times p}, \quad [\hat{\mathbf{C}}]_{ij} \rightarrow [\mathbf{C}]_{ij}$$

almost surely as $n \rightarrow \infty$: optimal for $n \gg p$ (or, for p “small”).

- » In the regime $n \sim p$, conventional wisdom breaks down: for $\mathbf{C} = \mathbf{I}_p$ with $n < p$, $\hat{\mathbf{C}}$ has at least $p - n$ **zero eigenvalues**:

$$\boxed{\|\hat{\mathbf{C}} - \mathbf{C}\| \not\rightarrow 0, \quad n, p \rightarrow \infty} \Rightarrow \text{eigenvalue mismatch and not consistent!}$$

- » due to $\|\mathbf{A}\|_\infty \leq \|\mathbf{A}\| \leq p\|\mathbf{A}\|_\infty$ for $\mathbf{A} \in \mathbb{R}^{p \times p}$ and $\|\mathbf{A}\|_\infty \equiv \max_{ij} |\mathbf{A}_{ij}|$.

What about $n = 100p$? For $\mathbf{C} = \mathbf{I}_p$, as $n, p \rightarrow \infty$ with $p/n \rightarrow c \in (0, \infty)$: MP law

$$\mu(dx) = (1 - c^{-1})^+ \delta(x) + \frac{1}{2\pi cx} \sqrt{(x - E_-)^+(E_+ - x)^+} dx$$

where $E_- = (1 - \sqrt{c})^2$, $E_+ = (1 + \sqrt{c})^2$ and $(x)^+ \equiv \max(x, 0)$. Close match!




Figure: Eigenvalue distribution of $\hat{\mathbf{C}}$ versus Marčenko-Pastur law, $p = 500$, $n = 50\,000$.

- » eigenvalues span on $[E_- = (1 - \sqrt{c})^2, E_+ = (1 + \sqrt{c})^2]$.
- » for $n = 100p$, on a range of $\pm 2\sqrt{c} = \pm 0.2$ around the population eigenvalue 1.

What about $n = 100p$? For $\mathbf{C} = \mathbf{I}_p$, as $n, p \rightarrow \infty$ with $p/n \rightarrow c \in (0, \infty)$: MP law

$$\mu(dx) = (1 - c^{-1})^+ \delta(x) + \frac{1}{2\pi cx} \sqrt{(x - E_-)^+(E_+ - x)^+} dx$$

where $E_- = (1 - \sqrt{c})^2$, $E_+ = (1 + \sqrt{c})^2$ and $(x)^+ \equiv \max(x, 0)$. Close match!




Figure: Eigenvalue distribution of $\hat{\mathbf{C}}$ versus Marčenko-Pastur law, $p = 500$, $n = 50\,000$.

- » eigenvalues span on $[E_- = (1 - \sqrt{c})^2, E_+ = (1 + \sqrt{c})^2]$.
- » for $n = 100p$, on a range of $\pm 2\sqrt{c} = \pm 0.2$ around the population eigenvalue 1.

What about $n = 100p$? For $\mathbf{C} = \mathbf{I}_p$, as $n, p \rightarrow \infty$ with $p/n \rightarrow c \in (0, \infty)$: MP law

$$\mu(dx) = (1 - c^{-1})^+ \delta(x) + \frac{1}{2\pi cx} \sqrt{(x - E_-)^+(E_+ - x)^+} dx$$

where $E_- = (1 - \sqrt{c})^2$, $E_+ = (1 + \sqrt{c})^2$ and $(x)^+ \equiv \max(x, 0)$. Close match!




Figure: Eigenvalue distribution of $\hat{\mathbf{C}}$ versus Marčenko-Pastur law, $p = 500$, $n = 50\,000$.

» eigenvalues span on $[E_- = (1 - \sqrt{c})^2, E_+ = (1 + \sqrt{c})^2]$.

» for $n = 100p$, on a range of $\pm 2\sqrt{c} = \pm 0.2$ around the population eigenvalue 1.

What about $n = 100p$? For $\mathbf{C} = \mathbf{I}_p$, as $n, p \rightarrow \infty$ with $p/n \rightarrow c \in (0, \infty)$: MP law

$$\mu(dx) = (1 - c^{-1})^+ \delta(x) + \frac{1}{2\pi cx} \sqrt{(x - E_-)^+(E_+ - x)^+} dx$$

where $E_- = (1 - \sqrt{c})^2$, $E_+ = (1 + \sqrt{c})^2$ and $(x)^+ \equiv \max(x, 0)$. **Close match!**




Figure: Eigenvalue distribution of $\hat{\mathbf{C}}$ versus Marčenko-Pastur law, $p = 500$, $n = 50\,000$.

- » eigenvalues span on $[E_- = (1 - \sqrt{c})^2, E_+ = (1 + \sqrt{c})^2]$.
- » for $n = 100p$, on a range of $\pm 2\sqrt{c} = \pm 0.2$ around the **population** eigenvalue 1.

What about $n = 100p$? For $\mathbf{C} = \mathbf{I}_p$, as $n, p \rightarrow \infty$ with $p/n \rightarrow c \in (0, \infty)$: MP law

$$\mu(dx) = (1 - c^{-1})^+ \delta(x) + \frac{1}{2\pi cx} \sqrt{(x - E_-)^+(E_+ - x)^+} dx$$

where $E_- = (1 - \sqrt{c})^2$, $E_+ = (1 + \sqrt{c})^2$ and $(x)^+ \equiv \max(x, 0)$. **Close match!**




Figure: Eigenvalue distribution of $\hat{\mathbf{C}}$ versus Marčenko-Pastur law, $p = 500$, $n = 50\,000$.

» eigenvalues span on $[E_- = (1 - \sqrt{c})^2, E_+ = (1 + \sqrt{c})^2]$.

» for $n = 100p$, on a range of $\pm 2\sqrt{c} = \pm 0.2$ around the population eigenvalue 1.

What about $n = 100p$? For $\mathbf{C} = \mathbf{I}_p$, as $n, p \rightarrow \infty$ with $p/n \rightarrow c \in (0, \infty)$: MP law

$$\mu(dx) = (1 - c^{-1})^+ \delta(x) + \frac{1}{2\pi cx} \sqrt{(x - E_-)^+(E_+ - x)^+} dx$$

where $E_- = (1 - \sqrt{c})^2$, $E_+ = (1 + \sqrt{c})^2$ and $(x)^+ \equiv \max(x, 0)$. **Close match!**




Figure: Eigenvalue distribution of $\hat{\mathbf{C}}$ versus Marčenko-Pastur law, $p = 500$, $n = 50\,000$.

- » eigenvalues span on $[E_- = (1 - \sqrt{c})^2, E_+ = (1 + \sqrt{c})^2]$.
- » for $\mathbf{n} = 100\mathbf{p}$, on a range of $\pm 2\sqrt{c} = \pm 0.2$ around the **population** eigenvalue 1.

Classical large- n asymptotic analysis mostly fails today

- » large- n intuition, and many existing popular methods in biology, finance, signal processing, telecommunication, and machine learning, must **fail** even with $n = 100p$!
- » RMT as a flexible and powerful tool to **understand** and **recreate** these methods
- » in essence, “**increasing** complexity of the system models employed in above fields demand **low** complexity analysis”
- » in the remainder, how RMT can be applied to assess
 - o telecommunication: code division multiple access (CDMA) technology
 - o signal processing: generalized likelihood ratio test (GLRT)
 - o machine learning: principle component analysis (PCA), kernel spectral clustering

Classical large- n asymptotic analysis mostly fails today

- » large- n intuition, and many existing popular methods in biology, finance, signal processing, telecommunication, and machine learning, must **fail** even with $n = 100p$!
- » **RMT** as a flexible and powerful tool to **understand** and **recreate** these methods
- » in essence, “**increasing** complexity of the system models employed in above fields demand **low** complexity analysis”
- » in the remainder, how RMT can be applied to assess
 - o telecommunication: code division multiple access (CDMA) technology
 - o signal processing: generalized likelihood ratio test (GLRT)
 - o machine learning: principle component analysis (PCA), kernel spectral clustering

Classical large- n asymptotic analysis mostly fails today

- » large- n intuition, and many existing popular methods in biology, finance, signal processing, telecommunication, and machine learning, must **fail** even with $n = 100p$!
- » **RMT** as a flexible and powerful tool to **understand** and **recreate** these methods
- » in essence, “**increasing** complexity of the system models employed in above fields demand **low** complexity analysis”
- » in the remainder, how RMT can be applied to assess
 - o telecommunication: code division multiple access (CDMA) technology
 - o signal processing: generalized likelihood ratio test (GLRT)
 - o machine learning: principle component analysis (PCA), kernel spectral clustering

Classical large- n asymptotic analysis mostly fails today

- » large- n intuition, and many existing popular methods in biology, finance, signal processing, telecommunication, and machine learning, must **fail** even with $n = 100p$!
- » **RMT** as a flexible and powerful tool to **understand** and **recreate** these methods
- » in essence, “**increasing** complexity of the system models employed in above fields demand **low** complexity analysis”
- » in the remainder, how RMT can be applied to assess
 - telecommunication: code division multiple access (CDMA) technology
 - signal processing: generalized likelihood ratio test (GLRT)
 - machine learning: principle component analysis (PCA), kernel spectral clustering

Classical large- n asymptotic analysis mostly fails today

- » large- n intuition, and many existing popular methods in biology, finance, signal processing, telecommunication, and machine learning, must **fail** even with $n = 100p$!
- » **RMT** as a flexible and powerful tool to **understand** and **recreate** these methods
- » in essence, “**increasing** complexity of the system models employed in above fields demand **low** complexity analysis”
- » in the remainder, how RMT can be applied to assess
 - o **telecommunication**: code division multiple access (CDMA) technology
 - o **signal processing**: generalized likelihood ratio test (GLRT)
 - o **machine learning**: principle component analysis (PCA), kernel spectral clustering

Classical large- n asymptotic analysis mostly fails today

- » large- n intuition, and many existing popular methods in biology, finance, signal processing, telecommunication, and machine learning, must **fail** even with $n = 100p$!
- » **RMT** as a flexible and powerful tool to **understand** and **recreate** these methods
- » in essence, “**increasing** complexity of the system models employed in above fields demand **low** complexity analysis”
- » in the remainder, how RMT can be applied to assess
 - **telecommunication**: code division multiple access (CDMA) technology
 - **signal processing**: generalized likelihood ratio test (GLRT)
 - **machine learning**: principle component analysis (PCA), kernel spectral clustering

Classical large- n asymptotic analysis mostly fails today

- » large- n intuition, and many existing popular methods in biology, finance, signal processing, telecommunication, and machine learning, must **fail** even with $n = 100p$!
- » **RMT** as a flexible and powerful tool to **understand** and **recreate** these methods
- » in essence, “**increasing** complexity of the system models employed in above fields demand **low** complexity analysis”
- » in the remainder, how RMT can be applied to assess
 - **telecommunication**: code division multiple access (CDMA) technology
 - **signal processing**: generalized likelihood ratio test (GLRT)
 - **machine learning**: principle component analysis (PCA), kernel spectral clustering

Outline

Sample Covariance

RMT for Telecom

RMT for SP

RMT for ML

Application to telecom: performance analysis of CDMA via RMT

- » CDMA in 3G succeeded the TDMA tech in 2G, for which users are successively allocated an exclusive amount of **time** to exchange data with the APs
- » **major issue**: at the same time a very **strict** maximal number of users could be accepted by a given AP, *regardless* of the users' requests in terms of quality of service
- » **CDMA**: to increase the max number of users, and to dynamically balancing the quality of service offered to each terminal
 - o each user is allocated a (long) **spreading code** orthogonal to the other users' codes
 - o so that all users can simultaneously receive data while experiencing a limited amount of interference from concurrent communications, due to code orthogonality
 - o codes not fully orthogonal, more users served, **more interference** and then less **quality of service**; but at no time is a user rejected for lack of available resource
- » **Question**: how to evaluate the **capacity** (max achievable transmission data rate) of CDMA network? (which clearly depends on pre-coding strategy)

Application to telecom: performance analysis of CDMA via RMT

- » CDMA in 3G succeeded the TDMA tech in 2G, for which users are successively allocated an exclusive amount of **time** to exchange data with the APs
- » **major issue**: at the same time a very **strict** maximal number of users could be accepted by a given AP, *regardless* of the users' requests in terms of quality of service
- » **CDMA**: to increase the max number of users, and to dynamically balancing the quality of service offered to each terminal
 - o each user is allocated a (long) **spreading code** orthogonal to the other users' codes
 - o so that all users can simultaneously receive data while experiencing a limited amount of interference from concurrent communications, due to code orthogonality
 - o codes not fully orthogonal, more users served, more interference and then less quality of service; but at no time is a user rejected for lack of available resource
- » **Question**: how to evaluate the **capacity** (max achievable transmission data rate) of CDMA network? (which clearly depends on pre-coding strategy)

Application to telecom: performance analysis of CDMA via RMT

- » CDMA in 3G succeeded the TDMA tech in 2G, for which users are successively allocated an exclusive amount of **time** to exchange data with the APs
- » **major issue**: at the same time a very **strict** maximal number of users could be accepted by a given AP, *regardless* of the users' requests in terms of quality of service
- » **CDMA**: to increase the max number of users, and to dynamically balancing the quality of service offered to each terminal
 - o each user is allocated a (long) **spreading code** orthogonal to the other users' codes
 - o so that all users can simultaneously receive data while experiencing a limited amount of interference from concurrent communications, due to code orthogonality
 - o codes not fully orthogonal, more users served, **more interference** and then **less quality of service**; but at no time is a user rejected for lack of available resource
- » **Question**: how to evaluate the **capacity** (max achievable transmission data rate) of CDMA network? (which clearly depends on pre-coding strategy)

Application to telecom: performance analysis of CDMA via RMT

- » CDMA in 3G succeeded the TDMA tech in 2G, for which users are successively allocated an exclusive amount of **time** to exchange data with the APs
- » **major issue**: at the same time a very **strict** maximal number of users could be accepted by a given AP, *regardless* of the users' requests in terms of quality of service
- » **CDMA**: to increase the max number of users, and to dynamically balancing the quality of service offered to each terminal
 - o each user is allocated a (long) **spreading code** orthogonal to the other users' codes
 - o so that all users can simultaneously receive data while experiencing a limited amount of interference from concurrent communications, due to code orthogonality
 - o codes not fully orthogonal, more users served, **more interference** and then **less quality of service**; but at no time is a user rejected for lack of available resource
- » **Question**: how to evaluate the **capacity** (max achievable transmission data rate) of CDMA network? (which clearly depends on pre-coding strategy)

Application to telecom: performance analysis of CDMA via RMT

- » CDMA in 3G succeeded the TDMA tech in 2G, for which users are successively allocated an exclusive amount of **time** to exchange data with the APs
- » **major issue**: at the same time a very **strict** maximal number of users could be accepted by a given AP, *regardless* of the users' requests in terms of quality of service
- » **CDMA**: to increase the max number of users, and to dynamically balancing the quality of service offered to each terminal
 - o each user is allocated a (long) **spreading code** orthogonal to the other users' codes
 - o so that all users can simultaneously receive data while experiencing a limited amount of interference from concurrent communications, due to code orthogonality
 - o codes not fully orthogonal, more users served, **more interference** and then **less quality of service**; but at no time is a user rejected for lack of available resource
- » **Question**: how to evaluate the **capacity** (max achievable transmission data rate) of CDMA network? (which clearly depends on pre-coding strategy)

Application to telecom: performance analysis of CDMA via RMT

- » CDMA in 3G succeeded the TDMA tech in 2G, for which users are successively allocated an exclusive amount of **time** to exchange data with the APs
- » **major issue**: at the same time a very **strict** maximal number of users could be accepted by a given AP, *regardless* of the users' requests in terms of quality of service
- » **CDMA**: to increase the max number of users, and to dynamically balancing the quality of service offered to each terminal
 - o each user is allocated a (long) **spreading code** orthogonal to the other users' codes
 - o so that all users can simultaneously receive data while experiencing a limited amount of interference from concurrent communications, due to code orthogonality
 - o codes not fully orthogonal, more users served, **more interference** and then **less quality of service**; but at no time is a user rejected for lack of available resource
- » **Question**: how to evaluate the **capacity** (max achievable transmission data rate) of CDMA network? (which clearly depends on pre-coding strategy)

Application to telecom: performance analysis of CDMA via RMT

- » CDMA in 3G succeeded the TDMA tech in 2G, for which users are successively allocated an exclusive amount of **time** to exchange data with the APs
- » **major issue**: at the same time a very **strict** maximal number of users could be accepted by a given AP, *regardless* of the users' requests in terms of quality of service
- » **CDMA**: to increase the max number of users, and to dynamically balancing the quality of service offered to each terminal
 - o each user is allocated a (long) **spreading code** orthogonal to the other users' codes
 - o so that all users can simultaneously receive data while experiencing a limited amount of interference from concurrent communications, due to code orthogonality
 - o codes not fully orthogonal, more users served, **more interference** and then **less quality of service**; but at no time is a user rejected for lack of available resource
- » **Question**: how to evaluate the **capacity** (max achievable transmission data rate) of CDMA network? (which clearly depends on pre-coding strategy)

Orthogonal CDMA versus TDMA

For **orthogonal** CDMA, assume:

» frequency flat channel conditions for all users; and

» channel stability over a large number of successive symbol periods;

then the rates achieved in the up-link are **maximal** when the orthogonal codes are as long as the number of users n , with system capacity given by

$$C_{\text{orth}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{W} \mathbf{G} \mathbf{G}^H \mathbf{W}^H \right), \quad (1)$$

with noise power σ^2 , $\mathbf{W} \in \mathbb{C}^{n \times n}$ the **orthogonal** CDMA codes (\mathbf{W} **unitary**), and $\mathbf{G} \equiv \text{diag}\{g_i\}_{i=1}^n$ represents channel **gains** of the users. Note that

$$C_{\text{orth}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{G} \mathbf{G}^H \right) = \frac{1}{n} \sum_{i=1}^n \log \left(1 + \frac{|g_i|^2}{\sigma^2} \right) = C_{\text{TDMA}}(\sigma^2). \quad (2)$$

This justifies the **equivalence** between TDMA and **orthogonal** CDMA rate performance.

Orthogonal CDMA versus TDMA

For **orthogonal** CDMA, assume:

» frequency flat channel conditions for all users; and

» channel stability over a large number of successive symbol periods;

then the rates achieved in the up-link are **maximal** when the orthogonal codes are as long as the number of users n , with system capacity given by

$$C_{\text{orth}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{W} \mathbf{G} \mathbf{G}^H \mathbf{W}^H \right), \quad (1)$$

with noise power σ^2 , $\mathbf{W} \in \mathbb{C}^{n \times n}$ the **orthogonal** CDMA codes (\mathbf{W} **unitary**), and $\mathbf{G} \equiv \text{diag}\{g_i\}_{i=1}^n$ represents channel **gains** of the users. Note that

$$C_{\text{orth}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{G} \mathbf{G}^H \right) = \frac{1}{n} \sum_{i=1}^n \log \left(1 + \frac{|g_i|^2}{\sigma^2} \right) = C_{\text{TDMA}}(\sigma^2). \quad (2)$$

This justifies the **equivalence** between TDMA and **orthogonal** CDMA rate performance.

Orthogonal CDMA versus TDMA

For **orthogonal** CDMA, assume:

- » frequency flat channel conditions for all users; and
- » channel stability over a large number of successive symbol periods;

then the rates achieved in the up-link are **maximal** when the orthogonal codes are as long as the number of users n , with system capacity given by

$$C_{\text{orth}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{W} \mathbf{G} \mathbf{G}^H \mathbf{W}^H \right), \quad (1)$$

with noise power σ^2 , $\mathbf{W} \in \mathbb{C}^{n \times n}$ the **orthogonal** CDMA codes (\mathbf{W} **unitary**), and $\mathbf{G} \equiv \text{diag}\{g_i\}_{i=1}^n$ represents channel **gains** of the users. Note that

$$C_{\text{orth}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{G} \mathbf{G}^H \right) = \frac{1}{n} \sum_{i=1}^n \log \left(1 + \frac{|g_i|^2}{\sigma^2} \right) = C_{\text{TDMA}}(\sigma^2). \quad (2)$$

This justifies the **equivalence** between TDMA and **orthogonal** CDMA rate performance.

Orthogonal CDMA versus TDMA

For **orthogonal** CDMA, assume:

- » frequency flat channel conditions for all users; and
- » channel stability over a large number of successive symbol periods;

then the rates achieved in the up-link are **maximal** when the orthogonal codes are as long as the number of users n , with system capacity given by

$$C_{\text{orth}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{W} \mathbf{G} \mathbf{G}^H \mathbf{W}^H \right), \quad (1)$$

with noise power σ^2 , $\mathbf{W} \in \mathbb{C}^{n \times n}$ the **orthogonal** CDMA codes (**W unitary**), and $\mathbf{G} \equiv \text{diag}\{g_i\}_{i=1}^n$ represents channel **gains** of the users. Note that

$$C_{\text{orth}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{G} \mathbf{G}^H \right) = \frac{1}{n} \sum_{i=1}^n \log \left(1 + \frac{|g_i|^2}{\sigma^2} \right) = C_{\text{TDMA}}(\sigma^2). \quad (2)$$

This justifies the **equivalence** between TDMA and **orthogonal** CDMA rate performance.

Orthogonal CDMA versus TDMA

For **orthogonal** CDMA, assume:

- » frequency flat channel conditions for all users; and
- » channel stability over a large number of successive symbol periods;

then the rates achieved in the up-link are **maximal** when the orthogonal codes are as long as the number of users n , with system capacity given by

$$C_{\text{orth}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{W} \mathbf{G} \mathbf{G}^H \mathbf{W}^H \right), \quad (1)$$

with noise power σ^2 , $\mathbf{W} \in \mathbb{C}^{n \times n}$ the **orthogonal** CDMA codes (\mathbf{W} **unitary**), and $\mathbf{G} \equiv \text{diag}\{g_i\}_{i=1}^n$ represents channel **gains** of the users. Note that

$$C_{\text{orth}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{G} \mathbf{G}^H \right) = \frac{1}{n} \sum_{i=1}^n \log \left(1 + \frac{|g_i|^2}{\sigma^2} \right) = C_{\text{TDMA}}(\sigma^2). \quad (2)$$

This justifies the **equivalence** between TDMA and **orthogonal** CDMA rate performance.

Random versus orthogonal CDMA

When it comes to (pseudo-)random CDMA with (random i.i.d. codes), under the same conditions, we have

$$C_{\text{rand}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{X} \mathbf{G} \mathbf{G}^H \mathbf{X}^H \right), \quad (3)$$

for $\mathbf{X} \in \mathbb{C}^{n \times n}$ the users' random codes.

Question: C_{rand} as a function of gains \mathbf{G} and (distribution of) codes \mathbf{X} ?

- » (first?) answered by Shami, Tse, and Verdú in [5, 6];
- » however **capacity** expressions not realistically achievable in practice, due to complicated and **nonlinear** processing algorithms;
- » if only **linear** pre-coders and/or decoders are used, optimal solution:
 - Tse and Hanly in [4] for frequency flat channels;
 - Evans and Tse in [2] for frequency selective channels;
 - Li and Verdú [3] for reduced-rank LMMSE decoders, etc.

Random versus orthogonal CDMA

When it comes to (pseudo-)random CDMA with (random i.i.d. codes), under the same conditions, we have

$$C_{\text{rand}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{X} \mathbf{G} \mathbf{G}^H \mathbf{X}^H \right), \quad (3)$$

for $\mathbf{X} \in \mathbb{C}^{n \times n}$ the users' random codes.

Question: C_{rand} as a function of gains \mathbf{G} and (distribution of) codes \mathbf{X} ?

- » (first?) answered by Shami, Tse, and Verdú in [5, 6];
- » however **capacity** expressions not realistically achievable in practice, due to complicated and **nonlinear** processing algorithms;
- » if only **linear** pre-coders and/or decoders are used, optimal solution:
 - Tse and Hanly in [4] for frequency flat channels;
 - Evans and Tse in [2] for frequency selective channels;
 - Li and Verdú [3] for reduced-rank LMMSE decoders, etc.

Random versus orthogonal CDMA

When it comes to (pseudo-)random CDMA with (random i.i.d. codes), under the same conditions, we have

$$C_{\text{rand}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{X} \mathbf{G} \mathbf{G}^H \mathbf{X}^H \right), \quad (3)$$

for $\mathbf{X} \in \mathbb{C}^{n \times n}$ the users' random codes.

Question: C_{rand} as a function of gains \mathbf{G} and (distribution of) codes \mathbf{X} ?

- » (first?) answered by Shami, Tse, and Verdú in [5, 6];
- » however **capacity** expressions not realistically achievable in practice, due to complicated and **nonlinear** processing algorithms;
- » if only **linear** pre-coders and/or decoders are used, optimal solution:
 - Tse and Hanly in [4] for frequency flat channels;
 - Evans and Tse in [2] for frequency selective channels;
 - Li and Verdú [3] for reduced-rank LMMSE decoders, etc.

Random versus orthogonal CDMA

When it comes to (pseudo-)random CDMA with (random i.i.d. codes), under the same conditions, we have

$$C_{\text{rand}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{X} \mathbf{G} \mathbf{G}^H \mathbf{X}^H \right), \quad (3)$$

for $\mathbf{X} \in \mathbb{C}^{n \times n}$ the users' random codes.

Question: C_{rand} as a function of gains \mathbf{G} and (distribution of) codes \mathbf{X} ?

- » (first?) answered by Shami, Tse, and Verdú in [5, 6];
- » however **capacity** expressions not realistically achievable in practice, due to complicated and **nonlinear** processing algorithms;
- » if only **linear** pre-coders and/or decoders are used, optimal solution:
 - Tse and Hanly in [4] for frequency flat channels;
 - Evans and Tse in [2] for frequency selective channels;
 - Li and Verdú [3] for reduced-rank LMMSE decoders, etc.

Random versus orthogonal CDMA

When it comes to (pseudo-)random CDMA with (random i.i.d. codes), under the same conditions, we have

$$C_{\text{rand}}(\sigma^2) = \frac{1}{n} \log \det \left(\mathbf{I}_n + \frac{1}{\sigma^2} \mathbf{X} \mathbf{G} \mathbf{G}^H \mathbf{X}^H \right), \quad (3)$$

for $\mathbf{X} \in \mathbb{C}^{n \times n}$ the users' random codes.

Question: C_{rand} as a function of gains \mathbf{G} and (distribution of) codes \mathbf{X} ?

- » (first?) answered by Shami, Tse, and Verdú in [5, 6];
- » however **capacity** expressions not realistically achievable in practice, due to complicated and **nonlinear** processing algorithms;
- » if only **linear** pre-coders and/or decoders are used, optimal solution:
 - Tse and Hanly in [4] for frequency flat channels;
 - Evans and Tse in [2] for frequency selective channels;
 - Li and Verdú [3] for reduced-rank LMMSE decoders, etc.

Outline

Sample Covariance

RMT for Telecom

RMT for SP

RMT for ML

Signal sensing using multi-dimensional sensor arrays

Motivation:

- » Shannon made us realize that, to achieve high rate of information transfer, increasing the transmission bandwidth is **largely preferred** over increasing the power
- » high rate communications with finite power budget, need **frequency multiplexing**
- » **cognitive radio**: to communicate **not** by exploiting the over-used frequency domain, or by exploiting the over-used space domain, **but** by exploiting so-called **spectrum holes**, **jointly** in time, space, and frequency

As such, a cognitive radio network (also called a *secondary network*)

- » can help **reuse** the resources in a licensed (*first*) network
- » but require constant awareness of the operations taking place in the licensed networks
- » for example, via **signal sensing/detection**

Signal sensing using multi-dimensional sensor arrays

Motivation:

- » Shannon made us realize that, to achieve high rate of information transfer, increasing the transmission bandwidth is **largely preferred** over increasing the power
- » high rate communications with finite power budget, need **frequency multiplexing**
- » **cognitive radio**: to communicate **not** by exploiting the over-used frequency domain, or by exploiting the over-used space domain, **but** by exploiting so-called **spectrum holes**, **jointly** in time, space, and frequency

As such, a cognitive radio network (also called a *secondary network*)

- » can help **reuse** the resources in a licensed (*first*) network
- » but require constant awareness of the operations taking place in the licensed networks
- » for example, via **signal sensing/detection**

Signal sensing using multi-dimensional sensor arrays

Motivation:

- » Shannon made us realize that, to achieve high rate of information transfer, increasing the transmission bandwidth is **largely preferred** over increasing the power
- » high rate communications with finite power budget, need **frequency multiplexing**
- » **cognitive radio**: to communicate **not** by exploiting the over-used frequency domain, or by exploiting the over-used space domain, **but** by exploiting so-called **spectrum holes**, **jointly** in time, space, and frequency

As such, a cognitive radio network (also called a *secondary network*)

- » can help reuse the resources in a licensed (*first*) network
- » but require constant awareness of the operations taking place in the licensed networks
- » for example, via **signal sensing/detection**

Signal sensing using multi-dimensional sensor arrays

Motivation:

- » Shannon made us realize that, to achieve high rate of information transfer, increasing the transmission bandwidth is **largely preferred** over increasing the power
- » high rate communications with finite power budget, need **frequency multiplexing**
- » **cognitive radio**: to communicate **not** by exploiting the over-used frequency domain, or by exploiting the over-used space domain, **but** by exploiting so-called **spectrum holes**, **jointly** in time, space, and frequency

As such, a cognitive radio network (also called a *secondary network*)

- » can help **reuse** the resources in a licensed (*first*) network
- » but require constant **awareness** of the operations taking place in the licensed networks
- » for example, via **signal sensing/detection**

Signal sensing using multi-dimensional sensor arrays

Motivation:

- » Shannon made us realize that, to achieve high rate of information transfer, increasing the transmission bandwidth is **largely preferred** over increasing the power
- » high rate communications with finite power budget, need **frequency multiplexing**
- » **cognitive radio**: to communicate **not** by exploiting the over-used frequency domain, or by exploiting the over-used space domain, **but** by exploiting so-called **spectrum holes**, **jointly** in time, space, and frequency

As such, a cognitive radio network (also called a *secondary network*)

- » can help **reuse** the resources in a licensed (*first*) network
- » but require constant **awareness** of the operations taking place in the licensed networks
- » for example, via **signal sensing/detection**

Signal sensing using multi-dimensional sensor arrays

Motivation:

- » Shannon made us realize that, to achieve high rate of information transfer, increasing the transmission bandwidth is **largely preferred** over increasing the power
- » high rate communications with finite power budget, need **frequency multiplexing**
- » **cognitive radio**: to communicate **not** by exploiting the over-used frequency domain, or by exploiting the over-used space domain, **but** by exploiting so-called **spectrum holes**, **jointly** in time, space, and frequency

As such, a cognitive radio network (also called a *secondary network*)

- » can help **reuse** the resources in a licensed (*first*) network
- » but require constant **awareness** of the operations taking place in the licensed networks
- » for example, via **signal sensing/detection**

Signal sensing using multi-dimensional sensor arrays

Motivation:

- » Shannon made us realize that, to achieve high rate of information transfer, increasing the transmission bandwidth is **largely preferred** over increasing the power
- » high rate communications with finite power budget, need **frequency multiplexing**
- » **cognitive radio**: to communicate **not** by exploiting the over-used frequency domain, or by exploiting the over-used space domain, **but** by exploiting so-called **spectrum holes**, **jointly** in time, space, and frequency

As such, a cognitive radio network (also called a *secondary network*)

- » can help **reuse** the resources in a licensed (*first*) network
- » but require constant **awareness** of the operations taking place in the licensed networks
- » for example, via **signal sensing/detection**

Hypothesis testing in a signal-plus-noise model for cognitive radios

System model: let $\mathbf{X} = [\mathbf{x}_1, \dots, \mathbf{x}_n] \in \mathbb{R}^{p \times n}$ with i.i.d. columns $\mathbf{x}_i \in \mathbb{R}^p$ received by array of p sensors, signal decision as the following binary hypothesis test:

$$\mathbf{X} = \begin{cases} \sigma \mathbf{Z}, & \mathcal{H}_0 \\ \mathbf{a} \mathbf{s}^\top + \sigma \mathbf{Z}, & \mathcal{H}_1 \end{cases}$$

where $\mathbf{Z} = [\mathbf{z}_1, \dots, \mathbf{z}_n] \in \mathbb{R}^{p \times n}$, $\mathbf{z}_i \sim \mathcal{N}(\mathbf{0}, \mathbf{I}_p)$, $\mathbf{a} \in \mathbb{R}^p$ deterministic of unit norm $\|\mathbf{a}\| = 1$, signal $\mathbf{s} = [s_1, \dots, s_n]^\top \in \mathbb{R}^n$ with s_i i.i.d. random, and $\sigma > 0$. Denote $c = p/n > 0$.

- » observation of either zero-mean Gaussian **noise** $\sigma \mathbf{z}_i$ of power σ^2 , or deterministic **information** vector \mathbf{a} modulated by an added scalar (random) **signal** s_i (e.g., ± 1).
- » If \mathbf{a} , σ , and statistics of s_i are known, the decision-optimal Neyman-Pearson () test:

$$\frac{\mathbb{P}(\mathbf{X} \mid \mathcal{H}_1)}{\mathbb{P}(\mathbf{X} \mid \mathcal{H}_0)} \underset{\mathcal{H}_0}{\overset{\mathcal{H}_1}{\gtrless}} \alpha \quad (4)$$

for some $\alpha > 0$ controlling the Type I and II error rates.

Hypothesis testing in a signal-plus-noise model for cognitive radios

System model: let $\mathbf{X} = [\mathbf{x}_1, \dots, \mathbf{x}_n] \in \mathbb{R}^{p \times n}$ with i.i.d. columns $\mathbf{x}_i \in \mathbb{R}^p$ received by array of p sensors, signal decision as the following binary hypothesis test:

$$\mathbf{X} = \begin{cases} \sigma \mathbf{Z}, & \mathcal{H}_0 \\ \mathbf{a} \mathbf{s}^\top + \sigma \mathbf{Z}, & \mathcal{H}_1 \end{cases}$$

where $\mathbf{Z} = [\mathbf{z}_1, \dots, \mathbf{z}_n] \in \mathbb{R}^{p \times n}$, $\mathbf{z}_i \sim \mathcal{N}(\mathbf{0}, \mathbf{I}_p)$, $\mathbf{a} \in \mathbb{R}^p$ deterministic of unit norm $\|\mathbf{a}\| = 1$, signal $\mathbf{s} = [s_1, \dots, s_n]^\top \in \mathbb{R}^n$ with s_i i.i.d. random, and $\sigma > 0$. Denote $c = p/n > 0$.

- » observation of either zero-mean Gaussian **noise** $\sigma \mathbf{z}_i$ of power σ^2 , or deterministic **information** vector \mathbf{a} modulated by an added scalar (random) **signal** s_i (e.g., ± 1).
- » If \mathbf{a} , σ , and statistics of s_i are known, the decision-optimal Neyman-Pearson () test:

$$\frac{\mathbb{P}(\mathbf{X} \mid \mathcal{H}_1)}{\mathbb{P}(\mathbf{X} \mid \mathcal{H}_0)} \underset{\mathcal{H}_0}{\overset{\mathcal{H}_1}{\gtrless}} \alpha \quad (4)$$

for some $\alpha > 0$ controlling the Type I and II error rates.

Hypothesis testing in a signal-plus-noise model for cognitive radios

System model: let $\mathbf{X} = [\mathbf{x}_1, \dots, \mathbf{x}_n] \in \mathbb{R}^{p \times n}$ with i.i.d. columns $\mathbf{x}_i \in \mathbb{R}^p$ received by array of p sensors, signal decision as the following binary hypothesis test:

$$\mathbf{X} = \begin{cases} \sigma \mathbf{Z}, & \mathcal{H}_0 \\ \mathbf{a} \mathbf{s}^\top + \sigma \mathbf{Z}, & \mathcal{H}_1 \end{cases}$$

where $\mathbf{Z} = [\mathbf{z}_1, \dots, \mathbf{z}_n] \in \mathbb{R}^{p \times n}$, $\mathbf{z}_i \sim \mathcal{N}(\mathbf{0}, \mathbf{I}_p)$, $\mathbf{a} \in \mathbb{R}^p$ deterministic of unit norm $\|\mathbf{a}\| = 1$, signal $\mathbf{s} = [s_1, \dots, s_n]^\top \in \mathbb{R}^n$ with s_i i.i.d. random, and $\sigma > 0$. Denote $c = p/n > 0$.

- » observation of either zero-mean Gaussian **noise** $\sigma \mathbf{z}_i$ of power σ^2 , or deterministic **information** vector \mathbf{a} modulated by an added scalar (random) **signal** s_i (e.g., ± 1).
- » If \mathbf{a} , σ , and statistics of s_i are known, the decision-optimal Neyman-Pearson () test:

$$\frac{\mathbb{P}(\mathbf{X} | \mathcal{H}_1)}{\mathbb{P}(\mathbf{X} | \mathcal{H}_0)} \underset{\mathcal{H}_0}{\overset{\mathcal{H}_1}{\geq}} \alpha \quad (4)$$

for some $\alpha > 0$ controlling the Type I and II error rates.

Hypothesis testing via GLRT

However,

- » in practice, we do **not** know σ , nor the information vector $\mathbf{a} \in \mathbb{R}^p$ (to be recovered)
- » in the case of **a** fully unknown, one may resort to a **generalized likelihood ratio test** (GLRT) defined as

$$\frac{\sup_{\sigma, \mathbf{a}} \mathbb{P}(\mathbf{X} \mid \sigma, \mathbf{a}, \mathcal{H}_1)}{\sup_{\sigma, \mathbf{a}} \mathbb{P}(\mathbf{X} \mid \sigma, \mathcal{H}_0)} \underset{\mathcal{H}_0}{\underset{\mathcal{H}_1}{\gtrless}} \alpha.$$

- » Gaussian noise and signal s_i , GLRT has an explicit expression as a monotonous increasing function of $\|\mathbf{X}\mathbf{X}^\top\| / \text{tr}(\mathbf{X}\mathbf{X}^\top)$, test equivalent to, for some known f ,

$$T_p \equiv \frac{\|\mathbf{X}\mathbf{X}^\top\|}{\text{tr}(\mathbf{X}\mathbf{X}^\top)} \underset{\mathcal{H}_0}{\underset{\mathcal{H}_1}{\gtrless}} f(\alpha).$$

- » to evaluate the **power** of GLRT above, we need to assess the **max** and **mean** eigenvalues of SCM $\frac{1}{n}\mathbf{X}\mathbf{X}^\top$

Hypothesis testing via GLRT

However,

- » in practice, we do **not** know σ , nor the information vector $\mathbf{a} \in \mathbb{R}^p$ (to be recovered)
- » in the case of **a** fully unknown, one may resort to a **generalized likelihood ratio test** (GLRT) defined as

$$\frac{\sup_{\sigma, \mathbf{a}} \mathbb{P}(\mathbf{X} \mid \sigma, \mathbf{a}, \mathcal{H}_1)}{\sup_{\sigma, \mathbf{a}} \mathbb{P}(\mathbf{X} \mid \sigma, \mathcal{H}_0)} \underset{\mathcal{H}_0}{\overset{\mathcal{H}_1}{\geq}} \alpha.$$

- » Gaussian noise and signal s_i , GLRT has an explicit expression as a monotonous increasing function of $\|\mathbf{X}\mathbf{X}^\top\| / \text{tr}(\mathbf{X}\mathbf{X}^\top)$, test equivalent to, for some known f ,

$$T_p \equiv \frac{\|\mathbf{X}\mathbf{X}^\top\|}{\text{tr}(\mathbf{X}\mathbf{X}^\top)} \underset{\mathcal{H}_0}{\overset{\mathcal{H}_1}{\geq}} f(\alpha).$$

- » to evaluate the **power** of GLRT above, we need to assess the **max** and **mean** eigenvalues of SCM $\frac{1}{n}\mathbf{X}\mathbf{X}^\top$

Hypothesis testing via GLRT

However,

- » in practice, we do **not** know σ , nor the information vector $\mathbf{a} \in \mathbb{R}^p$ (to be recovered)
- » in the case of \mathbf{a} fully unknown, one may resort to a **generalized likelihood ratio test** (GLRT) defined as

$$\frac{\sup_{\sigma, \mathbf{a}} \mathbb{P}(\mathbf{X} \mid \sigma, \mathbf{a}, \mathcal{H}_1)}{\sup_{\sigma, \mathbf{a}} \mathbb{P}(\mathbf{X} \mid \sigma, \mathcal{H}_0)} \underset{\mathcal{H}_0}{\overset{\mathcal{H}_1}{\geq}} \alpha.$$

- » Gaussian noise and signal s_i , GLRT has an explicit expression as a monotonous increasing function of $\|\mathbf{X}\mathbf{X}^\top\| / \text{tr}(\mathbf{X}\mathbf{X}^\top)$, test equivalent to, for some known f ,

$$T_p \equiv \frac{\|\mathbf{X}\mathbf{X}^\top\|}{\text{tr}(\mathbf{X}\mathbf{X}^\top)} \underset{\mathcal{H}_0}{\overset{\mathcal{H}_1}{\geq}} f(\alpha).$$

- » to evaluate the **power** of GLRT above, we need to assess the **max** and **mean** eigenvalues of SCM $\frac{1}{n}\mathbf{X}\mathbf{X}^\top$

Hypothesis testing via GLRT

However,

- » in practice, we do **not** know σ , nor the information vector $\mathbf{a} \in \mathbb{R}^p$ (to be recovered)
- » in the case of \mathbf{a} fully unknown, one may resort to a **generalized likelihood ratio test** (GLRT) defined as

$$\frac{\sup_{\sigma, \mathbf{a}} \mathbb{P}(\mathbf{X} \mid \sigma, \mathbf{a}, \mathcal{H}_1)}{\sup_{\sigma, \mathbf{a}} \mathbb{P}(\mathbf{X} \mid \sigma, \mathcal{H}_0)} \underset{\mathcal{H}_0}{\overset{\mathcal{H}_1}{\geq}} \alpha.$$

- » Gaussian noise and signal s_i , GLRT has an explicit expression as a monotonous increasing function of $\|\mathbf{X}\mathbf{X}^\top\| / \text{tr}(\mathbf{X}\mathbf{X}^\top)$, test equivalent to, for some known f ,

$$T_p \equiv \frac{\|\mathbf{X}\mathbf{X}^\top\|}{\text{tr}(\mathbf{X}\mathbf{X}^\top)} \underset{\mathcal{H}_0}{\overset{\mathcal{H}_1}{\geq}} f(\alpha).$$

- » to evaluate the **power** of GLRT above, we need to assess the **max** and **mean** eigenvalues of SCM $\frac{1}{n}\mathbf{X}\mathbf{X}^\top$

Hypothesis testing via GLRT

However,

- » in practice, we do **not** know σ , nor the information vector $\mathbf{a} \in \mathbb{R}^p$ (to be recovered)
- » in the case of \mathbf{a} fully unknown, one may resort to a **generalized likelihood ratio test** (GLRT) defined as

$$\frac{\sup_{\sigma, \mathbf{a}} \mathbb{P}(\mathbf{X} \mid \sigma, \mathbf{a}, \mathcal{H}_1)}{\sup_{\sigma, \mathbf{a}} \mathbb{P}(\mathbf{X} \mid \sigma, \mathcal{H}_0)} \underset{\mathcal{H}_0}{\overset{\mathcal{H}_1}{\geq}} \alpha.$$

- » Gaussian noise and signal s_i , GLRT has an explicit expression as a monotonous increasing function of $\|\mathbf{X}\mathbf{X}^\top\| / \text{tr}(\mathbf{X}\mathbf{X}^\top)$, test equivalent to, for some known f ,

$$T_p \equiv \frac{\|\mathbf{X}\mathbf{X}^\top\|}{\text{tr}(\mathbf{X}\mathbf{X}^\top)} \underset{\mathcal{H}_0}{\overset{\mathcal{H}_1}{\geq}} f(\alpha).$$

- » to evaluate the **power** of GLRT above, we need to assess the **max** and **mean** eigenvalues of SCM $\frac{1}{n}\mathbf{X}\mathbf{X}^\top$

Hypothesis testing in a signal-plus-noise model via GLRT

To set a **maximum** false alarm rate (or Type I error) of $r > 0$ for **large** n, p , according to RMT, one must choose a threshold $f(\alpha)$ for T_p :

$$\mathbb{P}(T_p \geq f(\alpha)) = r \Leftrightarrow \mu_{\text{TW}_1}((-\infty, A_p]) = r, \quad A_p = (f(\alpha) - (1 + \sqrt{c})^2)(1 + \sqrt{c})^{-\frac{4}{3}} c^{\frac{1}{6}} n^{\frac{2}{3}} \quad (5)$$

with μ_{TW_1} the **Tracy-Widom distribution** in RMT.




Figure: Comparison between empirical false alarm rates and $\text{TW}_1(A_p)$ for A_p of the form in (5), as a function of the threshold $f(\alpha) \in [(1 + \sqrt{c})^2 - 5n^{-2/3}, (1 + \sqrt{c})^2 + 5n^{-2/3}]$, for $p = 256$, $n = 1\,024$ and $\sigma = 1$.

Outline

Sample Covariance

RMT for Telecom

RMT for SP

RMT for ML

“Curse of dimensionality”: loss of relevance of Euclidean distance

» Binary Gaussian mixture classification $\mathbf{x} \in \mathbb{R}^p$:

$$\mathcal{C}_1 : \mathbf{x} \sim \mathcal{N}(\boldsymbol{\mu}_1, \mathbf{C}_1), \text{ versus } \mathcal{C}_2 : \mathbf{x} \sim \mathcal{N}(\boldsymbol{\mu}_2, \mathbf{C}_2);$$

» Neyman-Pearson test: classification is possible **only** when^[a]

$$\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\| \geq C_\mu, \text{ or } \|\mathbf{C}_1 - \mathbf{C}_2\| \geq C_C \cdot p^{-1/2}$$

for some constants $C_\mu, C_C > 0$.

» In this **non-trivial** setting, for $\mathbf{x}_i \in \mathcal{C}_a, \mathbf{x}_j \in \mathcal{C}_b$:

$$\max_{1 \leq i \neq j \leq n} \left\{ \frac{1}{p} \|\mathbf{x}_i - \mathbf{x}_j\|^2 - \frac{2}{p} \text{tr } \mathbf{C}^\circ \right\} \xrightarrow{a.s.} 0$$

as $n, p \rightarrow \infty$ (i.e., $n \sim p$), for $\mathbf{C}^\circ \equiv \frac{1}{2}(\mathbf{C}_1 + \mathbf{C}_2)$, **regardless** of the classes $\mathcal{C}_a, \mathcal{C}_b$!

[a] Couillet, Liao and Mai “Classification asymptotics in the random matrix regime” (2018).

“Curse of dimensionality”: loss of relevance of Euclidean distance

» Binary Gaussian mixture classification $\mathbf{x} \in \mathbb{R}^p$:

$$\mathcal{C}_1 : \mathbf{x} \sim \mathcal{N}(\boldsymbol{\mu}_1, \mathbf{C}_1), \text{ versus } \mathcal{C}_2 : \mathbf{x} \sim \mathcal{N}(\boldsymbol{\mu}_2, \mathbf{C}_2);$$

» Neyman-Pearson test: classification is possible **only** when^[a]

$$\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\| \geq C_\mu, \text{ or } \|\mathbf{C}_1 - \mathbf{C}_2\| \geq C_C \cdot p^{-1/2}$$

for some constants $C_\mu, C_C > 0$.

» In this **non-trivial** setting, for $\mathbf{x}_i \in \mathcal{C}_a, \mathbf{x}_j \in \mathcal{C}_b$:

$$\max_{1 \leq i \neq j \leq n} \left\{ \frac{1}{p} \|\mathbf{x}_i - \mathbf{x}_j\|^2 - \frac{2}{p} \text{tr } \mathbf{C}^\circ \right\} \xrightarrow{a.s.} 0$$

as $n, p \rightarrow \infty$ (i.e., $n \sim p$), for $\mathbf{C}^\circ \equiv \frac{1}{2}(\mathbf{C}_1 + \mathbf{C}_2)$, **regardless** of the classes $\mathcal{C}_a, \mathcal{C}_b$!

[a] Couillet, Liao and Mai “Classification asymptotics in the random matrix regime” (2018).

“Curse of dimensionality”: loss of relevance of Euclidean distance

» Binary Gaussian mixture classification $\mathbf{x} \in \mathbb{R}^p$:

$$\mathcal{C}_1 : \mathbf{x} \sim \mathcal{N}(\boldsymbol{\mu}_1, \mathbf{C}_1), \text{ versus } \mathcal{C}_2 : \mathbf{x} \sim \mathcal{N}(\boldsymbol{\mu}_2, \mathbf{C}_2);$$

» Neyman-Pearson test: classification is possible **only** when^[a]

$$\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\| \geq C_\mu, \text{ or } \|\mathbf{C}_1 - \mathbf{C}_2\| \geq C_C \cdot p^{-1/2}$$

for some constants $C_\mu, C_C > 0$.

» In this **non-trivial** setting, for $\mathbf{x}_i \in \mathcal{C}_a, \mathbf{x}_j \in \mathcal{C}_b$:

$$\max_{1 \leq i \neq j \leq n} \left\{ \frac{1}{p} \|\mathbf{x}_i - \mathbf{x}_j\|^2 - \frac{2}{p} \text{tr} \mathbf{C}^\circ \right\} \xrightarrow{a.s.} 0$$

as $n, p \rightarrow \infty$ (i.e., $n \sim p$), for $\mathbf{C}^\circ \equiv \frac{1}{2}(\mathbf{C}_1 + \mathbf{C}_2)$, **regardless** of the classes $\mathcal{C}_a, \mathcal{C}_b$!

[a] Couillet, Liao and Mai “Classification asymptotics in the random matrix regime” (2018).

Loss of relevance of Euclidean distance: visual representation




Figure: Visual representation of classification in (**left**) small and (**right**) large dimensions.

⇒ Direct consequence to various **distance-based** machine learning methods (e.g., kernel spectral clustering)!

Loss of relevance of Euclidean distance: visual representation





Figure: Visual representation of classification in (**left**) small and (**right**) large dimensions.

⇒ Direct consequence to various **distance-based** machine learning methods (e.g., kernel spectral clustering)!


Reminder on kernel spectral clustering

Two-step classification of n data points with distance kernel $\mathbf{K} \equiv \{f(\|\mathbf{x}_i - \mathbf{x}_j\|^2/p)\}_{i,j=1}^n$:




0 isolated eigenvalues

↓ Top eigenvectors ↓



Reminder on kernel spectral clustering

Two-step classification of n data points with distance kernel $\mathbf{K} \equiv \{f(\|\mathbf{x}_i - \mathbf{x}_j\|^2/p)\}_{i,j=1}^n$:



0 isolated eigenvalues


⇓ **Top eigenvectors** ⇓



Reminder on kernel spectral clustering



⇓ *K*-dimensional representation ⇓




Eig. 2

Eig. 1



EM or k-means clustering

Reminder on kernel spectral clustering



⇓ **K-dimensional representation** ⇓





Fig. 1



EM or k-means clustering

Reminder on kernel spectral clustering



⇓ **K-dimensional representation** ⇓






Fig. 1





EM or k-means clustering



Cluster Gaussian data $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbf{R}^p$ into \mathcal{C}_1 or \mathcal{C}_2 , with second top eigenvectors \mathbf{v}_2 of heat kernel $\mathbf{K}_{ij} = \exp(-\|\mathbf{x}_i - \mathbf{x}_j\|^2/2p)$, small and large dimensional data.

(a) $p = 5, n = 500$ (b) $p = 250, n = 500$ 



Cluster Gaussian data $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbf{R}^p$ into \mathcal{C}_1 or \mathcal{C}_2 , with second top eigenvectors \mathbf{v}_2 of heat kernel $\mathbf{K}_{ij} = \exp(-\|\mathbf{x}_i - \mathbf{x}_j\|^2/2p)$, small and large dimensional data.

(a) $p = 5, n = 500$ (b) $p = 250, n = 500$ 




Cluster Gaussian data $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbf{R}^p$ into \mathcal{C}_1 or \mathcal{C}_2 , with second top eigenvectors \mathbf{v}_2 of heat kernel $\mathbf{K}_{ij} = \exp(-\|\mathbf{x}_i - \mathbf{x}_j\|^2/2p)$, small and large dimensional data.

(a) $p = 5, n = 500$ (b) $p = 250, n = 500$ 

Cluster Gaussian data $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbf{R}^p$ into \mathcal{C}_1 or \mathcal{C}_2 , with second top eigenvectors \mathbf{v}_2 of heat kernel $\mathbf{K}_{ij} = \exp(-\|\mathbf{x}_i - \mathbf{x}_j\|^2/2p)$, small and large dimensional data.



(a) $p = 5, n = 500$ (b) $p = 250, n = 500$ 

Cluster Gaussian data $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbf{R}^p$ into \mathcal{C}_1 or \mathcal{C}_2 , with second top eigenvectors \mathbf{v}_2 of heat kernel $\mathbf{K}_{ij} = \exp(-\|\mathbf{x}_i - \mathbf{x}_j\|^2/2p)$, small and large dimensional data.



(a) $p = 5, n = 500$ (b) $p = 250, n = 500$ 

Kernel matrices for large dimensional real-world data

(a) MNIST





(b) Fashion-MNIST





Kernel matrices for large dimensional real-world data

(a) MNIST



(b) Fashion-MNIST



A RMT viewpoint of large kernel matrices

- » “local” **linearization** of *nonlinear* kernel matrices in large dimensions, e.g., Gaussian kernel matrix $\mathbf{K}_{ij} = \exp(-\|\mathbf{x}_i - \mathbf{x}_j\|^2/2p)$ with $\mathbf{C}_1 = \mathbf{C}_2 = \mathbf{I}_p$ (e.g., $\mathcal{C}_1 : \mathbf{x}_i = \boldsymbol{\mu}_1 + \mathbf{z}_i$ versus $\mathcal{C}_2 : \mathbf{x}_j = \boldsymbol{\mu}_2 + \mathbf{z}_j$) so that

$$\|\mathbf{x}_i - \mathbf{x}_j\|^2/p \xrightarrow{a.s.} 2, \text{ and } \mathbf{K} = \exp\left(-\frac{2}{2}\right) \left(\mathbf{1}_n \mathbf{1}_n^\top + \frac{1}{p} \mathbf{Z}^\top \mathbf{Z}\right) + g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \frac{1}{p} \mathbf{j} \mathbf{j}^\top + * + o_{\|\cdot\|}(1)$$

with Gaussian $\mathbf{Z} = [\mathbf{z}_1, \dots, \mathbf{z}_n] \in \mathbb{R}^{p \times n}$ and class-information $\mathbf{j} = [\mathbf{1}_{n/2}; -\mathbf{1}_{n/2}]$,

- » **accumulated effect** of small “hidden” statistical information ($\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|$ in this case)

A RMT viewpoint of large kernel matrices

- » “local” **linearization** of *nonlinear* kernel matrices in large dimensions, e.g., Gaussian kernel matrix $\mathbf{K}_{ij} = \exp(-\|\mathbf{x}_i - \mathbf{x}_j\|^2/2p)$ with $\mathbf{C}_1 = \mathbf{C}_2 = \mathbf{I}_p$ (e.g., $\mathcal{C}_1 : \mathbf{x}_i = \boldsymbol{\mu}_1 + \mathbf{z}_i$ versus $\mathcal{C}_2 : \mathbf{x}_j = \boldsymbol{\mu}_2 + \mathbf{z}_j$) so that

$$\|\mathbf{x}_i - \mathbf{x}_j\|^2/p \xrightarrow{a.s.} 2, \text{ and } \mathbf{K} = \exp\left(-\frac{2}{2}\right) \left(\mathbf{1}_n \mathbf{1}_n^\top + \frac{1}{p} \mathbf{Z}^\top \mathbf{Z}\right) + g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \frac{1}{p} \mathbf{j} \mathbf{j}^\top + * + o_{\|\cdot\|}(1)$$

with Gaussian $\mathbf{Z} = [\mathbf{z}_1, \dots, \mathbf{z}_n] \in \mathbb{R}^{p \times n}$ and class-information $\mathbf{j} = [\mathbf{1}_{n/2}; -\mathbf{1}_{n/2}]$,

- » **accumulated effect** of small “hidden” statistical information ($\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|$ in this case)

A RMT viewpoint of large kernel matrices

Therefore

» entry-wise:

$$\mathbf{K}_{ij} = \exp(-1) \left(1 + \underbrace{\frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j}_{O(p^{-1/2})} \right) \pm \underbrace{\frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|)}_{O(p^{-1})} + *, \text{ so that } \frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \ll \frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j,$$

» spectrum-wise:

$$\begin{aligned} \circ & \|\mathbf{K} - \exp(-1) \mathbf{1}_n \mathbf{1}_n^\top\| \not\rightarrow 0; \\ \circ & \|\frac{1}{p} \mathbf{Z}^\top \mathbf{Z}\| = O(1) \text{ and } \|g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \frac{1}{p} \mathbf{j} \mathbf{j}^\top\| = O(1)! \end{aligned}$$

» **Same** phenomenon as the sample covariance example: $[\hat{\mathbf{C}} - \mathbf{C}]_{ij} \rightarrow 0 \not\Rightarrow \|\hat{\mathbf{C}} - \mathbf{C}\| \rightarrow 0!$

\Rightarrow With **RMT**, we **understand** kernel spectral clustering for large dimensional data!

A RMT viewpoint of large kernel matrices

Therefore

» entry-wise:

$$\mathbf{K}_{ij} = \exp(-1) \left(1 + \underbrace{\frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j}_{O(p^{-1/2})} \right) \pm \underbrace{\frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|)}_{O(p^{-1})} + *, \text{ so that } \frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \ll \frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j,$$

» spectrum-wise:

$$\circ \|\mathbf{K} - \exp(-1) \mathbf{1}_n \mathbf{1}_n^\top\| \not\rightarrow 0;$$

$$\circ \|\frac{1}{p} \mathbf{Z}^\top \mathbf{Z}\| = O(1) \text{ and } \|g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \frac{1}{p} \mathbf{j} \mathbf{j}^\top\| = O(1)!$$

» **Same** phenomenon as the sample covariance example: $[\hat{\mathbf{C}} - \mathbf{C}]_{ij} \rightarrow 0 \not\Rightarrow \|\hat{\mathbf{C}} - \mathbf{C}\| \rightarrow 0!$

\Rightarrow With **RMT**, we **understand** kernel spectral clustering for large dimensional data!

A RMT viewpoint of large kernel matrices

Therefore

» entry-wise:

$$\mathbf{K}_{ij} = \exp(-1) \left(1 + \underbrace{\frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j}_{O(p^{-1/2})} \right) \pm \underbrace{\frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|)}_{O(p^{-1})} + *, \text{ so that } \frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \ll \frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j,$$

» spectrum-wise:

- $\|\mathbf{K} - \exp(-1) \mathbf{1}_n \mathbf{1}_n^\top\| \not\rightarrow 0$;
- $\|\frac{1}{p} \mathbf{Z}^\top \mathbf{Z}\| = O(1)$ and $\|g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \frac{1}{p} \mathbf{j} \mathbf{j}^\top\| = O(1)!$

» **Same** phenomenon as the sample covariance example: $[\hat{\mathbf{C}} - \mathbf{C}]_{ij} \rightarrow 0 \not\Rightarrow \|\hat{\mathbf{C}} - \mathbf{C}\| \rightarrow 0!$

\Rightarrow With **RMT**, we **understand** kernel spectral clustering for large dimensional data!

A RMT viewpoint of large kernel matrices

Therefore

» entry-wise:

$$\mathbf{K}_{ij} = \exp(-1) \left(1 + \underbrace{\frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j}_{O(p^{-1/2})} \right) \pm \underbrace{\frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|)}_{O(p^{-1})} + *, \text{ so that } \frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \ll \frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j,$$

» spectrum-wise:

$$\circ \|\mathbf{K} - \exp(-1) \mathbf{1}_n \mathbf{1}_n^\top\| \not\rightarrow 0;$$

$$\circ \|\frac{1}{p} \mathbf{Z}^\top \mathbf{Z}\| = O(1) \text{ and } \|g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \frac{1}{p} \mathbf{j} \mathbf{j}^\top\| = O(1)!$$

» **Same** phenomenon as the sample covariance example: $[\hat{\mathbf{C}} - \mathbf{C}]_{ij} \rightarrow 0 \not\Rightarrow \|\hat{\mathbf{C}} - \mathbf{C}\| \rightarrow 0!$

\Rightarrow With **RMT**, we **understand** kernel spectral clustering for large dimensional data!

A RMT viewpoint of large kernel matrices

Therefore

» entry-wise:

$$\mathbf{K}_{ij} = \exp(-1) \left(1 + \underbrace{\frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j}_{O(p^{-1/2})} \right) \pm \underbrace{\frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|)}_{O(p^{-1})} + *, \text{ so that } \frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \ll \frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j,$$

» spectrum-wise:

- $\|\mathbf{K} - \exp(-1) \mathbf{1}_n \mathbf{1}_n^\top\| \not\rightarrow 0$;
- $\|\frac{1}{p} \mathbf{Z}^\top \mathbf{Z}\| = O(1)$ and $\|g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \frac{1}{p} \mathbf{j} \mathbf{j}^\top\| = O(1)!$

» **Same** phenomenon as the sample covariance example: $[\hat{\mathbf{C}} - \mathbf{C}]_{ij} \rightarrow 0 \not\Rightarrow \|\hat{\mathbf{C}} - \mathbf{C}\| \rightarrow 0!$

\Rightarrow With **RMT**, we **understand** kernel spectral clustering for large dimensional data!

A RMT viewpoint of large kernel matrices

Therefore

» entry-wise:

$$\mathbf{K}_{ij} = \exp(-1) \left(1 + \underbrace{\frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j}_{O(p^{-1/2})} \right) \pm \underbrace{\frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|)}_{O(p^{-1})} + *, \text{ so that } \frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \ll \frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j,$$

» spectrum-wise:

- $\|\mathbf{K} - \exp(-1) \mathbf{1}_n \mathbf{1}_n^\top\| \not\rightarrow 0$;
- $\|\frac{1}{p} \mathbf{Z}^\top \mathbf{Z}\| = O(1)$ and $\|g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \frac{1}{p} \mathbf{j} \mathbf{j}^\top\| = O(1)!$

» **Same** phenomenon as the sample covariance example: $[\hat{\mathbf{C}} - \mathbf{C}]_{ij} \rightarrow 0 \not\Rightarrow \|\hat{\mathbf{C}} - \mathbf{C}\| \rightarrow 0!$

\Rightarrow With RMT, we understand kernel spectral clustering for large dimensional data!

A RMT viewpoint of large kernel matrices

Therefore

» entry-wise:

$$\mathbf{K}_{ij} = \exp(-1) \left(1 + \underbrace{\frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j}_{O(p^{-1/2})} \right) \pm \underbrace{\frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|)}_{O(p^{-1})} + *, \text{ so that } \frac{1}{p} g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \ll \frac{1}{p} \mathbf{z}_i^\top \mathbf{z}_j,$$



» spectrum-wise:

- $\|\mathbf{K} - \exp(-1) \mathbf{1}_n \mathbf{1}_n^\top\| \not\rightarrow 0$;
- $\|\frac{1}{p} \mathbf{Z}^\top \mathbf{Z}\| = O(1)$ and $\|g(\|\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2\|) \frac{1}{p} \mathbf{j} \mathbf{j}^\top\| = O(1)!$



» **Same** phenomenon as the sample covariance example: $[\hat{\mathbf{C}} - \mathbf{C}]_{ij} \rightarrow 0 \not\Rightarrow \|\hat{\mathbf{C}} - \mathbf{C}\| \rightarrow 0!$

\Rightarrow With **RMT**, we **understand** kernel spectral clustering for large dimensional data!

Some more numerical results





(a) MNIST





(b) Fashion-MNIST

Some more numerical results



(a) MNIST



(b) Fashion-MNIST

Thank you! And some more information

- » Find more information in the monograph “**Random Matrix Methods for Machine Learning**” with Cambridge University Press
- » with online book draft <https://zhenyu-liao.github.io/pdf/RMT4ML.pdf>
- » with online code <https://github.com/Zhenyu-LIAO/RMT4ML!>
- » and exercise solution https://zhenyu-liao.github.io/pdf/RMT4ML_solution.pdf

Thank you! Q & A?

Thank you! And some more information

- » Find more information in the monograph “**Random Matrix Methods for Machine Learning**” with Cambridge University Press
- » with online book draft <https://zhenyu-liao.github.io/pdf/RMT4ML.pdf>
- » with online code <https://github.com/Zhenyu-LIAO/RMT4ML!>
- » and exercise solution https://zhenyu-liao.github.io/pdf/RMT4ML_solution.pdf

Thank you! Q & A?

Thank you! And some more information

- » Find more information in the monograph “**Random Matrix Methods for Machine Learning**” with Cambridge University Press
- » with online book draft <https://zhenyu-liao.github.io/pdf/RMT4ML.pdf>
- » with online code <https://github.com/Zhenyu-LIAO/RMT4ML!>
- » and exercise solution https://zhenyu-liao.github.io/pdf/RMT4ML_solution.pdf

Thank you! Q & A?

Thank you! And some more information

- » Find more information in the monograph “**Random Matrix Methods for Machine Learning**” with Cambridge University Press
- » with online book draft <https://zhenyu-liao.github.io/pdf/RMT4ML.pdf>
- » with online code <https://github.com/Zhenyu-LIAO/RMT4ML!>
- » and exercise solution https://zhenyu-liao.github.io/pdf/RMT4ML_solution.pdf

Thank you! Q & A?

Thank you! And some more information

- » Find more information in the monograph “**Random Matrix Methods for Machine Learning**” with Cambridge University Press
- » with online book draft <https://zhenyu-liao.github.io/pdf/RMT4ML.pdf>
- » with online code <https://github.com/Zhenyu-LIAO/RMT4ML!>
- » and exercise solution https://zhenyu-liao.github.io/pdf/RMT4ML_solution.pdf

Thank you! Q & A?

-
- [1] Romain Couillet, Zhenyu Liao and Xiaoyi Mai. “Classification asymptotics in the random matrix regime”. In: *2018 26th European Signal Processing Conference (EUSIPCO)*. IEEE. 2018, pp. 1875–1879.
- [2] J. Evans and D.N.C. Tse. “Large system performance of linear multiuser receivers in multipath fading channels”. In: *IEEE Transactions on Information Theory* 46.6 (2000), 2059–2078. DOI: [10.1109/18.868478](https://doi.org/10.1109/18.868478).
- [3] Linbo Li, Antonia M. Tulino and Sergio Verdú. “Design of Reduced-Rank MMSE Multiuser Detectors Using Random Matrix Methods”. In: *IEEE Transactions on Information Theory* 50.6 (2004), 986–1008. ISSN: 0018-9448. DOI: [10.1109/tit.2004.828076](https://doi.org/10.1109/tit.2004.828076).
- [4] D.N.C. Tse and S.V. Hanly. “Linear multiuser receivers: effective interference, effective bandwidth and user capacity”. In: *IEEE Transactions on Information Theory* 45.2 (1999), 641–657. ISSN: 0018-9448. DOI: [10.1109/18.749008](https://doi.org/10.1109/18.749008).
- [5] D.N.C. Tse and S. Verdú. “Optimum asymptotic multiuser efficiency of randomly spread CDMA”. In: *IEEE Transactions on Information Theory* 46.7 (2000), 2718–2722. DOI: [10.1109/18.887887](https://doi.org/10.1109/18.887887).