
Where the signal sits, and a dose-response

model output







Right: R0/R1 papers, centred within citation bin; Spearman rho = 0.27, $p < 0.001$. (Stage 10, 8,894 papers, §6.6)

Co-authors help, and partly replace the title

model output · all 9,108 papers · 95% CI (Stage 11 E3, §6.11)





later authors **+0.17 to +0.23** (Stage 11 E3, 4,621 target, §6.11)

title-specific part **shrinks**

target > control still

Stages 1–9 · 20–200 papers

What we saw

- A–B lives on continuation tokens (+0.021), not the first token (+0.001)(7.1, 20 pairs)
- Open question: is that teacher forcing, initials or surnames?

Stages 10–11 · 9,108 papers

What scale showed


- 73% of names start with an initial(24,739 / 33,780; §6.7), which carries little
- Full given names carry as much as surnames and help predict them (+0.22)(final L63; §6.7)
- Information travels title → name positions (L44–52), partly via tail tokens
- Earlier co-authors make later ones easier, title matters less

Line D: the puzzle from 7.1 is explained by name format

The pilot's "continuation" result was mostly a format effect: for "S. Bree" the surname is a continuation token. Stage 12 P1 (done) patched single positions: the name positions carry the signal (+0.85 at L52), the colon alone little (+0.17)(P1, 1,186 papers; P1_patch_pos.csv).

Keys and shelves

Is the book on the shelf, or is the key failing to get it out?



1 Is the book on the shelf? Yes

True title beats false titles (≈0.44 at L62(§6.9)); a probe on the title token reads paper-specific authors from L24 (re-checked)

Lines A, B · Stage 5, 7.3, 8D, 10, 11

2 Key = the title, read into the name positions at L44–52

Whole prompt: 0.82 at L48, ≈1.0 from L52; name positions alone 0.61 → 0.85; ':' alone ≤ 0.17(E1, P1; 1,186 papers); knockout after L52 costs almost nothing

Line C · Stage 11, 12 P1

3 Book there but stuck? Not supported

Target − control ≈ 0 at L24–L40, slightly negative at L48 (−0.04 to −0.05), grows only at L57–61 (+0.21 at output(§6.4)): retrieval itself is weak

Lines A, C · Stage 7.2, 10

4 Which shelf? Both, in order

Attention brings the title in at L48 (0.23); MLP takes over at L52–56 (0.18, 0.22)(P2, 1,186 papers). One-layer patching is a lower bound; whether the MLP step is memory lookup is not yet separable

Stage 12 P2

Caveat: a readout not finding it ≠ absent. Stage 13: ':' and name positions hold the task; the title position holds paper attributes and meaning beyond the words, not shown to be paper identity.

What the small samples taught us to watch for

- **Single-paper leverage**: one paper = 71% of the Stage 4 L56 mean (20 papers)
- **Tail-driven contrasts**: Stage 8 A–B disappears after removing 10 of 100 pairs (8D, matched_pair_differences.csv)
- **Forking paths**: L56 inspected repeatedly, then made primary
- **Candidate artefacts**: 100 false names share ~46 first tokens; 3% tie with gold (7.2 quality.json: 156/5,000)
- **Label noise**: strict "pass" 25.5% in the 0–2 citation bin (label_README.md)
- **Partial coverage**: first-listed author stands in for the team
- **Metric choice**: KL fidelity and author ranking disagree
- **Protocol drift**: plan locked 10-18 14:29 (7-layer integral primary); the 21:14 PROTOCOL switched to L56, both before 8C scoring; who and why open (U28)

Stage 10 answered each one by design: full cohort, every author and token, all layers reported, full-vocabulary ranks, within-bin comparison, frozen inputs with parity checks. What it cannot fix: groups still come from one labelling run of the same model.


Small vs large, in one table

Finding	Stages 1–9 (20–200 papers)	Stages 10–11 (9,108 papers)	Verdict
True title helps	+9.3 pp pilot, +5.2 pp new 200 (7.3; 8D RQ1)	≈0.44 title-specific at L62 (X3_means.csv)	confirmed
Recognised > not recognised	uncertain, tail-driven	+0.21 at output (§6.4), ≈0 at L24–L40, slightly negative at L48 (−0.04 to −0.05)	confirmed, late only
Same groups (A vs B, R0 only)	A − B as above	+0.20 at output (§6.13), ≈0 at L24–L40, slightly negative at L48; R1 adds strength, not timing	comparable, unchanged
Key layer	L56	starts L56, rises L57–61; read L24–50	refined
J-Lens over Vanilla	no increment	more name shape, no paper identity	consistent
First vs rest of name	gap on continuation	explained by initials vs given names	explained
Citations	low–high inconclusive	monotonic, ρ = 0.451 (X2_spearman.csv)	resolved
Lens stability	split-half one split; Stage 9 only Fit A	three Jacobian lenses fitted on different text agree; fit stability rests on Stage 9 Fit A only	only one piece of evidence (Stage 9 Fit A); Fit B not completed

Changing the question

Coifman, Bonanno, Rafaeli (2007)

1. three questions
2. M3: compare states
3. X1: copy into other title
4. score first author



R from	authors	year	field
L24	**0.99**	**0.98**	**0.99**
L40	**0.92**	**0.92**	**0.92**
L48	**0.42**	**0.41**	**0.42**


R(l) = (patched − other) ÷ (own − other)

title states copied at layer l; 582 test papers

R: Stage 13 X1, test set 582 papers; 381_stage13/reports/x1_report.md

Paraphrased title (X3)


same paper in other words vs other paper, same words







para 0.22



D 0.14

G′ = cos(orig, para) − cos(orig, D)

+0.32 at L8 · peak +0.46 at L36 (test set)


medians: 0.61 vs 0.15

first-author score, paraphrase − D: +0.239

Word overlap 0.22 / 0.14: config/x3_lexical_neighbour_j2.csv (this paper) · medians: x3_report.md (primary set, 1,110) · G′: x3_textbase_recovery.md (test)
+0.239: Stage 13 X3 behaviour, test, 552 papers; x3_textbase_recovery.md

Patchscope (X4)

Coifman, Bonanno, Rafaeli (2007)



D = score(own state) − score(partner state)

score = log10(1/rank) of the true answer tokens

first author from L8: +0.046

year from L40: +0.013

D: Stage 13 X4, test set, team CI; first author L8 +0.046 [0.035, 0.059], year L40 +0.013 [0.008, 0.018]; 381_stage13/reports/x4_report.md

Stage 12–13: what the middle layers hold


Paper facts are readable at the title early (M2) · H2 (paper identity) partly supported but not established; H3 (hidden author knowledge): insufficient evidence · X2 (2026-11-05): H2 not supported; H3 passes by rule but the author subspace can hardly decode authors (held-out $R^2 \leq 0.009$) → still insufficient

Hypothesis	M1: top word of the lens in middle layers	M2: probe reads non-name attributes	M3: change-of-task control	Current result (report v29, 2026-11-07)
H1 task / format: the middle layers represent "output an author list"	mostly "author", punctuation, common name starts; unrelated to the title	paper attributes not readable or very weak	the same title under different questions separates early in the middle layers	holds at ":" and name positions; at L4–L40, ":" moves 3–5× more when the question changes than when the paper changes (2.2× at L48, 1.3–1.5× at L56–L63)
H2 paper identity: the middle layers represent "which paper this is"	title-related words (copied from the title); change with a false title	field, year (inferred from the title), citations and recognition all readable, and earlier than the names	the same paper under different questions is close in the middle layers and separates by task only late **Result:** not above the L4 text level, not supported	**M3 does not support it; X3 shows a semantic representation beyond wording in the middle layers, but it cannot be separated from paper identity; H2 currently rests on M2 and X1, and M2's Qwen-over-BERT advantage is reference only (addendum 2).** Also, the earliest decodable order in X4 is first author (L8) before year (L40), opposite to the H2 prediction. **X2 does not support it.**
H3 author information already there, just not in vocabulary directions	not necessarily	the authors' first token readable by the probe, not by the lens	an author-trained probe transfers across tasks; an author-specific lens (M4) reads names in the middle layers	**Text baseline not weaker than Qwen, a text explanation cannot be excluded: insufficient evidence** (X4: on the given-name first token BERT +0.088 ≥ Qwen L8 +0.018; the L8 signal sits mainly on the surname, see X4); **X2 passes by rule, but the author subspace can hardly decode authors (held-out $R^2 \leq 0.009$; refit on all authors it moves 0.032, about 7% of full patching): still insufficient**

Hypotheses H1–H3 × readouts M1–M3 and current results (report v29, 2026-11-07)

Layer order (X5)

Earliest layer at which each kind of information appears · existing results only, each source keeps its own rule



Read early, carried, spoken late

≤L8–L16: title facts and the first-author token

L48–L52: the paper signal reaches the post-title tail (patching R ≥ 0.5 at L48, ≥ 0.95 at L52; knockout costs nothing from L52)

L53–L62: names readable by lens

Stage 12: where the paper information travels

All 408 GPU units done · true title → false_0 · share of the true–false gap recovered at the output

- **P1 one position at a time:** the colon carries at most 0.17 (L52)(Stage 12 P1, 1,186 papers, paper bootstrap; P1_patch_pos.csv); all name positions together 0.85 at L52(same; CI [0.830, 0.864]); the whole prompt 1.00 (= Stage 11 E1)(same, 0.996)
- **P2 one component of one layer:** attention at L48 +0.23 [0.22, 0.24](Stage 12 P2, 1,186 papers; P2_patch_comp.csv), MLP at L52–L56 +0.18 to +0.22(same) → attention reads the title in, MLP processes it next
- **N1 name plausibility:** without a title the true list looks "most real" in 0.255 of papers (chance 0.25) (Stage 12 N1, 8,894 R0/R1 papers; N1_prior_mc.csv); with the true title 0.625(same, CI [0.615, 0.635])
- **N2 pure name prior (no paper):** target − control +0.047 [0.031, 0.062] vs +0.247 with the true title(Stage 12 N2, final L63, 4,621 + 2,220, within bin; stage12_report.md) → pure name prior ≈ 19% of the gap (delete-title prior of §6.12: 0.35)
- **F2 lens fitted on author prompts:** target − control ≤ 0 at L24–L56, +0.238 only at L62(Stage 12 F2, name positions, Stage 11 sample, true − 5 false; F2_author_lens.csv)

No single "notebook" token

The paper leaves the title at L44–L48 and is spread over the name positions; a lens fitted on author prompts still reads nothing paper-specific in the middle layers.

The Stage 11 timing holds for all 5 false titles

X6: replacement with each of the 5 false titles · X7: knockout minus the same knockout on the false-title run (S = T − F)

- **X6 replacement:** mean over 5 false titles 0.821 at L48 and 0.995 at L52(Stage 13 X6, 1,186 papers, team-cluster CI; x6_recovery.csv); each false title within 0.02 of false_0(x6_report.md) → "≈80% at L48, all from L52" is not specific to false_0
- **By name-token role:** surname first token 0.734 at L48, surname continuation 0.893; all roles ≥ 0.96 at L52(X6 roles, all papers; x6x7_roles.md)
- **X7 knockout:** blocking the title on the false-title run RAISES the true author score (F < 0), so the paper-specific loss S(L0) ≈ 1.00(Stage 13 X7, 1,186 papers, all: 1.004; x7_report.md); S(L52) = 0.029 [0.021, 0.038](same, all papers)
- **Pre-registered verdict (false_0 only):** holds for target (S(L52) 0.018) and all papers; control just misses (0.051, threshold 0.05)(X7, target 593 / control 593; x7_report.md)
- **Added 2026-11-06, mean of 5 false titles:** target +0.022, control +0.042, all +0.028 — all ≤ 0.05, so the claim holds in every group; control's 0.051 was one false title's fluctuation(addendum 10 item 2; b1_x7f_report.md)

What changes

Nothing in the timing: the title is used up to about L52 and the paper information sits in the post-title positions by then (with five false titles all three groups pass).

Same title, different question

M3: probes across three questions (authors / year / field) · X1: patch A's title state from another question into B's author prompt

- **M3 transfer at the title:** $T \geq 0.92$ at L16–L40, but never above the L4 text level (Stage 13 M3, 9,108 papers, team folds; m3_report.md) (year $T - T(L4)$ −0.03 to −0.06) (same, CIs exclude 0) → M3 does not support H2
- **M3 at the colon:** $T < 0.5$ → the state is already organised by the question (H1) (same; summary_m3/m3_transfer.csv)
- **X1 replacement:** $R \approx 0.99$ (L24), 0.92 (L40), 0.42 (L48) whichever question the state came from (Stage 13 X1, test 582 pairs, team CI; x1_report.md); authors – year within ±0.02, except a small +0.019 at L48 (same, [0.012, 0.026])
- **Retrieval (added 2026-11-05):** no layer retrieves the paper across questions better than L4 (X5 retrieval, 9,108 papers; x5_retrieval.md; post-defence)

Reading

The title state hardly depends on the question, and the replacement effect is task-independent; but nothing goes beyond what the title text alone gives at L4.

Patchscope and paraphrases

X4: decode year / first author / field from the paper's own title state · X3: paraphrased title vs a word-matched other paper

- **X4 first author:** decodable from L8, D = +0.046 [0.035, 0.059](Stage 13 X4, test split, team CI; x4_report.md); year only from L40, +0.013 [0.008, 0.018](same); field never → order opposite to the H2 prediction
- **But:** the L8 signal sits on the surname (+0.066), where the text-baseline check failed(X4 role split, 1,178 papers; x4_rolesplit.csv) → may be explained by the title text
- **X3 paraphrase:** closer to the original than a word-matched paper beyond L4, peak L36 +0.16(Stage 13 X3, test 552 papers, G′ − G′(L4), team CI [0.146, 0.171]; x3_report.md); behaviour keeps ≈ 90% of the first-author preference(same, 0.90 [0.86, 0.94])
- **Post-hoc checks:** a sentence-embedding model without author knowledge shows a comparable advantage, and target = control(X3 text baselines and group split; x3_textbase_recovery.md, x3_groupsplit.md) → meaning, not separable from paper identity

H2 / H3 so far

H2 partly supported but not established (rests on M2 and X1); H3: insufficient evidence (text baseline not weaker than Qwen).

X2: swap only a subspace

Patch only the paper-attribute (S_id, 9-dim) or the author (S_auth, 10-dim) component of A's title states into B · test 582 pairs · team-cluster 95% CI

- **Carry:** S_id at L40 moves +0.005 of the gap (random +0.003, full replacement +0.920); S_auth at L48 moves +0.018 (random +0.003, full +0.428)(Stage 13 X2, test 582 pairs; x2_report.md Verdict)
- **Pre-registered verdict:** H2 not supported (R_id 0.005 < 0.5 × R_full 0.460); H3 passes (R_auth − R_id +0.014 [+0.008, +0.020])(same, L40 / L48)
- **But:** the author subspace hardly decodes authors (held-out $R^2 \leq 0.003$; first-author token hit rate 0.078–0.079, below the constant baseline 0.080) and moves only about 4% of the full replacement(subspace fits on 5,041 training papers, 5 team folds; x2_report.md)
- **Remove arm:** setting either component to the mean costs no more than a random subspace (+0.001)(test, L_S − L_rand; same)

Reading

H3 passes by the pre-registered rule and H2 is not supported, but the author subspace cannot decode authors, so this is no strong evidence for H3. The information carried from the title to the names lies almost entirely outside both subspaces.

The probe on every name token

Title-position probe extended to all name tokens and split by role · L40 · true − false_0 · 1,395–1,754 target + control papers · team-cluster 95% CI

- **Surname first token:** +0.071 [0.058, 0.085], above the initial +0.044 [0.030, 0.057]; difference +0.028 [0.011, 0.045] → both pre-registered checks pass (addendum 9; e4b_alltok.md §5)
- **Given name first token strongest:** L40 +0.124, L56 +0.163 (1,706 papers; same)
- **So E4b underestimated it:** E4b scored only each author's first token, mostly an initial
- **Permutation controls:** ≈ 0 on surname and given-name tokens; ≈ +0.02 on initials → about half of the initial's signal is not paper-specific (e4b_alltok.md §7)
- **Target − control, three versions:** pre-registered (false_0; 1,706 / 1,395 papers): given name + at L24–L48, surname n.s. (L40 +0.012 [−0.026, +0.048]); per-donor (post hoc, D1; 4,654 papers): surname + from L24 (L40 +0.030 [0.013, 0.048]); 5-title mean (leaky, sensitivity only): surname L40 +0.024 [−0.006, +0.052] → given name consistent, surname evidence weak (post hoc only) (within bin; perdonor_by_run_layer.csv V0 / Vpd / V5x0)

Per-donor exclusion (batch 1)

Per-donor exclusion, 4,654 papers: surname L40 +0.076, surname − initial +0.033. Without the title-reuse exclusion (C-3, C-3b) the signals are unchanged but include leakage: sensitivity only. (b1_e4b5_report.md; c13_C3b.md)

What we learned: read early, spoken late

Read early	Causally the title is read in L24–L50 and gathered at the name positions by L52, then no longer needed. A probe at the title token reads a little of it from L24 (re-checked).
Spoken late	At the name positions, paper-specific author knowledge becomes lens-readable only from ~L50, fastest over L57–L61.
No lens lead	Read with a lens at the names, target is not ahead of control in middle layers; the +0.21 gap is at the end (Stage 10, final L63, §6.4) (probe at the title: target − control +0.03–0.08, re-checked (Stage 13 E4b, first name token only)).
Real knowledge	Name prior is ~1/3 of the gap overall but ~0 on surnames (Stage 12 A, 0.087 / 0.247, §6.12); the rest is paper-specific and grows with citations.
Lenses agree	Jacobian lenses read more in middle layers, but nothing target-specific.
Name format	Initials carry little; full given names carry as much as surnames and help predict them.

Limits

Done: Stage 12

- Single-position patching (P1); attention vs MLP (P2, hook check passed)
- Name priors (N1, N2); author-prompt lens (F1, F2): middle layers still not readable

Done: Stage 13

- Probes read year, citations, field at the title from ≤L16 (M2); identity not above the L4 text level (M3)
- Replacement is task-independent (X1); paraphrase meaning beyond wording in L28–L40, not separable from paper identity (X3)
- First author decodable at L8, may be text-explainable (X4); 5 false titles confirm the Stage 11 timing (X6, X7)

Limits

- One model (Qwen3-32B)
- Teacher-forced preference, not generation
- Labels from the team lead's package; labelling code (elm) not available
- H2 (paper identity) partly supported but not established; H3 (hidden author knowledge): insufficient evidence

Added after the defence (2026-11-05)

Group comparisons (plan fixed before the results: addenda 7, 8) · CPU leftovers (post-hoc) · experiments still running


1. Group comparisons A / B / C / D: three findings, intervention re-runs (E1 and P1 / P2 numerator / denominator), recognition
2. CPU leftovers on existing data: X5 retrieval curve, M3 scores, N2 by layer, paper vs team intervals, M5
3. Redo programme (addenda 10–14): done, batch 1 (only P1 / P2 with five false titles still running), batches 2 and 3; limits that cannot be redone

Added after the defence · groups

Group comparisons: three findings

Plan fixed before the results (addenda 7, 8) · unwritten authors only · output (L63) title-specific signal · within citation bin · team-bootstrap 95% CI · Holm over 4 tests

- **1 Recognition:** with no author written (R0), recognised papers (A) beat unrecognised ones (B) by **+0.200 [0.188, 0.213]**(P1 A − B, 3,417 / 2,148 papers, Holm p ≤ 0.002; primary.csv); with confounders +0.173 [0.161, 0.186](paper level, 5,565), author level + position +0.151 [0.139, 0.163](19,893 authors)
- **2 Graded:** each extra multiple-choice order right adds **+0.059 [0.056, 0.063]**(P3, 8,288 R0 papers, bin FE; Holm p ≤ 0.002) (confounders +0.046 [0.042, 0.049](author level)); ≈ 0.17 with none right, ≈ 0.46 with all four(R0, 927 / 4,105 papers; stage10_curves.csv)
- **3 Partial recall helps little (≈ ⅓ of recognition), output only:** C − A co-authors **+0.061 [0.034, 0.090]**(P2-other, 390 / 2,826 papers, Holm p ≤ 0.002), first author +0.031 [−0.006, 0.069], n.s.(P2-first, 292 / 3,199); ≈ 0 at L48–L62 with the logit lens, −0.07 to −0.11 at L48–L59 with the public J-lens(stage10_contrasts.csv, unwritten_other). The earlier ≈ +0.11 used all authors (circular)(r0_r1_analysis.md §2)
- **Reference only:** R2 written authors +0.844(200 papers; summary_table.md); only 28 R2 papers have unwritten authors(same)



Primary contrasts (blue) and regression versions; team-bootstrap 95% CI (391_groups/figures/fig3)

Added after the defence · re-runs

Re-runs: numerator and denominator

Addendum 8 · E1 recovery R = mean(patched − false) ÷ mean(true − false) · unwritten authors · team-cluster 95% CI

group (unwritten authors)	papers	denominator: true − false	E1 numerator L48	E1 R(L48)	E1 R(L52)
A R0 × recognised	557	+0.407 [0.386, 0.430]	+0.330	+0.811 [0.790, 0.832]	+0.988 [0.980, 0.996]
B R0 × not recognised	586	+0.214 [0.196, 0.234]	+0.186	+0.869 [0.835, 0.906]	+1.016 [1.002, 1.031]
U0 R0 × uncertain	599	+0.293 [0.271, 0.316]	+0.248	+0.844 [0.814, 0.877]	+1.000 [0.988, 1.012]
C R1 × recognised (descriptive)	32	+0.464 [0.388, 0.538]	+0.335	+0.721 [0.650, 0.806]	+0.996 [0.968, 1.026]
R2 written authors (reference)	200	+0.845 [0.798, 0.897]	+0.566	+0.670 [0.630, 0.707]	+0.948 [0.927, 0.965]


B's higher ratio is a small-denominator effect: numerator B − A −0.010, −0.040, −0.144, −0.184 at L24 / L40 / L48 / L52, all CIs below 0(e1_e2_num_den_B_minus_A.csv) — B carries no more absolute paper-specific signal than A at any layer.

U0 timing as A and B (descriptive); R2 upper reference only; C 32 / D 5 / R2-unwritten 28 papers → descriptive(rerun_report.md Counts)

Added after the defence · groups

Recognition changes the size, not the timing

Unwritten authors, output (L63) signal, plain means with team-bootstrap 95% CI; n < 30 descriptive



Left: multiple-choice orders right (0–4); right: mean probability of the true option. Blue R0, green R1 (391_groups/figures/fig2)

Re-runs: over 0–4 orders right the denominator rises 0.185 → 0.407, while E1 R(L48) stays flat, 0.90 → 0.81 (R0 papers A + U0 + B, 241 / 557 papers at 0 / 4; rerun_report.md "Continuous recognition")

Added after the defence · re-runs

P1 / P2: the same small-denominator effect

Stage 12 single positions (P1) and attention / MLP (P2) split by group · unwritten authors · paired team bootstrap 95% CI

patched part	layer	numerator B − A	ratio B − A	numerator B/A
P1 all name positions	L48	−0.105 [−0.123, −0.087]	+0.052 [+0.011, +0.098]	0.57
P1 all name positions	L56	−0.183 [−0.209, −0.157]	−0.050 [−0.087, −0.012]	0.50
P2 attention	L48	−0.029 [−0.038, −0.021]	+0.057 [+0.030, +0.086]	0.66
P2 MLP	L56	−0.041 [−0.053, −0.029]	+0.008 [−0.030, +0.044]	0.54
P1 ':' only	L48	−0.000 [−0.007, +0.005]	+0.050 [+0.026, +0.071]	0.99
P1 ':' only	L52	−0.013 [−0.024, −0.002]	+0.073 [+0.038, +0.106]	0.79

B's higher P1 / P2 ratios also come from the small denominator: B's numerator is below A's at the name positions, in attention and in the MLP; at the ':' token the numerators are similar in L44–L48 (B/A 0.78–0.99), and B's ratio is higher only because its denominator is about half of A's(A 557 / B 586 papers; denominator B − A −0.192, B/A 0.53; p1_p2_num_den_B_minus_A.csv; e1_num_den.md P1/P2)

Added after the defence · CPU

CPU leftovers on existing data (post-hoc)

No new GPU runs · descriptive only · not in the pre-registration except the X5 retrieval curve

- **X5 retrieval curve (pre-registered, computed now):** top-1 retrieval of the same paper across questions is never above L4 (M3 cache, 9,108 papers; x5_retrieval.md) (title token 1.000 up to L44, 0.734 at the output) (same, team CI)
- **M3 behaviour scores:** year target − control +0.007 [0.003, 0.012]; first-author first token +0.147 [0.096, 0.191] (output, 4,621 / 2,220, within bin, team CI; m3_scores.md)
- **N2 by layer:** pure name prior target − control +0.047 at the output, +0.039 at logit L62; public J-lens L48 −0.133 (true title) (Stage 12 N2 rescored by layer; n2_layers.md) → only L62 reproduces the output pattern
- **Paper vs team intervals:** width ratio 0.97–1.00 (median); "excludes 0" changes in 2 of 1,155 rows (X1, X4, X6, X7, M3; v42_paper_vs_team.md)
- **M5 true vs false title at the name positions:** output 0.919; logit L24 0.516 → L62 0.899 (share of pairs, all papers × 5 false titles, team CI; m5_report.md); probe at title / colon AUROC 0.50–0.52 (same, Part B)

Added after the defence · redo programme

Redo programme (addenda 10–14)

All rules fixed before the results · reproducing the published numbers is a hard check for every item · status 2026-11-06 evening

- **Done:** X7 with five false titles; all-token probe (addendum 9); CPU items C-1 to C-5; C-3b (no-exclusion sensitivity, includes leakage, not a conclusion)
- **Batch 1, done:** X1–X4 for all authors → conclusions unchanged (X1 task-independent, small L48 author – year +0.024; X3 keeps ≈ 90%; X4 from L8; X2 moves 0.032, subspace $R^2 \leq 0.009$, H3 still insufficient)(b1_xall_report.md) · E4b, per-donor exclusion (4,654 papers, ~1.5 false titles each): surname L40 +0.076 [0.068, 0.083], surname – initial +0.033(b1_e4b5_report.md)
- **Batch 1, running:** P1 / P2 with five false titles — 187 / 194 units done, result pending; result after approval
- **Batch 2 (addenda 11, 12):** code, tiny tests and hard-check unit tests done; starts automatically after batch 1; deviations recorded (D12-1 to D12-3; 2-7 source = year-free X4 prompt)(prereg_addendum12_deviations.json)
- **Batch 3 (addendum 14):** 3-1 Stage 10 L41–L47, L49 · 3-2 L0–L23: code ready, after batch 2 · 3-3 Stage 7.1B fast path: stopped (deviation D14-1; equivalence with the old per-prefix results not confirmed); 3-4 / 3-5 (Stage 8 GPU W) not run(prereg_addendum14.json)
- **Not done:** Stage 8 GPU re-run of the original W (user decision 2026-11-06; CPU proxy C-2 instead)(c13_C2.md)

Added after the defence · limits

Limits that cannot be redone

Written 2026-11-06

- **One model:** the groups (recognised or not, authors written or not) come from Qwen3-32B's own labels; another model would need new labels
- **Teacher forcing:** every score is the rank the model gives the correct name once it is in the prompt — a preference, not generation
- **Label pipeline:** the label package author's elm code and run.json are not on the cluster, so generation length, thinking mode and the multiple-choice setup cannot be re-checked
- **High-citation bins:** the 4097+ bin has no B / D papers(84 target, 0 control; m3_scores.md §2), so within-bin comparisons cannot use it