



Residual Multi-Task Learner for Applied Ranking

Based on joint work with Cong Fu et al. Deployed in Shopee Search.

Zhiming Zhou

|

SUFE

|

2024/12/07



Contents

01 Problem

02 Existing Methods

03 ResFlow

04 Online Deployment




01

Problem



Applied Ranking

Predicting which items users will be more interested in,



(e.g., search, recommendation)

based on user and item features and their interactions.

				
John 	5	1	3	5
Tom 	?	?	?	2
Alice 	4	?	3	?

Multi-Task in Applied Ranking

When ranking items,

we may **estimate**

the click-through rate (CTR)

the add-to-cart rate (ATCR)

the final conversion rate (CTCVR)


Multi-Task

(same input, different but related outputs)

of a user w.r.t. items,

and jointly consider all these predictions.

Attribute 0 : Sparse Data



latter task, e.g., CTCVR estimation, has significantly sparser data → multi-task learning


Attribute 1 : Large Scale & Real-Time

Practical application scenario:

- ❑ enormous items
- ❑ need to response in a second

Ranking algorithm **esquires high efficiency.**

Attribute 2 : Sequential Dependency




The slide features a large orange circle on the left containing the number '02'. To its right is a blue rounded rectangle containing the text 'Existing Methods'. The background is white with several abstract shapes: a small orange blob at the top left, a small light blue blob at the top right, and a small blue blob at the bottom center.

02


Existing Methods

The Shared Bottom Class



indirect information transfer → inferior performance

Adaptive Information Transfer




Transferring the last layer feature:

- via an attention-based module

❑ Computationally inefficient

❑ Inadequate information transfer

Entire Space Multitask Model (ESMM)



Transferring the output probability:

- multiplicatively
- modeling the conditional probability

□ Light-weight

□ Inadequate information transfer




03

ResFlow



Residual Multi-Task Learner (ResFlow)



Transferring all features and the final logit

- additively
- via cross-task residual connection

□ light weight

□ sufficient & effective information transfer

Results

Table 4: The AUC results of the CTCVR estimation task on offline e-commerce datasets. The best results are presented in bold font, while the second bests are marked with underlines. ResFlow consistently achieves the best.

Dataset	NSE	PLE	AITM	ESMM	ESCM ² -IPW	ESCM ² -DR	DCMT	ResFlow (ours)
S0	0.619±0.001	0.630±0.005	0.636 ± 0.002	0.632 ± 0.001	0.624 ± 0.007	0.622±0.006	<u>0.640 ± 0.001</u>	0.656 ± 0.001
S1	0.621±0.002	0.624±0.003	0.623 ± 0.001	0.623 ± 0.003	0.624 ± 0.002	0.623±0.003	<u>0.632 ± 0.002</u>	0.647 ± 0.002
S0&S1	0.623±0.002	0.635±0.001	0.637 ± 0.001	0.637 ± 0.003	0.623 ± 0.005	0.623±0.001	<u>0.634 ± 0.002</u>	0.661 ± 0.001
AliCCP	0.624±0.002	0.640±0.002	<u>0.644 ± 0.001</u>	0.641 ± 0.003	0.625 ± 0.005	0.627±0.003	0.643 ± 0.002	0.664 ± 0.002
AE-ES	0.861±0.002	0.873±0.002	0.876 ± 0.001	0.867 ± 0.003	0.868 ± 0.003	0.871±0.002	<u>0.886 ± 0.003</u>	0.893 ± 0.001
AE-FR	0.842±0.002	0.852±0.002	0.856 ± 0.002	0.851 ± 0.001	0.873 ± 0.007	0.870±0.005	<u>0.874 ± 0.003</u>	0.885 ± 0.001
AE-NL	0.831±0.003	0.844±0.002	0.843 ± 0.001	0.840 ± 0.002	0.854 ± 0.006	0.854±0.004	<u>0.858 ± 0.001</u>	0.864 ± 0.001
AE-US	0.826±0.001	0.851±0.003	0.843 ± 0.002	0.827 ± 0.002	0.843 ± 0.006	0.841±0.003	<u>0.863 ± 0.003</u>	0.872 ± 0.001
AE-RU	0.870±0.003	0.886±0.001	0.882 ± 0.002	0.878 ± 0.002	0.882 ± 0.006	0.880±0.006	<u>0.887 ± 0.001</u>	0.913 ± 0.002
Shopee-2	0.865±0.001	0.860±0.003	0.855 ± 0.006	<u>0.882 ± 0.001</u>	0.840 ± 0.012	0.812±0.041	0.867 ± 0.001	0.902 ± 0.001
Shopee-3	0.877±0.002	0.877±0.003	0.871 ± 0.003	<u>0.893 ± 0.001</u>	/	/	/	0.910 ± 0.002

Ablations

Table 5: Ablation results of ResFlow in terms of CTCVR AUC.

Model	AE-RU	Shopee-2
NSE	0.869 ± 0.003	0.865 ± 0.001
NSE + Feature Residual (FR)	0.897 ± 0.001	0.891 ± 0.001
NSE + FR (H1-only)	0.880 ± 0.002	0.868 ± 0.002
NSE + FR (H2-only)	0.898 ± 0.002	0.887 ± 0.001
NSE + Logit Residual (LR)	0.907 ± 0.002	0.896 ± 0.001
ResFlow (NSE + FR + LR)	0.913 ± 0.002	0.902 ± 0.001
ESMM	0.878 ± 0.002	0.882 ± 0.001
ESMM + FR	0.899 ± 0.004	0.891 ± 0.002
ESMM + FR + LR	0.896 ± 0.006	0.888 ± 0.001

✓ FR (H1-only) < FR (H2-only) < LR

- higher-level abstraction is more critical

✓ ESMM < ESMM + FR < LR

- additive is better than multiplicative

✓ FR (H2-only) < FR (i.e., H1 + H2) < FR + LR

- residual link in every layer benefits

Extension

Table 6: Performance on KuaiRand-Pure-S1 in terms of AUC. The bests are in bold font. The second bests are underlined.

Target	is_follow	is_forward	is_comment
NSE	0.821 ± 0.005	0.750 ± 0.011	0.779 ± 0.003
AITM	0.785 ± 0.014	<u>0.764 ± 0.012</u>	0.782 ± 0.005
ESMM	<u>0.822 ± 0.007</u>	0.757 ± 0.007	0.782 ± 0.004
ESCM ² -IPW	0.817 ± 0.010	0.754 ± 0.008	0.773 ± 0.004
ESCM ² -DR	0.821 ± 0.009	0.754 ± 0.008	0.782 ± 0.003
DCMT	0.819 ± 0.007	0.762 ± 0.008	<u>0.783 ± 0.003</u>
ResFlow	0.826 ± 0.002	0.776 ± 0.006	0.789 ± 0.003

- ResFlow generalizes well to non-sequentially dependent tasks.
- Building the task topology according to their sample sparsities is a good choice.




Figure 5: Visualization of different task topologies of KuaiRand-Pure-S1 Multi-Task.

Table 7: Performance on KuaiRand-Pure-S1 in terms of AUC. The bests are in bold font. The second bests are underlined.

Target	is_follow	is_forward	is_comment
ResFlow-topo1	0.826 ± 0.002	0.776 ± 0.006	0.789 ± 0.003
ResFlow-topo2	<u>0.825 ± 0.003</u>	0.756 ± 0.010	0.771 ± 0.002
ResFlow-topo3	0.811 ± 0.007	<u>0.774 ± 0.007</u>	0.778 ± 0.003
ResFlow-topo4	0.820 ± 0.002	0.748 ± 0.009	0.775 ± 0.002
NSE	0.821 ± 0.005	0.750 ± 0.011	<u>0.779 ± 0.003</u>

Extension

Regression (e.g., rating) as Progressive Multi-Task

- Task 0: the likelihood of v being larger than v_0
- Task 1: the likelihood of v being larger than v_1
- ...
- Task K: the likelihood of v being larger than v_K

$$v_0 < v_2 < \dots < v_K$$

Table 8: Regression performances on KuaiRand-Pure-S1 and MovieLens-1M in terms of MSE. Progressive indicates converting the regression into a progressive multi-task problem.

Dataset	KuaiRand-Pure-S1	MovieLens-1M
Traditional	1719.92 ± 3.82	0.906 ± 0.002
Progressive + NSE	1720.12 ± 4.32	0.906 ± 0.002
Progressive + ResFlow	1658.44 ± 5.21	0.894 ± 0.002

- ResFlow can also be used in regression tasks



04

Online Deployment



Score Fusion

How to fuse the predictions from multiple tasks into a simple ranking indicator:

- traditional, multiplicative: $CTR^\alpha * CTCVR^\beta$
- proposed, additive: $\alpha * CTV + \beta * CTCVR$

Method & Score Formula	WR@100	List AUC	OPU	CTR	CTCVR	BCR@20
ESMM, $CTR^{0.9} \times CVR^{1.1}$	+0.77%	+0.23%	+0.56%	-0.02%	+0.61%	+0.02%
ESMM, $CTR*2+CTCVR*19$	+2.7%	+0.09%	+0.75%	+0.12%	+0.67%	-0.01%
ResFlow, CTCVR	+1.41%	+1.82%	+0.45%	-0.15%	+0.40%	-0.02%
ResFlow, $CTR^{-0.2} \times CTCVR$	+3.37%	+1.03%	+1.33%	+0.06%	+1.19%	-0.02%
ResFlow, $CTR+CTCVR*20$	+4.19%	+0.88%	+2.14%	+0.66%	+2.11%	+0.02%
ResFlow, $CTR+CTCVR*20+RL$	+4.11%	+0.82%	+2.04%	+0.61%	+1.97%	-2.13%
ResFlow, $CTR+CTCVR*20+RS$	+0.03%	-0.13%	-0.53%	-0.19%	-0.44%	-2.99%

- Score fusion leads to better online performance than simply using CTCVR.
- Additive fusion leads to better online performance than multiplicative fusion.

Online-Offline Metric Alignment

Online metric OPU (order-per-user) is totally different from what we predict, while online A/B test is costly

- need a surrogate for online metric to more efficiently tune the model and fusion parameters
- it is a long-standing challenge that still remains unresolved

Propose an offline surrogate metric:

$$WR@K = \frac{\sum_{k=0}^K W_k}{\sum_{n=0}^N W_n},$$

- W_k indicates the number of orders of item k

Table 10: Pearson correlation coefficient (PCC) between offline metric uplift and online metric uplift.

Metrics	2 Targets Uplift		3 Targets Uplift	
	PCC	p-value	PCC	p-value
Recall@100	0.0814	0.4425	0.1974	0.0606
NDCG	0.3719	0.0002	0.3825	0.0002
List AUC	0.4353	1.6×10^{-5}	0.1564	0.1386
WR@100	0.7879	1.9×10^{-20}	0.8666	2.5×10^{-42}

- Significantly better than existing surrogates

Online Performance

Compared with the previously deployed:

- OPU: ↑ 1.29%
- Online CTR: ↑ 0.25%
- Online CTCVR: ↑ 1.37%



THANKS FOR YOUR ATTENTION!

Based on joint work with Cong Fu et al. Deployed in Shopee Search.


Zhiming Zhou

|

SUFE

|

2024/12/07



Q & A

