

# STAT 3690 Lecture 35


zhiyanggeezhou.github.io

Zhiyang Zhou (zhiyang.zhou@umanitoba.ca)

Apr 25, 2022

## Hierarchical clustering

- A simple example
  - Step 1:  $\{1\}, \{2\}, \{3\}, \{4\}, \{5\}, \{6\}, \{7\}$ ;
  - Step 2:  $\{1\}, \{2, 3\}, \{4\}, \{5\}, \{6\}, \{7\}$ ;
  - Step 3:  $\{1, 7\}, \{2, 3\}, \{4\}, \{5\}, \{6\}$ ;
  - Step 4:  $\{1, 7\}, \{2, 3\}, \{4, 5\}, \{6\}$ ;
  - Step 5:  $\{1, 7\}, \{2, 3, 6\}, \{4, 5\}$ ;
  - Step 6:  $\{1, 7\}, \{2, 3, 4, 5, 6\}$ ;
  - Step 7:  $\{1, 2, 3, 4, 5, 6, 7\}$ .



- Dendrogram: a tree displaying a hierarchical sequence of clustering assignments
  - Node representing a group

- \* Leaf node representing a singleton (i.e., a group containing a single data point)
- \* Root node representing the group containing all the data points
- \* Internal node: has two children nodes, representing the the groups that were merged to form it
- Height: draw each internal node at a height proportional to the dissimilarity between its two children nodes (if fix the leaf nodes at height zero)
- Distances
  - Dissimilarity  $d_{ij}$ : (Euclidean) distance between  $\mathbf{x}_i$  and  $\mathbf{x}_j$
  - Linkage: distance between groups  $G$  and  $H$ 
    - \* Options
      - Single linkage
 
$$d_{\text{single}}(G, H) = \min_{i \in G, j \in H} d_{ij}$$
      - Complete linkage
 
$$d_{\text{complete}}(G, H) = \max_{i \in G, j \in H} d_{ij}$$
      - Average linkage
 
$$d_{\text{average}}(G, H) = \frac{1}{n_G n_H} \sum_{i \in G, j \in H} d_{ij}$$
      - Centroid linkage
 
$$d_{\text{centroid}}(G, H) = \|\bar{\mathbf{x}}_G - \bar{\mathbf{x}}_H\|_2$$
      - Minimax linkage
 
$$d_{\text{minimax}}(G, H) = \min_{i \in G \cup H} \max_{j \in G \cup H} d_{ij}$$
    - \* Situation-dependent

- 
- Example (hierarchical clustering for iris)

```
options(digits = 4)
d = dist(iris[,1:4])

tree.sing = hclust(d,method="single")
tree.comp = hclust(d,method="complete")
tree.avg = hclust(d,method="average")
tree.cent = hclust(d,method="centroid")

par(mfrow=c(2,2))
plot(tree.sing,hang=-1e-10, main='Single',xlab = '', sub = '')
plot(tree.comp,hang=-1e-10, main='Complete',xlab = '', sub = '')
plot(tree.avg,hang=-1e-10, main='Average',xlab = '', sub = '')
plot(tree.cent,hang=-1e-10, main='Centroid',xlab = '', sub = '')

# determine K for clustering with single linkage
x = iris[,1:4]
Ks = 2:20
Ws = numeric(length(Ks))
Bs = numeric(length(Ks))
CHs = numeric(length(Ks))

for(l in 1:length(Ks)){
  labs = cutree(tree.sing, k = Ks[l])
  nks = numeric(Ks[l])
  centers = matrix(0, nrow = Ks[l], ncol = ncol(x))
```

```

for (k in 1:Ks[l]){
  nks[k] = nrow(x[labs == k,])
  centers[k,] = colMeans(x[labs == k,])
  Ws[l] = Ws[l]+sum(sweep(x[labs == k,], 2, centers[k,])^2)
}
Bs[l] = sum(nks * rowSums(sweep(centers, 2, colMeans(x))^2))
CHs[l] = (Bs[l]/(Ks[l]-1))/(Ws[l]/(nrow(x)-Ks[l]))
}
plot(Ks, CHs,
     type="b", pch = 19,
     xlab="Number of clusters K",
     ylab="CH index")

```

## Modern alternatives

- Density-based spatial clustering of applications with noise (DBSCAN, M. Ester, H. Kriegel, J. Sander, X. Xu (1996), *Proceedings of the Second International Conference on Knowledge Discovery and Data Mining (KDD)*.)
- $t$ -distributed stochastic neighbor embedding ( $t$ -SNE, S. Roweis & G. Hinton (2002). *Conference on Neural Information Processing Systems (NIPS)*.)
- Uniform manifold approximation and projection for dimension reduction (UMAP, L. McInnes & J. Healy (2018), arXiv:1802.03426)