

STAT 3690 Lecture 32

zhiyanggeezhou.github.io

Zhiyang Zhou (zhiyang.zhou@umanitoba.ca)

Apr 15, 2022

Misclassification/error rate

- Population: $\Pr(Y \neq h(\mathbf{X}))$
 - $h(\cdot)$: the classifier to be evaluated
 - Apparent estimation:
 - Implementation
 1. Apply the fitted classifier to each observation in the training data
 2. Estimate the error rate by the misclassification proportion
 - Training and testing with identical data points
 - Severe underestimation likely
 - Parametric estimation
 - Implementation
 1. Express $\Pr(Y \neq h(\mathbf{X}))$ in terms of unknown parameters
 2. Plug in estimates of unknown parameters
 - Underestimation likely
 - Estimation via M -fold cross validation (CV)
 - Implementation
 1. The dataset is randomly partitioned into M chunks.
 2. Train one classifier upon each combination of $M - 1$ chunks.
 3. Apply each classifier to the corresponding remaining chunk and compute the empirical error rate.
 4. Estimate the population error rate by averaging these M empirical error rates.
 - Leave-one-out CV $\Leftrightarrow n$ -fold CV
 - Estimation via $M \times L$ -fold CV
 - Implementation
 1. Repeat the four steps of M -fold CV L times.
 2. Average all the ML resulting empirical error rates.
 - $M \times 1$ -fold CV $\Leftrightarrow M$ -fold CV
-